


TPC Benchmark™ C

Full Disclosure Report for



**PRIMERGY R450**

**Using Microsoft SQL Server 2000  
Enterprise Edition SP3**

**and Microsoft .NET Server 2003  
Enterprise Edition**

January 21, 2003

**First Edition**

First Edition January 21, 2003

FUJITSU LIMITED believes that the information in this document is accurate as of the publication date. The information in this document is subject to change without notice. We assume no responsibility for any errors that may appear in this document. The pricing information in this document is believed to accurately reflect the current prices as of the publication date. However, we provide no warranty of the pricing information in this document.

Benchmark results are highly dependent upon workload, specific application requirements, system design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC Benchmark™ C should not be used as a substitute for a specific customer application benchmark when critical capacity planning and/or product evaluation decisions are contemplated.

All performance data contained in this report were obtained in a rigorously controlled environment. Results obtained in other operating environments may vary significantly. We do not warrant or represent that a user can or will achieve similar performance expressed in transactions per minute (tpmC) or normalized price/performance (Yen/tpmC). No warranty of system performance or price/performance is expressed or implied in this report.

**Copyright © 1995-2003 FUJITSU LIMITED. All rights reserved.**

Permission is hereby granted to reproduce this document in whole or in part provided the copyright notice printed above is set forth in full text on the title page of each item reproduced.

PRIMERGY R450 and PRIMERGY C200 are trademarks of FUJITSU LIMITED.

Microsoft, Windows 2000, .NET Server 2003, SQL Server and Benchcraft are registered trademarks of Microsoft Corporation.

Pentium®III, Pentium®III XEON and XEON™ MP are registered trademarks of Intel.

TPC Benchmark™ is a trademark of the Transaction Processing Performance Council (TPC).

Other product names mentioned in this document may be trademarks and/or registered trademarks of their respective companies.

# Preface

The Transaction Processing Performance Council (TPC), of which FUJITSU LIMITED is a member, is an organization of computer companies, dedicated to the development of objective, industry-wide performance metrics in the area of transaction processing. FUJITSU LIMITED is involved in this effort, participating on the council and utilizing TPC benchmarks in performance evaluation.

The TPC Benchmark™ C Standard Specification was developed by the Transaction Processing Performance Council. This benchmark exercises the system components necessary to perform tasks associated with that class of on-line transaction processing (OLTP) environments emphasizing a mixture of read-only and update intensive transactions. This is a complex OLTP application environment exercising a breadth of system components associated by such environments characterized by:

- The simultaneous execution of multiple transaction types that span a breadth of complexity
- On-line and deferred transaction execution modes
- Multiple on-line terminal sessions
- Moderate system and application execution time
- Significant disk input/output
- Transaction integrity (ACID properties)
- Non-uniform distribution of data access through primary and secondary keys
- Databases consisting of many tables with a wide variety of sizes, attributes, and relationships
- Contention on data access and update

This benchmark defines four on-line transactions and one deferred transaction, intended to emulate functions that are common to many OLTP applications. However, this benchmark does not reflect the entire range of OLTP requirements. The extent to which a customer can achieve the results reported by a vendor is highly dependent on how closely TPC-C approximates the customer application. The relative performance of systems derived from this benchmark does not necessarily hold for other workloads or environments. Extrapolations to any other environment are not recommended.

Benchmark results are highly dependent upon workload, specific application requirements, system design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC-C should not be used as a substitute for a specific customer application benchmarking when critical capacity planning and/or product evaluation decisions are contemplated.

The performance metric reported by TPC-C is a "business throughput" measuring the number of orders processed per minute. Multiple transactions are used to simulate the business activity of processing an order, and each transaction is subjected to a response time constraint. The performance metric for this benchmark is expressed in transactions-per-minute-C (tpmC). To be compliant with the TPC-C standard, all references to tpmC results must include the tpmC rate, the associated price-per-tpmC, and the availability date of the priced configuration.

# Summary

This report documents the TPC Benchmark™ C results achieved by the FUJITSU LIMITED using Microsoft SQL Server 2000 Enterprise Edition SP3 .

The TPC Benchmark™ C tests were run on a PRIMERGY R450 system using the Windows .NET Server 2003 Enterprise Edition operating system.

The results, summarized below, show the number of TPC Benchmark™ C transactions per minute (tpmC) and the price per tpmC (Yen/tpmC).

<b>Hardware</b>	<b>Software</b>	<b>Total System Cost</b>	<b>tpmC</b>	<b>Yen/tpmC</b>	<b>Availability Date</b>
FUJITSU LIMITED PRIMERGY R450	Microsoft SQL Server 2000 Enterprise Edition SP3 , Windows .NET Server 2003 Enterprise Edition	Yen 78,549,210	68,264.47	Yen 1,150.66	July 20, 2003



**PRIMERGY R450**  
**C/S with 3 PRIMERGY C200**

TPC-C REV 5.0  
EXECUTIVE SUMMARY

Report Date: January 21, 2003


Total System Cost	TPC-C Throughput	Price/Performance	Availability Date	
<b>Yen 78,549,210</b>	<b>68,264.47 tpmC</b>	<b>Yen 1,150.66/tpmC</b>	<b>July 20, 2003</b>	
Processors	Database Manager	Operating System	Other Software	Number of Users
<b>Server 4 Intel Xeon™ MP 2.00 GHz with 2M iL3 Cache Client 3 x 2 Intel Pentium® III 1400 MHz with 512 KB SLC</b>	<b>Microsoft SQL Server 2000 Enterprise Edition SP3</b>	<b>Microsoft Windows .NET Server 2003 Enterprise Edition</b>	<b>Windows 2000 Server, IIS 5.0 and COM+</b>	<b>55000</b>

**Terminals:  
55000 User**

**Client:  
2 x PRIMERGY C200  
18300 users per client  
1 x PRIMERGY C200  
18400 users per client**

**Server:  
PRIMERGY R450  
7 SCSI Controller**

**Storage:  
25 x PRIMERGY S30  
288 disk 18GB  
10 disks 36 GB**



100 Mbs

2 Gb/s FC Switch

System Components	Qty/Srv.	1 PRIMERGY R450	Qty/Client	3 PRIMERGY C200
Processors	4	Intel Xeon™ MP 2.00 GHz with 2M iL3 Cache	2	Intel Pentium® III 1400 MHz with 512 KB SLC
Memory	16	GB	768	MB
Disk Controller	7	Mylex eXtremeRAID 2000	1	SCSI Controller
Disk Drives	289	18 GB	1	18 GB
	10	36 GB		
Total GB of Storage	1	4,865 GB		
Tape Drive	1	20 GB DAT		



# PRIMERGY R450

TPC-C REV 5.0  
EXECUTIVE SUMMARY

C/S with 3 PRIMERGY C200

Report Date: January 21, 2003

Description	Part Number	Third Party Brand Pricing	Unit Price	Qty.	Extended Price	3yr Maint. Price
PRIMERGY R450 Xeon-MP 2.0GHz/2MB	PGR4AE1R2	1	1,421,000 Yen	1	1,421,000 Yen	
Processor Xeon MP 2.0 GHz/2MB	PGBFG21E	1	952,000 Yen	3	2,856,000 Yen	
Memory 512MB => 4GB Conversion Kit	PGBRU4M2	1	1,120,000 Yen	3	3,360,000 Yen	
Memory 4GB	PGBRM4M2	1	1,190,000 Yen	3	3,570,000 Yen	
Tape DAT DDS4 20GB	GP5SDT401	1	140,000 Yen	1	140,000 Yen	
18GB, 15k, U160, Hot plug, 1"	PG-HDH85B2	1	84,000 Yen	1	84,000 Yen	
Mylex eXtremeRAID 2000 4x U160 SCSI, BBU	PG-144B	1	294,000 Yen	7	2,058,000 Yen	
Keyboard	GP5-R1KB1	1	14,000 Yen	1	14,000 Yen	
Monitor 15"	FMV-DP849W	1	16,100 Yen	1	16,100 Yen	
PRIMERGY S30 GE RH 2-Channel U160 SCSI	PG-R1DC6	1	238,000 Yen	1	238,000 Yen	
SCSI Cable UHD68 (S)	PG-CBLS004	1	21,000 Yen	2	42,000 Yen	
3 Year Maintenance Server, 7x24, 4hr Resp.						2,831,570 Yen
<b>Server Hardware Subtotal</b>					<b>13,799,100 Yen</b>	
DataCenter Rack	PG-R3RC1	1	238,000 Yen	3	714,000 Yen	
APC-USV 3000VA Rack	GP5-R1UP3	1	271,600 Yen	2	543,200 Yen	
18GB, 15k, U160, Hot plug, 1"	PG-HDH85B2	1	84,000 Yen	288	24,192,000 Yen	
36GB, 15k, U160, Hot plug, 1"	PG-HDH65B	1	175,000 Yen	10	1,750,000 Yen	
PRIMERGY S30 GE RH 1-Ch	PG-R1DC6BZ	1	238,000 Yen	24	5,712,000 Yen	
SCSI Cable UHD68 (S)	PG-CBLS005	1	28,000 Yen	24	672,000 Yen	
3 Year Maintenance Storage, 7x24, 4hr Resp.						6,891,270 Yen
<b>Storage Subtotal</b>					<b>33,583,200 Yen</b>	
<b>Maint. Server + Storage</b>						<b>9,722,840 Yen</b>
PRIMERGY C200 GE FS PIII 1.26GHz/512KB	PGC2CP1A2	1	210,000 Yen	3	630,000 Yen	
Processor Pentium III 1.26GHz => 1.4GHz	PGBFU12V	1	35,000 Yen	3	105,000 Yen	
Pentium III Processor 1.4GHz 512kB	PGBFG12V	1	140,000 Yen	3	420,000 Yen	
Memory 512MB SDRAM PC133 ECC	PGBRM51HA	1	70,000 Yen	3	210,000 Yen	
Hard Disk 18GB, 10k, U160, hot plug, 1"	PG-HDH81B2	1	56,000 Yen	3	168,000 Yen	
Monitor 15"	FMV-DP849W	1	16,100 Yen	3	48,300 Yen	
3 Year Maintenance, 7x24, 4hr Resp.						324,480 Yen
<b>Client Hardware Subtotal</b>					<b>1,581,300 Yen</b>	<b>324,480 Yen</b>
Windows .NET Enterprise Server 2003 (open program no level)	N/A	1	567,200 Yen	1	567,200 Yen	
MS SQL-Server 2000 Ent.Edit. Per Proc Lic. (open program level C)	B293C80Y0	1	2,791,700 Yen	4	11,166,800 Yen	
<b>Server Software Subtotal</b>					<b>11,734,000 Yen</b>	
Windows Svr 2000 (open program no level)	B511C02A2	1	142,000 Yen	3	426,000 Yen	
VC++ Pro 6.0 Win32	B298C2033	1	84,600 Yen	1	84,600 Yen	
<b>Client Software Subtotal</b>					<b>510,600 Yen</b>	
Software Support (all above)						3,140,730 Yen
FC Switch 8 Port, 2Gbit	SN20M215	1	1,134,250 Yen	1	1,134,250 Yen	
FC GBIC SFP Multi Mode 2 GB	SN20SWSFP	1	42,250 Yen	4	169,000 Yen	
FC Cabel MMF 5m, Connector DLC-DLC	CBL-MLLB05	1	22,750 Yen	4	91,000 Yen	
Qlogic 2350	PG-FC104Z	1	490,000 Yen	4	1,960,000 Yen	
3 Year Maintenance FC, 7x24, 4hr Resp.						798,710 Yen
<b>User Connectivity Subtotal</b>					<b>3,354,250 Yen</b>	
<b>Total</b>					<b>64,562,450 Yen</b>	<b>13,986,760 Yen</b>

1=FUJITSU

Prices used in TPC benchmarks reflect the actual prices a customer would pay for a one-time purchase of the stated components. Individually negotiated discounts are not permitted. Special prices based on assumptions about past or future purchases are not permitted. All discounts reflect standard pricing policies for the listed components. For complete details, see the pricing section of the TPC benchmark pricing specifications. If you find that the stated prices are not available according to these terms, please inform the TPC at [pricing@tpc.org](mailto:pricing@tpc.org). Thank you.

3 -Year Cost of Ownership: Yen 78,549,210  
tpmC Rating: 68,264.47  
Yen / tpmC: 1,150.66

Note: The benchmark results and test methodology were audited by Bradley Askins of InfoSizing

# Numerical Quantities Summary

MQTh, computed Maximum Qualified Throughput		68,264.47 tpmC	
<b>Response Times (in seconds)</b>	<b>90th percentile</b>	<b>Average</b>	<b>Maximum</b>
- New-Order	0.95	0.58	5.61
- Payment	0.88	0.52	5.47
- Order-Status	0.89	0.53	6.00
- Delivery (interactive portion)	0.12	0.11	0.59
- Delivery (deferred portion)	0.55	0.31	1.77
- Stock-Level	1.78	1.29	5.50
- Menu	0.12	0.11	1.20
<b>Transaction Mix, in percent of total transactions</b>			
- New-Order			44.91 %
- Payment			43.03 %
- Order-Status			4.02 %
- Delivery			4.02 %
- Stock-Level			4.02 %
<b>Emulation Delay (in seconds)</b>		<b>Response Time</b>	<b>Menu</b>
- New-Order		0.1	0.1
- Payment		0.1	0.1
- Order-Status		0.1	0.1
- Delivery (interactive)		0.1	0.1
- Stock-Level		0.1	0.1
<b>Keying/Think Times (in seconds)</b>	<b>Minimum</b>	<b>Average</b>	<b>Maximum</b>
- New-Order	18.00/0.000	18.02/12.05	18.04/120.51
- Payment	3.00/0.000	3.02/12.04	3.04/120.51
- Order-Status	2.00/0.000	2.02/10.02	2.04/100.50
- Delivery (interactive)	2.00/0.000	2.02/ 5.05	2.03/ 50.50
- Stock-Level	2.00/0.000	2.02/ 5.06	2.04/ 50.50
<b>Test Duration and Checkpointing</b>			
- Ramp-up time		46 minutes	
- Measurement interval		120 minutes	
- Number of checkpoints		4	
- Checkpoint interval		30 minutes	
- Transactions during measurement interval (all types)		18,971,511	



# Contents

<b>PREFACE</b> .....	<b>3</b>
<b>SUMMARY</b> .....	<b>4</b>
<b>NUMERICAL QUANTITIES SUMMARY</b> .....	<b>7</b>
<b>CONTENTS</b> .....	<b>9</b>
<b>INTRODUCTION</b> .....	<b>12</b>
<i>System Overview</i> .....	12
<i>Full Disclosure</i> .....	12
<i>Report Format</i> .....	12
<i>Additional Copies</i> .....	13
<b>1. GENERAL ITEMS</b> .....	<b>15</b>
1.1 <i>Application Code</i> .....	15
1.2 <i>Benchmark Sponsor</i> .....	15
1.3 <i>Parameter Settings</i> .....	15
1.4 <i>Configuration Diagrams</i> .....	15
<b>2. CLAUSE 1 RELATED ITEMS - LOGICAL DATABASE DESIGN</b> .....	<b>18</b>
2.1 <i>Table Definitions</i> .....	18
2.2 <i>Physical Organization of Database</i> .....	18
2.3 <i>Insert and Delete Operations</i> .....	20
2.4 <i>Database Partitioning</i> .....	20
2.5 <i>Replication of Tables</i> .....	20
2.6 <i>Additional and/or Duplicated Attributes</i> .....	20
<b>3. CLAUSE 2 RELATED ITEMS - TRANSACTION AND TERMINAL PROFILES</b> .....	<b>21</b>
3.1 <i>Random Number Generator</i> .....	21
3.2 <i>Input/Output Screen Layout</i> .....	21
3.3 <i>Configured Terminal Features</i> .....	21
3.4 <i>Presentation Managers or Intelligent Terminals</i> .....	21
3.5 <i>Transaction Statistics</i> .....	21
3.6 <i>Queueing Mechanism</i> .....	22
<b>4. CLAUSE 3 RELATED ITEMS - TRANSACTION AND SYSTEM PROPERTIES</b> .....	<b>23</b>
4.1 <i>Atomicity</i> .....	23
4.2 <i>Consistency</i> .....	23
4.3 <i>Isolation</i> .....	24
4.4 <i>Durability</i> .....	24
<b>5. CLAUSE 4 RELATED ITEMS - SCALING AND DATABASE POPULATION</b> .....	<b>26</b>
5.1 <i>Initial Cardinality of Tables</i> .....	26
5.2 <i>Distribution of Tables and Log</i> .....	27
5.3 <i>Database Model, Interface, and Access Language</i> .....	27
5.4 <i>Database Partitions/Replications Mapping</i> .....	28
5.5 <i>60 day space Calculation</i> .....	28
<b>6. CLAUSE 5 RELATED ITEMS - PERFORMANCE METRICS AND RESPONSE TIME</b> .....	<b>29</b>

6.1	Measured tpmC.....	29
6.2	Response Times.....	29
6.3	Keying and Think Times.....	29
6.4	Graphs.....	30
6.5	Steady State Determination.....	34
6.6	Work Performed.....	34
6.7	Duration of Checkpoints.....	35
6.8	Duration of Measurement.....	35
6.9	Regulation of Transaction Mix.....	35
6.10	Transaction Mix.....	36
6.11	Transaction Statistics.....	36
6.12	Checkpoint Statistics.....	36
<b>7.</b>	<b>CLAUSE 6 RELATED ITEMS - SUT, DRIVER, AND COMMUNICATION DEFINITION .....</b>	<b>37</b>
7.1	RTE Inputs .....	37
7.2	Lost Connections.....	37
7.3	Functionality and Performance of Emulated Components.....	37
7.4	Functional Diagrams of the Benchmarked and Proposed Configuration.....	37
7.5	Network Configurations of the Tested and Proposed Services .....	37
7.6	Network Bandwidth.....	38
7.7	Operator Intervention .....	38
<b>8.</b>	<b>CLAUSE 7 RELATED ITEMS - PRICING.....</b>	<b>39</b>
8.1	System Pricing.....	39
8.2	Availability Dates.....	39
8.3	Throughput and Price/Performance .....	39
8.4	Country Specific Pricing.....	39
8.5	Usage Pricing .....	40
<b>9.</b>	<b>CLAUSE 8 RELATED ITEMS - AUDIT .....</b>	<b>41</b>
	<b>APPENDIX A - APPLICATION SOURCE CODE .....</b>	<b>42</b>
	<b>APPENDIX B - DATABASE DETAILS .....</b>	<b>135</b>
	BACKUP.SQL.....	136
	BACKUPDEV.SQL.....	136
	CREATEDB.SQL.....	136
	DBOPT1.SQL.....	137
	DBOPT2.SQL.....	137
	REMOVEDB.SQL.....	138
	RESTORE.SQL.....	138
	VERIFYTPCCLOAD.SQL.....	139
	IDXCUSCL.SQL .....	140
	IDXCUSNC.SQL.....	140
	IDXDISCL.SQL.....	140
	IDXITMCL.SQL.....	141
	IDXNODCL.SQL .....	141
	IDXODLCL.SQL.....	141
	IDXORDCL.SQL.....	141
	IDXORDNC.SQL.....	142
	IDXSTKCL.SQL.....	142
	IDXWARCL.SQL.....	142
	TABLES.SQL.....	143
	DELIVERY.SQL.....	144
	NEWORD.SQL.....	145
	ORDSTAT.SQL .....	148

<i>PAYMENT.SQL</i> .....	149
<i>STOCKLEV.SQL</i> .....	151
<i>VERSION.SQL</i> .....	151
<i>GETARGS.C</i> .....	152
<i>RANDOM.C</i> .....	154
<i>STRINGS.C</i> .....	156
<i>TIME.C</i> .....	159
<i>TPCC.H</i> .....	159
<i>TPCCLDR.C</i> .....	161
<b>APPENDIX C - TUNABLE PARAMETERS AND OPTIONS</b> .....	<b>189</b>
<b>APPENDIX D – SPACE CALCULATION</b> .....	<b>259</b>
<b>APPENDIX E - PRICE QUOTATIONS</b> .....	<b>260</b>
<b>APPENDIX F - ATTESTATION LETTER</b> .....	<b>261</b>

# Introduction

This is the Full Disclosure Report for the TPC Benchmark™ C running on the FUJITSU LIMITED Computers system PRIMERGY R450. It meets the requirements of the TPC Benchmark™ C Standard Revision 5.0.

<b>System Overview</b>	<i>This report documents the compliance of the FUJITSU LIMITED TPC Benchmark™ C tests using Microsoft SQL Server 2000 Enterprise Edition SP3 Relational Database Management System.</i>
------------------------	---

The TPC Benchmark™ C tests were carried out on a PRIMERGY R450. The PRIMERGY R450 is a powerful Server with a motherboard based on the ServerWorks chipset that holds up to 4 Intel Xeon™ MP 2.00 GHz processors with 2M iL3 cache. The Intel® Xeon™ Processor family with the Intel® NetBurst™ micro-architecture uses Hyper-Threading Technology to provide additional performance and application scalability to multi-processor servers. Hyper-Threading Technology enables multi-threaded software to execute tasks in parallel within each processor. The system was equipped with 16 GB of ECC DDR RAM memory. 7 PCI slots were used for SCSI RAID controllers and one Qlogic FC controller.

The client machines were 3 PRIMERGY C200 with 2 Intel Pentium® III 1400 MHz. They all included 768 MB ECC SDRAM memory, onboard ethernet adapter and one Qlogic FC Controller.

The server operating system was Windows .NET Server 2003 Enterprise Edition . The client operating system was Windows 2000 Server SP2.

<b>Full Disclosure</b>	<i>From Clause 8.1 of the TPC Benchmark™ C Standard Specification:</i>  The intent of this disclosure is for a customer to be able to replicate the results of this benchmark given the appropriate documentation and products.
------------------------	---

FUJITSU LIMITED believes that this full disclosure report meets the stated intention. FUJITSU LIMITED has strived to maintain the integrity of the Specification by adhering not only to the letter of the Specification, but also to its spirit.

<b>Report Format</b>	<i>The format of this document follows Clause 8 of the TPC Benchmark™ C specification (TPC Benchmark™ C Standard Specification, Revision 5.0, Transaction Processing Performance Council) which describes the full disclosure report requirements for the test.</i>
----------------------	---

Each section of this report begins with the specification requirement printed in *italic type*. It is followed by plain type text that explains how the test complies with the requirement. Sections which require extensive listings reference appropriate appendices.

Report organization:

- General Items
- Clause 1 Related Items - Logical Database Design
- Clause 2 Related Items - Transaction and Terminal Profiles
- Clause 3 Related Items - Transaction and System Properties
- Clause 4 Related Items - Scaling and Database Population
- Clause 5 Related Items - Performance Metrics and Response Time
- Clause 6 Related Items - SUT, Driver, and Communication Definition
- Clause 7 Related Items - Pricing
- Clause 8 Related Items - Audit
- Appendix A - Application Source Code
- Appendix B - Database Details
- Appendix C - Tunable Parameters and Options
- Appendix D - Space Calculation
- Appendix E - Price Quotations
- Appendix F - Attestation Letter

<b>Additional Copies</b>	<i>Additional copies of this report are available upon request from FUJITSU LIMITED: Masayoshi TAKEI IA Server Division Personal Systems Business Group Fujitsu Limited 1-1, Kamikodanaka 4-Chome, Nakahara-ku, Kawasaki 211-8588, Japan</i>
--------------------------	--



# 1. General Items

<b>1.1 Application Code</b>	<i>The application program (as defined in Clause 2.1.7) must be disclosed. This includes, but is not limited to, the code implementing the five transactions and the terminal input and output functions. [Clause 8.1.1.4]</i>
---------------------------------	--

The source code of the application program is provided in Appendix A - Application Source Code.

<b>1.2 Benchmark Sponsor</b>	<i>A statement identifying the benchmark sponsor(s) and other participating companies must be provided. [Clause 8.1.1.5]</i>
----------------------------------	--

This benchmark was sponsored and executed by FUJITSU LIMITED.

The benchmark was developed and engineered by FUJITSU LIMITED and Microsoft Corporation. Testing took place at Fujitsu Siemens Computers PRIMERGY benchmark laboratories in Paderborn, Germany.

<b>1.3 Parameter Settings</b>	<i>Settings must be provided for all customer-tunable parameters and options which have been changed from the defaults found in actual products, including but not limited to:</i> <ul style="list-style-type: none"><li>• <i>Database tuning options.</i></li><li>• <i>Recovery/commit options.</i></li><li>• <i>Consistency/locking options.</i></li><li>• <i>Operating system and application configuration parameters.</i></li></ul> <i>[Clause 8.1.1.6]</i>
-----------------------------------	--

The significant parameters and system configuration files are provided in Appendix C - Tunable Parameters and Options.

<b>1.4 Configuration Diagrams</b>	<i>Diagrams of both measured and priced configurations must be provided, accompanied by a description of the differences. This includes, but is not limited to:</i> <ul style="list-style-type: none"><li>• <i>Number and type of processors.</i></li><li>• <i>Size of allocated memory, and any specific mapping/partitioning of memory unique to the test.</i></li><li>• <i>Number and type of disk units (and controllers, if applicable).</i></li><li>• <i>Number of channels or bus connections to disk units, including their protocol type.</i></li><li>• <i>Number of LAN (e.g., Ethernet) connections, including routers, workstations, terminals, etc., that were physically used in the test or are incorporated into the pricing structure (see Clause 8.1.8).</i></li><li>• <i>Type and the run-time execution location of software components (e.g., DBMS, client processes, transaction monitors, software drivers, etc.).</i></li></ul> <i>[Clause 8.1.1.7]</i>
---------------------------------------	---

**Table 1: SUT Configuration PRIMERGY R450**


4	Intel Xeon™ MP 2.00 GHz with 2M iL3 Cache
16	GB memory
7	Mylex eXtremRAID 2000 SCSI controllers
0	disks 9 GB measured
289	disks 18 GB measured
10	disks 36 GB measured
0	disks 9 GB priced
289	disks 18 GB priced
10	disks 36 GB priced
1	Qlogic 2350 2 GBit FC controller

**Table 2: Client Configuration PRIMERGY C200**


2	Intel Pentium® III 1400 MHz with 512 KB Second Level Cache
768	MB memory
1	SCSI controller
1	disk 18 GB
1	Onboard Intel LAN
1	Qlogic 2350 2 GBit FC controller

The benchmarked and priced system configurations are shown in Figure 1 and Figure 2 in accordance with Clause 8.1.1.7.

**Figure 1: Benchmark System Configuration PRIMERGY R450**



**Figure 2: Priced System Configuration PRIMERGY R450**



## 2. Clause 1 Related Items - Logical Database Design

<b>2.1 Table Definitions</b>	<i>Listings must be provided for all table definition statements and all other statements used to set-up the database. [Clause 8.1.2.1]</i>
----------------------------------	---

The programs that defined, created, and populated the Microsoft SQL Server 2000 Enterprise Edition SP3 database for this TPC benchmark™ C are listed in Appendix B - Database Details.

<b>2.2 Physical Organization of Database</b>	<i>The physical organization of tables and indices, within the database, must be disclosed. [Clause 8.1.2.2]</i>
--	--

**Table 3: Physical Organization of the Database**

Controller	Channel 0	Channel 1	Channel 2	Channel 3	RAID	Drive
eXtremeRAID 2000 #0	0-0 1-0 2-0 3-0 4-0	0-1 1-1 2-1 3-1 4-1			SPAN 0 to 1 RAID1	L:
eXtremeRAID 2000 #1	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11 0-12	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11 1-12	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11 2-12	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11 3-12	SPAN 0 to 3 RAID0	E: N: U:
eXtremeRAID 2000 #2	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11 0-12	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11 1-12	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11 2-12	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11 3-12	SPAN 0 to 3 RAID0	F: O: V:
eXtremeRAID 2000 #3	0-0 0-1 0-2 0-3	1-0 1-1 1-2 1-3	2-0 2-1 2-2 2-3	3-0 3-1 3-2 3-3	SPAN 0 to 3 RAID0	G: P: W:

	0-4 0-5 0-6 0-8 0-9 0-10 0-11 0-12	1-4 1-5 1-6 1-8 1-9 1-10 1-11 1-12	2-4 2-5 2-6 2-8 2-9 2-10 2-11 2-12	3-4 3-5 3-6 3-8 3-9 3-10 3-11 3-12		
eXtremeRAID 2000 #4	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11 0-12	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11 1-12	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11 2-12	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11 3-12	SPAN 0 to 3 RAID0	H: Q: X:
eXtremeRAID 2000 #5	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11 0-12	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11 1-12	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11 2-12	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11 3-12	SPAN 0 to 3 RAID0	I: R: Y:
eXtremeRAID 2000 #6	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11 0-12	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11 1-12	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11 2-12	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11 3-12	SPAN 0 to 3 RAID0	J: S: Z:

All controllers were configured with write cache disabled. Write cache was enabled on the log drives and disabled on the data drives. Disk types are Seagate ST318452 LC 18 GB and ST328452 LC 36 GB with 15000 rpm. Space was allocated to Microsoft SQL Server 2000 Enterprise Edition SP3 on SUT disks according to the data in section 5.2. The size of the datafile on each disk drive was calculated to provide even distribution on load across the disk drives. The Windows Disk Manager was used to create raw devices for data/log and NTFS partitions for dump devices. For further information see Appendix B (Disk Usage) and Figure 4 in 5.2 (Distribution of Tables and Log). No attempt was made to alter the default physical organization of the database tables and indices chosen by Microsoft SQL Server 2000 Enterprise Edition SP3 .

<b>2.3 Insert and Delete Operations</b>	<i>It must be ascertained that insert and/or delete operations to any of the tables can occur concurrently with the TPC-C transaction mix. Furthermore, any restriction in the SUT database implementation that precludes inserts beyond the limits defined in Clause 1.4.11 must be disclosed. This includes the maximum number of rows that can be inserted and the maximum key value for these new rows. [Clause 8.1.2.3]</i>
---	--

There were no restrictions on insert and delete operations to any tables.

<b>2.4 Database Partitioning</b>	<i>While there are a few restrictions placed upon horizontal or vertical partitioning of tables and rows in the TPC benchmark™ C (see Clause 1.6), any such partitioning must be disclosed. [Clause 8.1.2.4]</i>
--------------------------------------	--

There was no partitioning used in this implementation.

<b>2.5 Replication of Tables</b>	<i>Replication of tables, if used, must be disclosed (see Clause 1.4.6). [Clause 8.1.2.5]</i>
--------------------------------------	---

Replication of tables was not used in this implementation.

<b>2.6 Additional and/or Duplicated Attributes</b>	<i>Additional and/or duplicated attributes in any table must be disclosed along with a statement on the impact on performance (see Clause 1.4.7). [Clause 8.1.2.6]</i>
--	--

No additional and/or duplicated attributes were used.

### 3. Clause 2 Related Items - Transaction and Terminal Profiles

<b>3.1 Random Number Generator</b>	<i>The method of verification for the random number generation must be described. [Clause 8.1.3.1]</i>
--	--

The random number generation was done in Microsoft BenchCraft, which was audited independently.

<b>3.2 Input/Output Screen Layout</b>	<i>The actual layouts of the terminal input/output screens must be disclosed. [Clause 8.1.3.2]</i>
---	--

The screen layout corresponded exactly to those of the TPC-C Standard Specification (specified in Clause 2.4.3, 2.5.3, 2.6.3, 2.7.3, and 2.8.3).

<b>3.3 Configured Terminal Features</b>	<i>The method used to verify that the emulated terminals provide all the features described in Clause 2.2.2.4 must be explained. Although not specifically priced, the type and model of the terminals used for the demonstration in 8.1.3.3 must be disclosed and commercially available (including supporting software and maintenance). [Clause 8.1.3.3]</i>
---	---

All of the requirements in clause 2.2.2.4. are supported. This was verified by manually exercising each specification on a PRIMERGY 870.

<b>3.4 Presentation Managers or Intelligent Terminals</b>	<i>Any usage of presentation managers or intelligent terminals must be explained. [Clause 8.1.3.4]</i>
---	--

Application code running on the client machines implemented the TPC-C user interface. No presentation manager software or intelligent terminal features were used. The source code for the forms application is listed in Appendix A - Application Source Code.

<b>3.5 Transaction Statistics</b>	<i>The numerical quantities which are required are listed in the following table. [Clause 8.1.3.5 to 8.1.3.11]</i>
---------------------------------------	--

**Table 4: Transaction Statistics**

	<b>Statistics</b>	<b>Percentage</b>
New-Order	Home order-lines	99.00%
	Remote order-lines	1.00%
	Rolled back transactions	0.99%
	Average items per order	10.00
Payment	Home transactions	85.00%
	Remote transactions	15.00%
	Non-primary key access	60.01%
Order-Status	Non-primary key access	60.01
Delivery	Skipped transactions	0
Transaction Mix	New-Order	44.91 %
	Payment	43.03 %
	Order-Status	4.02 %
	Delivery	4.02 %
	Stock-Level	4.02 %

<b>3.6 Queueing Mechanism</b>	<i>The queuing mechanism used to defer the execution of the Delivery transaction must be disclosed. [Clause 8.1.12]</i>
-----------------------------------	---

Deferred deliveries are queued by making an entry in an array within the client application process (tpcc.dll). The queued delivery transactions are processed and logged asynchronously by background threads within the application.

The source code is listed in Appendix A - Application Source Code.

## 4. Clause 3 Related Items - Transaction and System Properties

<b>ACID Tests</b>	<i>The results of the ACID tests must disclosed along with a description of how the ACID requirements were met. This includes disclosing which case was followed for the execution of Isolation Test 7. [Clause 8.1.4.1]</i>
-------------------	--

All ACID tests were performed successfully. The following sections describe the requirements of each of the tests as described in Clause 3 and the approach used to satisfy them.

All ACID tests were performed on the PRIMERGY R450 system using the fully scaled database, except for the test of durable media failure. This durability test was performed on a database scaled to 550 warehouses. This test would also pass on a fully scaled database.

<b>4.1 Atomicity</b>	<i>The system under test must guarantee that database transactions are atomic; the system will either perform all individual operations on the data, or will assure that no partially-completed operations leave any effects on the data. [Clause 3.2.1]</i>
----------------------	--

<b>Commit Transaction</b>	Perform the Payment transaction for a randomly selected warehouse, district, and customer (by customer number as specified in Clause 2.5.1.2) and verify that the records in the CUSTOMER, DISTRICT, and WAREHOUSE tables have been changed appropriately. [Clause 3.2.2.1]
---------------------------	---

The following steps demonstrated atomicity for completed (COMMIT) transactions:

- A row was randomly selected from the warehouse, district and customer table.
- the current balance was noted.
- A payment transaction was executed with the above identifiers and a known amount.
- The transaction was committed.
- It was verified, that the rows contain the correct updated balances.

<b>Rollback Transaction</b>	Perform the Payment transaction for a randomly selected warehouse, district, and customer (by customer number as specified in Clause 2.5.1.2) and substitute a ROLLBACK of the transaction for the COMMIT of the transaction. Verify that the records in the CUSTOMER, DISTRICT, and WAREHOUSE tables have NOT been changed. [Clause 3.2.2.2]
-----------------------------	---

The following steps demonstrated atomicity for aborted (ROLLBACK) transactions:

- A row was randomly selected from the warehouse, district and customer table.
- the current balance was noted.
- A payment transaction was executed with the above identifiers and a known amount.
- The transaction was rolled back.
- It was verified, that the rows contain the original balances.

<b>4.2 Consistency</b>	<i>Consistency is the property of the application that requires any execution of a database transaction to take the database from one consistent state to another, assuming that the database is initially in a consistent state. [Clause 3.3.1]</i>
------------------------	--

Consistency conditions 1 - 4 were tested by issuing queries to the database. The results of the queries verified that the database was consistent for all these tests. The tests were performed before and after the performance run on the same database that was used for the benchmark.

<b>4.3 Isolation</b>	<i>Operations of concurrent transactions must yield results which are indistinguishable from the results which would be obtained by forcing each transaction to be serially executed to completion in some order.</i>
--------------------------	---

We ran all of the seven isolation tests as described in clause 3.4.2.1 to 3.4.2.7 and additionally the two phantom protection tests. The tests were executed using shell scripts to issue queries to the database. The results of the queries verified that the required isolation had been met.

<b>4.4 Durability</b>	<p><i>The tested system must guarantee durability: the ability to preserve the effects of committed transactions and insure database consistency after recovery from any one of the failures listed in Clause 3.5.3. [Clause 3.5]</i></p> <p><i>List of single failures</i></p> <ol style="list-style-type: none"> <li><i>1 Permanent irrecoverable failure of any single durable medium containing TPC-C database tables or recovery log data</i></li> <li><i>2 Instantaneous interruption (system crash / system hang) in processing which requires system reboot to recover</i></li> <li><i>3 Failure of all or part of memory (loss of contents).</i></li> </ol>
	<p><i>[Clause 3.5.3]</i></p> <p><i>The intent of these tests is to demonstrate that all transactions whose output messages have been received at the terminal or RTE have in fact been committed in spite of any single failure from the list in Clause 3.5.3 and that all consistency conditions are still met after the database is recovered.</i></p> <p><i>It is required that the system crash test(s) and the loss of memory test(s) described in Clause 3.5.3.2 and 3.5.3.3 be performed under full terminal load and a fully scaled database. The durable media failure test(s) described in Clause 3.5.3.1 may be performed on a subset of the SUT configuration and database. For the SUT subset, all multiple hardware components, such as processors and disk / controllers in the full SUT configuration, must be represented by the greater of 10% of the configuration or two of each of the multiple hardware components. The database must be scaled to at least 10% of the fully scaled database, with a minimum of two warehouses. ... Furthermore, the standard driving mechanism must be used in this test. The test sponsor must state that to the best of their knowledge, a fully scaled test would also pass all durability tests. [Clause 3.5.4]</i></p>

The failure of all or part of memory test and the system crash test were combined with the loss of log disk and performed under full load and by using a fully scaled database.

The full hardware configuration of the SUT (in accordance with Clause 3.5.4) and the same test procedure was used during all durability tests, except the test for loss of data.

- The current count of the total number of orders was determined by summing up the D\_NEXT\_O\_ID fields of all rows in the DISTRICT table.
- A test was started under full load and a checkpoint executed.
- After 6 min in steady state we pulled off one of the log disks. As we use hardware-mirrored diskpairs with the SCSI-controller, execution continued.
  - After additional 6 min we powered of the server to emulate the loss of memory. After server system reboot, SQL-Server starts with recovering the database tpcc. After completion, we computed the sum of D\_NEXT\_O\_ID from district. Client and RTE systems were interrupted and evaluation started on the RTE. The difference of all D\_NEXT\_O\_ID between RTE an server was in the permitted scope.

The durable media failure test for loss of data disk was performed with 48 of the 288 data disks and a database scaled to 550 warehouses under the load of 5500 users. We used one RTE and one client system. To the best of the test sponsor's knowledge, a fully loaded and fully scaled database would also pass this durability test.

- The database was backed up.
- The current count of the total number of orders was determined by summing up the D\_NEXT\_O\_ID fields of all rows in the DISTRICT table before the test.
- After 5 min in steady state we pulled of one of the data disks.
- SQL-Server recognized the loss of a device. We dumped the transaction log and removed the database with dropdevice. Then we shut down SQL-Server and the system.
- We replaced the disk and made it online.
- We restarted SQL-Server, no tpcc database and none of its devices were present. We recreated the database, loaded dump and load transaction log
- After completion, we computed the sum of D\_NEXT\_O\_ID from district.
- Client and RTE systems were interrupted and evaluation started on the RTE. The difference of all D\_NEXT\_O\_ID between RTE an server was in the permitted scope.

## 5. Clause 4 Related Items - Scaling and Database Population

<b>5.1 Initial Cardinality of Tables</b>	<i>The cardinality (e.g., the number of rows) of each table, as it existed at the start of the benchmark run (see Clause 4.2), must be disclosed. If the database was over-scaled and inactive rows of the WAREHOUSE table were deleted (see Clause 4.2.2), the cardinality of the WAREHOUSE table as initially configured and the number of rows deleted must be disclosed. [Clause 8.1.5.1]</i>
--	---

The database for the PRIMERGY R450 system was scaled for 5500 warehouses. The performance run used 5500 warehouses. In accordance with Clause 4.2, the following number of records were loaded in the specified tables:

**Table 5: Number of Rows**

Table	Number of Records
Warehouse	5500
District	55,000
Customer	165,000,000
History	165,000,001
Order	165,000,000
New-Order	49,500,000
Order-Line	1,649,998,197
Stock	550,000,000
Item	100,000
Deleted Warehouses	00

The following constant values were used during the database build and benchmark test for the NURand function:

**Table 6: C\_LAST value**

Constant C	Value
C_LAST (build)	123
C_LAST (run)	233

**5.2  
Distribution of Tables and Log**

*The distribution of tables and logs across all media must be explicitly depicted for the tested and priced systems. [Clause 8.1.5.2]*

**Table 7: Logical Organization of the Database**

Disk	Controller	Disktype	RAID Configuration	Drive Letter	Size MB	Filegroup or Filesystem
0	Onboard SCSI	18 GB	-	System C:	17000	NTFS
1	eXtremeRAID 2000 #0	10 x 36 GB	RAID 1	L:	90000	log
2	eXtremeRAID 2000 #1	48 x 18 GB	RAID 0	E: N: U:	52500 29000 300000	cs1 misc1 backup1
3	eXtremeRAID 2000 #2	48 x 18 GB	RAID 0	F: O: V:	52500 29000 300000	cs2 misc2 backup2
4	eXtremeRAID 2000 #3	48 x 18 GB	RAID 0	G: P: W:	52500 29000 300000	cs3 misc3 backup3
5	eXtremeRAID 2000 #4	48 x 18 GB	RAID 0	H: Q: X:	52500 29000 300000	cs4 misc4 backup4
6	eXtremeRAID 2000 #5	48 x 18 GB	RAID 0	I: R: Y:	52500 29000 300000	cs5 misc5 backup5
7	eXtremeRAID 2000 #6	48 x 18 GB	RAID 0	J: S: Z:	52500 29000 300000	cs6 misc6 backup6

**5.3  
Database Model, Interface, and Access Language**

*A statement must be provided that describes:*

1. *The data model implemented by the DBMS used (e.g., relational, network, hierarchical)*
2. *The database interface (e.g., embedded, call level) and access language (e.g., SQL, DL/I, COBOL read/write) used to implement the TPC-C transactions. If more than one interface/access language is used to implement TPC-C, each interface / access language must be described and a list of which interface/access language is used with which transaction type must be disclosed.*

*[Clause 8.1.5.3]*

Microsoft SQL Server 2000 Enterprise Edition SP3 is a Relational DataBase Management System. The interface used was Microsoft SQL Server 2000 Enterprise Edition SP3 stored procedures accessed with Remote Procedure Calls embedded in C code.

<b>5.4 Database Partitions/Replications Mapping</b>	<i>The mapping of database partitions/replications must be explicitly described. [Clause 8.1.5.4]</i>
---	---

There was no partitioning and/or replication used in this implementation.

<b>5.5 60 day space Calculation</b>	<i>Details of the 60-day space computations along with proof that the database is configured to sustain 8 hours of growth for the dynamic tables (Order, Order-Line, and History) must be disclosed (see Clause 4.2.3). [Clause 8.1.5.5]</i>
---	--

Calculations of space requirements in the priced configurations for the 60-day period are provided in Appendix D – Space Calculation.

## 6. Clause 5 Related Items - Performance Metrics and Response Time

<b>6.1</b> <b>Measured tpmC</b>	<i>Measured tpmC must be reported. [Clause 8.1.6.1]</i>
------------------------------------	---

During the 120 minutes measurement period on the PRIMERGY R450 the throughput measured was 68,264.47 tpmC.

<b>6.2</b> <b>Response Times</b>	<i>Ninetieth percentile, maximum and average response times must be reported for all transaction types as well as for the Menu response time. [Clause 8.1.6.2]</i>
-------------------------------------	--

**Table 8: Response Times**

Type	Average	Maximum	90 Percentile
New-Order	0.58	5.61	0.95
Payment	0.52	5.47	0.88
Order-Status	0.53	6.00	0.89
Interactive Delivery	0.11	0.59	0.12
Deferred Delivery	0.31	1.77	0.55
Stock-Level	1.29	5.50	1.78
Menu	0.11	1.20	0.12

<b>6.3</b> <b>Keying and Think Times</b>	<i>The minimum, the average, and the maximum keying and think times must be reported for each transaction type. [Clause 8.1.6.3]</i>
---	--

**Table 9: Keying Times**

Keying Times			
Type	Average	Maximum	Minimum
New-Order	18.02	18.04	18.00
Payment	3.02	3.04	3.00
Order-Status	2.02	2.04	2.00
Delivery	2.02	2.03	2.00
Stock-Level	2.02	2.04	2.00

**Table 10: Think Times**

Think Times			
Type	Average	Maximum	Minimum
New-Order	12.05	120.51	0.000
Payment	12.04	120.51	0.000
Order-Status	10.02	100.50	0.000
Delivery	5.05	50.50	0.000
Stock-Level	5.06	50.50	0.000

**6.4  
Graphs**


Response Time frequency distribution curves (see Clause 5.6.1) must be reported for each transaction type. [Clause 8.1.6.4]

The performance curve for response times versus throughput (see Clause 5.6.2) must be reported for the New-Order transaction. [Clause 8.1.6.5]


Think Time frequency distribution curves (see Clause 5.6.3) must be reported for each transaction type. [Clause 8.1.6.6]

A graph of throughput versus elapsed time (see Clause 5.6.5) must be reported for the New-Order transaction. [Clause 8.1.6.8]


**Figure 3: New-Order Response Time Distribution**



**FIGURE 4: PAYMENT RESPONSE TIME DISTRIBUTION**




**Figure 5: Order-Status Response Time Distribution**



**Figure 6: Delivery Response Time Distribution**



**Figure 7: Stock-Level Response Time Distribution**



**Figure 8: Response Time Versus Throughput**




Figure 9: New-Order Think Time Distribution





Figure 10: Throughput Versus elapsed Time



**6.5  
Steady State  
Determination**

*The method used to determine that the SUT had reached a steady state prior to commencing the measurement interval (see Clause 5.5) must be described. [Clause 8.1.6.9]*

In all test runs, steady state was achieved before the measurement period began. Steady state was determined to occur based on a visual inspection of tpmC versus time (see graph in section 6.4).

The graph in section 6.4 illustrates that the measurement period was within the steady state period for the run. One checkpoint occurred before and four during the measurement period.

**6.6  
Work Performed**

*A description of how the work normally performed during a sustained test (for example checkpointing, writing redo/undo log records, etc.), actually occurred during the measurement interval must be reported. [Clause 8.1.6.10]*

The RTE generated the required input data to choose a transaction from the menu. This data was timestamped and captured in RTE log files before being transmitted. There was one log file for each user. The input screen for the requested transaction was returned and it was also captured and timestamped in the RTE log files. The difference between these two timestamps was the menu response time.

The RTE generated the required input data for the chosen transaction. It waited to complete the minimum required key time before transmitting the input screen. The transmission was timestamped and captured in RTE log files. The return of the screen with the required response data was timestamped and captured in the RTE log files. The difference between these two timestamps was the response time for that transaction.

The RTE then waited the required think time interval before repeating the process starting at selecting a transaction from the menu.

The RTE transmissions were sent to Internet Information Server running on the client machines through Ethernet LANs. Internet Information Server handled all screen I/O as well as all requests to the database on the server. Internet Information Server communicated with the database server over COM+ which was used as transaction monitor.

All database operations like update, select, delete and insert are performed by one of the TPC-C back end programs. The TPC-C backend program commits the transaction after all the corresponding operations are done.

Modified database buffers are migrated to disk a least-recently-used basis independent of transaction commits. In addition, every block modification is protected by log records. Asynchronously the log buffers are flushed to a log file on disk either when the transaction is committed or when the log buffer's fill state reaches its limit. The log buffer's always flushed by a commit before it become full.

To perform checkpoints at specific intervals, we wrote a script to schedule multiple checkpoints at specific intervals. By setting the trace flag #3502, SQL Server logged the checkpoint beginning and ending time in the ERRORLOG file. The script included a wait time between each checkpoint equal to a fourth of the measurement interval which was 120 minutes. The checkpoint script was started manually after the RTE had all users logged in and sending transactions.

At each checkpoint, Microsoft SQL Server wrote to disk all memory pages that had been updated but not yet physically written to disk. Upon completion of the checkpoint, Microsoft SQL Server wrote a special record to the recovery log to indicate that all disk operations had been satisfied to this point.

<b>6.7 Duration of Checkpoints</b>	<i>The start time and duration in seconds of at least the four (4) longest checkpoints during the MeasurementInterval must be disclosed (see Clause 5.5.2.2 (2)). [Clause 8.1.6.11]</i>
--	---

There was one checkpoint before measurement and four checkpoints during measurement. Starttime and duration of these four checkpoints is listed in the following table:

**Table 11: Duration of Checkpoints**

Measurement		duration	
Start =	End =	minutes	seconds
9:26:20	11:26:20	120	7200
4 Checkpoints		duration	
Start =	End =	minutes	seconds
09:27:21	09:56:21	29.00	1740
09:57:20	10:26:18	28.97	1738
10:27:19	10:56:19	29.00	1740
10:57:18	11:26:18	29.00	1740

<b>6.8 Duration of Measurement</b>	<i>A statement of the duration of the measurement interval for the reported Maximum Qualified Throughput (tpmC) must be included. [Clause 8.1.6.12]</i>
--	---

The measurement interval of the PRIMERGY R450 system test was 120 minutes.

<b>6.9 Regulation of Transaction Mix</b>	<i>The method of regulation of the transaction mix (e.g., card decks or weighted random distribution) must be described. If weighted distribution is used and the RTE adjusts the weights associated with each transaction type, the maximum adjustments to the weight from the initial value must be disclosed. [Clause 8.1.6.13]</i>
--	--

The transaction mix was regulated by weighted distribution. The chosen weights meet the required minimum percentages of the mix which are described in Clause 5.2.3 of the Standard Specifications. No adjustments were made by the RTE.

**6.10  
Transaction Mix**

*The percentage of the total mix for each transaction type must be disclosed. [Clause 8.1.6.14]*

**Table 12: Transaction Mix**

	<b>Percentage</b>
New-Order	44.91 %
Payment	43.03 %
Order-Status	4.02 %
Delivery	4.02 %
Stock-Level	4.02 %

**6.11  
Transaction Statistics**

*The percentage of New-Order transactions rolled back as a result of invalid item number must be disclosed. [Clause 8.1.6.15]*

*The average number of order-lines entered per New-Order transaction must be disclosed. [Clause 8.1.6.16]*

*The percentage of remote order-lines entered per New-Order transaction must be disclosed. [Clause 8.1.6.17]*

*The percentage of remote Payment transactions must be disclosed. [Clause 8.1.6.18]*

*The percentage of customer selections by customer last name in the Payment and Order-Status transactions must be disclosed. [Clause 8.1.6.19]*

*The percentage of Delivery transactions skipped due to there being fewer than necessary orders in the New-Order table must be disclosed. [Clause 8.1.6.20]*

The numerical quantities which are required in Clause 8.1.6.15 to 8.1.6.20 are already listed in a table above (see section 3.5).

**6.12  
Checkpoint Statistics**

*The number of checkpoints in the Measurement Interval, the time in seconds from the start of the Measurement Interval to the first checkpoint and the Checkpoint Interval must be disclosed. [Clause 8.1.6.21]*

The numerical quantities which are required in Clause 8.1.6.21 are already listed above (see section 6.7).

## 7. Clause 6 Related Items - SUT, Driver, and Communication Definition

<b>7.1 RTE Inputs</b>	<i>If the RTE is commercially available, then its inputs must be specified. Otherwise, a description must be supplied of what inputs (e.g., scripts) to the RTE had been used. [Clause 8.1.7.1]</i>
---------------------------	---

Microsoft Benchcraft was used as the RTE to emulate the terminals. Its input parameters are shown in Appendix C - Tunable Parameters and Options.

We used COM+ to simulate terminal users, generate random data, record response times and statistical data. Its input parameters are shown in Appendix C - Tunable Parameters and Options.

<b>7.2 Lost Connections</b>	<i>The number of terminal connections lost during the Measurement Interval must be disclosed (see Clause 6.6.2). [Clause 8.1.7.3]</i>
---------------------------------	---

There were no lost connections during measurement interval.

<b>7.3 Functionality and Performance of Emulated Components</b>	<i>It must be demonstrated that the functionality and performance of the components being emulated in the Driver System are equivalent to that of the priced system. The results of the test described in Clause 6.6.3.4 must be disclosed. [Clause 8.1.7.3]</i>
---	--

The Driver System consisted of a PRIMERGY 870. This driver was attached to the client machine through a 100 Mbps ethernet LAN and switch. Since this is exactly the same connectivity as configured in the priced system, no component was emulated. Therefore, the test described in Clause 6.6.3.4 was not required.

<b>7.4 Functional Diagrams of the Benchmarked and Proposed Configuration</b>	<i>A complete functional diagram of both the benchmark configuration and the configuration of the proposed (target) system must be disclosed. A detailed list of all software and hardware functionality being performed on the Driver System, and its interface to the SUT must be disclosed (see Clause 6.6.3.6). [Clause 8.1.7.4]</i>
--	--

Figure 1 and Figure 2 in section 1.4 show the functional diagrams of the benchmark configuration and the priced configuration.

<b>7.5 Network Configurations of the Tested and Proposed Services</b>	<i>The network configurations of both the tested services and the proposed (target) services which are being represented and a thorough explanation of exactly which parts of the proposed configuration are being replaced with the Driver System must be disclosed (see Clause 6.6.4). [Clause 8.1.7.5]</i>
---	---

Figure 1 and Figure 2 in section 1.4 show the network setup of both configurations. The driver replaces the workstations.

In both configurations 2 Mbs FC was used to connect the server with the 3 clients with VI over FC and 100Mbps LAN with switch to connect the RTE systems or 55000 workstations to the clients.

**7.6  
Network Bandwidth**

*The bandwidth of the network(s) used in the tested / priced configuration must be disclosed. [Clause 8.1.7.6]*

The ethernet used in the local area network (LAN) between the emulated user system and the front-end system complies with the IEEE 802.3 standard. Its bandwidth is 100 Mbps. Between front-end and SUT the bandwidth is 100 Mbps.

**7.7  
Operator Intervention**

*If the configuration requires operator intervention (see Clause 6.6.6), the mechanism and the frequency of this intervention must be disclosed. [Clause 8.1.7.7]*

The PRIMERGY R450 requires no operator intervention to sustain the reported throughput.

## 8. Clause 7 Related Items - Pricing

<p><b>8.1 System Pricing</b></p>	<p><i>A detailed list of hardware and software used in the priced system must be reported. Each separately orderable item must have vendor part number, description, and release/revision level, and either general availability status or committed delivery date. If package-pricing is used, vendor part number of the package and a description uniquely identifying each of the components of the package must be disclosed. Pricing source(s) and effective date(s) of price(s) must also be reported. [Clause 8.1.8.1]</i></p> <p><i>The total 3-year price of the entire configuration must be reported, including: hardware, software, and maintenance charges. Separate component pricing is recommended. The basis of all discounts used must be disclosed. [Clause 8.1.8.2]</i></p>
--------------------------------------	---

The details of the hardware and software are reported in the summary in front of this report. The spreadsheet used to determine the 3-year price and the spreadsheet used to describe the priced configuration can be found in Appendix E - Price Quotations.

<p><b>8.2 Availability Dates</b></p>	<p><i>The committed delivery date for general availability (availability date) of products used in the price calculations must be reported. When the priced system includes products with different availability dates, the reported availability date for the priced system must be the date at which all components are committed to be available. This single date must be reported on the first page of the Executive Summary. All availability dates, whether for individual components or for the SUT as a whole, must be disclosed to a precision of one day. [Clause 8.1.8.3]</i></p>
--	---

All hardware and software components used in the price calculations of the PRIMERGY R450 system will be generally available from FUJITSU LIMITED as of July 20, 2003.

<p><b>8.3 Throughput and Price/Performance</b></p>	<p><i>A statement of the measured tpmC, as well as the respective calculations for 3-year pricing, price/performance (price/tpmC), and the availability date must be included. [Clause 8.1.8.4]</i></p>
--	---

PRIMERGY R450 system was measured at 68,264.47 tpmC with Microsoft SQL Server 2000 Enterprise Edition SP3 with a 3-year system price of Yen 78,549,210. The respective price/performance for the PRIMERGY R450 is Yen 1,150.66/tpmC. The priced PRIMERGY R450 will be available as of July 20, 2003.

<p><b>8.4 Country Specific Pricing</b></p>	<p><i>Additional Clause 7 related items may be included in the Full Disclosure Report for each country specific priced configuration. Country specific pricing is subject to Clause 7.1.7 [Clause 8.1.8.5]</i></p>
--	--

The system is being priced for Germany.

**8.5  
Usage Pricing**

*For any usage pricing, the sponsor must disclose:*

- *Usage level at which the component was priced.*
- *A statement of the company policy allowing such pricing.*

*[Clause 8.1.8.6]*

The component pricing based on usage is shown below:

- One Microsoft SQL Server 2000 Enterprise Edition SP3
- One Windows .NET Server 2003 Enterprise Edition
- 3 Microsoft Windows 2000 Server SP2 license (includes 5 client access licenses)
- One Microsoft Visual C++ Professional 6.0

## 9. Clause 8 Related Items - Audit

<b>9.1 Auditor</b>	<p><i>The auditor's name, address, phone number, and a copy of the auditor's attestation letter indicating compliance must be included in the Full Disclosure Report.</i></p> <p><i>A review of the pricing model is required to ensure that all components required are priced (see Clause 9.2.8). The auditor is not required to review the final Full Disclosure Report or the final pricing prior to issuing the attestation letter. [Clause 8.1.9]</i></p>
------------------------	---

The benchmark test of the PRIMERGY R450 system with Microsoft SQL Server 2000 Enterprise Edition SP3 was independently audited by:

Bradley Askins, TPC certified auditors of Infosizing.  
The attestation letter is included in Appendix F.

Requests for this TPC-C Full Disclosure Report should be sent to:

Transaction Processing Performance Council  
c/o Shanley Public Relations  
777 North First Street, Suite 6000  
San Jose, CA 95112-6311

or

Masayoshi TAKEI  
IA Server Division  
Personal Systems Business Group  
Fujitsu Limited  
1-1, Kamikodanaka 4-Chome, Nakahara-ku, Kawasaki  
211-8588, Japan

## Appendix A - Application Source Code

```
LIBRARY TPCC.DLL
```

```
EXPORTS
```

```
    GetExtensionVersion @1
    HttpExtensionProc   @2
    TerminateExtension  @3
```

```
/* FILE:      TPCC.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
 *           Metrics, 3/17/99
 *
 * PURPOSE:  Header file for ISAPI TPCC.DLL, defines structures and
 *           functions used in the isapi tpcc.dll.
 */
```

```
//VERSION RESOURCE DEFINES
```

```
#define _APS_NEXT_RESOURCE_VALUE      101
#define _APS_NEXT_COMMAND_VALUE      40001
#define _APS_NEXT_CONTROL_VALUE      1000
#define _APS_NEXT_SYMED_VALUE        101
```

```
#define TP_MAX_RETRIES                50
```

```
//note that the welcome form must be processed first as terminal ids
//assigned here, once the
//terminal id is assigned then the forms can be processed in any order.
#define WELCOME_FORM                  1           //beginning form no
term id assigned, form id
#define MAIN_MENU_FORM                2           //term id
assigned main menu form id
#define NEW_ORDER_FORM                3           //new order
form id
#define PAYMENT_FORM                  4           //payment form id
#define DELIVERY_FORM                 5           //delivery
form id
#define ORDER_STATUS_FORM             6           //order status id
#define STOCK_LEVEL_FORM              7           //stock level form
id
```

```
//This macro is used to prevent the compiler error unused formal parameter
#define UNUSEDPARAM(x) (x = x)
```

```
//This structure defines the data necessary to keep distinct for each
terminal or client connection.
typedef struct _CLIENTDATA
{
    int             iNextFree;                //index of next free element
or -1 if this entry in use.
    int             w_id;                    //warehouse id assigned at
welcome form
    int             d_id;                    //district id assigned at
welcome form

    int             iSyncId;                 //synchronization id
    int             iTickCount;              //time of last access;

    CTPCC_BASE *pTxn;
} CLIENTDATA, *PCLIENTDATA;
```

```
//This structure is used to define the operational interface for terminal id
support
typedef struct _TERM
{
    int             iNumEntries;              //total allocated
terminal array entries
    int             iFreeList;                //next available
terminal array element or -1 if none
    int             iMasterSyncId;           //synchronization id
    CLIENTDATA *pClientData;                 //pointer to allocated
client data
} TERM;

typedef TERM *PTERM;                          //pointer to terminal
structure type
```

```
enum WEBERROR
{
    NO_ERR,
    ERR_COMMAND_UNDEFINED,
    ERR_D_ID_INVALID,
    ERR_DELIVERY_CARRIER_ID_RANGE,
    ERR_DELIVERY_CARRIER_INVALID,
    ERR_DELIVERY_MISSING_OCD_KEY,
    ERR_DELIVERY_THREAD_FAILED,
    ERR_GETPROCADDR_FAILED,
    ERR_HTML_ILL_FORMED,
    ERR_INVALID_SYNC_CONNECTION,
```

```

ERR_INVALID_TERMID,
ERR_LOADDLL_FAILED,
ERR_MAX_CONNECTIONS_EXCEEDED,
ERR_MEM_ALLOC_FAILED,
ERR_MISSING_REGISTRY_ENTRIES,
ERR_NEWORDER_CUSTOMER_INVALID,
ERR_NEWORDER_CUSTOMER_KEY,
ERR_NEWORDER_DISTRICT_INVALID,
ERR_NEWORDER_FORM_MISSING_DID,
ERR_NEWORDER_ITEMID_INVALID,
ERR_NEWORDER_ITEMID_RANGE,
ERR_NEWORDER_ITEMID_WITHOUT_SUPPW,
ERR_NEWORDER_MISSING_IID_KEY,
ERR_NEWORDER_MISSING_QTY_KEY,
ERR_NEWORDER_MISSING_SUPPW_KEY,
ERR_NEWORDER_NOITEMS_ENTERED,
ERR_NEWORDER_QTY_INVALID,
ERR_NEWORDER_QTY_RANGE,
ERR_NEWORDER_QTY_WITHOUT_SUPPW,
ERR_NEWORDER_SUPPW_INVALID,
ERR_NO_SERVER_SPECIFIED,
ERR_ORDERSTATUS_CID_AND_CLT,
ERR_ORDERSTATUS_CID_INVALID,
ERR_ORDERSTATUS_CLT_RANGE,
ERR_ORDERSTATUS_DID_INVALID,
ERR_ORDERSTATUS_MISSING_CID_CLT,
ERR_ORDERSTATUS_MISSING_CID_KEY,
ERR_ORDERSTATUS_MISSING_CLT_KEY,
ERR_ORDERSTATUS_MISSING_DID_KEY,
ERR_PAYMENT_CDI_INVALID,
ERR_PAYMENT_CID_AND_CLT,
ERR_PAYMENT_CUSTOMER_INVALID,
ERR_PAYMENT_CWI_INVALID,
ERR_PAYMENT_DISTRICT_INVALID,
ERR_PAYMENT_HAM_INVALID,
ERR_PAYMENT_HAM_RANGE,
ERR_PAYMENT_LAST_NAME_TO_LONG,
ERR_PAYMENT_MISSING_CDI_KEY,
ERR_PAYMENT_MISSING_CID_CLT,
ERR_PAYMENT_MISSING_CID_KEY,
ERR_PAYMENT_MISSING_CLT,
ERR_PAYMENT_MISSING_CLT_KEY,
ERR_PAYMENT_MISSING_CWI_KEY,
ERR_PAYMENT_MISSING_DID_KEY,
ERR_PAYMENT_MISSING_HAM_KEY,
ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY,
ERR_STOCKLEVEL_THRESHOLD_INVALID,
ERR_STOCKLEVEL_THRESHOLD_RANGE,
ERR_VERSION_MISMATCH,
ERR_W_ID_INVALID
};

class CWEBCLNT_ERR : public CBaseErr
{
public:

```

```

CWEBCLNT_ERR(WEBERROR Err)
{
    m_Error = Err;
    m_szTextDetail = NULL;
    m_SystemErr = 0;
    m_szErrorText = NULL;
};

CWEBCLNT_ERR(WEBERROR Err, char *szTextDetail, DWORD dwSystemErr)
{
    m_Error = Err;
    m_szTextDetail = new char[strlen(szTextDetail)+1];
    strcpy( m_szTextDetail, szTextDetail );
    m_SystemErr = dwSystemErr;
    m_szErrorText = NULL;
};

~CWEBCLNT_ERR()
{
    if ( m_szTextDetail != NULL)
        delete [] m_szTextDetail;
    if ( m_szErrorText != NULL)
        delete [] m_szErrorText;
};

WEBERROR    m_Error;
char        *m_szTextDetail;    //
char        *m_szErrorText;
DWORD      m_SystemErr;

int ErrorType() {return ERR_TYPE_WEBDLL;};
int ErrorNum() {return m_Error;};
char *ErrorText();
};

//These constants have already been defined in engstut.h, but since we do
//not want to include it in the delisrv executable
#define TXN_EVENT_START    2
#define TXN_EVENT_STOP    4
#define TXN_EVENT_WARNING 6    //used to record a warning into the log

//function prototypes

BOOL APIENTRY DllMain(HANDLE hModule, DWORD ul_reason_for_call, LPVOID
lpReserved);
void WriteMessageToEventLog(LPTSTR lpszMsg);
void ProcessQueryString(EXTENSION_CONTROL_BLOCK *pECB, int *pCmd, int
*pFormId, int *pTermId, int *pSyncId);
void WelcomeForm(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer);
void SubmitCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer);
void BeginCmd(EXTENSION_CONTROL_BLOCK *pECB, int iFormId, int iTermId);
void ProcessCmd(EXTENSION_CONTROL_BLOCK *pECB, int iFormId, int iTermId);
void StatsCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer);

```



```

#endif // !_MAC

#ifdef APSTUDIO_INVOKED
////////////////////////////////////
/
//
// TEXTINCLUDE
//

1 TEXTINCLUDE DISCARDABLE
BEGIN
    "resource.h\0"
END

2 TEXTINCLUDE DISCARDABLE
BEGIN
    "#include "afxres.h"\r\n"
    "\0"
END

3 TEXTINCLUDE DISCARDABLE
BEGIN
    "\r\n"
    "\0"
END

#endif // APSTUDIO_INVOKED

////////////////////////////////////
/
//
// Dialog
//

IDD_DIALOG1 DIALOG DISCARDABLE 0, 0, 186, 95
STYLE DS_MODALFRAME | WS_POPUP | WS_CAPTION | WS_SYSMENU
CAPTION "Dialog"
FONT 8, "MS Sans Serif"
BEGIN
    DEFPUSHBUTTON "OK", IDOK, 129, 7, 50, 14
    PUSHBUTTON "Cancel", IDCANCEL, 129, 24, 50, 14
END

////////////////////////////////////
/
//
// DESIGNINFO
//

#ifdef APSTUDIO_INVOKED
GUIDELINES DESIGNINFO DISCARDABLE
BEGIN

```

```

IDD_DIALOG1, DIALOG
BEGIN
    LEFTMARGIN, 7
    RIGHTMARGIN, 179
    TOPMARGIN, 7
    BOTTOMMARGIN, 88
END
END
#endif // APSTUDIO_INVOKED

#endif // English (U.S.) resources
////////////////////////////////////
/

#ifdef APSTUDIO_INVOKED
////////////////////////////////////
/
//
// Generated from the TEXTINCLUDE 3 resource.
//

////////////////////////////////////
/
#endif // not APSTUDIO_INVOKED

/* FILE: TPCC.C
* Microsoft TPC-C Kit Ver. 4.20.000
* Copyright Microsoft, 1999
* All Rights Reserved
*
* Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
*
* PURPOSE: Main module for TPCC.DLL which is an ISAPI service dll.
* Contact: Charles Levine (clevine@microsoft.com)
*
* Change history:
* 4.20.000 - reworked error handling; added options for COM and
Encina txn monitors
*/

#include <windows.h>
#include <process.h>
#include <tchar.h>
#include <stdio.h>
#include <stdarg.h>
#include <malloc.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>

```

```

#include <io.h>
#include <assert.h>

#include <sqltypes.h>

#ifdef ICECAP
#include <icapexp.h>
#endif

#include "..\..\common\src\trans.h" //tpckit transaction header
contains definitions of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "..\..\common\src\ReadRegistry.h"

#include "..\..\common\txnlog\include\rtetime.h"
#include "..\..\common\txnlog\include\spinlock.h"
#include "..\..\common\txnlog\include\txnlog.h"

// Database layer includes
#include "..\..\db_dblib_dll\src\tpcc_dblib.h" // DBLIB implementation
of TPC-C txns
#include "..\..\db_odbc_dll\src\tpcc_odbc.h" // ODBC implementation
of TPC-C txns

// Txn monitor layer includes
#include "..\..\tm_com_dll\src\tpcc_com.h" // COM Services
implementation on TPC-C txns
#include "..\..\tm_tuxedo_dll\src\tpcc_tux.h" // interface to Tuxedo
libraries
#include "..\..\tm_encina_dll\src\tpcc_enc.h" // interface to Encina
libraries

#include "httpext.h" //ISAPI DLL information header
#include "tpcc.h" //this dlls specific structure,
value e.t. header.

#define LEN_ERR_STRING 256

// defines for Make<Txn>Form calls to distinguish input and output flavors
#define OUTPUT_FORM 0
#define INPUT_FORM 1

char szMyComputerName[MAX_COMPUTERNAME_LENGTH+1];

//Terminal client id structure
TERM Term = { 0, 0, 0, NULL };

// The WEBCLIENT_VERSION string specifies the version level of this web
client interface.
// The RTE must be synchronized with the interface level on login, otherwise
the login
// will fail. This is a sanity check to catch problems resulting from
mismatched versions

```

```

// of the RTE and web client.
#define WEBCLIENT_VERSION "410"

static CRITICAL_SECTION TermCriticalSection;

static HINSTANCE hLibInstanceTm = NULL;
static HINSTANCE hLibInstanceDb = NULL;

TYPE_CTPCC_DBLIB *pCTPCC_DBLIB_new;
TYPE_CTPCC_ODBC *pCTPCC_ODBC_new;
TYPE_CTPCC_TUXEDO *pCTPCC_TUXEDO_new;
TYPE_CTPCC_ENCINA *pCTPCC_ENCINA_new;
TYPE_CTPCC_ENCINA *pCTPCC_ENCINA_post_init;
TYPE_CTPCC_COM *pCTPCC_COM_new;

// For deferred Delivery txns:

CTxnLog *txnDelilog = NULL; //used to log
delivery transaction information

HANDLE hWorkerSemaphore = INVALID_HANDLE_VALUE;
HANDLE hDoneEvent = INVALID_HANDLE_VALUE;
HANDLE *pDeliHandles = NULL;

// configuration settings from registry
TPCCREGISTRYDATA Reg;

DWORD dwNumDeliveryThreads = 4;
CRITICAL_SECTION DelBuffCriticalSection; //critical section
for delivery transactions cache
DELIVERY_TRANSACTION *pDelBuff = NULL;
DWORD dwDelBuffSize = 100; // size of
circular buffer for delivery txns
DWORD dwDelBuffFreeCount; // number of
buffers free
DWORD dwDelBuffBusyIndex = 0; // index position
of entry waiting to be delivered
DWORD dwDelBuffFreeIndex = 0; // index position
of unused entry

#include "..\..\common\src\ReadRegistry.cpp"

/* FUNCTION: DllMain
*
* PURPOSE: This function is the entry point for the DLL. This
implementation is based on the
* fact that DLL_PROCESS_ATTACH is only called from the inet
service once.
*
* ARGUMENTS: HANDLE hModule module handle
* DWORDul_reason_for_call reason for call
* LPVOID lpReserved reserved for future use
*
*/

```

```

* RETURNS:          BOOL FALSE          errors ocured in
initialization
*                  TRUE                 DLL successfully
initialized
*/

BOOL APIENTRY DllMain(HANDLE hModule, DWORD ul_reason_for_call, LPVOID
lpReserved)
{
    DWORD i;
    char szEvent[LEN_ERR_STRING] = "\0";
    char szLogFile[128];
    char szDllName[128];

// debugging...
// DebugBreak();

    try
    {
        switch( ul_reason_for_call )
        {
            case DLL_PROCESS_ATTACH:
                {
                    DWORD dwSize = MAX_COMPUTERNAME_LENGTH+1;
                    GetComputerName(szMyComputerName, &dwSize);
                    szMyComputerName[dwSize] = 0;

                    DisableThreadLibraryCalls((HMODULE)hModule);
                    InitializeCriticalSection(&TermCriticalSection);

                    if ( ReadTPCCRegistrySettings( &Reg ) )
                        throw new CWEBCLNT_ERR(
ERR_MISSING_REGISTRY_ENTRIES );

                    dwDelBuffSize = min( Reg.dwMaxPendingDeliveries, 10000
); // min with 10000 as a sanity constraint
                    dwNumDeliveryThreads = min(
Reg.dwNumberOfDeliveryThreads, 100 ); // min with 100 as a sanity
constraint

                    TermInit();

                    // load DLL for txn monitor
                    if (Reg.eTxnMon == TUXEDO)
                    {
                        strcpy( szDllName, Reg.szPath );
                        strcat( szDllName, "tpcc_tuxedo.dll");
                        hLibInstanceTm = LoadLibrary( szDllName );
                        if (hLibInstanceTm == NULL)
                            throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

                        // get function pointer to wrapper for class
                    constructor
                }

                pCTPCC_TUXEDO_new = (TYPE_CTPCC_TUXEDO*)
GetProcAddress(hLibInstanceTm, "CTPCC_TUXEDO_new");
                if (pCTPCC_TUXEDO_new == NULL)
                    throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
            }
            else if (Reg.eTxnMon == ENCINA)
            {
                strcpy( szDllName, Reg.szPath );
                strcat( szDllName, "tpcc_encina.dll");
                hLibInstanceTm = LoadLibrary( szDllName );
                if (hLibInstanceTm == NULL)
                    throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

                // get function pointer to wrapper for class
            constructor
                pCTPCC_ENCINA_new = (TYPE_CTPCC_ENCINA*)
GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_new");
                pCTPCC_ENCINA_post_init = (TYPE_CTPCC_ENCINA*)
GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_post_init");
                if (pCTPCC_ENCINA_new == NULL)
                    throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
            }
            else if (Reg.eTxnMon == COM)
            {
                strcpy( szDllName, Reg.szPath );
                strcat( szDllName, "tpcc_com.dll");
                hLibInstanceTm = LoadLibrary( szDllName );
                if (hLibInstanceTm == NULL)
                    throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

                // get function pointer to wrapper for class
            constructor
                pCTPCC_COM_new = (TYPE_CTPCC_COM*)
GetProcAddress(hLibInstanceTm, "CTPCC_COM_new");
                if (pCTPCC_COM_new == NULL)
                    throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );

                // load DLL for database connection
                if ((Reg.eTxnMon == None) || (dwNumDeliveryThreads >
0))
                {
                    if (Reg.eDB_Protocol == DBLIB)
                    {
                        strcpy( szDllName, Reg.szPath );
                        strcat( szDllName, "tpcc_dblib.dll");
                        hLibInstanceDb = LoadLibrary( szDllName );
                        if (hLibInstanceDb == NULL)
                            throw new CWEBCLNT_ERR(
ERR_LOADDLL_FAILED, szDllName, GetLastError() );
                    }
                }
            }
        }
    }
}

```

```

pCTPCC_TUXEDO_new = (TYPE_CTPCC_TUXEDO*)
GetProcAddress(hLibInstanceTm, "CTPCC_TUXEDO_new");
if (pCTPCC_TUXEDO_new == NULL)
    throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
}
else if (Reg.eTxnMon == ENCINA)
{
    strcpy( szDllName, Reg.szPath );
    strcat( szDllName, "tpcc_encina.dll");
    hLibInstanceTm = LoadLibrary( szDllName );
    if (hLibInstanceTm == NULL)
        throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

    // get function pointer to wrapper for class
constructor
    pCTPCC_ENCINA_new = (TYPE_CTPCC_ENCINA*)
GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_new");
    pCTPCC_ENCINA_post_init = (TYPE_CTPCC_ENCINA*)
GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_post_init");
    if (pCTPCC_ENCINA_new == NULL)
        throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
}
else if (Reg.eTxnMon == COM)
{
    strcpy( szDllName, Reg.szPath );
    strcat( szDllName, "tpcc_com.dll");
    hLibInstanceTm = LoadLibrary( szDllName );
    if (hLibInstanceTm == NULL)
        throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

    // get function pointer to wrapper for class
constructor
    pCTPCC_COM_new = (TYPE_CTPCC_COM*)
GetProcAddress(hLibInstanceTm, "CTPCC_COM_new");
    if (pCTPCC_COM_new == NULL)
        throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );

    // load DLL for database connection
    if ((Reg.eTxnMon == None) || (dwNumDeliveryThreads >
0))
    {
        if (Reg.eDB_Protocol == DBLIB)
        {
            strcpy( szDllName, Reg.szPath );
            strcat( szDllName, "tpcc_dblib.dll");
            hLibInstanceDb = LoadLibrary( szDllName );
            if (hLibInstanceDb == NULL)
                throw new CWEBCLNT_ERR(
ERR_LOADDLL_FAILED, szDllName, GetLastError() );
        }
    }
}

```

```

        // get function pointer to wrapper for class
constructor
    pCTPCC_DBLIB_new = (TYPE_CTPCC_DBLIB*)
GetProcAddress(hLibInstanceDb, "CTPCC_DBLIB_new");
    if (pCTPCC_DBLIB_new == NULL)
        throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
    }
    else if (Reg.eDB_Protocol == ODBC)
    {
        strcpy( szDllName, Reg.szPath );
        strcat( szDllName, "tpcc_odbc.dll");
        hLibInstanceDb = LoadLibrary( szDllName );
        if (hLibInstanceDb == NULL)
            throw new CWEBCLNT_ERR(
ERR_LOADDLL_FAILED, szDllName, GetLastError() );
    }

    // get function pointer to wrapper for class
constructor
    pCTPCC_ODBC_new = (TYPE_CTPCC_ODBC*)
GetProcAddress(hLibInstanceDb, "CTPCC_ODBC_new");
    if (pCTPCC_ODBC_new == NULL)
        throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
    }
}

if (dwNumDeliveryThreads)
{
    // for deferred delivery txns:
    hDoneEvent = CreateEvent( NULL, TRUE /* manual
reset */, FALSE /* initially not signalled */, NULL );

    InitializeCriticalSection(&DelBuffCriticalSection);
    hWorkerSemaphore = CreateSemaphore( NULL, 0,
dwDelBuffSize, NULL );
    dwDelBuffFreeCount = dwDelBuffSize;

    InitJulianTime(NULL);

    // create unique log file name based on delilog-
yymmdd-hhmm.log
    SYSTEMTIME Time;
    GetLocalTime( &Time );
    wsprintf( szLogFile, "%sdelivery-%2.2d%2.2d%2.2d-
%2.2d%2.2d.log",
        Reg.szPath, Time.wYear % 100,
Time.wMonth, Time.wDay, Time.wHour, Time.wMinute );
    txnDelilog = new CTxnLog(szLogFile,
TXN_LOG_WRITE);

    //write event into txn log for START
    txnDelilog->WriteCtrlRecToLog(TXN_EVENT_START,
szMyComputerName, sizeof(szMyComputerName));
}

```

```

        // allocate structures for delivery buffers and
thread mgmt
    pDeliHandles = new HANDLE[dwNumDeliveryThreads];
    pDelBuff = new
DELIVERY_TRANSACTION[dwDelBuffSize];
    // launch DeliveryWorkerThread to perform actual
delivery txns
    for(i=0; i<dwNumDeliveryThreads; i++)
    {
        pDeliHandles[i] = (HANDLE) _beginthread(
DeliveryWorkerThread, 0, NULL );
        if (pDeliHandles[i] == INVALID_HANDLE_VALUE)
            throw new CWEBCLNT_ERR(
ERR_DELIVERY_THREAD_FAILED );
    }
}

break;

case DLL_PROCESS_DETACH:
    if (dwNumDeliveryThreads)
    {
        if (txnDelilog != NULL)
        {
            //write event into txn log for STOP
            txnDelilog->WriteCtrlRecToLog(TXN_EVENT_STOP,
szMyComputerName, sizeof(szMyComputerName));

            // This will do a clean shutdown of the
delivery log file
            CTxnLog *txnDelilogLocal = txnDelilog;
            txnDelilog= NULL;
            delete txnDelilogLocal;
        }

        delete [] pDeliHandles;
        delete [] pDelBuff;

        CloseHandle( hWorkerSemaphore );
        CloseHandle( hDoneEvent );
        DeleteCriticalSection(&DelBuffCriticalSection);
    }

    DeleteCriticalSection(&TermCriticalSection);

    if (hLibInstanceTm != NULL)
        FreeLibrary( hLibInstanceTm );
    hLibInstanceTm = NULL;

    if (hLibInstanceDb != NULL)
        FreeLibrary( hLibInstanceDb );
    hLibInstanceDb = NULL;

    Sleep(500);
    break;
}

```

```

        default:
            /* nothing */;
    }
}
catch (CBaseErr *e)
{
    WriteMessageToEventLog( e->ErrorText() );
    delete e;
    TerminateExtension(0);
    return FALSE;
}
catch (...)
{
    WriteMessageToEventLog(TEXT("Unhandled exception. DLL could not
load."));
    TerminateExtension(0);
    return FALSE;
}

return TRUE;
}

/* FUNCTION: GetExtensionVersion
*
* PURPOSE: This function is called by the inet service when the DLL is
first loaded.
*
* ARGUMENTS: HSE_VERSION_INFO *pVerpassed in structure in which to
place expected version number.
*
* RETURNS: TRUE inet service expected return value.
*/

BOOL WINAPI GetExtensionVersion(HSE_VERSION_INFO *pVer)
{
    pVer->dwExtensionVersion = MAKELONG(HSE_VERSION_MINOR,
HSE_VERSION_MAJOR);
    lstrcpy(pVer->lpszExtensionDesc, "TPC-C Server.",
HSE_MAX_EXT_DLL_NAME_LEN);

    // TODO: why do we need this here instead of in the DLL attach?
    if (Reg.eTxnMon == ENCINA)
        pCTPCC_ENCINA_post_init();

    return TRUE;
}

/* FUNCTION: TerminateExtension
*
* PURPOSE: This function is called by the inet service when the DLL is
about to be unloaded.
*
* Release all resources in anticipation of being unloaded.
*

```

```

* RETURNS: TRUE inet service expected return value.
*/

BOOL WINAPI TerminateExtension( DWORD dwFlags )
{
    if (pDeliHandles)
    {
        SetEvent( hDoneEvent );
        for(DWORD i=0; i<dwNumDeliveryThreads; i++)
            WaitForSingleObject( pDeliHandles[i], INFINITE );
    }

    TermDeleteAll();
    return TRUE;
}

/* FUNCTION: HttpExtensionProc
*
* PURPOSE: This function is the main entry point for the TPCC DLL. The
internet service
*
* calls this function passing in the http string.
*
* ARGUMENTS: EXTENSION_CONTROL_BLOCK *pECBstructure pointer to passed
in internet
*
* service
information.
*
* RETURNS: DWORDHSE_STATUS_SUCCESS
connection can be dropped if error
*
* HSE_STATUS_SUCCESS_AND_KEEP_CONN keep
connect valid comment sent
*
* COMMENTS: None
*
*/

DWORD WINAPI HttpExtensionProc(EXTENSION_CONTROL_BLOCK *pECB)
{
    int iCmd, FormId, TermId, iSyncId;
    char szBuffer[4096];

    int lpbSize;
    static char szHeader[] = "200 Ok";
    DWORD dwSize = 6; // initial value is strlen(szHeader)
    char szHeader1[4096];

#ifdef ICECAP
    StartCAP();
#endif

    try
    {
        //process http query
    }
}

```

```

ProcessQueryString(pECB, &iCmd, &FormId, &TermId, &iSyncId);

if (TermId != 0)
{
    if ( TermId < 0 || TermId >= Term.iNumEntries ||
Term.pClientData[TermId].iNextFree != -1 )
    {
        // debugging...
        char szTmp[128];
        wsprintf( szTmp, "Invalid term ID; TermId = %d", TermId
);

        WriteMessageToEventLog( szTmp );

        throw new CWEBCLNT_ERR( ERR_INVALID_TERMID );
    }

    //must have a valid syncid here since termid is valid
    if (iSyncId != Term.pClientData[TermId].iSyncId)
        throw new CWEBCLNT_ERR( ERR_INVALID_SYNC_CONNECTION );

    //set use time
    Term.pClientData[TermId].iTickCount = GetTickCount();
}

switch(iCmd)
{
case 0:
    WelcomeForm(pECB, szBuffer);
    break;
case 1:
    switch( FormId )
    {
        case WELCOME_FORM:
        case MAIN_MENU_FORM:
            break;
        case NEW_ORDER_FORM:
            ProcessNewOrderForm(pECB, TermId, szBuffer);
            break;
        case PAYMENT_FORM:
            ProcessPaymentForm(pECB, TermId, szBuffer);
            break;
        case DELIVERY_FORM:
            ProcessDeliveryForm(pECB, TermId, szBuffer);
            break;
        case ORDER_STATUS_FORM:
            ProcessOrderStatusForm(pECB, TermId, szBuffer);
            break;
        case STOCK_LEVEL_FORM:
            ProcessStockLevelForm(pECB, TermId, szBuffer);
            break;
    }
    break;
case 2:
    // new-order selected from menu; display new-order input form

```

```

        MakeNewOrderForm(TermId, NULL, INPUT_FORM, szBuffer);
        break;
case 3:
    // payment selected from menu; display payment input form
    MakePaymentForm(TermId, NULL, INPUT_FORM, szBuffer);
    break;
case 4:
    // delivery selected from menu; display delivery input form
    MakeDeliveryForm(TermId, NULL, INPUT_FORM, szBuffer);
    break;
case 5:
    // order-status selected from menu; display order-status
input form
    MakeOrderStatusForm(TermId, NULL, INPUT_FORM, szBuffer);
    break;
case 6:
    // stock-level selected from menu; display stock-level input
form
    MakeStockLevelForm(TermId, NULL, INPUT_FORM, szBuffer);
    break;
case 7:
    // ExitCmd
    TermDelete(TermId);
    WelcomeForm(pECB, szBuffer);
    break;
case 8:
    SubmitCmd(pECB, szBuffer);
    break;
case 9:
    // menu
    MakeMainMenuForm(TermId, Term.pClientData[TermId].iSyncId,
szBuffer);
    break;
case 10:
    // CMD=Clear
    // resets all connections; should only be used when no other
connections are active
    TermDeleteAll();
    TermInit();
    WelcomeForm(pECB, szBuffer);
    break;
case 11: // CMD=Stats
    StatsCmd(pECB, szBuffer);
    break;
}
}
catch (CBaseErr *e)
{
    ErrorForm( pECB, e->ErrorType(), e->ErrorNum(), TermId, iSyncId,
e->ErrorText(), szBuffer );
    delete e;
}
catch (...)
{

```

```

        ErrorForm( pECB, ERR_TYPE_WEBDLL, 0, TermId, iSyncId, "Error:
Unhandled exception in Web Client.", szBuffer );
    }

```

```

#ifdef ICECAP
    StopCAP();
#endif

```

```

    lpbSize = strlen(szBuffer);
    wsprintf(szHeader1,
        "Content-Type: text/html\r\n"
        "Content-Length: %d\r\n"
        "Connection: Keep-Alive\r\n\r\n" , lpbSize);
    strcat( szHeader1, szBuffer );

```

```

    (*pECB->ServerSupportFunction)(pECB->ConnID,
HSE_REQ_SEND_RESPONSE_HEADER, szHeader, (LPDWORD) &dwSize,
(LPDWORD)szHeader1);

```

```

    //finish up and keep connection
    pECB->dwHttpStatusCode = 200;
    return HSE_STATUS_SUCCESS_AND_KEEP_CONN;
}

```

```

void WriteMessageToEventLog(LPTSTR lpszMsg)
{

```

```

    TCHAR    szMsg[256];
    HANDLE   hEventSource;
    LPTSTR   lpszStrings[2];

```

```

    // Use event logging to log the error.
    //
    hEventSource = RegisterEventSource(NULL, TEXT("TPCC.DLL"));

```

```

    _stprintf(szMsg, TEXT("Error in TPCC.DLL: "));
    lpszStrings[0] = szMsg;
    lpszStrings[1] = lpszMsg;

```

```

    if (hEventSource != NULL)
    {

```

```

        ReportEvent(hEventSource, // handle of event source
            EVENTLOG_ERROR_TYPE, // event type
            0, // event category
            0, // event ID
            NULL, // current user's SID
            2, // strings in lpszStrings
            0, // no bytes of raw data
            (LPTSTR *)lpszStrings, // array of error strings
            NULL); // no raw data

```

```

        (VOID) DeregisterEventSource(hEventSource);
    }
}

```

```

/* FUNCTION: DeliveryWorkerThread

```

```

 *
 * PURPOSE: This function processes deferred delivery txns. There are
typically several
 * threads running this routine. The number of threads is
determined by an entry
 * read from the registry. The thread waits for work by waiting
on semaphore.
 * When a delivery txn is posted, the semaphore is released.
After processing
 * the delivery txn, information is logged to record the txn
status and execution
 * time.
 */

```

```

/*static*/ void DeliveryWorkerThread(void *ptr)
{

```

```

    CTPCC_BASE    *pTxn = NULL;

```

```

    DELIVERY_TRANSACTION    delivery;
    PDELIVERY_DATA          pDeliveryData;
    TXN_RECORD_TPCC_DELIV_DEF    txnDeliRec;

```

```

    DWORD          index;
    HANDLE          handles[2];

```

```

    SYSTEMTIME    trans_end; //delivery transaction finished time
    SYSTEMTIME    trans_start; //delivery transaction start time

```

```

    assert(txnDelilog != NULL);

```

```

    try
    {

```

```

        if (Reg.eDB_Protocol == ODBC)
            pTxn = pCTPCC_ODBC_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
        else if (Reg.eDB_Protocol == DBLIB)
            pTxn = pCTPCC_DBLIB_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
        pDeliveryData = pTxn->BuffAddr_Delivery();
    }

```

```

    catch (CBaseErr *e)
    {

```

```

        char szTmp[1024];
        wsprintf( szTmp, "Error in Delivery Txn thread. Could not connect
to database. "

```

```

                "%s. Server=%s, User=%s, Password=%s, Database=%s",
                e->ErrorText(), Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, Reg.szDbName );

```

```

        WriteMessageToEventLog( szTmp );
        delete e;
        goto ErrorExit;
    }
}

```

```

catch (...)
{
    WriteMessageToEventLog(TEXT("Unhandled exception caught in
DeliveryWorkerThread."));
    goto ErrorExit;
}

while (TRUE)
{
    try
    {
        //while delivery thread running, i.e. user has not requested
        termination
        while (TRUE)
        {
            // need to wait for multiple objects: program exit or
            worker semaphore;
            handles[0] = hDoneEvent;
            handles[1] = hWorkerSemaphore;
            index = WaitForMultipleObjects( 2, &handles[0], FALSE,
            INFINITE );

            if (index == WAIT_OBJECT_0)
                goto ErrorExit;

            ZeroMemory(&txnDeliRec, sizeof(txnDeliRec));
            txnDeliRec.TxnType = TXN_REC_TYPE_TPCC_DELIV_DEF;

            // make a local copy of current entry from delivery
            buffer and increment buffer index
            EnterCriticalSection(&DelBuffCriticalSection);
            delivery = *(pDelBuff+dwDelBuffBusyIndex);
            dwDelBuffFreeCount++;
            dwDelBuffBusyIndex++;
            if (dwDelBuffBusyIndex == dwDelBuffSize) // wrap-
            around if at end of buffer
                dwDelBuffBusyIndex = 0;

            LeaveCriticalSection(&DelBuffCriticalSection);

            pDeliveryData->w_id = delivery.w_id;
            pDeliveryData->o_carrier_id = delivery.o_carrier_id;

            txnDeliRec.w_id = pDeliveryData->w_id;
            txnDeliRec.o_carrier_id = pDeliveryData->o_carrier_id;
            txnDeliRec.TxnStartT0 = Get64BitTime(&delivery.queue);

            GetLocalTime( &trans_start );
            pTxn->Delivery();
            GetLocalTime( &trans_end );

            //log txn
            txnDeliRec.TxnStatus = ERR_SUCCESS;
            for (int i=0; i<10; i++)
                txnDeliRec.o_id[i] = pDeliveryData->o_id[i];

```

```

        txnDeliRec.DeltaT4 = (int)(Get64BitTime(&trans_end) -
txnDeliRec.TxnStartT0);
        txnDeliRec.DeltaTxnExec =
(int)(Get64BitTime(&trans_end) - Get64BitTime(&trans_start));

        if (txnDelilog != NULL)
            txnDelilog->WriteToLog(&txnDeliRec);
    }
}
catch (CBaseErr *e)
{
    char szTmp[1024];
    wsprintf( szTmp, "Error in Delivery Txn thread. %s", e-
>ErrorText() );
    WriteMessageToEventLog( szTmp );

    // log the error txn
    txnDeliRec.TxnStatus = e->ErrorType();
    if (txnDelilog != NULL)
        txnDelilog->WriteToLog(&txnDeliRec);

    delete e;
}
catch (...)
{
    // unhandled exception; shouldn't happen; not much we can
do...
    WriteMessageToEventLog(TEXT("Unhandled exception caught in
DeliveryWorkerThread."));
}

ErrorExit:
    delete pTxn;
    _endthread();
}

/* FUNCTION: PostDeliveryInfo
*
* PURPOSE: This function enters the delivery txn into the deferred
delivery buffer.
*
* RETURNS: BOOL FALSE delivery information posted successfully
*          TRUE error cannot post delivery info
*/

BOOL PostDeliveryInfo(short w_id, short o_carrier_id)
{
    BOOL bError;

    EnterCriticalSection(&DelBuffCriticalSection);
    if (dwDelBuffFreeCount > 0)
    {
        bError = FALSE;
        (pDelBuff+dwDelBuffFreeIndex)->w_id
            = w_id;

```

```

    (pDelBuff+dwDelBuffFreeIndex)->o_carrier_id    = o_carrier_id;
    GetLocalTime(&(pDelBuff+dwDelBuffFreeIndex)->queue);

    dwDelBuffFreeCount--;
    dwDelBuffFreeIndex++;
    if (dwDelBuffFreeIndex == dwDelBuffSize)
        dwDelBuffFreeIndex = 0;          // wrap-around if at end of
buffer
    }
    else
        // No free buffers. Return an error, which indicates that the
delivery buffer is full.
        // Most likely, the number of delivery worker threads needs to be
increased to keep up
        // with the txn rate.
        bError = TRUE;
        LeaveCriticalSection(&DelBuffCriticalSection);

    if (!bError)
        // increment worker semaphore to wake up a worker thread
        ReleaseSemaphore( hWorkerSemaphore, 1, NULL );

    return bError;
}

/* FUNCTION: ProcessQueryString
 *
 * PURPOSE:      This function extracts the relevent information out of the
http command passed in from
 *               the browser.
 *
 * COMMENTS:     If this is the initial connection i.e. client is at welcome
screen then
 *               there will not be a terminal id or current form id. If
this is the case
 *               then the pTermid and pFormid return values are
undefined.
 */

void ProcessQueryString(EXTENSION_CONTROL_BLOCK *pECB, int *pCmd, int
*pFormId, int *pTermId, int *pSyncId)
{
    char *ptr = pECB->lpszQueryString;
    char szBuffer[25];
    int i;

    //allowable client command strings i.e. CMD=command
    static char *szCmds[] =
    {
        "Process", "..NewOrder..", "..Payment..", "..Delivery..",
        "..Order-Status..", "..Stock-Level..",
        "..Exit..", "Submit", "Menu", "Clear", "Stats", ""
    };

    *pCmd = 0;          // default is the login screen

```

```

    *pTermId = 0;

    // if no params (i.e., empty query string), then return login screen
    if (strlen(pECB->lpszQueryString) == 0)
        return;

    // parse FORMID, TERMID, and SYNCID
    *pFormId = GetIntKeyValue(&ptr, "FORMID", NO_ERR, NO_ERR);
    *pTermId = GetIntKeyValue(&ptr, "TERMID", NO_ERR, NO_ERR);
    *pSyncId = GetIntKeyValue(&ptr, "SYNCID", NO_ERR, NO_ERR);

    // parse CMD
    GetKeyValue(&ptr, "CMD", szBuffer, sizeof(szBuffer),
ERR_COMMAND_UNDEFINED);

    // see which command it matches
    for(i=0; ; i++)
    {
        if (szCmds[i][0] == 0)
            // no more; no match; return error
            throw new CWEBCLNT_ERR( ERR_COMMAND_UNDEFINED );
        if ( !strcmp(szCmds[i], szBuffer) )
        {
            *pCmd = i+1;
            break;
        }
    }
}

/* FUNCTION: void WelcomeForm
 *
 */

void WelcomeForm(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer)
{
    char szTmp[1024];

    //welcome to tpc-c html form buffer, this is first form client sees.
    strcpy( szBuffer, "<HTML><HEAD><TITLE>TPC-C Web
Client</TITLE></HEAD><BODY>"
        "<B><BIG>Microsoft TPC-C Web Client (ver
4.20)</BIG></B> <BR> <BR>"
        "<font face=\"Courier New\"><PRE>"
        "Compiled: \"__DATE__\", \"__TIME__\" <BR>"
        "Source: \"__FILE__\" ( \"__TIMESTAMP__\" ) <BR>"
        "</PRE></font>"
        "<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
        "<INPUT TYPE=\"hidden\" NAME=\"STATUSID\"
VALUE=\"0\">"
        "<INPUT TYPE=\"hidden\" NAME=\"ERROR\"
VALUE=\"0\">"
        "<INPUT TYPE=\"hidden\" NAME=\"FORMID\"
VALUE=\"1\">"
        "<INPUT TYPE=\"hidden\" NAME=\"TERMID\"
VALUE=\"0\">"

```

```

                "<INPUT TYPE=\"hidden\" NAME=\"SYNCID\"
VALUE=\"0\">"
                "<INPUT TYPE=\"hidden\" NAME=\"VERSION\"
VALUE=\"\" WEBCLIENT_VERSION \"\">"
            );

    sprintf( szTmp, "Configuration Settings: <BR><font face=\"Courier New\"
color=\"blue\"><PRE>"
            "Txn Monitor          = <B>%s</B><BR>"
            "Database protocol      = <B>%s</B><BR>"
            "Max Connections          = <B>%d</B><BR>"
            "# of Delivery Threads    = <B>%d</B><BR>"
            "Max Pending Deliveries = <B>%d</B><BR>"
            , szTxnMonNames[Reg.eTxnMon], szDBNames[Reg.eDB_Protocol],
            Reg.dwMaxConnections, dwNumDeliveryThreads, dwDelBuffSize );
    strcat( szBuffer, szTmp);

    if (Reg.eTxnMon == COM)
    {
        sprintf( szTmp, "COM Single Pool          = <B>%s</B><BR>",
            Reg.bCOM_SinglePool ? "YES" : "NO" );
        strcat( szBuffer, szTmp);
    }
    strcat( szBuffer, "</PRE></font>");

    if (Reg.eTxnMon == None)
        // connection options may be specified when not using a txn
        monitor
        sprintf( szTmp, "Please enter your database options for this
connection:<BR>"
                "<font face=\"Courier New\"
color=\"blue\"><PRE>"
                "DB Server      = <INPUT NAME=\"db_server\"
SIZE=20 VALUE=\"%s\"><BR>"
                "DB User ID    = <INPUT NAME=\"db_user\"
SIZE=20 VALUE=\"%s\"><BR>"
                "DB Password  = <INPUT NAME=\"db_passwd\"
SIZE=20 VALUE=\"%s\"><BR>"
                "DB Name      = <INPUT NAME=\"db_name\"
SIZE=20 VALUE=\"%s\"><BR>"
                "</PRE></font>"
                , Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
Reg.szDbName );
    else
        // if using a txn monitor, connection options are determined from
        registry; can't
        // set per user. show options fyi
        sprintf( szTmp, "Database options which will be used by the
transaction monitor:<BR>"
                "<font face=\"Courier New\"
color=\"blue\"><PRE>"
                "DB Server      = <B>%s</B><BR>"
                "DB User ID    = <B>%s</B><BR>"
                "DB Password  = <B>%s</B><BR>"
                "DB Name      = <B>%s</B><BR>"

```

```

                "</PRE></font>"
                , Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
Reg.szDbName );
    strcat( szBuffer, szTmp);

    sprintf( szTmp, "Please enter your Warehouse and District for this
session:<BR>"
            "<font face=\"Courier New\" color=\"blue\"><PRE>"
            );
    strcat( szBuffer, szTmp);
    strcat( szBuffer, "Warehouse ID = <INPUT NAME=\"w_id\" SIZE=4><BR>"
            "District ID = <INPUT NAME=\"d_id\"
SIZE=2><BR>"
            "</PRE></font><HR>"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"Submit\">"
            "</FORM></BODY></HTML>");
}

/* FUNCTION: SubmitCmd
 *
 * PURPOSE: This function allocated a new terminal id in the Term
structure array.
 *
 */

void SubmitCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer)
{
    int iNewTerm;
    char *ptr = pECB->lpszQueryString;

    char szVersion[32] = { 0 };
    char szServer[32] = { 0 };
    char szUser[32] = "sa";
    char szPassword[32] = { 0 };
    char szDatabase[32] = "tpcc";

    // validate version field; the version field ensures that the RTE is
    synchronized with the web client
    GetKeyValue(&ptr, "VERSION", szVersion, sizeof(szVersion),
ERR_VERSION_MISMATCH);
    if ( strcmp( szVersion, WEBCLIENT_VERSION ) )
        throw new CWEBCLNT_ERR( ERR_VERSION_MISMATCH );

    if (Reg.eTxnMon == None)
    {
        // parse Server name
        GetKeyValue(&ptr, "db_server", szServer, sizeof(szServer),
ERR_NO_SERVER_SPECIFIED);
        // parse User name
        GetKeyValue(&ptr, "db_user", szUser, sizeof(szUser), NO_ERR);
        // parse Password
        GetKeyValue(&ptr, "db_passwd", szPassword, sizeof(szPassword),
NO_ERR);
        // parse Database name

```

```

        GetKeyValue(&ptr, "db_name", szDatabase, sizeof(szDatabase),
NO_ERR);
    }

    // parse warehouse ID
    int w_id = GetIntKeyValue(&ptr, "w_id", ERR_HTML_ILL_FORMED,
ERR_W_ID_INVALID);
    if ( w_id < 1 )
        throw new CWEBCLNT_ERR( ERR_W_ID_INVALID );

    // parse district ID
    int d_id = GetIntKeyValue(&ptr, "d_id", ERR_HTML_ILL_FORMED,
ERR_D_ID_INVALID);
    if ( d_id < 1 || d_id > 10 )
        throw new CWEBCLNT_ERR( ERR_D_ID_INVALID );

    iNewTerm = TermAdd();

    Term.pClientData[iNewTerm].w_id = w_id;
    Term.pClientData[iNewTerm].d_id = d_id;

    try
    {
        if (Reg.eTxnMon == TUXEDO)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_TUXEDO_new();
        else if (Reg.eTxnMon == ENCINA)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_ENCINA_new();
        else if (Reg.eTxnMon == COM)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_COM_new(
Reg.bCOM_SinglePool );
        else if (Reg.eDB_Protocol == ODBC)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_ODBC_new( szServer,
szUser, szPassword, szMyComputerName, szDatabase );
        else if (Reg.eDB_Protocol == DBLIB)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_DBLIB_new( szServer,
szUser, szPassword, szMyComputerName, szDatabase );
    }
    catch (...)
    {
        TermDelete(iNewTerm);
        throw; // pass exception upward
    }

    MakeMainMenuForm(iNewTerm, Term.pClientData[iNewTerm].iSyncId,
szBuffer);
}

/* FUNCTION: StatsCmd
 *
 * PURPOSE: This function returns to the browser the total number of
active terminal ids.
 * This routine is for development/debugging purposes.
 */

```

```

void StatsCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer)
{
    int i;
    int iTot;

    EnterCriticalSection(&TermCriticalSection);

    iTot = 0;
    for(i=0; i<Term.iNumEntries; i++)
    {
        if (Term.pClientData[i].iNextFree == -1)
            iTot++;
    }

    LeaveCriticalSection(&TermCriticalSection);

    wsprintf( szBuffer,
        "<HTML><HEAD><TITLE>TPC-C Web Client Stats</TITLE></HEAD>"
        "<BODY><B><BIG> Total Active Connections: %d"
</BIG></B><BR></BODY></HTML>"
        , iTot );
}

char *CWEBCLNT_ERR::ErrorText()
{
    static SERRORMSG errorMsgs[] =
    {
        { ERR_COMMAND_UNDEFINED, "Command
undefined." },
        { ERR_D_ID_INVALID, "Invalid
District ID Must be 1 to 10." },
        { ERR_DELIVERY_CARRIER_ID_RANGE, "Delivery Carrier
ID out of range must be 1 - 10." },
        { ERR_DELIVERY_CARRIER_INVALID, "Delivery Carrier
ID invalid must be numeric 1 - 10." },
        { ERR_DELIVERY_MISSING_OCD_KEY, "Delivery missing
Carrier ID key \"OCD*\"." },
        { ERR_DELIVERY_THREAD_FAILED, "Could not
start delivery worker thread." },
        { ERR_GETPROCADDR_FAILED, "Could not
map proc in DLL. GetProcAddr error. DLL="
        { ERR_HTML_ILL_FORMED, "Required key field
is missing from HTML string." },
        { ERR_INVALID_SYNC_CONNECTION, "Invalid Terminal
Sync ID." },
        { ERR_INVALID_TERMID, "Invalid
Terminal ID." },
        { ERR_LOADDLL_FAILED, "Load of DLL
failed. DLL=" },
        { ERR_MAX_CONNECTIONS_EXCEEDED, "No connections
available. Max Connections is probably too low." },
        { ERR_MISSING_REGISTRY_ENTRIES, "Required registry
entries are missing. Rerun INSTALL to correct." },
    }
}

```

<pre>         { ERR_NEWORDER_CUSTOMER_INVALID, id invalid data type, range = 1 to 3000." },         { ERR_NEWORDER_CUSTOMER_KEY, Customer key \"CID*\".\" },         { ERR_NEWORDER_DISTRICT_INVALID, ID Invalid range 1 - 10.\" },         { ERR_NEWORDER_FORM_MISSING_DID, District key \"DID*\".\" },         { ERR_NEWORDER_ITEMID_INVALID, is wrong data type, must be numeric.\" },         { ERR_NEWORDER_ITEMID_RANGE, is out of range. Range = 1 to 999999.\" },         { ERR_NEWORDER_ITEMID_WITHOUT_SUPPW, field entered without a corresponding Supp.W.\" },         { ERR_NEWORDER_MISSING_IID_KEY, Item Id key \"IID*\".\" },         { ERR_NEWORDER_MISSING_QTY_KEY, Qty key \"Qty##*\".\" },         { ERR_NEWORDER_MISSING_SUPPW_KEY, Supp_W key \"SP##*\".\" },         { ERR_NEWORDER_NOITEMS_ENTERED, lines entered.\" },         { ERR_NEWORDER_QTY_INVALID, invalid must be numeric range 1 - 99.\" },         { ERR_NEWORDER_QTY_RANGE, Qty is out of range. Range = 1 to 99.\" },         { ERR_NEWORDER_QTY_WITHOUT_SUPPW, field entered without a corresponding Supp.W.\" },         { ERR_NEWORDER_SUPPW_INVALID, Supp_W invalid data type must be numeric.\" },         { ERR_NO_SERVER_SPECIFIED, specified.\" },         { ERR_ORDERSTATUS_CID_AND_CLT, Customer ID or Last Name may be entered, not both.\" },         { ERR_ORDERSTATUS_CID_INVALID, Customer ID invalid, range must be numeric 1 - 3000.\" },         { ERR_ORDERSTATUS_CLT_RANGE, Customer last name longer than 16 characters.\" },         { ERR_ORDERSTATUS_DID_INVALID, District invalid, value must be numeric 1 - 10.\" },         { ERR_ORDERSTATUS_MISSING_CID_CLT, Either Customer ID or Last Name must be entered.\" },         { ERR_ORDERSTATUS_MISSING_CID_KEY, missing Customer key \"CID*\".\" },         { ERR_ORDERSTATUS_MISSING_CLT_KEY, missing Customer Last Name key \"CLT*\".\" },         { ERR_ORDERSTATUS_MISSING_DID_KEY, missing District key \"DID*\".\" },         { ERR_PAYMENT_CDI_INVALID, district invalid must be numeric.\" },         { ERR_PAYMENT_CID_AND_CLT, Customer ID or Last Name may be entered, not both.\" },         { ERR_PAYMENT_CUSTOMER_INVALID, data type invalid, must be numeric.\" }, </pre>	<pre> "New Order customer "New Order missing "New Order District "New Order missing "New Order Item Id "New Order Item Id "New Order Item Id "New Order missing "New Order Missing "New Order missing "New Order No order "New Order Qty "New Order Qty "New Order "New Order Qty "New Order "No Server name "Order Status Only "Order Status "Payment Customer "Payment Only "Payment Customer </pre>	<pre>         { ERR_PAYMENT_CWI_INVALID, Warehouse invalid, must be numeric.\" },         { ERR_PAYMENT_DISTRICT_INVALID, ID is invalid, must be 1 - 10.\" },         { ERR_PAYMENT_HAM_INVALID, invalid data type must be numeric.\" },         { ERR_PAYMENT_HAM_RANGE, Amount out of range, 0 - 9999.99.\" },         { ERR_PAYMENT_LAST_NAME_TO_LONG, last name longer than 16 characters.\" },         { ERR_PAYMENT_MISSING_CDI_KEY, Customer district key \"CDI*\".\" },         { ERR_PAYMENT_MISSING_CID_CLT, Customer ID or Last Name must be entered.\" },         { ERR_PAYMENT_MISSING_CID_KEY, Customer Key \"CID*\".\" },         { ERR_PAYMENT_MISSING_CLT_KEY, Customer Last Name key \"CLT*\".\" },         { ERR_PAYMENT_MISSING_CWI_KEY, Customer Warehouse key \"CWI*\".\" },         { ERR_PAYMENT_MISSING_DID_KEY, District Key \"DID*\".\" },         { ERR_PAYMENT_MISSING_HAM_KEY, Amount key \"HAM*\".\" },         { ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY, missing Threshold key \"TT*\".\" },         { ERR_STOCKLEVEL_THRESHOLD_INVALID, Threshold value must be in the range = 1 - 99.\" },         { ERR_STOCKLEVEL_THRESHOLD_RANGE, Threshold out of range, range must be 1 - 99.\" },         { ERR_VERSION_MISMATCH, version field. RTE and Web Client are probably out of sync.\" },         { ERR_W_ID_INVALID, Warehouse ID.\" },         { 0, } };  char szTmp[256]; int i = 0; while (TRUE) {     if (errorMsgs[i].szMsg[0] == 0)     {         strcpy( szTmp, "Unknown error number.\" );         break;     }     if (m_Error == errorMsgs[i].iError)     {         strcpy( szTmp, errorMsgs[i].szMsg );         break;     }     i++; } </pre>	<pre> "Payment Customer "Payment District "Payment Amount "Payment "Payment Customer "Payment missing "Payment Either "Payment missing "Payment missing "Payment missing "Payment missing "Payment missing "Payment missing "Stock Level; "Stock Level; "Stock Level "Invalid "Invalid " </pre>
--	--	---	---

```

if (m_szTextDetail)
    strcat( szTmp, m_szTextDetail );
if (m_SystemErr)
    wsprintf( szTmp+strlen(szTmp), " Error=%d", m_SystemErr );

m_szErrorText = new char[strlen(szTmp)+1];
strcpy( m_szErrorText, szTmp );
return m_szErrorText;
}

/* FUNCTION: GetKeyValue
 *
 * PURPOSE:      This function parses a http formatted string for specific key
 values.
 *
 * ARGUMENTS:   char          *pQueryString  http string from client
 browser
 *              char          *pKey          key value to look for
 *              char          *pValue       character array
 into which to place key's value
 *              int           iMax          maximum length of
 key value array.
 *              WEBERROR      err          error value to
 throw
 *
 * RETURNS:     nothing.
 *
 * ERROR:       if (the pKey value is not found) then
 *               if (err == 0)
 *                   return (empty string)
 *               else
 *                   throw CWEBCLNT_ERR(err)
 *
 * COMMENTS:    http keys are formatted either KEY=value& or KEY=value\0.
 This DLL formats
 *              TPC-C input fields in such a manner that the keys can
 be extracted in the
 *              above manner.
 */

void GetKeyValue(char **pQueryString, char *pKey, char *pValue, int iMax,
WEBERROR err)
{
    char *ptr;

    if ( !(ptr=strstr(*pQueryString, pKey)) )
        goto ErrorExit;
    ptr += strlen(pKey);
    if ( *ptr != '=' )
        goto ErrorExit;
    ptr++;

    iMax--; // one position is for terminating null

```

```

while( *ptr && *ptr != '&' && iMax)
{
    *pValue++ = *ptr++;
    iMax--;
}
*pValue = 0; // terminating null

*pQueryString = ptr;
return;

ErrorExit:
if (err != NO_ERR)
    throw new CWEBCLNT_ERR( err );
*pValue = 0; // return empty result string
}

/* FUNCTION: GetIntKeyValue
 *
 * PURPOSE:      This function parses a http formatted string for a specific
 key value.
 *
 * ARGUMENTS:   char          *pQueryString  http string from client
 browser
 *              char          *pKey          key value to look for
 *              WEBERROR      NoKeyErr     error value to throw if
 key not found
 *              WEBERROR      NotIntErr    error value to throw if
 value not numeric
 *
 * RETURNS:     integer
 *
 * ERROR:       if (the pKey value is not found) then
 *               if (NoKeyErr != NO_ERR)
 *                   throw CWEBCLNT_ERR(err)
 *               else
 *                   return 0
 *               else if (non-numeric char found) then
 *                   if (NotIntErr != NO_ERR) then
 *                       throw CWEBCLNT_ERR(err)
 *                   else
 *                       return 0
 *
 * COMMENTS:    http keys are formatted either KEY=value& or KEY=value\0.
 This DLL formats
 *              TPC-C input fields in such a manner that the keys can
 be extracted in the
 *              above manner.
 */

int GetIntKeyValue(char **pQueryString, char *pKey, WEBERROR NoKeyErr,
WEBERROR NotIntErr)
{
    char *ptr0;
    char *ptr;

```

```

if ( !(ptr=strstr(*pQueryString, pKey)) )
    goto ErrorNoKey;
ptr += strlen(pKey);
if ( *ptr != '=' )
    goto ErrorNoKey;
ptr++;

ptr0 = ptr;          // remember starting point
// scan string until a terminator (null or &) or a non-digit
while( *ptr && *ptr != '&' && isdigit(*ptr) )
    ptr++;

// make sure we stopped scanning for the right reason
if ((ptr0 == ptr) || (*ptr && *ptr != '&'))
{
    if (NotIntErr != NO_ERR)
        throw new CWEBCLNT_ERR( NoKeyErr );
    return 0;
}

*pQueryString = ptr;
return atoi(ptr0);

ErrorNoKey:
if (NoKeyErr != NO_ERR)
    throw new CWEBCLNT_ERR( NoKeyErr );
return 0;
}

/* FUNCTION: TermInit
 *
 * PURPOSE:      This function initializes the client terminal structure; it
is called when the TPCC.DLL
 *
 *               is first loaded by the inet service.
 *
 */

void TermInit(void)
{
    EnterCriticalSection(&TermCriticalSection);

    Term.iMasterSyncId   = 1;
    Term.iNumEntries     = Reg.dwMaxConnections+1;

    Term.pClientData     = NULL;
    Term.pClientData     = (PCLIENTDATA)malloc(Term.iNumEntries *
sizeof(CLIENTDATA));
    if (Term.pClientData == NULL)
    {
        LeaveCriticalSection(&TermCriticalSection);
        throw new CWEBCLNT_ERR( ERR_MEM_ALLOC_FAILED );
    }

    ZeroMemory( Term.pClientData, Term.iNumEntries * sizeof(CLIENTDATA) );

```

```

    Term.iFreeList       = Term.iNumEntries-1;
    // build free list
    // note: Term.pClientData[0].iNextFree gets set to -1, which marks it
as "in use".
    //      This is intentional, as the zero entry is used as an anchor
and never
    //      allocated as an actual terminal.
    for(int i=0; i<Term.iNumEntries; i++)
        Term.pClientData[i].iNextFree = i-1;

    LeaveCriticalSection(&TermCriticalSection);
}

/* FUNCTION: TermDeleteAll
 *
 * PURPOSE:      This function frees allocated resources associated with the
terminal structure.
 *
 * ARGUMENTS:    none
 *
 * RETURNS:      None
 *
 * COMMENTS:     This function is called only when the inet service unloads
the TPCC.DLL
 *
 */

void TermDeleteAll(void)
{
    EnterCriticalSection(&TermCriticalSection);

    for(int i=1; i<Term.iNumEntries; i++)
    {
        if (Term.pClientData[i].iNextFree == -1)
            delete Term.pClientData[i].pTxn;
    }

    Term.iFreeList       = 0;
    Term.iNumEntries     = 0;
    if ( Term.pClientData )
        free(Term.pClientData);
    Term.pClientData     = NULL;

    LeaveCriticalSection(&TermCriticalSection);
}

/* FUNCTION: TermAdd
 *
 * PURPOSE:      This function assigns a terminal id which is used to identify
a client browser.
 *
 * RETURNS:      int          assigned terminal id
 *
 */

```

```

int TermAdd(void)
{
    DWORD i;
    int iNewTerm, iTickCount;

    if (Term.iNumEntries == 0)
        return -1;

    EnterCriticalSection(&TermCriticalSection);
    if (Term.iFreeList != 0)
    {
        // position is available
        iNewTerm = Term.iFreeList;
        Term.iFreeList = Term.pClientData[iNewTerm].iNextFree;
        Term.pClientData[iNewTerm].iNextFree = -1; // indicates this
position is in use
    }
    else
    {
        // no open slots, so find the slot that hasn't been used in the
longest time and reuse it
        for(iNewTerm=1, i=1, iTickCount=0x7FFFFFFF;
i<Reg.dwMaxConnections; i++)
        {
            if (iTickCount > Term.pClientData[i].iTickCount)
            {
                iTickCount = Term.pClientData[i].iTickCount;
                iNewTerm = i;
            }
        }
        // if oldest term is less than one minute old, it probably means
that more connections
        // are being attempted than were specified as "Max Connections" at
install. In this case,
        // do not bump existing connection; instead, return error to
requestor.
        if ((GetTickCount() - iTickCount) < 60000)
        {
            LeaveCriticalSection(&TermCriticalSection);
            throw new CWEBCLNT_ERR( ERR_MAX_CONNECTIONS_EXCEEDED );
        }

        Term.pClientData[iNewTerm].iTickCount = GetTickCount();
        Term.pClientData[iNewTerm].iSyncId = Term.iMasterSyncId++;
        Term.pClientData[iNewTerm].pTxn = NULL;

        LeaveCriticalSection(&TermCriticalSection);
        return iNewTerm;
    }

/* FUNCTION: TermDelete
*
* PURPOSE: This function makes a terminal entry in the Term array
available for reuse.
*

```

```

* ARGUMENTS: int id Terminal id of
client exiting
*
*/

void TermDelete(int id)
{
    if ( id > 0 && id < Term.iNumEntries )
    {
        delete Term.pClientData[id].pTxn;

        // put onto free list
        EnterCriticalSection(&TermCriticalSection);

        Term.pClientData[id].iNextFree = Term.iFreeList;
        Term.iFreeList = id;

        LeaveCriticalSection(&TermCriticalSection);
    }
}

/* FUNCTION: MakeErrorForm
*/

void ErrorForm(EXTENSION_CONTROL_BLOCK *pECB, int iType, int iErrorNum, int
iTermId, int iSyncId, char *szErrorText, char *szBuffer )
{
    wsprintf(szBuffer,
        "<HTML><HEAD><TITLE>TPC-C Error</TITLE></HEAD><BODY>"
        "<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
        "<INPUT TYPE=\"hidden\" NAME=\"STATUSID\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"ERROR\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"FORMID\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"TERMID\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"SYNCID\" VALUE=\"%d\">"
        "<BOLD>An Error Occurred</BOLD><BR><BR>"
        "%s"
        "<BR><BR><HR>"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..NewOrder..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Payment..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Delivery..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Order-Status..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Stock-Level..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Exit..\">"
        "</FORM></BODY></HTML>"
        , iType, iErrorNum, MAIN_MENU_FORM, iTermId, iSyncId, szErrorText
    );
}

/* FUNCTION: MakeMainMenuForm
*/

void MakeMainMenuForm(int iTermId, int iSyncId, char *szForm)
{

```



```

" <PRE><font face="Courier">
New Order<BR>"
, bValid ? 0 : ERR_BAD_ITEM_ID, NEW_ORDER_FORM, iTermId,
Term.pClientData[iTermId].iSyncId);

if ( bInput )
{
c += sprintf(szForm+c, "Warehouse: %4.4d ",
Term.pClientData[iTermId].w_id );

strcpy( szForm+c,
"District: <INPUT NAME="DID*" SIZE=1>
Date:<BR>"
"Customer: <INPUT NAME="CID*" SIZE=4> Name:
Credit: %Disc:<BR>"
"Order Number: Number of Lines: W_tax:
D_tax:<BR> <BR>"
" Supp_W Item_Id Item Name Qty Stock B/G
Price Amount<BR>"
" <INPUT NAME="SP00*" SIZE=4> <INPUT NAME="IID00*"
<INPUT NAME="Qty00*" SIZE=1><BR>"
" <INPUT NAME="SP01*" SIZE=4> <INPUT NAME="IID01*"
<INPUT NAME="Qty01*" SIZE=1><BR>"
" <INPUT NAME="SP02*" SIZE=4> <INPUT NAME="IID02*"
<INPUT NAME="Qty02*" SIZE=1><BR>"
" <INPUT NAME="SP03*" SIZE=4> <INPUT NAME="IID03*"
<INPUT NAME="Qty03*" SIZE=1><BR>"
" <INPUT NAME="SP04*" SIZE=4> <INPUT NAME="IID04*"
<INPUT NAME="Qty04*" SIZE=1><BR>"
" <INPUT NAME="SP05*" SIZE=4> <INPUT NAME="IID05*"
<INPUT NAME="Qty05*" SIZE=1><BR>"
" <INPUT NAME="SP06*" SIZE=4> <INPUT NAME="IID06*"
<INPUT NAME="Qty06*" SIZE=1><BR>"
" <INPUT NAME="SP07*" SIZE=4> <INPUT NAME="IID07*"
<INPUT NAME="Qty07*" SIZE=1><BR>"
" <INPUT NAME="SP08*" SIZE=4> <INPUT NAME="IID08*"
<INPUT NAME="Qty08*" SIZE=1><BR>"
" <INPUT NAME="SP09*" SIZE=4> <INPUT NAME="IID09*"
<INPUT NAME="Qty09*" SIZE=1><BR>"
" <INPUT NAME="SP10*" SIZE=4> <INPUT NAME="IID10*"
<INPUT NAME="Qty10*" SIZE=1><BR>"
" <INPUT NAME="SP11*" SIZE=4> <INPUT NAME="IID11*"
<INPUT NAME="Qty11*" SIZE=1><BR>"
" <INPUT NAME="SP12*" SIZE=4> <INPUT NAME="IID12*"
<INPUT NAME="Qty12*" SIZE=1><BR>"
" <INPUT NAME="SP13*" SIZE=4> <INPUT NAME="IID13*"
<INPUT NAME="Qty13*" SIZE=1><BR>"
" <INPUT NAME="SP14*" SIZE=4> <INPUT NAME="IID14*"
<INPUT NAME="Qty14*" SIZE=1><BR>"
"Execution Status:
Total:<BR>"
</font></PRE><HR>"
<INPUT TYPE="submit" NAME="CMD" VALUE="Process">
<INPUT TYPE="submit" NAME="CMD" VALUE="Menu">
</FORM></HTML>"

```

```

);
}
else
{
c += sprintf(szForm+c, "Warehouse: %4.4d District: %2.2d
Date: ",
pNewOrderData->w_id,
pNewOrderData->d_id);

if ( bValid )
{
c += sprintf(szForm+c, "%2.2d-%2.2d-%4.4d
%2.2d:%2.2d:%2.2d",
pNewOrderData->o_entry_d.day,
pNewOrderData->o_entry_d.month,
pNewOrderData->o_entry_d.year,
pNewOrderData->o_entry_d.hour,
pNewOrderData->o_entry_d.minute,
pNewOrderData->o_entry_d.second);
}

c += sprintf(szForm+c, "<BR>Customer: %4.4d Name: %-16s
Credit: %-2s ",
pNewOrderData->c_id, pNewOrderData->c_last, pNewOrderData-
>c_credit);

if ( bValid )
{
c += sprintf(szForm+c,
"%Disc: %5.2f <BR>"
"Order Number: %8.8d Number of Lines: %2.2d
W_tax: %5.2f D_tax: %5.2f <BR>"
" Supp_W Item_Id Item Name
Qty Stock B/G Price Amount<BR>",
100.0*pNewOrderData->c_discount,
pNewOrderData->o_id,
pNewOrderData->o_ol_cnt,
100.0 * pNewOrderData->w_tax,
100.0 * pNewOrderData->d_tax);

for(i=0; i<pNewOrderData->o_ol_cnt; i++)
{
c += sprintf(szForm+c, " %4.4d %6.6d %-24s %2.2d
%3.3d %1.1s %6.2f %7.2f <BR>",
pNewOrderData->OL[i].ol_supply_w_id,
pNewOrderData->OL[i].ol_i_id,
pNewOrderData->OL[i].ol_i_name,
pNewOrderData->OL[i].ol_quantity,
pNewOrderData->OL[i].ol_stock,
pNewOrderData->OL[i].ol_brand_generic,
pNewOrderData->OL[i].ol_i_price,
pNewOrderData->OL[i].ol_amount );
}
}
else

```

```

    {
        c += sprintf(szForm+c,
            "%Disc:<BR>"
            "Order Number: %8.8d Number of Lines:
W_tax:      D_tax:<BR> <BR>"
            " Supp_W Item_Id Item Name          Qty Stock
B/G Price  Amount<BR>"
            , pNewOrderData->o_id);

        i = 0;
    }

    strncpy( szForm+c, szBR, (15-i)*5 );
    c += (15-i)*5;

    if ( bValid )
        c += sprintf(szForm+c, "Execution Status: Transaction
committed.          Total: $%8.2f ",
            pNewOrderData->total_amount);
    else
        c += sprintf(szForm+c, "Execution Status: Item number is not
valid.              Total:");

    strcpy(szForm+c,
        "<BR></font></PRE><HR>"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..NewOrder..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Payment..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Delivery..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Order-
Status..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Stock-
Level..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Exit..\">"
        "</FORM></HTML>"
    );
}

/* FUNCTION: MakePaymentForm
*
* COMMENTS:  The internal client buffer is created when the terminal id is
assigned and should not
*            be freed except when the client terminal id is no
longer needed.
*/

void MakePaymentForm(int iTermId, PAYMENT_DATA *pPaymentData, BOOL bInput,
char *szForm)
{
    int c;

    c = sprintf(szForm,
        "<HTML><HEAD><TITLE>TPC-C Payment</TITLE></HEAD><BODY>"
        "<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
        "<INPUT TYPE=\"hidden\" NAME=\"STATUSID\" VALUE=\"0\">"

```

```

        "<INPUT TYPE=\"hidden\" NAME=\"ERROR\" VALUE=\"0\">"
        "<INPUT TYPE=\"hidden\" NAME=\"FORMID\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"TERMINID\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"SYNCID\" VALUE=\"%d\">"
        "<PRE><font face=\"Courier\">"
        "Payment<BR>"
        "Date: "
        , PAYMENT_FORM, iTermId, Term.pClientData[iTermId].iSyncId);

    if ( !bInput )
    {
        c += sprintf(szForm+c, "%2.2d-%2.2d-%4.4d %2.2d:%2.2d:%2.2d",
            pPaymentData->h_date.day,
            pPaymentData->h_date.month,
            pPaymentData->h_date.year,
            pPaymentData->h_date.hour,
            pPaymentData->h_date.minute,
            pPaymentData->h_date.second);
    }

    if ( bInput )
    {
        c += sprintf(szForm+c,
            "<BR> <BR>Warehouse: %4.4d
            " District: <INPUT NAME=\"DID*\"
            SIZE=1><BR> <BR> <BR> <BR> <BR>"
            "Customer: <INPUT NAME=\"CID*\" SIZE=4>"
            "Cust-Warehouse: <INPUT NAME=\"CWI*\" SIZE=4> "
            "Cust-District: <INPUT NAME=\"CDI*\" SIZE=1><BR>"
            "Name: <INPUT NAME=\"CLT*\" SIZE=16>"
            "Since:<BR>"
            "
            "Credit:<BR>"
            "
            " Disc:<BR>"
            " Phone:<BR>"
            "Amount Paid: $<INPUT NAME=\"HAM*\" SIZE=7> New
Cust-Balance:<BR>"
            "Credit Limit:<BR> <BR>Cust-Data: <BR> <BR> <BR> <BR>
<BR></font></PRE><HR>"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Process\"><INPUT
TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">"
            "</BODY></FORM></HTML>"
            , Term.pClientData[iTermId].w_id);
    }
    else
    {
        c += sprintf(szForm+c,
            "<BR> <BR>Warehouse: %4.4d District:
%2.2d<BR>"
            "%-20s %-20s<BR>"
            "%-20s %-20s<BR>"
            "%-20s %-2s %5.5s-%4.4s %-20s %-2s %5.5s-%4.4s<BR>"
            <BR>"

```

```

"Customer: %4.4d Cust-Warehouse: %4.4d Cust-District:
%2.2d<BR>"
"Name: %-16s %-2s %-16s Since: %2.2d-%2.2d-%4.4d<BR>"
" %-20s Credit: %-2s<BR>"
, Term.pClientData[iTermId].w_id, pPaymentData->d_id
, pPaymentData->w_street_1, pPaymentData->d_street_1
, pPaymentData->w_street_2, pPaymentData->d_street_2
, pPaymentData->w_city, pPaymentData->w_state, pPaymentData-
>w_zip, pPaymentData->w_zip+5
, pPaymentData->d_city, pPaymentData->d_state, pPaymentData-
>d_zip, pPaymentData->d_zip+5
, pPaymentData->c_id, pPaymentData->c_w_id, pPaymentData-
>c_d_id
, pPaymentData->c_first, pPaymentData->c_middle,
pPaymentData->c_last
, pPaymentData->c_since.day, pPaymentData->c_since.month,
pPaymentData->c_since.year
, pPaymentData->c_street_1, pPaymentData->c_credit
);

c += sprintf(szForm+c,
" %-20s %%Disc: %5.2f<BR>",
pPaymentData->c_street_2, 100.0*pPaymentData->c_discount);

c += wsprintf(szForm+c,
" %-20s %-2s %5.5s-%4.4s Phone: %6.6s-%3.3s-
%3.3s-%4.4s<BR> <BR>",
pPaymentData->c_city, pPaymentData->c_state, pPaymentData-
>c_zip, pPaymentData->c_zip+5,
pPaymentData->c_phone, pPaymentData->c_phone+6, pPaymentData-
>c_phone+9, pPaymentData->c_phone+12 );

c += sprintf(szForm+c,
"Amount Paid: $%7.2f New Cust-Balance:
$%14.2f<BR>"
"Credit Limit: $%13.2f<BR> <BR>"
, pPaymentData->h_amount, pPaymentData->c_balance
, pPaymentData->c_credit_lim
);

if ( pPaymentData->c_credit[0] == 'B' && pPaymentData->c_credit[1]
== 'C' )
c += wsprintf(szForm+c,
"Cust-Data: %-50.50s<BR> %-50.50s<BR>"
%-50.50s<BR> %-50.50s<BR>",
pPaymentData->c_data, pPaymentData->c_data+50,
pPaymentData->c_data+100, pPaymentData->c_data+150 );
else
strcpy(szForm+c, "Cust-Data: <BR> <BR> <BR> <BR>");

strcat(szForm, " <BR></font></PRE><HR>"
" <INPUT TYPE=\"submit\" NAME=\"CMD\" "
VALUE=\"..NewOrder..\">"

```

```

" <INPUT TYPE=\"submit\" NAME=\"CMD\" "
VALUE=\"..Payment..\">"
" <INPUT TYPE=\"submit\" NAME=\"CMD\" "
VALUE=\"..Delivery..\">"
" <INPUT TYPE=\"submit\" NAME=\"CMD\" "
VALUE=\"..Order-Status..\">"
" <INPUT TYPE=\"submit\" NAME=\"CMD\" "
VALUE=\"..Stock-Level..\">"
" <INPUT TYPE=\"submit\" NAME=\"CMD\" "
VALUE=\"..Exit..\">"
" </BODY></FORM></HTML>");
}

/* FUNCTION: MakeOrderStatusForm
*
* COMMENTS: The internal client buffer is created when the terminal id is
* assigned and should not
* be freed except when the client terminal id is no
* longer needed.
*/

void MakeOrderStatusForm(int iTermId, ORDER_STATUS_DATA *pOrderStatusData,
BOOL bInput, char *szForm)
{
int i, c;
static char szBR[] = " <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR> <BR> <BR> <BR> <BR> <BR> <BR>";

c = wsprintf(szForm,
"<HTML><HEAD><TITLE>TPC-C Order-Status</TITLE></HEAD><BODY>"
"<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
"<INPUT TYPE=\"hidden\" NAME=\"STATUSID\" VALUE=\"0\">"
"<INPUT TYPE=\"hidden\" NAME=\"ERROR\" VALUE=\"0\">"
"<INPUT TYPE=\"hidden\" NAME=\"FORMID\" VALUE=\"%d\">"
"<INPUT TYPE=\"hidden\" NAME=\"TERMINID\" VALUE=\"%d\">"
"<INPUT TYPE=\"hidden\" NAME=\"SYNCID\" VALUE=\"%d\">"
"<PRE><font face=\"Courier\">"
Order-Status<BR>"
"Warehouse: %4.4d ",
ORDER_STATUS_FORM, iTermId, Term.pClientData[iTermId].iSyncId,
Term.pClientData[iTermId].w_id);

if ( bInput )
{
strcpy(szForm+c,
"District: <INPUT NAME=\"DID*\" SIZE=1><BR>"
"Customer: <INPUT NAME=\"CID*\" SIZE=4> Name:
<INPUT NAME=\"CLT*\" SIZE=23><BR>"
"Cust-Balance:<BR> <BR>"
"Order-Number: Entry-Date:
Carrier-Number:<BR>"
"Supply-W Item-Id Qty Amount Delivery-
Date<BR> <BR> <BR> <BR> <BR>"

```

```

" <BR> <BR>
<BR></font></PRE>"
"<HR><INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"Process\"><INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">"
"/BODY></FORM></HTML>" );
}
else
{
c += sprintf(szForm+c,
"District: %2.2d<BR>"
"Customer: %4.4d Name: %-16s %-2s %-16s<BR>",
pOrderStatusData->d_id, pOrderStatusData->c_id,
pOrderStatusData->c_first, pOrderStatusData->c_middle,
pOrderStatusData->c_last);

c += sprintf(szForm+c, "Cust-Balance: $%9.2f<BR> <BR>",
pOrderStatusData->c_balance);

c += sprintf(szForm+c,
"Order-Number: %8.8d Entry-Date: %2.2d-%2.2d-%4.4d
%2.2d:%2.2d:%2.2d Carrier-Number: %2.2d<BR>"
"Supply-W Item-Id Qty Amount Delivery-
Date<BR>",
pOrderStatusData->o_id,
pOrderStatusData->o_entry_d.day,
pOrderStatusData->o_entry_d.month,
pOrderStatusData->o_entry_d.year,
pOrderStatusData->o_entry_d.hour,
pOrderStatusData->o_entry_d.minute,
pOrderStatusData->o_entry_d.second,
pOrderStatusData->o_carrier_id);

for(i=0; i< pOrderStatusData->o_ol_cnt; i++)
{
c += sprintf(szForm+c, " %4.4d %6.6d %2.2d
%8.2f %2.2d-%2.2d-%4.4d<BR>",
pOrderStatusData->OL[i].ol_supply_w_id,
pOrderStatusData->OL[i].ol_i_id,
pOrderStatusData->OL[i].ol_quantity,
pOrderStatusData->OL[i].ol_amount,
pOrderStatusData->OL[i].ol_delivery_d.day,
pOrderStatusData->OL[i].ol_delivery_d.month,
pOrderStatusData->OL[i].ol_delivery_d.year);
}

strncpy( szForm+c, szBR, (15-i)*5 );
c += (15-i)*5;

strcpy(szForm+c,
"/font></PRE><HR><INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..NewOrder..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Payment..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Delivery..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Order-
Status..\">"

```

```

"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Stock-
Level..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Exit..\">"
"/BODY></FORM></HTML>" );
}
}
/* FUNCTION: MakeDeliveryForm
*
* COMMENTS: The internal client buffer is created when the terminal id is
assigned and should not
* be freed except when the client terminal id is no
longer needed.
*/

void MakeDeliveryForm(int iTermId, DELIVERY_DATA *pDeliveryData, BOOL
bInput, char *szForm)
{
int c;

c = sprintf(szForm,
"<HTML><HEAD><TITLE>TPC-C Delivery</TITLE></HEAD><BODY>"
"<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
"<INPUT TYPE=\"hidden\" NAME=\"STATUSID\" VALUE=\"%d\">"
"<INPUT TYPE=\"hidden\" NAME=\"ERROR\" VALUE=\"0\">"
"<INPUT TYPE=\"hidden\" NAME=\"FORMID\" VALUE=\"%d\">"
"<INPUT TYPE=\"hidden\" NAME=\"TERMINID\" VALUE=\"%d\">"
"<INPUT TYPE=\"hidden\" NAME=\"SYNCID\" VALUE=\"%d\">"
"<PRE><font face=\"Courier\">"
Delivery<BR>"
"Warehouse: %4.4d<BR> <BR>",
(!bInput && (pDeliveryData->exec_status_code != eOK)) ?
ERR_TYPE_DELIVERY_POST : 0,
DELIVERY_FORM, iTermId, Term.pClientData[iTermId].iSyncId,
Term.pClientData[iTermId].w_id);

if ( bInput )
{
strcpy( szForm+c,
"Carrier Number: <INPUT NAME=\"OCD*\" SIZE=1><BR> <BR>"
"Execution Status: <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>"
" <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> </font></PRE><HR>"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Process\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">"
"/BODY></FORM></HTML>" );
}
else
{
sprintf( szForm+c,
"Carrier Number: %2.2d<BR> <BR>"
"Execution Status: %s <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>"
" <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> </font></PRE>"
"<HR><INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..NewOrder..\">"

```

```

        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Payment..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Delivery..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Order-
Status..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Stock-
Level..\">"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Exit..\">"
        "</BODY></FORM></HTML>"
        , pDeliveryData->o_carrier_id,
        (pDeliveryData->exec_status_code == eOK) ? "Delivery has been
queued." : "Delivery Post Failed "
    );
}
}

```

```

/* FUNCTION: ProcessNewOrderForm
 *
 * PURPOSE: This function gets and validates the input data from the new
order form
 *
 * filling in the required input variables. it then calls the
SQLNewOrder
 *
 * transaction, constructs the output form and writes it back to
client
 *
 * browser.
 */

```

```

void ProcessNewOrderForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    PNEW_ORDER_DATA pNewOrder;

    pNewOrder = Term.pClientData[iTermId].pTxn->BuffAddr_NewOrder();

    ZeroMemory(pNewOrder, sizeof(NEW_ORDER_DATA));
    pNewOrder->w_id = Term.pClientData[iTermId].w_id;
    GetNewOrderData(pECB->lpszQueryString, pNewOrder);

    Term.pClientData[iTermId].pTxn->NewOrder();

    pNewOrder = Term.pClientData[iTermId].pTxn->BuffAddr_NewOrder();
    MakeNewOrderForm(iTermId, pNewOrder, OUTPUT_FORM, szBuffer );
}

```

```

/* FUNCTION: void ProcessPaymentForm
 *
 * PURPOSE: This function gets and validates the input data from the
payment form
 *
 * filling in the required input variables. It then calls the
SQLPayment
 *
 * transaction, constructs the output form and writes it back to
client
 *
 * browser.
 *

```

```

 * ARGUMENTS: EXTENSION_CONTROL_BLOCK *pECBpassed in structure pointer
from inetsrv.
 *
 * int iTermId client
browser terminal id
 *
 */

void ProcessPaymentForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    PPAYMENT_DATA pPayment;

    pPayment = Term.pClientData[iTermId].pTxn->BuffAddr_Payment();
    ZeroMemory(pPayment, sizeof(PAYMENT_DATA));
    pPayment->w_id = Term.pClientData[iTermId].w_id;
    GetPaymentData(pECB->lpszQueryString, pPayment);

    Term.pClientData[iTermId].pTxn->Payment();

    pPayment = Term.pClientData[iTermId].pTxn->BuffAddr_Payment();
    MakePaymentForm(iTermId, pPayment, OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessOrderStatusForm
 *
 * PURPOSE: This function gets and validates the input data from the
Order Status
 *
 * form filling in the required input variables. It then calls
the
 *
 * SQLOrderStatus transaction, constructs the output form and
writes it
 *
 * back to client browser.
 *
 * ARGUMENTS: EXTENSION_CONTROL_BLOCK *pECBpassed in structure pointer
from inetsrv.
 *
 * int iTermId client
browser terminal id
 *
 */

void ProcessOrderStatusForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    PORDER_STATUS_DATA pOrderStatus;

    pOrderStatus = Term.pClientData[iTermId].pTxn->BuffAddr_OrderStatus();
    ZeroMemory(pOrderStatus, sizeof(ORDER_STATUS_DATA));
    pOrderStatus->w_id = Term.pClientData[iTermId].w_id;
    GetOrderStatusData(pECB->lpszQueryString, pOrderStatus);

    Term.pClientData[iTermId].pTxn->OrderStatus();

    pOrderStatus = Term.pClientData[iTermId].pTxn->BuffAddr_OrderStatus();
    MakeOrderStatusForm(iTermId, pOrderStatus, OUTPUT_FORM, szBuffer);
}

```

```

/* FUNCTION: ProcessDeliveryForm
*
* PURPOSE:      This function gets and validates the input data from the
delivery form
*              filling in the required input variables. It then calls the
PostDeliveryInfo
*              Api, The client is then informed that the transaction has
been posted.
*
* ARGUMENTS:   EXTENSION_CONTROL_BLOCK *pECBpassed in structure pointer
from inetsrv.
*              int iTermId client
browser terminal id
*/

void ProcessDeliveryForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    char *ptr = pECB->lpszQueryString;

    PDELIVERY_DATA pDelivery;

    pDelivery = Term.pClientData[iTermId].pTxn->BuffAddr_Delivery();
    ZeroMemory(pDelivery, sizeof(DELIVERY_DATA));
    pDelivery->w_id = Term.pClientData[iTermId].w_id;

    pDelivery->o_carrier_id = GetIntKeyValue(&ptr, "OCD*",
ERR_DELIVERY_MISSING_OCD_KEY, ERR_DELIVERY_CARRIER_INVALID);
    if ( pDelivery->o_carrier_id > 10 || pDelivery->o_carrier_id < 1 )
        throw new CWEBCLNT_ERR( ERR_DELIVERY_CARRIER_ID_RANGE );

    if (dwNumDeliveryThreads)
    {
        //post delivery info
        if ( PostDeliveryInfo(pDelivery->w_id, pDelivery->o_carrier_id) )
            pDelivery->exec_status_code = eDeliveryFailed;
        else
            pDelivery->exec_status_code = eOK;
    }
    else // delivery is done synchronously if no delivery threads
configured
        Term.pClientData[iTermId].pTxn->Delivery();

    pDelivery = Term.pClientData[iTermId].pTxn->BuffAddr_Delivery();
    MakeDeliveryForm(iTermId, pDelivery, OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessStockLevelForm
*
* PURPOSE:      This function gets and validates the input data from the
Stock Level
*              form filling in the required input variables. It then calls
the

```

```

*              SQLStockLevel transaction, constructs the output form and
writes it
*              back to client browser.
*
* ARGUMENTS:   EXTENSION_CONTROL_BLOCK *pECBpassed in structure pointer
from inetsrv.
*              int iTermId client
browser terminal id
*/

void ProcessStockLevelForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    char *ptr = pECB->lpszQueryString;

    PSTOCK_LEVEL_DATA pStockLevel;

    pStockLevel = Term.pClientData[iTermId].pTxn->BuffAddr_StockLevel();
    ZeroMemory( pStockLevel, sizeof(STOCK_LEVEL_DATA) );

    pStockLevel->w_id = Term.pClientData[iTermId].w_id;
    pStockLevel->d_id = Term.pClientData[iTermId].d_id;

    pStockLevel->threshold = GetIntKeyValue(&ptr, "TT*",
ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY, ERR_STOCKLEVEL_THRESHOLD_INVALID);
    if ( pStockLevel->threshold >= 100 || pStockLevel->threshold < 0 )
        throw new CWEBCLNT_ERR( ERR_STOCKLEVEL_THRESHOLD_RANGE );

    Term.pClientData[iTermId].pTxn->StockLevel();

    pStockLevel = Term.pClientData[iTermId].pTxn->BuffAddr_StockLevel();
    MakeStockLevelForm(iTermId, pStockLevel, OUTPUT_FORM, szBuffer);
}

/* FUNCTION: GetNewOrderData
*
* PURPOSE:      This function extracts and validates the new order form data
from an http command string.
*
* ARGUMENTS:   LPSTR lpszQueryString client browser http
command string
*              NEW_ORDER_DATA *pNewOrderData pointer to new
order data structure
*/

void GetNewOrderData(LPSTR lpszQueryString, NEW_ORDER_DATA *pNewOrderData)
{
    char szTmp[26];
    int i;
    short items;
    int ol_i_id, ol_quantity;
    char *ptr = lpszQueryString;

```

```

static char szSP[MAX_OL_NEW_ORDER_ITEMS][6] =
{ "SP00*", "SP01*", "SP02*", "SP03*", "SP04*",
  "SP05*", "SP06*", "SP07*", "SP08*", "SP09*",
  "SP10*", "SP11*", "SP12*", "SP13*", "SP14*" };
static char szIID[MAX_OL_NEW_ORDER_ITEMS][7] =
{ "IID00*", "IID01*", "IID02*", "IID03*", "IID04*",
  "IID05*", "IID06*", "IID07*", "IID08*", "IID09*",
  "IID10*", "IID11*", "IID12*", "IID13*", "IID14*" };
static char szQty[MAX_OL_NEW_ORDER_ITEMS][7] =
{ "Qty00*", "Qty01*", "Qty02*", "Qty03*", "Qty04*",
  "Qty05*", "Qty06*", "Qty07*", "Qty08*", "Qty09*",
  "Qty10*", "Qty11*", "Qty12*", "Qty13*", "Qty14*" };

pNewOrderData->d_id = GetIntKeyValue(&ptr, "DID*",
ERR_NEWORDER_FORM_MISSING_DID, ERR_NEWORDER_DISTRICT_INVALID);
pNewOrderData->c_id = GetIntKeyValue(&ptr, "CID*",
ERR_NEWORDER_CUSTOMER_KEY, ERR_NEWORDER_CUSTOMER_INVALID);

for(i=0, items=0; i<MAX_OL_NEW_ORDER_ITEMS; i++)
{
    GetKeyValue(&ptr, szSP[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_SUPPW_KEY);
    if ( szTmp[0] )
    {
        if ( !IsNumeric(szTmp) )
            throw new CWEBCLNT_ERR( ERR_NEWORDER_SUPPW_INVALID );
        pNewOrderData->OL[items].ol_supply_w_id = (short)atoi(szTmp);

        ol_i_id = pNewOrderData->OL[items].ol_i_id =
            GetIntKeyValue(&ptr, szIID[i],
ERR_NEWORDER_MISSING_IID_KEY, ERR_NEWORDER_ITEMID_INVALID);
        if ( ol_i_id > 999999 || ol_i_id < 1 )
            throw new CWEBCLNT_ERR( ERR_NEWORDER_ITEMID_RANGE );

        ol_quantity = pNewOrderData->OL[items].ol_quantity =
            GetIntKeyValue(&ptr, szQty[i],
ERR_NEWORDER_MISSING_QTY_KEY, ERR_NEWORDER_QTY_INVALID);
        if ( ol_quantity > 99 || ol_quantity < 1 )
            throw new CWEBCLNT_ERR( ERR_NEWORDER_QTY_RANGE );

        items++;
    }
    else
    { // nothing entered for supply warehouse, so item id and qty
must also be blank
        GetKeyValue(&ptr, szIID[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_IID_KEY);
        if ( szTmp[0] )
            throw new CWEBCLNT_ERR(
ERR_NEWORDER_ITEMID_WITHOUT_SUPPW );

        GetKeyValue(&ptr, szQty[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_QTY_KEY);
        if ( szTmp[0] )

```

```

        throw new CWEBCLNT_ERR( ERR_NEWORDER_QTY_WITHOUT_SUPPW
);
    }
}
if ( items == 0 )
    throw new CWEBCLNT_ERR( ERR_NEWORDER_NOITEMS_ENTERED );

pNewOrderData->o_ol_cnt = items;
}

/* FUNCTION: GetPaymentData
*
* PURPOSE: This function extracts and validates the payment form data
from an http command string.
*
* ARGUMENTS: LPSTR lpszQueryString client browser http
command string
*
* PAYMENT_DATA *pPaymentData pointer to payment
data structure
*/

void GetPaymentData(LPSTR lpszQueryString, PAYMENT_DATA *pPaymentData)
{
    char szTmp[26];
    char *ptr = lpszQueryString;
    BOOL bCustIdBlank;

    pPaymentData->d_id = GetIntKeyValue(&ptr, "DID*",
ERR_PAYMENT_MISSING_DID_KEY, ERR_PAYMENT_DISTRICT_INVALID);

    GetKeyValue(&ptr, "CID*", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_CID_KEY);
    if ( szTmp[0] == 0 )
    {
        bCustIdBlank = TRUE;
        pPaymentData->c_id = 0;
    }
    else
    { // parse customer id and verify that last name was NOT entered
bCustIdBlank = FALSE;
        if ( !IsNumeric(szTmp) )
            throw new CWEBCLNT_ERR( ERR_PAYMENT_CUSTOMER_INVALID );
        pPaymentData->c_id = atoi(szTmp);
    }

    pPaymentData->c_w_id = GetIntKeyValue(&ptr, "CWI*",
ERR_PAYMENT_MISSING_CWI_KEY, ERR_PAYMENT_CWI_INVALID);
    pPaymentData->c_d_id = GetIntKeyValue(&ptr, "CDI*",
ERR_PAYMENT_MISSING_CDI_KEY, ERR_PAYMENT_CDI_INVALID);

    if ( bCustIdBlank )
    { // customer id is blank, so last name must be entered
        GetKeyValue(&ptr, "CLT*", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_CLT_KEY);
        if ( szTmp[0] == 0 )

```

```

        throw new CWEBCLNT_ERR( ERR_PAYMENT_MISSING_CID_CLT );

        _strupr( szTmp );
        if ( strlen(pPaymentData->c_last) > LAST_NAME_LEN )
            throw new CWEBCLNT_ERR( ERR_PAYMENT_LAST_NAME_TO_LONG );
        strcpy(pPaymentData->c_last, szTmp);
    }
    else
    {
        // parse customer id and verify that last name was NOT entered
        GetKeyValue(&ptr, "CLT*", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_CLT_KEY);
        if ( szTmp[0] != 0 )
            throw new CWEBCLNT_ERR( ERR_PAYMENT_CID_AND_CLT );
    }

    GetKeyValue(&ptr, "HAM*", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_HAM_KEY);
    if (!IsDecimal(szTmp))
        throw new CWEBCLNT_ERR( ERR_PAYMENT_HAM_INVALID );
    pPaymentData->h_amount = atof(szTmp);
    if ( pPaymentData->h_amount >= 10000.00 || pPaymentData->h_amount < 0 )
        throw new CWEBCLNT_ERR( ERR_PAYMENT_HAM_RANGE );
}

/* FUNCTION: GetOrderStatusData
 *
 * PURPOSE:      This function extracts and validates the payment form data
from an http command string.
 *
 */
void GetOrderStatusData(LPSTR lpszQueryString, ORDER_STATUS_DATA
*pOrderStatusData)
{
    char szTmp[26];
    char *ptr = lpszQueryString;

    pOrderStatusData->d_id = GetIntKeyValue(&ptr, "DID*",
ERR_ORDERSTATUS_MISSING_DID_KEY, ERR_ORDERSTATUS_DID_INVALID);

    GetKeyValue(&ptr, "CID*", szTmp, sizeof(szTmp),
ERR_ORDERSTATUS_MISSING_CID_KEY);
    if ( szTmp[0] == 0 )
    {
        // customer id is blank, so last name must be entered
        pOrderStatusData->c_id = 0;
        GetKeyValue(&ptr, "CLT*", szTmp, sizeof(szTmp),
ERR_ORDERSTATUS_MISSING_CLT_KEY);
        if ( szTmp[0] == 0 )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_MISSING_CID_CLT );

        _strupr( szTmp );
        if ( strlen(pOrderStatusData->c_last) > LAST_NAME_LEN )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_CLT_RANGE );
        strcpy(pOrderStatusData->c_last, szTmp);
    }
    else

```

```

    {
        // parse customer id and verify that last name was NOT entered
        if ( !IsNumeric(szTmp) )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_CID_INVALID );
        pOrderStatusData->c_id = atoi(szTmp);
        GetKeyValue(&ptr, "CLT*", szTmp, sizeof(szTmp),
ERR_ORDERSTATUS_MISSING_CLT_KEY);
        if ( szTmp[0] != 0 )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_CID_AND_CLT );
    }
}

/* FUNCTION: BOOL IsNumeric(char *ptr)
 *
 * PURPOSE:      This function determines if a string is numeric. It fails if
any characters other
 *               than numeric and null terminator are present.
 *
 * ARGUMENTS:   char          *ptr pointer to string to check.
 *
 * RETURNS:     BOOL FALSE if string is not all numeric
 *               TRUE  if string contains only numeric
characters i.e. '0' - '9'
 */
BOOL IsNumeric(char *ptr)
{
    if ( *ptr == 0 )
        return FALSE;

    while( *ptr && isdigit(*ptr) )
        ptr++;
    return ( !*ptr );
}

/* FUNCTION: BOOL IsDecimal(char *ptr)
 *
 * PURPOSE:      This function determines if a string is a non-negative
decimal value.
 *               It fails if any characters other than a series of numbers
followed by
 *               a decimal point, another series of numbers, and a null
terminator are present.
 *
 * ARGUMENTS:   char          *ptr pointer to string to check.
 *
 * RETURNS:     BOOL FALSE if string is not a valid non-negative decimal
value
 *               TRUE  if string is OK
 */
BOOL IsDecimal(char *ptr)
{
    char *dotptr;
    BOOL bValid;

```

```

if ( *ptr == 0 )
    return FALSE;

// find decimal point
dotptr = strchr( ptr, '.' );
if (dotptr == NULL)
    // no decimal point, so just check for numeric
    return IsNumeric(ptr);
*dotptr = 0; // temporarily replace decimal with a terminator

if ( *ptr != 0 )
    bValid = IsNumeric(ptr);
// string starts with decimal point
else if (*(dotptr+1) == 0)
    return FALSE; // nothing but a decimal point is bad
else
    bValid = TRUE;

if (*(dotptr+1) != 0)
    // check text after decimal point
    bValid &= IsNumeric(dotptr+1);

*dotptr = '.'; // replace decimal point
return bValid;
}

```

```

//{{NO_DEPENDENCIES}}
// Microsoft Developer Studio generated include file.
// Used by tpcc.rc
//
#define IDD_DIALOG1                101

// Next default values for new objects
//
#ifdef APSTUDIO_INVOKED
#ifndef APSTUDIO_READONLY_SYMBOLS
#define _APS_NEXT_RESOURCE_VALUE    102
#define _APS_NEXT_COMMAND_VALUE    40001
#define _APS_NEXT_CONTROL_VALUE    1000
#define _APS_NEXT_SYMED_VALUE      101
#endif
#endif

```

```

/* FILE:      READREGISTRY.CPP
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not yet audited
 *
 * PURPOSE:   Implementation for TPC-C Tuxedo class.
 * Contact:   Charles Levine (clevine@microsoft.com)
 *
 * Change history:

```

```

*           4.20.000 - first version
*/

/* FUNCTION: ReadTPCCRegistrySettings
 *
 * PURPOSE:   This function reads the NT registry for startup parameters.
There parameters are
 *           under the TPCC key.
 *
 * RETURNS FALSE = no errors
 *           TRUE  = error reading registry
 */
BOOL ReadTPCCRegistrySettings( TPCCREGISTRYDATA *pReg )
{
    HKEY hKey;
    DWORD size;
    DWORD type;
    DWORD dwTmp;
    char szTmp[256];

    if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE, "SOFTWARE\\Microsoft\\TPCC", 0,
KEY_READ, &hKey) != ERROR_SUCCESS )
        return TRUE;

    // determine database protocol to use; may be either ODBC or DBLIB
    pReg->eDB_Protocol = Unspecified;
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "DB_Protocol", 0, &type, (BYTE *)&szTmp,
&size) == ERROR_SUCCESS )
    {
        if ( !strcmp(szTmp, szDBNames[ODBC]) )
            pReg->eDB_Protocol = ODBC;
        else if ( !strcmp(szTmp, szDBNames[DBLIB]) )
            pReg->eDB_Protocol = DBLIB;
    }

    pReg->eTxnMon = None;
    // determine txn monitor to use; may be either TUXEDO, or blank
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "TxnMonitor", 0, &type, (BYTE *)&szTmp,
&size) == ERROR_SUCCESS )
    {
        if ( !strcmp(szTmp, szTxnMonNames[TUXEDO]) )
            pReg->eTxnMon = TUXEDO;
        else if ( !strcmp(szTmp, szTxnMonNames[ENCINA]) )
            pReg->eTxnMon = ENCINA;
        else if ( !strcmp(szTmp, szTxnMonNames[COM]) )
            pReg->eTxnMon = COM;
    }

    pReg->bCOM_SinglePool = FALSE;
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "COM_SinglePool", 0, &type, (BYTE *)&szTmp,
&size) == ERROR_SUCCESS )

```

```

{
    if ( !stricmp(szTmp, "YES") )
        pReg->bCOM_SinglePool = TRUE;
}

pReg->dwMaxConnections = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey, "MaxConnections", 0, &type,
(LPBYTE)&dwTmp, &size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwMaxConnections = dwTmp;

pReg->dwMaxPendingDeliveries = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey, "MaxPendingDeliveries", 0, &type,
(LPBYTE)&dwTmp, &size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwMaxPendingDeliveries = dwTmp;

pReg->dwNumberOfDeliveryThreads = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey, "NumberOfDeliveryThreads", 0, &type,
(LPBYTE)&dwTmp, &size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwNumberOfDeliveryThreads = dwTmp;

size = sizeof( pReg->szPath );
if ( RegQueryValueEx(hKey, "Path", 0, &type, (BYTE *)&pReg->szPath,
&size) != ERROR_SUCCESS )
    pReg->szPath[0] = 0;

size = sizeof( pReg->szDbServer );
if ( RegQueryValueEx(hKey, "DbServer", 0, &type, (BYTE *)&pReg-
>szDbServer, &size) != ERROR_SUCCESS )
    pReg->szDbServer[0] = 0;

size = sizeof( pReg->szDbName );
if ( RegQueryValueEx(hKey, "DbName", 0, &type, (BYTE *)&pReg->szDbName,
&size) != ERROR_SUCCESS )
    pReg->szDbName[0] = 0;

size = sizeof( pReg->szDbUser );
if ( RegQueryValueEx(hKey, "DbUser", 0, &type, (BYTE *)&pReg->szDbUser,
&size) != ERROR_SUCCESS )
    pReg->szDbUser[0] = 0;

size = sizeof( pReg->szDbPassword );
if ( RegQueryValueEx(hKey, "DbPassword", 0, &type, (BYTE *)&pReg-
>szDbPassword, &size) != ERROR_SUCCESS )
    pReg->szDbPassword[0] = 0;

RegCloseKey(hKey);

return FALSE;
}

```

```

/* FILE:      ReadRegistry.h
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not audited
 *
 * PURPOSE:   Header for registry related code.
 *
 * Change history:
 *           4.20.000 - first version
 */

enum DBPROTOCOL { Unspecified, ODBC, DBLIB };
const char *szDBNames[] = { "Unspecified", "ODBC", "DBLIB" };

enum TXNMON { None, TUXEDO, ENCINA, COM };
const char *szTxnMonNames[] = { "NONE", "TUXEDO", "ENCINA", "COM" };

//This structure defines the data necessary to keep distinct for each
terminal or client connection.
typedef struct _TPCCREGISTRYDATA
{
    enum DBPROTOCOL eDB_Protocol;
    enum TXNMON eTxnMon;
    BOOL bCOM_SinglePool;
    DWORD dwMaxConnections;
    DWORD dwMaxPendingDeliveries;
    DWORD dwNumberOfDeliveryThreads;
    char szPath[128];
    char szDbServer[32];
    char szDbName[32];
    char szDbUser[32];
    char szDbPassword[32];
} TPCCREGISTRYDATA, *PTPCCREGISTRYDATA;

BOOL ReadTPCCRegistrySettings( TPCCREGISTRYDATA *pReg );

/* FILE:      ERROR.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE:   Header file for error exception classes.
 *
 * Change history:
 *           4.20.000 - updated rev number to match kit
 *           4.21.000 - fixed bug: ~CBaseErr needed to be declared virtual
 */

#pragma once

```

```

#ifndef _INC_STRING
#include <string.h>
#endif

const int m_szMsg_size = 512;
const int m_szApp_size = 64;
const int m_szLoc_size = 64;

//error message structure used in ErrorText routines
typedef struct _SERRORMSG
{
    int          iError;          //error id of message
    char szMsg[256];             //message to sent to browser
} SERRORMSG;

#define ERR_FATAL_LEVEL          1
#define ERR_WARNING_LEVEL       2
#define ERR_INFORMATION_LEVEL   3

#define ERR_TYPE_LOGIC           -1      //logic
error in program; internal error
#define ERR_SUCCESS              0
//success (a non-error error)
#define ERR_BAD_ITEM_ID         1
//expected abort record in txnRecord
#define ERR_TYPE_DELIVERY_POST   2      //expected
delivery post failed
#define ERR_TYPE_WEBDLL         3      //tpcc
web generated error
#define ERR_TYPE_SQL            4      //sql
server generated error
#define ERR_TYPE_DBLIB          5      //dblib
generated error
#define ERR_TYPE_ODBC           6      //odbc
generated error
#define ERR_TYPE_SOCKET         7      //error
on communication socket client rte only
#define ERR_TYPE_DEADLOCK       8      //dblib and
odbc only deadlock condition
#define ERR_TYPE_COM            9      //error from
COM call
#define ERR_TYPE_TUXEDO         10     //tuxedo
error
#define ERR_TYPE_OS             11
//operating system error
#define ERR_TYPE_MEMORY         12     //memory
allocation error
#define ERR_TYPE_TPCC_ODBC      13     //error from
tpcc odbc txn module
#define ERR_TYPE_TPCC_DBLIB     14     //error
from tpcc dblib txn module
#define ERR_TYPE_DELISRV        15     //delivery
server error

```

```

#define ERR_TYPE_TXNLOG         16     //txn
log error
#define ERR_TYPE_BCCONN        17
//Benchcraft connection class
#define ERR_TYPE_TPCC_CONN     18     //Benchcraft
connection class
#define ERR_TYPE_ENCINA        19     //Encina
error
#define ERR_TYPE_COMPONENT     20     //error from
COM component
#define ERR_TYPE_RTE           21     //Benchcraft
rte
#define ERR_TYPE_AUTOMATION    22
//Benchcraft automation errors

class CBaseErr
{
public:
    char *m_szApp;
    char *m_szMsg;
    char *m_szLoc; // code location where the error occurred
    int m_idMsg;

    CBaseErr(void)
    {
        m_idMsg = 0;
        m_szMsg = new char[m_szMsg_size];
        m_szApp = new char[m_szApp_size];
        m_szLoc = NULL;

        m_szMsg[0] = 0;
        m_szApp[0] = 0;

        GetModuleFileName(GetModuleHandle(NULL), m_szApp, m_szApp_size);
    }

    virtual ~CBaseErr(void)
    {
        if (m_szMsg)
            delete [] m_szMsg;
        if (m_szApp)
            delete [] m_szApp;
        if (m_szLoc)
            delete [] m_szLoc;
    };

    CBaseErr(int idMsg)
    {
        m_idMsg = idMsg;
        m_szApp = new char[m_szApp_size];
        m_szMsg = new char[m_szMsg_size];
        m_szLoc = NULL;

        GetModuleFileName(GetModuleHandle(NULL), m_szApp, m_szApp_size);
    }
};

```

```

        LoadString(GetModuleHandle(NULL), idMsg, m_szMsg, m_szMsg_size);
    }

CBaseErr(LPCTSTR szMsg)
{
    m_idMsg        = 0;
    m_szApp        = new char[m_szApp_size];
    m_szMsg        = new char[m_szMsg_size];
    m_szLoc        = NULL;

    GetModuleFileName(GetModuleHandle(NULL), m_szApp, m_szApp_size);
    strcpy(m_szMsg, szMsg);
}

void SetError(char *szMsg, LPCTSTR szLocation)
{
    if (szMsg != NULL)
        strcpy(m_szMsg, szMsg);
    else
        m_szMsg[0] = 0;

    if (szLocation != NULL)
    {
        delete [] m_szLoc;
        m_szLoc = new char[strlen(szLocation)+1];
        strcpy(m_szLoc, szLocation);
    }
    else
    {
        delete [] m_szLoc;
        m_szLoc = NULL;
    }
}

virtual void Draw(HWND hwnd, LPCTSTR szStr = NULL)
{
    int          j;
    char szTmp[512];

    if (szStr)
        j = wsprintf(szTmp, "%s\n", szStr);
    if (m_szLoc)
        j += wsprintf(szTmp+j, "Location=%s\n", m_szLoc);
    if (m_szMsg)
        j += wsprintf(szTmp+j, "%s\n", m_szMsg);

    ::MessageBox(hwnd, szTmp, m_szApp, MB_OK);
}

char *GetApp(void) { return m_szApp; }
char *GetMsg(void) { return m_szMsg; }
char *GetLocation(void) { return m_szLoc; }

virtual int ErrorType() = 0;    // a value which distinguishes the kind
of error that occurred

```

```

        virtual int ErrorNum() = 0;    // an error value specific to the
error type
        virtual char *ErrorText() = 0; // a string (i.e., human readable)
representation of the error
};

class CSocketErr : public CBaseErr
{
public:
    enum Action
    {
        eNone,
        eSend,
        eSocket,
        eConnect
    };

    CSocketErr(Action eAction, LPCTSTR szLocation);
    CSocketErr(int iError) { m_errId = iError; };
    int          m_errId;
    Action       m_eAction;

    int ErrorType() { return ERR_TYPE_SOCKET; };
    int ErrorNum() { return m_errId; };
    char *ErrorText(void);
};

class CSystemErr : public CBaseErr
{
public:
    enum Action
    {
        eNone,
        eTransactNamedPipe,
        eWaitNamedPipe,
        eSetNamedPipeHandleState,
        eCreateFile,
        eCreateProcess,
        eCallNamedPipe,
        eCreateEvent,
        eCreateThread,
        eVirtualAlloc,
        eReadFile,
        eWriteFile,
        eMapViewOfFile,
        eCreateFileMapping,
        eInitializeSecurityDescriptor,
        eSetSecurityDescriptorDacl,
        eCreateNamedPipe,
        eConnectNamedPipe,
        eWaitForSingleObject,
        eRegOpenKeyEx,
        eRegQueryValueEx,
    };
};

```

```

CSystemErr(Action eAction, LPCTSTR szLocation);

void Draw(HWND hwnd, LPCTSTR szStr = NULL);

int      m_errId;
Action   m_eAction;

int ErrorType() { return ERR_TYPE_OS;}
int ErrorNum() { return m_errId;}
char *ErrorText() { return m_szMsg; }
};

class CMemoryErr : public CBaseErr
{
public:
    CMemoryErr(void);

    int ErrorType() { return ERR_TYPE_MEMORY;}
    int ErrorNum() { return 0;}
    char *ErrorText() { return "Insufficient Memory to continue.";}
};

/* FILE:      TRANS.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE:   Header file for TPC-C structure templates.
 *
 * Change history:
 *           4.20.000 - updated rev number to match kit
 */
#pragma once

// String length constants
#define SERVER_NAME_LEN      20
#define DATABASE_NAME_LEN   20
#define USER_NAME_LEN       20
#define PASSWORD_LEN        20
#define TABLE_NAME_LEN    20
#define I_DATA_LEN          50
#define I_NAME_LEN          24
#define BRAND_LEN           1
#define LAST_NAME_LEN       16
#define W_NAME_LEN          10
#define ADDRESS_LEN         20
#define STATE_LEN           2
#define ZIP_LEN              9
#define S_DIST_LEN          24
#define S_DATA_LEN          50
#define D_NAME_LEN          10

```

```

#define FIRST_NAME_LEN      16
#define MIDDLE_NAME_LEN    2
#define PHONE_LEN           16
#define DATETIME_LEN       30
#define CREDIT_LEN         2
#define C_DATA_LEN         250
#define H_DATA_LEN         24
#define DIST_INFO_LEN      24
#define MAX_OL_NEW_ORDER_ITEMS 15
#define MAX_OL_ORDER_STATUS_ITEMS 15
#define STATUS_LEN         25
#define OL_DIST_INFO_LEN   24

// TIMESTAMP_STRUCT is provided by the ODBC header file sqltypes.h, but is
not available
// when compiling with dblink, so redefined here. Note: we are using the
symbol "__SQLTYPES"
// (declared in sqltypes.h) as a way to determine if TIMESTAMP_STRUCT has
been declared.
#ifndef __SQLTYPES
typedef struct
{
    short          /* SQLSMALLINT */    year;
    unsigned short /* SQLUSMALLINT */   month;
    unsigned short /* SQLUSMALLINT */   day;
    unsigned short /* SQLUSMALLINT */   hour;
    unsigned short /* SQLUSMALLINT */   minute;
    unsigned short /* SQLUSMALLINT */   second;
    unsigned long  /* SQLUINTEGER */    fraction;
} TIMESTAMP_STRUCT;
#endif

// possible values for exec_status_code after transaction completes
enum EXEC_STATUS
{
    eOK,           // 0 "Transaction committed."
    eInvalidItem, // 1 "Item number is not valid."
    eDeliveryFailed // 2 "Delivery Post Failed."
};

// transaction structures
typedef struct
{
    // input params
    short          ol_supply_w_id;
    long           ol_i_id;
    short          ol_quantity;

    // output params
    char           ol_i_name[I_NAME_LEN+1];
    char           ol_brand_generic[BRAND_LEN+1];
    double         ol_i_price;
    double         ol_amount;
    short          ol_stock;
} OL_NEW_ORDER_DATA;

```

```

typedef struct
{
    // input params
    short      w_id;
    short      d_id;
    long       c_id;
    short      o_ol_cnt;

    // output params
    EXEC_STATUS      exec_status_code;
    char             c_last[LAST_NAME_LEN+1];
    char             c_credit[CREDIT_LEN+1];
    double           c_discount;
    double           w_tax;
    double           d_tax;
    long            o_id;
    short           o_commit_flag;
    TIMESTAMP_STRUCT o_entry_d;
    short           o_all_local;
    double          total_amount;
    OL_NEW_ORDER_DATA OL[MAX_OL_NEW_ORDER_ITEMS];
} NEW_ORDER_DATA, *PNEW_ORDER_DATA;

typedef struct
{
    // input params
    short      w_id;
    short      d_id;
    long       c_id;
    short      c_d_id;
    short      c_w_id;
    double     h_amount;
    char       c_last[LAST_NAME_LEN+1];

    // output params
    EXEC_STATUS      exec_status_code;
    TIMESTAMP_STRUCT h_date;
    char             w_street_1[ADDRESS_LEN+1];
    char             w_street_2[ADDRESS_LEN+1];
    char             w_city[ADDRESS_LEN+1];
    char             w_state[STATE_LEN+1];
    char             w_zip[ZIP_LEN+1];
    char             d_street_1[ADDRESS_LEN+1];
    char             d_street_2[ADDRESS_LEN+1];
    char             d_city[ADDRESS_LEN+1];
    char             d_state[STATE_LEN+1];
    char             d_zip[ZIP_LEN+1];
    char             c_first[FIRST_NAME_LEN+1];
    char             c_middle[MIDDLE_NAME_LEN + 1];
    char             c_street_1[ADDRESS_LEN+1];
    char             c_street_2[ADDRESS_LEN+1];
    char             c_city[ADDRESS_LEN+1];
    char             c_state[STATE_LEN+1];
    char             c_zip[ZIP_LEN+1];
    char             c_phone[PHONE_LEN+1];
}

```

```

TIMESTAMP_STRUCT      c_since;
char                  c_credit[CREDIT_LEN+1];
double                c_credit_lim;
double                c_discount;
double                c_balance;
char                  c_data[200+1];
} PAYMENT_DATA, *PPAYMENT_DATA;

typedef struct
{
    long            ol_i_id;
    short           ol_supply_w_id;
    short           ol_quantity;
    double          ol_amount;
    TIMESTAMP_STRUCT ol_delivery_d;
} OL_ORDER_STATUS_DATA;

typedef struct
{
    // input params
    short      w_id;
    short      d_id;
    long       c_id;
    char       c_last[LAST_NAME_LEN+1];

    // output params
    EXEC_STATUS      exec_status_code;
    char             c_first[FIRST_NAME_LEN+1];
    char             c_middle[MIDDLE_NAME_LEN+1];
    double           c_balance;
    long            o_id;
    TIMESTAMP_STRUCT o_entry_d;
    short           o_carrier_id;
    OL_ORDER_STATUS_DATA OL[MAX_OL_ORDER_STATUS_ITEMS];
    short           o_ol_cnt;
} ORDER_STATUS_DATA, *PORDER_STATUS_DATA;

typedef struct
{
    // input params
    short      w_id;
    short      o_carrier_id;

    // output params
    EXEC_STATUS      exec_status_code;
    SYSTEMTIME       queue_time;
    long             o_id[10];    // id's of delivered orders for
                                // districts 1 to 10
} DELIVERY_DATA, *PDELIVERY_DATA;

//This structure is used for posting delivery transactions and for writing
//them to the delivery server.
typedef struct _DELIVERY_TRANSACTION
{
    SYSTEMTIME queue;    //time delivery transaction queued
    short      w_id;    //delivery warehouse
}

```

```

    short    o_carrier_id; //carrier id
} DELIVERY_TRANSACTION;

typedef struct
{
    // input params
    short    w_id;
    short    d_id;
    short    threshold;

    // output params
    EXEC_STATUS    exec_status_code;
    long    low_stock;
} STOCK_LEVEL_DATA, *PSTOCK_LEVEL_DATA;

/* FILE:      TXN_BASE.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE:   Header file for TPC-C txn class implementation.
 *
 * Change history:
 * 4.20.000 - updated rev number to match kit
 */

#pragma once

// need to declare functions for import, unless define has already been
created
// by the DLL's .cpp module for export.
#ifndef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class DllDecl CTPCC_BASE
{
public:
    CTPCC_BASE(void) {} ;
    virtual ~CTPCC_BASE(void) {} ;

    virtual PNEW_ORDER_DATA    BuffAddr_NewOrder()    = 0 ;
    virtual PPAYMENT_DATA      BuffAddr_Payment()      = 0 ;
    virtual PDELIVERY_DATA     BuffAddr_Delivery()     = 0 ;
    virtual PSTOCK_LEVEL_DATA  BuffAddr_StockLevel()   = 0 ;
    virtual PORDER_STATUS_DATA BuffAddr_OrderStatus()  = 0 ;

    virtual void NewOrder      () = 0 ;
    virtual void Payment       () = 0 ;
    virtual void Delivery      () = 0 ;
    virtual void StockLevel    () = 0 ;
    virtual void OrderStatus   () = 0 ;
};

```

```

/* FILE:      TPCC_DBLIB.CPP
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE:   Implements dblib calls for TPC-C txns.
 * Contact:   Charles Levine (clevine@microsoft.com)
 *
 * Change history:
 * 4.20.000 - updated rev number to match kit
 * 4.10.001 - not deleting error class in catch handler on deadlock
retry;
 *           not a functional bug, but a memory leak
 *           - had to tweak some declarations to compile with
latest SDK; no functional change
 */

#include <windows.h>
#include <stdio.h>
#include <assert.h>

#define DBNTWIN32
#include <sqlfront.h>
#include <sqlldb.h>

#ifndef ICECAP
#include <icapexp.h>
#endif

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\error.h"
#include "..\..\common\src\trans.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_dblib.h"

#define DEFCLPACKSIZE 4096

// version string; must match return value from tpcc_version stored proc
const char sVersion[] = "4.10.000";

const iMaxRetries = 10; // how many retries on deadlock
static long iConnectionCount = 0; // number of current dblib connections

const int iErrOleDbProvider = 7312;
const char sErrTimeoutExpired[] = "Timeout expired";

BOOL APIENTRY DllMain(HMODULE hModule, DWORD ul_reason_for_call, LPVOID
lpReserved)
{

```

```

switch( ul_reason_for_call )
{
    case DLL_PROCESS_ATTACH:
        DisableThreadLibraryCalls(hModule);
        dbinit();          // initialize dblib
        break;

    case DLL_PROCESS_DETACH:
        dbexit();         // close all dblib structures/connections
        break;

    default:
        /* nothing */;
}
return TRUE;
}

int err_handler(DBPROCESS *dbproc, int severity, int dberr, int oserr,
LPCSTR dberrstr, LPCSTR oserrstr)
{
    CTPCC_DBLIB          *pConn;

    assert(dbproc != NULL);
    pConn = (CTPCC_DBLIB*)dbgetuserdata(dbproc);

    if (pConn != NULL)
    {
        pConn->SetDbLibError( severity, dberr, oserr, dberrstr, oserrstr
);
    }
    return INT_CANCEL;
}

/* FUNCTION: int msg_handler(DBPROCESS *dbproc, DBINT msgno, int msgstate,
int severity, char *msgtext)
*
* PURPOSE:      This function handles DB-Library SQL Server error messages
*
* ARGUMENTS:    DBPROCESS      *dbproc          DBPROCESS id pointer
*                DBINT          msgno           message number
*                int             msgstate       message state
*                int             severity       message severity
*                char            *msgtext       printable message
description
*
* RETURNS:      int             INT_CONTINUE    continue if error
is SQLETIME else INT_CANCEL action
*
*                INT_CANCEL    cancel operation
*
* COMMENTS:     This function also sets the dead lock dbproc variable if
necessary.
*
*/

```

```

// typedef INT (SQLAPI *DBMSGHANDLE_PROC)(PDBPROCESS, DBINT, INT, INT,
LPCSTR, LPCSTR, LPCSTR, DBUSMALLINT);

int msg_handler(DBPROCESS *dbproc, DBINT msgno, int msgstate, int severity,
                LPCSTR msgtext, LPCSTR srvname, LPCSTR procname,
DBUSMALLINT line)
{
    CTPCC_DBLIB          *pConn;

    assert(dbproc != NULL);
    pConn = (CTPCC_DBLIB*)dbgetuserdata(dbproc);

    if (pConn != NULL)
    {
        pConn->SetSqlError( msgno, msgstate, severity, msgtext );
    }

    return 0;
}

/* FUNCTION: void UtilStrCpy(char * pDest, char * pSrc, int n)
*
* PURPOSE:      This function copies n characters from string pSrc to pDst
and places a
*
*                null character at the end of the destination string.
*
* ARGUMENTS:    char            *pDest         destination string pointer
*                char            *pSrc         *pSrcsource string pointer
*                int             n            number of characters to
copy
*
* RETURNS:      None
*
* COMMENTS:     Unlike strncpy this function ensures that the result string
is
*
*                always null terminated.
*
*/

inline static void UtilStrCpy(char * pDest, const BYTE * pSrc, int n)
{
    strncpy(pDest, (char *)pSrc, n);
    pDest[n] = '\0';

    return;
}

/* FUNCTION: CTPCC_DBLIB_ERR::ErrorText
*
*/

char* CTPCC_DBLIB_ERR::ErrorText(void)
{
    int i;

```

```

static SERRORMSG errorMsgs[] =
{
    { ERR_WRONG_SP_VERSION,      "Wrong version of stored procs on
database server" },
    { ERR_INVALID_CUST,         "Invalid Customer id,name." },
    { ERR_NO_SUCH_ORDER,        "No orders found for customer." },
    { ERR_RETRIED_TRANS,        "Retries before transaction succeeded." },
    { 0,                        "" }
};

static char szNotFound[] = "Unknown error number.";

for(i=0; errorMsgs[i].szMsg[0]; i++)
{
    if ( m_errno == errorMsgs[i].iError )
        break;
}
if ( !errorMsgs[i].szMsg[0] )
    return szNotFound;
else
    return errorMsgs[i].szMsg;
}

// wrapper routine for class constructor
_declspec(dllexport) CTPCC_DBLIB* CTPCC_DBLIB_new(
    LPCSTR szServer,          // name of SQL server
    LPCSTR szUser,           // user name for login
    LPCSTR szPassword,       // password for login
    LPCSTR szHost,          // workstation name; shows up in sp_who; max
30 chars, only first 10 kept by SQL Server
    LPCSTR szDatabase )     // name of database to use
{
    return new CTPCC_DBLIB( szServer, szUser, szPassword, szHost,
szDatabase );
}

CTPCC_DBLIB::CTPCC_DBLIB (
    LPCSTR szServer,        // name of SQL server
    LPCSTR szUser,         // user name for login
    LPCSTR szPassword,     // password for login
    LPCSTR szHost,        // workstation name; shows up in sp_who; max
30 chars, only first 10 kept by SQL Server
    LPCSTR szDatabase )    // name of database to use
{
    LOGINREC *login;
    const BYTE *pData;

    // initialization
    m_dbproc = NULL;
    m_DbLibErr = (CDBLIBERR*)NULL;

```

```

m_SqlErr = (CSQLERR*)NULL;

m_MaxRetries = 10;        // how many retries on deadlock

// increase max number of connections if getting close
if ( dbgetmaxprocs() < (iConnectionCount+5) )
{
    if ( dbsetmaxprocs(iConnectionCount+10) == FAIL )
        ThrowError(CDBLIBERR::eDbSetMaxProcs);
}

// allocate a login structure
login = dblogin();
if (login == NULL)
    ThrowError(CDBLIBERR::eLogin);
InterlockedIncrement( &iConnectionCount );

// register error and message handler functions
if (dbprocerrhandle(login, err_handler) == NULL)
    ThrowError(CDBLIBERR::eDbProcHandler);

if (dbprocmsghandle(login, msg_handler) == NULL)
    ThrowError(CDBLIBERR::eDbProcHandler);

DBSETLUSER(login, szUser);
DBSETLPWD(login, szPassword);
DBSETLHOST(login, szHost);
DBSETLPACKET(login, (unsigned short)DEFCLPACKSIZE);
DBSETLVERSION(login, DBVER60);    // use dblib ver 6.0 client
behavior

// set time to wait for login
if (dbsetlogintime(60) == FAIL)
    ThrowError(CDBLIBERR::eDbSet);

// set time to wait for statement execution
if (dbsettime(180) == FAIL)
    ThrowError(CDBLIBERR::eDbSet);

m_dbproc = dbopen(login, szServer);

// deallocate login structure before checking for success
dbfreelogin( login );

if (m_dbproc == NULL)
    ThrowError(CDBLIBERR::eDbOpen);

// save address of class instance so that the message and error handler
// can get to data.
dbsetuserdata(m_dbproc, (LPVOID)this);

// Use the the right database
if (dbuse(m_dbproc, szDatabase) == FAIL)
    ThrowError(CDBLIBERR::eDbUse);

```

```

        dbcmd(m_dbproc, "set nocount on ");           // do not return row
counts
        dbcmd(m_dbproc, "set XACT_ABORT ON");       // rollback transaction
on abort

        if (dbsqlEXEC(m_dbproc) == FAIL)
            ThrowError(CDBLIBERR::eDbSqlExec);

        DiscardNextResults(2);

        // verify that version of stored procs on server is correct
        dbrpcinit(m_dbproc, "tpcc_version", 0);

        if (dbrpcEXEC(m_dbproc) == FAIL)
            ThrowError(CDBLIBERR::eDbRpcExec);

        if (dbresults(m_dbproc) != SUCCEED)
            ThrowError(CDBLIBERR::eDbResults);

        if (dbnextrow(m_dbproc) != REG_ROW)
            ThrowError(CDBLIBERR::eDbNextRow);

        char szSrvVersion[16];
        pData=dbdata(m_dbproc, 1);
        if (pData)
            UtilStrCpy(szSrvVersion, pData, dbdatlen(m_dbproc, 1));
        else
            szSrvVersion[0]=0;
        if (strcmp(szSrvVersion,sVersion))
            throw new CTPCC_DBLIB_ERR( CTPCC_DBLIB_ERR::ERR_WRONG_SP_VERSION
);

        DiscardNextRows(0);
        DiscardNextResults(0);
}

CTPCC_DBLIB::~CTPCC_DBLIB( void )
{
    // close db connection and deallocate resources
    dbclose(m_dbproc);
    InterlockedDecrement( &iConnectionCount );
    if (m_DbLibErr != NULL)
        delete m_DbLibErr;
    if (m_SqlErr != NULL)
        delete m_SqlErr;
}

void CTPCC_DBLIB::SetDbLibError(int severity, int dberr, int oserr, LPCSTR
dberrstr, LPCSTR oserrstr)
{
    delete m_DbLibErr;

```

```

        m_DbLibErr = new CDBLIBERR(CDBLIBERR::eUnknown, severity, dberr,
oserr);

        if (dberrstr != NULL)
        {
            m_DbLibErr->m_dberrstr = new char[ strlen(dberrstr)+1 ];
            strcpy( m_DbLibErr->m_dberrstr, dberrstr );
        }

        if (oserrstr != NULL)
        {
            m_DbLibErr->m_oserrstr = new char[ strlen(oserrstr)+1 ];
            strcpy( m_DbLibErr->m_oserrstr, oserrstr );
        }
}

void CTPCC_DBLIB::SetSqlError( int /*DBINT*/ msgno, int msgstate, int
severity, LPCSTR msgtext )
{
    if (m_SqlErr == NULL)
        m_SqlErr = new CSQLERR();

    m_SqlErr->m_msgno = msgno;
    m_SqlErr->m_msgstate = msgstate;
    m_SqlErr->m_severity = severity;

    delete [] m_SqlErr->m_msgtext;
    if (msgtext != NULL)
    {
        m_SqlErr->m_msgtext = new char[ strlen(msgtext)+1 ];
        strcpy( m_SqlErr->m_msgtext, msgtext );
    }
}

void CTPCC_DBLIB::ThrowError( CDBLIBERR::ACTION eAction )
{
    // discard anything still in return buffer
    DiscardNextRows(-1);
    DiscardNextResults(-1);

    // check for SQL Server error first; if yes, throw it and ignore any
DBLib error.
    if (m_SqlErr != NULL)
    {
        CSQLERR *pSqlErr;
        pSqlErr = m_SqlErr;
        m_SqlErr = NULL; // clear our pointer to instance; catch
handler will delete
        throw pSqlErr;
    }

    CDBLIBERR *pDbLibErr;
    if (m_DbLibErr == NULL)

```

```

        // this case isn't expected to happen, since it means that an
error was returned
        // but the error handlers were not called.
        pDbLibErr = new CDBLIBERR(eAction);
    else
    {
        pDbLibErr = m_DbLibErr;
        pDbLibErr->m_eAction = eAction;
        m_DbLibErr = NULL;        // clear our pointer to instance; catch
handler will delete
    }

    throw pDbLibErr;
}

// Read and discard rows until no more. Throw an exception if number of
rows read doesn't
// match number of rows expected. The row count will be ignored if the
expected count value
// passed in is negative. A typical use of this routine is to verify that
there are no more
// rows to be read.
void CTPCC_DBLIB::DiscardNextRows(int iExpectedCount)
{
    int        iRowsRead = 0;
    RETCODE    rc;

    while (TRUE)
    {
        rc = dbnextrow(m_dbproc);
        if (rc == NO_MORE_ROWS)
            break;
        if (rc == FAIL)
        {
            if (iExpectedCount >= 0)
                ThrowError(CDBLIBERR::eDbNextRow);
            else
                break;
        }
        iRowsRead++;
    }

    if ((iExpectedCount >= 0) &&
        (iExpectedCount != iRowsRead))
        ThrowError(CDBLIBERR::eWrongRowCount);
}

// Read and discard results until no more. Throw an exception if number of
result sets read doesn't
// match number expected. The result set count will be ignored if the
expected count value
// passed in is negative. A typical use of this routine is to verify that
there are no more
// result sets to be read.
void CTPCC_DBLIB::DiscardNextResults(int iExpectedCount)

```

```

{
    int        iResultsRead = 0;
    RETCODE    rc;

    while (TRUE)
    {
        rc = dbresults(m_dbproc);
        if (rc == NO_MORE_RESULTS)
            break;
        if (rc == FAIL)
        {
            if (iExpectedCount >= 0)
                ThrowError(CDBLIBERR::eDbResults);
            else
                break;
        }

        DiscardNextRows(-1);
        iResultsRead++;
    }

    if ((iExpectedCount >= 0) &&
        (iExpectedCount != iResultsRead))
        ThrowError(CDBLIBERR::eWrongRowCount);
}

void CTPCC_DBLIB::StockLevel()
{
    int        iTryCount = 0;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_stocklevel", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.StockLevel.w_id);        // @w_id smallint
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.StockLevel.d_id);        // @d_id tinyint
            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.StockLevel.threshold);    // @threshold smallint

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            if (dbresults(m_dbproc) != SUCCEED)
                ThrowError(CDBLIBERR::eDbResults);

            if (dbnextrow(m_dbproc) != REG_ROW)
                ThrowError(CDBLIBERR::eDbNextRow);
        }
    }
}

```

```

        if (pData=dbdata(m_dbproc, 1))
            m_txn.StockLevel.low_stock = *((long *) pData);

        DiscardNextRows(0);
        DiscardNextResults(0);

        m_txn.StockLevel.exec_status_code = eOK;
        return;
    }
    catch (CSQLERR *e)
    {
        if ((e->m_msgno == 1205 ||
            (e->m_msgno == iErrOleDbProvider &&
             strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
            (++iTryCount <= iMaxRetries))
        {
            // hit deadlock; backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
        else
            throw;
    }
} // while (TRUE)

//if (iTryCount)
//    throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

```

```

void CTPCC_DBLIB::NewOrder()
{
    int            i;
    DBINT         commit_flag;
    DBDATETIME    datetime;
    DBDATEREC     daterec;

    int            iTryCount = 0;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_neworder", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.NewOrder.w_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.NewOrder.d_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.NewOrder.c_id);

```

```

            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.NewOrder.o_ol_cnt);

            // check whether any order lines are for a remote warehouse
            m_txn.NewOrder.o_all_local = 1;
            for (i = 0; i < m_txn.NewOrder.o_ol_cnt; i++)
            {
                if (m_txn.NewOrder.OL[i].ol_supply_w_id !=
m_txn.NewOrder.w_id)
                {
                    m_txn.NewOrder.o_all_local = 0; // at least one
remote warehouse
                    break;
                }
            }
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.NewOrder.o_all_local);

            for (i = 0; i < m_txn.NewOrder.o_ol_cnt; i++)
            {
                dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.NewOrder.OL[i].ol_i_id);
                dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.NewOrder.OL[i].ol_supply_w_id);
                dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.NewOrder.OL[i].ol_quantity);
            }

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            // Get order line results
            m_txn.NewOrder.total_amount = 0;
            for (i = 0; i < m_txn.NewOrder.o_ol_cnt; i++)
            {
                if (dbresults(m_dbproc) != SUCCEED)
                    ThrowError(CDBLIBERR::eDbResults);

                if (dbnumcols(m_dbproc) != 5)
                    ThrowError(CDBLIBERR::eWrongNumCols);

                if (dbnextrow(m_dbproc) != REG_ROW)
                    ThrowError(CDBLIBERR::eDbNextRow);

                if (pData=dbdata(m_dbproc, 1))
                    UtilStrCpy(m_txn.NewOrder.OL[i].ol_i_name, pData,
dbdatlen(m_dbproc, 1));
                if (pData=dbdata(m_dbproc, 2))
                    m_txn.NewOrder.OL[i].ol_stock = (*(DBSMALLINT *)
pData);
                if (pData=dbdata(m_dbproc, 3))
                    UtilStrCpy(m_txn.NewOrder.OL[i].ol_brand_generic,
pData, dbdatlen(m_dbproc, 3));
                if (pData=dbdata(m_dbproc, 4))

```

```

        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,4),
        SQLFLT8, (BYTE *)&m_txn.NewOrder.OL[i].ol_i_price,
8);
        if(pData=dbdata(m_dbproc, 5))

        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,5),
        SQLFLT8, (BYTE *)&m_txn.NewOrder.OL[i].ol_amount,
8);

        m_txn.NewOrder.total_amount =
m_txn.NewOrder.total_amount + m_txn.NewOrder.OL[i].ol_amount;

        DiscardNextRows(0);
    }

    // get remaining values for w_tax, d_tax, o_id, c_last,
c_discount, c_credit, o_entry_d, commit_flag
    if (dbresults(m_dbproc) != SUCCEED)
        ThrowError(CDBLIBERR::eDbResults);

    if (dbnextrow(m_dbproc) != REG_ROW)
        ThrowError(CDBLIBERR::eDbNextRow);

    if (dbnumcols(m_dbproc) != 8)
        ThrowError(CDBLIBERR::eWrongNumCols);

    if (pData=dbdata(m_dbproc, 1))

        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,1), SQLFLT8, (BYTE *)&m_txn.NewOrder.w_tax, 8);
        if (pData=dbdata(m_dbproc, 2))

        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,2), SQLFLT8, (BYTE *)&m_txn.NewOrder.d_tax, 8);
        if (pData=dbdata(m_dbproc, 3))
            m_txn.NewOrder.o_id = *(DBINT *) pData);
        if (pData=dbdata(m_dbproc, 4))
            UtilStrCpy(m_txn.NewOrder.c_last, pData,
dbdatlen(m_dbproc, 4));
        if (pData=dbdata(m_dbproc, 5))
            dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,5), SQLFLT8, (BYTE *)&m_txn.NewOrder.c_discount, 8);
        if (pData=dbdata(m_dbproc, 6))
            UtilStrCpy(m_txn.NewOrder.c_credit, pData,
dbdatlen(m_dbproc, 6));
        if (pData=dbdata(m_dbproc, 7))
        {
            datetime = *((DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);
            m_txn.NewOrder.o_entry_d.year = daterec.year;
            m_txn.NewOrder.o_entry_d.month = daterec.month;
            m_txn.NewOrder.o_entry_d.day = daterec.day;

```

```

        m_txn.NewOrder.o_entry_d.hour = daterec.hour;
        m_txn.NewOrder.o_entry_d.minute = daterec.minute;
        m_txn.NewOrder.o_entry_d.second = daterec.second;
    }
    if (pData=dbdata(m_dbproc, 8))
        commit_flag = (*(DBTINYINT *) pData);

    DiscardNextRows(0);
    DiscardNextResults(0);

    if (commit_flag == 1)
    {
        m_txn.NewOrder.total_amount *= ((1 +
m_txn.NewOrder.w_tax + m_txn.NewOrder.d_tax) * (1 -
m_txn.NewOrder.c_discount));
        m_txn.NewOrder.exec_status_code = eOK;
    }
    else
        m_txn.NewOrder.exec_status_code = eInvalidItem;

    return;
}
catch (CSQLERR *e)
{
    if ((e->m_msgno == 1205 ||
(e->m_msgno == iErrOleDbProvider &&
strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
(++iTryCount <= iMaxRetries))
    {
        // hit deadlock; backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }
    else
        throw;
}
} // while (TRUE)

// if (iTryCount)
// throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::Payment()
{
    DBDATETIME datetime;
    DBDATEREC daterec;

    int iTryCount = 0;
    const BYTE *pData;

    ResetError();

```

```

while (TRUE)
{
    try
    {
        dbrpcinit(m_dbproc, "tpcc_payment", 0);

        dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.Payment.w_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.Payment.c_w_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLFLT8, -1, -1, (BYTE *)
&m_txn.Payment.h_amount);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Payment.d_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Payment.c_d_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.Payment.c_id);

        // if customer id is zero, then payment is by name
        if (m_txn.Payment.c_id == 0)
            dbrpcparam(m_dbproc, NULL, 0, SQLCHAR, -1,
strlen(m_txn.Payment.c_last), (unsigned char *)m_txn.Payment.c_last);

        if (dbrpcexec(m_dbproc) == FAIL)
            ThrowError(CDBLIBERR::eDbRpcExec);

        if (dbresults(m_dbproc) != SUCCEED)
            ThrowError(CDBLIBERR::eDbResults);

        if (dbnextrow(m_dbproc) != REG_ROW)
            ThrowError(CDBLIBERR::eDbNextRow);

        if (dbnumcols(m_dbproc) != 27)
            ThrowError(CDBLIBERR::eWrongNumCols);

        if (pData=dbdata(m_dbproc, 1))
            m_txn.Payment.c_id = *((DBINT *) pData);
        if (pData=dbdata(m_dbproc, 2))
            UtilStrCpy(m_txn.Payment.c_last, pData,
dbdatlen(m_dbproc, 2));
        if (pData=dbdata(m_dbproc, 3))
        {
            datetime = *((DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);
            m_txn.Payment.h_date.year = daterec.year;
            m_txn.Payment.h_date.month = daterec.month;
            m_txn.Payment.h_date.day = daterec.day;
            m_txn.Payment.h_date.hour = daterec.hour;
            m_txn.Payment.h_date.minute = daterec.minute;
            m_txn.Payment.h_date.second = daterec.second;
        }
        if (pData=dbdata(m_dbproc, 4))
            UtilStrCpy(m_txn.Payment.w_street_1, pData,
dbdatlen(m_dbproc, 4));

```

```

        if (pData=dbdata(m_dbproc, 5))
            UtilStrCpy(m_txn.Payment.w_street_2, pData,
dbdatlen(m_dbproc, 5));
        if (pData=dbdata(m_dbproc, 6))
            UtilStrCpy(m_txn.Payment.w_city, pData,
dbdatlen(m_dbproc, 6));
        if (pData=dbdata(m_dbproc, 7))
            UtilStrCpy(m_txn.Payment.w_state, pData,
dbdatlen(m_dbproc, 7));
        if (pData=dbdata(m_dbproc, 8))
            UtilStrCpy(m_txn.Payment.w_zip, pData,
dbdatlen(m_dbproc, 8));
        if (pData=dbdata(m_dbproc, 9))
            UtilStrCpy(m_txn.Payment.d_street_1, pData,
dbdatlen(m_dbproc, 9));
        if (pData=dbdata(m_dbproc, 10))
            UtilStrCpy(m_txn.Payment.d_street_2, pData,
dbdatlen(m_dbproc, 10));
        if (pData=dbdata(m_dbproc, 11))
            UtilStrCpy(m_txn.Payment.d_city, pData,
dbdatlen(m_dbproc, 11));
        if (pData=dbdata(m_dbproc, 12))
            UtilStrCpy(m_txn.Payment.d_state, pData,
dbdatlen(m_dbproc, 12));
        if (pData=dbdata(m_dbproc, 13))
            UtilStrCpy(m_txn.Payment.d_zip, pData,
dbdatlen(m_dbproc, 13));
        if (pData=dbdata(m_dbproc, 14))
            UtilStrCpy(m_txn.Payment.c_first, pData,
dbdatlen(m_dbproc, 14));
        if (pData=dbdata(m_dbproc, 15))
            UtilStrCpy(m_txn.Payment.c_middle, pData,
dbdatlen(m_dbproc, 15));
        if (pData=dbdata(m_dbproc, 16))
            UtilStrCpy(m_txn.Payment.c_street_1, pData,
dbdatlen(m_dbproc, 16));
        if (pData=dbdata(m_dbproc, 17))
            UtilStrCpy(m_txn.Payment.c_street_2, pData,
dbdatlen(m_dbproc, 17));
        if (pData=dbdata(m_dbproc, 18))
            UtilStrCpy(m_txn.Payment.c_city, pData,
dbdatlen(m_dbproc, 18));
        if (pData=dbdata(m_dbproc, 19))
            UtilStrCpy(m_txn.Payment.c_state, pData,
dbdatlen(m_dbproc, 19));
        if (pData=dbdata(m_dbproc, 20))
            UtilStrCpy(m_txn.Payment.c_zip, pData,
dbdatlen(m_dbproc, 20));
        if (pData=dbdata(m_dbproc, 21))
            UtilStrCpy(m_txn.Payment.c_phone, pData,
dbdatlen(m_dbproc, 21));
        if (pData=dbdata(m_dbproc, 22))
        {
            datetime = *((DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);

```

```

        m_txn.Payment.c_since.year   = daterec.year;
        m_txn.Payment.c_since.month  = daterec.month;
        m_txn.Payment.c_since.day    = daterec.day;
        m_txn.Payment.c_since.hour   = daterec.hour;
        m_txn.Payment.c_since.minute = daterec.minute;
        m_txn.Payment.c_since.second = daterec.second;
    }
    if(pData=dbdata(m_dbproc, 23))
        UtilStrCpy(m_txn.Payment.c_credit, pData,
dbdatlen(m_dbproc, 23));
    if(pData=dbdata(m_dbproc, 24))
        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,24), SQLFLT8, (BYTE *)&m_txn.Payment.c_credit_lim, 8);
    if(pData=dbdata(m_dbproc, 25))
        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,25), SQLFLT8, (BYTE *)&m_txn.Payment.c_discount, 8);
    if(pData=dbdata(m_dbproc, 26))
        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,26), SQLFLT8, (BYTE *)&m_txn.Payment.c_balance, 8);
    if(pData=dbdata(m_dbproc, 27))
        UtilStrCpy(m_txn.Payment.c_data, pData,
dbdatlen(m_dbproc, 27));

    DiscardNextRows(0);
    DiscardNextResults(0);

    if (m_txn.Payment.c_id == 0)
        throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_INVALID_CUST );
    else
        m_txn.Payment.exec_status_code = eOK;

    return;
}
catch (CSQLERR *e)
{
    if ((e->m_msgno == 1205 ||
        (e->m_msgno == iErrOleDbProvider &&
        strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
        (++iTryCount <= iMaxRetries))
    {
        // hit deadlock; backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }
    else
        throw;
}
} // while (TRUE)

// if (iTryCount)
//     throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

```

```

void CTPCC_DBLIB::OrderStatus()
{
    int          i;
    DBDATETIME  datetime;
    DBDATEREC   daterec;

    int          iTryCount = 0;
    RETCODE     rc;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_orderstatus", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.OrderStatus.w_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.OrderStatus.d_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.OrderStatus.c_id);

            // if customer id is zero, then order status is by name
            if (m_txn.OrderStatus.c_id == 0)
                dbrpcparam(m_dbproc, NULL, 0, SQLCHAR, -1,
strlen(m_txn.OrderStatus.c_last), (unsigned char
*)m_txn.OrderStatus.c_last);

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            // Get order lines
            if (dbresults(m_dbproc) != SUCCEED)
            {
                if ((m_DbLibErr == NULL) && (m_SqlErr == NULL))
                    throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_NO_SUCH_ORDER );
                else
                    ThrowError(CDBLIBERR::eDbResults);
            }

            if (dbnumcols(m_dbproc) != 5)
                ThrowError(CDBLIBERR::eWrongNumCols);

            i = 0;
            while (TRUE)
            {
                rc = dbnextrow(m_dbproc);

```

```

        if (rc == NO_MORE_ROWS)
            break;
        if (rc != REG_ROW)
            ThrowError(CDBLIBERR::eDbNextRow);

        if(pData=dbdata(m_dbproc, 1))
            m_txn.OrderStatus.OL[i].ol_supply_w_id =
(* (DBSMALLINT *) pData);
        if(pData=dbdata(m_dbproc, 2))
            m_txn.OrderStatus.OL[i].ol_i_id = (*(DBINT *)
pData);
        if(pData=dbdata(m_dbproc, 3))
            m_txn.OrderStatus.OL[i].ol_quantity =
(* (DBSMALLINT *) pData);
        if(pData=dbdata(m_dbproc, 4))
            dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,4),
                    SQLFLT8, (BYTE
*)&m_txn.OrderStatus.OL[i].ol_amount, 8);
        if(pData=dbdata(m_dbproc, 5))
        {
            datetime = *((DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);
            m_txn.OrderStatus.OL[i].ol_delivery_d.year =
daterec.year;
            m_txn.OrderStatus.OL[i].ol_delivery_d.month =
daterec.month;
            m_txn.OrderStatus.OL[i].ol_delivery_d.day =
daterec.day;
            m_txn.OrderStatus.OL[i].ol_delivery_d.hour =
daterec.hour;
            m_txn.OrderStatus.OL[i].ol_delivery_d.minute =
daterec.minute;
            m_txn.OrderStatus.OL[i].ol_delivery_d.second =
daterec.second;
        }
        i++;
    }
    m_txn.OrderStatus.o_ol_cnt = i;

    if (dbresults(m_dbproc) != SUCCEED)
        ThrowError(CDBLIBERR::eDbResults);

    if (dbnextrow(m_dbproc) != REG_ROW)
        ThrowError(CDBLIBERR::eDbNextRow);

    if (dbnumcols(m_dbproc) != 8)
        ThrowError(CDBLIBERR::eWrongNumCols);

    if(pData=dbdata(m_dbproc, 1))
        m_txn.OrderStatus.c_id = (*(DBINT *) pData);
    if(pData=dbdata(m_dbproc, 2))
        UtilStrCpy(m_txn.OrderStatus.c_last, pData,
dbdatlen(m_dbproc, 2));

```

```

        if(pData=dbdata(m_dbproc, 3))
            UtilStrCpy(m_txn.OrderStatus.c_first, pData,
dbdatlen(m_dbproc, 3));
        if(pData=dbdata(m_dbproc, 4))
            UtilStrCpy(m_txn.OrderStatus.c_middle, pData,
dbdatlen(m_dbproc, 4));
        if(pData=dbdata(m_dbproc, 5))
        {
            datetime = *((DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);
            m_txn.OrderStatus.o_entry_d.year = daterec.year;
            m_txn.OrderStatus.o_entry_d.month = daterec.month;
            m_txn.OrderStatus.o_entry_d.day = daterec.day;
            m_txn.OrderStatus.o_entry_d.hour = daterec.hour;
            m_txn.OrderStatus.o_entry_d.minute = daterec.minute;
            m_txn.OrderStatus.o_entry_d.second = daterec.second;
        }
        if(pData=dbdata(m_dbproc, 6))
            m_txn.OrderStatus.o_carrier_id = (*(DBSMALLINT *)
pData);
        if(pData=dbdata(m_dbproc, 7))
            dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,7),
                    SQLFLT8, (BYTE
*)&m_txn.OrderStatus.c_balance, 8);
        if(pData=dbdata(m_dbproc, 8))
            m_txn.OrderStatus.o_id = (*(DBINT *) pData);

        DiscardNextRows(0);
        DiscardNextResults(0);

        if (m_txn.OrderStatus.o_ol_cnt == 0)
            throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_NO_SUCH_ORDER );
        else if (m_txn.OrderStatus.c_id == 0 &&
m_txn.OrderStatus.c_last[0] == 0)
            throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_INVALID_CUST );
        else
            m_txn.OrderStatus.exec_status_code = eOK;

        return;
    }
    catch (CSQLERR *e)
    {
        if ((e->m_msgno == 1205 ||
(e->m_msgno == iErrOleDbProvider &&
strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
(++iTryCount <= iMaxRetries))
        {
            // hit deadlock; backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
    }

```

```

        else
            throw;
    }
} // while (TRUE)

// if (iTryCount)
// throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::Delivery()
{
    int i;
    int iTryCount = 0;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_delivery", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&_txn.Delivery.w_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&_txn.Delivery.o_carrier_id);

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            if (dbresults(m_dbproc) != SUCCEEDED)
                ThrowError(CDBLIBERR::eDbResults);

            if (dbnextrow(m_dbproc) != REG_ROW)
                ThrowError(CDBLIBERR::eDbNextRow);

            if (dbnumcols(m_dbproc) != 10)
                ThrowError(CDBLIBERR::eWrongNumCols);

            for (i=0; i<10; i++)
            {
                if (pData = dbdata(m_dbproc, i+1))
                    m_txn.Delivery.o_id[i] = *((DBINT *)pData);
            }

            DiscardNextRows(0);
            DiscardNextResults(0);

            m_txn.Delivery.exec_status_code = eOK;
            return;
        }
        catch (CSQLERR *e)

```

```

        {
            if ((e->m_msgno == 1205 ||
                (e->m_msgno == iErrOleDbProvider &&
                 strstr(e->m_msgtext, sErrTimeoutExpired) != NULL) &&
                (++iTryCount <= iMaxRetries))
            {
                // hit deadlock; backoff for increasingly longer period
                delete e;
                Sleep(10 * iTryCount);
            }
            else
                throw;
        }
    } // while (TRUE)

// if (iTryCount)
// throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::ResetError()
{
    if (m_DbLibErr != NULL)
    {
        delete m_DbLibErr;
        m_DbLibErr = (CDBLIBERR*)NULL;
    }

    if (m_SqlErr != NULL)
    {
        delete m_SqlErr;
        m_SqlErr = (CSQLERR*)NULL;
    }
    return;
}

/* FILE:      TPCC_DBLIB.H
*             Microsoft TPC-C Kit Ver. 4.20.000
*             Copyright Microsoft, 1999
*             All Rights Reserved
*
*             Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
*
* PURPOSE:   Header file for TPC-C txn class implementation.
*
* Change history:
* 4.20.000 - updated rev number to match kit
*/
#pragma once

#ifndef PDBPROCESS
#define DBPROCESS void // dbprocess structure type
typedef DBPROCESS * PDBPROCESS;
#endif

```

```

// need to declare functions for import, unless define has already been
// created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class CSQLERR : public CBaseErr
{
public:
    CSQLERR(void)
    {
        m_msgno = 0;
        m_msgstate = 0;
        m_severity = 0;
        m_msgtext = NULL;
    };

~CSQLERR()
{
    delete [] m_msgtext;
};

int      m_msgno;
int      m_msgstate;
int      m_severity;
char     *m_msgtext;

int ErrorType() {return ERR_TYPE_SQL;};
int ErrorNum() {return m_msgno;};
char *ErrorText() {return m_msgtext;};
};

class CDBLIBERR : public CBaseErr
{
public:
    enum ACTION
    {
        eNone,
        eUnknown,
        eLogin, // error from dblogin
        eDbOpen, // error from dbopen
        eDbUse, // error from dbuse
        eDbSqlExec, // error from dbsqlexec
        eDbSet, // error from one of the dbset*
        eDbNextRow, // error from dbnextrow
        eWrongRowCount, // more or less rows returned than
        eWrongNumCols, // more or less columns returned than
        eDbResults, // error from dbresults
    };
};

```

```

        eDbRpcExec, // error from dbrpcexec
        eDbSetMaxProcs, // error from dbsetmaxprocs
        eDbProcHandler // error from either dbprocerrhandle or
dbprocmsghandle
};

CDBLIBERR(ACTION eAction, int severity = 0, int dberror = 0, int
oserr = 0)
{
    m_eAction = eAction;
    m_severity = severity;
    m_dberror = dberror;
    m_oserr = oserr;

    m_dberrstr = NULL;
    m_oserrstr = NULL;
};

~CDBLIBERR()
{
    delete [] m_dberrstr;
    delete [] m_oserrstr;
};

ACTION      m_eAction;
int          m_severity;
int          m_dberror;
int          m_oserr;
char        *m_dberrstr;
char        *m_oserrstr;

int ErrorType() {return ERR_TYPE_DBLIB;};
int ErrorNum() {return m_dberror;};
char *ErrorText() {return m_dberrstr;};
};

class CTPCC_DBLIB_ERR : public CBaseErr
{
public:
    enum CTPCC_DBLIB_ERRS
    {
        ERR_WRONG_SP_VERSION = 1, // "Wrong version of stored procs
on database server"
        ERR_INVALID_CUST, // "Invalid Customer
id,name."
        ERR_NO_SUCH_ORDER, // "No orders found for
customer."
        ERR_RETRIED_TRANS, // "Retries before
transaction succeeded."
    };

    CTPCC_DBLIB_ERR( int iErr ) { m_errno = iErr; m_iTryCount = 0; };
};

```

```

        CTPCC_DBLIB_ERR( int iErr, int iTryCount ) { m_errno = iErr;
m_iTryCount = iTryCount; };

        int          m_errno;
        int          m_iTryCount;

        int ErrorType() {return ERR_TYPE_TPCC_DBLIB;};
        int ErrorNum() {return m_errno;};

        char *ErrorText();
};

class DllDecl CTPCC_DBLIB : public CTPCC_BASE
{
private:
        // declare variables and private functions here...
        PDBPROCESS m_dbproc;
        CDBLIBERR *m_DbLibErr;          // not allocated until needed
(maybe never)
        CSQLERR      *m_SqlErr;          // not allocated until needed
(maybe never)
        int          m_MaxRetries;      // retry count on deadlock

        void DiscardNextRows(int iExpectedCount);
        void DiscardNextResults(int iExpectedCount);
        void ThrowError( CDBLIBERR::ACTION eAction );
        void ResetError();

        union
        {
                NEW_ORDER_DATA      NewOrder;
                PAYMENT_DATA         Payment;
                DELIVERY_DATA        Delivery;
                STOCK_LEVEL_DATA     StockLevel;
                ORDER_STATUS_DATA    OrderStatus;
        }
                m_txn;

public:
        CTPCC_DBLIB(LPCSTR szServer, LPCSTR szUser, LPCSTR szPassword,
LPCSTR szHost, LPCSTR szDatabase );
        ~CTPCC_DBLIB(void);

        inline PNEW_ORDER_DATA      BuffAddr_NewOrder()      { return
&m_txn.NewOrder; };
        inline PPAYMENT_DATA        BuffAddr_Payment()       { return
&m_txn.Payment; };
        inline PDELIVERY_DATA       BuffAddr_Delivery()      { return
&m_txn.Delivery; };
        inline PSTOCK_LEVEL_DATA    BuffAddr_StockLevel()    { return
&m_txn.StockLevel; };
        inline PORDER_STATUS_DATA   BuffAddr_OrderStatus()   { return
&m_txn.OrderStatus; };

        void NewOrder      ();
        void Payment       ();

```

```

        void Delivery      ();
        void StockLevel    ();
        void OrderStatus   ();

        // these are public because they must be called from the dblink
err_handler and msg_hangler
        // outside of the class
        void SetDbLibError(int severity, int dberr, int oserr, LPCSTR
dberrstr, LPCSTR oserrstr);
        void SetSqlError( int msgno, int msgstate, int severity, LPCSTR
msgtext );
};

extern "C" DllDecl CTPCC_DBLIB* CTPCC_DBLIB_new
( LPCSTR szServer, LPCSTR szUser, LPCSTR szPassword, LPCSTR szHost,
LPCSTR szDatabase );

typedef CTPCC_DBLIB* (TYPE_CTPCC_DBLIB)(LPCSTR, LPCSTR, LPCSTR, LPCSTR,
LPCSTR);

/* FILE:          TPCC_COM.CPP
*                Microsoft TPC-C Kit Ver. 4.20.000
*                Copyright Microsoft, 1999
*                All Rights Reserved
*
*                not yet audited
*
* PURPOSE:       Source file for TPC-C COM+ class implementation.
* Contact:       Charles Levine (clevine@microsoft.com)
*
* Change history:
* 4.20.000 - first version
*/

// needed for CoInitializeEx
#define _WIN32_WINNT 0x0400

#include <windows.h>

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\trans.h" //tpckit transaction header
contains definations of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_com.h"

#include "..\..\tpcc_com_ps\src\tpcc_com_ps_i.c"
#include "..\..\tpcc_com_all\src\tpcc_com_all_i.c"

// wrapper routine for class constructor
__declspec(dllexport) CTPCC_COM* CTPCC_COM_new(BOOL bSinglePool)

```

```

{
    return new CTPCC_COM(bSinglePool);
}

CTPCC_COM::CTPCC_COM(BOOL bSinglePool)
{
    HRESULT hr = NULL;
    long lRet = 0;
    ULONG ulTmpSize = 0;

    m_pTxn          = NULL;
    m_pNewOrder     = NULL;
    m_pPayment      = NULL;
    m_pStockLevel   = NULL;
    m_pOrderStatus  = NULL;

    m_bSinglePool  = bSinglePool;

    ulTmpSize = (ULONG) sizeof(COM_DATA);
    VariantInit(&m_vTxn);
    m_vTxn.vt = VT_SAFEARRAY;

    m_vTxn.parray = SafeArrayCreateVector(VT_UI1, ulTmpSize, ulTmpSize);
    if (!m_vTxn.parray)
        throw new CCOMERR( E_FAIL );

    memset((void*)m_vTxn.parray->pvData, 0, ulTmpSize);
    m_pTxn = (COM_DATA*)m_vTxn.parray->pvData;

    hr = CoInitializeEx(NULL, COINIT_MULTITHREADED);
    if (FAILED(hr))
    {
        throw new CCOMERR( hr );
    }

    // create components
    if (m_bSinglePool)
    {
        hr = CoCreateInstance(CLSID_TPCC, NULL, CLSCTX_SERVER, IID_ITPCC,
(void **) &m_pNewOrder);
        if (FAILED(hr))
            throw new CCOMERR(hr);

        // all txns will use same component
        m_pPayment = m_pNewOrder;
        m_pStockLevel = m_pNewOrder;
        m_pOrderStatus = m_pNewOrder;
    }
    else
    {
        // use different components for each txn

        hr = CoCreateInstance(CLSID_NewOrder, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pNewOrder);
        if (FAILED(hr))

```

```

        throw new CCOMERR(hr);

        hr = CoCreateInstance(CLSID_Payment, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pPayment);
        if (FAILED(hr))
            throw new CCOMERR(hr);

        hr = CoCreateInstance(CLSID_StockLevel, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pStockLevel);
        if (FAILED(hr))
            throw new CCOMERR(hr);

        hr = CoCreateInstance(CLSID_OrderStatus, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pOrderStatus);
        if (FAILED(hr))
            throw new CCOMERR(hr);
    }

    // call setcomplete to release each component back into pool
    hr = m_pNewOrder->CallSetComplete();
    if (FAILED(hr))
        throw new CCOMERR(hr);

    if (!m_bSinglePool)
    {
        hr = m_pPayment->CallSetComplete();
        if (FAILED(hr))
            throw new CCOMERR(hr);

        hr = m_pStockLevel->CallSetComplete();
        if (FAILED(hr))
            throw new CCOMERR(hr);

        hr = m_pOrderStatus->CallSetComplete();
        if (FAILED(hr))
            throw new CCOMERR(hr);
    }
}

CTPCC_COM::~CTPCC_COM()
{
    if (m_pTxn)
        SafeArrayDestroy(m_vTxn.parray);

    ReleaseInterface(m_pNewOrder);
    if (!m_bSinglePool)
    {
        ReleaseInterface(m_pPayment);
        ReleaseInterface(m_pStockLevel);
        ReleaseInterface(m_pOrderStatus);
    }
    CoUninitialize();
}

void CTPCC_COM::NewOrder()

```

```

{
    VARIANT    vTxn_out;

    HRESULT hr = m_pNewOrder->NewOrder(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

void CTPCC_COM::Payment()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pPayment->Payment(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

void CTPCC_COM::StockLevel()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pStockLevel->StockLevel(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

void CTPCC_COM::OrderStatus()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pOrderStatus->OrderStatus(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);
}

```

```

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

/* FILE:      TPCC_COM.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not yet audited
 *
 * PURPOSE:   Header file for TPC-C COM+ class implementation.
 *
 * Change history:
 *           4.20.000 - first version
 */

#pragma once

#include <stdio.h>
#include "..\..\tpcc_com_ps\src\tpcc_com_ps.h"

// need to declare functions for import, unless define has already been
// created
// by the DLL's .cpp module for export.
#ifndef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class CCOMERR : public CBaseErr
{
private:
    char m_szErrorText[64];

public:
    // use this interface for genuine COM errors
    CCOMERR( HRESULT hr )
    {
        m_hr = hr;
        m_iErrorType = 0;
        m_iError = 0;
    }

    // use this interface to impersonate a non-COM error type
    CCOMERR( int iErrorType, int iError )
    {
        m_iErrorType = iErrorType;
        m_iError = iError;
        m_hr = S_OK;
    }

    int     m_hr;
    int     m_iErrorType;
    int     m_iError;
}

```

```

// A CCOMERR class can impersonate another class, which happens if
the error // was not actually a COM Services error, but was simply
transmitted back via COM.
int ErrorType()
{
    if (m_iErrorType == 0)
        return ERR_TYPE_COM;
    else
        return m_iErrorType;
}

int ErrorNum() {return m_hr;}

char *ErrorText()
{
    if (m_hr == S_OK)
        sprintf( m_szErrorText, "Error: Class %d, error # %d",
m_iErrorType, m_iError );
    else
        sprintf( m_szErrorText, "Error: COM HRESULT %x", m_hr
);
    return m_szErrorText;
};

};

class DllDecl CTPCC_COM : public CTPCC_BASE
{
private:
    BOOL m_bSinglePool;

    // COM Interface pointers
    ITPCC*      m_pNewOrder;
    ITPCC*      m_pPayment;
    ITPCC*      m_pStockLevel;
    ITPCC*      m_pOrderStatus;

    struct COM_DATA
    {
        int ErrorType;
        int error;
        union
        {
            NEW_ORDER_DATA      NewOrder;
            PAYMENT_DATA         Payment;
            DELIVERY_DATA        Delivery;
            STOCK_LEVEL_DATA     StockLevel;
            ORDER_STATUS_DATA    OrderStatus;
        } u;
    } *m_pTxn;

    VARIANT m_vTxn;
public:
    CTPCC_COM(BOOL bSinglePool);
    ~CTPCC_COM(void);

```

```

        inline PNEW_ORDER_DATA      BuffAddr_NewOrder()      { return
&m_pTxn->u.NewOrder; };
        inline PPAYMENT_DATA        BuffAddr_Payment()       { return
&m_pTxn->u.Payment; };
        inline PDELIVERY_DATA       BuffAddr_Delivery()      { return
&m_pTxn->u.Delivery; };
        inline PSTOCK_LEVEL_DATA    BuffAddr_StockLevel()    { return
&m_pTxn->u.StockLevel; };
        inline PORDER_STATUS_DATA   BuffAddr_OrderStatus()   { return
&m_pTxn->u.OrderStatus; };

        void NewOrder      ();
        void Payment       ();
        void StockLevel    ();
        void OrderStatus   ();
        void Delivery      () { throw new CCOMERR(E_NOTIMPL); } // not
supported
};

inline void ReleaseInterface(IUnknown *pUnk)
{
    if (pUnk)
    {
        pUnk->Release();
        pUnk = NULL;
    }
}

// wrapper routine for class constructor
extern "C" __declspec(dllexport) CTPCC_COM* CTPCC_COM_new(BOOL);

typedef CTPCC_COM* (TYPE_CTPCC_COM)(BOOL);

/* FILE: METHODS.H
* Microsoft TPC-C Kit Ver. 4.20.000
* Copyright Microsoft, 1999
* All Rights Reserved
*
* not yet audited
*
* PURPOSE: Header file for COM components.
* Change history:
* 4.20.000 - first version
*/

enum COMPONENT_ERROR
{
    ERR_MISSING_REGISTRY_ENTRIES = 1,
    ERR_LOADDLL_FAILED,
    ERR_GETPROCADDR_FAILED,

```

```

ERR_UNKNOWN_DB_PROTOCOL
};

class CCOMPONENT_ERR : public CBaseErr
{
public:
    CCOMPONENT_ERR(COMPONENT_ERROR Err)
    {
        m_Error = Err;
        m_szTextDetail = NULL;
        m_SystemErr = 0;
        m_szErrorText = NULL;
    };

    CCOMPONENT_ERR(COMPONENT_ERROR Err, char *szTextDetail, DWORD
dwSystemErr)
    {
        m_Error = Err;
        m_szTextDetail = new char[strlen(szTextDetail)+1];
        strcpy( m_szTextDetail, szTextDetail );
        m_SystemErr = dwSystemErr;
        m_szErrorText = NULL;
    };

    ~CCOMPONENT_ERR()
    {
        if (m_szTextDetail != NULL)
            delete [] m_szTextDetail;
        if (m_szErrorText != NULL)
            delete [] m_szErrorText;
    };

    COMPONENT_ERROR m_Error;
    char            *m_szTextDetail;
    char            *m_szErrorText;
    DWORD           m_SystemErr;

    int ErrorType() {return ERR_TYPE_COMPONENT;};
    int ErrorNum() {return m_Error;};
    char *ErrorText();
};

static void WriteMessageToEventLog(LPTSTR lpszMsg);

/////////////////////////////////////////////////////////////////
/
// CTPCC_Common
class CTPCC_Common :
    public ITPCC,
    public IObjectControl,
    public IObjectConstruct,
    public CComObjectRootEx<CComSingleThreadModel>
{

```

```

public:
BEGIN_COM_MAP(CTPCC_Common)
    COM_INTERFACE_ENTRY(ITPCC)
    COM_INTERFACE_ENTRY(IObjectControl)
    COM_INTERFACE_ENTRY(IObjectConstruct)
END_COM_MAP()

    CTPCC_Common();
    ~CTPCC_Common();

// ITPCC
public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn);
    HRESULT __stdcall Payment(          int* iSize, UCHAR** txn);
    HRESULT __stdcall Delivery(         int* iSize, UCHAR** txn) {return
E_NOTIMPL;};
    HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn);
    HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn);

    HRESULT __stdcall CallSetComplete();

// IObjectControl
    STDMETHODIMP_(BOOL) CanBePooled() { return m_bCanBePooled; }
    STDMETHODIMP Activate() { return S_OK; } // we don't support COM
Services transactions (no enlistment)
    STDMETHODIMP_(void) Deactivate() { /* nothing to do */ }

// IObjectConstruct
    STDMETHODIMP Construct(IDispatch * pUnk);

// helper methods
private:
    BOOL            m_bCanBePooled;
    CTPCC_BASE *m_pTxn;

    struct COM_DATA
    {
        int retval;
        int error;
        union
        {
            NEW_ORDER_DATA      NewOrder;
            PAYMENT_DATA         Payment;
            DELIVERY_DATA        Delivery;
            STOCK_LEVEL_DATA     StockLevel;
            ORDER_STATUS_DATA    OrderStatus;
        } u;
    };
};

/////////////////////////////////////////////////////////////////
/
// CTPCC
class CTPCC :

```

```

        public CTPCC_Common,
        public CComCoClass<CTPCC, &CLSID_TPCC>
    {
    public:
    DECLARE_REGISTRY_RESOURCEID(IDR_TPCC)

    BEGIN_COM_MAP(CTPCC)
        COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
    END_COM_MAP()

    };

    ///////////////////////////////////////////////////////////////////
    /
    // CNewOrder
    class CNewOrder :
        public CTPCC_Common,
        public CComCoClass<CNewOrder, &CLSID_NewOrder>
    {
    public:
    DECLARE_REGISTRY_RESOURCEID(IDR_NEWORDER)

    BEGIN_COM_MAP(CNewOrder)
        COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
    END_COM_MAP()

    // ITPCC
    public:
    // HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    // HRESULT __stdcall Payment(         int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    // HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    // HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    };

    ///////////////////////////////////////////////////////////////////
    // COrderStatus
    class COrderStatus :
        public CTPCC_Common,
        public CComCoClass<COrderStatus, &CLSID_OrderStatus>
    {
    public:
    DECLARE_REGISTRY_RESOURCEID(IDR_ORDERSTATUS)

    BEGIN_COM_MAP(COrderStatus)
        COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)

```

```

    END_COM_MAP()

    // ITPCC
    public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    HRESULT __stdcall Payment(         int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    // HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    };

    ///////////////////////////////////////////////////////////////////
    /
    // CPayment
    class CPayment :
        public CTPCC_Common,
        public CComCoClass<CPayment, &CLSID_Payment>
    {
    public:
    DECLARE_REGISTRY_RESOURCEID(IDR_PAYMENT)

    BEGIN_COM_MAP(CPayment)
        COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
    END_COM_MAP()

    // ITPCC
    public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    // HRESULT __stdcall Payment(         int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn) {return
    E_NOTIMPL;}
    };

    ///////////////////////////////////////////////////////////////////
    /
    // CStockLevel
    class CStockLevel :
        public CTPCC_Common,
        public CComCoClass<CStockLevel, &CLSID_StockLevel>
    {
    public:
    DECLARE_REGISTRY_RESOURCEID(IDR_STOCKLEVEL)

    BEGIN_COM_MAP(CStockLevel)
        COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)

```

```

        COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
END_COM_MAP()

// ITPCC
public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall Payment(         int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    // HRESULT __stdcall StockLevel(   int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
};

//{{{NO_DEPENDENCIES}}
// Microsoft Developer Studio generated include file.
// Used by tpcc_com_all.rc
//
#define IDS_PROJNAME                100
#define IDR_TPCC                    101
#define IDR_NEWORDER                102
#define IDR_ORDERSTATUS             103
#define IDR_PAYMENT                 104
#define IDR_STOCKLEVEL              105

// Next default values for new objects
//
#ifdef APSTUDIO_INVOKED
#ifdef APSTUDIO_READONLY_SYMBOLS
#define _APS_NEXT_RESOURCE_VALUE    202
#define _APS_NEXT_COMMAND_VALUE    32768
#define _APS_NEXT_CONTROL_VALUE    201
#define _APS_NEXT_SYMED_VALUE      106
#endif
#endif

/* FILE:      TPCC_COM_ALL.CPP
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE:   Implementation for TPC-C Tuxedo class.
 * Contact:   Charles Levine (clevine@microsoft.com)
 *
 * Change history:
 * 4.20.000 - updated rev number to match kit
 */

#define STRICT
#define _WIN32_WINNT 0x0400

```

```

#define _ATL_APARTMENT_THREADED

#include <stdio.h>
#include <atlbase.h>
//You may derive a class from CComModule and use it if you want to override
//something, but do not change the name of _Module
extern CComModule _Module;

#include <atlcom.h>
#include <initguid.h>
#include <transact.h>
#include <atlimpl.cpp>
#include <comsvcs.h>

#include <sqltypes.h>
#include <sql.h>
#include <sqlext.h>

#include "tpcc_com_ps.h"
#include "..\..\common\src\trans.h" //tpckit
transaction header contains definitions of structures specific to TPC-C
#include "..\..\common\src\txn_base.h"
#include "..\..\common\src\error.h"
#include "..\..\common\src\ReadRegistry.h"
#include "..\..\db_dblib_dll\src\tpcc_dblib.h" // DBLIB implementation
of TPC-C txns
#include "..\..\db_odbc_dll\src\tpcc_odbc.h" // ODBC implementation
of TPC-C txns

#include "resource.h"
#include "tpcc_com_all.h"
#include "tpcc_com_all_i.c"
#include "Methods.h"
#include "..\..\tpcc_com_ps\src\tpcc_com_ps_i.c"
#include "..\..\common\src\ReadRegistry.cpp"

CComModule _Module;

BEGIN_OBJECT_MAP(ObjectMap)
    OBJECT_ENTRY(CLSID_TPCC, CTPCC)
    OBJECT_ENTRY(CLSID_NewOrder, CNewOrder)
    OBJECT_ENTRY(CLSID_OrderStatus, COrderStatus)
    OBJECT_ENTRY(CLSID_Payment, CPayment)
    OBJECT_ENTRY(CLSID_StockLevel, CStockLevel)
END_OBJECT_MAP()

// configuration settings from registry
TPCCREGISTRYDATA Reg;
char szMyComputerName[MAX_COMPUTERNAME_LENGTH+1];

static HINSTANCE hLibInstanceDb = NULL;

```

```

TYPE_CTPCC_DBLIB      *pCTPCC_DBLIB_new;
TYPE_CTPCC_ODBC       *pCTPCC_ODBC_new;

////////////////////////////////////
/
// DLL Entry Point

extern "C"
BOOL WINAPI DllMain(HINSTANCE hInstance, DWORD dwReason, LPVOID
/*lpReserved*/)
{
    char szDllName[128];

    try
    {
        if (dwReason == DLL_PROCESS_ATTACH)
        {
            _Module.Init(ObjectMap, hInstance);
            DisableThreadLibraryCalls(hInstance);

            DWORD dwSize = MAX_COMPUTERNAME_LENGTH+1;
            GetComputerName(szMyComputerName, &dwSize);
            szMyComputerName[dwSize] = 0;

            if ( ReadTPCCRegistrySettings( &Reg ) )
                throw new CCOMPONENT_ERR( ERR_MISSING_REGISTRY_ENTRIES
);

            if (Reg.eDB_Protocol == DBLIB)
            {
                strcpy( szDllName, Reg.szPath );
                strcat( szDllName, "tpcc_dblib.dll");
                hLibInstanceDb = LoadLibrary( szDllName );
                if (hLibInstanceDb == NULL)
                    throw new CCOMPONENT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

                // get function pointer to wrapper for class
            constructor
                pCTPCC_DBLIB_new = (TYPE_CTPCC_DBLIB*)
GetProcAddress(hLibInstanceDb, "CTPCC_DBLIB_new");
                if (pCTPCC_DBLIB_new == NULL)
                    throw new CCOMPONENT_ERR( ERR_GETPROCADDR_FAILED,
szDllName, GetLastError() );
            }
            else if (Reg.eDB_Protocol == ODBC)
            {
                strcpy( szDllName, Reg.szPath );
                strcat( szDllName, "tpcc_odbc.dll");
                hLibInstanceDb = LoadLibrary( szDllName );
                if (hLibInstanceDb == NULL)
                    throw new CCOMPONENT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );
            }
        }
    }
}

```

```

// get function pointer to wrapper for class
constructor
    pCTPCC_ODBC_new = (TYPE_CTPCC_ODBC*)
GetProcAddress(hLibInstanceDb, "CTPCC_ODBC_new");
    if (pCTPCC_ODBC_new == NULL)
        throw new CCOMPONENT_ERR( ERR_GETPROCADDR_FAILED,
szDllName, GetLastError() );
    }
    else
        throw new CCOMPONENT_ERR( ERR_UNKNOWN_DB_PROTOCOL );
}
else if (dwReason == DLL_PROCESS_DETACH)
    _Module.Term();

}
catch (CBaseErr *e)
{
    WriteMessageToEventLog(e->ErrorText());
    delete e;
    return FALSE;
}
catch (...)
{
    WriteMessageToEventLog(TEXT("Unhandled exception in object
DllMain"));
    return FALSE;
}

return TRUE;    // OK
}

////////////////////////////////////
/
// Used to determine whether the DLL can be unloaded by OLE
STDAPI DllCanUnloadNow(void)
{
    return (_Module.GetLockCount()==0) ? S_OK : S_FALSE;
}

////////////////////////////////////
/
// Returns a class factory to create an object of the requested type
STDAPI DllGetClassObject(REFCLSID rclsid, REFIID riid, LPVOID* ppv)
{
    return _Module.GetClassObject(rclsid, riid, ppv);
}

////////////////////////////////////
/
// DllRegisterServer - Adds entries to the system registry
STDAPI DllRegisterServer(void)
{

```

```

    // registers object, typelib and all interfaces in typelib
    return _Module.RegisterServer(TRUE);
}

////////////////////////////////////
/
// DllUnregisterServer - Removes entries from the system registry

STDAPI DllUnregisterServer(void)
{
    _Module.UnregisterServer();
    return S_OK;
}

static void WriteMessageToEventLog(LPTSTR lpszMsg)
{
    TCHAR    szMsg[256];
    HANDLE   hEventSource;
    LPTSTR   lpszStrings[2];

    // Use event logging to log the error.
    //
    hEventSource = RegisterEventSource(NULL, TEXT("tpcc_com_all.dll"));

    _stprintf(szMsg, TEXT("Error in COM+ TPC-C Component: "));
    lpszStrings[0] = szMsg;
    lpszStrings[1] = lpszMsg;

    if (hEventSource != NULL)
    {
        ReportEvent(hEventSource, // handle of event source
            EVENTLOG_ERROR_TYPE, // event type
            0, // event category
            0, // event ID
            NULL, // current user's SID
            2, // strings in lpszStrings
            0, // no bytes of raw data
            (LPTSTR *)lpszStrings, // array of error strings
            NULL); // no raw data

        (VOID) DeregisterEventSource(hEventSource);
    }
}

inline void ReleaseInterface(IUnknown *pUnk)
{
    if (pUnk)
    {
        pUnk->Release();
        pUnk = NULL;
    }
}

/* FUNCTION: CCOMPONENT_ERR::ErrorText

```

```

*
*/
char* CCOMPONENT_ERR::ErrorText(void)
{
    static SERRORMSG errorMsgs[] =
    {
        { ERR_MISSING_REGISTRY_ENTRIES, "Required entries missing from
registry." },
        { ERR_LOADDLL_FAILED, "Load of DLL failed. DLL="
},
        { ERR_GETPROCADDR_FAILED, "Could not map proc in DLL.
GetProcAddress error. DLL=" },
        { ERR_UNKNOWN_DB_PROTOCOL, "Unknown database protocol
specified in registry." },
        { 0, ""
}
    };

    char szTmp[256];
    int i = 0;
    while (TRUE)
    {
        if (errorMsgs[i].szMsg[0] == 0)
        {
            strcpy( szTmp, "Unknown error number." );
            break;
        }
        if (m_Error == errorMsgs[i].iError)
        {
            strcpy( szTmp, errorMsgs[i].szMsg );
            break;
        }
        i++;
    }

    if (m_szTextDetail)
        strcat( szTmp, m_szTextDetail );
    if (m_SystemErr)
        wsprintf( szTmp+strlen(szTmp), " Error=%d", m_SystemErr );

    m_szErrorText = new char[strlen(szTmp)+1];
    strcpy( m_szErrorText, szTmp );
    return m_szErrorText;
}

CTPCC_Common::CTPCC_Common()
{
    m_pTxn = NULL;
    m_bCanBePooled = TRUE;
}

CTPCC_Common::~~CTPCC_Common()
{
}

```

```

        if (m_pTxn)
            delete m_pTxn;
    }

HRESULT CTPCC_Common::CallSetComplete()
{
    IObjectContext* pObjectContext = NULL;

    // get our object context
    HRESULT hr = CoGetObjectContext( IID_IObjectContext, (void
**)&pObjectContext );
    pObjectContext->SetComplete();
    ReleaseInterface(pObjectContext);
    return hr;
}

//
// called by the ctor activator
//
STDMETHODIMP CTPCC_Common::Construct(IDispatch * pUnk)
{
    // Code to access construction string, if needed later...
    // if (!pUnk)
    //     return E_UNEXPECTED;
    // IObjectConstructString * pString = NULL;
    // HRESULT hr = pUnk->QueryInterface(IID_IObjectConstructString,
(void **)&pString);
    // pString->Release();

    try
    {
        if (Reg.eDB_Protocol == ODBC)
            m_pTxn = pCTPCC_ODBC_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
        else if (Reg.eDB_Protocol == DBLIB)
            m_pTxn = pCTPCC_DBLIB_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
    }
    catch (CBaseErr *e)
    {
        WriteMessageToEventLog(e->ErrorText());
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception in object
::Construct"));
        return E_FAIL;
    }

    return S_OK;
}

HRESULT CTPCC_Common::NewOrder(int* iSize, UCHAR **txn)

```

```

{
    PNEW_ORDER_DATA pNewOrder;
    COM_DATA *pData;

    try
    {
        pData = (COM_DATA*)*txn;
        pNewOrder = m_pTxn->BuffAddr_NewOrder();

        memcpy(pNewOrder, &pData->u.NewOrder, sizeof(NEW_ORDER_DATA));
        m_pTxn->NewOrder();
        memcpy( &pData->u.NewOrder, pNewOrder, sizeof(NEW_ORDER_DATA));

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database connection; if yes, component is toast
        if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
            ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==
10054)) )
            m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception.));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

HRESULT CTPCC_Common::Payment(int* iSize, UCHAR** txn)
{
    PPAYMENT_DATA pPayment;
    COM_DATA *pData;

    try
    {
        pData = (COM_DATA*)*txn;
        pPayment = m_pTxn->BuffAddr_Payment();

        memcpy(pPayment, &pData->u.Payment, sizeof(PAYMENT_DATA) );
        m_pTxn->Payment();
        memcpy( &pData->u.Payment, pPayment, sizeof(PAYMENT_DATA) );
    }
}

```

```

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database connection; if yes, component is toast
        if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
10054)) )
            ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==

                m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception.));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

HRESULT CTPCC_Common::StockLevel(int* iSize, UCHAR** txn)
{
    PSTOCK_LEVEL_DATA    pStockLevel;
    COM_DATA              *pData;

    try
    {
        pData = (COM_DATA*)*txn;
        pStockLevel = m_pTxn->BuffAddr_StockLevel();

        memcpy(pStockLevel, &pData->u.StockLevel, sizeof(STOCK_LEVEL_DATA)
);
        m_pTxn->StockLevel();
        memcpy( &pData->u.StockLevel, pStockLevel,
sizeof(STOCK_LEVEL_DATA) );

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database connection; if yes, component is toast
        if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
10054)) )
            ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==

```

```

        m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception.));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

HRESULT CTPCC_Common::OrderStatus(int* iSize, UCHAR** txn)
{
    PORDER_STATUS_DATA  pOrderStatus;
    COM_DATA              *pData;

    try
    {
        pData = (COM_DATA*)*txn;
        pOrderStatus = m_pTxn->BuffAddr_OrderStatus();

        memcpy(pOrderStatus, &pData->u.OrderStatus,
sizeof(ORDER_STATUS_DATA) );
        m_pTxn->OrderStatus();
        memcpy( &pData->u.OrderStatus, pOrderStatus,
sizeof(ORDER_STATUS_DATA) );

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database connection; if yes, component is toast
        if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
10054)) )
            ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==

                m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception.));
        pData->retval = ERR_TYPE_LOGIC;

```

```

        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

; tpcc_com_all.def : Declares the module parameters.

LIBRARY      "tpcc_com_all.dll"

EXPORTS
    DllCanUnloadNow      @1 PRIVATE
    DllGetClassObject    @2 PRIVATE
    DllRegisterServer    @3 PRIVATE
    DllUnregisterServer  @4 PRIVATE

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the definitions for the interfaces */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:20 2000
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
    Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
    error checks: allocation ref bounds_check enum stub_data
    VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

/* verify that the <rpcndr.h> version is high enough to compile this file*/
#ifndef __REQUIRED_RPCNDR_H_VERSION__
#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

#include "rpc.h"
#include "rpcndr.h"

#ifndef __tpcc_com_all_h__
#define __tpcc_com_all_h__

/* Forward Declarations */

#ifndef __TPCC_FWD_DEFINED__
#define __TPCC_FWD_DEFINED__

#ifdef __cplusplus
typedef class TPCC TPCC;
#else
typedef struct TPCC TPCC;
#endif

```

```

#endif /* __cplusplus */

#endif /* __TPCC_FWD_DEFINED__ */

#ifndef __NewOrder_FWD_DEFINED__
#define __NewOrder_FWD_DEFINED__

#ifdef __cplusplus
typedef class NewOrder NewOrder;
#else
typedef struct NewOrder NewOrder;
#endif /* __cplusplus */

#endif /* __NewOrder_FWD_DEFINED__ */

#ifndef __OrderStatus_FWD_DEFINED__
#define __OrderStatus_FWD_DEFINED__

#ifdef __cplusplus
typedef class OrderStatus OrderStatus;
#else
typedef struct OrderStatus OrderStatus;
#endif /* __cplusplus */

#endif /* __OrderStatus_FWD_DEFINED__ */

#ifndef __Payment_FWD_DEFINED__
#define __Payment_FWD_DEFINED__

#ifdef __cplusplus
typedef class Payment Payment;
#else
typedef struct Payment Payment;
#endif /* __cplusplus */

#endif /* __Payment_FWD_DEFINED__ */

#ifndef __StockLevel_FWD_DEFINED__
#define __StockLevel_FWD_DEFINED__

#ifdef __cplusplus
typedef class StockLevel StockLevel;
#else
typedef struct StockLevel StockLevel;
#endif /* __cplusplus */

#endif /* __StockLevel_FWD_DEFINED__ */

/* header files for imported files */
#include "oaidl.h"

```

```

#include "ocidl.h"
#include "tpcc_com_ps.h"

#ifdef __cplusplus
extern "C"{
#endif

void __RPC_FAR * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void __RPC_FAR * );

/* interface __MIDL_itf_tpcc_com_all_0000 */
/* [local] */

extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_all_0000_v0_0_c_ifspec;
extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_all_0000_v0_0_s_ifspec;

#ifndef __TPCCLib_LIBRARY_DEFINED__
#define __TPCCLib_LIBRARY_DEFINED__

/* library TPCCLib */
/* [helpstring][version][uuid] */

EXTERN_C const IID LIBID_TPCCLib;

EXTERN_C const CLSID CLSID_TPCC;

#ifdef __cplusplus
class DECLSPEC_UUID("122A3128-2520-11D3-BA71-00C04FBFE08B")
TPCC;
#endif

EXTERN_C const CLSID CLSID_NewOrder;

#ifdef __cplusplus
class DECLSPEC_UUID("975BAABF-84A7-11D2-BA47-00C04FBFE08B")
NewOrder;
#endif

EXTERN_C const CLSID CLSID_OrderStatus;

#ifdef __cplusplus
class DECLSPEC_UUID("266836AD-A50D-11D2-BA4E-00C04FBFE08B")
OrderStatus;

```

```

#endif

EXTERN_C const CLSID CLSID_Payment;

#ifdef __cplusplus
class DECLSPEC_UUID("CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B")
Payment;
#endif

EXTERN_C const CLSID CLSID_StockLevel;

#ifdef __cplusplus
class DECLSPEC_UUID("2668369E-A50D-11D2-BA4E-00C04FBFE08B")
StockLevel;
#endif
#endif /* __TPCCLib_LIBRARY_DEFINED__ */

/* Additional Prototypes for ALL interfaces */
/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif

#endif

/* FILE: TPCC.IDL
 * Microsoft TPC-C Kit Ver. 4.20.000
 * Copyright Microsoft, 1999
 * All Rights Reserved
 *
 * not yet audited
 *
 * PURPOSE: IDL source for TPCC.dll. This file is processed by the MIDL
tool to
 * produce the type library (TPCC.tlb) and marshalling
code.
 *
 * Change history:
 * 4.20.000 - first version
 */

interface TPCC;
interface NewOrder;
interface OrderStatus;
interface Payment;
interface StockLevel;

import "oidl.idl";

```



```

    "1 TYPELIB "tpcc_com_all.tlb"\r\n"
    "\0"
END

#endif // APSTUDIO_INVOKED

#ifdef _MAC
////////////////////////////////////
/
//
// Version
//
VS_VERSION_INFO VERSIONINFO
FILEVERSION 1,0,0,1
PRODUCTVERSION 1,0,0,1
FILEFLAGSMASK 0x3fL
#ifdef _DEBUG
FILEFLAGS 0x1L
#else
FILEFLAGS 0x0L
#endif
FILEOS 0x4L
FILETYPE 0x2L
FILESUBTYPE 0x0L
BEGIN
    BLOCK "StringFileInfo"
    BEGIN
        BLOCK "040904B0"
        BEGIN
            VALUE "CompanyName", "\0"
            VALUE "FileDescription", "tpcc_com_all Module\0"
            VALUE "FileVersion", "1, 0, 0, 1\0"
            VALUE "InternalName", "TPCCNEWORDER\0"
            VALUE "LegalCopyright", "Copyright 1997\0"
            VALUE "OriginalFilename", "tpcc_com_all.DLL\0"
            VALUE "ProductName", "tpcc_com_all Module\0"
            VALUE "ProductVersion", "1, 0, 0, 1\0"
            VALUE "OLESelfRegister", "\0"
        END
    END
    BLOCK "VarFileInfo"
    BEGIN
        VALUE "Translation", 0x409, 1200
    END
END
#endif // !_MAC

////////////////////////////////////
/
//
// REGISTRY

```

```

//
IDR_TPCC                REGISTRY DISCARDABLE    "tpcc_com_all.rgs"
IDR_NEWORDER            REGISTRY DISCARDABLE    "tpcc_com_no.rgs"
IDR_ORDERSTATUS         REGISTRY DISCARDABLE    "tpcc_com_os.rgs"
IDR_PAYMENT              REGISTRY DISCARDABLE    "tpcc_com_pay.rgs"
IDR_STOCKLEVEL          REGISTRY DISCARDABLE    "tpcc_com_sl.rgs"
////////////////////////////////////
/
//
// String Table
//
STRINGTABLE DISCARDABLE
BEGIN
    IDS_PROJNAME            "tpcc_com_all"
END

#endif // English (U.S.) resources
////////////////////////////////////
/
#ifdef APSTUDIO_INVOKED
////////////////////////////////////
/
//
// Generated from the TEXTINCLUDE 3 resource.
//
1 TYPELIB "tpcc_com_all.tlb"
////////////////////////////////////
/
#endif // not APSTUDIO_INVOKED

HKCR
{
    TPCC.AllTxns.1 = s 'All Txns Class'
    {
        CLSID = s '{122A3128-2520-11D3-BA71-00C04FBFE08B}'
    }
    TPCC.AllTxns = s 'TPCC Class'
    {
        CurVer = s 'TPCC.AllTxns.1'
    }
    NoRemove CLSID
    {
        ForceRemove {122A3128-2520-11D3-BA71-00C04FBFE08B} = s 'TPCC
Class'
        {
            ProgID = s 'TPCC.AllTxns.1'
            VersionIndependentProgID = s 'TPCC.AllTxns'

```

```

        InprocServer32 = s '%MODULE%'
        {
            val ThreadingModel = s 'Both'
        }
    }
}

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */

/* link this file in with the server and any clients */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:20 2000
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
   Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
   error checks: allocation ref bounds_check enum stub_data
   VC __declspec() decoration level:
       __declspec(uuid()), __declspec(selectany), __declspec(novtable)
       DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

#if !defined(_M_IA64) && !defined(_M_AXP64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
        DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

```

```

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
LIBID_TPCClib,0x122A3117,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_TPCC,0x122A3128,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x8B)
;

MIDL_DEFINE_GUID(CLSID,
CLSID_NewOrder ,0x975BAABF,0x84A7,0x11D2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_OrderStatus,0x266836AD,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_Payment,0xCD02F7EF,0xA4FA,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_StockLevel,0x2668369E,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif
#endif

```

```

#endif /* !defined(_M_IA64) && !defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */

/* link this file in with the server and any clients */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:20 2000
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
    Oicf (OptLev=i2), Wl, Zp8, env=Win64 (32b run,appending), ms_ext, c_ext,
robust
    error checks: allocation ref bounds_check enum stub_data
    VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

#if defined(_M_IA64) || defined(_M_AXP64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
        DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID

```

```

{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char  c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
LIBID_TPCCLib,0x122A3117,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_TPCC,0x122A3128,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x8B)
;

MIDL_DEFINE_GUID(CLSID,
CLSID_NewOrder ,0x975BAABF,0x84A7,0x11D2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_OrderStatus,0x266836AD,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_Payment,0xCD02F7EF,0xA4FA,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_StockLevel,0x2668369E,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

```

```

#endif /* defined(_M_IA64) || defined(_M_AXP64)*/

HKCR
{
    TPCC.NewOrder.1 = s 'NewOrder Class'
    {
        CLSID = s '{975BAABF-84A7-11D2-BA47-00C04FBFE08B}'
    }
    TPCC.NewOrder = s 'NewOrder Class'
    {
        CurVer = s 'TPCC.NewOrder.1'
    }
    NoRemove CLSID
    {
        ForceRemove {975BAABF-84A7-11D2-BA47-00C04FBFE08B} = s 'NewOrder
Class'
        {
            ProgID = s 'TPCC.NewOrder.1'
            VersionIndependentProgID = s 'TPCC.NewOrder'
            InprocServer32 = s '%MODULE%'
            {
                val ThreadingModel = s 'Both'
            }
        }
    }
}

HKCR
{
    TPCC.OrderStatus.1 = s 'OrderStatus Class'
    {
        CLSID = s '{266836AD-A50D-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.OrderStatus = s 'OrderStatus Class'
    {
        CurVer = s 'TPCC.OrderStatus.1'
    }
    NoRemove CLSID
    {
        ForceRemove {266836AD-A50D-11D2-BA4E-00C04FBFE08B} = s
'OrderStatus Class'
        {
            ProgID = s 'TPCC.OrderStatus.1'
            VersionIndependentProgID = s 'TPCC.OrderStatus'
            InprocServer32 = s '%MODULE%'
            {
                val ThreadingModel = s 'Both'
            }
        }
    }
}

HKCR

```

```

{
    TPCC.Payment.1 = s 'Payment Class'
    {
        CLSID = s '{CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.Payment = s 'Payment Class'
    {
        CurVer = s 'TPCC.Payment.1'
    }
    NoRemove CLSID
    {
        ForceRemove {CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B} = s 'Payment
Class'
        {
            ProgID = s 'TPCC.Payment.1'
            VersionIndependentProgID = s 'TPCC.Payment'
            InprocServer32 = s '%MODULE%'
            {
                val ThreadingModel = s 'Both'
            }
        }
    }
}

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the definitions for the interfaces */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:07 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany), __declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

/* verify that the <rpcndr.h> version is high enough to compile this file*/
#ifndef __REQUIRED_RPCNDR_H_VERSION__
#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

#include "rpc.h"
#include "rpcndr.h"

#ifndef __RPCNDR_H_VERSION__
#error this stub requires an updated version of <rpcndr.h>
#endif // __RPCNDR_H_VERSION__

```

```

#ifndef COM_NO_WINDOWS_H
#include "windows.h"
#include "ole2.h"
#endif /*COM_NO_WINDOWS_H*/

#ifndef __tpcc_com_ps_h__
#define __tpcc_com_ps_h__

/* Forward Declarations */

#ifndef __ITPCC_FWD_DEFINED__
#define __ITPCC_FWD_DEFINED__
typedef interface ITPCC ITPCC;
#endif /* __ITPCC_FWD_DEFINED__ */

/* header files for imported files */
#include "oaidl.h"
#include "ocidl.h"

#ifdef __cplusplus
extern "C"{
#endif

void __RPC_FAR * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void __RPC_FAR * );

#ifndef __ITPCC_INTERFACE_DEFINED__
#define __ITPCC_INTERFACE_DEFINED__

/* interface ITPCC */
/* [unique][helpstring][uuid][object] */

EXTERN_C const IID IID_ITPCC;

#if defined(__cplusplus) && !defined(CINTERFACE)

    MIDL_INTERFACE("FEEE6AA2-84B1-11d2-BA47-00C04FBFE08B")
    ITPCC : public IUnknown
    {
    public:
        virtual HRESULT __stdcall NewOrder(
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            * __RPC_FAR *txn) = 0;

        virtual HRESULT __stdcall Payment(
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            * __RPC_FAR *txn) = 0;

        virtual HRESULT __stdcall Delivery(
            /* [in] */ int __RPC_FAR *iSize,

```

```

            /* [size_is][size_is][in] */ unsigned char __RPC_FAR * __RPC_FAR
            *txn) = 0;

        virtual HRESULT __stdcall StockLevel(
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            * __RPC_FAR *txn) = 0;

        virtual HRESULT __stdcall OrderStatus(
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            * __RPC_FAR *txn) = 0;

        virtual HRESULT __stdcall CallSetComplete( void) = 0;

    };
#else /* C style interface */

    typedef struct ITPCCVtbl
    {
        BEGIN_INTERFACE

        HRESULT ( STDMETHODCALLTYPE __RPC_FAR *QueryInterface )(
            ITPCC __RPC_FAR * This,
            /* [in] */ REFIID riid,
            /* [iid_is][out] */ void __RPC_FAR * __RPC_FAR *ppvObject);

        ULONG ( STDMETHODCALLTYPE __RPC_FAR *AddRef )(
            ITPCC __RPC_FAR * This);

        ULONG ( STDMETHODCALLTYPE __RPC_FAR *Release )(
            ITPCC __RPC_FAR * This);

        HRESULT ( STDMETHODCALLTYPE __RPC_FAR *NewOrder )(
            ITPCC __RPC_FAR * This,
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            * __RPC_FAR *txn);

        HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Payment )(
            ITPCC __RPC_FAR * This,
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            * __RPC_FAR *txn);

        HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Delivery )(
            ITPCC __RPC_FAR * This,
            /* [in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][in] */ unsigned char __RPC_FAR * __RPC_FAR
            *txn);

        HRESULT ( STDMETHODCALLTYPE __RPC_FAR *StockLevel )(
            ITPCC __RPC_FAR * This,
            /* [out][in] */ int __RPC_FAR *iSize,

```

```

        /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
*_RPC_FAR *txn);

        HRESULT ( __stdcall __RPC_FAR *OrderStatus )(
            ITPCC __RPC_FAR * This,
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
*_RPC_FAR *txn);

        HRESULT ( __stdcall __RPC_FAR *CallSetComplete )(
            ITPCC __RPC_FAR * This);

        END_INTERFACE
    } ITPCCVtbl;

interface ITPCC
{
    CONST_VTBL struct ITPCCVtbl __RPC_FAR *lpVtbl;
};

#ifdef COBJMACROS

#define ITPCC_QueryInterface(This,riid,ppvObject) \
    (This)->lpVtbl -> QueryInterface(This,riid,ppvObject)

#define ITPCC_AddRef(This) \
    (This)->lpVtbl -> AddRef(This)

#define ITPCC_Release(This) \
    (This)->lpVtbl -> Release(This)

#define ITPCC_NewOrder(This,iSize,txn) \
    (This)->lpVtbl -> NewOrder(This,iSize,txn)

#define ITPCC_Payment(This,iSize,txn) \
    (This)->lpVtbl -> Payment(This,iSize,txn)

#define ITPCC_Delivery(This,iSize,txn) \
    (This)->lpVtbl -> Delivery(This,iSize,txn)

#define ITPCC_StockLevel(This,iSize,txn) \
    (This)->lpVtbl -> StockLevel(This,iSize,txn)

#define ITPCC_OrderStatus(This,iSize,txn) \
    (This)->lpVtbl -> OrderStatus(This,iSize,txn)

#define ITPCC_CallSetComplete(This) \
    (This)->lpVtbl -> CallSetComplete(This)

#endif /* COBJMACROS */

```

```

#endif /* C style interface */

HRESULT __stdcall ITPCC_NewOrder_Proxy(
    ITPCC __RPC_FAR * This,
    /* [out][in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
*txn);

void __RPC_STUB ITPCC_NewOrder_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Payment_Proxy(
    ITPCC __RPC_FAR * This,
    /* [out][in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
*txn);

void __RPC_STUB ITPCC_Payment_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Delivery_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][in] */ unsigned char __RPC_FAR *__RPC_FAR *txn);

void __RPC_STUB ITPCC_Delivery_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_StockLevel_Proxy(
    ITPCC __RPC_FAR * This,
    /* [out][in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
*txn);

void __RPC_STUB ITPCC_StockLevel_Stub(
    IRpcStubBuffer *This,

```

```

IRpcChannelBuffer *_pRpcChannelBuffer,
PRPC_MESSAGE _pRpcMessage,
DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_OrderStatus_Proxy(
ITPCC __RPC_FAR * This,
/* [out][in] */ int __RPC_FAR *iSize,
/* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
*txn);

void __RPC_STUB ITPCC_OrderStatus_Stub(
IRpcStubBuffer *This,
IRpcChannelBuffer *_pRpcChannelBuffer,
PRPC_MESSAGE _pRpcMessage,
DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_CallSetComplete_Proxy(
ITPCC __RPC_FAR * This);

void __RPC_STUB ITPCC_CallSetComplete_Stub(
IRpcStubBuffer *This,
IRpcChannelBuffer *_pRpcChannelBuffer,
PRPC_MESSAGE _pRpcMessage,
DWORD *_pdwStubPhase);

#endif /* __ITPCC_INTERFACE_DEFINED__ */

/* Additional Prototypes for ALL interfaces */
/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif

#endif

HKCR
{
    TPCC.StockLevel.1 = s 'StockLevel Class'
    {
        CLSID = s '{2668369E-A50D-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.StockLevel = s 'StockLevel Class'
    {
        CurVer = s 'TPCC.StockLevel.1'

```

```

    }
    NoRemove CLSID
    {
        ForceRemove {2668369E-A50D-11D2-BA4E-00C04FBFE08B} = s 'StockLevel
Class'
        {
            ProgID = s 'TPCC.StockLevel.1'
            VersionIndependentProgID = s 'TPCC.StockLevel'
            InprocServer32 = s '%MODULE%'
            {
                val ThreadingModel = s 'Both'
            }
        }
    }
}

/*****
DllData file -- generated by MIDL compiler

DO NOT ALTER THIS FILE

This file is regenerated by MIDL on every IDL file compile.

To completely reconstruct this file, delete it and rerun MIDL
on all the IDL files in this DLL, specifying this file for the
/dlldata command line option

*****/

#include <rpcproxy.h>

#ifdef __cplusplus
extern "C" {
#endif

EXTERN_PROXY_FILE( tpcc_com_ps )

PROXYFILE_LIST_START
/* Start of list */
REFERENCE_PROXY_FILE( tpcc_com_ps ),
/* End of list */
PROXYFILE_LIST_END

DLLDATA_ROUTINES( aProxyFileList, GET_DLL_CLSID )

#ifdef __cplusplus
} /*extern "C" */
#endif

/* end of generated dlldata file */

```

```

LIBRARY      "tpcc_com_ps"

DESCRIPTION  'Proxy/Stub DLL'

EXPORTS
    DllGetClassObject      @1 PRIVATE
    DllCanUnloadNow        @2 PRIVATE
    GetProxyDllInfo        @3 PRIVATE
    DllRegisterServer      @4 PRIVATE
    DllUnregisterServer    @5 PRIVATE

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the definitions for the interfaces */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
    Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
    error checks: allocation ref bounds_check enum stub_data
    VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

/* verify that the <rpcndr.h> version is high enough to compile this file*/
#ifndef __REQUIRED_RPCNDR_H_VERSION__
#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

#include "rpc.h"
#include "rpcndr.h"

#ifndef __RPCNDR_H_VERSION__
#error this stub requires an updated version of <rpcndr.h>
#endif // __RPCNDR_H_VERSION__

#ifndef COM_NO_WINDOWS_H
#include "windows.h"
#include "ole2.h"
#endif /*COM_NO_WINDOWS_H*/

#ifndef __tpcc_com_ps_h__
#define __tpcc_com_ps_h__

/* Forward Declarations */

#ifndef __ITPCC_FWD_DEFINED__
#define __ITPCC_FWD_DEFINED__
typedef interface ITPCC ITPCC;

```

```

#endif /* __ITPCC_FWD_DEFINED__ */

/* header files for imported files */
#include "oaidl.h"
#include "ocidl.h"

#ifdef __cplusplus
extern "C"{
#endif

void __RPC_FAR * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void __RPC_FAR * );

/* interface __MIDL_itf_tpcc_com_ps_0000 */
/* [local] */

extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_ps_0000_v0_0_c_ifspec;
extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_ps_0000_v0_0_s_ifspec;

#ifndef __ITPCC_INTERFACE_DEFINED__
#define __ITPCC_INTERFACE_DEFINED__

/* interface ITPCC */
/* [unique][helpstring][uuid][oleautomation][object] */

EXTERN_C const IID IID_ITPCC;

#if defined(__cplusplus) && !defined(CINTERFACE)

    MIDL_INTERFACE("FEEE6AA2-84B1-11d2-BA47-00C04FBFE08B")
    ITPCC : public IUnknown
    {
    public:
        virtual HRESULT __stdcall NewOrder(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

        virtual HRESULT __stdcall Payment(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

        virtual HRESULT __stdcall Delivery(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

        virtual HRESULT __stdcall StockLevel(
            /* [in] */ VARIANT txn_in,
            /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

        virtual HRESULT __stdcall OrderStatus(

```

```

    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

    virtual HRESULT __stdcall CallSetComplete( void) = 0;
};

#else    /* C style interface */

typedef struct ITPCCVtbl
{
    BEGIN_INTERFACE

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *QueryInterface )(
        ITPCC __RPC_FAR * This,
        /* [in] */ REFIID riid,
        /* [iid_is][out] */ void __RPC_FAR *__RPC_FAR *ppvObject);

    ULONG ( STDMETHODCALLTYPE __RPC_FAR *AddRef )(
        ITPCC __RPC_FAR * This);

    ULONG ( STDMETHODCALLTYPE __RPC_FAR *Release )(
        ITPCC __RPC_FAR * This);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *NewOrder )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Payment )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Delivery )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *StockLevel )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *OrderStatus )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *CallSetComplete )(
        ITPCC __RPC_FAR * This);

    END_INTERFACE
} ITPCCVtbl;

```

```

interface ITPCC
{
    CONST_VTBL struct ITPCCVtbl __RPC_FAR *lpVtbl;
};

#ifdef COBJMACROS

#define ITPCC_QueryInterface(This,riid,ppvObject) \
    (This)->lpVtbl -> QueryInterface(This,riid,ppvObject)

#define ITPCC_AddRef(This) \
    (This)->lpVtbl -> AddRef(This)

#define ITPCC_Release(This) \
    (This)->lpVtbl -> Release(This)

#define ITPCC_NewOrder(This,txn_in,txn_out) \
    (This)->lpVtbl -> NewOrder(This,txn_in,txn_out)

#define ITPCC_Payment(This,txn_in,txn_out) \
    (This)->lpVtbl -> Payment(This,txn_in,txn_out)

#define ITPCC_Delivery(This,txn_in,txn_out) \
    (This)->lpVtbl -> Delivery(This,txn_in,txn_out)

#define ITPCC_StockLevel(This,txn_in,txn_out) \
    (This)->lpVtbl -> StockLevel(This,txn_in,txn_out)

#define ITPCC_OrderStatus(This,txn_in,txn_out) \
    (This)->lpVtbl -> OrderStatus(This,txn_in,txn_out)

#define ITPCC_CallSetComplete(This) \
    (This)->lpVtbl -> CallSetComplete(This)

#endif /* COBJMACROS */

#endif    /* C style interface */

HRESULT __stdcall ITPCC_NewOrder_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_NewOrder_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,

```

```

DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Payment_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_Payment_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Delivery_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_Delivery_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_StockLevel_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_StockLevel_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_OrderStatus_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_OrderStatus_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

```

```

HRESULT __stdcall ITPCC_CallSetComplete_Proxy(
    ITPCC __RPC_FAR * This);

void __RPC_STUB ITPCC_CallSetComplete_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

#endif /* __ITPCC_INTERFACE_DEFINED__ */

/* Additional Prototypes for ALL interfaces */

unsigned long __RPC_USER VARIANT_UserSize( unsigned long
__RPC_FAR *, unsigned long , VARIANT __RPC_FAR * );
unsigned char __RPC_FAR * __RPC_USER VARIANT_UserMarshal( unsigned long
__RPC_FAR *, unsigned char __RPC_FAR *, VARIANT __RPC_FAR * );
unsigned char __RPC_FAR * __RPC_USER VARIANT_UserUnmarshal( unsigned long
__RPC_FAR *, unsigned char __RPC_FAR *, VARIANT __RPC_FAR * );
void __RPC_USER VARIANT_UserFree( unsigned long
__RPC_FAR *, VARIANT __RPC_FAR * );

/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif
#endif

/* FILE: ITPCC.IDL
* Microsoft TPC-C Kit Ver. 4.20.000
* Copyright Microsoft, 1999
* All Rights Reserved
*
* not yet audited
*
* PURPOSE: Defines the interface used by TPC-C. This interface can be
implemented by C++ components.
*
* Change history:
* 4.20.000 - first version
*/

// Forward declare all types defined
interface ITPCC;
import "oidl.idl";
import "ocidl.idl";

```

```

[
    object,
    oleautomation,
    uuid(FEEE6AA2-84B1-11d2-BA47-00C04FBFE08B),
    helpstring("ITPCC Interface"),
    pointer_default(unique)
]
interface ITPCC : IUnknown
{
    HRESULT _stdcall NewOrder
    (
        [in] VARIANT txn_in,
        [out] VARIANT *txn_out
    );

    HRESULT _stdcall Payment
    (
        [in] VARIANT txn_in,
        [out] VARIANT *txn_out
    );

    HRESULT _stdcall Delivery
    (
        [in] VARIANT txn_in,
        [out] VARIANT *txn_out
    );

    HRESULT _stdcall StockLevel
    (
        [in] VARIANT txn_in,
        [out] VARIANT *txn_out
    );

    HRESULT _stdcall OrderStatus
    (
        [in] VARIANT txn_in,
        [out] VARIANT *txn_out
    );

    HRESULT _stdcall CallSetComplete
    (
    );

}; // interface ITPCC

```

```
#pragma warning( disable: 4049 ) /* more than 64k source lines */
```

```
/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */
```

```
/* link this file in with the server and any clients */
```

```

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
    Oicf (OptLev=i2), Wl, Zp8, env=Win32 (32b run), ms_ext, c_ext
    error checks: allocation ref bounds_check enum stub_data
    VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

#ifdef _M_IA64 && !defined(_M_AXP64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

```

```

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
IID_ITPCC,0xFEEE6AA2,0x84B1,0x11d2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* !defined(_M_IA64) && !defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */

/* link this file in with the server and any clients */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf (OptLev=i2), W1, Zp8, env=Win64 (32b run,appending), ms_ext, c_ext,
robust
error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany), __declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@MIDL_FILE_HEADING( )

#if defined(_M_IA64) || defined(_M_AXP64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>

```

```

#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
IID_ITPCC,0xFEEE6AA2,0x84B1,0x11d2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* defined(_M_IA64) || defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the proxy stub code */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000

```

```

*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany), __declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@@MIDL_FILE_HEADING( )

#if !defined(_M_IA64) && !defined(_M_AXP64)
#define USE_STUBLESS_PROXY

/* verify that the <rpcproxy.h> version is high enough to compile this file*/
#ifndef __REDQ_RPCPROXY_H_VERSION__
#define __REQUIRED_RPCPROXY_H_VERSION__ 440
#endif

#include "rpcproxy.h"
#ifndef __RPCPROXY_H_VERSION__
#error this stub requires an updated version of <rpcproxy.h>
#endif // __RPCPROXY_H_VERSION__

#include "tpcc_com_ps.h"

#define TYPE_FORMAT_STRING_SIZE 997
#define PROC_FORMAT_STRING_SIZE 193
#define TRANSMIT_AS_TABLE_SIZE 0
#define WIRE_MARSHAL_TABLE_SIZE 1

typedef struct _MIDL_TYPE_FORMAT_STRING
{
    short    Pad;
    unsigned char    Format[ TYPE_FORMAT_STRING_SIZE ];
} MIDL_TYPE_FORMAT_STRING;

typedef struct _MIDL_PROC_FORMAT_STRING
{
    short    Pad;
    unsigned char    Format[ PROC_FORMAT_STRING_SIZE ];
} MIDL_PROC_FORMAT_STRING;

extern const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString;
extern const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString;

/* Standard interface: __MIDL_itf_tpcc_com_ps_0000, ver. 0.0,
GUID={0x00000000,0x0000,0x0000,{0x00,0x00,0x00,0x00,0x00,0x00,0x00,0x00}} */

/* Object interface: IUnknown, ver. 0.0,

```

```

GUID={0x00000000,0x0000,0x0000,{0xC0,0x00,0x00,0x00,0x00,0x00,0x00,0x46}} */

/* Object interface: ITPCC, ver. 0.0,
GUID={0xFEE6AA2,0x84B1,0x11d2,{0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B}} */

extern const MIDL_STUB_DESC Object_StubDesc;

extern const MIDL_SERVER_INFO ITPCC_ServerInfo;

#pragma code_seg(".orpc")
static const unsigned short ITPCC_FormatStringOffsetTable[] =
{
    0,
    34,
    68,
    102,
    136,
    170
};

static const MIDL_SERVER_INFO ITPCC_ServerInfo =
{
    &Object_StubDesc,
    0,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0,
    0
};

static const MIDL_STUBLESS_PROXY_INFO ITPCC_ProxyInfo =
{
    &Object_StubDesc,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0
};

CINTERFACE_PROXY_VTABLE(9) _ITPCCProxyVtbl =
{
    &ITPCC_ProxyInfo,
    &IID_ITPCC,
    IUnknown_QueryInterface_Proxy,
    IUnknown_AddRef_Proxy,
    IUnknown_Release_Proxy ,
    (void *)-1 /* ITPCC::NewOrder */,
    (void *)-1 /* ITPCC::Payment */,
    (void *)-1 /* ITPCC::Delivery */,

```

```
(void *)-1 /* ITPCC::StockLevel */ ,
(void *)-1 /* ITPCC::OrderStatus */ ,
(void *)-1 /* ITPCC::CallSetComplete */
};
```

```
const CInterfaceStubVtbl _ITPCCStubVtbl =
{
    &IID_ITPCC,
    &ITPCC_ServerInfo,
    9,
    0, /* pure interpreted */
    CStdStubBuffer_METHODS
};
```

```
extern const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE];
```

```
static const MIDL_STUB_DESC Object_StubDesc =
{
    0,
    NdrOleAllocate,
    NdrOleFree,
    0,
    0,
    0,
    0,
    0,
    0,
    0,
    __MIDL_TypeFormatString.Format,
    1, /* -error bounds_check flag */
    0x20000, /* Ndr library version */
    0,
    0x5030118, /* MIDL Version 5.3.280 */
    0,
    UserMarshalRoutines,
    0, /* notify & notify_flag routine table */
    0x1, /* MIDL flag */
    0, /* Reserved3 */
    0, /* Reserved4 */
    0 /* Reserved5 */
};
```

```
#pragma data_seg(".rdata")
```

```
static const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE ] =
{
    {
        VARIANT_UserSize
    ,VARIANT_UserMarshal
    ,VARIANT_UserUnmarshal
    ,VARIANT_UserFree
    }
};
```

```
#if !defined(__RPC_WIN32__)
#error Invalid build platform for this stub.
#endif
```

```
#if !(TARGET_IS_NT40_OR_LATER)
#error You need a Windows NT 4.0 or later to run this stub because it uses these features:
#error -Oif or -Oicf, [wire_marshall] or [user_marshall] attribute.
#error However, your C/C++ compilation flags indicate you intend to run this app on earlier systems.
#error This app will die there with the RPC_X_WRONG_STUB_VERSION error.
#endif
```

```
static const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString =
{
    0,
    {
        /* Procedure NewOrder */

        0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */

        /* 2 */NdrFcLong( 0x0 ), /* 0 */
        /* 6 */NdrFcShort( 0x3 ), /* 3 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 8 */NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#endif
NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
/* 10 */NdrFcShort( 0x0 ), /* 0 */
/* 12 */NdrFcShort( 0x8 ), /* 8 */
/* 14 */0x7, /* Oi2 Flags: srv must size, clt must size, has return, */
/* 0x3, /* 3 */

        /* Parameter txn_in */

        /* 16 */NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 18 */NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#endif
NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
};
```

```

#endif
#else
        NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 20 */NdrFcShort( 0x3c8 ), /* Type Offset=968 */

        /* Parameter txn_out */

/* 22 */NdrFcShort( 0x4113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=16 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 24 */NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
        NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#endif
#else
        NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#endif
#else
        NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 26 */NdrFcShort( 0x3da ), /* Type Offset=986 */

        /* Return value */

/* 28 */NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 30 */NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
        NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#endif
#else
        NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#endif
#else
        NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 32 */0x8, /* FC_LONG */
0x0, /* 0 */

        /* Procedure Payment */

/* 34 */0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 36 */NdrFcLong( 0x0 ), /* 0 */
/* 40 */NdrFcShort( 0x4 ), /* 4 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 42 */NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
        NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */

```

```

#endif
#else
        NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#endif
#else
        NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
/* 44 */NdrFcShort( 0x0 ), /* 0 */
/* 46 */NdrFcShort( 0x8 ), /* 8 */
/* 48 */0x7, /* Oi2 Flags: srv must size, clt must size, has return, */
0x3, /* 3 */

        /* Parameter txn_in */

/* 50 */NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 52 */NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
        NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
        NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#endif
#else
        NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 54 */NdrFcShort( 0x3c8 ), /* Type Offset=968 */

        /* Parameter txn_out */

/* 56 */NdrFcShort( 0x4113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=16 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 58 */NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
        NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#endif
#else
        NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#endif
#else
        NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 60 */NdrFcShort( 0x3da ), /* Type Offset=986 */

        /* Return value */

/* 62 */NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 64 */NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */

```

```

#else
    NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#else
    NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
    NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 66 */0x8, /* FC_LONG */
0x0, /* 0 */

/* Procedure Delivery */

/* 68 */0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 70 */NdrFcLong( 0x0 ), /* 0 */
/* 74 */NdrFcShort( 0x5 ), /* 5 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 76 */NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
    NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#else
    NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#else
    NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
/* 78 */NdrFcShort( 0x0 ), /* 0 */
/* 80 */NdrFcShort( 0x8 ), /* 8 */
/* 82 */0x7, /* Oi2 Flags: srv must size, clt must size, has return, */
0x3, /* 3 */

/* Parameter txn_in */

/* 84 */NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 86 */NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
    NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
    NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#else
    NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 88 */NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Parameter txn_out */

```

```

/* 90 */NdrFcShort( 0x4113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=16 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 92 */NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
    NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#else
    NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#else
    NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 94 */NdrFcShort( 0x3da ), /* Type Offset=986 */

/* Return value */

/* 96 */NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 98 */NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
    NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#endif
#else
    NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
    NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 100 */ 0x8, /* FC_LONG */
0x0, /* 0 */

/* Procedure StockLevel */

/* 102 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 104 */ NdrFcLong( 0x0 ), /* 0 */
/* 108 */ NdrFcShort( 0x6 ), /* 6 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 110 */ NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
    NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#else
    NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#else
    NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif

```

```

/* 112 */      NdrFcShort( 0x0 ), /* 0 */
/* 114 */      NdrFcShort( 0x8 ), /* 8 */
/* 116 */      0x7, /* Oi2 Flags: srv must size, clt must size, has return, */
                0x3, /* 3 */

/* Parameter txn_in */

/* 118 */      NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 120 */      NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
                NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
                NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#endif
                NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 122 */      NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Parameter txn_out */

/* 124 */      NdrFcShort( 0x4113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=16 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 126 */      NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
                NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#endif
#else
                NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#endif
                NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 128 */      NdrFcShort( 0x3da ), /* Type Offset=986 */

/* Return value */

/* 130 */      NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 132 */      NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
                NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#endif
#else
                NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#endif

```

```

                NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 134 */      0x8, /* FC_LONG */
                0x0, /* 0 */

/* Procedure OrderStatus */

/* 136 */      0x33, /* FC_AUTO_HANDLE */
                0x6c, /* Old Flags: object, Oi2 */
/* 138 */      NdrFcLong( 0x0 ), /* 0 */
/* 142 */      NdrFcShort( 0x7 ), /* 7 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 144 */      NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
                NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#else
                NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#endif
                NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
/* 146 */      NdrFcShort( 0x0 ), /* 0 */
/* 148 */      NdrFcShort( 0x8 ), /* 8 */
/* 150 */      0x7, /* Oi2 Flags: srv must size, clt must size, has return, */
                0x3, /* 3 */

/* Parameter txn_in */

/* 152 */      NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 154 */      NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
                NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
                NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#endif
                NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 156 */      NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Parameter txn_out */

/* 158 */      NdrFcShort( 0x4113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=16 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 160 */      NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else

```

```

NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#else
NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#else
NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 162 */ NdrFcShort( 0x3da ), /* Type Offset=986 */

/* Return value */

/* 164 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 166 */ NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#else
NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 168 */ 0x8, /* FC_LONG */
0x0, /* 0 */

/* Procedure CallSetComplete */

/* 170 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 172 */ NdrFcLong( 0x0 ), /* 0 */
/* 176 */ NdrFcShort( 0x8 ), /* 8 */
#ifndef _ALPHA_
/* 178 */ NdrFcShort( 0x8 ), /* x86, MIPS, PPC Stack size/offset = 8 */
#else
NdrFcShort( 0x10 ), /* Alpha Stack size/offset = 16 */
#endif
/* 180 */ NdrFcShort( 0x0 ), /* 0 */
/* 182 */ NdrFcShort( 0x8 ), /* 8 */
/* 184 */ 0x4, /* Oi2 Flags: has return, */
0x1, /* 1 */

/* Return value */

/* 186 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
/* 188 */ NdrFcShort( 0x4 ), /* x86, MIPS, PPC Stack size/offset = 4 */
#else
NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 190 */ 0x8, /* FC_LONG */
0x0, /* 0 */

```

```

}
0x0
};
static const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString =
{
0,
{
NdrFcShort( 0x0 ), /* 0 */
/* 2 */
0x12, 0x0, /* FC_UP */
/* 4 */ NdrFcShort( 0x3b0 ), /* Offset= 944 (948) */
/* 6 */
0x2b, /* FC_NON_ENCAPSULATED_UNION */
0x9, /* FC_ULONG */
/* 8 */ 0x7, /* Corr desc: FC_USHORT */
0x0, /* */
/* 10 */ NdrFcShort( 0xff8 ), /* -8 */
/* 12 */ NdrFcShort( 0x2 ), /* Offset= 2 (14) */
/* 14 */ NdrFcShort( 0x10 ), /* 16 */
/* 16 */ NdrFcShort( 0x2b ), /* 43 */
/* 18 */ NdrFcLong( 0x3 ), /* 3 */
/* 22 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 24 */ NdrFcLong( 0x11 ), /* 17 */
/* 28 */ NdrFcShort( 0x8001 ), /* Simple arm type: FC_BYTE */
/* 30 */ NdrFcLong( 0x2 ), /* 2 */
/* 34 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 36 */ NdrFcLong( 0x4 ), /* 4 */
/* 40 */ NdrFcShort( 0x800a ), /* Simple arm type: FC_FLOAT */
/* 42 */ NdrFcLong( 0x5 ), /* 5 */
/* 46 */ NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 48 */ NdrFcLong( 0xb ), /* 11 */
/* 52 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 54 */ NdrFcLong( 0xa ), /* 10 */
/* 58 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 60 */ NdrFcLong( 0x6 ), /* 6 */
/* 64 */ NdrFcShort( 0xd6 ), /* Offset= 214 (278) */
/* 66 */ NdrFcLong( 0x7 ), /* 7 */
/* 70 */ NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 72 */ NdrFcLong( 0x8 ), /* 8 */
/* 76 */ NdrFcShort( 0xd0 ), /* Offset= 208 (284) */
/* 78 */ NdrFcLong( 0xd ), /* 13 */
/* 82 */ NdrFcShort( 0xe2 ), /* Offset= 226 (308) */
/* 84 */ NdrFcLong( 0x9 ), /* 9 */
/* 88 */ NdrFcShort( 0xee ), /* Offset= 238 (326) */
/* 90 */ NdrFcLong( 0x2000 ), /* 8192 */
/* 94 */ NdrFcShort( 0xfa ), /* Offset= 250 (344) */
/* 96 */ NdrFcLong( 0x24 ), /* 36 */
/* 100 */ NdrFcShort( 0x308 ), /* Offset= 776 (876) */
/* 102 */ NdrFcLong( 0x4024 ), /* 16420 */
/* 106 */ NdrFcShort( 0x302 ), /* Offset= 770 (876) */
/* 108 */ NdrFcLong( 0x4011 ), /* 16401 */
/* 112 */ NdrFcShort( 0x300 ), /* Offset= 768 (880) */
/* 114 */ NdrFcLong( 0x4002 ), /* 16386 */

```

```

/* 118 */ NdrFcShort( 0x2fe ), /* Offset= 766 (884) */
/* 120 */ NdrFcLong( 0x4003 ), /* 16387 */
/* 124 */ NdrFcShort( 0x2fc ), /* Offset= 764 (888) */
/* 126 */ NdrFcLong( 0x4004 ), /* 16388 */
/* 130 */ NdrFcShort( 0x2fa ), /* Offset= 762 (892) */
/* 132 */ NdrFcLong( 0x4005 ), /* 16389 */
/* 136 */ NdrFcShort( 0x2f8 ), /* Offset= 760 (896) */
/* 138 */ NdrFcLong( 0x400b ), /* 16395 */
/* 142 */ NdrFcShort( 0x2e6 ), /* Offset= 742 (884) */
/* 144 */ NdrFcLong( 0x400a ), /* 16394 */
/* 148 */ NdrFcShort( 0x2e4 ), /* Offset= 740 (888) */
/* 150 */ NdrFcLong( 0x4006 ), /* 16390 */
/* 154 */ NdrFcShort( 0x2ea ), /* Offset= 746 (900) */
/* 156 */ NdrFcLong( 0x4007 ), /* 16391 */
/* 160 */ NdrFcShort( 0x2e0 ), /* Offset= 736 (896) */
/* 162 */ NdrFcLong( 0x4008 ), /* 16392 */
/* 166 */ NdrFcShort( 0x2e2 ), /* Offset= 738 (904) */
/* 168 */ NdrFcLong( 0x400d ), /* 16397 */
/* 172 */ NdrFcShort( 0x2e0 ), /* Offset= 736 (908) */
/* 174 */ NdrFcLong( 0x4009 ), /* 16393 */
/* 178 */ NdrFcShort( 0x2de ), /* Offset= 734 (912) */
/* 180 */ NdrFcLong( 0x6000 ), /* 24576 */
/* 184 */ NdrFcShort( 0x2dc ), /* Offset= 732 (916) */
/* 186 */ NdrFcLong( 0x400c ), /* 16396 */
/* 190 */ NdrFcShort( 0x2da ), /* Offset= 730 (920) */
/* 192 */ NdrFcLong( 0x10 ), /* 16 */
/* 196 */ NdrFcShort( 0x8002 ), /* Simple arm type: FC_CHAR */
/* 198 */ NdrFcLong( 0x12 ), /* 18 */
/* 202 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 204 */ NdrFcLong( 0x13 ), /* 19 */
/* 208 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 210 */ NdrFcLong( 0x16 ), /* 22 */
/* 214 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 216 */ NdrFcLong( 0x17 ), /* 23 */
/* 220 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 222 */ NdrFcLong( 0xe ), /* 14 */
/* 226 */ NdrFcShort( 0x2be ), /* Offset= 702 (928) */
/* 228 */ NdrFcLong( 0x400e ), /* 16398 */
/* 232 */ NdrFcShort( 0x2c4 ), /* Offset= 708 (940) */
/* 234 */ NdrFcLong( 0x4010 ), /* 16400 */
/* 238 */ NdrFcShort( 0x2c2 ), /* Offset= 706 (944) */
/* 240 */ NdrFcLong( 0x4012 ), /* 16402 */
/* 244 */ NdrFcShort( 0x280 ), /* Offset= 640 (884) */
/* 246 */ NdrFcLong( 0x4013 ), /* 16403 */
/* 250 */ NdrFcShort( 0x27e ), /* Offset= 638 (888) */
/* 252 */ NdrFcLong( 0x4016 ), /* 16406 */
/* 256 */ NdrFcShort( 0x278 ), /* Offset= 632 (888) */
/* 258 */ NdrFcLong( 0x4017 ), /* 16407 */
/* 262 */ NdrFcShort( 0x272 ), /* Offset= 626 (888) */
/* 264 */ NdrFcLong( 0x0 ), /* 0 */
/* 268 */ NdrFcShort( 0x0 ), /* Offset= 0 (268) */
/* 270 */ NdrFcLong( 0x1 ), /* 1 */
/* 274 */ NdrFcShort( 0x0 ), /* Offset= 0 (274) */
/* 276 */ NdrFcShort( 0xffffffff ), /* Offset= -1 (275) */
/* 278 */

```

```

0x15, /* FC_STRUCT */
0x7, /* 7 */
/* 280 */ NdrFcShort( 0x8 ), /* 8 */
/* 282 */ 0xb, /* FC_HYPER */
0x5b, /* FC_END */
/* 284 */
0x12, 0x0, /* FC_UP */
/* 286 */ NdrFcShort( 0xc ), /* Offset= 12 (298) */
/* 288 */
0x1b, /* FC_CARRAY */
0x1, /* 1 */
/* 290 */ NdrFcShort( 0x2 ), /* 2 */
/* 292 */ 0x9, /* Corr desc: FC_ULONG */
0x0, /* */
/* 294 */ NdrFcShort( 0xfffc ), /* -4 */
/* 296 */ 0x6, /* FC_SHORT */
0x5b, /* FC_END */
/* 298 */
0x17, /* FC_CSTRUCT */
0x3, /* 3 */
/* 300 */ NdrFcShort( 0x8 ), /* 8 */
/* 302 */ NdrFcShort( 0xffffffff2 ), /* Offset= -14 (288) */
/* 304 */ 0x8, /* FC_LONG */
0x8, /* FC_LONG */
/* 306 */ 0x5c, /* FC_PAD */
0x5b, /* FC_END */
/* 308 */
0x2f, /* FC_IP */
0x5a, /* FC_CONSTANT_IID */
/* 310 */ NdrFcLong( 0x0 ), /* 0 */
/* 314 */ NdrFcShort( 0x0 ), /* 0 */
/* 316 */ NdrFcShort( 0x0 ), /* 0 */
/* 318 */ 0xc0, /* 192 */
0x0, /* 0 */
/* 320 */ 0x0, /* 0 */
0x0, /* 0 */
/* 322 */ 0x0, /* 0 */
0x0, /* 0 */
/* 324 */ 0x0, /* 0 */
0x46, /* 70 */
/* 326 */
0x2f, /* FC_IP */
0x5a, /* FC_CONSTANT_IID */
/* 328 */ NdrFcLong( 0x20400 ), /* 132096 */
/* 332 */ NdrFcShort( 0x0 ), /* 0 */
/* 334 */ NdrFcShort( 0x0 ), /* 0 */
/* 336 */ 0xc0, /* 192 */
0x0, /* 0 */
/* 338 */ 0x0, /* 0 */
0x0, /* 0 */
/* 340 */ 0x0, /* 0 */
0x0, /* 0 */
/* 342 */ 0x0, /* 0 */
0x46, /* 70 */
/* 344 */

```

```

/* 346 */      0x12, 0x10, /* FC_UP [pointer_deref] */
/* 348 */      NdrFcShort( 0x2 ), /* Offset= 2 (348) */

      0x12, 0x0, /* FC_UP */
/* 350 */      NdrFcShort( 0x1fc ), /* Offset= 508 (858) */
/* 352 */

      0x2a, /* FC_ENCAPSULATED_UNION */
      0x49, /* 73 */
/* 354 */      NdrFcShort( 0x18 ), /* 24 */
/* 356 */      NdrFcShort( 0xa ), /* 10 */
/* 358 */      NdrFcLong( 0x8 ), /* 8 */
/* 362 */      NdrFcShort( 0x58 ), /* Offset= 88 (450) */
/* 364 */      NdrFcLong( 0xd ), /* 13 */
/* 368 */      NdrFcShort( 0x78 ), /* Offset= 120 (488) */
/* 370 */      NdrFcLong( 0x9 ), /* 9 */
/* 374 */      NdrFcShort( 0x94 ), /* Offset= 148 (522) */
/* 376 */      NdrFcLong( 0xc ), /* 12 */
/* 380 */      NdrFcShort( 0xbc ), /* Offset= 188 (568) */
/* 382 */      NdrFcLong( 0x24 ), /* 36 */
/* 386 */      NdrFcShort( 0x114 ), /* Offset= 276 (662) */
/* 388 */      NdrFcLong( 0x800d ), /* 32781 */
/* 392 */      NdrFcShort( 0x130 ), /* Offset= 304 (696) */
/* 394 */      NdrFcLong( 0x10 ), /* 16 */
/* 398 */      NdrFcShort( 0x148 ), /* Offset= 328 (726) */
/* 400 */      NdrFcLong( 0x2 ), /* 2 */
/* 404 */      NdrFcShort( 0x160 ), /* Offset= 352 (756) */
/* 406 */      NdrFcLong( 0x3 ), /* 3 */
/* 410 */      NdrFcShort( 0x178 ), /* Offset= 376 (786) */
/* 412 */      NdrFcLong( 0x14 ), /* 20 */
/* 416 */      NdrFcShort( 0x190 ), /* Offset= 400 (816) */
/* 418 */      NdrFcShort( 0xffffffff ), /* Offset= -1 (417) */
/* 420 */

      0x1b, /* FC_CARRAY */
      0x3, /* 3 */
/* 422 */      NdrFcShort( 0x4 ), /* 4 */
/* 424 */      0x19, /* Corr desc: field pointer, FC_ULONG */

      0x0, /* */
/* 426 */      NdrFcShort( 0x0 ), /* 0 */
/* 428 */

      0x4b, /* FC_PP */
      0x5c, /* FC_PAD */

/* 430 */

      0x48, /* FC_VARIABLE_REPEAT */
      0x49, /* FC_FIXED_OFFSET */
/* 432 */      NdrFcShort( 0x4 ), /* 4 */
/* 434 */      NdrFcShort( 0x0 ), /* 0 */
/* 436 */      NdrFcShort( 0x1 ), /* 1 */
/* 438 */      NdrFcShort( 0x0 ), /* 0 */
/* 440 */      NdrFcShort( 0x0 ), /* 0 */
/* 442 */      0x12, 0x0, /* FC_UP */
/* 444 */      NdrFcShort( 0xfffff6e ), /* Offset= -146 (298) */
/* 446 */

      0x5b, /* FC_END */

      0x8, /* FC_LONG */

```

```

/* 448 */      0x5c, /* FC_PAD */
/* 450 */      0x5b, /* FC_END */

      0x16, /* FC_PSTRUCT */
      0x3, /* 3 */
/* 452 */      NdrFcShort( 0x8 ), /* 8 */
/* 454 */

      0x4b, /* FC_PP */
      0x5c, /* FC_PAD */

/* 456 */

      0x46, /* FC_NO_REPEAT */
      0x5c, /* FC_PAD */
/* 458 */      NdrFcShort( 0x4 ), /* 4 */
/* 460 */      NdrFcShort( 0x4 ), /* 4 */
/* 462 */      0x11, 0x0, /* FC_RP */
/* 464 */      NdrFcShort( 0xfffffd4 ), /* Offset= -44 (420) */
/* 466 */

      0x5b, /* FC_END */

      0x8, /* FC_LONG */
/* 468 */      0x8, /* FC_LONG */
/* 470 */      0x5b, /* FC_END */

      0x21, /* FC_BOGUS_ARRAY */
      0x3, /* 3 */
/* 472 */      NdrFcShort( 0x0 ), /* 0 */
/* 474 */      0x19, /* Corr desc: field pointer, FC_ULONG */
      0x0, /* */
/* 476 */      NdrFcShort( 0x0 ), /* 0 */
/* 478 */      NdrFcLong( 0xffffffff ), /* -1 */
/* 482 */      0x4c, /* FC_EMBEDDED_COMPLEX */
      0x0, /* 0 */
/* 484 */      NdrFcShort( 0xfffff50 ), /* Offset= -176 (308) */
/* 486 */      0x5c, /* FC_PAD */
      0x5b, /* FC_END */

/* 488 */

      0x1a, /* FC_BOGUS_STRUCT */
      0x3, /* 3 */
/* 490 */      NdrFcShort( 0x8 ), /* 8 */
/* 492 */      NdrFcShort( 0x0 ), /* 0 */
/* 494 */      NdrFcShort( 0x6 ), /* Offset= 6 (500) */
/* 496 */      0x8, /* FC_LONG */
      0x36, /* FC_POINTER */
/* 498 */      0x5c, /* FC_PAD */
      0x5b, /* FC_END */

/* 500 */

      0x11, 0x0, /* FC_RP */
/* 502 */      NdrFcShort( 0xfffffe0 ), /* Offset= -32 (470) */
/* 504 */

      0x21, /* FC_BOGUS_ARRAY */
      0x3, /* 3 */
/* 506 */      NdrFcShort( 0x0 ), /* 0 */
/* 508 */      0x19, /* Corr desc: field pointer, FC_ULONG */
      0x0, /* */
/* 510 */      NdrFcShort( 0x0 ), /* 0 */

```

```

/* 512 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 516 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
          0x0, /* 0 */
/* 518 */ NdrFcShort( 0xfffff40 ), /* Offset= -192 (326) */
/* 520 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 522 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 524 */ NdrFcShort( 0x8 ), /* 8 */
/* 526 */ NdrFcShort( 0x0 ), /* 0 */
/* 528 */ NdrFcShort( 0x6 ), /* Offset= 6 (534) */
/* 530 */ 0x8, /* FC_LONG */
          0x36, /* FC_POINTER */
/* 532 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 534 */
          0x11, 0x0, /* FC_RP */
/* 536 */ NdrFcShort( 0xfffffe0 ), /* Offset= -32 (504) */
/* 538 */
          0x1b, /* FC_CARRAY */
          0x3, /* 3 */
/* 540 */ NdrFcShort( 0x4 ), /* 4 */
/* 542 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 544 */ NdrFcShort( 0x0 ), /* 0 */
/* 546 */
          0x4b, /* FC_PP */
          0x5c, /* FC_PAD */
/* 548 */
          0x48, /* FC_VARIABLE_REPEAT */
          0x49, /* FC_FIXED_OFFSET */
/* 550 */ NdrFcShort( 0x4 ), /* 4 */
/* 552 */ NdrFcShort( 0x0 ), /* 0 */
/* 554 */ NdrFcShort( 0x1 ), /* 1 */
/* 556 */ NdrFcShort( 0x0 ), /* 0 */
/* 558 */ NdrFcShort( 0x0 ), /* 0 */
/* 560 */ 0x12, 0x0, /* FC_UP */
/* 562 */ NdrFcShort( 0x182 ), /* Offset= 386 (948) */
/* 564 */
          0x5b, /* FC_END */
          0x8, /* FC_LONG */
/* 566 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 568 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 570 */ NdrFcShort( 0x8 ), /* 8 */
/* 572 */ NdrFcShort( 0x0 ), /* 0 */
/* 574 */ NdrFcShort( 0x6 ), /* Offset= 6 (580) */
/* 576 */ 0x8, /* FC_LONG */
          0x36, /* FC_POINTER */
/* 578 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */

```

```

/* 580 */
          0x11, 0x0, /* FC_RP */
/* 582 */ NdrFcShort( 0xfffffd4 ), /* Offset= -44 (538) */
/* 584 */
          0x2f, /* FC_IP */
          0x5a, /* FC_CONSTANT_IID */
/* 586 */ NdrFcLong( 0x2f ), /* 47 */
/* 590 */ NdrFcShort( 0x0 ), /* 0 */
/* 592 */ NdrFcShort( 0x0 ), /* 0 */
/* 594 */ 0xc0, /* 192 */
          0x0, /* 0 */
/* 596 */ 0x0, /* 0 */
          0x0, /* 0 */
/* 598 */ 0x0, /* 0 */
          0x0, /* 0 */
/* 600 */ 0x0, /* 0 */
          0x46, /* 70 */
/* 602 */
          0x1b, /* FC_CARRAY */
          0x0, /* 0 */
/* 604 */ NdrFcShort( 0x1 ), /* 1 */
/* 606 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 608 */ NdrFcShort( 0x4 ), /* 4 */
/* 610 */ 0x1, /* FC_BYTE */
          0x5b, /* FC_END */
/* 612 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 614 */ NdrFcShort( 0x10 ), /* 16 */
/* 616 */ NdrFcShort( 0x0 ), /* 0 */
/* 618 */ NdrFcShort( 0xa ), /* Offset= 10 (628) */
/* 620 */ 0x8, /* FC_LONG */
          0x8, /* FC_LONG */
/* 622 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
          0x0, /* 0 */
/* 624 */ NdrFcShort( 0xfffffd8 ), /* Offset= -40 (584) */
/* 626 */ 0x36, /* FC_POINTER */
          0x5b, /* FC_END */
/* 628 */
          0x12, 0x0, /* FC_UP */
/* 630 */ NdrFcShort( 0xfffffe4 ), /* Offset= -28 (602) */
/* 632 */
          0x1b, /* FC_CARRAY */
          0x3, /* 3 */
/* 634 */ NdrFcShort( 0x4 ), /* 4 */
/* 636 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 638 */ NdrFcShort( 0x0 ), /* 0 */
/* 640 */
          0x4b, /* FC_PP */
          0x5c, /* FC_PAD */
/* 642 */
          0x48, /* FC_VARIABLE_REPEAT */
          0x49, /* FC_FIXED_OFFSET */

```

```

/* 644 */ NdrFcShort( 0x4 ), /* 4 */
/* 646 */ NdrFcShort( 0x0 ), /* 0 */
/* 648 */ NdrFcShort( 0x1 ), /* 1 */
/* 650 */ NdrFcShort( 0x0 ), /* 0 */
/* 652 */ NdrFcShort( 0x0 ), /* 0 */
/* 654 */ 0x12, 0x0, /* FC_UP */
/* 656 */ NdrFcShort( 0xfffffd4 ), /* Offset= -44 (612) */
/* 658 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 660 */ 0x5c, /* FC_PAD */
    0x5b, /* FC_END */

/* 662 */
    0x1a, /* FC_BOGUS_STRUCT */
    0x3, /* 3 */
/* 664 */ NdrFcShort( 0x8 ), /* 8 */
/* 666 */ NdrFcShort( 0x0 ), /* 0 */
/* 668 */ NdrFcShort( 0x6 ), /* Offset= 6 (674) */
/* 670 */ 0x8, /* FC_LONG */
    0x36, /* FC_POINTER */
/* 672 */ 0x5c, /* FC_PAD */
    0x5b, /* FC_END */

/* 674 */
    0x11, 0x0, /* FC_RP */
/* 676 */ NdrFcShort( 0xfffffd4 ), /* Offset= -44 (632) */
/* 678 */
    0x1d, /* FC_SMFARRAY */
    0x0, /* 0 */
/* 680 */ NdrFcShort( 0x8 ), /* 8 */
/* 682 */ 0x2, /* FC_CHAR */
    0x5b, /* FC_END */

/* 684 */
    0x15, /* FC_STRUCT */
    0x3, /* 3 */
/* 686 */ NdrFcShort( 0x10 ), /* 16 */
/* 688 */ 0x8, /* FC_LONG */
    0x6, /* FC_SHORT */
/* 690 */ 0x6, /* FC_SHORT */
    0x4c, /* FC_EMBEDDED_COMPLEX */
/* 692 */ 0x0, /* 0 */
    NdrFcShort( 0xfffffff1 ), /* Offset= -15 (678) */
    0x5b, /* FC_END */

/* 696 */
    0x1a, /* FC_BOGUS_STRUCT */
    0x3, /* 3 */
/* 698 */ NdrFcShort( 0x18 ), /* 24 */
/* 700 */ NdrFcShort( 0x0 ), /* 0 */
/* 702 */ NdrFcShort( 0xa ), /* Offset= 10 (712) */
/* 704 */ 0x8, /* FC_LONG */
    0x36, /* FC_POINTER */
/* 706 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
    0x0, /* 0 */
/* 708 */ NdrFcShort( 0xffffffe8 ), /* Offset= -24 (684) */
/* 710 */ 0x5c, /* FC_PAD */

```

```

    0x5b, /* FC_END */
/* 712 */
    0x11, 0x0, /* FC_RP */
/* 714 */ NdrFcShort( 0xfffff0c ), /* Offset= -244 (470) */
/* 716 */
    0x1b, /* FC_CARRAY */
    0x0, /* 0 */
/* 718 */ NdrFcShort( 0x1 ), /* 1 */
/* 720 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
    0x0, /* */
/* 722 */ NdrFcShort( 0x0 ), /* 0 */
/* 724 */ 0x1, /* FC_BYTE */
    0x5b, /* FC_END */

/* 726 */
    0x16, /* FC_PSTRUCT */
    0x3, /* 3 */
/* 728 */ NdrFcShort( 0x8 ), /* 8 */
/* 730 */
    0x4b, /* FC_PP */
    0x5c, /* FC_PAD */

/* 732 */
    0x46, /* FC_NO_REPEAT */
    0x5c, /* FC_PAD */
/* 734 */ NdrFcShort( 0x4 ), /* 4 */
/* 736 */ NdrFcShort( 0x4 ), /* 4 */
/* 738 */ 0x12, 0x0, /* FC_UP */
/* 740 */ NdrFcShort( 0xffffffe8 ), /* Offset= -24 (716) */
/* 742 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 744 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */

/* 746 */
    0x1b, /* FC_CARRAY */
    0x1, /* 1 */
/* 748 */ NdrFcShort( 0x2 ), /* 2 */
/* 750 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
    0x0, /* */
/* 752 */ NdrFcShort( 0x0 ), /* 0 */
/* 754 */ 0x6, /* FC_SHORT */
    0x5b, /* FC_END */

/* 756 */
    0x16, /* FC_PSTRUCT */
    0x3, /* 3 */
/* 758 */ NdrFcShort( 0x8 ), /* 8 */
/* 760 */
    0x4b, /* FC_PP */
    0x5c, /* FC_PAD */

/* 762 */
    0x46, /* FC_NO_REPEAT */
    0x5c, /* FC_PAD */
/* 764 */ NdrFcShort( 0x4 ), /* 4 */
/* 766 */ NdrFcShort( 0x4 ), /* 4 */
/* 768 */ 0x12, 0x0, /* FC_UP */

```

```

/* 770 */ NdrFcShort( 0xfffffe8 ), /* Offset= -24 (746) */
/* 772 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 774 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 776 */
    0x1b, /* FC_CARRAY */
    0x3, /* 3 */
/* 778 */ NdrFcShort( 0x4 ), /* 4 */
/* 780 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
    0x0, /* */
/* 782 */ NdrFcShort( 0x0 ), /* 0 */
/* 784 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 786 */
    0x16, /* FC_PSTRUCT */
    0x3, /* 3 */
/* 788 */ NdrFcShort( 0x8 ), /* 8 */
/* 790 */
    0x4b, /* FC_PP */
    0x5c, /* FC_PAD */
/* 792 */
    0x46, /* FC_NO_REPEAT */
    0x5c, /* FC_PAD */
/* 794 */ NdrFcShort( 0x4 ), /* 4 */
/* 796 */ NdrFcShort( 0x4 ), /* 4 */
/* 798 */ 0x12, 0x0, /* FC_UP */
/* 800 */ NdrFcShort( 0xfffffe8 ), /* Offset= -24 (776) */
/* 802 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 804 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 806 */
    0x1b, /* FC_CARRAY */
    0x7, /* 7 */
/* 808 */ NdrFcShort( 0x8 ), /* 8 */
/* 810 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
    0x0, /* */
/* 812 */ NdrFcShort( 0x0 ), /* 0 */
/* 814 */ 0xb, /* FC_HYPER */
    0x5b, /* FC_END */
/* 816 */
    0x16, /* FC_PSTRUCT */
    0x3, /* 3 */
/* 818 */ NdrFcShort( 0x8 ), /* 8 */
/* 820 */
    0x4b, /* FC_PP */
    0x5c, /* FC_PAD */
/* 822 */
    0x46, /* FC_NO_REPEAT */
    0x5c, /* FC_PAD */

```

```

/* 824 */ NdrFcShort( 0x4 ), /* 4 */
/* 826 */ NdrFcShort( 0x4 ), /* 4 */
/* 828 */ 0x12, 0x0, /* FC_UP */
/* 830 */ NdrFcShort( 0xfffffe8 ), /* Offset= -24 (806) */
/* 832 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 834 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 836 */
    0x15, /* FC_STRUCT */
    0x3, /* 3 */
/* 838 */ NdrFcShort( 0x8 ), /* 8 */
/* 840 */ 0x8, /* FC_LONG */
    0x8, /* FC_LONG */
/* 842 */ 0x5c, /* FC_PAD */
    0x5b, /* FC_END */
/* 844 */
    0x1b, /* FC_CARRAY */
    0x3, /* 3 */
/* 846 */ NdrFcShort( 0x8 ), /* 8 */
/* 848 */ 0x7, /* Corr desc: FC_USHORT */
    0x0, /* */
/* 850 */ NdrFcShort( 0xffd8 ), /* -40 */
/* 852 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
    0x0, /* 0 */
/* 854 */ NdrFcShort( 0xfffffee ), /* Offset= -18 (836) */
/* 856 */ 0x5c, /* FC_PAD */
    0x5b, /* FC_END */
/* 858 */
    0x1a, /* FC_BOGUS_STRUCT */
    0x3, /* 3 */
/* 860 */ NdrFcShort( 0x28 ), /* 40 */
/* 862 */ NdrFcShort( 0xfffffee ), /* Offset= -18 (844) */
/* 864 */ NdrFcShort( 0x0 ), /* Offset= 0 (864) */
/* 866 */ 0x6, /* FC_SHORT */
    0x6, /* FC_SHORT */
/* 868 */ 0x38, /* FC_ALIGNM4 */
    0x8, /* FC_LONG */
/* 870 */ 0x8, /* FC_LONG */
    0x4c, /* FC_EMBEDDED_COMPLEX */
/* 872 */ 0x0, /* 0 */
    NdrFcShort( 0xffffdf7 ), /* Offset= -521 (352) */
    0x5b, /* FC_END */
/* 876 */
    0x12, 0x0, /* FC_UP */
/* 878 */ NdrFcShort( 0xffffef6 ), /* Offset= -266 (612) */
/* 880 */
    0x12, 0x8, /* FC_UP [simple_pointer] */
/* 882 */ 0x1, /* FC_BYTE */
    0x5c, /* FC_PAD */
/* 884 */
    0x12, 0x8, /* FC_UP [simple_pointer] */
/* 886 */ 0x6, /* FC_SHORT */

```

```

/* 888 */      0x5c,      /* FC_PAD */
/* 890 */      0x12, 0x8, /* FC_UP [simple_pointer] */
/* 892 */      0x8,      /* FC_LONG */
/* 894 */      0x5c,      /* FC_PAD */
/* 896 */      0x12, 0x8, /* FC_UP [simple_pointer] */
/* 898 */      0xa,      /* FC_FLOAT */
/* 900 */      0x5c,      /* FC_PAD */
/* 902 */      0x12, 0x8, /* FC_UP [simple_pointer] */
/* 904 */      0xc,      /* FC_DOUBLE */
/* 906 */      0x5c,      /* FC_PAD */
/* 908 */      0x12, 0x0, /* FC_UP */
/* 910 */      NdrFcShort( 0xffffd90 ), /* Offset= -624 (278) */
/* 912 */      0x12, 0x10, /* FC_UP [pointer_deref] */
/* 914 */      NdrFcShort( 0xffffd92 ), /* Offset= -622 (284) */
/* 916 */      0x12, 0x10, /* FC_UP [pointer_deref] */
/* 918 */      NdrFcShort( 0xffffda6 ), /* Offset= -602 (308) */
/* 920 */      0x12, 0x10, /* FC_UP [pointer_deref] */
/* 922 */      NdrFcShort( 0xffffdb4 ), /* Offset= -588 (326) */
/* 924 */      0x12, 0x10, /* FC_UP [pointer_deref] */
/* 926 */      NdrFcShort( 0xffffdc2 ), /* Offset= -574 (344) */
/* 928 */      0x12, 0x10, /* FC_UP [pointer_deref] */
/* 930 */      NdrFcShort( 0x2 ), /* Offset= 2 (924) */
/* 932 */      0x12, 0x0, /* FC_UP */
/* 934 */      NdrFcShort( 0x16 ), /* Offset= 22 (948) */
/* 936 */      0x15, /* FC_STRUCT */
/* 938 */      0x7, /* 7 */
/* 940 */      NdrFcShort( 0x10 ), /* 16 */
/* 942 */      0x6, /* FC_SHORT */
/* 944 */      0x1, /* FC_BYTE */
/* 946 */      0x1, /* FC_BYTE */
/* 948 */      0x38, /* FC_ALIGNM4 */
/* 950 */      0x8, /* FC_LONG */
/* 952 */      0x39, /* FC_ALIGNM8 */
/* 954 */      0xb, /* FC_HYPER */
/* 956 */      0x5b, /* FC_END */
/* 958 */      0x12, 0x0, /* FC_UP */
/* 960 */      NdrFcShort( 0xfffff2 ), /* Offset= -14 (928) */
/* 962 */      0x12, 0x8, /* FC_UP [simple_pointer] */
/* 964 */      0x2, /* FC_CHAR */
/* 966 */      0x5c, /* FC_PAD */
/* 968 */      0x1a, /* FC_BOGUS_STRUCT */

```

```

/* 950 */      0x7, /* 7 */
/* 952 */      NdrFcShort( 0x20 ), /* 32 */
/* 954 */      NdrFcShort( 0x0 ), /* 0 */
/* 956 */      NdrFcShort( 0x0 ), /* Offset= 0 (954) */
/* 958 */      0x8, /* FC_LONG */
/* 960 */      0x8, /* FC_LONG */
/* 962 */      0x6, /* FC_SHORT */
/* 964 */      0x6, /* FC_SHORT */
/* 966 */      0x6, /* FC_SHORT */
/* 968 */      0x6, /* FC_SHORT */
/* 970 */      0x4c, /* FC_EMBEDDED_COMPLEX */
/* 972 */      0x0, /* 0 */
/* 974 */      NdrFcShort( 0xffffc42 ), /* Offset= -958 (6) */
/* 976 */      0x5c, /* FC_PAD */
/* 978 */      0x5b, /* FC_END */
/* 980 */      0xb4, /* FC_USER_MARSHAL */
/* 982 */      0x83, /* 131 */
/* 984 */      NdrFcShort( 0x0 ), /* 0 */
/* 986 */      NdrFcShort( 0x10 ), /* 16 */
/* 988 */      NdrFcShort( 0x0 ), /* 0 */
/* 990 */      NdrFcShort( 0xffffc32 ), /* Offset= -974 (2) */
/* 992 */      0x11, 0x4, /* FC_RP [allocated_on_stack] */
/* 994 */      NdrFcShort( 0x6 ), /* Offset= 6 (986) */
/* 996 */      0x13, 0x0, /* FC_OP */
/* 998 */      NdrFcShort( 0xffffdc ), /* Offset= -36 (948) */
/* 1000 */      0xb4, /* FC_USER_MARSHAL */
/* 1002 */      0x83, /* 131 */
/* 1004 */      NdrFcShort( 0x0 ), /* 0 */
/* 1006 */      NdrFcShort( 0x10 ), /* 16 */
/* 1008 */      NdrFcShort( 0x0 ), /* 0 */
/* 1010 */      NdrFcShort( 0xfffff4 ), /* Offset= -12 (982) */
/* 1012 */      0x0
/* 1014 */      }
/* 1016 */      };
const CInterfaceProxyVtbl * _tpcc_com_ps_ProxyVtblList[] =
{
( CInterfaceProxyVtbl *) &_ITPCCProxyVtbl,
0
};
const CInterfaceStubVtbl * _tpcc_com_ps_StubVtblList[] =
{
( CInterfaceStubVtbl *) &_ITPCCStubVtbl,
0
};
PCInterfaceName const _tpcc_com_ps_InterfaceNamesList[] =
{
"ITPCC",
0
};

```

```

#define _tpcc_com_ps_CHECK_IID(n)      IID_GENERIC_CHECK_IID( _tpcc_com_ps, pIID, n)

int __stdcall _tpcc_com_ps_IID_Lookup( const IID * pIID, int * pIndex )
{
    if(!_tpcc_com_ps_CHECK_IID(0))
    {
        *pIndex = 0;
        return 1;
    }

    return 0;
}

const ExtendedProxyFileInfo tpcc_com_ps_ProxyFileInfo =
{
    (PCInterfaceProxyVtblList *) & _tpcc_com_ps_ProxyVtblList,
    (PCInterfaceStubVtblList *) & _tpcc_com_ps_StubVtblList,
    (const PCInterfaceName *) & _tpcc_com_ps_InterfaceNamesList,
    0, // no delegation
    & _tpcc_com_ps_IID_Lookup,
    1,
    2,
    0, /* table of [async_uuid] interfaces */
    0, /* Filler1 */
    0, /* Filler2 */
    0 /* Filler3 */
};

#endif /* !defined(_M_IA64) && !defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the proxy stub code */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf (OptLev=i2), W1, Zp8, env=Win64 (32b run,appending), ms_ext, c_ext, robust
error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany), __declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@@MIDL_FILE_HEADING( )

#if defined(_M_IA64) || defined(_M_AXP64)
#define USE_STUBLESS_PROXY

```

```

/* verify that the <rpcproxy.h> version is high enough to compile this file*/
#ifndef __REDQ_RPCPROXY_H_VERSION__
#define __REQUIRED_RPCPROXY_H_VERSION__ 475
#endif

#include "rpcproxy.h"
#ifndef __RPCPROXY_H_VERSION__
#error this stub requires an updated version of <rpcproxy.h>
#endif // __RPCPROXY_H_VERSION__

#include "tpcc_com_ps.h"

#define TYPE_FORMAT_STRING_SIZE 979
#define PROC_FORMAT_STRING_SIZE 253
#define TRANSMIT_AS_TABLE_SIZE 0
#define WIRE_MARSHAL_TABLE_SIZE 1

typedef struct _MIDL_TYPE_FORMAT_STRING
{
    short    Pad;
    unsigned char    Format[ TYPE_FORMAT_STRING_SIZE ];
} MIDL_TYPE_FORMAT_STRING;

typedef struct _MIDL_PROC_FORMAT_STRING
{
    short    Pad;
    unsigned char    Format[ PROC_FORMAT_STRING_SIZE ];
} MIDL_PROC_FORMAT_STRING;

extern const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString;
extern const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString;

/* Standard interface: __MIDL_itf_tpcc_com_ps_0000, ver. 0.0,
GUID={0x00000000,0x0000,0x0000,{0x00,0x00,0x00,0x00,0x00,0x00,0x00,0x00}} */

/* Object interface: IUnknown, ver. 0.0,
GUID={0x00000000,0x0000,0x0000,{0xC0,0x00,0x00,0x00,0x00,0x00,0x00,0x46}} */

/* Object interface: ITPCC, ver. 0.0,
GUID={0xFEE6AA2,0x84B1,0x11d2,{0xBA,0x47,0x00,0x00,0x4F,0xBF,0xE0,0x8B}} */

extern const MIDL_STUB_DESC Object_StubDesc;

extern const MIDL_SERVER_INFO ITPCC_ServerInfo;

#pragma code_seg(".orpc")

```

```

static const unsigned short ITPCC_FormatStringOffsetTable[] =
{
    0,
    44,
    88,
    132,
    176,
    220
};

static const MIDL_SERVER_INFO ITPCC_ServerInfo =
{
    &Object_StubDesc,
    0,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0,
    0
};

static const MIDL_STUBLESS_PROXY_INFO ITPCC_ProxyInfo =
{
    &Object_StubDesc,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0
};

CINTERFACE_PROXY_VTABLE(9) _ITPCCProxyVtbl =
{
    &ITPCC_ProxyInfo,
    &IID_ITPCC,
    IUnknown_QueryInterface_Proxy,
    IUnknown_AddRef_Proxy,
    IUnknown_Release_Proxy ,
    (void *)-1 /* ITPCC::NewOrder */ ,
    (void *)-1 /* ITPCC::Payment */ ,
    (void *)-1 /* ITPCC::Delivery */ ,
    (void *)-1 /* ITPCC::StockLevel */ ,
    (void *)-1 /* ITPCC::OrderStatus */ ,
    (void *)-1 /* ITPCC::CallSetComplete */
};

const CInterfaceStubVtbl _ITPCCStubVtbl =
{
    &IID_ITPCC,
    &ITPCC_ServerInfo,
    9,
    0, /* pure interpreted */
    CStdStubBuffer_METHODS
};

```

```

extern const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE ];

static const MIDL_STUB_DESC Object_StubDesc =
{
    0,
    NdrOleAllocate,
    NdrOleFree,
    0,
    0,
    0,
    0,
    0,
    0,
    __MIDL_TypeFormatString.Format,
    1, /* -error bounds_check flag */
    0x50002, /* Ndr library version */
    0,
    0x5030118, /* MIDL Version 5.3.280 */
    0,
    UserMarshalRoutines,
    0, /* notify & notify_flag routine table */
    0x1, /* MIDL flag */
    0, /* Reserved3 */
    0, /* Reserved4 */
    0 /* Reserved5 */
};

#pragma data_seg(".rdata")

static const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE ] =
{
    {
        VARIANT_UserSize
        ,VARIANT_UserMarshal
        ,VARIANT_UserUnmarshal
        ,VARIANT_UserFree
    }
};

#if !defined(__RPC_WIN64__)
#error Invalid build platform for this stub.
#endif

static const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString =
{
    0,
    {
        /* Procedure NewOrder */

```

```

0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 2 */NdrFcLong( 0x0 ), /* 0 */
/* 6 */NdrFcShort( 0x3 ), /* 3 */
#ifdef _ALPHA_
/* 8 */NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 10 */NdrFcShort( 0x0 ), /* 0 */
/* 12 */NdrFcShort( 0x8 ), /* 8 */
/* 14 */0x47, /* Oi2 Flags: srv must size, clt must size, has return, has ext, */
0x3, /* 3 */
/* 16 */0xa, /* 10 */
0x7, /* Ext Flags: new corr desc, clt corr check, srv corr check, */
/* 18 */NdrFcShort( 0x20 ), /* 32 */
/* 20 */NdrFcShort( 0x20 ), /* 32 */
/* 22 */NdrFcShort( 0x0 ), /* 0 */
/* 24 */NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 26 */NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
/* 28 */NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 30 */NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 32 */NdrFcShort( 0x6113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 34 */NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 36 */NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

/* 38 */NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 40 */NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 42 */0x8, /* FC_LONG */
0x0, /* 0 */

/* Procedure Payment */

/* 44 */0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */

```

```

/* 46 */NdrFcLong( 0x0 ), /* 0 */
/* 50 */NdrFcShort( 0x4 ), /* 4 */
#ifdef _ALPHA_
/* 52 */NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 54 */NdrFcShort( 0x0 ), /* 0 */
/* 56 */NdrFcShort( 0x8 ), /* 8 */
/* 58 */0x47, /* Oi2 Flags: srv must size, clt must size, has return, has ext, */
0x3, /* 3 */
/* 60 */0xa, /* 10 */
0x7, /* Ext Flags: new corr desc, clt corr check, srv corr check, */
/* 62 */NdrFcShort( 0x20 ), /* 32 */
/* 64 */NdrFcShort( 0x20 ), /* 32 */
/* 66 */NdrFcShort( 0x0 ), /* 0 */
/* 68 */NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 70 */NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
/* 72 */NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 74 */NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 76 */NdrFcShort( 0x6113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 78 */NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 80 */NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

/* 82 */NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 84 */NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 86 */0x8, /* FC_LONG */
0x0, /* 0 */

/* Procedure Delivery */

/* 88 */0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 90 */NdrFcLong( 0x0 ), /* 0 */
/* 94 */NdrFcShort( 0x5 ), /* 5 */

```

```

#ifdef _ALPHA_
/* 96 */NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
    NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 98 */NdrFcShort( 0x0 ), /* 0 */
/* 100 */ NdrFcShort( 0x8 ), /* 8 */
/* 102 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has return, has ext, */
    0x3, /* 3 */
/* 104 */ 0xa, /* 10 */
    0x7, /* Ext Flags: new corr desc, clt corr check, srv corr check, */
/* 106 */ NdrFcShort( 0x20 ), /* 32 */
/* 108 */ NdrFcShort( 0x20 ), /* 32 */
/* 110 */ NdrFcShort( 0x0 ), /* 0 */
/* 112 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 114 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
/* 116 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
    NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 118 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 120 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 122 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
    NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 124 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

/* 126 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 128 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
    NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 130 */ 0x8, /* FC_LONG */
    0x0, /* 0 */

/* Procedure StockLevel */

/* 132 */ 0x33, /* FC_AUTO_HANDLE */
    0x6c, /* Old Flags: object, Oi2 */
/* 134 */ NdrFcLong( 0x0 ), /* 0 */
/* 138 */ NdrFcShort( 0x6 ), /* 6 */
#ifdef _ALPHA_
/* 140 */ NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */

```

```

#else
    NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 142 */ NdrFcShort( 0x0 ), /* 0 */
/* 144 */ NdrFcShort( 0x8 ), /* 8 */
/* 146 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has return, has ext, */
    0x3, /* 3 */
/* 148 */ 0xa, /* 10 */
    0x7, /* Ext Flags: new corr desc, clt corr check, srv corr check, */
/* 150 */ NdrFcShort( 0x20 ), /* 32 */
/* 152 */ NdrFcShort( 0x20 ), /* 32 */
/* 154 */ NdrFcShort( 0x0 ), /* 0 */
/* 156 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 158 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
/* 160 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
    NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 162 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 164 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 166 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
    NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 168 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

/* 170 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 172 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
    NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 174 */ 0x8, /* FC_LONG */
    0x0, /* 0 */

/* Procedure OrderStatus */

/* 176 */ 0x33, /* FC_AUTO_HANDLE */
    0x6c, /* Old Flags: object, Oi2 */
/* 178 */ NdrFcLong( 0x0 ), /* 0 */
/* 182 */ NdrFcShort( 0x7 ), /* 7 */
#ifdef _ALPHA_
/* 184 */ NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
    NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */

```

```

#endif
/* 186 */ NdrFcShort( 0x0 ), /* 0 */
/* 188 */ NdrFcShort( 0x8 ), /* 8 */
/* 190 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has return, has ext, */
          0x3, /* 3 */
/* 192 */ 0xa, /* 10 */
          0x7, /* Ext Flags: new corr desc, clt corr check, srv corr check, */
/* 194 */ NdrFcShort( 0x20 ), /* 32 */
/* 196 */ NdrFcShort( 0x20 ), /* 32 */
/* 198 */ NdrFcShort( 0x0 ), /* 0 */
/* 200 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 202 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val, */
#ifdef _ALPHA_
/* 204 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 206 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 208 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out, simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 210 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 212 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

/* 214 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 216 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 218 */ 0x8, /* FC_LONG */
          0x0, /* 0 */

/* Procedure CallSetComplete */

/* 220 */ 0x33, /* FC_AUTO_HANDLE */
          0x6c, /* Old Flags: object, Oi2 */
/* 222 */ NdrFcLong( 0x0 ), /* 0 */
/* 226 */ NdrFcShort( 0x8 ), /* 8 */
/* 228 */ NdrFcShort( 0x10 ), /* ia64, axp64 Stack size/offset = 16 */
/* 230 */ NdrFcShort( 0x0 ), /* 0 */
/* 232 */ NdrFcShort( 0x8 ), /* 8 */
/* 234 */ 0x44, /* Oi2 Flags: has return, has ext, */
          0x1, /* 1 */
/* 236 */ 0xa, /* 10 */

```

```

          0x1, /* Ext Flags: new corr desc, */
/* 238 */ NdrFcShort( 0x0 ), /* 0 */
/* 240 */ NdrFcShort( 0x0 ), /* 0 */
/* 242 */ NdrFcShort( 0x0 ), /* 0 */
/* 244 */ NdrFcShort( 0x0 ), /* 0 */

/* Return value */

/* 246 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
/* 248 */ NdrFcShort( 0x8 ), /* ia64, axp64 Stack size/offset = 8 */
/* 250 */ 0x8, /* FC_LONG */
          0x0, /* 0 */

          0x0

}
};

static const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString =
{
    0,
    {
        NdrFcShort( 0x0 ), /* 0 */
/* 2 */
        0x12, 0x0, /* FC_UP */
/* 4 */ NdrFcShort( 0x39e ), /* Offset= 926 (930) */
/* 6 */
        0x2b, /* FC_NON_ENCAPSULATED_UNION */
        0x9, /* FC_ULONG */
/* 8 */ 0x7, /* Corr desc: FC_USHORT */
        0x0, /* */
/* 10 */NdrFcShort( 0xffff ), /* -8 */
/* 12 */NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 14 */NdrFcShort( 0x2 ), /* Offset= 2 (16) */
/* 16 */NdrFcShort( 0x10 ), /* 16 */
/* 18 */NdrFcShort( 0x2b ), /* 43 */
/* 20 */NdrFcLong( 0x3 ), /* 3 */
/* 24 */NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 26 */NdrFcLong( 0x11 ), /* 17 */
/* 30 */NdrFcShort( 0x8001 ), /* Simple arm type: FC_BYTE */
/* 32 */NdrFcLong( 0x2 ), /* 2 */
/* 36 */NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 38 */NdrFcLong( 0x4 ), /* 4 */
/* 42 */NdrFcShort( 0x800a ), /* Simple arm type: FC_FLOAT */
/* 44 */NdrFcLong( 0x5 ), /* 5 */
/* 48 */NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 50 */NdrFcLong( 0xb ), /* 11 */
/* 54 */NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 56 */NdrFcLong( 0xa ), /* 10 */
/* 60 */NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 62 */NdrFcLong( 0x6 ), /* 6 */
/* 66 */NdrFcShort( 0xd6 ), /* Offset= 214 (280) */
/* 68 */NdrFcLong( 0x7 ), /* 7 */
/* 72 */NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 74 */NdrFcLong( 0x8 ), /* 8 */
/* 78 */NdrFcShort( 0xd0 ), /* Offset= 208 (286) */

```

```

/* 80 */NdrFcLong( 0xd ), /* 13 */
/* 84 */NdrFcShort( 0xe4 ), /* Offset= 228 (312) */
/* 86 */NdrFcLong( 0x9 ), /* 9 */
/* 90 */NdrFcShort( 0xf0 ), /* Offset= 240 (330) */
/* 92 */NdrFcLong( 0x2000 ), /* 8192 */
/* 96 */NdrFcShort( 0xfc ), /* Offset= 252 (348) */
/* 98 */NdrFcLong( 0x24 ), /* 36 */
/* 102 */ NdrFcShort( 0x2f4 ), /* Offset= 756 (858) */
/* 104 */ NdrFcLong( 0x4024 ), /* 16420 */
/* 108 */ NdrFcShort( 0x2ee ), /* Offset= 750 (858) */
/* 110 */ NdrFcLong( 0x4011 ), /* 16401 */
/* 114 */ NdrFcShort( 0x2ec ), /* Offset= 748 (862) */
/* 116 */ NdrFcLong( 0x4002 ), /* 16386 */
/* 120 */ NdrFcShort( 0x2ea ), /* Offset= 746 (866) */
/* 122 */ NdrFcLong( 0x4003 ), /* 16387 */
/* 126 */ NdrFcShort( 0x2e8 ), /* Offset= 744 (870) */
/* 128 */ NdrFcLong( 0x4004 ), /* 16388 */
/* 132 */ NdrFcShort( 0x2e6 ), /* Offset= 742 (874) */
/* 134 */ NdrFcLong( 0x4005 ), /* 16389 */
/* 138 */ NdrFcShort( 0x2e4 ), /* Offset= 740 (878) */
/* 140 */ NdrFcLong( 0x400b ), /* 16395 */
/* 144 */ NdrFcShort( 0x2d2 ), /* Offset= 722 (866) */
/* 146 */ NdrFcLong( 0x400a ), /* 16394 */
/* 150 */ NdrFcShort( 0x2d0 ), /* Offset= 720 (870) */
/* 152 */ NdrFcLong( 0x4006 ), /* 16390 */
/* 156 */ NdrFcShort( 0x2d6 ), /* Offset= 726 (882) */
/* 158 */ NdrFcLong( 0x4007 ), /* 16391 */
/* 162 */ NdrFcShort( 0x2cc ), /* Offset= 716 (878) */
/* 164 */ NdrFcLong( 0x4008 ), /* 16392 */
/* 168 */ NdrFcShort( 0x2ce ), /* Offset= 718 (886) */
/* 170 */ NdrFcLong( 0x400d ), /* 16397 */
/* 174 */ NdrFcShort( 0x2cc ), /* Offset= 716 (890) */
/* 176 */ NdrFcLong( 0x4009 ), /* 16393 */
/* 180 */ NdrFcShort( 0x2ca ), /* Offset= 714 (894) */
/* 182 */ NdrFcLong( 0x6000 ), /* 24576 */
/* 186 */ NdrFcShort( 0x2c8 ), /* Offset= 712 (898) */
/* 188 */ NdrFcLong( 0x400c ), /* 16396 */
/* 192 */ NdrFcShort( 0x2c6 ), /* Offset= 710 (902) */
/* 194 */ NdrFcLong( 0x10 ), /* 16 */
/* 198 */ NdrFcShort( 0x8002 ), /* Simple arm type: FC_CHAR */
/* 200 */ NdrFcLong( 0x12 ), /* 18 */
/* 204 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 206 */ NdrFcLong( 0x13 ), /* 19 */
/* 210 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 212 */ NdrFcLong( 0x16 ), /* 22 */
/* 216 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 218 */ NdrFcLong( 0x17 ), /* 23 */
/* 222 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 224 */ NdrFcLong( 0xe ), /* 14 */
/* 228 */ NdrFcShort( 0x2aa ), /* Offset= 682 (910) */
/* 230 */ NdrFcLong( 0x400e ), /* 16398 */
/* 234 */ NdrFcShort( 0x2b0 ), /* Offset= 688 (922) */
/* 236 */ NdrFcLong( 0x4010 ), /* 16400 */
/* 240 */ NdrFcShort( 0x2ae ), /* Offset= 686 (926) */
/* 242 */ NdrFcLong( 0x4012 ), /* 16402 */

```

```

/* 246 */ NdrFcShort( 0x26c ), /* Offset= 620 (866) */
/* 248 */ NdrFcLong( 0x4013 ), /* 16403 */
/* 252 */ NdrFcShort( 0x26a ), /* Offset= 618 (870) */
/* 254 */ NdrFcLong( 0x4016 ), /* 16406 */
/* 258 */ NdrFcShort( 0x264 ), /* Offset= 612 (870) */
/* 260 */ NdrFcLong( 0x4017 ), /* 16407 */
/* 264 */ NdrFcShort( 0x25e ), /* Offset= 606 (870) */
/* 266 */ NdrFcLong( 0x0 ), /* 0 */
/* 270 */ NdrFcShort( 0x0 ), /* Offset= 0 (270) */
/* 272 */ NdrFcLong( 0x1 ), /* 1 */
/* 276 */ NdrFcShort( 0x0 ), /* Offset= 0 (276) */
/* 278 */ NdrFcShort( 0xffffffff ), /* Offset= -1 (277) */
/* 280 */
        0x15, /* FC_STRUCT */
        0x7, /* 7 */
/* 282 */ NdrFcShort( 0x8 ), /* 8 */
/* 284 */ 0xb, /* FC_HYPER */
        0x5b, /* FC_END */
/* 286 */
        0x12, 0x0, /* FC_UP */
/* 288 */ NdrFcShort( 0xe ), /* Offset= 14 (302) */
/* 290 */
        0x1b, /* FC_CARRAY */
        0x1, /* 1 */
/* 292 */ NdrFcShort( 0x2 ), /* 2 */
/* 294 */ 0x9, /* Corr desc: FC_ULONG */
        0x0, /* */
/* 296 */ NdrFcShort( 0xfffc ), /* -4 */
/* 298 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 300 */ 0x6, /* FC_SHORT */
        0x5b, /* FC_END */
/* 302 */
        0x17, /* FC_CSTRUCT */
        0x3, /* 3 */
/* 304 */ NdrFcShort( 0x8 ), /* 8 */
/* 306 */ NdrFcShort( 0xffffffff0 ), /* Offset= -16 (290) */
/* 308 */ 0x8, /* FC_LONG */
        0x8, /* FC_LONG */
/* 310 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 312 */
        0x2f, /* FC_IP */
        0x5a, /* FC_CONSTANT_IID */
/* 314 */ NdrFcLong( 0x0 ), /* 0 */
/* 318 */ NdrFcShort( 0x0 ), /* 0 */
/* 320 */ NdrFcShort( 0x0 ), /* 0 */
/* 322 */ 0xc0, /* 192 */
        0x0, /* 0 */
/* 324 */ 0x0, /* 0 */
        0x0, /* 0 */
/* 326 */ 0x0, /* 0 */
        0x0, /* 0 */
/* 328 */ 0x0, /* 0 */
        0x46, /* 70 */
/* 330 */

```

```

0x2f, /* FC_IP */
0x5a, /* FC_CONSTANT_IID */
/* 332 */ NdrFcLong( 0x20400 ), /* 132096 */
/* 336 */ NdrFcShort( 0x0 ), /* 0 */
/* 338 */ NdrFcShort( 0x0 ), /* 0 */
/* 340 */ 0xc0, /* 192 */
/* 342 */ 0x0, /* 0 */
/* 344 */ 0x0, /* 0 */
/* 346 */ 0x0, /* 0 */
/* 348 */ 0x46, /* 70 */
/* 350 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 352 */ NdrFcShort( 0x2 ), /* Offset= 2 (352) */
/* 354 */ 0x12, 0x0, /* FC_UP */
/* 356 */ NdrFcShort( 0x1e6 ), /* Offset= 486 (840) */
/* 358 */ 0x2a, /* FC_ENCAPSULATED_UNION */
/* 360 */ 0x89, /* 137 */
/* 362 */ NdrFcShort( 0x20 ), /* 32 */
/* 364 */ NdrFcShort( 0xa ), /* 10 */
/* 366 */ NdrFcLong( 0x8 ), /* 8 */
/* 368 */ NdrFcShort( 0x50 ), /* Offset= 80 (446) */
/* 370 */ NdrFcLong( 0xd ), /* 13 */
/* 372 */ NdrFcShort( 0x70 ), /* Offset= 112 (484) */
/* 374 */ NdrFcLong( 0x9 ), /* 9 */
/* 376 */ NdrFcShort( 0x90 ), /* Offset= 144 (522) */
/* 378 */ NdrFcLong( 0xc ), /* 12 */
/* 380 */ NdrFcShort( 0xb0 ), /* Offset= 176 (560) */
/* 382 */ NdrFcLong( 0x24 ), /* 36 */
/* 384 */ NdrFcShort( 0x104 ), /* Offset= 260 (650) */
/* 386 */ NdrFcLong( 0x800d ), /* 32781 */
/* 388 */ NdrFcShort( 0x120 ), /* Offset= 288 (684) */
/* 390 */ NdrFcLong( 0x10 ), /* 16 */
/* 392 */ NdrFcShort( 0x13a ), /* Offset= 314 (716) */
/* 394 */ NdrFcLong( 0x2 ), /* 2 */
/* 396 */ NdrFcShort( 0x150 ), /* Offset= 336 (744) */
/* 398 */ NdrFcLong( 0x3 ), /* 3 */
/* 400 */ NdrFcShort( 0x166 ), /* Offset= 358 (772) */
/* 402 */ NdrFcLong( 0x14 ), /* 20 */
/* 404 */ NdrFcShort( 0x17c ), /* Offset= 380 (800) */
/* 406 */ NdrFcShort( 0xfffffff ), /* Offset= -1 (421) */
/* 408 */ 0x21, /* FC_BOGUS_ARRAY */
/* 410 */ 0x3, /* 3 */
/* 412 */ NdrFcShort( 0x0 ), /* 0 */
/* 414 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 416 */ 0x0, /* */
/* 418 */ NdrFcShort( 0x0 ), /* 0 */
/* 420 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 422 */ NdrFcLong( 0xfffffff ), /* -1 */
/* 424 */ NdrFcShort( 0x0 ), /* Corr flags: */

```

```

/* 440 */ 0x12, 0x0, /* FC_UP */
/* 442 */ NdrFcShort( 0xfffff74 ), /* Offset= -140 (302) */
/* 444 */ 0x5c, /* FC_PAD */
/* 446 */ 0x5b, /* FC_END */
/* 448 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 450 */ 0x3, /* 3 */
/* 452 */ NdrFcShort( 0x10 ), /* 16 */
/* 454 */ NdrFcShort( 0x0 ), /* 0 */
/* 456 */ NdrFcShort( 0x6 ), /* Offset= 6 (458) */
/* 458 */ 0x8, /* FC_LONG */
/* 460 */ 0x39, /* FC_ALIGNM8 */
/* 462 */ 0x36, /* FC_POINTER */
/* 464 */ 0x5b, /* FC_END */
/* 466 */ 0x11, 0x0, /* FC_RP */
/* 468 */ NdrFcShort( 0xfffffdc ), /* Offset= -36 (424) */
/* 470 */ 0x21, /* FC_BOGUS_ARRAY */
/* 472 */ 0x3, /* 3 */
/* 474 */ NdrFcShort( 0x0 ), /* 0 */
/* 476 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 478 */ 0x0, /* */
/* 480 */ NdrFcShort( 0x0 ), /* 0 */
/* 482 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 484 */ NdrFcLong( 0xfffffff ), /* -1 */
/* 486 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 488 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
/* 490 */ 0x0, /* 0 */
/* 492 */ NdrFcShort( 0xfffff58 ), /* Offset= -168 (312) */
/* 494 */ 0x5c, /* FC_PAD */
/* 496 */ 0x5b, /* FC_END */
/* 498 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 500 */ 0x3, /* 3 */
/* 502 */ NdrFcShort( 0x10 ), /* 16 */
/* 504 */ NdrFcShort( 0x0 ), /* 0 */
/* 506 */ NdrFcShort( 0x6 ), /* Offset= 6 (496) */
/* 508 */ 0x8, /* FC_LONG */
/* 510 */ 0x39, /* FC_ALIGNM8 */
/* 512 */ 0x36, /* FC_POINTER */
/* 514 */ 0x5b, /* FC_END */
/* 516 */ 0x11, 0x0, /* FC_RP */
/* 518 */ NdrFcShort( 0xfffffdc ), /* Offset= -36 (462) */
/* 520 */ 0x21, /* FC_BOGUS_ARRAY */
/* 522 */ 0x3, /* 3 */
/* 524 */ NdrFcShort( 0x0 ), /* 0 */
/* 526 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 528 */ 0x0, /* */
/* 530 */ NdrFcShort( 0x0 ), /* 0 */
/* 532 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 534 */ NdrFcLong( 0xfffffff ), /* -1 */

```

```

/* 514 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 516 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
          0x0, /* 0 */
/* 518 */ NdrFcShort( 0xfffff44 ), /* Offset= -188 (330) */
/* 520 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 522 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 524 */ NdrFcShort( 0x10 ), /* 16 */
/* 526 */ NdrFcShort( 0x0 ), /* 0 */
/* 528 */ NdrFcShort( 0x6 ), /* Offset= 6 (534) */
/* 530 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 532 */ 0x36, /* FC_POINTER */
          0x5b, /* FC_END */
/* 534 */
          0x11, 0x0, /* FC_RP */
/* 536 */ NdrFcShort( 0xfffffdc ), /* Offset= -36 (500) */
/* 538 */
          0x21, /* FC_BOGUS_ARRAY */
          0x3, /* 3 */
/* 540 */ NdrFcShort( 0x0 ), /* 0 */
/* 542 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 544 */ NdrFcShort( 0x0 ), /* 0 */
/* 546 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 548 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 552 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 554 */
          0x12, 0x0, /* FC_UP */
/* 556 */ NdrFcShort( 0x176 ), /* Offset= 374 (930) */
/* 558 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 560 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 562 */ NdrFcShort( 0x10 ), /* 16 */
/* 564 */ NdrFcShort( 0x0 ), /* 0 */
/* 566 */ NdrFcShort( 0x6 ), /* Offset= 6 (572) */
/* 568 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 570 */ 0x36, /* FC_POINTER */
          0x5b, /* FC_END */
/* 572 */
          0x11, 0x0, /* FC_RP */
/* 574 */ NdrFcShort( 0xfffffdc ), /* Offset= -36 (538) */
/* 576 */
          0x2f, /* FC_IP */
          0x5a, /* FC_CONSTANT_IID */
/* 578 */ NdrFcLong( 0x2f ), /* 47 */
/* 582 */ NdrFcShort( 0x0 ), /* 0 */
/* 584 */ NdrFcShort( 0x0 ), /* 0 */
/* 586 */ 0xc0, /* 192 */
          0x0, /* 0 */

```

```

/* 588 */ 0x0, /* 0 */
          0x0, /* 0 */
/* 590 */ 0x0, /* 0 */
          0x0, /* 0 */
/* 592 */ 0x0, /* 0 */
          0x46, /* 70 */
/* 594 */
          0x1b, /* FC_CARRAY */
          0x0, /* 0 */
/* 596 */ NdrFcShort( 0x1 ), /* 1 */
/* 598 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 600 */ NdrFcShort( 0x4 ), /* 4 */
/* 602 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 604 */ 0x1, /* FC_BYTE */
          0x5b, /* FC_END */
/* 606 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 608 */ NdrFcShort( 0x18 ), /* 24 */
/* 610 */ NdrFcShort( 0x0 ), /* 0 */
/* 612 */ NdrFcShort( 0xc ), /* Offset= 12 (624) */
/* 614 */ 0x8, /* FC_LONG */
          0x8, /* FC_LONG */
/* 616 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
          0x0, /* 0 */
/* 618 */ NdrFcShort( 0xfffffd6 ), /* Offset= -42 (576) */
/* 620 */ 0x39, /* FC_ALIGNM8 */
          0x36, /* FC_POINTER */
/* 622 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 624 */
          0x12, 0x0, /* FC_UP */
/* 626 */ NdrFcShort( 0xfffffe0 ), /* Offset= -32 (594) */
/* 628 */
          0x21, /* FC_BOGUS_ARRAY */
          0x3, /* 3 */
/* 630 */ NdrFcShort( 0x0 ), /* 0 */
/* 632 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 634 */ NdrFcShort( 0x0 ), /* 0 */
/* 636 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 638 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 642 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 644 */
          0x12, 0x0, /* FC_UP */
/* 646 */ NdrFcShort( 0xfffffd8 ), /* Offset= -40 (606) */
/* 648 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 650 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 652 */ NdrFcShort( 0x10 ), /* 16 */
/* 654 */ NdrFcShort( 0x0 ), /* 0 */
/* 656 */ NdrFcShort( 0x6 ), /* Offset= 6 (662) */

```

```

/* 658 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 660 */ 0x36, /* FC_POINTER */
          0x5b, /* FC_END */
/* 662 */
          0x11, 0x0, /* FC_RP */
/* 664 */ NdrFcShort( 0xfffff1dc ), /* Offset= -36 (628) */
/* 666 */
          0x1d, /* FC_SMFARRAY */
          0x0, /* 0 */
/* 668 */ NdrFcShort( 0x8 ), /* 8 */
/* 670 */ 0x2, /* FC_CHAR */
          0x5b, /* FC_END */
/* 672 */
          0x15, /* FC_STRUCT */
          0x3, /* 3 */
/* 674 */ NdrFcShort( 0x10 ), /* 16 */
/* 676 */ 0x8, /* FC_LONG */
          0x6, /* FC_SHORT */
/* 678 */ 0x6, /* FC_SHORT */
          0x4c, /* FC_EMBEDDED_COMPLEX */
/* 680 */ 0x0, /* 0 */
          NdrFcShort( 0xfffff1 ), /* Offset= -15 (666) */
          0x5b, /* FC_END */
/* 684 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 686 */ NdrFcShort( 0x20 ), /* 32 */
/* 688 */ NdrFcShort( 0x0 ), /* 0 */
/* 690 */ NdrFcShort( 0xa ), /* Offset= 10 (700) */
/* 692 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 694 */ 0x36, /* FC_POINTER */
          0x4c, /* FC_EMBEDDED_COMPLEX */
/* 696 */ 0x0, /* 0 */
          NdrFcShort( 0xfffff7 ), /* Offset= -25 (672) */
          0x5b, /* FC_END */
/* 700 */
          0x11, 0x0, /* FC_RP */
/* 702 */ NdrFcShort( 0xfffff10 ), /* Offset= -240 (462) */
/* 704 */
          0x1b, /* FC_CARRAY */
          0x0, /* 0 */
/* 706 */ NdrFcShort( 0x1 ), /* 1 */
/* 708 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 710 */ NdrFcShort( 0x0 ), /* 0 */
/* 712 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 714 */ 0x1, /* FC_BYTE */
          0x5b, /* FC_END */
/* 716 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 718 */ NdrFcShort( 0x10 ), /* 16 */
/* 720 */ NdrFcShort( 0x0 ), /* 0 */

```

```

/* 722 */ NdrFcShort( 0x6 ), /* Offset= 6 (728) */
/* 724 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 726 */ 0x36, /* FC_POINTER */
          0x5b, /* FC_END */
/* 728 */
          0x12, 0x0, /* FC_UP */
/* 730 */ NdrFcShort( 0xfffffe6 ), /* Offset= -26 (704) */
/* 732 */
          0x1b, /* FC_CARRAY */
          0x1, /* 1 */
/* 734 */ NdrFcShort( 0x2 ), /* 2 */
/* 736 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 738 */ NdrFcShort( 0x0 ), /* 0 */
/* 740 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 742 */ 0x6, /* FC_SHORT */
          0x5b, /* FC_END */
/* 744 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 746 */ NdrFcShort( 0x10 ), /* 16 */
/* 748 */ NdrFcShort( 0x0 ), /* 0 */
/* 750 */ NdrFcShort( 0x6 ), /* Offset= 6 (756) */
/* 752 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 754 */ 0x36, /* FC_POINTER */
          0x5b, /* FC_END */
/* 756 */
          0x12, 0x0, /* FC_UP */
/* 758 */ NdrFcShort( 0xfffffe6 ), /* Offset= -26 (732) */
/* 760 */
          0x1b, /* FC_CARRAY */
          0x3, /* 3 */
/* 762 */ NdrFcShort( 0x4 ), /* 4 */
/* 764 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
          0x0, /* */
/* 766 */ NdrFcShort( 0x0 ), /* 0 */
/* 768 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 770 */ 0x8, /* FC_LONG */
          0x5b, /* FC_END */
/* 772 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 774 */ NdrFcShort( 0x10 ), /* 16 */
/* 776 */ NdrFcShort( 0x0 ), /* 0 */
/* 778 */ NdrFcShort( 0x6 ), /* Offset= 6 (784) */
/* 780 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 782 */ 0x36, /* FC_POINTER */
          0x5b, /* FC_END */
/* 784 */
          0x12, 0x0, /* FC_UP */
/* 786 */ NdrFcShort( 0xfffffe6 ), /* Offset= -26 (760) */
/* 788 */

```

```

0x1b, /* FC_CARRAY */
0x7, /* 7 */
/* 790 */ NdrFcShort( 0x8 ), /* 8 */
/* 792 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
0x0, /* */
/* 794 */ NdrFcShort( 0x0 ), /* 0 */
/* 796 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 798 */ 0xb, /* FC_HYPER */
0x5b, /* FC_END */
/* 800 */
0x1a, /* FC_BOGUS_STRUCT */
0x3, /* 3 */
/* 802 */ NdrFcShort( 0x10 ), /* 16 */
/* 804 */ NdrFcShort( 0x0 ), /* 0 */
/* 806 */ NdrFcShort( 0x6 ), /* Offset= 6 (812) */
/* 808 */ 0x8, /* FC_LONG */
0x39, /* FC_ALIGNM8 */
/* 810 */ 0x36, /* FC_POINTER */
0x5b, /* FC_END */
/* 812 */
0x12, 0x0, /* FC_UP */
/* 814 */ NdrFcShort( 0xfffffe6 ), /* Offset= -26 (788) */
/* 816 */
0x15, /* FC_STRUCT */
0x3, /* 3 */
/* 818 */ NdrFcShort( 0x8 ), /* 8 */
/* 820 */ 0x8, /* FC_LONG */
0x8, /* FC_LONG */
/* 822 */ 0x5c, /* FC_PAD */
0x5b, /* FC_END */
/* 824 */
0x1b, /* FC_CARRAY */
0x3, /* 3 */
/* 826 */ NdrFcShort( 0x8 ), /* 8 */
/* 828 */ 0x7, /* Corr desc: FC_USHORT */
0x0, /* */
/* 830 */ NdrFcShort( 0xffc8 ), /* -56 */
/* 832 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 834 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
0x0, /* 0 */
/* 836 */ NdrFcShort( 0xfffffec ), /* Offset= -20 (816) */
/* 838 */ 0x5c, /* FC_PAD */
0x5b, /* FC_END */
/* 840 */
0x1a, /* FC_BOGUS_STRUCT */
0x3, /* 3 */
/* 842 */ NdrFcShort( 0x38 ), /* 56 */
/* 844 */ NdrFcShort( 0xfffffec ), /* Offset= -20 (824) */
/* 846 */ NdrFcShort( 0x0 ), /* Offset= 0 (846) */
/* 848 */ 0x6, /* FC_SHORT */
0x6, /* FC_SHORT */
/* 850 */ 0x38, /* FC_ALIGNM4 */
0x8, /* FC_LONG */
/* 852 */ 0x8, /* FC_LONG */
0x4c, /* FC_EMBEDDED_COMPLEX */

```

```

/* 854 */ 0x4, /* 4 */
NdrFcShort( 0xfffffe0d ), /* Offset= -499 (356) */
0x5b, /* FC_END */
/* 858 */
0x12, 0x0, /* FC_UP */
/* 860 */ NdrFcShort( 0xfffff02 ), /* Offset= -254 (606) */
/* 862 */
0x12, 0x8, /* FC_UP [simple_pointer] */
/* 864 */ 0x1, /* FC_BYTE */
0x5c, /* FC_PAD */
/* 866 */
0x12, 0x8, /* FC_UP [simple_pointer] */
/* 868 */ 0x6, /* FC_SHORT */
0x5c, /* FC_PAD */
/* 870 */
0x12, 0x8, /* FC_UP [simple_pointer] */
/* 872 */ 0x8, /* FC_LONG */
0x5c, /* FC_PAD */
/* 874 */
0x12, 0x8, /* FC_UP [simple_pointer] */
/* 876 */ 0xa, /* FC_FLOAT */
0x5c, /* FC_PAD */
/* 878 */
0x12, 0x8, /* FC_UP [simple_pointer] */
/* 880 */ 0xc, /* FC_DOUBLE */
0x5c, /* FC_PAD */
/* 882 */
0x12, 0x0, /* FC_UP */
/* 884 */ NdrFcShort( 0xffffda4 ), /* Offset= -604 (280) */
/* 886 */
0x12, 0x10, /* FC_UP [pointer_deref] */
/* 888 */ NdrFcShort( 0xffffda6 ), /* Offset= -602 (286) */
/* 890 */
0x12, 0x10, /* FC_UP [pointer_deref] */
/* 892 */ NdrFcShort( 0xffffdbc ), /* Offset= -580 (312) */
/* 894 */
0x12, 0x10, /* FC_UP [pointer_deref] */
/* 896 */ NdrFcShort( 0xffffdca ), /* Offset= -566 (330) */
/* 898 */
0x12, 0x10, /* FC_UP [pointer_deref] */
/* 900 */ NdrFcShort( 0xffffdd8 ), /* Offset= -552 (348) */
/* 902 */
0x12, 0x10, /* FC_UP [pointer_deref] */
/* 904 */ NdrFcShort( 0x2 ), /* Offset= 2 (906) */
/* 906 */
0x12, 0x0, /* FC_UP */
/* 908 */ NdrFcShort( 0x16 ), /* Offset= 22 (930) */
/* 910 */
0x15, /* FC_STRUCT */
0x7, /* 7 */
/* 912 */ NdrFcShort( 0x10 ), /* 16 */
/* 914 */ 0x6, /* FC_SHORT */
0x1, /* FC_BYTE */
/* 916 */ 0x1, /* FC_BYTE */
0x38, /* FC_ALIGNM4 */

```

```

/* 918 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 920 */ 0xb, /* FC_HYPER */
          0x5b, /* FC_END */
/* 922 */
          0x12, 0x0, /* FC_UP */
/* 924 */ NdrFcShort( 0xfffff2 ), /* Offset= -14 (910) */
/* 926 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 928 */ 0x2, /* FC_CHAR */
          0x5c, /* FC_PAD */
/* 930 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x7, /* 7 */
/* 932 */ NdrFcShort( 0x20 ), /* 32 */
/* 934 */ NdrFcShort( 0x0 ), /* 0 */
/* 936 */ NdrFcShort( 0x0 ), /* Offset= 0 (936) */
/* 938 */ 0x8, /* FC_LONG */
          0x8, /* FC_LONG */
/* 940 */ 0x6, /* FC_SHORT */
          0x6, /* FC_SHORT */
/* 942 */ 0x6, /* FC_SHORT */
          0x6, /* FC_SHORT */
/* 944 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
          0x0, /* 0 */
/* 946 */ NdrFcShort( 0xffffc54 ), /* Offset= -940 (6) */
/* 948 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 950 */ 0xb4, /* FC_USER_MARSHAL */
          0x83, /* 131 */
/* 952 */ NdrFcShort( 0x0 ), /* 0 */
/* 954 */ NdrFcShort( 0x18 ), /* 24 */
/* 956 */ NdrFcShort( 0x0 ), /* 0 */
/* 958 */ NdrFcShort( 0xffffc44 ), /* Offset= -956 (2) */
/* 960 */
          0x11, 0x4, /* FC_RP [alloted_on_stack] */
/* 962 */ NdrFcShort( 0x6 ), /* Offset= 6 (968) */
/* 964 */
          0x13, 0x0, /* FC_OP */
/* 966 */ NdrFcShort( 0xfffffdc ), /* Offset= -36 (930) */
/* 968 */ 0xb4, /* FC_USER_MARSHAL */
          0x83, /* 131 */
/* 970 */ NdrFcShort( 0x0 ), /* 0 */
/* 972 */ NdrFcShort( 0x18 ), /* 24 */
/* 974 */ NdrFcShort( 0x0 ), /* 0 */
/* 976 */ NdrFcShort( 0xfffff4 ), /* Offset= -12 (964) */

          0x0
    }
};

const CInterfaceProxyVtbl * _tpcc_com_ps_ProxyVtblList[] =
{
    ( CInterfaceProxyVtbl *) &_ITPCCProxyVtbl,
    0
}

```

```

};

const CInterfaceStubVtbl * _tpcc_com_ps_StubVtblList[] =
{
    ( CInterfaceStubVtbl *) &_ITPCCStubVtbl,
    0
};

PCInterfaceName const _tpcc_com_ps_InterfaceNamesList[] =
{
    "ITPCC",
    0
};

#define _tpcc_com_ps_CHECK_IID(n) IID_GENERIC_CHECK_IID( _tpcc_com_ps, pIID, n)

int __stdcall _tpcc_com_ps_IID_Lookup( const IID * pIID, int * pIndex )
{
    if(!_tpcc_com_ps_CHECK_IID(0))
    {
        *pIndex = 0;
        return 1;
    }

    return 0;
}

const ExtendedProxyFileInfo tpcc_com_ps_ProxyFileInfo =
{
    (PCInterfaceProxyVtblList *) &_tpcc_com_ps_ProxyVtblList,
    (PCInterfaceStubVtblList *) &_tpcc_com_ps_StubVtblList,
    (const PCInterfaceName *) &_tpcc_com_ps_InterfaceNamesList,
    0, // no delegation
    &_tpcc_com_ps_IID_Lookup,
    1,
    2,
    0, /* table of [async_uuid] interfaces */
    0, /* Filler1 */
    0, /* Filler2 */
    0 /* Filler3 */
};

#endif /* defined(_M_IA64) || defined(_M_AXP64) */

```

## Appendix B - Database Details

## BACKUP.SQL

```
-- File:      BACKUP.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates backup of tpcc database

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

dump database tpcc to tpccback1, tpccback2, tpccback3, tpccback4, tpccback5,
tpccback6 with init, stats = 1

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go
```

## BACKUPDEV.SQL

```
-- File:      BACKUPDEVB.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates tpcc database Backup Devices

use master
go

-- create backup devices

exec sp_addumpdevice 'disk','tpccback1','U:\tpccback1.dmp'
exec sp_addumpdevice 'disk','tpccback2','V:\tpccback2.dmp'
exec sp_addumpdevice 'disk','tpccback3','W:\tpccback3.dmp'
exec sp_addumpdevice 'disk','tpccback4','X:\tpccback4.dmp'
exec sp_addumpdevice 'disk','tpccback5','Y:\tpccback5.dmp'
exec sp_addumpdevice 'disk','tpccback6','Z:\tpccback6.dmp'

go
```

## CREATEDB.SQL

```
-- File:      CREATEDB.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates tpcc database and backup files

use master
go
```

```
-- Create temporary table for timing

if exists ( select name from sysobjects where name = 'tpcc_timer' )
drop table tpcc_timer
go

create table tpcc_timer
(
    start_date          char(30),
    end_date            char(30)
)

insert into tpcc_timer values (0,0)
go

-- Store starting time

update tpcc_timer
set start_date = (select convert(char(30), getdate(),9))
go

-- create main database files

CREATE DATABASE tpcc
ON PRIMARY
(
    NAME          = MSSQL70_tpcc_root,
    FILENAME      = "C:\tpcc_root.mdf",
    SIZE          = 50MB,
    FILEGROWTH    = 0),
FILEGROUP MSSQL70_cs_fg
(
    NAME          = MSSQL70_cs1,
    FILENAME      = "E:",
    SIZE          = 52000MB,
    FILEGROWTH    = 0),
(
    NAME          = MSSQL70_cs2,
    FILENAME      = "F:",
    SIZE          = 52000MB,
    FILEGROWTH    = 0),
(
    NAME          = MSSQL70_cs3,
    FILENAME      = "G:",
    SIZE          = 52000MB,
    FILEGROWTH    = 0),
(
    NAME          = MSSQL70_cs4,
    FILENAME      = "H:",
    SIZE          = 52000MB,
    FILEGROWTH    = 0),
(
    NAME          = MSSQL70_cs5,
    FILENAME      = "I:",
    SIZE          = 52000MB,
    FILEGROWTH    = 0),
(
    NAME          = MSSQL70_cs6,
    FILENAME      = "J:",
    SIZE          = 52000MB,
    FILEGROWTH    = 0),
FILEGROUP MSSQL70_misc_fg
```

```

( NAME      = MSSQL70_misc1,
  FILENAME  = "N:",
  SIZE      = 28000MB,
  FILEGROWTH = 0),
( NAME      = MSSQL70_misc2,
  FILENAME  = "O:",
  SIZE      = 28000MB,
  FILEGROWTH = 0),
( NAME      = MSSQL70_misc3,
  FILENAME  = "P:",
  SIZE      = 28000MB,
  FILEGROWTH = 0),
( NAME      = MSSQL70_misc4,
  FILENAME  = "Q:",
  SIZE      = 28000MB,
  FILEGROWTH = 0),
( NAME      = MSSQL70_misc5,
  FILENAME  = "R:",
  SIZE      = 28000MB,
  FILEGROWTH = 0),
( NAME      = MSSQL70_misc6,
  FILENAME  = "S:",
  SIZE      = 28000MB,
  FILEGROWTH = 0)
LOG ON
( NAME      =MSSQL70_tpcc_log,
  FILENAME  = "L:",
  SIZE      =80000MB,
  FILEGROWTH=0)
go

-- Store ending time
update   tpcc_timer
set end_date = (select convert(char(30), getdate(),9))
go

select "Elapsed time (in seconds): ", datediff(second,(select start_date
from tpcc_timer),(select end_date from tpcc_timer))

-- remove temporary table

if exists ( select name from sysobjects where name = 'tpcc_timer' )
  drop table tpcc_timer
go

```

## DBOPT1.SQL

```

-- File:      DBOPT1.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Sets database options for data load

```

```
use master
```

```

go
exec sp_dboption tpcc,'select into/bulkcopy',true
exec sp_dboption tpcc,'trunc. log on chkpt.',true
go

use tpcc
go

checkpoint
go

```

## DBOPT2.SQL

```

-- File:      DBOPT2.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Resets database options after data load

sp_dboption tpcc,'select into/bulkcopy',FALSE
GO

sp_dboption tpcc,'trunc. log on chkpt.',FALSE
GO

USE tpcc
GO

CHECKPOINT
GO

sp_configure 'allow updates',1
GO

RECONFIGURE WITH OVERRIDE
GO

DECLARE   @msg          varchar(50)

IF (SELECT (SUBSTRING((SELECT @@version),1,26))) = 'Microsoft SQL Server
2000'
  BEGIN
    --
    --           OPTIONS FOR SQL SERVER 8.0
    -- Set option values for user-defined indexes
    --
    SET @msg = ' '
    PRINT@msg
    SET @msg = 'Setting SQL Server 8.0 indexoptions'
    PRINT@msg
  END

```

```

SET @msg = ' '
PRINT @msg

EXEC sp_indexoption 'customer', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'district', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'warehouse', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'stock', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'order_line', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'orders', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'new_order', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'item', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'item', 'DisallowPageLocks', TRUE

END
ELSE
BEGIN
--
-- OPTIONS FOR SQL SERVER 7.0
-- Set option values for user-defined indexes
--

SET @msg = ' '
PRINT @msg
SET @msg = 'Setting SQL Server 7.0 indexoptions'
PRINT @msg
SET @msg = ' '
PRINT @msg

EXEC sp_indexoption 'customer', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'district', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'warehouse', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'stock', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'order_line', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'orders', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'new_order', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'item', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'item', 'AllowPageLocks', FALSE

END
GO

Print ' '
Print '*****'
Print 'Pre-specified Locking Hierarchy:'
Print ' Lockflag = 0 ==> No pre-specified hierarchy'
Print ' Lockflag = 1 ==> Lock at Page-level then Table-level'
Print ' Lockflag = 2 ==> Lock at Row-level then Table-level'
Print ' Lockflag = 3 ==> Lock at Table-level'
Print ' '

SELECT name,lockflags
FROM sysindexes
WHERE object_id('warehouse') = id OR
object_id('district') = id OR
object_id('customer') = id OR
object_id('stock') = id OR

```

```

object_id('orders') = id OR
object_id('order_line') = id OR
object_id('history') = id OR
object_id('new_order') = id OR
object_id('item') = id
ORDERBY lockflags asc
GO

sp_configure 'allow updates',0
GO

RECONFIGURE WITH OVERRIDE
GO

EXEC sp_dboption tpcc, 'auto update statistics', FALSE
EXEC sp_dboption tpcc, 'auto create statistics', FALSE
EXEC sp_dboption tpcc, 'torn page detection', FALSE
GO

EXEC sp_tableoption 'district', 'pintable',true
EXEC sp_tableoption 'warehouse', 'pintable',true
EXEC sp_tableoption 'new_order', 'pintable',true
EXEC sp_tableoption 'item', 'pintable',true
GO

```

## REMOVEDB.SQL

```

-- File: REMOVEDB.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.20
-- Copyright Microsoft, 1999
-- Purpose: Removes tpcc database and backup files

use master
go

-- remove any existing database and backup files

exec sp_dbremove tpcc, dropdev
go

exec sp_dropdevice 'tpccback1'
exec sp_dropdevice 'tpccback2'
exec sp_dropdevice 'tpccback3'
exec sp_dropdevice 'tpccback4'
exec sp_dropdevice 'tpccback5'
exec sp_dropdevice 'tpccback6'
go

```

## RESTORE.SQL

```

-- File: RESTORE.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.20
-- Copyright Microsoft, 1999

```

```
-- Purpose: Loads database backup from backup files

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

load database tpcc from tpccback1, tpccback2, tpccback3, tpccback4,
tpccback5, tpccback6 with stats = 1

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go
```

## VERIFYTPCCLOAD.SQL

```
-- File:      VERIFYTPCCLOAD.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Performs series of TPC-C database checks to verify
--           that database load completed correctly
```

```
print " "
select      convert(char(30), getdate(),9)
print " "

use tpcc
go

-- *****
--
-- Check rows per table from SYSINDEXES
--
-- *****

print 'WAREHOUSE TABLE'

select      rows
from sysindexes
whereid    = object_id("warehouse")
go

print 'DISTRICT TABLE = (10 * No of warehouses)'

select      rows
from sysindexes
whereid    =object_id("district")
go

print 'ITEM TABLE = 100,000'

select      rows
```

```
from sysindexes
whereid    =object_id("item")
go

print 'CUSTOMER TABLE = (30,000 * No of warehouses)'
```

```
select      rows
from sysindexes
whereid    =object_id("customer")
go

print 'ORDERS TABLE = (30,000 * No of warehouses)'
```

```
select      rows
from sysindexes
whereid    =object_id("orders")
go

print 'HISTORY TABLE = (30,000 * No of warehouses)'
```

```
select      rows
from sysindexes
whereid    =object_id("history")
go

print 'STOCK TABLE = (100,000 * No of warehouses)'
```

```
select      rows
from sysindexes
whereid    =object_id("stock")
go

print 'ORDER_LINE TABLE = (300,000 * No of warehouses + some change)'
```

```
select      rows
from sysindexes
whereid    =object_id("order_line")
go

print 'NEW_ORDER TABLE = (9000 * No of warehouses)'
```

```
select      rows
from sysindexes
whereid    =object_id("new_order")
go

-- *****
--
-- Check indices
--
-- *****

print '*****Index Check*****'

use tpcc
```

```

go

sp_helpindex customer
go

sp_helpindex stock
go

sp_helpindex district
go

sp_helpindex item
go

sp_helpindex new_order
go

sp_helpindex orders
go

sp_helpindex order_line
go

sp_helpindex warehouse
go

```

## IDXCUSCL.SQL

```

-- File: IDXCUSCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.20
-- Copyright Microsoft, 1999
-- Purpose: Creates clustered index on customer table

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'customer_c1' )
    drop index customer.customer_c1

create unique clustered index customer_c1 on customer(c_w_id, c_d_id, c_id)
on MSSQL70_cs_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

## IDXCUSNC.SQL

```

-- File: IDXCUSNC.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.20
-- Copyright Microsoft, 1999
-- Purpose: Creates non-clustered index on customer table

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'customer_nc1' )
    drop index customer.customer_nc1

create unique nonclustered index customer_nc1 on customer(c_w_id, c_d_id,
c_last, c_first, c_id)
on MSSQL70_cs_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

## IDXDISCL.SQL

```

-- File: IDXDISCL.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.20
-- Copyright Microsoft, 1999
-- Purpose: Creates clustered index on district table

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'district_c1' )
    drop index district.district_c1

create unique clustered index district_c1 on district(d_w_id, d_id)
with fillfactor=100 on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)

```

```
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
go
```

## IDXITMCL.SQL

```
-- File:      IDXITMCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on item table
```

```
use tpcc
go
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```
if exists ( select name from sysindexes where name = 'item_c1' )
    drop index item.item_c1
```

```
create unique clustered index item_c1 on item(i_id)
    on MSSQL70_misc_fg
```

```
select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
go
```

## IDXNODCL.SQL

```
-- File:      IDXNODCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on new_order table
```

```
use tpcc
go
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```
if exists ( select name from sysindexes where name = 'new_order_c1' )
    drop index new_order.new_order_c1
```

```
create unique clustered index new_order_c1 on new_order(no_w_id, no_d_id,
no_o_id)
    on MSSQL70_misc_fg
```

```
select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
```

```
go
```

## IDXODLCL.SQL

```
-- File:      IDXODLCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on order_line table
```

```
use tpcc
go
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```
if exists ( select name from sysindexes where name = 'order_line_c1' )
    drop index order_line.order_line_c1
```

```
create unique clustered index order_line_c1 on order_line(ol_w_id, ol_d_id,
ol_o_id, ol_number)
    on MSSQL70_misc_fg
```

```
select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
```

```
go
```

## IDXORDCL.SQL

```
-- File:      IDXORDCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on orders table
```

```
use tpcc
go
```

```
declare @startdate datetime
```

```

declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'orders_cl' )
    drop index orders.orders_cl

create unique clustered index orders_cl on orders(o_w_id, o_d_id, o_id)
    on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

## IDXORDNC.SQL

```

-- File:      IDXORDNC.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates non-clustered index on orders table

```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'orders_ncl' )
    drop index orders.orders_ncl

create index orders_ncl on orders(o_w_id, o_d_id, o_c_id, o_id)
    on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

## IDXSTKCL.SQL

```

-- File:      IDXSTKCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on stock table

```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'stock_cl' )
    drop index stock.stock_cl

create unique clustered index stock_cl on stock(s_i_id, s_w_id)
    on MSSQL70_cs_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

## IDXWARCL.SQL

```

-- File:      IDXWARCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on warehouse table

```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'warehouse_cl' )
    drop index warehouse.warehouse_cl

create unique clustered index warehouse_cl on warehouse(w_id)
    with fillfactor=100 on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

## TABLES.SQL

```
-- File:      TABLES.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates TPC-C tables

use tpcc
go

--
-- Remove all existing TPC-C tables
--

if exists ( select name from sysobjects where name = 'warehouse' )
    drop table warehouse
go
if exists ( select name from sysobjects where name = 'district' )
    drop table district
go
if exists ( select name from sysobjects where name = 'customer' )
    drop table customer
go
if exists ( select name from sysobjects where name = 'history' )
    drop table history
go
if exists ( select name from sysobjects where name = 'new_order' )
    drop table new_order
go
if exists ( select name from sysobjects where name = 'orders' )
    drop table orders
go
if exists ( select name from sysobjects where name = 'order_line' )
    drop table order_line
go
if exists ( select name from sysobjects where name = 'item' )
    drop table item
go
if exists ( select name from sysobjects where name = 'stock' )
    drop table stock
go

--
-- Create new tables
--

create table warehouse
(
    w_id          smallint,
    w_name        char(10),
    w_street_1    char(20),
    w_street_2    char(20),
    w_city        char(20),
    w_state       char(2),


```

```
    w_zip        char(9),
    w_tax        numeric(4,4),
    w_ytd        numeric(12,2)
) on MSSQL70_misc_fg
go

create table district
(
    d_id          tinyint,
    d_w_id        smallint,
    d_name        char(10),
    d_street_1    char(20),
    d_street_2    char(20),
    d_city        char(20),
    d_state       char(2),
    d_zip        char(9),
    d_tax        numeric(4,4),
    d_ytd        numeric(12,2),
    d_next_o_id   int
) on MSSQL70_misc_fg
go

create table customer
(
    c_id          int,
    c_d_id        tinyint,
    c_w_id        smallint,
    c_first       char(16),
    c_middle      char(2),
    c_last        char(16),
    c_street_1    char(20),
    c_street_2    char(20),
    c_city        char(20),
    c_state       char(2),
    c_zip        char(9),
    c_phone       char(16),
    c_since       datetime,
    c_credit      char(2),
    c_credit_lim  numeric(12,2),
    c_discount    numeric(4,4),
    c_balance     numeric(12,2),
    c_ytd_payment numeric(12,2),
    c_payment_cnt smallint,
    c_delivery_cnt smallint,
    c_data        char(500)
) on MSSQL70_cs_fg
go

create table history
(
    h_c_id        int,
    h_c_d_id      tinyint,
    h_c_w_id      smallint,
    h_d_id        tinyint,
    h_w_id        smallint,
```

```

        h_date            datetime,
        h_amount          numeric(6,2),
        h_data            char(24)
) on MSSQL70_misc_fg
go

create table new_order
(
    no_o_id              int,
    no_d_id              tinyint,
    no_w_id              smallint
) on MSSQL70_misc_fg
go

create table orders
(
    o_id                int,
    o_d_id              tinyint,
    o_w_id              smallint,
    o_c_id              int,
    o_entry_d           datetime,
    o_carrier_id        tinyint,
    o_ol_cnt            tinyint,
    o_all_local         tinyint
) on MSSQL70_misc_fg
go

create table order_line
(
    ol_o_id             int,
    ol_d_id             tinyint,
    ol_w_id             smallint,
    ol_number           tinyint,
    ol_i_id             int,
    ol_supply_w_id     smallint,
    ol_delivery_d       datetime,
    ol_quantity         smallint,
    ol_amount           numeric(6,2),
    ol_dist_info        char(24)
) on MSSQL70_misc_fg
go

create table item
(
    i_id               int,
    i_im_id            int,
    i_name              char(24),
    i_price             numeric(5,2),
    i_data              char(50)
) on MSSQL70_misc_fg
go

create table stock
(
    s_i_id             int,

```

```

    s_w_id              smallint,
    s_quantity         smallint,
    s_dist_01          char(24),
    s_dist_02          char(24),
    s_dist_03          char(24),
    s_dist_04          char(24),
    s_dist_05          char(24),
    s_dist_06          char(24),
    s_dist_07          char(24),
    s_dist_08          char(24),
    s_dist_09          char(24),
    s_dist_10          char(24),
    s_ytd              int,
    s_order_cnt        smallint,
    s_remote_cnt       smallint,
    s_data              char(50)
) on MSSQL70_cs_fg
go

```

## DELIVERY.SQL

```

-- File:      DELIVERY.SQL
--            Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--            Copyright Microsoft, 1999, 2000
-- Purpose:   Creates delivery transaction stored procedure
--
-- Interface Level: 4.10.000

use tpcc
go

if exists (select name from sysobjects where name = "tpcc_delivery" )
drop procedure tpcc_delivery
go

create proc tpcc_delivery @w_id          smallint,
                        @o_carrier_id    smallint
as

declare @d_id  tinyint,
        @o_id  int,
        @c_id  int,
        @total numeric(12,2),
        @oid1  int,
        @oid2  int,
        @oid3  int,
        @oid4  int,
        @oid5  int,
        @oid6  int,
        @oid7  int,
        @oid8  int,
        @oid9  int,
        @oid10 int

```

```

select @d_id = 0

begin tran d

  while (@d_id < 10)
  begin

    select @d_id = @d_id + 1,
           @total = 0,
           @o_id = 0

    select top 1
           @o_id= no_o_id
    from new_order (serializable uplock)
    where no_w_id = @w_id and
          no_d_id = @d_id
    order by no_o_id asc

    if (@@rowcount <> 0)
    begin

-- claim the order for this district

      delete new_order
      where no_w_id = @w_id and
            no_d_id = @d_id and
            no_o_id = @o_id

-- set carrier_id on this order (and get customer id)

      update orders
      set o_carrier_id = @o_carrier_id,
          @c_id = o_c_id
      where o_w_id = @w_id and
            o_d_id = @d_id and
            o_id = @o_id

-- set date in all lineitems for this order (and sum amounts)

      update order_line
      set ol_delivery_d = getdate(),
          @total = @total + ol_amount
      where ol_w_id = @w_id and
            ol_d_id = @d_id and
            ol_o_id = @o_id

-- accumulate lineitem amounts for this order into customer

      update customer
      set c_balance = c_balance + @total,
          c_delivery_cnt = c_delivery_cnt + 1
      where c_w_id = @w_id and
            c_d_id = @d_id and
            c_id = @c_id

```

```

end

select @oid1 = case @d_id when 1 then @o_id else @oid1 end,
       @oid2 = case @d_id when 2 then @o_id else @oid2 end,
       @oid3 = case @d_id when 3 then @o_id else @oid3 end,
       @oid4 = case @d_id when 4 then @o_id else @oid4 end,
       @oid5 = case @d_id when 5 then @o_id else @oid5 end,
       @oid6 = case @d_id when 6 then @o_id else @oid6 end,
       @oid7 = case @d_id when 7 then @o_id else @oid7 end,
       @oid8 = case @d_id when 8 then @o_id else @oid8 end,
       @oid9 = case @d_id when 9 then @o_id else @oid9 end,
       @oid10 = case @d_id when 10 then @o_id else @oid10 end

end

commit tran d

-- return delivery data to client

select @oid1,
       @oid2,
       @oid3,
       @oid4,
       @oid5,
       @oid6,
       @oid7,
       @oid8,
       @oid9,
       @oid10

```

go

## NEWORDER.SQL

```

-- File:      NEWORDER.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Creates new order transaction stored procedure
--
-- Interface Level: 4.10.000

use tpcc
go

if exists ( select name from sysobjects where name = "tpcc_neworder" )
drop procedure tpcc_neworder
go

create proc tpcc_neworder
           @w_id      smallint,
           @d_id      tinyint,
           @c_id      int,
           @o_ol_cnt  tinyint,
           @o_all_local tinyint,

```

```

        @i_id1 int = 0, @s_w_id1 smallint = 0, @ol_qty1
smallint = 0,
        @i_id2 int = 0, @s_w_id2 smallint = 0, @ol_qty2
smallint = 0,
        @i_id3 int = 0, @s_w_id3 smallint = 0, @ol_qty3
smallint = 0,
        @i_id4 int = 0, @s_w_id4 smallint = 0, @ol_qty4
smallint = 0,
        @i_id5 int = 0, @s_w_id5 smallint = 0, @ol_qty5
smallint = 0,
        @i_id6 int = 0, @s_w_id6 smallint = 0, @ol_qty6
smallint = 0,
        @i_id7 int = 0, @s_w_id7 smallint = 0, @ol_qty7
smallint = 0,
        @i_id8 int = 0, @s_w_id8 smallint = 0, @ol_qty8
smallint = 0,
        @i_id9 int = 0, @s_w_id9 smallint = 0, @ol_qty9
smallint = 0,
        @i_id10 int = 0, @s_w_id10 smallint = 0, @ol_qty10
smallint = 0,
        @i_id11 int = 0, @s_w_id11 smallint = 0, @ol_qty11
smallint = 0,
        @i_id12 int = 0, @s_w_id12 smallint = 0, @ol_qty12
smallint = 0,
        @i_id13 int = 0, @s_w_id13 smallint = 0, @ol_qty13
smallint = 0,
        @i_id14 int = 0, @s_w_id14 smallint = 0, @ol_qty14
smallint = 0,
        @i_id15 int = 0, @s_w_id15 smallint = 0, @ol_qty15
smallint = 0

as
declare    @w_tax          numeric(4,4),
           @d_tax          numeric(4,4),
           @c_last        char(16),
           @c_credit      char(2),
           @c_discount    numeric(4,4),
           @i_price       numeric(5,2),
           @i_name        char(24),
           @i_data        char(50),
           @o_entry_d     datetime,
           @remote_flag   int,
           @s_quantity    smallint,
           @s_data        char(50),
           @s_dist        char(24),
           @li_no         int,
           @o_id          int,
           @commit_flag   tinyint,
           @li_id         int,
           @li_s_w_id     smallint,
           @li_qty        smallint,
           @ol_number    int,
           @c_id_local    int

begin

```

```

begin transaction n
-- get district tax and next available order id and update
-- plus initialize local variables

        update    district
        set    @d_tax      = d_tax,
               @o_id      = d_next_o_id,
               d_next_o_id = d_next_o_id + 1,
               @o_entry_d = getdate(),
               @li_no     = 0,
               @commit_flag = 1
        whered_w_id      = @w_id and
               d_id      = @d_id

-- process orderlines

        while (@li_no < @o_ol_cnt)
        begin

                select @li_no = @li_no + 1

-- set i_id, s_w_id, and qty for this lineitem

                select    @li_id = case @li_no
                           when 1 then @i_id1
                           when 2 then @i_id2
                           when 3 then @i_id3
                           when 4 then @i_id4
                           when 5 then @i_id5
                           when 6 then @i_id6
                           when 7 then @i_id7
                           when 8 then @i_id8
                           when 9 then @i_id9
                           when 10 then @i_id10
                           when 11 then @i_id11
                           when 12 then @i_id12
                           when 13 then @i_id13
                           when 14 then @i_id14
                           when 15 then @i_id15
                           end,

                           @li_s_w_id = case @li_no
                                           when 1 then @s_w_id1
                                           when 2 then @s_w_id2
                                           when 3 then @s_w_id3
                                           when 4 then @s_w_id4
                                           when 5 then @s_w_id5
                                           when 6 then @s_w_id6
                                           when 7 then @s_w_id7
                                           when 8 then @s_w_id8
                                           when 9 then @s_w_id9
                                           when 10 then @s_w_id10
                                           when 11 then @s_w_id11

```

```

        when 12 then @s_w_id12
        when 13 then @s_w_id13
        when 14 then @s_w_id14
        when 15 then @s_w_id15
    end,

    @li_qty = case @li_no
        when 1 then @ol_qty1
        when 2 then @ol_qty2
        when 3 then @ol_qty3
        when 4 then @ol_qty4
        when 5 then @ol_qty5
        when 6 then @ol_qty6
        when 7 then @ol_qty7
        when 8 then @ol_qty8
        when 9 then @ol_qty9
        when 10 then @ol_qty10
        when 11 then @ol_qty11
        when 12 then @ol_qty12
        when 13 then @ol_qty13
        when 14 then @ol_qty14
        when 15 then @ol_qty15
    end

-- get item data (no one updates item)

    select      @i_price = i_price,
               @i_name  = i_name,
               @i_data  = i_data
    from item (tablock repeatableread)
    where i_id = @li_id

-- update stock values

    update      stock
    set  s_ytd      = s_ytd + @li_qty,
        @s_quantity = s_quantity - @li_qty +
            case when (s_quantity - @li_qty < 10)
then 91 else 0 end,
        s_order_cnt      = s_order_cnt + 1,
        s_remote_cnt     = s_remote_cnt + case when (@li_s_w_id =
@w_id) then 0 else 1 end,
        @s_data          = s_data,
        @s_dist          = case @d_id
            when 1 then s_dist_01
            when 2 then s_dist_02
            when 3 then s_dist_03
            when 4 then s_dist_04
            when 5 then s_dist_05
            when 6 then s_dist_06
            when 7 then s_dist_07
            when 8 then s_dist_08
            when 9 then s_dist_09
            when 10 then s_dist_10
        end

```

```

        where s_i_id      = @li_id and
               s_w_id     = @li_s_w_id

-- if there actually is a stock (and item) with these ids, go to work

        if (@@rowcount > 0)
        begin

-- insert order_line data (using data from item and stock)

            insert into order_line values(@o_id,
                                           @d_id,
                                           @w_id,
                                           @li_no,
                                           @li_id,
                                           @li_s_w_id,
                                           "dec 31, 1899",
                                           @li_qty,
                                           @i_price * @li_qty,
                                           @s_dist)

-- send line-item data to client

            select      @i_name,
                       @s_quantity,
                       b_g = case when ( (patindex("%ORIGINAL%",@i_data) > 0)
and
                                           (patindex("%ORIGINAL%",@s_data) > 0) )
                           then "B" else "G" end,
                       @i_price,
                       @i_price * @li_qty

            end
            else
            begin

-- no item (or stock) found - triggers rollback condition

            select "",0,"",0,0
            select @commit_flag = 0

            end

-- get customer last name, discount, and credit rating

            select      @c_last      = c_last,
                       @c_discount = c_discount,
                       @c_credit   = c_credit,
                       @c_id_local = c_id
            from customer (repeatableread)
            where c_id      = @c_id and
                   c_w_id  = @w_id and
                   c_d_id  = @d_id

```

```

-- insert fresh row into orders table

    insert into orders values (      @o_id,
                                @d_id,
                                @w_id,
                                @c_id_local,
                                @o_entry_d,
                                0,
                                @o_ol_cnt,
                                @o_all_local)

-- insert corresponding row into new-order table

    insert into new_order values ( @o_id,
                                @d_id,
                                @w_id)

-- select warehouse tax

select      @w_tax      = w_tax
from warehouse (repeatableread)
where w_id = @w_id

if (@commit_flag = 1)
    commit transaction n
else

-- all that work for nuthin!!!

    rollback transaction n

-- return order data to client

select      @w_tax,
            @d_tax,
            @o_id,
            @c_last,
            @c_discount,
            @c_credit,
            @o_entry_d,
            @commit_flag

end

go

ORDSTAT.SQL

-- File:      ORDSTAT.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Creates order status transaction stored procedure
--
--           Interface Level: 4.10.000

```

```

use tpcc
go

if exists ( select name from sysobjects where name = "tpcc_orderstatus" )
    drop procedure    tpcc_orderstatus
go

create proc tpcc_orderstatus    @w_idsmallint,
                                @d_idtinyint,
                                @c_idint,
                                @c_last    char(16) = ""

as

declare @c_balance      numeric(12,2),
        @c_first        char(16),
        @c_middle       char(2),
        @o_id           int,
        @o_entry_d      datetime,
        @o_carrier_id   smallint,
        @cnt            smallint

begin tran o

if (@c_id = 0)
    begin

-- get customer id and info using last name

        select      @cnt = (count(*)+1)/2
        from customer (repeatableread)
        where c_last = @c_last and
              c_w_id = @w_id and
              c_d_id = @d_id

        set rowcount @cnt

        select      @c_id      = c_id,
                    @c_balance = c_balance,
                    @c_first   = c_first,
                    @c_last    = c_last,
                    @c_middle  = c_middle
        from customer (repeatableread)
        where c_last = @c_last and
              c_w_id = @w_id and
              c_d_id = @d_id

        order by c_w_id, c_d_id, c_last, c_first

        set rowcount 0

    end

else

begin

```

```

-- get customer info if by id

    select      @c_balance = c_balance,
               @c_first   = c_first,
               @c_middle  = c_middle,
               @c_last    = c_last
    from customer (repeatableread)
    where c_id      = @c_id and
          c_d_id    = @d_id and
          c_w_id    = @w_id

    select      @cnt = @@rowcount

end

-- if no such customer

    if (@cnt = 0)
    begin
        raiserror("Customer not found",18,1)
        goto custnotfound
    end

-- get order info

    select      @o_id      = o_id,
               @o_entry_d = o_entry_d,
               @o_carrier_id = o_carrier_id
    from orders (serializable)
    where o_c_id      = @c_id and
          o_d_id      = @d_id and
          o_w_id      = @w_id
    order by o_id asc

-- select order lines for the current order

    select      ol_supply_w_id,
               ol_i_id,
               ol_quantity,
               ol_amount,
               ol_delivery_d
    from order_line (repeatableread)
    where ol_o_id = @o_id and
          ol_d_id = @d_id and
          ol_w_id = @w_id

custnotfound:

commit tran o

-- return data to client

select      @c_id,
           @c_last,
           @c_first,

```

```

@c_middle,
@o_entry_d,
@o_carrier_id,
@c_balance,
@o_id

```

go

## PAYMENT.SQL

```

-- File:      PAYMENT.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Creates payment transaction stored procedure
--
--           Interface Level: 4.10.000

use tpcc
go

if exists (select name from sysobjects where name = "tpcc_payment" )
    drop procedure tpcc_payment
go

create proc tpcc_payment @w_id          smallint,
                       @c_w_id        smallint,
                       @h_amount       numeric(6,2),
                       @d_id           tinyint,
                       @c_d_id         tinyint,
                       @c_id           int,
                       @c_last         char(16) = ""

as
declare @w_street_1    char(20),
        @w_street_2    char(20),
        @w_city         char(20),
        @w_state        char(2),
        @w_zip          char(9),
        @w_name         char(10),
        @d_street_1    char(20),
        @d_street_2    char(20),
        @d_city         char(20),
        @d_state        char(2),
        @d_zip          char(9),
        @d_name         char(10),
        @c_first        char(16),
        @c_middle       char(2),
        @c_street_1    char(20),
        @c_street_2    char(20),
        @c_city         char(20),
        @c_state        char(2),
        @c_zip          char(9),
        @c_phone        char(16),
        @c_since        datetime,

```

```

        @c_credit      char(2),
        @c_credit_lim  numeric(12,2),
        @c_balance     numeric(12,2),
        @c_discount    numeric(4,4),
        @data          char(500),
        @c_data        char(500),
        @datetime      datetime,
        @w_ytd         numeric(12,2),
        @d_ytd         numeric(12,2),
        @cnt           smallint,
        @val           smallint,
        @screen_data   char(200),
        @d_id_local    tinyint,
        @w_id_local    smallint,
        @c_id_local    int

select @screen_data = ""

begin tran p

-- get payment date

        select      @datetime = getdate()

        if (@c_id = 0)
        begin

-- get customer id and info using last name

                select      @cnt = count(*)
                from customer (repeatableread)
                where c_last = @c_last and
                       c_w_id = @c_w_id and
                       c_d_id = @c_d_id

                select      @val = (@cnt + 1) / 2
                set rowcount @val

                select      @c_id= c_id
                from customer (repeatableread)
                where c_last = @c_last and
                       c_w_id = @c_w_id and
                       c_d_id = @c_d_id
                order by c_last, c_first

                set rowcount 0
        end

-- get customer info and update balances

        update      customer
        set @c_balance = c_balance - @h_amount,
            c_payment_cnt = c_payment_cnt + 1,
            c_ytd_payment = c_ytd_payment + @h_amount,
            @c_first = c_first,

```

```

        @c_middle = c_middle,
        @c_last = c_last,
        @c_street_1 = c_street_1,
        @c_street_2 = c_street_2,
        @c_city = c_city,
        @c_state = c_state,
        @c_zip = c_zip,
        @c_phone = c_phone,
        @c_credit = c_credit,
        @c_credit_lim = c_credit_lim,
        @c_discount = c_discount,
        @c_since = c_since,
        @data = c_data,
        @c_id_local = c_id
where c_id = @c_id and
       c_w_id = @c_w_id and
       c_d_id = @c_d_id

-- if customer has bad credit get some more info

        if (@c_credit = "BC")
        begin

-- compute new info

                select @c_data = convert(char(5),@c_id) +
                               convert(char(4),@c_d_id) +
                               convert(char(5),@c_w_id) +
                               convert(char(4),@d_id) +
                               convert(char(5),@w_id) +
                               convert(char(19),@h_amount) +
                               substring(@data, 1, 458)

-- update customer info

                update      customer
                set c_data = @c_data
                where c_id = @c_id and
                       c_w_id = @c_w_id and
                       c_d_id = @c_d_id

                select      @screen_data = substring (@c_data,1,200)
        end

-- get district data and update year-to-date

        update      district
        set d_ytd = d_ytd + @h_amount,
            @d_street_1 = d_street_1,
            @d_street_2 = d_street_2,
            @d_city = d_city,
            @d_state = d_state,
            @d_zip = d_zip,
            @d_name = d_name,
            @d_id_local = d_id

```

```

whered_w_id      = @w_id and
d_id            = @d_id

-- get warehouse data and update year-to-date

update warehouse
set w_ytd      = w_ytd + @h_amount,
  @w_street_1 = w_street_1,
  @w_street_2 = w_street_2,
  @w_city      = w_city,
  @w_state     = w_state,
  @w_zip       = w_zip,
  @w_name      = w_name,
  @w_id_local  = w_id
wherew_id      = @w_id

-- create history record

insert into history values ( @c_id_local,
                             @c_d_id,
                             @c_w_id,
                             @d_id_local,
                             @w_id_local,
                             @datetime,
                             @h_amount,
                             @w_name + " " + @d_name)

commit tran p

-- return data to client

select @c_id,
       @c_last,
       @datetime,
       @w_street_1,
       @w_street_2,
       @w_city,
       @w_state,
       @w_zip,
       @d_street_1,
       @d_street_2,
       @d_city,
       @d_state,
       @d_zip,
       @c_first,
       @c_middle,
       @c_street_1,
       @c_street_2,
       @c_city,
       @c_state,
       @c_zip,
       @c_phone,
       @c_since,
       @c_credit,
       @c_credit_lim,
       @c_discount,

```

```

@c_balance,
@screen_data

go

STOCKLEV.SQL

-- File:      STOCKLEV.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Creates stock level transaction stored procedure
--
-- Interface Level: 4.10.000

use tpcc
go

if exists (select name from sysobjects where name = "tpcc_stocklevel" )
drop procedure tpcc_stocklevel
go

create proc tpcc_stocklevel @w_id      smallint,
                           @d_id      tinyint,
                           @threshold smallint
as

declare @o_id_low int,
        @o_id_high int

select @o_id_low = (d_next_o_id - 20),
       @o_id_high = (d_next_o_id - 1)
from district
whered_w_id      = @w_id and
d_id            = @d_id

select count(distinct(s_i_id))
from stock, order_line
where ol_w_id    = @w_id and
      ol_d_id    = @d_id and
      ol_o_id    between @o_id_low and
                  @o_id_high and
      s_w_id     = ol_w_id and
      s_i_id     = ol_i_id and
      s_quantity < @threshold

go

VERSION.SQL

-- File:      VERSION.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Returns version level of TPC-C stored procs

```

```

-- Note:      Always update the return value of this proc for
--            any interface changes or "must have" bug fixes.
--
-- The value returned by this SP defines the "interface level",
-- which must match between the stored procs and the client code.
-- The interface level may be down rev from the current kit. This
-- indicates that the interface hasn't changed since that version.

use tpcc
go

if exists ( select name from sysobjects where name = "tpcc_version" )
    drop procedure tpcc_version
go

create proc tpcc_version
as
declare    @version  char(8)

begin
    select @version = "4.10.000"
    select @version as "Version"
end

go

```

## GETARGS.C

```

// File:      GETARGS.C
//            Microsoft TPC-C Kit Ver. 4.20
//            Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for command line processing

// Includes
#include "tpcc.h"

//=====
//
// Function name: GetArgsLoader
//
//=====

void GetArgsLoader(int argc, char **argv, TPCCLDR_ARGS *pargs)
{
    int    i;
    char  *ptr;

#ifdef DEBUG
    printf("[%ld]DBG: Entering GetArgsLoader()\n", (int)
GetCurrentThreadId());
#endif

    /* init args struct with some useful values */
    pargs->server    = SERVER;

```

```

pargs->user        = USER;
pargs->password    = PASSWORD;
pargs->database    = DATABASE;
pargs->batch       = BATCH;
pargs->num_warehouses = UNDEF;
pargs->tables_all  = TRUE;
pargs->table_item  = FALSE;
pargs->table_warehouse = FALSE;
pargs->table_customer = FALSE;
pargs->table_orders = FALSE;
pargs->loader_res_file = LOADER_RES_FILE;
pargs->pack_size   = DEFLDPACKSIZE;
pargs->starting_warehouse = DEF_STARTING_WAREHOUSE;
pargs->build_index = BUILD_INDEX;
pargs->index_order = INDEX_ORDER;
pargs->index_script_path = INDEX_SCRIPT_PATH;
pargs->scale_down  = SCALE_DOWN;

```

```

/* check for zero command line args */
if ( argc == 1 )
    GetArgsLoaderUsage();

for ( i = 1; i < argc; ++i)
{
    if (argv[i][0] != '-' && argv[i][0] != '/')
    {
        printf("\nUnrecognized command");
        GetArgsLoaderUsage();
        exit(1);
    }

    ptr = argv[i];

    switch (ptr[1])
    {
        case 'h':      /* Fall throught */
        case 'H':
            GetArgsLoaderUsage();
            break;

        case 'D':
            pargs->database = ptr+2;
            break;

        case 'P':
            pargs->password = ptr+2;
            break;

        case 'S':
            pargs->server = ptr+2;
            break;

        case 'U':
            pargs->user = ptr+2;
            break;
    }
}

```

```

case 'b':
    pargs->batch = atol(ptr+2);
    break;

case 'W':
    pargs->num_warehouses = atol(ptr+2);
    break;

case 's':
    pargs->starting_warehouse = atol(ptr+2);
    break;

case 't':
    {
        pargs->tables_all = FALSE;
        if (strcmp(ptr+2,"item") == 0)
            pargs->table_item = TRUE;
        else if (strcmp(ptr+2,"warehouse") == 0)
            pargs->table_warehouse = TRUE;
        else if (strcmp(ptr+2,"customer") == 0)
            pargs->table_customer = TRUE;
        else if (strcmp(ptr+2,"orders") == 0)
            pargs->table_orders = TRUE;
        else
        {
            printf("\nUnrecognized command");
            GetArgsLoaderUsage();
            exit(1);
        }

        break;
    }

case 'f':
    pargs->loader_res_file = ptr+2;
    break;

case 'p':
    pargs->pack_size = atol(ptr+2);
    break;

case 'i':
    pargs->build_index = atol(ptr+2);
    break;

case 'o':
    pargs->index_order = atol(ptr+2);
    break;

case 'c':
    pargs->scale_down = atol(ptr+2);
    break;

case 'd':

```

```

        pargs->index_script_path = ptr+2;
        break;

        default:
            GetArgsLoaderUsage();
            exit(-1);
            break;
    }
}

/* check for required args */
if (pargs->num_warehouses == UNDEF )
{
    printf("Number of Warehouses is required\n");
    exit(-2);
}

return;
}

//=====
//
// Function name: GetArgsLoaderUsage
//
//=====

void GetArgsLoaderUsage()
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering GetArgsLoaderUsage()\n", (int)
GetCurrentThreadId());
#endif

    printf("TPCCLDR:\n\n");
    printf("Parameter
Default\n");
    printf("-----\n");
    printf("-W Number of Warehouses to Load           Required
\n");
    printf("-S Server                               %s\n",
SERVER);
    printf("-U Username                               %s\n",
USER);
    printf("-P Password                               %s\n",
PASSWORD);
    printf("-D Database                               %s\n",
DATABASE);
    printf("-b Batch Size                               %ld\n",
(long) BATCH);
    printf("-p TDS packet size                           %ld\n",
(long) DEFLDPACKSIZE);

```

```

    printf("-f Loader Results Output Filename           %s\n",
LOADER_RES_FILE);
    printf("-s Starting Warehouse                       %ld\n",
(long) DEF_STARTING_WAREHOUSE);
    printf("-i Build Option (data = 0, data and index = 1) %ld\n",
(long) BUILD_INDEX);
    printf("-o Cluster Index Build Order (before = 1, after = 0) %ld\n",
(long) INDEX_ORDER);
    printf("-c Build Scaled Database (normal = 0, tiny = 1) %ld\n",
(long) SCALE_DOWN);
    printf("-d Index Script Path                             %s\n",
INDEX_SCRIPT_PATH);
    printf("-t Table to Load                                     all
tables \n");
    printf("    [item|warehouse|customer|orders]\n");
    printf("    Notes: \n");
    printf("    - the '-t' parameter may be included multiple times to
\n");
    printf("    specify multiple tables to be loaded \n");
    printf("    - 'item' loads ITEM table \n");
    printf("    - 'warehouse' loads WAREHOUSE, DISTRICT, and STOCK tables
\n");
    printf("    - 'customer' loads CUSTOMER and HISTORY tables \n");
    printf("    - 'orders' load NEW-ORDER, ORDERS, ORDER-LINE tables \n");

    printf("\nNote: Command line switches are case sensitive.\n");

    exit(0);
}

```

## RANDOM.C

```

// File:      RANDOM.C
//            Microsoft TPC-C Kit Ver. 4.20
//            Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Random number generation routines for database loader

// Includes
#include "tpcc.h"
#include "math.h"

// Defines
#define A      16807
#define M      2147483647
#define Q      127773      /* M div A */
#define R      2836       /* M mod A */
#define Thread __declspec(thread)

// Globals
long Thread Seed = 0;      /* thread local seed */

```

```

/*****
*
*
* random -
*
* Implements a GOOD pseudo random number generator. This generator
*
* will/should? run the complete period before repeating.
*
*
* Copied from:
*
* Random Numbers Generators: Good Ones Are Hard to Find.
*
* Communications of the ACM - October 1988 Volume 31 Number 10
*
*
* Machine Dependencies:
*
* long must be 2 ^ 31 - 1 or greater.
*
*
*****/

/*****
*
* seed - load the Seed value used in irand and drand. Should be used before
*
* first call to irand or drand.
*
*****/

void seed(long val)
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering seed()...\n", (int) GetCurrentThreadId());
    printf("Old Seed %ld New Seed %ld\n",Seed, val);
#endif

    if ( val < 0 )
        val = abs(val);

    Seed = val;
}

```

```

/*****
**
*
*
* irand - returns a 32 bit integer pseudo random number with a period of
*
*      1 to 2 ^ 32 - 1.
*
*
*
* parameters:
*
*      none.
*
*
*
* returns:
*
*      32 bit integer - defined as long ( see above ).
*
*
*
* side effects:
*
*      seed get recomputed.
*
*****/
long irand()
{
    register long    s;      /* copy of seed */
    register long    test;   /* test flag */
    register long    hi;     /* tmp value for speed */
    register long    lo;     /* tmp value for speed */

#ifdef DEBUG
    printf("[%ld]DBG: Entering irand()...\n", (int) GetCurrentThreadId());
#endif

    s = Seed;
    hi = s / Q;
    lo = s % Q;

    test = A * lo - R * hi;
    if ( test > 0 )
        Seed = test;
    else
        Seed = test + M;

    return( Seed );
}

```

```

/*****
**
*
*
* drand - returns a double pseudo random number between 0.0 and 1.0.
*
*      See irand.
*
*****/
double drand()
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering drand()...\n", (int) GetCurrentThreadId());
#endif

    return( (double)irand() / 2147483647.0);
}

//=====
// Function    : RandomNumber
//
// Description:
//=====
long RandomNumber(long lower, long upper)
{
    long rand_num;

#ifdef DEBUG
    printf("[%ld]DBG: Entering RandomNumber()...\n", (int)
GetCurrentThreadId());
#endif

    if ( upper == lower )      /* pgd 08-13-96 perf enhancement */
        return lower;

    upper++;

    if ( upper <= lower )
        rand_num = upper;
    else
        rand_num = lower + irand() % (upper - lower); /* pgd 08-13-96 perf
enhancement */

#ifdef DEBUG
    printf("[%ld]DBG: RandomNumber between %ld & %ld ==> %ld\n",
(int) GetCurrentThreadId(), lower, upper, rand_num);
#endif

    return rand_num;
}

```

```

#if 0
//Original code pgd 08/13/96

long RandomNumber(long lower,
                  long upper)
{
    long rand_num;

#ifdef DEBUG
    printf("[%ld]DBG: Entering RandomNumber()...\n", (int)
GetCurrentThreadId());
#endif

    upper++;

    if ((upper <= lower))
        rand_num = upper;
    else
        rand_num = lower + irand() % ((upper > lower) ? upper - lower :
upper);

#ifdef DEBUG
    printf("[%ld]DBG: RandomNumber between %ld & %ld ==> %ld\n",
(int) GetCurrentThreadId(), lower, upper, rand_num);
#endif

    return rand_num;
}
#endif

//=====
// Function   : NURand
//
// Description:
//=====
long NURand(int iConst,
            long x,
            long y,
            long C)
{
    long rand_num;

#ifdef DEBUG
    printf("[%ld]DBG: Entering NURand()...\n", (int) GetCurrentThreadId());
#endif

    rand_num = (((RandomNumber(0,iConst) | RandomNumber(x,y)) + C) % (y-
x+1))+x;

#ifdef DEBUG

```

```

    printf("[%ld]DBG: NURand: num = %d\n", (int) GetCurrentThreadId(),
rand_num);
#endif

    return rand_num;
}

```

## STRINGS.C

```

// File:      STRINGS.C
//             Microsoft TPC-C Kit Ver. 4.20
//             Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for database loader string functions

// Includes
#include "tpcc.h"
#include <string.h>
#include <ctype.h>

//=====
//
// Function name: MakeAddress
//
//=====

void MakeAddress(char *street_1,
                 char *street_2,
                 char *city,
                 char *state,
                 char *zip)
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeAddress()\n", (int)
GetCurrentThreadId());
#endif

    MakeAlphaString (10, 20, ADDRESS_LEN, street_1);
    MakeAlphaString (10, 20, ADDRESS_LEN, street_2);
    MakeAlphaString (10, 20, ADDRESS_LEN, city);
    MakeAlphaString ( 2,  2, STATE_LEN, state);
    MakeZipNumberString( 9,  9, ZIP_LEN, zip);

#ifdef DEBUG
    printf("[%ld]DBG: MakeAddress: street_1: %s, street_2: %s, city: %s,
state: %s, zip: %s\n",
(int) GetCurrentThreadId(), street_1, street_2, city, state,
zip);
#endif

    return;
}

```

```

}

//=====
//
// Function name: LastName
//
//=====

void LastName(int num,
              char *name)
{
    static char *n[] =
    {
        "BAR" , "OUGHT" , "ABLE" , "PRI" , "PRES",
        "ESE" , "ANTI" , "CALLY" , "ATION", "EING"
    };

#ifdef DEBUG
    printf("[%ld]DBG: Entering LastName()\n", (int) GetCurrentThreadId());
#endif

    if ((num >= 0) && (num < 1000))
    {
        strcpy(name, n[(num/100)%10]);
        strcat(name, n[(num/10)%10]);
        strcat(name, n[(num/1)%10]);

        if (strlen(name) < LAST_NAME_LEN)
        {
            PaddString(LAST_NAME_LEN, name);
        }
    }
    else
    {
        printf("\nError in LastName()... num <=%ld> out of range
(0,999)\n", num);
        exit(-1);
    }

#ifdef DEBUG
    printf("[%ld]DBG: LastName: num = [%d] ==> [%d][%d][%d]\n",
           (int) GetCurrentThreadId(), num, num/100, (num/10)%10,
           num%10);
    printf("[%ld]DBG: LastName: String = %s\n", (int) GetCurrentThreadId(),
           name);
#endif

    return;
}

```

```

//=====
//
// Function name: MakeAlphaString
//
//=====

//philipdu 08/13/96 Changed MakeAlphaString to use A-Z, a-z, and 0-9 in
//accordance with spec see below:
//The spec says:
//4.3.2.2 The notation random a-string [x .. y]
//(respectively, n-string [x .. y]) represents a string of random
alphanumeric
//(respectively, numeric) characters of a random length of minimum x,
maximum y,
//and mean (y+x)/2. Alphanumerics are A..Z, a..z, and 0..9. The only other
//requirement is that the character set used "must be able to represent a
minimum
//of 128 different characters". We are using 8-bit chars, so this is a non
issue.
//It is completely unreasonable to stuff non-printing chars into the text
fields.
//-CLevine 08/13/96

int MakeAlphaString( int x, int y, int z, char *str)
{
    int len;
    int i;
    char cc = 'a';
    static char chArray[] =
"0123456789ABCDEFGHIJKLMNOPQRSTUVWXYZabcdefghijklmnopqrstuvwxyz";
    static int chArrayMax = 61;

#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeAlphaString()\n", (int)
GetCurrentThreadId());
#endif

    len= RandomNumber(x, y);

    for (i=0; i<len; i++)
    {
        cc = chArray[RandomNumber(0, chArrayMax)];
        str[i] = cc;
    }
    if ( len < z )
        memset(str+len, ' ', z - len);
    str[len] = 0;

    return len;
}

//=====
//
// Function name: MakeOriginalAlphaString

```

```

//
//=====
int MakeOriginalAlphaString(int x,
                           int y,
                           int z,
                           char *str,
                           int percent)
{
    int len;
    int val;
    int start;

#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeOriginalAlphaString()\n", (int)
GetCurrentThreadId());
#endif

    // verify percentage is valid
    if ((percent < 0) || (percent > 100))
    {
        printf("MakeOrigianlAlphaString: Invalid percentage: %d\n",
percent);
        exit(-1);
    }

    // verify string is at least 8 chars in length
    if ((x + y) <= 8)
    {
        printf("MakeOriginalAlphaString: string length must be >= 8\n");
        exit(-1);
    }

    // Make Alpha String
    len = MakeAlphaString(x,y, z, str);

    val = RandomNumber(1,100);
    if (val <= percent)
    {
        start = RandomNumber(0, len - 8);
        strncpy(str + start, "ORIGINAL", 8);
    }

#ifdef DEBUG
    printf("[%ld]DBG: MakeOriginalAlphaString: : %s\n",
           (int) GetCurrentThreadId(), str);
#endif

    return strlen(str);
}

//=====
//

```

```

// Function name: MakeNumberString
//
//=====
int MakeNumberString(int x, int y, int z, char *str)
{
    char tmp[16];

    //MakeNumberString is always called MakeZipNumberString(16, 16, 16,
string)

    memset(str, '0', 16);
    itoa(RandomNumber(0, 99999999), tmp, 10);
    memcpy(str, tmp, strlen(tmp));

    itoa(RandomNumber(0, 99999999), tmp, 10);
    memcpy(str+8, tmp, strlen(tmp));

    str[16] = 0;

    return 16;
}

//=====
//
// Function name: MakeZipNumberString
//
//=====
int MakeZipNumberString(int x, int y, int z, char *str)
{
    char tmp[16];

    //MakeZipNumberString is always called MakeZipNumberString(9, 9, 9,
string)

    strcpy(str, "000011111");

    itoa(RandomNumber(0, 9999), tmp, 10);
    memcpy(str, tmp, strlen(tmp));

    return 9;
}

//=====
//
// Function name: InitString
//
//=====
void InitString(char *str, int len)
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering InitString()\n", (int) GetCurrentThreadId());
#endif
}

```

```

    memset(str, ' ', len);
    str[len] = 0;
}

//=====
// Function name: InitAddress
//
// Description:
//
//=====
void InitAddress(char *street_1, char *street_2, char *city, char *state,
char *zip)
{
    memset(street_1, ' ', ADDRESS_LEN+1);
    memset(street_2, ' ', ADDRESS_LEN+1);
    memset(city, ' ', ADDRESS_LEN+1);

    street_1[ADDRESS_LEN+1] = 0;
    street_2[ADDRESS_LEN+1] = 0;
    city[ADDRESS_LEN+1] = 0;

    memset(state, ' ', STATE_LEN+1);
    state[STATE_LEN+1] = 0;

    memset(zip, ' ', ZIP_LEN+1);
    zip[ZIP_LEN+1] = 0;
}

```

```

//=====
//
// Function name: PaddString
//
//=====
void PaddString(int max, char *name)
{
    int    len;

    len = strlen(name);
    if ( len < max )
        memset(name+len, ' ', max - len);
    name[max] = 0;

    return;
}

```

**TIME.C**

```

// File:      TIME.C
//           Microsoft TPC-C Kit Ver. 4.20
//           Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for time functions

```

```

// Includes
#include "tpcc.h"

// Globals
static long start_sec;

//=====
//
// Function name: TimeNow
//
//=====
long TimeNow()
{
    long    time_now;
    struct _timeb el_time;

#ifdef DEBUG
    printf("[%ld]DBG: Entering TimeNow()\n", (int) GetCurrentThreadId());
#endif

    _ftime(&el_time);

    time_now = ((el_time.time - start_sec) * 1000) + el_time.millitm;

    return time_now;
}

```

**TPCC.H**

```

// File:      TPCC.H
//           Microsoft TPC-C Kit Ver. 4.20
//           Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Header file for TPC-C database loader

// Build number of TPC Benchmark Kit
#define TPCKIT_VER    "4.20"

// General headers
#include <windows.h>
#include <winbase.h>
#include <stdlib.h>
#include <stdio.h>
#include <process.h>
#include <stddef.h>
#include <stdarg.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>

```

```

#include <sys\types.h>

// ODBC headers
#include <sql.h>
#include <sqlext.h>
#include <odbcss.h>

// General constants
#define MILLI          1000
#define FALSE          0
#define TRUE           1
#define UNDEF          -1
#define MINPRINTASCII 32
#define MAXPRINTASCII 126

// Default environment constants
#define SERVER         ""
#define DATABASE       "tpcc"
#define USER           "sa"
#define PASSWORD       ""

// Default loader arguments
#define BATCH          10000
#define DEFLDPACKSIZE 32768
#define LOADER_RES_FILE "logs\\load.out"
#define LOADER_NURAND_C 123
#define DEF_STARTING_WAREHOUSE 1
#define BUILD_INDEX    1 // build both data and
indexes
#define INDEX_ORDER    1 // build indexes before load
#define SCALE_DOWN     0 // build a normal scale
database
#define INDEX_SCRIPT_PATH "scripts"

typedef struct
{
    char          *server;
    char          *database;
    char          *user;
    char          *password;
    BOOL          tables_all; // set if loading all
tables
    BOOL          table_item; // set if loading ITEM
table specifically
    BOOL          table_warehouse; // set if loading WAREHOUSE,
DISTRICT, and STOCK
    BOOL          table_customer; // set if loading CUSTOMER
and HISTORY
    BOOL          table_orders; // set if loading NEW-ORDER,
ORDERS, ORDER-LINE
    long          num_warehouses;
    long          batch;
    long          verbose;
    long          pack_size;
    char          *loader_res_file;

```

```

    char          *synch_servername;
    long          case_sensitivity;
    long          starting_warehouse;
    long          build_index;
    long          index_order;
    long          scale_down;
    char          *index_script_path;
} TPCCLDR_ARGS;

// String length constants
#define SERVER_NAME_LEN 20
#define DATABASE_NAME_LEN 20
#define USER_NAME_LEN 20
#define PASSWORD_LEN 20
#define TABLE_NAME_LEN 20
#define I_DATA_LEN 50
#define I_NAME_LEN 24
#define BRAND_LEN 1
#define LAST_NAME_LEN 16
#define W_NAME_LEN 10
#define ADDRESS_LEN 20
#define STATE_LEN 2
#define ZIP_LEN 9
#define S_DIST_LEN 24
#define S_DATA_LEN 50
#define D_NAME_LEN 10
#define FIRST_NAME_LEN 16
#define MIDDLE_NAME_LEN 2
#define PHONE_LEN 16
#define CREDIT_LEN 2
#define C_DATA_LEN 500
#define H_DATA_LEN 24
#define DIST_INFO_LEN 24
#define MAX_OL_NEW_ORDER_ITEMS 15
#define MAX_OL_ORDER_STATUS_ITEMS 15
#define STATUS_LEN 25
#define OL_DIST_INFO_LEN 24
#define C_SINCE_LEN 23
#define H_DATE_LEN 23
#define OL_DELIVERY_D_LEN 23
#define O_ENTRY_D_LEN 23

// Functions in random.c
void seed();
long irand();
double drand();
void WUCreate();
short WURand();
long RandomNumber(long lower, long upper);

// Functions in getargs.c;
void GetArgsLoader();
void GetArgsLoaderUsage();

```

```
// Functions in time.c
long TimeNow();

// Functions in strings.c
void MakeAddress();
void LastName();
int MakeAlphaString();
int MakeOriginalAlphaString();
int MakeNumberString();
int MakeZipNumberString();
void InitString();
void InitAddress();
void PaddString();
```

## TPCCLDR.C

```
// File:      TPCCLDR.C
//           Microsoft TPC-C Kit Ver. 4.20
//           Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for TPC-C database loader
```

```
// Includes
#include "tpcc.h"
#include "search.h"
```

```
// Defines
#define MAXITEMS          100000
#define MAXITEMS_SCALE_DOWN  100
#define CUSTOMERS_PER_DISTRICT 3000
#define CUSTOMERS_SCALE_DOWN 30
#define DISTRICT_PER_WAREHOUSE 10
#define ORDERS_PER_DISTRICT  3000
#define ORDERS_SCALE_DOWN    30
#define MAX_CUSTOMER_THREADS  2
#define MAX_ORDER_THREADS    3
#define MAX_MAIN_THREADS      4
```

```
// Functions declarations
```

```
void HandleErrorDBC (SQLHDBC hdbc1);
```

```
void CheckSQL();
void CheckDataBase();
```

```
long NURand();
void LoadItem();
void LoadWarehouse();
```

```
void Stock();
void District();
```

```
void LoadCustomer();
void CustomerBufInit();
void CustomerBufLoad();
```

```
void LoadCustomerTable();
void LoadHistoryTable();
```

```
void LoadOrders();
void OrdersBufInit();
void OrdersBufLoad();
void LoadOrdersTable();
void LoadNewOrderTable();
void LoadOrderLineTable();
void GetPermutation();
void CheckForCommit();
void OpenConnections();
void BuildIndex();
void FormatDate ();
```

```
// Shared memory structures
```

```
typedef struct
{
    long          ol;
    long          ol_i_id;
    short         ol_supply_w_id;
    short         ol_quantity;
    double        ol_amount;
    char          ol_dist_info[DIST_INFO_LEN+1];
    char          ol_delivery_d[OL_DELIVERY_D_LEN+1];
} ORDER_LINE_STRUCT;
```

```
typedef struct
{
    long          o_id;
    short         o_d_id;
    short         o_w_id;
    long          o_c_id;
    short         o_carrier_id;
    short         o_ol_cnt;
    short         o_all_local;
    ORDER_LINE_STRUCT o_ol[15];
} ORDERS_STRUCT;
```

```
typedef struct
{
    long          c_id;
    short         c_d_id;
    short         c_w_id;
    char          c_first[FIRST_NAME_LEN+1];
    char          c_middle[MIDDLE_NAME_LEN+1];
    char          c_last[LAST_NAME_LEN+1];
    char          c_street_1[ADDRESS_LEN+1];
    char          c_street_2[ADDRESS_LEN+1];
    char          c_city[ADDRESS_LEN+1];
    char          c_state[STATE_LEN+1];
    char          c_zip[ZIP_LEN+1];
    char          c_phone[PHONE_LEN+1];
    char          c_credit[CREDIT_LEN+1];
```

```

    double          c_credit_lim;
    double          c_discount;
// fix to avoid ODBC float to numeric conversion problem.
// double         c_balance;
    char           c_balance[6];

    double          c_ytd_payment;
    short          c_payment_cnt;
    short          c_delivery_cnt;
    char           c_data[C_DATA_LEN+1];
    double         h_amount;
    char           h_data[H_DATA_LEN+1];
} CUSTOMER_STRUCT;

typedef struct
{
    char           c_last[LAST_NAME_LEN+1];
    char           c_first[FIRST_NAME_LEN+1];
    long          c_id;
} CUSTOMER_SORT_STRUCT;

typedef struct
{
    long          time_start;
} LOADER_TIME_STRUCT;

// Global variables

char szLastError[300];

HENV henv;

HDBC v_hdbc;                // for SQL Server version
verification
HDBC i_hdbc1;              // for ITEM table
HDBC w_hdbc1;              // for WAREHOUSE, DISTRICT, STOCK
HDBC c_hdbc1;              // for CUSTOMER
HDBC c_hdbc2;              // for HISTORY
HDBC o_hdbc1;              // for ORDERS
HDBC o_hdbc2;              // for NEW-ORDER
HDBC o_hdbc3;              // for ORDER-LINE

HSTMTv_hstmt;              // for SQL Server version verification
HSTMTi_hstmt1;
HSTMTw_hstmt1;
HSTMTc_hstmt1, c_hstmt2;
HSTMTo_hstmt1, o_hstmt2, o_hstmt3;

ORDERS_STRUCT  orders_buf[ORDERS_PER_DISTRICT];
CUSTOMER_STRUCT customer_buf[CUSTOMERS_PER_DISTRICT];
long           orders_rows_loaded;
long           new_order_rows_loaded;
long           order_line_rows_loaded;
long           history_rows_loaded;

```

```

long           customer_rows_loaded;
long           stock_rows_loaded;
long           district_rows_loaded;
long           item_rows_loaded;
long           warehouse_rows_loaded;
long           main_time_start;
long           main_time_end;
long           max_items;
long           customers_per_district;
long           orders_per_district;
long           first_new_order;
long           last_new_order;

TPCCLDR_ARGS  *aptr, args;

//=====
//
// Function name: main
//
//=====

int main(int  argc, char **argv)
{
    DWORD          dwThreadId[MAX_MAIN_THREADS];
    HANDLE         hThread[MAX_MAIN_THREADS];
    FILE           *fLoader;
    char           buffer[255];
    int            i;

    for (i=0; i<MAX_MAIN_THREADS; i++)
        hThread[i] = NULL;

    printf("\n*****");
    printf("\n*                *");
    printf("\n* Microsoft SQL Server *");
    printf("\n*                *");
    printf("\n* TPC-C BENCHMARK KIT: Database loader *");
    printf("\n* Version %s          *",
TPCKIT_VER);
    printf("\n*                *");
    printf("\n*****\n\n");

    // process command line arguments

    aptr = &args;
    GetArgsLoader(argc, argv, aptr);

    // verify correct SQL Server version in use
    // you must be using SQL Server 7.00.623 or better to load

    CheckSQL();

```

```

// verify database and tables exist before attempting to load
CheckDataBase();

printf("Build interface is ODBC.\n");

if (aptr->build_index == 0)
    printf("Data load only - no index creation.\n");
else
    printf("Data load and index creation.\n");

if (aptr->index_order == 0)
    printf("Clustered indexes will be created after bulk load.\n");
else
    printf("Clustered indexes will be created before bulk load.\n");

// set database scale values
if (aptr->scale_down == 1)
{
    printf("*** Scaled Down Database ***\n");
    max_items = MAXITEMS_SCALE_DOWN;
    customers_per_district = CUSTOMERS_SCALE_DOWN;
    orders_per_district = ORDERS_SCALE_DOWN;
    first_new_order = 0;
    last_new_order = 30;
}
else
{
    max_items = MAXITEMS;
    customers_per_district = CUSTOMERS_PER_DISTRICT;
    orders_per_district = ORDERS_PER_DISTRICT;
    first_new_order = 2100;
    last_new_order = 3000;
}

// open connections to SQL Server
OpenConnections();

// open file for loader results
fLoader = fopen(aptr->loader_res_file, "w");

if (fLoader == NULL)
{
    printf("Error, loader result file open failed.");
    exit(-1);
}

// start loading data

sprintf(buffer,"TPC-C load started for %ld warehouses.\n",aptr-
>num_warehouses);

printf("%s",buffer);

```

```

fprintf(fLoader,"%s",buffer);

main_time_start = (TimeNow() / MILLI);

// start parallel load threads

if (aptr->tables_all || aptr->table_item)
{
    fprintf(fLoader, "\nStarting loader threads for: item\n");

    hThread[0] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
                                LoadItem,
                                NULL,
                                0,
                                &dwThreadID[0]);

    if (hThread[0] == NULL)
    {
        printf("Error, failed in creating creating thread = 0.\n");
        exit(-1);
    }

    if (aptr->tables_all || aptr->table_warehouse)
    {
        fprintf(fLoader, "Starting loader threads for: warehouse\n");

        hThread[1] = CreateThread(NULL,
                                    0,
                                    (LPTHREAD_START_ROUTINE)
                                    LoadWarehouse,
                                    NULL,
                                    0,
                                    &dwThreadID[1]);

        if (hThread[1] == NULL)
        {
            printf("Error, failed in creating creating thread = 1.\n");
            exit(-1);
        }

        if (aptr->tables_all || aptr->table_customer)
        {
            fprintf(fLoader, "Starting loader threads for: customer\n");

            hThread[2] = CreateThread(NULL,
                                        0,
                                        (LPTHREAD_START_ROUTINE)
                                        LoadCustomer,
                                        NULL,
                                        0,
                                        &dwThreadID[2]);

```

```

                &dwThreadID[2]);

    if (hThread[2] == NULL)
    {
        printf("Error, failed in creating creating main thread =
2.\n");
        exit(-1);
    }
}

if (aptr->tables_all || aptr->table_orders)
{
    fprintf(fLoader, "Starting loader threads for: orders\n");

    hThread[3] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadOrders,
                                NULL,
                                0,
                                &dwThreadID[3]);

    if (hThread[3] == NULL)
    {
        printf("Error, failed in creating creating main thread =
3.\n");
        exit(-1);
    }
}

// Wait for threads to finish...
for (i=0; i<MAX_MAIN_THREADS; i++)
{
    if (hThread[i] != NULL)
    {
        WaitForSingleObject( hThread[i], INFINITE );
        CloseHandle(hThread[i]);
        hThread[i] = NULL;
    }
}

main_time_end = (TimeNow() / MILLI);
sprintf(buffer, "\nTPC-C load completed successfully in %ld minutes.\n",
        (main_time_end - main_time_start)/60);

printf("%s", buffer);
fprintf(fLoader, "%s", buffer);

fclose(fLoader);

SQLFreeEnv(henv);

exit(0);

```

```

    return 0;
}

//=====
//
// Function name: LoadItem
//
//=====

void LoadItem()
{
    long        i_id;
    long        i_im_id;
    char        i_name[I_NAME_LEN+1];
    double      i_price;
    char        i_data[I_DATA_LEN+1];
    char        name[20];
    long        time_start;
    RETCODE     rc;
    DBINT       rcint;
    char        bcphint[128];

    // Seed with unique number
    seed(1);

    printf("Loading item table...\n");

    // if build index before load
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxitmc1");

    InitString(i_name, I_NAME_LEN+1);
    InitString(i_data, I_DATA_LEN+1);

    sprintf(name, "%s..%s", aptr->database, "item");

    rc = bcp_init(i_hdbc1, name, NULL, "logs\\item.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(i_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (i_id), ROWS_PER_BATCH =
100000");
        rc = bcp_control(i_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(i_hdbc1);
    }

    rc = bcp_bind(i_hdbc1, (BYTE *) &i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(i_hdbc1);
}

```

```

rc = bcp_bind(i_hdbc1, (BYTE *) &i_im_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 2);
if (rc != SUCCEED)
    HandleErrorDBC(i_hdbc1);

rc = bcp_bind(i_hdbc1, (BYTE *) i_name, 0, I_NAME_LEN, NULL, 0, 0, 3);
if (rc != SUCCEED)
    HandleErrorDBC(i_hdbc1);

rc = bcp_bind(i_hdbc1, (BYTE *) &i_price, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 4);
if (rc != SUCCEED)
    HandleErrorDBC(i_hdbc1);

rc = bcp_bind(i_hdbc1, (BYTE *) i_data, 0, I_DATA_LEN, NULL, 0, 0, 5);
if (rc != SUCCEED)
    HandleErrorDBC(i_hdbc1);

time_start = (TimeNow() / MILLI);

item_rows_loaded = 0;

for (i_id = 1; i_id <= max_items; i_id++)
{
    i_im_id = RandomNumber(1L, 10000L);

    MakeAlphaString(14, 24, I_NAME_LEN, i_name);

    i_price = ((float) RandomNumber(100L, 10000L))/100.0;

    MakeOriginalAlphaString(26, 50, I_DATA_LEN, i_data, 10);

    rc = bcp_sendrow(i_hdbc1);
    if (rc != SUCCEED)
        HandleErrorDBC(i_hdbc1);

    item_rows_loaded++;
    CheckForCommit(i_hdbc1, i_hstmt1, item_rows_loaded, "item",
&time_start);
}

rcint = bcp_done(i_hdbc1);
if (rcint < 0)
    HandleErrorDBC(i_hdbc1);

printf("Finished loading item table.\n");

SQLFreeStmt(i_hstmt1, SQL_DROP);
SQLDisconnect(i_hdbc1);
SQLFreeConnect(i_hdbc1);

// if build index after load
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxitm1");

```

```

}

//=====
===
//
// Function : LoadWarehouse
//
// Loads WAREHOUSE table and loads Stock and District as Warehouses are
created
//
//=====
===

void LoadWarehouse()
{
    short w_id;
    char w_name[W_NAME_LEN+1];
    char w_street_1[ADDRESS_LEN+1];
    char w_street_2[ADDRESS_LEN+1];
    char w_city[ADDRESS_LEN+1];
    char w_state[STATE_LEN+1];
    char w_zip[ZIP_LEN+1];
    double w_tax;
    double w_ytd;
    char name[20];
    long time_start;
    RETCODE rc;
    DBINT rcint;
    char bcphint[128];

    // Seed with unique number
    seed(2);

    printf("Loading warehouse table...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxwar1");

    InitString(w_name, W_NAME_LEN+1);
    InitAddress(w_street_1, w_street_2, w_city, w_state, w_zip);

    sprintf(name, "%s..%s", aptr->database, "warehouse");

    rc = bcp_init(w_hdbc1, name, NULL, "logs\\whouse.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (w_id), ROWS_PER_BATCH = %d",
aptr->num_warehouses);
        rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
    }
}

```

```

        if (rc != SUCCEED)
            HandleErrorDBC(w_hdbc1);
    }

    rc = bcp_bind(w_hdbc1, (BYTE *) &w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) w_name, 0, W_NAME_LEN, NULL, 0, 0, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) w_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
3);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) w_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
4);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) w_city, 0, ADDRESS_LEN, NULL, 0, 0, 5);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) w_state, 0, STATE_LEN, NULL, 0, 0, 6);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) w_zip, 0, ZIP_LEN, NULL, 0, 0, 7);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) &w_tax, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 8);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) &w_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 9);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    time_start = (TimeNow() / MILLI);

    warehouse_rows_loaded = 0;

    for (w_id = (short)aptr->starting_warehouse; w_id <= aptr-
>num_warehouses; w_id++)
    {
        MakeAlphaString(6,10, W_NAME_LEN, w_name);

        MakeAddress(w_street_1, w_street_2, w_city, w_state, w_zip);

```

```

        w_tax = ((float) RandomNumber(0L,2000L))/10000.00;

        w_ytd = 300000.00;

        rc = bcp_sendrow(w_hdbc1);
        if (rc != SUCCEED)
            HandleErrorDBC(w_hdbc1);

        warehouse_rows_loaded++;
        CheckForCommit(w_hdbc1, i_hstmt1, warehouse_rows_loaded,
"warehouse", &time_start);
    }

    rcint = bcp_done(w_hdbc1);
    if (rcint < 0)
        HandleErrorDBC(w_hdbc1);

    printf("Finished loading warehouse table.\n");

    // if build index after load...
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
        BuildIndex("idxwarcl");

    stock_rows_loaded = 0;
    district_rows_loaded = 0;

    District();
    Stock();
}

//=====
//
// Function : District
//
//=====

void District()
{
    short d_id;
    short d_w_id;
    char d_name[D_NAME_LEN+1];
    char d_street_1[ADDRESS_LEN+1];
    char d_street_2[ADDRESS_LEN+1];
    char d_city[ADDRESS_LEN+1];
    char d_state[STATE_LEN+1];
    char d_zip[ZIP_LEN+1];
    double d_tax;
    double d_ytd;
    char name[20];
    long d_next_o_id;
    long time_start;
    int w_id;

```

```

RETCODE rc;
DBINTrcnt;
char bcphint[128];

// Seed with unique number
seed(4);

printf("Loading district table...\n");

// build index before load
if ((aptr->build_index == 1) && (aptr->index_order == 1))
    BuildIndex("idxdiscl");

InitString(d_name, D_NAME_LEN+1);
InitAddress(d_street_1, d_street_2, d_city, d_state, d_zip);
sprintf(name, "%s..%s", aptr->database, "district");

rc = bcp_init(w_hdbc1, name, NULL, "logs\\district.err", DB_IN);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

if ((aptr->build_index == 1) && (aptr->index_order == 1))
{
    sprintf(bcphint, "tablock, order (d_w_id, d_id), ROWS_PER_BATCH =
%u", (aptr->num_warehouses * 10));
    rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
}

rc = bcp_bind(w_hdbc1, (BYTE *) &d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 1);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &d_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) d_name, 0, D_NAME_LEN, NULL, 0, 0, 3);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) d_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
4);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) d_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
5);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) d_city, 0, ADDRESS_LEN, NULL, 0, 0, 6);

```

```

if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) d_state, 0, STATE_LEN, NULL, 0, 0, 7);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) d_zip, 0, ZIP_LEN, NULL, 0, 0, 8);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &d_tax, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 9);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &d_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 10);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &d_next_o_id, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT4, 11);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

d_ytd = 30000.0;

d_next_o_id = orders_per_district+1;

time_start = (TimeNow() / MILLI);

for (w_id = aptr->starting_warehouse; w_id <= aptr->num_warehouses;
w_id++)
{
    d_w_id = w_id;

    for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
    {
        MakeAlphaString(6,10,D_NAME_LEN, d_name);

        MakeAddress(d_street_1, d_street_2, d_city, d_state, d_zip);

        d_tax = ((float) RandomNumber(0L,2000L))/10000.00;

        rc = bcp_sendrow(w_hdbc1);
        if (rc != SUCCEED)
            HandleErrorDBC(w_hdbc1);

        district_rows_loaded++;
        CheckForCommit(w_hdbc1, w_hstmt1, district_rows_loaded,
"district", &time_start);
    }
}

```

```

rcint = bcp_done(w_hdbc1);
if (rcint < 0)
    HandleErrorDBC(w_hdbc1);

printf("Finished loading district table.\n");

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxdiscl");

return;
}

//=====
//
// Function   : Stock
//
//=====

void Stock()
{
    long   s_i_id;
    short  s_w_id;
    short  s_quantity;
    char   s_dist_01[S_DIST_LEN+1];
    char   s_dist_02[S_DIST_LEN+1];
    char   s_dist_03[S_DIST_LEN+1];
    char   s_dist_04[S_DIST_LEN+1];
    char   s_dist_05[S_DIST_LEN+1];
    char   s_dist_06[S_DIST_LEN+1];
    char   s_dist_07[S_DIST_LEN+1];
    char   s_dist_08[S_DIST_LEN+1];
    char   s_dist_09[S_DIST_LEN+1];
    char   s_dist_10[S_DIST_LEN+1];
    long   s_ytd;
    short  s_order_cnt;
    short  s_remote_cnt;
    char   s_data[S_DATA_LEN+1];
    short  len;
    char   name[20];
    long   time_start;
    RETCODE rc;
    DBINT rcint;
    char   bcphint[128];

    // Seed with unique number
    seed(3);

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxstkcl");

    sprintf(name, "%s..%s", aptr->database, "stock");

```

```

rc = bcp_init(w_hdbc1, name, NULL, "logs\\stock.err", DB_IN);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

if ((aptr->build_index == 1) && (aptr->index_order == 1))
{
    sprintf(bcphint, "tablock, order (s_i_id, s_w_id), ROWS_PER_BATCH
= %u", (aptr->num_warehouses * 10000));
    rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
}

rc = bcp_bind(w_hdbc1, (BYTE *) &s_i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

bcp_bind(w_hdbc1, (BYTE *) &s_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &s_quantity, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 3);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_01, 0, S_DIST_LEN, NULL, 0, 0,
4);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_02, 0, S_DIST_LEN, NULL, 0, 0,
5);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_03, 0, S_DIST_LEN, NULL, 0, 0,
6);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_04, 0, S_DIST_LEN, NULL, 0, 0,
7);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_05, 0, S_DIST_LEN, NULL, 0, 0,
8);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_06, 0, S_DIST_LEN, NULL, 0, 0,
9);

```

```

    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_07, 0, S_DIST_LEN, NULL, 0, 0,
10);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_08, 0, S_DIST_LEN, NULL, 0, 0,
11);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_09, 0, S_DIST_LEN, NULL, 0, 0,
12);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_10, 0, S_DIST_LEN, NULL, 0, 0,
13);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &s_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 14);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &s_order_cnt, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 15);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &s_remote_cnt, 0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 16);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_data, 0, S_DATA_LEN, NULL, 0, 0, 17);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

s_ytd = s_order_cnt = s_remote_cnt = 0;

time_start = (TimeNow() / MILLI);

printf("...Loading stock table\n");

for (s_i_id=1; s_i_id <= max_items; s_i_id++)
{
    for (s_w_id = (short)aptr->starting_warehouse; s_w_id <= aptr-
>num_warehouses; s_w_id++)
    {

```

```

s_quantity = (short)RandomNumber(10L,100L);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_01);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_02);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_03);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_04);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_05);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_06);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_07);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_08);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_09);
len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_10);

len = MakeOriginalAlphaString(26,50, S_DATA_LEN, s_data,10);

rc = bcp_sendrow(w_hdbc1);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

stock_rows_loaded++;
    CheckForCommit(w_hdbc1, w_hstmt1, stock_rows_loaded, "stock",
&time_start);
    }
}

rcint = bcp_done(w_hdbc1);
if (rcint < 0)
    HandleErrorDBC(w_hdbc1);

printf("Finished loading stock table.\n");

SQLFreeStmt(w_hstmt1, SQL_DROP);
SQLDisconnect(w_hdbc1);
SQLFreeConnect(w_hdbc1);

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxstkcl");

return;
}

//=====
//
// Function : LoadCustomer
//
//=====

void LoadCustomer()
{
    LOADER_TIME_STRUCT customer_time_start;
    LOADER_TIME_STRUCT history_time_start;
    short w_id;
    short d_id;

```

```

DWORD                dwThreadID[MAX_CUSTOMER_THREADS];
HANDLE               hThread[MAX_CUSTOMER_THREADS];
char                 name[20];
RETCODE              rc;
DBINT                rcint;
char                 bcphint[128];
char                 cmd[256];
// SQLRETURN         rc_1;
// SQLSMALLINT       recnum, MsgLen;
// SQLCHAR           SqlState[6],
Msg[SQL_MAX_MESSAGE_LENGTH];
// SQLINTEGER        NativeError;

// Seed with unique number
seed(5);

printf("Loading customer and history tables...\n");

// if build index before load...
if ((aptr->build_index == 1) && (aptr->index_order == 1))
    BuildIndex("idxcuscl");

// Initialize bulk copy
sprintf(name, "%s..%s", aptr->database, "customer");

rc = bcp_init(c_hdbc1, name, NULL, "logs\\customer.err", DB_IN);
if (rc != SUCCEEDED)
    HandleErrorDBC(c_hdbc1);

if ((aptr->build_index == 1) && (aptr->index_order == 1))
{
    sprintf(bcphint, "tablock, order (c_w_id, c_d_id, c_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 30000));
    rc = bcp_control(c_hdbc1, BCPHINTS, (void*) bcphint);
    if (rc != SUCCEEDED)
        HandleErrorDBC(c_hdbc1);
}

sprintf(name, "%s..%s", aptr->database, "history");

rc = bcp_init(c_hdbc2, name, NULL, "logs\\history.err", DB_IN);
if (rc != SUCCEEDED)
    HandleErrorDBC(c_hdbc2);

sprintf(bcphint, "tablock");
rc = bcp_control(c_hdbc2, BCPHINTS, (void*) bcphint);
if (rc != SUCCEEDED)
    HandleErrorDBC(c_hdbc2);

customer_rows_loaded = 0;
history_rows_loaded = 0;

CustomerBufInit();

customer_time_start.time_start = (TimeNow() / MILLI);

```

```

        history_time_start.time_start = (TimeNow() / MILLI);

        for (w_id = (short)aptr->starting_warehouse; w_id <= aptr-
>num_warehouses; w_id++)
        {
            for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
            {
                CustomerBufLoad(d_id, w_id);

                // Start parallel loading threads here...

                // Start customer table thread

                printf("...Loading customer table for: d_id = %d, w_id =
%d\n", d_id, w_id);

                hThread[0] = CreateThread(NULL,
0,
(LPTHREAD_START_ROUTINE)
LoadCustomerTable,
&customer_time_start,
0,
&dwThreadID[0]);

                if (hThread[0] == NULL)
                {
                    printf("Error, failed in creating creating thread =
0.\n");
                    exit(-1);
                }

                // Start History table thread

                printf("...Loading history table for: d_id = %d, w_id =
%d\n", d_id, w_id);

                hThread[1] = CreateThread(NULL,
0,
(LPTHREAD_START_ROUTINE)
LoadHistoryTable,
&history_time_start,
0,
&dwThreadID[1]);

                if (hThread[1] == NULL)
                {
                    printf("Error, failed in creating creating thread =
1.\n");
                    exit(-1);
                }

                WaitForSingleObject( hThread[0], INFINITE );
                WaitForSingleObject( hThread[1], INFINITE );
            }
        }

```

```

        if (CloseHandle(hThread[0]) == FALSE)
        {
            printf("Error, failed in closing customer thread handle
with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[1]) == FALSE)
        {
            printf("Error, failed in closing history thread handle
with errno: %d\n", GetLastError());
        }

    }

}

// flush the bulk connection
rcint = bcp_done(c_hdbc1);
if (rcint < 0)
    HandleErrorDBC(c_hdbc1);

rcint = bcp_done(c_hdbc2);
if (rcint < 0)
    HandleErrorDBC(c_hdbc2);

printf("Finished loading customer table.\n");

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxcuscl");

// build non-clustered index
if (aptr->build_index == 1)
    BuildIndex("idxcusnc");

// Output the NURAND used for the loader into C_FIRST for C_ID = 1,
// C_W_ID = 1, and C_D_ID = 1
sprintf(cmd, "isql -S%s -U%s -P%s -d%s -e -Q \"update customer set
c_first = 'C_LOAD = %d' where c_id = 1 and c_w_id = 1 and c_d_id = 1\" >
logs\\nurand_load.log",
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database,
        LOADER_NURAND_C);

system(cmd);

SQLFreeStmt(c_hstmt1, SQL_DROP);
SQLDisconnect(c_hdbc1);
SQLFreeConnect(c_hdbc1);

SQLFreeStmt(c_hstmt2, SQL_DROP);
SQLDisconnect(c_hdbc2);

```

```

    SQLFreeConnect(c_hdbc2);

return;
}

//=====
//
// Function   : CustomerBufInit
//
//=====

void CustomerBufInit()
{
    int    i;

    for (i=0;i<customers_per_district;i++)
    {
        customer_buf[i].c_id = 0;
        customer_buf[i].c_d_id = 0;
        customer_buf[i].c_w_id = 0;

        strcpy(customer_buf[i].c_first,"");
        strcpy(customer_buf[i].c_middle,"");
        strcpy(customer_buf[i].c_last,"");
        strcpy(customer_buf[i].c_street_1,"");
        strcpy(customer_buf[i].c_street_2,"");
        strcpy(customer_buf[i].c_city,"");
        strcpy(customer_buf[i].c_state,"");
        strcpy(customer_buf[i].c_zip,"");
        strcpy(customer_buf[i].c_phone,"");
        strcpy(customer_buf[i].c_credit,"");

        customer_buf[i].c_credit_lim = 0;
        customer_buf[i].c_discount = (float) 0;

        // fix to avoid ODBC float to numeric conversion problem.
        // customer_buf[i].c_balance = 0;
        strcpy(customer_buf[i].c_balance,"");

        customer_buf[i].c_ytd_payment = 0;
        customer_buf[i].c_payment_cnt = 0;
        customer_buf[i].c_delivery_cnt = 0;

        strcpy(customer_buf[i].c_data,"");

        customer_buf[i].h_amount = 0;

        strcpy(customer_buf[i].h_data,"");
    }
}

```

```

//=====
//
// Function   : CustomerBufLoad
//
// Fills shared buffer for HISTORY and CUSTOMER
//=====
void CustomerBufLoad(int d_id, int w_id)
{
    long          i;
    CUSTOMER_SORT_STRUCT  c[CUSTOMERS_PER_DISTRICT];

    for (i=0;i<customers_per_district;i++)
    {
        if (i < 1000)
            LastName(i, c[i].c_last);
        else
            LastName(NURand(255,0,999,LOADER_NURAND_C), c[i].c_last);

        MakeAlphaString(8,16,FIRST_NAME_LEN, c[i].c_first);

        c[i].c_id = i+1;
    }

    printf("...Loading customer buffer for: d_id = %d, w_id = %d\n",
           d_id, w_id);

    for (i=0;i<customers_per_district;i++)
    {
        customer_buf[i].c_d_id = d_id;
        customer_buf[i].c_w_id = w_id;
        customer_buf[i].h_amount = 10.0;

        customer_buf[i].c_ytd_payment = 10.0;

        customer_buf[i].c_payment_cnt = 1;
        customer_buf[i].c_delivery_cnt = 0;

        // Generate CUSTOMER and HISTORY data
        customer_buf[i].c_id = c[i].c_id;

        strcpy(customer_buf[i].c_first, c[i].c_first);
        strcpy(customer_buf[i].c_last, c[i].c_last);

        customer_buf[i].c_middle[0] = 'O';
        customer_buf[i].c_middle[1] = 'E';

        MakeAddress(customer_buf[i].c_street_1,
                   customer_buf[i].c_street_2,

```

```

        customer_buf[i].c_city,
        customer_buf[i].c_state,
        customer_buf[i].c_zip);

        MakeNumberString(16, 16, PHONE_LEN, customer_buf[i].c_phone);

        if (RandomNumber(1L, 100L) > 10)
            customer_buf[i].c_credit[0] = 'G';
        else
            customer_buf[i].c_credit[0] = 'B';
        customer_buf[i].c_credit[1] = 'C';

        customer_buf[i].c_credit_lim = 50000.0;
        customer_buf[i].c_discount = ((float) RandomNumber(0L, 5000L)) /
10000.0;

        // fix to avoid ODBC float to numeric conversion problem.

        // customer_buf[i].c_balance = -10.0;
        strcpy(customer_buf[i].c_balance, "-10.0");

        MakeAlphaString(300, 500, C_DATA_LEN, customer_buf[i].c_data);

        // Generate HISTORY data
        MakeAlphaString(12, 24, H_DATA_LEN, customer_buf[i].h_data);
    }
}

//=====
//
// Function   : LoadCustomerTable
//
//=====
void LoadCustomerTable(LOADER_TIME_STRUCT *customer_time_start)
{
    int          i;
    long         c_id;
    short        c_d_id;
    short        c_w_id;
    char         c_first[FIRST_NAME_LEN+1];
    char         c_middle[MIDDLE_NAME_LEN+1];
    char         c_last[LAST_NAME_LEN+1];
    char         c_street_1[ADDRESS_LEN+1];
    char         c_street_2[ADDRESS_LEN+1];
    char         c_city[ADDRESS_LEN+1];
    char         c_state[STATE_LEN+1];
    char         c_zip[ZIP_LEN+1];
    char         c_phone[PHONE_LEN+1];
    char         c_credit[CREDIT_LEN+1];
    double       c_credit_lim;
    double       c_discount;

```

```

// fix to avoid ODBC float to numeric conversion problem.
// double      c_balance;
char          c_balance[6];

double       c_ytd_payment;
short        c_payment_cnt;
short        c_delivery_cnt;
char         c_data[C_DATA_LEN+1];
char         c_since[C_SINCE_LEN+1];
RETCODE      rc;

rc = bcp_bind(c_hdbc1, (BYTE *) &c_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_first, 0, FIRST_NAME_LEN, NULL, 0, 0,
4);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_middle, 0, MIDDLE_NAME_LEN, NULL, 0, 0,
5);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_last, 0, LAST_NAME_LEN, NULL, 0, 0,
6);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
7);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
8);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_city, 0, ADDRESS_LEN, NULL, 0, 0, 9);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

```

```

rc = bcp_bind(c_hdbc1, (BYTE *) c_state, 0, STATE_LEN, NULL, 0, 0, 10);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_zip, 0, ZIP_LEN, NULL, 0, 0, 11);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_phone, 0, PHONE_LEN, NULL, 0, 0, 12);

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_since, 0, C_SINCE_LEN, NULL, 0,
SQLCHARACTER, 13);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_credit, 0, CREDIT_LEN, NULL, 0, 0,
14);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_credit_lim, 0, SQL_VARLEN_DATA, NULL,
0, SQLFLT8, 15);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_discount, 0, SQL_VARLEN_DATA, NULL,
0, SQLFLT8, 16);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

// fix to avoid ODBC float to numeric conversion problem.

// rc = bcp_bind(c_hdbc1, (BYTE *) &c_balance, 0, SQL_VARLEN_DATA,
NULL, 0, SQLFLT8, 17);
// if (rc != SUCCEED)
//     HandleErrorDBC(c_hdbc1);
rc = bcp_bind(c_hdbc1, (BYTE *) c_balance, 0, 5, NULL, 0, SQLCHARACTER,
17);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_ytd_payment, 0, SQL_VARLEN_DATA,
NULL, 0, SQLFLT8, 18);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_payment_cnt, 0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 19);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

```

```

rc = bcp_bind(c_hdbc1, (BYTE *) &c_delivery_cnt,0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 20);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_data, 0, 500, NULL, 0, 0, 21);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

for (i = 0; i < customers_per_district; i++)
{
    c_id = customer_buf[i].c_id;
    c_d_id = customer_buf[i].c_d_id;
    c_w_id = customer_buf[i].c_w_id;

    strcpy(c_first, customer_buf[i].c_first);
    strcpy(c_middle, customer_buf[i].c_middle);
    strcpy(c_last, customer_buf[i].c_last);
    strcpy(c_street_1, customer_buf[i].c_street_1);
    strcpy(c_street_2, customer_buf[i].c_street_2);
    strcpy(c_city, customer_buf[i].c_city);
    strcpy(c_state, customer_buf[i].c_state);
    strcpy(c_zip, customer_buf[i].c_zip);
    strcpy(c_phone, customer_buf[i].c_phone);
    strcpy(c_credit, customer_buf[i].c_credit);

    FormatDate(&c_since);

    c_credit_lim = customer_buf[i].c_credit_lim;
    c_discount = customer_buf[i].c_discount;

    // fix to avoid ODBC float to numeric conversion problem.

    // c_balance = customer_buf[i].c_balance;
    strcpy(c_balance, customer_buf[i].c_balance);

    c_ytd_payment = customer_buf[i].c_ytd_payment;
    c_payment_cnt = customer_buf[i].c_payment_cnt;
    c_delivery_cnt = customer_buf[i].c_delivery_cnt;

    strcpy(c_data, customer_buf[i].c_data);

    // Send data to server
    rc = bcp_sendrow(c_hdbc1);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc1);

    customer_rows_loaded++;
    CheckForCommit(c_hdbc1, c_hstmt1, customer_rows_loaded,
"customer", &customer_time_start->time_start);
}
}

```

```

//=====
//
// Function : LoadHistoryTable
//
//=====

void LoadHistoryTable(LOADER_TIME_STRUCT *history_time_start)
{
    int i;
    long c_id;
    short c_d_id;
    short c_w_id;
    double h_amount;
    char h_data[H_DATA_LEN+1];
    char h_date[H_DATE_LEN+1];
    RETCODE rc;

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 4);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 5);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &h_date, 0, H_DATE_LEN, NULL, 0,
SQLCHARACTER, 6);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &h_amount, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 7);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) h_data, 0, H_DATA_LEN, NULL, 0, 0, 8);
    if (rc != SUCCEED)

```

```

        HandleErrorDBC(c_hdbc2);
for (i = 0; i < customers_per_district; i++)
{
    c_id = customer_buf[i].c_id;
    c_d_id = customer_buf[i].c_d_id;
    c_w_id = customer_buf[i].c_w_id;
    h_amount = customer_buf[i].h_amount;
    strcpy(h_data, customer_buf[i].h_data);

    FormatDate(&h_date);

    // send to server
    rc = bcp_sendrow(c_hdbc2);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    history_rows_loaded++;
    CheckForCommit(c_hdbc2, c_hstmt2, history_rows_loaded, "history",
&history_time_start->time_start);
}
}

//=====
//
// Function   : LoadOrders
//
//=====
void LoadOrders()
{
    LOADER_TIME_STRUCT    orders_time_start;
    LOADER_TIME_STRUCT    new_order_time_start;
    LOADER_TIME_STRUCT    order_line_time_start;
    short                  w_id;
    short                  d_id;
    DWORD                  dwThreadId[MAX_ORDER_THREADS];
    HANDLE                  hThread[MAX_ORDER_THREADS];
    char                    name[20];
    RETCODE                 rc;
    char                    bcphint[128];

    // seed with unique number
    seed(6);

    printf("Loading orders...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        BuildIndex("idxordc1");

```

```

        BuildIndex("idxnodc1");
        BuildIndex("idxodlc1");
    }

    // initialize bulk copy
    sprintf(name, "%s.%s", aptr->database, "orders");

    rc = bcp_init(o_hdbc1, name, NULL, "logs\\orders.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (o_w_id, o_d_id, o_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 30000));
        rc = bcp_control(o_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc1);
    }

    sprintf(name, "%s.%s", aptr->database, "new_order");

    rc = bcp_init(o_hdbc2, name, NULL, "logs\\neword.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (no_w_id, no_d_id, no_o_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 9000));
        rc = bcp_control(o_hdbc2, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc2);
    }

    sprintf(name, "%s.%s", aptr->database, "order_line");

    rc = bcp_init(o_hdbc3, name, NULL, "logs\\ordline.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (ol_w_id, ol_d_id, ol_o_id,
ol_number), ROWS_PER_BATCH = %u", (aptr->num_warehouses * 300000));
        rc = bcp_control(o_hdbc3, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc3);
    }

    orders_rows_loaded    = 0;
    new_order_rows_loaded = 0;
    order_line_rows_loaded = 0;

```

```

OrdersBufInit();

orders_time_start.time_start = (TimeNow() / MILLI);
new_order_time_start.time_start = (TimeNow() / MILLI);
order_line_time_start.time_start = (TimeNow() / MILLI);

for (w_id = (short)aptr->starting_warehouse; w_id <= aptr-
>num_warehouses; w_id++)
{
    for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
    {
        OrdersBufLoad(d_id, w_id);

        // start parallel loading threads here...

        // start Orders table thread
        printf("...Loading Order Table for: d_id = %d, w_id = %d\n",
d_id, w_id);

        hThread[0] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadOrdersTable,
                                &orders_time_start,
                                0,
                                &dwThreadID[0]);

        if (hThread[0] == NULL)
        {
            printf("Error, failed in creating creating thread =
0.\n");
            exit(-1);
        }

        // start NewOrder table thread
        printf("...Loading New-Order Table for: d_id = %d, w_id =
%d\n", d_id, w_id);

        hThread[1] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadNewOrderTable,
                                &new_order_time_start,
                                0,
                                &dwThreadID[1]);

        if (hThread[1] == NULL)
        {
            printf("Error, failed in creating creating thread =
1.\n");
            exit(-1);
        }
    }
}

```

```

// start Order-Line table thread
        printf("...Loading Order-Line Table for: d_id = %d, w_id =
%d\n", d_id, w_id);

        hThread[2] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadOrderLineTable,
                                &order_line_time_start,
                                0,
                                &dwThreadID[2]);

        if (hThread[2] == NULL)
        {
            printf("Error, failed in creating creating thread =
2.\n");
            exit(-1);
        }

        WaitForSingleObject( hThread[0], INFINITE );
        WaitForSingleObject( hThread[1], INFINITE );
        WaitForSingleObject( hThread[2], INFINITE );

        if (CloseHandle(hThread[0]) == FALSE)
        {
            printf("Error, failed in closing Orders thread handle
with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[1]) == FALSE)
        {
            printf("Error, failed in closing NewOrder thread handle
with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[2]) == FALSE)
        {
            printf("Error, failed in closing OrderLine thread
handle with errno: %d\n", GetLastError());
        }
    }

    printf("Finished loading orders.\n");

    return;
}

//=====
//

```

```

// Function   : OrdersBufInit
//
// Clears shared buffer for ORDERS, NEWORDER, and ORDERLINE
//
//=====

void OrdersBufInit()
{
    int     i;
    int     j;

    for (i=0;i<orders_per_district;i++)
    {
        orders_buf[i].o_id = 0;
        orders_buf[i].o_d_id = 0;
        orders_buf[i].o_w_id = 0;
        orders_buf[i].o_c_id = 0;
        orders_buf[i].o_carrier_id = 0;
        orders_buf[i].o_ol_cnt = 0;
        orders_buf[i].o_all_local = 0;

        for (j=0;j<=14;j++)
        {
            orders_buf[i].o_ol[j].ol = 0;
            orders_buf[i].o_ol[j].ol_i_id = 0;
            orders_buf[i].o_ol[j].ol_supply_w_id = 0;
            orders_buf[i].o_ol[j].ol_quantity = 0;
            orders_buf[i].o_ol[j].ol_amount = 0;
            strcpy(orders_buf[i].o_ol[j].ol_dist_info,"");
        }
    }
}

//=====
//
// Function   : OrdersBufLoad
//
// Fills shared buffer for ORDERS, NEWORDER, and ORDERLINE
//
//=====

void OrdersBufLoad(int d_id, int w_id)
{
    int     cust[ORDERS_PER_DISTRICT+1];
    long    o_id;
    short   ol;

    printf("...Loading Order Buffer for: d_id = %d, w_id = %d\n",
           d_id, w_id);

    GetPermutation(cust, orders_per_district);

```

```

for (o_id=0;o_id<orders_per_district;o_id++)
{
    // Generate ORDER and NEW-ORDER data

    orders_buf[o_id].o_d_id = d_id;
    orders_buf[o_id].o_w_id = w_id;
    orders_buf[o_id].o_id = o_id+1;
    orders_buf[o_id].o_c_id = cust[o_id+1];
    orders_buf[o_id].o_ol_cnt = (short)RandomNumber(5L, 15L);

    if (o_id < first_new_order)
    {
        orders_buf[o_id].o_carrier_id = (short)RandomNumber(1L, 10L);
        orders_buf[o_id].o_all_local = 1;
    }
    else
    {
        orders_buf[o_id].o_carrier_id = 0;
        orders_buf[o_id].o_all_local = 1;
    }

    for (ol=0; ol<orders_buf[o_id].o_ol_cnt; ol++)
    {
        orders_buf[o_id].o_ol[ol].ol = ol+1;
        orders_buf[o_id].o_ol[ol].ol_i_id = RandomNumber(1L,
max_items);
        orders_buf[o_id].o_ol[ol].ol_supply_w_id = w_id;
        orders_buf[o_id].o_ol[ol].ol_quantity = 5;
        MakeAlphaString(24, 24, OL_DIST_INFO_LEN,
&orders_buf[o_id].o_ol[ol].ol_dist_info);

        // Generate ORDER-LINE data
        if (o_id < first_new_order)
        {
            orders_buf[o_id].o_ol[ol].ol_amount = 0;
            // Added to insure ol_delivery_d set properly during
load

            FormatDate(&orders_buf[o_id].o_ol[ol].ol_delivery_d);

        }
        else
        {
            orders_buf[o_id].o_ol[ol].ol_amount =
RandomNumber(1,999999)/100.0;
            // Added to insure ol_delivery_d set properly during
load

            // odbc datetime format
            strcpy(orders_buf[o_id].o_ol[ol].ol_delivery_d,"1899-
12-31 00:00:00.000");

        }
    }
}

```

```

    }
}

//=====
//
// Function   : LoadOrdersTable
//
//=====

void LoadOrdersTable(LOADER_TIME_STRUCT *orders_time_start)
{
    int         i;
    long        o_id;
    short       o_d_id;
    short       o_w_id;
    long        o_c_id;
    short       o_carrier_id;
    short       o_ol_cnt;
    short       o_all_local;
    char        o_entry_d[O_ENTRY_D_LEN+1];
    RETCODE     rc;
    DBINT       rcint;

    // bind ORDER data
    rc = bcp_bind(o_hdbc1, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_c_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 4);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_entry_d, 0, O_ENTRY_D_LEN, NULL, 0,
SQLCHARACTER, 5);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_carrier_id, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 6);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);
}

```

```

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_ol_cnt, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 7);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_all_local, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 8);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    for (i = 0; i < orders_per_district; i++)
    {
        o_id         = orders_buf[i].o_id;
        o_d_id       = orders_buf[i].o_d_id;
        o_w_id       = orders_buf[i].o_w_id;
        o_c_id       = orders_buf[i].o_c_id;
        o_carrier_id = orders_buf[i].o_carrier_id;
        o_ol_cnt     = orders_buf[i].o_ol_cnt;
        o_all_local  = orders_buf[i].o_all_local;

        FormatDate(&o_entry_d);

        // send data to server
        rc = bcp_sendrow(o_hdbc1);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc1);

        orders_rows_loaded++;
        CheckForCommit(o_hdbc1, o_hstmt1, orders_rows_loaded, "orders",
&orders_time_start->time_start);
    }

    // rcint = bcp_batch(o_hdbc1);
    // if (rcint < 0)
    //     HandleErrorDBC(o_hdbc1);

    if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
    {
        rcint = bcp_done(o_hdbc1);
        if (rcint < 0)
            HandleErrorDBC(o_hdbc1);

        SQLFreeStmt(o_hstmt1, SQL_DROP);
        SQLDisconnect(o_hdbc1);
        SQLFreeConnect(o_hdbc1);

        // if build index after load...
        if ((aptr->build_index == 1) && (aptr->index_order == 0))
            BuildIndex("idxordcl");

        // build non-clustered index
        if (aptr->build_index == 1)
            BuildIndex("idxordnc");
    }
}

```

```

}

//=====
//
// Function   : LoadNewOrderTable
//
//=====

void LoadNewOrderTable(LOADER_TIME_STRUCT *new_order_time_start)
{
    int         i;
    long        o_id;
    short       o_d_id;
    short       o_w_id;
    RETCODE     rc;
    DBINT       rcint;

    // Bind NEW-ORDER data

    rc = bcp_bind(o_hdbc2, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    rc = bcp_bind(o_hdbc2, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    rc = bcp_bind(o_hdbc2, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    for (i = first_new_order; i < last_new_order; i++)
    {
        o_id   = orders_buf[i].o_id;
        o_d_id = orders_buf[i].o_d_id;
        o_w_id = orders_buf[i].o_w_id;

        rc = bcp_sendrow(o_hdbc2);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc2);

        new_order_rows_loaded++;
        CheckForCommit(o_hdbc2, o_hstmt2, new_order_rows_loaded,
"new_order", &new_order_time_start->time_start);
    }

    // rcint = bcp_batch(o_hdbc2);
    // if (rcint < 0)
    //     HandleErrorDBC(o_hdbc2);

```

```

    if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
    {
        rcint = bcp_done(o_hdbc2);
        if (rcint < 0)
            HandleErrorDBC(o_hdbc2);

        SQLFreeStmt(o_hstmt2, SQL_DROP);
        SQLDisconnect(o_hdbc2);
        SQLFreeConnect(o_hdbc2);

        // if build index after load...
        if ((aptr->build_index == 1) && (aptr->index_order == 0))
            BuildIndex("idxnodcl");
    }
}

//=====
//
// Function   : LoadOrderLineTable
//
//=====

void LoadOrderLineTable(LOADER_TIME_STRUCT *order_line_time_start)
{
    int         i, j;
    long        o_id;
    short       o_d_id;
    short       o_w_id;
    long        ol;
    long        ol_i_id;
    short       ol_supply_w_id;
    short       ol_quantity;
    double      ol_amount;
    char        ol_dist_info[DIST_INFO_LEN+1];
    char        ol_delivery_d[OL_DELIVERY_D_LEN+1];
    RETCODE     rc;
    DBINT       rcint;

    // bind ORDER-LINE data
    rc = bcp_bind(o_hdbc3, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
    if (rc != SUCCEED)

```

```

        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &ol, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 4);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 5);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_supply_w_id, 0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 6);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_delivery_d, 0, OL_DELIVERY_D_LEN,
NULL, 0, SQLCHARACTER, 7);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_quantity, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 8);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) &ol_amount, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 9);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    rc = bcp_bind(o_hdbc3, (BYTE *) ol_dist_info, 0, DIST_INFO_LEN, NULL, 0,
0, 10);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    for (i = 0; i < orders_per_district; i++)
    {
        o_id    = orders_buf[i].o_id;
        o_d_id  = orders_buf[i].o_d_id;
        o_w_id  = orders_buf[i].o_w_id;

        for (j=0; j < orders_buf[i].o_ol_cnt; j++)
        {
            ol            = orders_buf[i].o_ol[j].ol;
            ol_i_id      = orders_buf[i].o_ol[j].ol_i_id;
            ol_supply_w_id = orders_buf[i].o_ol[j].ol_supply_w_id;
            ol_quantity   = orders_buf[i].o_ol[j].ol_quantity;
            ol_amount     = orders_buf[i].o_ol[j].ol_amount;

            strcpy(ol_delivery_d,orders_buf[i].o_ol[j].ol_delivery_d);

            strcpy(ol_dist_info,orders_buf[i].o_ol[j].ol_dist_info);

```

```

        rc = bcp_sendrow(o_hdbc3);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc3);

        order_line_rows_loaded++;
        CheckForCommit(o_hdbc3, o_hstmt3, order_line_rows_loaded,
"order_line", &order_line_time_start->time_start);
    }

}

// rcint = bcp_batch(o_hdbc3);
// if (rcint < 0)
//     HandleErrorDBC(o_hdbc3);

if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
{
    rcint = bcp_done(o_hdbc3);
    if (rcint < 0)
        HandleErrorDBC(o_hdbc3);

    SQLFreeStmt(o_hstmt3, SQL_DROP);
    SQLDisconnect(o_hdbc3);
    SQLFreeConnect(o_hdbc3);

    // if build index after load...
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
        BuildIndex("idxodlcl");

}

}

//=====
//
// Function    : GetPermutation
//
//=====

void GetPermutation(int perm[], int n)
{
    int i, r, t;

    for (i=1;i<=n;i++)
        perm[i] = i;

    for (i=1;i<=n;i++)
    {
        r = RandomNumber(i,n);
        t = perm[i];
        perm[i] = perm[r];
        perm[r] = t;
    }
}

```

```

}

//=====
//
// Function   : CheckForCommit
//
//=====

void CheckForCommit(HDBC hdbc,
                   HSTMT hstmt,
                   int rows_loaded,
                   char *table_name,
                   long *time_start)
{
    long time_end, time_diff;
    // DBINT rcint;

    if ( !(rows_loaded % aptr->batch) )
    {
        // rcint = bcp_batch(hdbc);
        // if (rcint < 0)
        // HandleErrorDBC(hdbc);

        time_end = (TimeNow() / MILLI);
        time_diff = time_end - *time_start;

        printf("-> Loaded %ld rows into %s in %ld sec - Total = %d (%.2f
rps)\n",
              aptr->batch,
              table_name,
              time_diff,
              rows_loaded,
              (float) aptr->batch / (time_diff ? time_diff : 1L));

        *time_start = time_end;
    }

    return;
}

//=====
//
// Function   : OpenConnections
//
//=====

void OpenConnections()
{
    RETCODE rc;

```

```

char          szDriverString[300];
char          szDriverStringOut[1024];
SQLSMALLINT   cbDriverStringOut;

SQLAllocHandle(SQL_HANDLE_ENV, SQL_NULL_HANDLE, &henv );

SQLSetEnvAttr(henv, SQL_ATTR_ODBC_VERSION, (void*)SQL_OV_ODBC3, 0 );

SQLAllocHandle(SQL_HANDLE_DBC, henv , &i_hdbc1);
SQLAllocHandle(SQL_HANDLE_DBC, henv , &w_hdbc1);
SQLAllocHandle(SQL_HANDLE_DBC, henv , &c_hdbc1);
SQLAllocHandle(SQL_HANDLE_DBC, henv , &c_hdbc2);
SQLAllocHandle(SQL_HANDLE_DBC, henv , &o_hdbc1);
SQLAllocHandle(SQL_HANDLE_DBC, henv , &o_hdbc2);
SQLAllocHandle(SQL_HANDLE_DBC, henv , &o_hdbc3);

SQLSetConnectAttr(i_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
SQLSetConnectAttr(w_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
SQLSetConnectAttr(c_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
SQLSetConnectAttr(c_hdbc2, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
SQLSetConnectAttr(o_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
SQLSetConnectAttr(o_hdbc2, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
SQLSetConnectAttr(o_hdbc3, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

// Open connections to SQL Server

// Connection 1

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (i_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(i_hdbc1);

rc = SQLDriverConnect ( i_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,

```

```

                SQL_DRIVER_NOPROMPT );
if (rc != SUCCEED)
    HandleErrorDBC(i_hdbc1);

// Connection 2

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (w_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = SQLDriverConnect ( w_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

// Connection 3

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (c_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = SQLDriverConnect ( c_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

// Connection 4

```

```

        sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                aptr->server,
                aptr->user,
                aptr->password,
                aptr->database );

rc = SQLSetConnectOption (c_hdbc2, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc2);

rc = SQLDriverConnect ( c_hdbc2,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc2);

// Connection 5

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (o_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc1);

rc = SQLDriverConnect ( o_hdbc1,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc1);

// Connection 6

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,

```

```

                aptr->password,
                aptr->database );

rc = SQLSetConnectOption (o_hdbc2, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc2);

rc = SQLDriverConnect ( o_hdbc2,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc2);

// Connection 7

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (o_hdbc3, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = SQLDriverConnect ( o_hdbc3,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);
}

//=====
//
// Function name: BuildIndex
//
//=====

void BuildIndex(char *index_script)
{
    char cmd[256];

```

```

    printf("Starting index creation:  %s\n",index_script);

    sprintf(cmd, "isql -S%s -U%s -P%s -e -i%s\\%s.sql > logs\\%s.log",
            aptr->server,
            aptr->user,
            aptr->password,
            aptr->index_script_path,
            index_script,
            index_script);

    system(cmd);

    printf("Finished index creation:  %s\n",index_script);
}

void HandleErrorDBC (SQLHDBC hdbc1)
{
    SQLCHAR          SqlState[6], Msg[SQL_MAX_MESSAGE_LENGTH];
    SQLINTEGER        NativeError;
    SQLSMALLINT       i, MsgLen;
    SQLRETURN         rc2;
    char              timebuf[128];
    char              datebuf[128];
    FILE              *fp1;

    i = 1;
    while (( rc2 = SQLGetDiagRec(SQL_HANDLE_DBC , hdbc1, i, SqlState ,
&NativeError,
                                Msg, sizeof(Msg) , &MsgLen ) != SQL_NO_DATA )
        {
            sprintf( szLastError , "%s" , Msg );

            _strtime(timebuf);
            _strdate(datebuf);

            printf( "[%s : %s] %s\n" , datebuf, timebuf, szLastError);

            fp1 = fopen("logs\\tpccldr.err","w");
            if (fp1 == NULL)
                printf("ERROR:  Unable to open errorlog file.\n");
            else
            {
                fprintf(fp1, "[%s : %s] %s\n" , datebuf, timebuf,
szLastError);
                fclose(fp1);
            }

            i++;
        }
}

```

```

void HandleErrorSTMT (HSTMT hstmt1)
{
    SQLCHAR          SqlState[6], Msg[SQL_MAX_MESSAGE_LENGTH];
    SQLINTEGER       NativeError;
    SQLSMALLINT     i, MsgLen;
    SQLRETURN        rc2;
    char             timebuf[128];
    char             datebuf[128];
    FILE             *fpl;

    i = 1;
    while (( rc2 = SQLGetDiagRec(SQL_HANDLE_STMT , hstmt1, i, SqlState ,
&NativeError,
                                Msg, sizeof(Msg) , &MsgLen )) != SQL_NO_DATA )
    {
        sprintf( szLastError , "%s" , Msg );

        _strtime(timebuf);
        _strdate(datebuf);

        printf( "[%s : %s] %s\n" , datebuf, timebuf, szLastError);

        fpl = fopen("logs\\tpccldr.err","w");
        if (fpl == NULL)
            printf("ERROR: Unable to open errorlog file.\n");
        else
        {
            fprintf(fpl, "[%s : %s] %s\n" , datebuf, timebuf,
szLastError);
            fclose(fpl);
        }

        i++;
    }
}

void FormatDate ( char* szTimeCOutput )
{
    struct tm when;
    time_t now;

    time( &now );
    when = *localtime( &now );

    mktime( &when );

    // odbc datetime format
    strftime( szTimeCOutput , 30 , "%Y-%m-%d %H:%M:%S.000", &when );
}

```

```

return;
}

//=====
//
// Function   : CheckSQL
//
//=====

void CheckSQL()
{
    RETCODE          rc;

    char             szDriverString[300];
    char             szDriverStringOut[1024];
    int              SQLBuildFlag;

    SQLSMALLINT      cbDriverStringOut;
    SQLCHAR          SQLVersion[19];
    SQLINTEGER       SQLVersionInd;

    SQLAllocHandle(SQL_HANDLE_ENV, SQL_NULL_HANDLE, &henv );

    SQLSetEnvAttr(henv, SQL_ATTR_ODBC_VERSION, (void*)SQL_OV_ODBC3, 0 );

    SQLAllocHandle(SQL_HANDLE_DBC, henv , &v_hdbc);

    SQLSetConnectAttr(v_hdbc, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

    // Open connection to SQL Server

    sprintf( szDriverString , "DRIVER={SQL Server};SERVER=%s;UID=%s;PWD=%s"
,
                                aptr->server,
                                aptr->user,
                                aptr->password );

    if ( SQLSetConnectAttr( v_hdbc, SQL_ATTR_PACKET_SIZE, (SQLPOINTER)aptr-
>pack_size, SQL_IS_UIINTEGER ) != SQL_SUCCESS )
        HandleErrorDBC(v_hdbc);

    rc = SQLDriverConnect ( v_hdbc,
                            NULL,
                            (SQLCHAR*)&szDriverString[0] ,
                            SQL_NTS,
                            (SQLCHAR*)&szDriverStringOut[0],
                            sizeof(szDriverStringOut),
                            &cbDriverStringOut,
                            SQL_DRIVER_NOPROMPT );
}

```



```

    if ( SQLBuildFlag == 1 )
    {
        printf("ERROR. The SQL Server version you are using is not
supported\n");
        printf("for TPC-C benchmarking. You currently have SQL Server
version %9s\n",SQLVersion);
        printf("installed. Please upgrade to Microsoft SQL Server
7.00.623 or better.\n");
        printf("and re-run the SETUP program.\n\n");
        exit(1);
    }

    SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
    SQLDisconnect(v_hdbc);
    SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

    return;
}

//=====
//
// Function : CheckDataBase
//
//=====

void CheckDataBase()
{
    RETCODE          rc;

    char             szDriverString[300];
    char             szDriverStringOut[1024];
    char             TablesBitMap[9] = {"000000000"};
    int              i, ExitFlag;

    SQLSMALLINT      cbDriverStringOut;
    SQLCHAR          TabName[10];
    SQLINTEGER       TabNameInd, TabCount, TabCountInd;

    ExitFlag = 0;

    SQLAllocHandle(SQL_HANDLE_ENV, SQL_NULL_HANDLE, &henv );

    SQLSetEnvAttr(henv, SQL_ATTR_ODBC_VERSION, (void*)SQL_OV_ODBC3, 0 );

    SQLAllocHandle(SQL_HANDLE_DBC, henv , &v_hdbc);

    SQLSetConnectAttr(v_hdbc, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

    // Open connection to SQL Server

```

```

        sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
                aptr->server,
                aptr->user,
                aptr->password,
                aptr->database );

        rc = SQLSetConnectAttr( v_hdbc, SQL_ATTR_PACKET_SIZE, (SQLPOINTER)aptr-
>pack_size, SQL_IS_UIINTEGER );
        if (rc != SQL_SUCCESS)
            HandleErrorDBC(v_hdbc);

        rc = SQLDriverConnect ( v_hdbc,
                                NULL,
                                (SQLCHAR*)&szDriverString[0] ,
                                SQL_NTS,
                                (SQLCHAR*)&szDriverStringOut[0],
                                sizeof(szDriverStringOut),
                                &cbDriverStringOut,
                                SQL_DRIVER_NOPROMPT );

        // if the rc is SQL_ERROR, the the TPCC database probably does not
exist
        if (rc == SQL_ERROR)
        {
            printf("The database TPCC does not appear to exist!\n");
            printf("\nCheck LOGS\ directory for database creation
errors.\n");

            // cleanup database connections and handles
            SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
            SQLDisconnect(v_hdbc);
            SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

            // since there is not a database, exit back to SETUP.CMD
            exit(1);
        }

        if ( SQLAllocHandle(SQL_HANDLE_STMT, v_hdbc , &v_hstmt) != SQL_SUCCESS
)
            HandleErrorDBC(v_hdbc);

        if ( SQLBindCol(v_hstmt, 1, SQL_C_ULONG, &TabCount, 0, &TabCountInd) !=
SQL_SUCCESS )
            HandleErrorSTMT(v_hstmt);

        // count the number of user tables from sysobjects
        rc = SQLExecDirect(v_hstmt, "select count(*) from sysobjects where
xtype = 'U'", SQL_NTS);
        if ((rc != SQL_SUCCESS) && (rc != SQL_SUCCESS_WITH_INFO))
            HandleErrorSTMT(v_hstmt);

        if ( SQLFetch(v_hstmt) != SQL_SUCCESS )
            HandleErrorSTMT(v_hstmt);

```

```

// if the number of tables is less than 9, select all the user tables
in TPCC
if (TabCount != 9)
{
    SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);

    SQLAllocHandle(SQL_HANDLE_STMT, v_hdbc , &v_hstmt);

    if ( SQLBindCol(v_hstmt, 1, SQL_C_CHAR, &TabName, sizeof(TabName),
&TabNameInd) != SQL_SUCCESS )
        HandleErrorSTMT(v_hstmt);

    // select the list of user tables into a result set
rc = SQLExecDirect(v_hstmt, "select * from sysobjects where xtype
= 'U'", SQL_NTS);
if ((rc != SQL_SUCCESS) && (rc != SQL_SUCCESS_WITH_INFO))
    HandleErrorSTMT(v_hstmt);

// go through the result set and set the bitmap for each found
table
// set the bitmap to '1' if the table name is found

while ((rc = SQLFetch(v_hstmt)) != SQL_NO_DATA)
{
    switch( TabName[0] )
    {
    case 'w':
        TablesBitMap[0] = '1';
        break;
    case 'd':
        TablesBitMap[1] = '1';
        break;
    case 'c':
        TablesBitMap[2] = '1';
        break;
    case 'h':
        TablesBitMap[3] = '1';
        break;
    case 'n':
        TablesBitMap[4] = '1';
        break;
    case 'o':
        if (TabName[5] = 's')
            TablesBitMap[5] = '1';
        if (TabName[5] = '_')
            TablesBitMap[6] = '1';
        break;
    case 'i':
        TablesBitMap[7] = '1';
        break;
    case 's':
        TablesBitMap[8] = '1';
        break;
    }
}

```

```

// a '0' ExitFlag means do NOT exit the loader early, a '1' means
exit the loader early
ExitFlag = 0;

// iterate through the bitmap to display which table(s) is
actually missing
for (i = 0; i <= 8; i++)
{
    switch(i)
    {
    case 0:
        if (TablesBitMap[i] == '0')
        {
            printf("The Warehouse table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 1:
        if (TablesBitMap[i] == '0')
        {
            printf("The District table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 2:
        if (TablesBitMap[i] == '0')
        {
            printf("The Customer table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 3:
        if (TablesBitMap[i] == '0')
        {
            printf("The History table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 4:
        if (TablesBitMap[i] == '0')
        {
            printf("The New_Order table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 5:
        if (TablesBitMap[i] == '0')
        {

```

```

        printf("The Orders table is missing or
damaged.\n");
        ExitFlag = 1;
    }
    break;
case 6:
    if (TablesBitMap[i] == '0')
    {
        printf("The Order_Line table is missing or
damaged.\n");
        ExitFlag = 1;
    }
    break;
case 7:
    if (TablesBitMap[i] == '0')
    {
        printf("The Item table is missing or damaged.\n");
        ExitFlag = 1;
    }
    break;
case 8:
    if (TablesBitMap[i] == '0')
    {
        printf("The Stock table is missing or
damaged.\n");
        ExitFlag = 1;
    }
    break;
}

// if one or more tables are missing, display message and exit the
loader
if (ExitFlag = 1)
{
    printf("\nExiting TPC-C Loader!\n");
    printf("\nCheck LOGS\\ directory for database\n");
    printf("or table creation errors.\n");

    // cleanup database connections and handles
    SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
    SQLDisconnect(v_hdbc);
    SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

    exit(1);
}

// cleanup database connections and handles
SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
SQLDisconnect(v_hdbc);
SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

return;
}

```

## Appendix C - Tunable Parameters and Options

**This section discloses hardware information and the Windows .NET Server 2003 Enterprise Edition registry parameters used on the PRIMERGY R450 server system.**

System Information report written at: 10/24/02 13:56:48  
System Name: ASTERIX  
[System Summary]

Item Value  
OS Name Microsoft® Windows® .NET Enterprise Server  
Version 5.2.3663 Build 3663  
OS Manufacturer Microsoft Corporation  
System Name ASTERIX  
System Manufacturer FUJITSU SIEMENS  
System Model PRIMERGY R450  
System Type X86-based PC  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
Processor x86 Family 15 Model 2 Stepping 2 GenuineIntel ~1988 Mhz  
BIOS Version/Date FSC 4.06 Rev. 1.04.1290, 8/21/2002  
SMBIOS Version 2.31  
Windows Directory C:\WINDOWS  
System Directory C:\WINDOWS\system32  
Boot Device \Device\HarddiskVolume10  
Locale United States  
Hardware Abstraction LayerVersion = "5.2.3663.0 (main.020715-1506)"  
User Name ASTERIX\Administrator  
Time Zone W. Europe Daylight Time  
Total Physical Memory 16,384.00 MB  
Available Physical Memory 14.95 GB  
Total Virtual Memory 32.32 GB  
Available Virtual Memory 31.91 GB  
Page File Space 17.04 GB  
Page File C:\pagefile.sys

[Hardware Resources]

[Conflicts/Sharing]

Resource Device  
I/O Port 0x0000A000-0x0000AFFF DEC 21154 PCI to PCI bridge  
I/O Port 0x0000A000-0x0000AFFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
Memory Address 0xF0000000-0xF21FFFFFF PCI bus  
Memory Address 0xF0000000-0xF21FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xF0000000-0xF21FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
I/O Port 0x00000000-0x000003AF PCI bus  
I/O Port 0x00000000-0x000003AF Direct memory access controller  
  
Memory Address 0xF4000000-0xF5FFFFFF PCI bus  
Memory Address 0xF4000000-0xF5FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xF4000000-0xF5FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
I/O Port 0x00002000-0x00003FFF PCI bus  
I/O Port 0x00002000-0x00003FFF DEC 21154 PCI to PCI bridge  
I/O Port 0x00002000-0x00003FFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
Memory Address 0xE8000000-0xE9FFFFFF PCI bus  
Memory Address 0xE8000000-0xE9FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xE8000000-0xE9FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
Memory Address 0xD8000000-0xD9FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xD8000000-0xD9FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
Memory Address 0xDA000000-0xDDFFFFFF PCI bus  
Memory Address 0xDA000000-0xDDFFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xDA000000-0xDDFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
I/O Port 0x00009000-0x0000AFFF PCI bus  
I/O Port 0x00009000-0x0000AFFF QLogic QLA23xx PCI Fibre Channel Adapter  
  
I/O Port 0x00006000-0x00006FFF PCI bus  
I/O Port 0x00006000-0x00006FFF DEC 21154 PCI to PCI bridge  
I/O Port 0x00006000-0x00006FFF Mylex eXtremeRAID 2000 Disk Array Controller  
  
I/O Port 0x00003000-0x00003FFF DEC 21154 PCI to PCI bridge

I/O Port 0x00003000-0x00003FFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xF6000000-0xF9FFFFFF PCI bus  
Memory Address 0xF6000000-0xF9FFFFFF Intel 8255x-based PCI Ethernet Adapter (10/100)

Memory Address 0xD6000000-0xD7FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xD6000000-0xD7FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xE4000000-0xE61FFFFFF PCI bus  
Memory Address 0xE4000000-0xE61FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xE4000000-0xE61FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xE0000000-0xE1FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xE0000000-0xE1FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

I/O Port 0x00005000-0x00005FFF DEC 21154 PCI to PCI bridge  
I/O Port 0x00005000-0x00005FFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xE2000000-0xE3FFFFFF PCI bus  
Memory Address 0xE2000000-0xE3FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xE2000000-0xE3FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xDE000000-0xE1FFFFFF PCI bus  
Memory Address 0xDE000000-0xE1FFFFFF Adaptec AIC-7899 Ultra160 PCI SCSI Card

Memory Address 0xA0000-0xBFFFF PCI bus  
Memory Address 0xA0000-0xBFFFF RAGE XL PCI (Microsoft Corporation)

Memory Address 0xF8000000-0xF9FFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xF8000000-0xF9FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xFA000000-0xFBFFFFFF PCI bus  
Memory Address 0xFA000000-0xFBFFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xFA000000-0xFBFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

I/O Port 0x00007000-0x00007FFF PCI bus  
I/O Port 0x00007000-0x00007FFF DEC 21154 PCI to PCI bridge  
I/O Port 0x00007000-0x00007FFF Mylex eXtremeRAID 2000 Disk Array Controller

I/O Port 0x00001000-0x0000144F PCI bus  
I/O Port 0x00001000-0x0000144F RAGE XL PCI (Microsoft Corporation)

I/O Port 0x000003B0-0x000003DF PCI bus  
I/O Port 0x000003B0-0x000003DF RAGE XL PCI (Microsoft Corporation)

I/O Port 0x00004000-0x00005FFF PCI bus  
I/O Port 0x00004000-0x00005FFF Adaptec AIC-7899 Ultra160 PCI SCSI Card

I/O Port 0x00008000-0x00008FFF PCI bus  
I/O Port 0x00008000-0x00008FFF DEC 21154 PCI to PCI bridge  
I/O Port 0x00008000-0x00008FFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xDC000000-0xDDFFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xDC000000-0xDDFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xEE000000-0xEFFFFFF PCI bus  
Memory Address 0xEE000000-0xEFFFFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xEE000000-0xEFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller

Memory Address 0xEA000000-0xEC1FFFF PCI bus  
Memory Address 0xEA000000-0xEC1FFFF DEC 21154 PCI to PCI bridge  
Memory Address 0xEA000000-0xEC1FFFF Mylex eXtremeRAID 2000 Disk Array Controller

[DMA]

Resource	Device	Status
Channel 4	Direct memory access controller	OK
Channel 2	Standard floppy disk controller	OK

[Forced Hardware]

Device	PNP Device ID

[I/O]

Resource	Device	Status
0x00000000-0x000003AF	PCI bus	OK
0x00000000-0x000003AF	Direct memory access controller	OK
0x000003B0-0x000003DF	PCI bus	OK
0x000003B0-0x000003DF	RAGE XL PCI (Microsoft Corporation)	OK
0x000003E0-0x00000CF7	PCI bus	OK
0x00000D00-0x00000FFF	PCI bus	OK
0x00001000-0x0000144F	PCI bus	OK
0x00001000-0x0000144F	RAGE XL PCI (Microsoft Corporation)	OK
0x000003C0-0x000003DF	RAGE XL PCI (Microsoft Corporation)	OK
0x00000060-0x00000060	Standard 101/102-Key or Microsoft Natural PS/2 Keyboard	OK
0x00000064-0x00000064	Standard 101/102-Key or Microsoft Natural PS/2 Keyboard	OK
0x00000081-0x0000008F	Direct memory access controller	OK
0x000000C0-0x000000DF	Direct memory access controller	OK
0x00000070-0x00000071	System CMOS/real time clock	OK
0x00000020-0x00000021	Programmable interrupt controller	OK
0x000000A0-0x000000A1	Programmable interrupt controller	OK
0x000000F0-0x000000FF	Numeric data processor	OK
0x00000040-0x00000043	System timer	OK

```

0x00000061-0x00000061 System speaker OK
0x00000080-0x00000080 Motherboard resources OK
0x0000040B-0x0000040B Motherboard resources OK
0x000004D0-0x000004D1 Motherboard resources OK
0x000004D6-0x000004D6 Motherboard resources OK
0x00000500-0x0000051F Motherboard resources OK
0x00000C00-0x00000C01 Motherboard resources OK
0x00000C06-0x00000C08 Motherboard resources OK
0x00000C14-0x00000C14 Motherboard resources OK
0x00000C20-0x00000C3F Motherboard resources OK
0x00000C50-0x00000C52 Motherboard resources OK
0x00000C6F-0x00000C6F Motherboard resources OK
0x00000CD6-0x00000CD7 Motherboard resources OK
0x00000CE0-0x00000CEF Motherboard resources OK
0x00000F50-0x00000F58 Motherboard resources OK
0x000003F0-0x000003F5 Standard floppy disk controller OK
0x000003F7-0x000003F7 Standard floppy disk controller OK
0x00001440-0x0000144F Standard Dual Channel PCI IDE Controller OK
0x00001F00-0x00001F7 Primary IDE Channel OK
0x000003F6-0x000003F6 Primary IDE Channel OK
0x00000170-0x00000177 Secondary IDE Channel OK
0x00000376-0x00000376 Secondary IDE Channel OK
0x00000A79-0x00000A79 ISAPNP Read Data Port OK
0x00000279-0x00000279 ISAPNP Read Data Port OK
0x00000274-0x00000277 ISAPNP Read Data Port OK
0x00002000-0x00003FFF PCI bus OK
0x00002000-0x00003FFF DEC 21154 PCI to PCI bridge OK
0x00002000-0x00003FFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0x00003000-0x00003FFF DEC 21154 PCI to PCI bridge OK
0x00003000-0x00003FFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0x00004000-0x00005FFF PCI bus OK
0x00004000-0x00005FFF Adaptec AIC-7899 Ultra160 PCI SCSI Card OK
0x00005000-0x00005FFF DEC 21154 PCI to PCI bridge OK
0x00005000-0x00005FFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0x00004400-0x000044FF Adaptec AIC-7899 Ultra160 PCI SCSI Card OK
0x00006000-0x00006FFF PCI bus OK
0x00006000-0x00006FFF DEC 21154 PCI to PCI bridge OK
0x00006000-0x00006FFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0x00007000-0x00007FFF PCI bus OK
0x00007000-0x00007FFF DEC 21154 PCI to PCI bridge OK
0x00007000-0x00007FFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0x00008000-0x00008FFF PCI bus OK
0x00008000-0x00008FFF DEC 21154 PCI to PCI bridge OK
0x00008000-0x00008FFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0x00009000-0x0000AFFF PCI bus OK
0x00009000-0x0000AFFF QLogic QLA23xx PCI Fibre Channel Adapter OK
0x0000A000-0x0000AFFF DEC 21154 PCI to PCI bridge OK
0x0000A000-0x0000AFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK

```

```

0x00009400-0x0000943F Intel 825x-based PCI Ethernet Adapter (10/100)
OK

```

[IRQs]

```

Resource Device Status
IRQ 9Microsoft ACPI-Compliant System OK
IRQ 36 RAGE XL PCI (Microsoft Corporation) OK
IRQ 1Standard 101/102-Key or Microsoft Natural PS/2 Keyboard OK
IRQ 8System CMOS/real time clock OK
IRQ 13 Numeric data processor OK
IRQ 0System timer OK
IRQ 12 PS/2 Compatible Mouse OK
IRQ 6Standard floppy disk controller OK
IRQ 15 Secondary IDE Channel OK
IRQ 28 Mylex eXtremeRAID 2000 Disk Array Controller OK
IRQ 30 Mylex eXtremeRAID 2000 Disk Array Controller OK
IRQ 26 Mylex eXtremeRAID 2000 Disk Array Controller OK
IRQ 38 Adaptec AIC-7899 Ultra160 PCI SCSI Card OK
IRQ 39 Adaptec AIC-7899 Ultra160 PCI SCSI Card OK
IRQ 24 Mylex eXtremeRAID 2000 Disk Array Controller OK
IRQ 22 Mylex eXtremeRAID 2000 Disk Array Controller OK
IRQ 20 Mylex eXtremeRAID 2000 Disk Array Controller OK
IRQ 16 QLogic QLA23xx PCI Fibre Channel Adapter OK
IRQ 18 Mylex eXtremeRAID 2000 Disk Array Controller OK
IRQ 37 Intel 825x-based PCI Ethernet Adapter (10/100) OK

```

[Memory]

```

Resource Device Status
0xA0000-0xBFFFF PCI bus OK
0xA0000-0xBFFFF RAGE XL PCI (Microsoft Corporation) OK
0xD0000-0xE7FFF PCI bus OK
0xD2000000-0xD3FFFFFF PCI bus OK
0xD4000000-0xD40FFFFFF PCI bus OK
0xD3000000-0xD3FFFFFF RAGE XL PCI (Microsoft Corporation) OK
0xD2001000-0xD2001FFF RAGE XL PCI (Microsoft Corporation) OK
0xD4200000-0xD9FFFFFF PCI bus OK
0xDA000000-0xDDFFFFFF PCI bus OK
0xDA000000-0xDDFFFFFF DEC 21154 PCI to PCI bridge OK
0xDA000000-0xDDFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xD6000000-0xD7FFFFFF DEC 21154 PCI to PCI bridge OK
0xD6000000-0xD7FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xD8000000-0xD9FFFFFF DEC 21154 PCI to PCI bridge OK
0xD8000000-0xD9FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xDC000000-0xDDFFFFFF DEC 21154 PCI to PCI bridge OK
0xDC000000-0xDDFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xDE000000-0xE1FFFFFF PCI bus OK
0xDE000000-0xE1FFFFFF Adaptec AIC-7899 Ultra160 PCI SCSI Card OK
0xE2000000-0xE3FFFFFF PCI bus OK
0xE2000000-0xE3FFFFFF DEC 21154 PCI to PCI bridge OK

```

```

0xE2000000-0xE3FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xE0000000-0xE1FFFFFF DEC 21154 PCI to PCI bridge OK
0xE0000000-0xE1FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xDE001000-0xDE001FFF Adaptec AIC-7899 Ultra160 PCI SCSI Card OK
0xE4000000-0xE61FFFFFF PCI bus OK
0xE4000000-0xE61FFFFFF DEC 21154 PCI to PCI bridge OK
0xE4000000-0xE61FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xE8000000-0xE9FFFFFF PCI bus OK
0xE8000000-0xE9FFFFFF DEC 21154 PCI to PCI bridge OK
0xE8000000-0xE9FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xEA000000-0xEC1FFFFFF PCI bus OK
0xEA000000-0xEC1FFFFFF DEC 21154 PCI to PCI bridge OK
0xEA000000-0xEC1FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xEE000000-0xEFFFFFFF PCI bus OK
0xEE000000-0xEFFFFFFF DEC 21154 PCI to PCI bridge OK
0xEE000000-0xEFFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xF0000000-0xF21FFFFFF PCI bus OK
0xF0000000-0xF21FFFFFF DEC 21154 PCI to PCI bridge OK
0xF0000000-0xF21FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xF4000000-0xF5FFFFFF PCI bus OK
0xF4000000-0xF5FFFFFF DEC 21154 PCI to PCI bridge OK
0xF4000000-0xF5FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xF6000000-0xF9FFFFFF PCI bus OK
0xF6000000-0xF9FFFFFF Intel 8255x-based PCI Ethernet Adapter (10/100)
OK
0xFA000000-0xFBFFFFFF PCI bus OK
0xFA000000-0xFBFFFFFF DEC 21154 PCI to PCI bridge OK
0xFA000000-0xFBFFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xF6020000-0xF6020FFF QLogic QLA23xx PCI Fibre Channel Adapter OK
0xF8000000-0xF9FFFFFF DEC 21154 PCI to PCI bridge OK
0xF8000000-0xF9FFFFFF Mylex eXtremeRAID 2000 Disk Array Controller
OK
0xF6021000-0xF6021FFF Intel 8255x-based PCI Ethernet Adapter (10/100)
OK

```

[Components]

[Multimedia]

[Audio Codecs]

CODEC Manufacturer	Description	Status	File Version	Size
	Creation Date			

```

c:\windows\system32\msg711.acm Microsoft Corporation OK
C:\WINDOWS\system32\MSG711.ACM 5.2.3663.0 (main.020715-1506) 10.00
KB (10,240 bytes) 7/18/2002 2:00 PM
c:\windows\system32\msgsm32.acm Microsoft Corporation OK
C:\WINDOWS\system32\MSGSM32.ACM 5.2.3663.0 (main.020715-1506) 20.00
KB (20,480 bytes) 7/18/2002 2:00 PM
c:\windows\system32\sl_anet.acm Sipro Lab Telecom Inc. Sipro Lab
Telecom Audio Codec OK C:\WINDOWS\system32\SL_ANET.ACM 3.02 84.00 KB
(86,016 bytes) 7/18/2002 2:00 PM
c:\windows\system32\l3codeca.acm Fraunhofer Institut Integrierte
Schaltungen IIS Fraunhofer IIS MPEG Layer-3 Codec OK
C:\WINDOWS\system32\L3CODECA.ACM 1, 9, 0, 0305 284.00 KB
(290,816 bytes) 7/18/2002 2:00 PM
c:\windows\system32\imaadp32.acm Microsoft Corporation OK
C:\WINDOWS\system32\IMAADP32.ACM 5.2.3663.0 (main.020715-1506)
15.50 KB (15,872 bytes) 7/18/2002 2:00 PM
c:\windows\system32\tssoft32.acm DSP GROUP, INC. OK
C:\WINDOWS\system32\TSSOFT32.ACM 1.01 9.50 KB (9,728 bytes)
7/18/2002 2:00 PM
c:\windows\system32\msg723.acm Microsoft Corporation OK
C:\WINDOWS\system32\MSG723.ACM 4.4.4000 116.00 KB (118,784 bytes)
8/20/2002 10:47 AM
c:\windows\system32\msadp32.acm Microsoft Corporation OK
C:\WINDOWS\system32\MSADP32.ACM 5.2.3663.0 (main.020715-1506) 14.50
KB (14,848 bytes) 7/18/2002 2:00 PM
c:\windows\system32\msaud32.acm Microsoft Corporation Windows Media
Audio Codec OK C:\WINDOWS\system32\MSAUD32.ACM 8.00.00.4477
288.00 KB (294,912 bytes) 7/18/2002 2:00 PM

```

[Video Codecs]

CODEC Manufacturer	Description	Status	File Version	Size
	Creation Date			
c:\windows\system32\iyuv_32.dll	Microsoft Corporation	OK		
C:\WINDOWS\system32\IYUV_32.DLL	5.2.3663.0 (main.020715-1506)			45.00 KB (46,080 bytes) 7/16/2002 3:47 PM
c:\windows\system32\iccvid.dll	Radius Inc.	OK		
C:\WINDOWS\system32\ICCVID.DLL	1.10.0.6			108.00 KB (110,592 bytes) 7/18/2002 2:00 PM
c:\windows\system32\msh263.drv	Microsoft Corporation	OK		
C:\WINDOWS\system32\MSH263.DRV	4.4.4000			280.00 KB (286,720 bytes) 7/16/2002 3:46 PM
c:\windows\system32\msyuv.dll	Microsoft Corporation	OK		
C:\WINDOWS\system32\MSYUV.DLL	5.2.3663.0 (main.020715-1506)			16.50 KB (16,896 bytes) 7/16/2002 3:47 PM
c:\windows\system32\msrle32.dll	Microsoft Corporation	OK		
C:\WINDOWS\system32\MSRLE32.DLL	5.2.3663.0 (main.020715-1506)			10.50 KB (10,752 bytes) 7/18/2002 2:00 PM
c:\windows\system32\msvidc32.dll	Microsoft Corporation	OK		
C:\WINDOWS\system32\MSVIDC32.DLL	5.2.3663.0 (main.020715-1506)			26.50 KB (27,136 bytes) 7/18/2002 2:00 PM
c:\windows\system32\tsbyuv.dll	Microsoft Corporation	OK		
C:\WINDOWS\system32\TSBYUV.DLL	5.2.3663.0 (main.020715-1506)			8.00 KB (8,192 bytes) 7/16/2002 3:48 PM

c:\windows\system32\ir32\_32.dll Not Available OK  
C:\WINDOWS\system32\IR32\_32.DLL Not Available 194.50 KB (199,168 bytes) 7/18/2002 2:00 PM  
c:\windows\system32\msh261.drv Microsoft Corporation OK  
C:\WINDOWS\system32\MSH261.DRV 4.4.4000 180.00 KB (184,320 bytes) 8/20/2002 10:47 AM

[CD-ROM]

Item Value  
DriveD:  
Description CD-ROM Drive  
Media Loaded No  
Media Type CD-ROM  
Name MITSUMI CD-ROM SR243T  
Manufacturer (Standard CD-ROM drives)  
Status OK  
Transfer Rate Not Available  
SCSI Target ID 0  
PNP Device ID IDE\CDROMMITSUMI\_CD-ROM\_SR243T\_\_\_\_L02G\_\_\_\_\5&1159A16&0&0.0.0  
Driver c:\windows\system32\drivers\cdrom.sys (5.2.3663.0 (main.020715-1506), 47.75 KB (48,896 bytes), 7/18/2002 2:00 PM)

[Sound Device]

Item Value

[Display]

Item Value  
Name RAGE XL PCI (Microsoft Corporation)  
PNP Device ID PCI\VEN\_1002&DEV\_4752&SUBSYS\_0083110A&REV\_27\3&291BF6FF&0&28  
Adapter Type ATI RAGE XL PCI (B41), ATI Technologies Inc. compatible  
Adapter Description RAGE XL PCI (Microsoft Corporation)  
Adapter RAM 8.00 MB (8,388,608 bytes)  
Installed Drivers ati2drad.dll  
Driver Version 5.10.2600.6009  
INF File atiixpad.inf (ati2mpad section)  
Color Planes 1  
Color Table Entries 65536  
Resolution 800 x 600 x 60 hertz  
Bits/Pixel 16  
Memory Address 0xD3000000-0xD3FFFFFF  
I/O Port 0x00001000-0x0000144F  
Memory Address 0xD2001000-0xD2001FFF  
IRQ Channel IRQ 36  
I/O Port 0x000003B0-0x000003DF  
I/O Port 0x000003C0-0x000003DF  
Memory Address 0xA0000-0xBFFFF  
Driver c:\windows\system32\drivers\ati2mpad.sys (5.10.2600.6009 built by: jlu, 296.13 KB (303,232 bytes), 10/16/2002 8:11 AM)

[Infrared]

Item Value

[Input]

[Keyboard]

Item Value  
Description Standard 101/102-Key or Microsoft Natural PS/2 Keyboard  
Name Enhanced (101- or 102-key)  
Layout 00000409  
PNP Device ID ACPI\PNP0303\4&2647A8AF&0  
Number of Function Keys 12  
I/O Port 0x00000060-0x00000060  
I/O Port 0x00000064-0x00000064  
IRQ Channel IRQ 1  
Driver c:\windows\system32\drivers\i8042prt.sys (5.2.3663.0 (main.020715-1506), 50.50 KB (51,712 bytes), 7/18/2002 2:00 PM)

[Pointing Device]

Item Value  
Hardware Type PS/2 Compatible Mouse  
Number of Buttons 3  
Status OK  
PNP Device ID ACPI\PNP0F13\4&2647A8AF&0  
Power Management SupportedNo  
Double Click Threshold 6  
Handedness Right Handed Operation  
IRQ Channel IRQ 12  
Driver c:\windows\system32\drivers\i8042prt.sys (5.2.3663.0 (main.020715-1506), 50.50 KB (51,712 bytes), 7/18/2002 2:00 PM)

[Modem]

Item Value

[Network]

[Adapter]

Item Value  
Name [00000001] Broadcom NetXtreme Gigabit Ethernet  
Adapter Type Not Available  
Product Type Broadcom NetXtreme Gigabit Ethernet  
Installed Yes  
PNP Device ID Not Available  
Last Reset 10/24/2002 10:43 AM  
Index1  
Service Name b57w2k  
IP Address 129.103.181.44  
IP Subnet 255.255.255.0  
Default IP Gateway Not Available

DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address 00:30:05:30:19:62

Name [00000002] RAS Async Adapter  
Adapter Type Not Available  
Product Type RAS Async Adapter  
Installed Yes  
PNP Device ID Not Available  
Last Reset 10/24/2002 10:43 AM  
Index 2  
Service Name AsyncMac  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available

Name [00000003] WAN Miniport (L2TP)  
Adapter Type Not Available  
Product Type WAN Miniport (L2TP)  
Installed Yes  
PNP Device ID ROOT\MS\_L2TPMINIPORT\0000  
Last Reset 10/24/2002 10:43 AM  
Index 3  
Service Name Rasl2tp  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Driver c:\windows\system32\drivers\rasl2tp.sys (5.2.3663.0  
(main.020715-1506), 61.63 KB (63,104 bytes), 7/18/2002 2:00 PM)

Name [00000004] WAN Miniport (PPTP)  
Adapter Type Wide Area Network (WAN)  
Product Type WAN Miniport (PPTP)  
Installed Yes  
PNP Device ID ROOT\MS\_PPTPMINIPORT\0000  
Last Reset 10/24/2002 10:43 AM  
Index 4  
Service Name PptpMiniport  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available

DHCP Lease Obtained Not Available  
MAC Address 50:50:54:50:30:30  
Driver c:\windows\system32\drivers\rasptp.sys (5.2.3663.0  
(main.020715-1506), 56.00 KB (57,344 bytes), 7/18/2002 2:00 PM)

Name [00000005] WAN Miniport (PPPOE)  
Adapter Type Wide Area Network (WAN)  
Product Type WAN Miniport (PPPOE)  
Installed Yes  
PNP Device ID ROOT\MS\_PPPOEMINIPORT\0000  
Last Reset 10/24/2002 10:43 AM  
Index 5  
Service Name RasPppoe  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address 33:50:6F:45:30:30  
Driver c:\windows\system32\drivers\raspppoe.sys (5.2.3663.0  
(main.020715-1506), 36.88 KB (37,760 bytes), 7/18/2002 2:00 PM)

Name [00000006] Direct Parallel  
Adapter Type Not Available  
Product Type Direct Parallel  
Installed Yes  
PNP Device ID ROOT\MS\_PTMINIPORT\0000  
Last Reset 10/24/2002 10:43 AM  
Index 6  
Service Name Raspti  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Driver c:\windows\system32\drivers\raspti.sys (5.2.3663.0  
(main.020715-1506), 16.38 KB (16,768 bytes), 7/18/2002 2:00 PM)

Name [00000007] WAN Miniport (IP)  
Adapter Type Not Available  
Product Type WAN Miniport (IP)  
Installed Yes  
PNP Device ID ROOT\MS\_NDISWANIP\0000  
Last Reset 10/24/2002 10:43 AM  
Index 7  
Service Name NdisWan  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available

DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Driver c:\windows\system32\drivers\ndiswan.sys (5.2.3663.0  
(main.020715-1506), 87.13 KB (89,216 bytes), 7/18/2002 2:00 PM)

Name [00000008] Intel(R) PRO/1000 XT Server Adapter  
Adapter Type Not Available  
Product Type Intel(R) PRO/1000 XT Server Adapter  
Installed Yes  
PNP Device ID Not Available  
Last Reset 10/24/2002 10:43 AM  
Index 8  
Service Name E1000  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available

Name [00000009] Intel 8255x-based PCI Ethernet Adapter (10/100)  
Adapter Type Ethernet 802.3  
Product Type Intel 8255x-based PCI Ethernet Adapter (10/100)  
Installed Yes  
PNP Device ID  
PCI\VEN\_8086&DEV\_1229&SUBSYS\_0083110A&REV\_09\3&2AEF1B1C&0&48

Last Reset 10/24/2002 10:43 AM  
Index 9  
Service Name E100B  
IP Address 129.103.181.44  
IP Subnet 255.255.255.0  
Default IP Gateway Not Available  
DHCP Enabled No  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address 00:30:05:30:19:62  
Memory Address 0xF6021000-0xF6021FFF  
I/O Port 0x00009400-0x0000943F  
Memory Address 0xF6000000-0xF9FFFFFFF  
IRQ Channel IRQ 37  
Driver c:\windows\system32\drivers\e100b325.sys (6.03.03.0000 built  
by: WinDDK, 135.50 KB (138,752 bytes), 10/16/2002 8:20 AM)

[Protocol]

Item Value  
Name MSAFD Tcpip [TCP/IP]  
Connectionless Service No  
Guarantees Delivery Yes  
Guarantees Sequencing Yes  
Maximum Address Size 16 bytes  
Maximum Message Size 0 bytes

Message Oriented No  
Minimum Address Size 16 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting No  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data Yes  
Supports Graceful Closing Yes  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSFAD Tcpip [UDP/IP]  
Connectionless Service Yes  
Guarantees Delivery No  
Guarantees Sequencing No  
Maximum Address Size 16 bytes  
Maximum Message Size 63.93 KB (65,467 bytes)  
Message Oriented Yes  
Minimum Address Size 16 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting Yes  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting Yes

Name RSVP UDP Service Provider  
Connectionless Service Yes  
Guarantees Delivery No  
Guarantees Sequencing No  
Maximum Address Size 16 bytes  
Maximum Message Size 63.93 KB (65,467 bytes)  
Message Oriented Yes  
Minimum Address Size 16 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting Yes  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption Yes  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting Yes

Name RSVP TCP Service Provider  
Connectionless Service No  
Guarantees Delivery Yes  
Guarantees Sequencing Yes  
Maximum Address Size 16 bytes  
Maximum Message Size 0 bytes  
Message Oriented No  
Minimum Address Size 16 bytes

Pseudo Stream Oriented No  
Supports Broadcasting No  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption Yes  
Supports Expedited Data Yes  
Supports Graceful Closing Yes  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{D4DE74E3-F20A-44E1-81C4-647C574E5775}] SEQPACKET 4

Connectionless Service No  
Guarantees Delivery Yes  
Guarantees Sequencing Yes  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting No  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{D4DE74E3-F20A-44E1-81C4-647C574E5775}] DATAGRAM 4

Connectionless Service Yes  
Guarantees Delivery No  
Guarantees Sequencing No  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting Yes  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{04C22C36-E69B-4BF7-B81D-DADCF9EF2717}] SEQPACKET 3

Connectionless Service No  
Guarantees Delivery Yes  
Guarantees Sequencing Yes  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes

Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting No  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{04C22C36-E69B-4BF7-B81D-DADCF9EF2717}] DATAGRAM 3

Connectionless Service Yes  
Guarantees Delivery No  
Guarantees Sequencing No  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting Yes  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{D3EC93BE-CC09-4B70-B14F-00B02436065D}] SEQPACKET 0

Connectionless Service No  
Guarantees Delivery Yes  
Guarantees Sequencing Yes  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting No  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{D3EC93BE-CC09-4B70-B14F-00B02436065D}] DATAGRAM 0

Connectionless Service Yes  
Guarantees Delivery No  
Guarantees Sequencing No  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)

Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting Yes  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{AAF5F905-FEF4-4551-BD8A-2FC82BCCC14E}] SEQUENCE 1  
Connectionless Service No  
Guarantees Delivery Yes  
Guarantees Sequencing Yes  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting No  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{AAF5F905-FEF4-4551-BD8A-2FC82BCCC14E}] DATAGRAM 1  
Connectionless Service Yes  
Guarantees Delivery No  
Guarantees Sequencing No  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting Yes  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{78F8B33D-13E0-4BAC-92B5-3AAD2E2A6076}] SEQUENCE 2  
Connectionless Service No  
Guarantees Delivery Yes  
Guarantees Sequencing Yes  
Maximum Address Size 20 bytes

Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting No  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{78F8B33D-13E0-4BAC-92B5-3AAD2E2A6076}] DATAGRAM 2  
Connectionless Service Yes  
Guarantees Delivery No  
Guarantees Sequencing No  
Maximum Address Size 20 bytes  
Maximum Message Size 62.50 KB (64,000 bytes)  
Message Oriented Yes  
Minimum Address Size 20 bytes  
Pseudo Stream Oriented No  
Supports Broadcasting Yes  
Supports Connect Data No  
Supports Disconnect Data No  
Supports Encryption No  
Supports Expedited Data No  
Supports Graceful Closing No  
Supports Guaranteed Bandwidth No  
Supports Multicasting No

[WinSock]

Item Value  
File c:\windows\system32\winsock.dll  
Size 2.80 KB (2,864 bytes)  
Version 3.10

File c:\windows\system32\wsock32.dll  
Size 22.00 KB (22,528 bytes)  
Version 5.2.3663.0 (main.020715-1506)

[Ports]

[Serial]

Item Value

[Parallel]

Item Value

[Storage]

[Drives]

Item Value  
DriveA:  
Description 3 1/2 Inch Floppy Drive

DriveC:  
Description Local Fixed Disk  
Compressed No  
File System NTFS  
Size 17.09 GB (18,350,563,328 bytes)  
Free Space 12.73 GB (13,672,247,296 bytes)  
Volume Name  
Volume Serial Number A83A7583

DriveD:  
Description CD-ROM Disc

DriveE:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveF:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveG:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveH:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveI:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveJ:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveL:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveN:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveO:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveP:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveQ:

Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveR:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveS:  
Description Local Fixed Disk  
Compressed Not Available  
File System Not Available  
Size Not Available  
Free Space Not Available  
Volume Name Not Available  
Volume Serial Number Not Available

DriveU:  
Description Local Fixed Disk  
Compressed No  
File System NTFS  
Size 292.97 GB (314,575,798,272 bytes)  
Free Space 225.40 GB (242,024,095,744 bytes)  
Volume Name backup1  
Volume Serial Number C4FDA507

DriveV:  
Description Local Fixed Disk  
Compressed No  
File System NTFS  
Size 292.97 GB (314,575,798,272 bytes)  
Free Space 225.40 GB (242,024,079,360 bytes)  
Volume Name backup2  
Volume Serial Number 508E74B3

DriveW:  
Description Local Fixed Disk  
Compressed No  
File System NTFS  
Size 292.97 GB (314,575,798,272 bytes)  
Free Space 225.40 GB (242,020,323,328 bytes)  
Volume Name backup3  
Volume Serial Number F4DD24D2

DriveX:  
Description Local Fixed Disk  
Compressed No

File System NTFS  
Size 292.97 GB (314,575,798,272 bytes)  
Free Space 225.40 GB (242,024,128,512 bytes)  
Volume Name backup4  
Volume Serial Number D4FBE081

DriveY:  
Description Local Fixed Disk  
Compressed No  
File System NTFS  
Size 292.97 GB (314,575,798,272 bytes)  
Free Space 225.40 GB (242,024,128,512 bytes)  
Volume Name backup5  
Volume Serial Number 1824F05E

DriveZ:  
Description Local Fixed Disk  
Compressed No  
File System NTFS  
Size 292.97 GB (314,575,798,272 bytes)  
Free Space 225.40 GB (242,023,682,048 bytes)  
Volume Name backup6  
Volume Serial Number EC384D2E

[Disks]

Item Value  
Description \\.\PHYSICALDRIVE4  
Manufacturer Not Available  
Model Not Available  
Bytes/Sector 512  
Media Loaded Yes  
Media Type Fixed hard disk  
Partitions 3  
SCSI Bus 4  
SCSI Logical Unit 0  
SCSI Port 7  
SCSI Target ID 0  
Sectors/Track 63  
Size 810.74 GB (870,530,734,080 bytes)  
Total Cylinders 105,836  
Total Sectors 1,700,255,340  
Total Tracks 26,988,180  
Tracks/Cylinder 255  
Partition Disk #4, Partition #0  
Partition Size 51.27 GB (55,051,766,784 bytes)  
Partition Starting Offset 8,257,536 bytes  
Partition Disk #4, Partition #1  
Partition Size 28.81 GB (30,935,245,824 bytes)  
Partition Starting Offset 55,060,056,576 bytes  
Partition Disk #4, Partition #2  
Partition Size 292.97 GB (314,575,801,344 bytes)  
Partition Starting Offset 152,044,333,056 bytes

Description \\.\PHYSICALDRIVE3  
Manufacturer Not Available

ModelNot Available  
Bytes/Sector 512  
Media Loaded Yes  
Media Type Fixed hard disk  
Partitions 1  
SCSI Bus 4  
SCSI Logical Unit 0  
SCSI Port 6  
SCSI Target ID 0  
Sectors/Track 63  
Size 169.41 GB (181,902,067,200 bytes)  
Total Cylinders 22,115  
Total Sectors 355,277,475  
Total Tracks 5,639,325  
Tracks/Cylinder 255  
Partition Disk #3, Partition #0  
Partition Size 117.19 GB (125,830,301,184 bytes)  
Partition Starting Offset 8,257,536 bytes

Description \\.\PHYSICALDRIVE7  
Manufacturer Not Available  
ModelNot Available  
Bytes/Sector 512  
Media Loaded Yes  
Media Type Fixed hard disk  
Partitions 3  
SCSI Bus 4  
SCSI Logical Unit 0  
SCSI Port 10  
SCSI Target ID 0  
Sectors/Track 63  
Size 810.74 GB (870,530,734,080 bytes)  
Total Cylinders 105,836  
Total Sectors 1,700,255,340  
Total Tracks 26,988,180  
Tracks/Cylinder 255  
Partition Disk #7, Partition #0  
Partition Size 51.27 GB (55,051,766,784 bytes)  
Partition Starting Offset 8,257,536 bytes  
Partition Disk #7, Partition #1  
Partition Size 28.81 GB (30,935,245,824 bytes)  
Partition Starting Offset 55,060,056,576 bytes  
Partition Disk #7, Partition #2  
Partition Size 292.97 GB (314,575,801,344 bytes)  
Partition Starting Offset 152,044,333,056 bytes

Description \\.\PHYSICALDRIVE2  
Manufacturer Not Available  
ModelNot Available  
Bytes/Sector 512  
Media Loaded Yes  
Media Type Fixed hard disk  
Partitions 3  
SCSI Bus 4  
SCSI Logical Unit 0  
SCSI Port 5

SCSI Target ID 0  
Sectors/Track 63  
Size 810.74 GB (870,530,734,080 bytes)  
Total Cylinders 105,836  
Total Sectors 1,700,255,340  
Total Tracks 26,988,180  
Tracks/Cylinder 255  
Partition Disk #2, Partition #0  
Partition Size 51.27 GB (55,051,766,784 bytes)  
Partition Starting Offset 8,257,536 bytes  
Partition Disk #2, Partition #1  
Partition Size 28.81 GB (30,935,245,824 bytes)  
Partition Starting Offset 55,060,056,576 bytes  
Partition Disk #2, Partition #2  
Partition Size 292.97 GB (314,575,801,344 bytes)  
Partition Starting Offset 152,044,333,056 bytes

Description \\.\PHYSICALDRIVE8  
Manufacturer Not Available  
ModelNot Available  
Bytes/Sector 512  
Media Loaded Yes  
Media Type Fixed hard disk  
Partitions 3  
SCSI Bus 4  
SCSI Logical Unit 0  
SCSI Port 11  
SCSI Target ID 0  
Sectors/Track 63  
Size 810.74 GB (870,530,734,080 bytes)  
Total Cylinders 105,836  
Total Sectors 1,700,255,340  
Total Tracks 26,988,180  
Tracks/Cylinder 255  
Partition Disk #8, Partition #0  
Partition Size 51.27 GB (55,051,766,784 bytes)  
Partition Starting Offset 8,257,536 bytes  
Partition Disk #8, Partition #1  
Partition Size 28.81 GB (30,935,245,824 bytes)  
Partition Starting Offset 55,060,056,576 bytes  
Partition Disk #8, Partition #2  
Partition Size 292.97 GB (314,575,801,344 bytes)  
Partition Starting Offset 152,044,333,056 bytes

Description \\.\PHYSICALDRIVE5  
Manufacturer Not Available  
ModelNot Available  
Bytes/Sector 512  
Media Loaded Yes  
Media Type Fixed hard disk  
Partitions 3  
SCSI Bus 4  
SCSI Logical Unit 0  
SCSI Port 8  
SCSI Target ID 0  
Sectors/Track 63

Size 810.74 GB (870,530,734,080 bytes)  
 Total Cylinders 105,836  
 Total Sectors 1,700,255,340  
 Total Tracks 26,988,180  
 Tracks/Cylinder 255  
 Partition Disk #5, Partition #0  
 Partition Size 51.27 GB (55,051,766,784 bytes)  
 Partition Starting Offset 8,257,536 bytes  
 Partition Disk #5, Partition #1  
 Partition Size 28.81 GB (30,935,245,824 bytes)  
 Partition Starting Offset 55,060,056,576 bytes  
 Partition Disk #5, Partition #2  
 Partition Size 292.97 GB (314,575,801,344 bytes)  
 Partition Starting Offset 152,044,333,056 bytes

Description \\.\PHYSICALDRIVE6  
 Manufacturer Not Available  
 Model Not Available  
 Bytes/Sector 512  
 Media Loaded Yes  
 Media Type Fixed hard disk  
 Partitions 3  
 SCSI Bus 4  
 SCSI Logical Unit 0  
 SCSI Port 9  
 SCSI Target ID 0  
 Sectors/Track 63  
 Size 810.74 GB (870,530,734,080 bytes)  
 Total Cylinders 105,836  
 Total Sectors 1,700,255,340  
 Total Tracks 26,988,180  
 Tracks/Cylinder 255  
 Partition Disk #6, Partition #0  
 Partition Size 51.27 GB (55,051,766,784 bytes)  
 Partition Starting Offset 8,257,536 bytes  
 Partition Disk #6, Partition #1  
 Partition Size 28.81 GB (30,935,245,824 bytes)  
 Partition Starting Offset 55,060,056,576 bytes  
 Partition Disk #6, Partition #2  
 Partition Size 292.97 GB (314,575,801,344 bytes)  
 Partition Starting Offset 152,060,783,616 bytes

Description Disk drive  
 Manufacturer (Standard disk drives)  
 Model QLOGIC PSEUDO LUN SCSI Disk Device  
 Bytes/Sector 512  
 Media Loaded No  
 Media Type Fixed hard disk  
 Partitions Not Available  
 SCSI Bus 0  
 SCSI Logical Unit 0  
 SCSI Port 2  
 SCSI Target ID 127  
 Sectors/Track 0  
 Size 0 bytes  
 Total Cylinders 0

Total Sectors 0  
 Total Tracks 0  
 Tracks/Cylinder 0

Description Disk drive  
 Manufacturer (Standard disk drives)  
 Model SEAGATE ST318452LC SCSI Disk Device  
 Bytes/Sector 512  
 Media Loaded Yes  
 Media Type Fixed hard disk  
 Partitions 1  
 SCSI Bus 0  
 SCSI Logical Unit 0  
 SCSI Port 3  
 SCSI Target ID 0  
 Sectors/Track 63  
 Size 17.09 GB (18,350,599,680 bytes)  
 Total Cylinders 2,231  
 Total Sectors 35,841,015  
 Total Tracks 568,905  
 Tracks/Cylinder 255  
 Partition Disk #1, Partition #0  
 Partition Size 17.09 GB (18,350,567,424 bytes)  
 Partition Starting Offset 32,256 bytes

[SCSI]

Item Value  
 Name Mylex eXtremeRAID 2000 Disk Array Controller  
 Manufacturer Mylex  
 Status OK  
 PNP Device ID  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2254B0D&0&4030  
 Memory Address 0xD6000000-0xD7FFFFFFF  
 I/O Port 0x00002000-0x00003FFF  
 Memory Address 0xDA000000-0xDDFFFFFFF  
 IRQ Channel IRQ 28  
 Driver c:\windows\system32\drivers\dac2w2k.sys (80.00-01, 170.38 KB (174,464 bytes), 6/10/2002 4:11 PM)

Name Mylex eXtremeRAID 2000 Disk Array Controller  
 Manufacturer Mylex  
 Status OK  
 PNP Device ID  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&1C72A60D&0&4038  
 Memory Address 0xD8000000-0xD9FFFFFFF  
 I/O Port 0x00003000-0x00003FFF  
 Memory Address 0xDC000000-0xDDFFFFFFF  
 IRQ Channel IRQ 30  
 Driver c:\windows\system32\drivers\dac2w2k.sys (80.00-01, 170.38 KB (174,464 bytes), 6/10/2002 4:11 PM)

Name Mylex eXtremeRAID 2000 Disk Array Controller  
 Manufacturer Mylex  
 Status OK

PNP Device ID  
PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&1ECE4987&0&4028  
Memory Address 0xE0000000-0xE1FFFFFF  
I/O Port 0x00005000-0x00005FFF  
Memory Address 0xE2000000-0xE3FFFFFF  
IRQ Channel IRQ 26  
Driver c:\windows\system32\drivers\dac2w2k.sys (80.00-01, 170.38 KB  
(174,464 bytes), 6/10/2002 4:11 PM)

Name Adaptec AIC-7899 Ultra160 PCI SCSI Card  
Manufacturer Adaptec  
Status OK  
PNP Device ID  
PCI\VEN\_9005&DEV\_00CF&SUBSYS\_0083110A&REV\_01\3&12F48E42&0&40  
I/O Port 0x00004000-0x00005FFF  
Memory Address 0xDE000000-0xE1FFFFFF  
IRQ Channel IRQ 38  
Driver c:\windows\system32\drivers\adpul60m.sys (RTC\_XP07  
(lab01\_n(storbuild).010917-1031), 99.63 KB (102,016 bytes), 7/18/2002  
2:00 PM)

Name Adaptec AIC-7899 Ultra160 PCI SCSI Card  
Manufacturer Adaptec  
Status OK  
PNP Device ID  
PCI\VEN\_9005&DEV\_00CF&SUBSYS\_0083110A&REV\_01\3&12F48E42&0&41  
I/O Port 0x00004400-0x000044FF  
Memory Address 0xDE001000-0xDE001FFF  
IRQ Channel IRQ 39  
Driver c:\windows\system32\drivers\adpul60m.sys (RTC\_XP07  
(lab01\_n(storbuild).010917-1031), 99.63 KB (102,016 bytes), 7/18/2002  
2:00 PM)

Name Mylex eXtremeRAID 2000 Disk Array Controller  
Manufacturer Mylex  
Status OK  
PNP Device ID  
PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2F92D4B0&0&4020  
Memory Address 0xE4000000-0xE61FFFFFF  
I/O Port 0x00006000-0x00006FFF  
Memory Address 0xE8000000-0xE9FFFFFF  
IRQ Channel IRQ 24  
Driver c:\windows\system32\drivers\dac2w2k.sys (80.00-01, 170.38 KB  
(174,464 bytes), 6/10/2002 4:11 PM)

Name Mylex eXtremeRAID 2000 Disk Array Controller  
Manufacturer Mylex  
Status OK  
PNP Device ID  
PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2DF34B01&0&4018  
Memory Address 0xEA000000-0xEC1FFFFFF  
I/O Port 0x00007000-0x00007FFF  
Memory Address 0xEE000000-0xEFFFFFFF  
IRQ Channel IRQ 22  
Driver c:\windows\system32\drivers\dac2w2k.sys (80.00-01, 170.38 KB  
(174,464 bytes), 6/10/2002 4:11 PM)

Name Mylex eXtremeRAID 2000 Disk Array Controller  
Manufacturer Mylex  
Status OK  
PNP Device ID  
PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2BEE4042&0&4010  
Memory Address 0xF0000000-0xF21FFFFFF  
I/O Port 0x00008000-0x00008FFF  
Memory Address 0xF4000000-0xF5FFFFFF  
IRQ Channel IRQ 20  
Driver c:\windows\system32\drivers\dac2w2k.sys (80.00-01, 170.38 KB  
(174,464 bytes), 6/10/2002 4:11 PM)

Name QLogic QLA23xx PCI Fibre Channel Adapter  
Manufacturer QLogic  
Status OK  
PNP Device ID  
PCI\VEN\_1077&DEV\_2312&SUBSYS\_010C1077&REV\_02\3&2AEF1B1C&0&20  
I/O Port 0x00009000-0x0000AFFF  
Memory Address 0xF6020000-0xF6020FFF  
IRQ Channel IRQ 16  
Driver c:\windows\system32\drivers\ql2300.sys (8.2.0 Beta 3 (W2K VI),  
429.70 KB (440,012 bytes), 10/7/2002 2:36 PM)

Name Mylex eXtremeRAID 2000 Disk Array Controller  
Manufacturer Mylex  
Status OK  
PNP Device ID  
PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&3AE9BCCD&0&4028  
Memory Address 0xF8000000-0xF9FFFFFF  
I/O Port 0x0000A000-0x0000AFFF  
Memory Address 0xFA000000-0xFBFFFFFF  
IRQ Channel IRQ 18  
Driver c:\windows\system32\drivers\dac2w2k.sys (80.00-01, 170.38 KB  
(174,464 bytes), 6/10/2002 4:11 PM)

Name QLogic VI Kernel Agent driver  
Manufacturer QLogic  
Status Degraded  
PNP Device ID ROOT\SCSIADAPTER\0000  
Driver c:\windows\system32\drivers\qlvika.sys (1.00.14 (W2K), 48.75 KB  
(49,916 bytes), 10/7/2002 2:37 PM)

[IDE]

Item Value  
Name Standard Dual Channel PCI IDE Controller  
Manufacturer (Standard IDE ATA/ATAPI controllers)  
Status OK  
PNP Device ID  
PCI\VEN\_1166&DEV\_0212&SUBSYS\_02121166&REV\_93\3&291BF6FF&0&79  
I/O Port 0x00001440-0x0000144F  
Driver c:\windows\system32\drivers\pciide.sys (5.2.3663.0  
(main.020715-1506), 3.50 KB (3,584 bytes), 10/16/2002 8:12 AM)

Name Primary IDE Channel

Manufacturer (Standard IDE ATA/ATAPI controllers)  
 Status OK  
 PNP Device ID PCI\IDE\IDECHANNEL\4&15AF076&0&0  
 I/O Port 0x000001F0-0x000001F7  
 I/O Port 0x000003F6-0x000003F6  
 Driver c:\windows\system32\drivers\ataapi.sys (5.2.3663.0 (main.020715-1506), 90.38 KB (92,544 bytes), 7/18/2002 2:00 PM)

Name Secondary IDE Channel  
 Manufacturer (Standard IDE ATA/ATAPI controllers)  
 Status OK  
 PNP Device ID PCI\IDE\IDECHANNEL\4&15AF076&0&1  
 I/O Port 0x00000170-0x00000177  
 I/O Port 0x00000376-0x00000376  
 IRQ Channel IRQ 15  
 Driver c:\windows\system32\drivers\ataapi.sys (5.2.3663.0 (main.020715-1506), 90.38 KB (92,544 bytes), 7/18/2002 2:00 PM)

[Printing]

Name Driver Port Name Server Name

[Problem Devices]

Device PNP Device ID Error Code  
 FSC Remote Service Controller, mailbox device  
 PCI\VEN\_110A&DEV\_007B&SUBSYS\_008F110A&REV\_00\3&291BF6FF&0&20 This device is disabled.  
 FSC Remote Service Controller, shared memory device  
 PCI\VEN\_110A&DEV\_007C&SUBSYS\_008F110A&REV\_00\3&291BF6FF&0&21 This device is disabled.  
 FSC Remote Service Controller, SMIC device  
 PCI\VEN\_110A&DEV\_007D&SUBSYS\_008F110A&REV\_00\3&291BF6FF&0&22 This device is disabled.  
 Communications Port (COM1) ACPI\PNP0501\1 This device is disabled.  
 Communications Port (COM2) ACPI\PNP0501\2 This device is disabled.  
 ECP Printer Port (LPT1) ACPI\PNP0401\4&2647A8AF&0 This device is disabled.  
 ServerWorks (RCC) PCI to USB Open Host Controller  
 PCI\VEN\_1166&DEV\_0220&SUBSYS\_02201166&REV\_05\3&291BF6FF&0&7A This device is disabled.

[USB]

Device PNP Device ID  
 ServerWorks (RCC) PCI to USB Open Host Controller  
 PCI\VEN\_1166&DEV\_0220&SUBSYS\_02201166&REV\_05\3&291BF6FF&0&7A

[Software Environment]

[System Drivers]

Name	Description	File	Type	Started	Start	Mode	State	Status	Error
Control	Accept Pause	Accept	Stop						

abiosdsk	Abiosdsk	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Ignore	No	No				
acpi	Microsoft ACPI Driver	c:\windows\system32\drivers\acpi.sys	Kernel Driver	Yes	Boot Running	OK	Normal	No	Yes
acpiec	ACPIEC	c:\windows\system32\drivers\acpiec.sys	Kernel Driver	No	Disabled	Stopped	OK	Normal	No
adpu160m	adpu160m	c:\windows\system32\drivers\adpu160m.sys	Kernel Driver	Yes	Boot Running	OK	Normal	No	Yes
adpu320	adpu320	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Normal	No	No				
afcntafcnt	Not Available	Kernel Driver	No	Disabled	Stopped	OK			
	Normal	No	No						
afd	AFD Networking Support Environment	c:\windows\system32\drivers\afd.sys	Kernel Driver	Yes	Auto	Running	OK	Normal	Yes
ahal54x	Ahal54x	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Normal	No	No				
aic78u2	aic78u2	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Normal	No	No				
aic78xx	aic78xx	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Normal	No	No				
aliide	AliIde	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Normal	No	No				
asynmac	RAS Asynchronous Media Driver	c:\windows\system32\drivers\asynmac.sys	Kernel Driver	No		Manual	Stopped	OK	Normal
				No	No				
atapi	Standard IDE/ESDI Hard Disk Controller	c:\windows\system32\drivers\ataapi.sys	Kernel Driver	Yes	Boot	Running	OK	Normal	Yes
				Yes	Yes				
atdisk	Atdisk	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Ignore	No	No				
ati2mpad	ati2mpad	c:\windows\system32\drivers\ati2mpad.sys	Kernel Driver	Yes	Manual	Running	OK	Ignore	No
	Driver			Yes	Yes				
atmarpc	ATM ARP Client Protocol	c:\windows\system32\drivers\atmarpc.sys	Kernel Driver	No		Manual	Stopped	OK	Normal
				No	No				
audstub	Audio Stub Driver	c:\windows\system32\drivers\audstub.sys	Kernel Driver	Yes	Manual	Running	OK	Normal	No
				Yes	Yes				
b57w2k	Broadcom NetXtreme Gigabit Ethernet	c:\windows\system32\drivers\b57xp32.sys	Kernel Driver	No		Manual	Stopped	OK	Normal
				No	No				
beep	Beep	c:\windows\system32\drivers\beep.sys	Kernel Driver	Yes		System	Running	OK	Normal
				Yes	Yes				
cbidf2k	cbidf2k	c:\windows\system32\drivers\cbidf2k.sys	Kernel Driver	No	Disabled	Stopped	OK	Normal	No
	Driver			No	No				
cd20xrnt	cd20xrnt	Not Available	Kernel Driver	No	Disabled				
	Stopped	OK	Normal	No	No				
cdfs	Cdfs	c:\windows\system32\drivers\cdfs.sys	File System Driver	Yes	Disabled	Running	OK	Normal	Yes
				Yes	Yes				
cdrom	CD-ROM Driver	c:\windows\system32\drivers\cdrom.sys	Kernel Driver	Yes	System	Running	OK	Normal	No
	Driver			Yes	Yes				
changer	Changer	Not Available	Kernel Driver	No	System	Stopped	OK	Ignore	No
				No	No				
clusdisk	Cluster Disk Driver	c:\windows\system32\drivers\clusdisk.sys	Kernel Driver	No	Disabled	Stopped	OK	Normal	No
				No	No				

```

cmdide CmdIde Not Available Kernel Driver No Disabled
Stopped OK Normal No No
cpqarray Cpqarray Not Available Kernel Driver No Disabled
Stopped OK Normal No No
cpqarray2 cpqarray2 Not Available Kernel Driver No Disabled
Stopped OK Normal No No
cpqcissm cpqcissm Not Available Kernel Driver No Disabled
Stopped OK Normal No No
cpqfcalm cpqfcalm Not Available Kernel Driver No Disabled
Stopped OK Normal No No
crcdisk CRC Disk Filter Driver
c:\windows\system32\drivers\crcdisk.sys Kernel Driver Yes Boot
Running OK Normal No Yes
dac2w2k dac2w2k c:\windows\system32\drivers\dac2w2k.sys Kernel
Driver Yes Boot Running OK Normal No Yes
dac960nt dac960nt Not Available Kernel Driver No Disabled
Stopped OK Normal No No
dfsdriver DfsDriver c:\windows\system32\drivers\dfs.sys File System
Driver Yes Boot Running OK Normal No Yes
disk Disk Driver c:\windows\system32\drivers\disk.sys Kernel Driver
Yes Boot Running OK Normal No Yes
dmboot dmboot c:\windows\system32\drivers\dmboot.sys Kernel
Driver No Disabled Stopped OK Normal No No
dmio Logical Disk Manager Driver c:\windows\system32\drivers\dmio.sys
Kernel Driver Yes Boot Running OK Normal No Yes
dmload dmload c:\windows\system32\drivers\dmload.sys Kernel
Driver Yes Boot Running OK Normal No Yes
dpti2o dpti2o Not Available Kernel Driver No Disabled
Stopped OK Normal No No
dspciCfg DsPciCfg \??\c:\windows\system32\drivers\dspciCfg.sys
Kernel Driver Yes Auto Running OK Normal No Yes
e1000 Intel(R) PRO/1000 Device Driver
c:\windows\system32\drivers\e1000325.sys Kernel Driver No
Manual Stopped OK Normal No No
e100b Intel(R) PRO Adapter Driver
c:\windows\system32\drivers\e100b325.sys Kernel Driver Yes
Manual Running OK Normal No Yes
em em c:\windows\system32\drivers\em.sys Kernel Driver No
Manual Stopped OK Normal No No
fastfat Fastfat c:\windows\system32\drivers\fastfat.sys File
System Driver Yes Disabled Running OK Normal No Yes
fdc Floppy Disk Controller Driver c:\windows\system32\drivers\fdc.sys
Kernel Driver Yes Manual Running OK Normal No Yes
fips Fips c:\windows\system32\drivers\fips.sys Kernel Driver Yes
System Running OK Normal No Yes
flpydisk Floppy Disk Driver c:\windows\system32\drivers\flpydisk.sys
Kernel Driver Yes Manual Running OK Normal No Yes
ftdisk Volume Manager Driver
c:\windows\system32\drivers\ftdisk.sys Kernel Driver Yes Boot
Running OK Normal No Yes
gpc Generic Packet Classifier c:\windows\system32\drivers\msgpc.sys
Kernel Driver Yes Manual Running OK Normal No Yes
hpn hpn Not Available Kernel Driver No Disabled Stopped OK
Normal No No
hpt3xx hpt3xx Not Available Kernel Driver No Disabled
Stopped OK Normal No No

```

```

http HTTP c:\windows\system32\drivers\http.sys Kernel Driver No
Manual Stopped OK Normal No No
i2omgmt i2omgmt Not Available Kernel Driver No System
Stopped OK Normal No No
i2omp i2omp Not Available Kernel Driver No Disabled Stopped OK
Normal No No
i8042prt i8042 Keyboard and PS/2 Mouse Port Driver
c:\windows\system32\drivers\i8042prt.sys Kernel Driver Yes
System Running OK Normal No Yes
imapi CD-Burning Filter Driver c:\windows\system32\drivers\imapi.sys
Kernel Driver No System Stopped OK Normal No No
intelide IntelIde Not Available Kernel Driver No Disabled
Stopped OK Normal No No
ipfilterdriver IP Traffic Filter Driver
c:\windows\system32\drivers\ipfltdrv.sys Kernel Driver No
Manual Stopped OK Normal No No
ipinip IP in IP Tunnel Driver
c:\windows\system32\drivers\ipinip.sys Kernel Driver No
Manual Stopped OK Normal No No
ipnat IP Network Address Translator
c:\windows\system32\drivers\ipnat.sys Kernel Driver No
Manual Stopped OK Normal No No
ipsec IPSEC driver c:\windows\system32\drivers\ipsec.sys Kernel
Driver Yes System Running OK Normal No Yes
ipsraidn ipsraidn Not Available Kernel Driver No Disabled
Stopped OK Normal No No
isapnp PnP ISA/EISA Bus Driver
c:\windows\system32\drivers\isapnp.sys Kernel Driver Yes Boot
Running OK Critical No Yes
kbdclass Keyboard Class Driver
c:\windows\system32\drivers\kbdclass.sys Kernel Driver Yes
System Running OK Normal No Yes
ksecdd KSecDD c:\windows\system32\drivers\ksecdd.sys Kernel
Driver Yes Boot Running OK Normal No Yes
lp6nds35 lp6nds35 Not Available Kernel Driver No Disabled
Stopped OK Normal No No
macdisk macdisk c:\windows\system32\drivers\mac2w2k.sys Kernel
Driver Yes Boot Running OK Normal No Yes
mnmdd mnmdd c:\windows\system32\drivers\mnmdd.sys Kernel Driver Yes
System Running OK Ignore No Yes
modem Modem c:\windows\system32\drivers\modem.sys Kernel Driver No
Manual Stopped OK Ignore No No
mouclass Mouse Class Driver c:\windows\system32\drivers\mouclass.sys
Kernel Driver Yes System Running OK Normal No Yes
mountmgr Mount Point Manager c:\windows\system32\drivers\mountmgr.sys
Kernel Driver Yes Boot Running OK Normal No Yes
mraid35x mraid35x Not Available Kernel Driver No Disabled
Stopped OK Normal No No
mrxdav WebDav Client Redirector
c:\windows\system32\drivers\mrxdav.sys File System Driver No
Manual Stopped OK Normal No No
mrxsmb MRXSMB c:\windows\system32\drivers\mrxsmb.sys File
System Driver Yes System Running OK Normal No Yes
msfs Msfs c:\windows\system32\drivers\msfs.sys File System Driver Yes
System Running OK Normal No Yes

```

```

mup Mup c:\windows\system32\drivers\mup.sys File System Driver Yes
  Boot Running OK Normal No Yes
ndis NDIS System Driver c:\windows\system32\drivers\ndis.sys Kernel
Driver Yes Boot Running OK Normal No Yes
ndistapi Remote Access NDIS TAPI Driver
  c:\windows\system32\drivers\ndistapi.sys Kernel Driver Yes
  Manual Running OK Normal No Yes
ndisuio NDIS Usermode I/O Protocol
  c:\windows\system32\drivers\ndisuio.sys Kernel Driver No
  Manual Stopped OK Normal No No
ndiswan Remote Access NDIS WAN Driver
  c:\windows\system32\drivers\ndiswan.sys Kernel Driver Yes
  Manual Running OK Normal No Yes
ndproxy NDIS Proxy c:\windows\system32\drivers\ndproxy.sys Kernel
Driver Yes Manual Running OK Normal No Yes
netbios NetBIOS Interface c:\windows\system32\drivers\netbios.sys
File System Driver Yes System Running OK Normal No
Yes
netbt NetBios over Tcpip c:\windows\system32\drivers\netbt.sys
Kernel Driver Yes System Running OK Normal No Yes
nfrd960 nfrd960 Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
nmescfg NIC Management Service Configuration Driver
  \??\c:\windows\system32\drivers\nmescfg.sys Kernel Driver No
  Manual Stopped OK Normal No No
npfs Npfs c:\windows\system32\drivers\npfs.sys File System Driver Yes
System Running OK Normal No Yes
ntfs Ntfs c:\windows\system32\drivers\ntfs.sys File System Driver Yes
Disabled Running OK Normal No Yes
null Null c:\windows\system32\drivers\null.sys Kernel Driver Yes
System Running OK Normal No Yes
parport Parallel port driver c:\windows\system32\drivers\parport.sys
Kernel Driver No Manual Stopped OK Normal No No
partmgr Partition Manager c:\windows\system32\drivers\partmgr.sys
Kernel Driver Yes Boot Running OK Normal No Yes
parvdm ParVdm c:\windows\system32\drivers\parvdm.sys Kernel
Driver No Auto Stopped OK Ignore No No
pci PCI Bus Driver c:\windows\system32\drivers\pci.sys Kernel Driver
Yes Boot Running OK Critical No Yes
pciide PCIIde c:\windows\system32\drivers\pciide.sys Kernel
Driver Yes Boot Running OK Normal No Yes
pcmcia Pcmcia c:\windows\system32\drivers\pcmcia.sys Kernel
Driver No Disabled Stopped OK Normal No No
pdcomp PDCOMP Not Available Kernel Driver No Manual
  Stopped OK Ignore No No
pdframe PDFRAME Not Available Kernel Driver No Manual
  Stopped OK Ignore No No
pdreli PDRELI Not Available Kernel Driver No Manual
  Stopped OK Ignore No No
pdrframe PDRFRAME Not Available Kernel Driver No Manual
  Stopped OK Ignore No No
perc2perc2 Not Available Kernel Driver No Disabled Stopped OK
Normal No No
perc2hib perc2hib Not Available Kernel Driver No Disabled
  Stopped OK Normal No No

```

```

pptpminiport WAN Miniport (PPTP)
  c:\windows\system32\drivers\rasppptp.sys Kernel Driver Yes
  Manual Running OK Normal No Yes
processor Processor Driver c:\windows\system32\drivers\processr.sys
Kernel Driver Yes Manual Running OK Normal No Yes
ptilink Direct Parallel Link Driver
  c:\windows\system32\drivers\ptilink.sys Kernel Driver Yes
  Manual Running OK Normal No Yes
ql1080 ql1080 Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
ql10wnt Ql10wnt Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
ql12160 ql12160 Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
ql1240 ql1240 Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
ql1280 ql1280 Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
ql2100 ql2100 Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
ql2200 ql2200 Not Available Kernel Driver No Disabled
  Stopped OK Normal No No
ql2300 ql2300 c:\windows\system32\drivers\ql2300.sys Kernel
Driver Yes Boot Running OK Normal No Yes
qlvika qlvika c:\windows\system32\drivers\qlvika.sys Kernel
Driver Yes Auto Running OK Normal No Yes
rasacd Remote Access Auto Connection Driver
  c:\windows\system32\drivers\rasacd.sys Kernel Driver Yes
  System Running OK Normal No Yes
rasl2tp WAN Miniport (L2TP) c:\windows\system32\drivers\rasl2tp.sys
Kernel Driver Yes Manual Running OK Normal No Yes
raspppoe Remote Access PPPOE Driver
  c:\windows\system32\drivers\raspppoe.sys Kernel Driver Yes
  Manual Running OK Normal No Yes
raspti Direct Parallel c:\windows\system32\drivers\raspti.sys
Kernel Driver Yes Manual Running OK Normal No Yes
rdbss Rdbss c:\windows\system32\drivers\rdbss.sys File System Driver
Yes System Running OK Normal No Yes
rdpcdd RDPcDD c:\windows\system32\drivers\rdpcdd.sys Kernel
Driver Yes System Running OK Ignore No Yes
rdpdr Terminal Server Device Redirector Driver
  c:\windows\system32\drivers\rdpdr.sys Kernel Driver Yes
  Manual Running OK Normal No Yes
rdpwd RDPWD c:\windows\system32\drivers\rdpwd.sys Kernel Driver No
  Manual Stopped OK Ignore No No
redbook Digital CD Audio Playback Filter Driver
  c:\windows\system32\drivers\redbook.sys Kernel Driver Yes
  System Running OK Normal No Yes
s3savage4 S3SAVAGE4 c:\windows\system32\drivers\s3gsav4m.sys Kernel
Driver No Manual Stopped OK Ignore No No
sccoper Copernicus Management Controllers
  c:\windows\system32\drivers\sccoper.sys Kernel Driver No
  Manual Stopped OK Normal No No
secdrv Secdrv c:\windows\system32\drivers\secdrv.sys Kernel
Driver No Manual Stopped OK Normal No No

```

```

serenum Serenum Filter Driver
c:\windows\system32\drivers\serenum.sys Kernel Driver No
Manual Stopped OK Normal No No
serial Serial port driver c:\windows\system32\drivers\serial.sys
Kernel Driver No System Stopped OK Ignore No No
sfloppy Sfloppy c:\windows\system32\drivers\sfloppy.sys Kernel
Driver No System Stopped OK Ignore No No
simbad Simbad Not Available Kernel Driver No Disabled
Stopped OK Normal No No
sparrow Sparrow Not Available Kernel Driver No Disabled
Stopped OK Normal No No
srv Srv c:\windows\system32\drivers\srv.sys File System Driver Yes
Manual Running OK Normal No Yes
swenum Software Bus Driver c:\windows\system32\drivers\swenum.sys
Kernel Driver Yes Manual Running OK Normal No Yes
symc810 symc810 Not Available Kernel Driver No Disabled
Stopped OK Normal No No
symc8xx symc8xx Not Available Kernel Driver No Disabled
Stopped OK Normal No No
symmpi symmpi Not Available Kernel Driver No Disabled
Stopped OK Normal No No
sym_hi sym_hi Not Available Kernel Driver No Disabled
Stopped OK Normal No No
sym_u3 sym_u3 Not Available Kernel Driver No Disabled
Stopped OK Normal No No
tcip TCP/IP Protocol Driver c:\windows\system32\drivers\tcip.sys
Kernel Driver Yes System Running OK Normal No Yes
tdpipe TDPIPE c:\windows\system32\drivers\tdpipe.sys Kernel
Driver No Manual Stopped OK Ignore No No
tdtcp TDCPC c:\windows\system32\drivers\tdtcp.sys Kernel Driver No
Manual Stopped OK Ignore No No
termdd Terminal Device Driver
c:\windows\system32\drivers\termdd.sys Kernel Driver Yes
System Running OK Normal No Yes
toside TosIde Not Available Kernel Driver No Disabled
Stopped OK Normal No No
udfs Udfs c:\windows\system32\drivers\udfs.sys File System Driver No
Disabled Stopped OK Normal No No
ultraultra Not Available Kernel Driver No Disabled Stopped OK
Normal No No
update Microcode Update Driver
c:\windows\system32\drivers\update.sys Kernel Driver Yes
Manual Running OK Normal No Yes
usbhub USB2 Enabled Hub c:\windows\system32\drivers\usbhub.sys
Kernel Driver No Manual Stopped OK Normal No No
usbohci Microsoft USB Open Host Controller Miniport Driver
c:\windows\system32\drivers\usbohci.sys Kernel Driver No
Manual Stopped OK Normal No No
usbuhci Microsoft USB Universal Host Controller Miniport Driver
c:\windows\system32\drivers\usbuhci.sys Kernel Driver No
Manual Stopped OK Normal No No
vgasave VGA Display Controller. c:\windows\system32\drivers\vga.sys
Kernel Driver Yes System Running OK Ignore No Yes
viaide ViaIde c:\windows\system32\drivers\viaide.sys Kernel
Driver Yes Boot Running OK Normal No Yes

```

```

volsnap VolSnap c:\windows\system32\drivers\volsnap.sys Kernel
Driver Yes Boot Running OK Normal No Yes
wanarp Remote Access IP ARP Driver
c:\windows\system32\drivers\wanarp.sys Kernel Driver Yes
Manual Running OK Normal No Yes
wdica WDICANot Available Kernel Driver No Manual Stopped OK
Ignore No No
wlbs Network Load Balancing c:\windows\system32\drivers\wlbs.sys
Kernel Driver No Manual Stopped OK Normal No No

```

[Signed Drivers]

```

Device Name Signed Device Class Driver Version Driver Date
Manufacturer INF Name Driver Name Device ID
Not Available Not Available Not Available Not Available Not
Available Not Available Not Available Not Available HTREE\ROOT\0
ACPI Multiprocessor PC No COMPUTER 5.2.3663.0 7/15/2002 (Standard
computers) hal.inf Not Available ROOT\ACPI_HAL\0000
Microsoft ACPI-Compliant System No SYSTEM 5.2.3663.0 7/15/2002
Microsoft acpi.inf Not Available ACPI_HAL\PNP0C08\0
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\0
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\1
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\2
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\3
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\4
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\5
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\6
Processor No PROCESSOR 5.2.3663.0 7/15/2002 (Standard processor types)
cpu.inf Not Available ACPI\GENUINEINTEL_-
_X86_FAMILY_15_MODEL_2\7
PCI bus No SYSTEM 5.2.3663.0 7/15/2002 (Standard system devices)
machine.inf Not Available ACPI\PNP0A03\40
ServerWorks Grand Champion - NorthBridge High End No SYSTEM
5.2.3663.0 7/15/2002 ServerWorks (RCC) machine.inf Not
Available PCI\VEN_1166&DEV_0011&SUBSYS_00000000&REV_22\3&291BF6FF&0&00
ServerWorks Grand Champion - NorthBridge High End No SYSTEM
5.2.3663.0 7/15/2002 ServerWorks (RCC) machine.inf Not
Available PCI\VEN_1166&DEV_0011&SUBSYS_00000000&REV_00\3&291BF6FF&0&01
ServerWorks Grand Champion - NorthBridge High End No SYSTEM
5.2.3663.0 7/15/2002 ServerWorks (RCC) machine.inf Not
Available PCI\VEN_1166&DEV_0011&SUBSYS_00000000&REV_00\3&291BF6FF&0&02

```

ServerWorks Grand Champion - NorthBridge High End No SYSTEM  
5.2.3663.0 7/15/2002 ServerWorks (RCC) machine.inf Not  
Available PCI\VEN\_1166&DEV\_0011&SUBSYS\_00000000&REV\_00\3&291BF6FF&0&03  
FSC Remote Service Controller, mailbox device No MANAGEMENT 3.13.0.0  
9/21/2001 Fujitsu Siemens Computers oem7.inf Not Available  
PCI\VEN\_110A&DEV\_007B&SUBSYS\_008F110A&REV\_00\3&291BF6FF&0&20  
FSC Remote Service Controller, shared memory device No MANAGEMENT  
3.13.0.0 9/21/2001 Fujitsu Siemens Computers oem7.inf Not  
Available PCI\VEN\_110A&DEV\_007C&SUBSYS\_008F110A&REV\_00\3&291BF6FF&0&21  
FSC Remote Service Controller, SMIC device No MANAGEMENT 3.13.0.0  
9/21/2001 Fujitsu Siemens Computers oem7.inf Not Available  
PCI\VEN\_110A&DEV\_007D&SUBSYS\_008F110A&REV\_00\3&291BF6FF&0&22  
RAGE XL PCI (Microsoft Corporation) No DISPLAY 5.10.2600.6009  
7/2/2001 ATI Technologies Inc. atiixpad.inf Not Available  
PCI\VEN\_1002&DEV\_4752&SUBSYS\_0083110A&REV\_27\3&291BF6FF&0&28  
Default Monitor No MONITOR 5.1.2001.0 6/6/2001 (Standard monitor  
types) monitor.inf Not Available  
DISPLAY\DEFAULT\_MONITOR\4&121B755&0&80000000&00&05  
PCI standard host CPU bridge No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0201&SUBSYS\_00000000&REV\_93\3&291BF6FF&0&78  
Standard 101/102-Key or Microsoft Natural PS/2 Keyboard No KEYBOARD  
5.2.3663.0 7/15/2002 (Standard keyboards) keyboard.inf Not  
Available ACPI\PNP0303\4&2647A8AF&0  
Direct memory access controller No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
ACPI\PNP0200\4&2647A8AF&0  
System CMOS/real time clock No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
ACPI\PNP0B00\4&2647A8AF&0  
Programmable interrupt controller No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
ACPI\PNP0000\4&2647A8AF&0  
Numeric data processor No SYSTEM 5.2.3663.0 7/15/2002 (Standard  
system devices) machine.inf Not Available ACPI\PNP0C04\4&2647A8AF&0  
System timer No SYSTEM 5.2.3663.0 7/15/2002 (Standard system  
devices) machine.inf Not Available ACPI\PNP0100\4&2647A8AF&0  
System speaker No SYSTEM 5.2.3663.0 7/15/2002 (Standard system  
devices) machine.inf Not Available ACPI\PNP0800\4&2647A8AF&0  
PS/2 Compatible Mouse No MOUSE 5.2.3663.0 7/15/2002 Microsoft  
msmouse.inf Not Available ACPI\PNP0F13\4&2647A8AF&0  
Motherboard resources No SYSTEM 5.2.3663.0 7/15/2002 (Standard  
system devices) machine.inf Not Available ACPI\PNP0C02\51  
Communications Port No PORTS 5.2.3663.0 7/15/2002 (Standard port types)  
msports.inf Not Available ACPI\PNP0501\1  
Communications Port No PORTS 5.2.3663.0 7/15/2002 (Standard port types)  
msports.inf Not Available ACPI\PNP0501\2  
ECP Printer Port No PORTS 5.2.3663.0 7/15/2002 (Standard port types)  
msports.inf Not Available ACPI\PNP0401\4&2647A8AF&0  
Standard floppy disk controller No FDC 5.2.3663.0 7/15/2002 (Standard  
floppy disk controllers) fdc.inf Not Available  
ACPI\PNP0700\4&2647A8AF&0  
Floppy disk drive No FLOPPYDISK 5.2.3663.0 7/15/2002 (Standard  
floppy disk drives) flpydisk.inf Not Available  
FDC\GENERIC\_FLOPPY\_DRIVE\5&2045E8EE&0&0

Standard Dual Channel PCI IDE Controller No HDC 5.2.3663.0 7/15/2002  
(Standard IDE ATA/ATAPI controllers) mshdc.inf Not Available  
PCI\VEN\_1166&DEV\_0212&SUBSYS\_02121166&REV\_93\3&291BF6FF&0&79  
Primary IDE Channel No HDC 5.2.3663.0 7/15/2002 (Standard IDE  
ATA/ATAPI controllers) mshdc.inf Not Available  
PCIIDE\IDECHANNEL\4&15AF076&0&0  
Secondary IDE Channel No HDC 5.2.3663.0 7/15/2002 (Standard IDE  
ATA/ATAPI controllers) mshdc.inf Not Available  
PCIIDE\IDECHANNEL\4&15AF076&0&1  
CD-ROM Drive No CDROM 5.2.3663.0 7/15/2002 (Standard CD-ROM drives)  
cdrom.inf Not Available IDE\CDROMMITSUMI\_CD-  
ROM\_SR243T\_\_\_\_\_L02G\_\_\_\_\_\5&1159A16&0&0.0.0  
ServerWorks (RCC) PCI to USB Open Host Controller No USB 5.2.3663.0  
7/15/2002 ServerWorks (RCC) usbport.inf Not Available  
PCI\VEN\_1166&DEV\_0220&SUBSYS\_02201166&REV\_05\3&291BF6FF&0&7A  
PCI standard ISA bridge No SYSTEM 5.2.3663.0 7/15/2002 (Standard  
system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0225&SUBSYS\_00000000&REV\_00\3&291BF6FF&0&7B  
ISAPNP Read Data Port No SYSTEM 5.2.3663.0 7/15/2002 (Standard  
system devices) machine.inf Not Available ISAPNP\READDATAPORT\0  
PCI standard host CPU bridge No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0010&SUBSYS\_00000000&REV\_03\3&291BF6FF&0&80  
PCI standard host CPU bridge No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0010&SUBSYS\_00000000&REV\_03\3&291BF6FF&0&82  
PCI standard host CPU bridge No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0010&SUBSYS\_00000000&REV\_03\3&291BF6FF&0&88  
PCI standard host CPU bridge No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0010&SUBSYS\_00000000&REV\_03\3&291BF6FF&0&8A  
PCI standard host CPU bridge No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0010&SUBSYS\_00000000&REV\_03\3&291BF6FF&0&90  
PCI standard host CPU bridge No SYSTEM 5.2.3663.0 7/15/2002  
(Standard system devices) machine.inf Not Available  
PCI\VEN\_1166&DEV\_0010&SUBSYS\_00000000&REV\_03\3&291BF6FF&0&92  
PCI bus No SYSTEM 5.2.3663.0 7/15/2002 (Standard system devices)  
machine.inf Not Available ACPI\PNP0A03\41  
DEC 21154 PCI to PCI bridge No SYSTEM 5.2.3663.0 7/15/2002 DEC  
machine.inf Not Available  
PCI\VEN\_1011&DEV\_0026&SUBSYS\_00000000&REV\_05\3&3ADD9D&0&30  
Mylex eXtremeRAID 2000 Disk Array Controller No SCSIADAPTER  
9.0.4.0 9/8/2000 Mylexoem2.inf Not Available  
PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2254B0D&0&4030  
Mylex Accelerated Driver No DISKDRIVE Not Available 9/8/2000 Mylex  
oem3.inf Not Available  
SCSI\DISK&VEN\_MYLEX&PROD\_EXTREMERAIID\_2000&REV\_0701\5&2EB0A3BB&0&400  
Mylex GAM Device No SYSTEM 5.2.3663.0 7/15/2002 Mylex  
scsidedv.inf Not Available  
SCSI\PROCESSOR&VEN\_MYLEX&PROD\_GAM\_DEVICE&REV\_5\5&2EB0A3BB&0&660  
DEC 21154 PCI to PCI bridge No SYSTEM 5.2.3663.0 7/15/2002 DEC  
machine.inf Not Available  
PCI\VEN\_1011&DEV\_0026&SUBSYS\_00000000&REV\_05\3&3ADD9D&0&38

Mylex eXtremeRAID 2000 Disk Array Controller No SCSIADAPTER  
 9.0.4.0 9/8/2000 Mylexoem2.inf Not Available  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&1C72A60D&0&4038  
 Qlogic processor device No SYSTEM 5.2.3663.0 7/15/2002 QLOGIC  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_QLOGIC&PROD\_GEM359&REV\_1.07\5&231C90DA&0&080  
 Qlogic processor device No SYSTEM 5.2.3663.0 7/15/2002 QLOGIC  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_QLOGIC&PROD\_GEM359&REV\_1.07\5&231C90DA&0&180  
 Qlogic processor device No SYSTEM 5.2.3663.0 7/15/2002 QLOGIC  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_QLOGIC&PROD\_GEM359&REV\_1.07\5&231C90DA&0&280  
 Qlogic processor device No SYSTEM 5.2.3663.0 7/15/2002 QLOGIC  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_QLOGIC&PROD\_GEM359&REV\_1.07\5&231C90DA&0&380  
 Mylex Accelerated Driver No DISKDRIVE Not Available 9/8/2000 Mylex  
 oem3.inf Not Available  
 SCSI\DISK&VEN\_MYLEX&PROD\_EXTREMERAIID\_2000&REV\_0701\5&231C90DA&0&400  
 Mylex GAM Device No SYSTEM 5.2.3663.0 7/15/2002 Mylex  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_MYLEX&PROD\_GAM\_DEVICE&REV\_\5&231C90DA&0&660  
 PCI bus No SYSTEM 5.2.3663.0 7/15/2002 (Standard system devices)  
 machine.inf Not Available ACPI\PNP0A03\42  
 DEC 21154 PCI to PCI bridge No SYSTEM 5.2.3663.0 7/15/2002 DEC  
 machine.inf Not Available  
 PCI\VEN\_1011&DEV\_0026&SUBSYS\_00000000&REV\_05\3&12F48E42&0&28  
 Mylex eXtremeRAID 2000 Disk Array Controller No SCSIADAPTER  
 9.0.4.0 9/8/2000 Mylexoem2.inf Not Available  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&1ECE4987&0&4028  
 Mylex Accelerated Driver No DISKDRIVE Not Available 9/8/2000 Mylex  
 oem3.inf Not Available  
 SCSI\DISK&VEN\_MYLEX&PROD\_EXTREMERAIID\_2000&REV\_0701\5&F3FB0E4&0&400  
 Mylex GAM Device No SYSTEM 5.2.3663.0 7/15/2002 Mylex  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_MYLEX&PROD\_GAM\_DEVICE&REV\_\5&F3FB0E4&0&660  
 Adaptec AIC-7899 Ultra160 PCI SCSI Card No SCSIADAPTER 5.2.3663.0  
 7/15/2002 Adaptec pnpscsi.inf Not Available  
 PCI\VEN\_9005&DEV\_00CF&SUBSYS\_0083110A&REV\_01\3&12F48E42&0&40  
 Disk drive No DISKDRIVE 5.2.3663.0 7/15/2002 (Standard disk drives)  
 disk.inf Not Available  
 SCSI\DISK&VEN\_SEAGATE&PROD\_ST318452LC&REV\_8500\4&2477DA67&0&000  
 HP SAF-TE SCSI Processor Device No SYSTEM 5.2.3663.0 7/15/2002 HP  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_SDR&PROD\_GEM318&REV\_0\4&2477DA67&0&080  
 Adaptec AIC-7899 Ultra160 PCI SCSI Card No SCSIADAPTER 5.2.3663.0  
 7/15/2002 Adaptec pnpscsi.inf Not Available  
 PCI\VEN\_9005&DEV\_00CF&SUBSYS\_0083110A&REV\_01\3&12F48E42&0&41  
 HP SAF-TE SCSI Processor Device No SYSTEM 5.2.3663.0 7/15/2002 HP  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_SDR&PROD\_GEM318&REV\_0\4&37318B0C&0&080  
 PCI bus No SYSTEM 5.2.3663.0 7/15/2002 (Standard system devices)  
 machine.inf Not Available ACPI\PNP0A03\43  
 DEC 21154 PCI to PCI bridge No SYSTEM 5.2.3663.0 7/15/2002 DEC  
 machine.inf Not Available  
 PCI\VEN\_1011&DEV\_0026&SUBSYS\_00000000&REV\_05\3&25AE3EE7&0&20

Mylex eXtremeRAID 2000 Disk Array Controller No SCSIADAPTER  
 9.0.4.0 9/8/2000 Mylexoem2.inf Not Available  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2F92D4B0&0&4020  
 Mylex Accelerated Driver No DISKDRIVE Not Available 9/8/2000 Mylex  
 oem3.inf Not Available  
 SCSI\DISK&VEN\_MYLEX&PROD\_EXTREMERAIID\_2000&REV\_0701\5&6CEC074&0&400  
 Mylex GAM Device No SYSTEM 5.2.3663.0 7/15/2002 Mylex  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_MYLEX&PROD\_GAM\_DEVICE&REV\_\5&6CEC074&0&660  
 PCI bus No SYSTEM 5.2.3663.0 7/15/2002 (Standard system devices)  
 machine.inf Not Available ACPI\PNP0A03\44  
 DEC 21154 PCI to PCI bridge No SYSTEM 5.2.3663.0 7/15/2002 DEC  
 machine.inf Not Available  
 PCI\VEN\_1011&DEV\_0026&SUBSYS\_00000000&REV\_05\3&3867EF8C&0&18  
 Mylex eXtremeRAID 2000 Disk Array Controller No SCSIADAPTER  
 9.0.4.0 9/8/2000 Mylexoem2.inf Not Available  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2DF34B01&0&4018  
 Mylex Accelerated Driver No DISKDRIVE Not Available 9/8/2000 Mylex  
 oem3.inf Not Available  
 SCSI\DISK&VEN\_MYLEX&PROD\_EXTREMERAIID\_2000&REV\_0701\5&27A1714F&0&400  
 Mylex GAM Device No SYSTEM 5.2.3663.0 7/15/2002 Mylex  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_MYLEX&PROD\_GAM\_DEVICE&REV\_\5&27A1714F&0&660  
 PCI bus No SYSTEM 5.2.3663.0 7/15/2002 (Standard system devices)  
 machine.inf Not Available ACPI\PNP0A03\45  
 DEC 21154 PCI to PCI bridge No SYSTEM 5.2.3663.0 7/15/2002 DEC  
 machine.inf Not Available  
 PCI\VEN\_1011&DEV\_0026&SUBSYS\_00000000&REV\_05\3&20E01BA&0&10  
 Mylex eXtremeRAID 2000 Disk Array Controller No SCSIADAPTER  
 9.0.4.0 9/8/2000 Mylexoem2.inf Not Available  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&2BEE4042&0&4010  
 Mylex Accelerated Driver No DISKDRIVE Not Available 9/8/2000 Mylex  
 oem3.inf Not Available  
 SCSI\DISK&VEN\_MYLEX&PROD\_EXTREMERAIID\_2000&REV\_0701\5&944483E&0&400  
 Mylex GAM Device No SYSTEM 5.2.3663.0 7/15/2002 Mylex  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_MYLEX&PROD\_GAM\_DEVICE&REV\_\5&944483E&0&660  
 PCI bus No SYSTEM 5.2.3663.0 7/15/2002 (Standard system devices)  
 machine.inf Not Available ACPI\PNP0A03\46  
 QLogic QLA23xx PCI Fibre Channel Adapter No SCSIADAPTER 8.2.0.0  
 8/5/2002 QLogic oem6.inf Not Available  
 PCI\VEN\_1077&DEV\_2312&SUBSYS\_010C1077&REV\_02\3&2AEF1B1C&0&20  
 Disk drive No DISKDRIVE 5.2.3663.0 7/15/2002 (Standard disk drives)  
 disk.inf Not Available  
 SCSI\DISK&VEN\_QLOGIC&PROD\_PSEUDO\_LUN&REV\_\4&AC124D8&0&07F0  
 DEC 21154 PCI to PCI bridge No SYSTEM 5.2.3663.0 7/15/2002 DEC  
 machine.inf Not Available  
 PCI\VEN\_1011&DEV\_0026&SUBSYS\_00000000&REV\_05\3&2AEF1B1C&0&28  
 Mylex eXtremeRAID 2000 Disk Array Controller No SCSIADAPTER  
 9.0.4.0 9/8/2000 Mylexoem2.inf Not Available  
 PCI\VEN\_1069&DEV\_BA56&SUBSYS\_00401069&REV\_00\4&3AE9BCCD&0&4028  
 Qlogic processor device No SYSTEM 5.2.3663.0 7/15/2002 QLOGIC  
 scsidev.inf Not Available  
 SCSI\PROCESSOR&VEN\_QLOGIC&PROD\_GEM359&REV\_1.06\5&23372C65&0&080

Qlogic processor device No SYSTEM 5.2.3663.0 7/15/2002 QLOGIC  
scsidev.inf Not Available  
SCSI\PROCESSOR&VEN\_QLOGIC&PROD\_GEM359&REV\_1.06\5&23372C65&0&180  
Mylex Accelerated Driver No DISKDRIVE Not Available 9/8/2000 Mylex  
oem3.inf Not Available  
SCSI\DISK&VEN\_MYLEX&PROD\_EXTREMER RAID\_2000&REV\_0701\5&23372C65&0&400  
Mylex GAM Device No SYSTEM 5.2.3663.0 7/15/2002 Mylex  
scsidev.inf Not Available  
SCSI\PROCESSOR&VEN\_MYLEX&PROD\_GAM\_DEVICE&REV\_\5&23372C65&0&660  
Intel 8255x-based PCI Ethernet Adapter (10/100) No NET 6.3.3.0  
7/15/2002 Intelnet557.inf Not Available  
PCI\VEN\_8086&DEV\_1229&SUBSYS\_0083110A&REV\_09\3&2AEF1B1C&0&48  
ACPI Fixed Feature Button No SYSTEM 5.2.3663.0 7/15/2002 (Standard  
system devices) machine.inf Not Available  
ACPI\FIXEDBUTTON\2&DABA3FF&0  
Logical Disk Manager No SYSTEM 5.2.3663.0 7/15/2002 (Standard  
system devices) machine.inf Not Available ROOT\DMIO\0000  
Volume Manager No SYSTEM 5.2.3663.0 7/15/2002 (Standard system  
devices) machine.inf Not Available ROOT\FTDISK\0000  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8024OFFSET7E0000LENGTHCD157  
4C00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8024OFFSETCD1D5CA00LENGTH73  
3E26400  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8024OFFSET23668C6800LENGTH4  
93E2DCC00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8025OFFSET7E0000LENGTHCD157  
4C00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8025OFFSETCD1D5CA00LENGTH73  
3E26400  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8025OFFSET23668C6800LENGTH4  
93E2DCC00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8020OFFSET7E0000LENGTHCD157  
4C00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8020OFFSETCD1D5CA00LENGTH73  
3E26400  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8020OFFSET2367876C00LENGTH4  
93E2DCC00

Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE72A272A2OFFSET7E00LENGTH445C770  
00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8021OFFSET7E0000LENGTHCD157  
4C00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8021OFFSETCDD1D5CA00LENGTH73  
3E26400  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8021OFFSET23668C6800LENGTH4  
93E2DCC00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8023OFFSET7E0000LENGTHCD157  
4C00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8023OFFSETCDD1D5CA00LENGTH73  
3E26400  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8023OFFSET23668C6800LENGTH4  
93E2DCC00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8022OFFSET7E0000LENGTHCD157  
4C00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8022OFFSETCDD1D5CA00LENGTH73  
3E26400  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE18FA8022OFFSET23668C6800LENGTH4  
93E2DCC00  
Generic volume No VOLUME 5.2.3663.0 7/15/2002 Microsoft volume.inf  
Not Available  
STORAGE\VOLUME\1&30A96598&0&SIGNATURE2753D81EOFFSET7E0000LENGTH1D4C1  
20600  
AFD Networking Support Environment Not Available LEGACYDRIVER Not  
Available Not Available Not Available Not Available  
ROOT\LEGACY\_AFD\0000  
Beep Not Available LEGACYDRIVER Not Available Not Available Not  
Available Not Available Not Available ROOT\LEGACY\_BEEP\0000  
CRC Disk Filter Driver Not Available LEGACYDRIVER Not Available  
Not Available Not Available Not Available Not Available  
ROOT\LEGACY\_CRCDISK\0000  
dmbboot Not Available LEGACYDRIVER Not Available Not Available  
Not Available Not Available Not Available  
ROOT\LEGACY\_DMBOOT\0000

```

dmload      Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_DMLOAD\0000
DsPciCfg    Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_DSPICCFG\0000
Fips        Not Available  LEGACYDRIVER  Not Available  Not Available  Not
Available  Not Available  Not Available  ROOT\LEGACY_FIPS\0000
Generic Packet Classifier Not Available  LEGACYDRIVER  Not Available
             Not Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_GPC\0000
IPSEC driver Not Available  LEGACYDRIVER  Not Available  Not
Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_IPSEC\0000
ksecdd      Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_KSECDD\0000
macdisk     Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_MACDISK\0000
mnmdd      Not Available  LEGACYDRIVER  Not Available  Not Available  Not
Available  Not Available  Not Available  ROOT\LEGACY_MNMDD\0000
mountmgr    Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_MOUNTMGR\0000
NDIS System Driver  Not Available  LEGACYDRIVER  Not Available  Not
Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_NDIS\0000
Remote Access NDIS TAPI Driver Not Available  LEGACYDRIVER  Not
Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_NDISTAPI\0000
NDIS Usermode I/O Protocol Not Available  LEGACYDRIVER  Not Available
             Not Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_NDISUIO\0000
NDProxy     Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_NDPROXY\0000
NetBios over Tcpi Not Available  LEGACYDRIVER  Not Available  Not
Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_NETBT\0000
NIC Management Service Configuration Driver  Not Available
             LEGACYDRIVER  Not Available  Not Available  Not Available  Not
Available  Not Available  ROOT\LEGACY_NMCFG\0000
Null        Not Available  LEGACYDRIVER  Not Available  Not Available  Not
Available  Not Available  Not Available  ROOT\LEGACY_NULL\0000
Partition Manager  Not Available  LEGACYDRIVER  Not Available  Not
Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_PARTMGR\0000
ParVdm      Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_PARVDM\0000
Remote Access Auto Connection Driver Not Available  LEGACYDRIVER  Not
Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_RASACD\0000

```

```

RDPCDD      Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_RDPCDD\0000
TCP/IP Protocol Driver  Not Available  LEGACYDRIVER  Not Available
             Not Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_TCPIP\0000
VGA Display Controller.  Not Available  LEGACYDRIVER  Not Available
             Not Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_VGASAVE\0000
ViaIde      Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_VIAIDE\0000
volsnap     Not Available  LEGACYDRIVER  Not Available  Not Available
             Not Available  Not Available  Not Available
             ROOT\LEGACY_VOLSNAP\0000
Remote Access IP ARP Driver  Not Available  LEGACYDRIVER  Not
Available  Not Available  Not Available  Not Available
             ROOT\LEGACY_WANARP\0000
Audio Codecs  No  MEDIA5.2.3663.0 7/15/2002 (Standard system devices)
             wave.inf  Not Available  ROOT\MEDIA\MS_MMACM
Legacy Audio Drivers No  MEDIA5.2.3663.0 7/15/2002 (Standard system
             devices) wave.inf  Not Available  ROOT\MEDIA\MS_MMDRV
Media Control Devices  No  MEDIA5.2.3663.0 7/15/2002 (Standard
             system devices) wave.inf  Not Available  ROOT\MEDIA\MS_MMMCI
Legacy Video Capture Devices  No  MEDIA5.2.3663.0 7/15/2002 (Standard
             system devices) wave.inf  Not Available  ROOT\MEDIA\MS_MMVCD
Video Codecs  No  MEDIA5.2.3663.0 7/15/2002 (Standard system devices)
             wave.inf  Not Available  ROOT\MEDIA\MS_MMVID
WAN Miniport (L2TP) No  NET  5.2.3663.0 7/15/2002 Microsoft
             netrasa.inf  Not Available  ROOT\MS_L2TPMINIPOINT\0000
WAN Miniport (IP) No  NET  5.2.3663.0 7/15/2002 Microsoft
             netrasa.inf  Not Available  ROOT\MS_NDISWANIP\0000
WAN Miniport (PPPOE) No  NET  5.2.3663.0 7/15/2002 Microsoft
             netrasa.inf  Not Available  ROOT\MS_PPPOEMINIPOINT\0000
WAN Miniport (PPTP) No  NET  5.2.3663.0 7/15/2002 Microsoft
             netrasa.inf  Not Available  ROOT\MS_PPTPMINIPOINT\0000
Direct Parallel No  NET  5.2.3663.0 7/15/2002 Microsoft netrasa.inf
             Not Available  ROOT\MS_PTMINIPOINT\0000
Terminal Server Device Redirector  No  SYSTEM  5.2.3663.0 7/15/2002
             (Standard system devices) machine.inf  Not Available
             ROOT\RDPPDR\0000
Terminal Server Keyboard Driver No  SYSTEM  5.2.3663.0 7/15/2002
             (Standard system devices) machine.inf  Not Available
             ROOT\RDP_KBD\0000
Terminal Server Mouse Driver  No  SYSTEM  5.2.3663.0 7/15/2002
             (Standard system devices) machine.inf  Not Available
             ROOT\RDP_MOU\0000
QLogic VI Kernel Agent driver  No  SCSIADAPTER  Not Available  Not
Available  Not Available  oem1.inf  Not Available  ROOT\SCSIADAPTER\0000
Plug and Play Software Device Enumerator  No  SYSTEM  5.2.3663.0
             7/15/2002 (Standard system devices) machine.inf  Not Available
             ROOT\SYSTEM\0000
Microcode Update Device  No  SYSTEM  5.2.3663.0 7/15/2002 (Standard
             system devices) machine.inf  Not Available  ROOT\SYSTEM\0001

```

[Environment Variables]

```
Variable Value User Name
ClusterLog C:\WINDOWS\Cluster\cluster.log <SYSTEM>
ComSpec %SystemRoot%\system32\cmd.exe <SYSTEM>
NUMBER_OF_PROCESSORS 8 <SYSTEM>
OS Windows_NT <SYSTEM>
Path
%SystemRoot%\system32;%SystemRoot%;%SystemRoot%\System32\Wbem;C:\Program Files\Microsoft SQL Server\MSSQL\BINN;C:\Program Files\Microsoft SQL Server\80\Tools\BINN <SYSTEM>
PATHEXT .COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS;.JSE;.WSF;.WSH <SYSTEM>
PROCESSOR_ARCHITECTURE x86 <SYSTEM>
PROCESSOR_IDENTIFIER x86 Family 15 Model 2 Stepping 2, GenuineIntel <SYSTEM>
PROCESSOR_LEVEL 15 <SYSTEM>
PROCESSOR_REVISION 0202 <SYSTEM>
TEMP %SystemRoot%\TEMP <SYSTEM>
TMP %SystemRoot%\TEMP <SYSTEM>
windir %SystemRoot% <SYSTEM>
TEMP %USERPROFILE%\Local Settings\Temp NT AUTHORITY\SYSTEM
TMP %USERPROFILE%\Local Settings\Temp NT AUTHORITY\SYSTEM
TEMP %USERPROFILE%\Local Settings\Temp NT AUTHORITY\LOCAL SERVICE
TMP %USERPROFILE%\Local Settings\Temp NT AUTHORITY\LOCAL SERVICE
TEMP %USERPROFILE%\Local Settings\Temp ASTERIX\Administrator
TMP %USERPROFILE%\Local Settings\Temp ASTERIX\Administrator
```

[Print Jobs]

Document	Size	Owner	Notify	Status	Time Submitted	Start Time	Until
Time Elapsed	Time	Pages Printed	Job ID	Priority	Parameters	Driver	Print Processor
Host	Print Queue	Data Type	Name				

[Network Connections]

Local Name	Remote Name	Type	Status	User Name
------------	-------------	------	--------	-----------

[Running Tasks]

Name	Path	Process ID	Priority	Min Working Set	Max Working Set	Start Time
Version	Size	File Date				
system	idle	process	Not Available	0	0	Not Available
Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
system	Not Available	4	8	0	1413120	Not Available
Available	Not Available	Not Available	Not Available	Not Available	Not Available	Not Available
smss.exe	c:\windows\system32\smss.exe	424	11	204800	1413120	
(47,104 bytes)	7/18/2002 10:45 AM	5.2.3663.0 (main.020715-1506)	46.00 KB			
csrss.exe	Not Available	472	13	Not Available	Not Available	
10/24/2002 10:45 AM	Not Available	Not Available	Not Available	Not Available	Not Available	
winlogon.exe	c:\windows\system32\winlogon.exe	496	13	204800	1413120	
10/24/2002 10:45 AM	5.2.3663.0 (main.020715-1506)	512.00 KB (524,288 bytes)	7/18/2002 2:00 PM			
services.exe	c:\windows\system32\services.exe	540	9	204800	1413120	
10/24/2002 10:45 AM	5.2.3663.0 (main.020715-1506)	99.00 KB (101,376 bytes)	7/18/2002 2:00 PM			

```
lsass.exe c:\windows\system32\lsass.exe 552 9 204800 1413120
10/24/2002 10:45 AM 5.2.3663.0 (main.020715-1506) 13.00 KB
(13,312 bytes) 7/18/2002 2:00 PM
svchost.exe c:\windows\system32\svchost.exe 760 8 204800
1413120 10/24/2002 10:45 AM 5.2.3663.0 (main.020715-1506) 12.00
KB (12,288 bytes) 7/18/2002 2:00 PM
svchost.exe Not Available 848 8 Not Available Not Available
10/24/2002 10:45 AM Not Available Not Available Not Available
svchost.exe c:\windows\system32\svchost.exe 884 8 204800
1413120 10/24/2002 10:45 AM 5.2.3663.0 (main.020715-1506) 12.00
KB (12,288 bytes) 7/18/2002 2:00 PM
explorer.exe c:\windows\explorer.exe 1224 8 204800 1413120
10/24/2002 10:46 AM 6.00.3663.0 (main.020715-1506) 989.50 KB
(1,013,248 bytes) 7/18/2002 2:00 PM
svchost.exe c:\windows\system32\svchost.exe 1376 8 204800
1413120 10/24/2002 10:46 AM 5.2.3663.0 (main.020715-1506) 12.00
KB (12,288 bytes) 7/18/2002 2:00 PM
helpctr.exe c:\windows\pchealth\helpctr\binaries\helpctr.exe 1172
8 204800 1413120 10/24/2002 1:54 PM 5.2.3663.0
(main.020715-1506) 670.00 KB (686,080 bytes) 8/20/2002 10:47 AM
helpsvc.exe c:\windows\pchealth\helpctr\binaries\helpsvc.exe 1528
8 204800 1413120 10/24/2002 1:54 PM 5.2.3663.0
(main.020715-1506) 683.50 KB (699,904 bytes) 8/20/2002 10:47 AM
wmiprvse.exe Not Available 1544 8 Not Available Not Available
10/24/2002 1:54 PM Not Available Not Available Not Available
```

[Loaded Modules]

Name	Version	Size	File Date	Manufacturer	Path
smss	5.2.3663.0 (main.020715-1506)	46.00 KB (47,104 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\smss.exe
ntdll	5.2.3663.0 (main.020715-1506)	697.50 KB (714,240 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\ntdll.dll
winlogon	5.2.3663.0 (main.020715-1506)	512.00 KB (524,288 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\winlogon.exe
kernel32	5.2.3663.0 (main.020715-1506)	934.50 KB (956,928 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\kernel32.dll
msvcrt	7.0.3663.0 (main.020715-1506)	319.50 KB (327,168 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\msvcrt.dll
advapi32	5.2.3663.0 (main.020715-1506)	526.00 KB (538,624 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\advapi32.dll
rpcrt4	5.2.3663.0 (main.020715-1506)	544.50 KB (557,568 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\rpcrt4.dll
user32	5.2.3663.0 (main.020715-1506)	547.50 KB (560,640 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\user32.dll
gdi32	5.2.3663.0 (main.020715-1506)	246.00 KB (251,904 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\gdi32.dll
userenv	5.2.3663.0 (main.020715-1506)	710.00 KB (727,040 bytes)	7/18/2002 2:00 PM	Microsoft Corporation	c:\windows\system32\userenv.dll

```

nddeapi 5.2.3663.0 (main.020715-1506) 15.00 KB (15,360 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\nddeapi.dll
crypt32 5.131.3663.0 (main.020715-1506) 545.00 KB (558,080 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\crypt32.dll
msasn1 5.2.3663.0 (main.020715-1506) 51.00 KB (52,224 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\msasn1.dll
secur32 5.2.3663.0 (main.020715-1506) 57.00 KB (58,368 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\secur32.dll
winsta 5.2.3663.0 (main.020715-1506) 48.00 KB (49,152 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\winsta.dll
netapi32 5.2.3663.0 (main.020715-1506) 309.50 KB (316,928 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\netapi32.dll
profmap 5.2.3663.0 (main.020715-1506) 21.00 KB (21,504 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\profmap.dll
regapi 5.2.3663.0 (main.020715-1506) 47.00 KB (48,128 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\regapi.dll
ws2_32 5.2.3663.0 (main.020715-1506) 77.00 KB (78,848 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ws2_32.dll
ws2help 5.2.3663.0 (main.020715-1506) 19.00 KB (19,456 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ws2help.dll
authz 5.2.3663.0 (main.020715-1506) 56.50 KB (57,856 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\authz.dll
psapi 5.2.3663.0 (main.020715-1506) 21.00 KB (21,504 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\psapi.dll
version 5.2.3663.0 (main.020715-1506) 16.50 KB (16,896 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\version.dll
setupapi 5.2.3663.0 (main.020715-1506) 917.50 KB (939,520 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\setupapi.dll
msgina 5.2.3663.0 (main.020715-1506) 1.19 MB (1,252,864 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\msgina.dll
shsvcs 6.00.3663.0 (main.020715-1506) 122.50 KB (125,440 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\shsvcs.dll
shlwapi 6.00.3663.0 (main.020715-1506) 269.00 KB (275,456 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\shlwapi.dll
sfc 5.2.3663.0 (main.020715-1506) 4.50 KB (4,608 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\sfc.dll
sfc_os 5.2.3663.0 (main.020715-1506) 130.00 KB (133,120 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\sfc_os.dll

```

```

wintrust 5.131.3663.0 (main.020715-1506) 155.00 KB (158,720 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\wintrust.dll
ole32 5.2.3663.0 (main.020715-1506) 1.08 MB (1,134,592 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\ole32.dll
imagehlp 5.2.3663.0 (main.020715-1506) 123.00 KB (125,952 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\imagehlp.dll
comctl32 6.0 (main.020715-1506) 905.00 KB (926,720 bytes) 8/20/2002
12:29 PM Microsoft Corporation
c:\windows\winsxs\x86_microsoft.windows.common-
controls_6595b64144ccf1df_6.0.100.0_x-ww_8417450b\comctl32.dll
winscard 5.2.3663.0 (main.020715-1506) 93.50 KB (95,744 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\winscard.dll
wtsapi32 5.2.3663.0 (main.020715-1506) 17.00 KB (17,408 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\wtsapi32.dll
sxs 5.2.3663.0 (main.020715-1506) 685.50 KB (701,952 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\sxs.dll
rsaenh 5.2.3663.0 (main.020715-1506) 174.07 KB (178,248 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rsaenh.dll
wldap32 5.2.3663.0 (main.020715-1506) 167.00 KB (171,008 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\wldap32.dll
shell32 6.00.3663.0 (main.020715-1506) 7.69 MB (8,067,072 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\shell32.dll
csddl 5.2.3663.0 (main.020715-1506) 92.50 KB (94,720 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\csddl.dll
wlnotify 5.2.3663.0 (main.020715-1506) 84.50 KB (86,528 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\wlnotify.dll
winmm 5.2.3663.0 (main.020715-1506) 163.00 KB (166,912 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\winmm.dll
winspool 5.2.3663.0 (main.020715-1506) 131.50 KB (134,656 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\winspool.drv
mpr 5.2.3663.0 (main.020715-1506) 55.00 KB (56,320 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\mpr.dll
comctl32 5.82 (main.020715-1506) 559.50 KB (572,928 bytes) 8/20/2002
12:29 PM Microsoft Corporation
c:\windows\winsxs\x86_microsoft.windows.common-
controls_6595b64144ccf1df_5.82.0.0_x-ww_8a69ba05\comctl32.dll
uxtheme 6.00.3663.0 (main.020715-1506) 190.50 KB (195,072 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\uxtheme.dll
samlib 5.2.3663.0 (main.020715-1506) 40.50 KB (41,472 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\samlib.dll
cscui 5.2.3663.0 (main.020715-1506) 299.00 KB (306,176 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\cscui.dll

```

```

mprapi 5.2.3663.0 (main.020715-1506) 78.00 KB (79,872 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\mprapi.dll
activeds 5.2.3663.0 (main.020715-1506) 184.50 KB (188,928 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\activeds.dll
adsldpc 5.2.3663.0 (main.020715-1506) 139.50 KB (142,848 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\adsldpc.dll
credui 5.2.3663.0 (main.020715-1506) 161.00 KB (164,864 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\credui.dll
atl 3.05.2144 82.00 KB (83,968 bytes) 7/18/2002 2:00 PM Microsoft
Corporation c:\windows\system32\atl.dll
oleaut32 5.2.3663.0 483.50 KB (495,104 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\oleaut32.dll
rtutils 5.2.3663.0 (main.020715-1506) 31.00 KB (31,744 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rtutils.dll
clbcatq 2001.12.4593.0 (main.020715-1506) 465.50 KB (476,672 bytes)
8/20/2002 10:44 AM Microsoft Corporation
c:\windows\system32\clbcatq.dll
comres 2001.12.4593.0 (main.020715-1506) 778.00 KB (796,672 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\comres.dll
ntmarta 5.2.3663.0 (main.020715-1506) 110.50 KB (113,152 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ntmarta.dll
wbemprox 5.2.3663.0 (main.020715-1506) 16.00 KB (16,384 bytes)
8/20/2002 10:44 AM Microsoft Corporation
c:\windows\system32\wbem\wbemprox.dll
wbemcomn 5.2.3663.0 (main.020715-1506) 205.00 KB (209,920 bytes)
8/20/2002 10:44 AM Microsoft Corporation
c:\windows\system32\wbem\wbemcomn.dll
wbemsvc 5.2.3663.0 (main.020715-1506) 42.50 KB (43,520 bytes)
8/20/2002 10:44 AM Microsoft Corporation
c:\windows\system32\wbem\wbemsvc.dll
fastprox 5.2.3663.0 (main.020715-1506) 434.50 KB (444,928 bytes)
8/20/2002 10:43 AM Microsoft Corporation
c:\windows\system32\wbem\fastprox.dll
msvcpc60 6.05.2144.0 388.00 KB (397,312 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\msvcpc60.dll
ntdsapi 5.2.3663.0 (main.020715-1506) 67.00 KB (68,608 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ntdsapi.dll
dnsapi 5.2.3663.0 (main.020715-1506) 141.50 KB (144,896 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\dnsapi.dll
services 5.2.3663.0 (main.020715-1506) 99.00 KB (101,376 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\services.exe
scserv 5.2.3663.0 (main.020715-1506) 301.00 KB (308,224 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\scserv.dll

```

```

umpnpgm 5.2.3663.0 (main.020715-1506) 115.00 KB (117,760 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\umpnpgm.dll
ncobjapi 5.2.3663.0 (main.020715-1506) 33.00 KB (33,792 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ncobjapi.dll
eventlog 5.2.3663.0 (main.020715-1506) 58.50 KB (59,904 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\eventlog.dll
lsass 5.2.3663.0 (main.020715-1506) 13.00 KB (13,312 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\lsass.exe
lsasrv 5.2.3663.0 (main.020715-1506) 711.00 KB (728,064 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\lsasrv.dll
samsrv 5.2.3663.0 (main.020715-1506) 408.00 KB (417,792 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\samsrv.dll
cryptdll 5.2.3663.0 (main.020715-1506) 30.00 KB (30,720 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\cryptdll.dll
msprivs 5.2.3663.0 (main.020715-1506) 44.00 KB (45,056 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\msprivs.dll
kerberos 5.2.3663.0 (main.020715-1506) 299.00 KB (306,176 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\kerberos.dll
msvl_0 5.2.3663.0 (main.020715-1506) 114.50 KB (117,248 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\msvl_0.dll
netlogon 5.2.3663.0 (main.020715-1506) 401.50 KB (411,136 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\netlogon.dll
w32time 5.2.3663.0 (main.020715-1506) 205.50 KB (210,432 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\w32time.dll
iphlpapi 5.2.3663.0 (main.020715-1506) 80.50 KB (82,432 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\iphlpapi.dll
schannel 5.2.3663.0 (main.020715-1506) 138.50 KB (141,824 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\schannel.dll
wdigest 5.2.3663.0 (main.020715-1506) 59.50 KB (60,928 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\wdigest.dll
rassfm 5.2.3663.0 (main.020715-1506) 20.50 KB (20,992 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rassfm.dll
kdcsvc 5.2.3663.0 (main.020715-1506) 190.50 KB (195,072 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\kdcsvc.dll
ntdsa 5.2.3663.0 (main.020715-1506) 1.40 MB (1,465,344 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\ntdsa.dll
ntdsatq 5.2.3663.0 (main.020715-1506) 27.50 KB (28,160 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ntdsatq.dll

```

mswsock 5.2.3663.0 (main.020715-1506) 243.50 KB (249,344 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\mswsock.dll  
 esent 5.2.3663.0 (main.020715-1506) 925.50 KB (947,712 bytes) 7/18/2002  
 2:00 PM Microsoft Corporation c:\windows\system32\esent.dll  
 certcli 5.2.3663.0 (main.020715-1506) 215.00 KB (220,160 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\certcli.dll  
 cryptui 5.131.3663.0 (main.020715-1506) 463.50 KB (474,624 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\cryptui.dll  
 scecli 5.2.3663.0 (main.020715-1506) 174.00 KB (178,176 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\scecli.dll  
 pstorsvc 5.2.3663.0 (main.020715-1506) 24.00 KB (24,576 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\pstorsvc.dll  
 psbase 5.2.3663.0 (main.020715-1506) 81.00 KB (82,944 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\psbase.dll  
 dssenh 5.2.3663.0 (main.020715-1506) 129.07 KB (132,168 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\dssenh.dll  
 svchost 5.2.3663.0 (main.020715-1506) 12.00 KB (12,288 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\svchost.exe  
 rpcss 5.2.3663.0 (main.020715-1506) 266.00 KB (272,384 bytes) 7/18/2002  
 2:00 PM Microsoft Corporation c:\windows\system32\rpcss.dll  
 wshtcpip 5.2.3663.0 (main.020715-1506) 17.00 KB (17,408 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\wshtcpip.dll  
 wkssvc 5.2.3663.0 (main.020715-1506) 122.00 KB (124,928 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\wkssvc.dll  
 es 2001.12.4593.0 (main.020715-1506) 218.00 KB (223,232 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\es.dll  
 srvsvc 5.2.3663.0 (main.020715-1506) 87.50 KB (89,600 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\srvsvc.dll  
 wmisvc 5.2.3663.0 (main.020715-1506) 113.50 KB (116,224 bytes)  
 8/20/2002 10:44 AM Microsoft Corporation  
 c:\windows\system32\wbem\wmisvc.dll  
 vssapi 5.2.3663.0 (main.020715-1506) 471.00 KB (482,304 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\vssapi.dll  
 sens 5.2.3663.0 (main.020715-1506) 35.00 KB (35,840 bytes) 7/18/2002  
 2:00 PM Microsoft Corporation c:\windows\system32\sens.dll  
 netman 5.2.3663.0 (main.020715-1506) 147.00 KB (150,528 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\netman.dll  
 rasapi32 5.2.3663.0 (main.020715-1506) 217.00 KB (222,208 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\rasapi32.dll

rasman 5.2.3663.0 (main.020715-1506) 55.00 KB (56,320 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\rasman.dll  
 tapi32 5.2.3663.0 (main.020715-1506) 169.50 KB (173,568 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\tapi32.dll  
 wzcsvc 5.2.3663.0 (main.020715-1506) 271.00 KB (277,504 bytes)  
 7/16/2002 3:48 PM Microsoft Corporation  
 c:\windows\system32\wzcsvc.dll  
 wmi 5.2.3663.0 (main.020715-1506) 6.50 KB (6,656 bytes) 7/18/2002  
 2:00 PM Microsoft Corporation c:\windows\system32\wmi.dll  
 dhcpcsvc 5.2.3663.0 (main.020715-1506) 101.00 KB (103,424 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\dhcpcsvc.dll  
 wzcsapi 5.2.3663.0 (main.020715-1506) 24.00 KB (24,576 bytes)  
 7/16/2002 3:48 PM Microsoft Corporation  
 c:\windows\system32\wzcsapi.dll  
 netshell 5.2.3663.0 (main.020715-1506) 1.57 MB (1,648,128 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\netshell.dll  
 clusapi 5.2.3663.0 (main.020715-1506) 54.50 KB (55,808 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\clusapi.dll  
 netcfgx 5.2.3663.0 (main.020715-1506) 616.00 KB (630,784 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\netcfgx.dll  
 winipsec 5.2.3663.0 (main.020715-1506) 29.00 KB (29,696 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\winipsec.dll  
 hnetcfg 5.2.3663.0 (main.020715-1506) 241.50 KB (247,296 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\hnetcfg.dll  
 wininet 6.00.3663.0 (main.020715-1506) 581.00 KB (594,944 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\wininet.dll  
 wbemcore 5.2.3663.0 (main.020715-1506) 448.50 KB (459,264 bytes)  
 8/20/2002 10:44 AM Microsoft Corporation  
 c:\windows\system32\wbem\wbemcore.dll  
 esscli 5.2.3663.0 (main.020715-1506) 232.00 KB (237,568 bytes)  
 8/20/2002 10:43 AM Microsoft Corporation  
 c:\windows\system32\wbem\esscli.dll  
 wmiutils 5.2.3663.0 (main.020715-1506) 88.50 KB (90,624 bytes)  
 8/20/2002 10:44 AM Microsoft Corporation  
 c:\windows\system32\wbem\wmiutils.dll  
 repdrvfs 5.2.3663.0 (main.020715-1506) 140.00 KB (143,360 bytes)  
 8/20/2002 10:43 AM Microsoft Corporation  
 c:\windows\system32\wbem\repdrvfs.dll  
 wmiprvsd 5.2.3663.0 (main.020715-1506) 403.50 KB (413,184 bytes)  
 8/20/2002 10:44 AM Microsoft Corporation  
 c:\windows\system32\wbem\wmiprvsd.dll  
 wbemess 5.2.3663.0 (main.020715-1506) 253.00 KB (259,072 bytes)  
 8/20/2002 10:44 AM Microsoft Corporation  
 c:\windows\system32\wbem\wbemess.dll  
 rasman 5.2.3663.0 (main.020715-1506) 161.50 KB (165,376 bytes)  
 7/18/2002 2:00 PM Microsoft Corporation  
 c:\windows\system32\rasman.dll

```

rastapi 5.2.3663.0 (main.020715-1506) 54.50 KB (55,808 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rastapi.dll
ncprov 5.2.3663.0 (main.020715-1506) 42.50 KB (43,520 bytes)
8/20/2002 10:43 AM Microsoft Corporation
c:\windows\system32\wbem\ncprov.dll
rasppp 5.2.3663.0 (main.020715-1506) 193.50 KB (198,144 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rasppp.dll
ntlsapi 5.2.3663.0 (main.020715-1506) 7.00 KB (7,168 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ntlsapi.dll
raschap 5.2.3663.0 (main.020715-1506) 105.00 KB (107,520 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\raschap.dll
rastls 5.2.3663.0 (main.020715-1506) 147.50 KB (151,040 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rastls.dll
ipbootp 5.2.3663.0 (main.020715-1506) 34.50 KB (35,328 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ipbootp.dll
rasdlg 5.2.3663.0 (main.020715-1506) 637.00 KB (652,288 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rasdlg.dll
rasadhlp 5.2.3663.0 (main.020715-1506) 6.00 KB (6,144 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\rasadhlp.dll
pchsvc 5.2.3663.0 (main.020715-1506) 30.00 KB (30,720 bytes)
8/20/2002 10:48 AM Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\pchsvc.dll
wbemcons 5.2.3663.0 (main.020715-1506) 69.00 KB (70,656 bytes)
8/20/2002 10:44 AM Microsoft Corporation
c:\windows\system32\wbem\wbemcons.dll
explorer 6.00.3663.0 (main.020715-1506) 989.50 KB (1,013,248 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\explorer.exe
browseui 6.00.3663.0 (main.020715-1506) 999.50 KB (1,023,488 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\browseui.dll
shdocvw 6.00.3663.0 (main.020715-1506) 1.28 MB (1,341,952 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\shdocvw.dll
apphelp 5.2.3663.0 (main.020715-1506) 117.00 KB (119,808 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\apphelp.dll
themeui 6.00.3663.0 (main.020715-1506) 360.00 KB (368,640 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\themeui.dll
msimg32 5.2.3663.0 (main.020715-1506) 4.50 KB (4,608 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\msimg32.dll
linkinfo 5.2.3663.0 (main.020715-1506) 15.50 KB (15,872 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\linkinfo.dll

```

```

ntshrui 6.00.3663.0 (main.020715-1506) 134.50 KB (137,728 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ntshrui.dll
webcheck 6.00.3663.0 (main.020715-1506) 253.50 KB (259,584 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\webcheck.dll
wsock32 5.2.3663.0 (main.020715-1506) 22.00 KB (22,528 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\wsock32.dll
stobject 5.2.3663.0 (main.020715-1506) 116.50 KB (119,296 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\stobject.dll
batmeter 6.00.3663.0 (main.020715-1506) 28.00 KB (28,672 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\batmeter.dll
powrprof 6.00.3663.0 (main.020715-1506) 14.00 KB (14,336 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\powrprof.dll
urlmon 6.00.3663.0 (main.020715-1506) 442.00 KB (452,608 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\urlmon.dll
printui 5.2.3663.0 (main.020715-1506) 522.00 KB (534,528 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\printui.dll
cfgmgr32 5.2.3663.0 (main.020715-1506) 17.00 KB (17,408 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\cfgmgr32.dll
drprov 5.2.3663.0 (main.020715-1506) 12.00 KB (12,288 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\drprov.dll
ntlanman 5.2.3663.0 (main.020715-1506) 39.50 KB (40,448 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ntlanman.dll
netui0 5.2.3663.0 (main.020715-1506) 73.00 KB (74,752 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\netui0.dll
netui1 5.2.3663.0 (main.020715-1506) 176.50 KB (180,736 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\netui1.dll
davclnt 5.2.3663.0 (main.020715-1506) 23.00 KB (23,552 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\davclnt.dll
browseui 6.00.3663.0 (main.020715-1506) 61.50 KB (62,976 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\browseui.dll
shdoclc 6.00.3663.0 (main.020715-1506) 521.00 KB (533,504 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\shdoclc.dll
gdiplus 5.2.3663.0 (main.020715-1506) 1.65 MB (1,728,512 bytes)
8/20/2002 12:29 PM Microsoft Corporation
c:\windows\winsxs\x86_microsoft.windows.gdiplus_6595b64144ccf1df_1.0
.3000.0_x-ww_4a2ca156\gdiplus.dll
tapisrv 5.2.3663.0 (main.020715-1506) 234.00 KB (239,616 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\tapisrv.dll

```

```

unimdm 5.2.3663.0 (main.020715-1506) 188.50 KB (193,024 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\unimdm.tsp
uniplat 5.2.3663.0 (main.020715-1506) 14.50 KB (14,848 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\uniplat.dll
kmdisp 5.2.3663.0 (main.020715-1506) 32.50 KB (33,280 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\kmdisp.tsp
ndptsp 5.2.3663.0 (main.020715-1506) 54.50 KB (55,808 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ndptsp.tsp
ipconf 5.2.3663.0 (main.020715-1506) 16.50 KB (16,896 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\ipconf.tsp
h323 5.2.3663.0 (main.020715-1506) 249.00 KB (254,976 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\h323.tsp
hidphone 5.2.3663.0 (main.020715-1506) 28.00 KB (28,672 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\hidphone.tsp
hid 5.2.3663.0 (main.020715-1506) 17.00 KB (17,408 bytes) 7/16/2002
3:47 PM Microsoft Corporation c:\windows\system32\hid.dll
helpctr 5.2.3663.0 (main.020715-1506) 670.00 KB (686,080 bytes)
8/20/2002 10:47 AM Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\helpctr.exe
hcappres 5.2.3663.0 (main.020715-1506) 6.50 KB (6,656 bytes)
8/20/2002 10:47 AM Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\hcappres.dll
itss 5.2.3663.0 (main.020715-1506) 118.50 KB (121,344 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\itss.dll
msxml3 8.40.8806.0 1.06 MB (1,107,968 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\msxml3.dll
pchshell 5.2.3663.0 (main.020715-1506) 94.00 KB (96,256 bytes)
8/20/2002 10:48 AM Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\pchshell.dll
mlang 6.00.3663.0 (main.020715-1506) 564.50 KB (578,048 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\mlang.dll
mshtml 6.00.3663.0 (main.020715-1506) 2.57 MB (2,690,560 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\mshtml.dll
msimtf 5.2.3663.0 (main.020715-1506) 141.00 KB (144,384 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\msimtf.dll
msctf 5.2.3663.0 (main.020715-1506) 273.00 KB (279,552 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\msctf.dll
jscript 5.6.0.7727 412.00 KB (421,888 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\jscript.dll
msls31 3.10.349.0 137.00 KB (140,288 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\msls31.dll
imm32 5.2.3663.0 (main.020715-1506) 104.00 KB (106,496 bytes) 7/18/2002
2:00 PM Microsoft Corporation c:\windows\system32\imm32.dll
mshtml 6.00.3663.0 (main.020715-1506) 424.00 KB (434,176 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\mshtml.dll
vbscript 5.6.0.7727 388.00 KB (397,312 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\vbscript.dll

```

```

mfc426.05.2178.0 960.00 KB (983,040 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\mfc42.dll
msinfo 5.2.3663.0 (main.020715-1506) 352.00 KB (360,448 bytes)
8/20/2002 10:47 AM Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\msinfo.dll
mfc42u 6.05.2178.0 960.00 KB (983,040 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\mfc42u.dll
comdlg32 6.00.3663.0 (main.020715-1506) 255.00 KB (261,120 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\comdlg32.dll
riched32 5.2.3663.0 (main.020715-1506) 3.50 KB (3,584 bytes)
7/18/2002 2:00 PM Microsoft Corporation
c:\windows\system32\riched32.dll
riched20 5.31.23.1217 394.50 KB (403,968 bytes) 7/18/2002 2:00 PM
Microsoft Corporation c:\windows\system32\riched20.dll
helpsvc 5.2.3663.0 (main.020715-1506) 683.50 KB (699,904 bytes)
8/20/2002 10:47 AM Microsoft Corporation
c:\windows\pchealth\helpctr\binaries\helpsvc.exe

```

[Services]

Display Name	Name	State	Start Mode	Service Type	Path	Error Control
	Start Name	Tag ID				
Alerter	Alerter	Running	Auto	Share Process	c:\windows\system32\svchost.exe -k localService	Normal NT
AUTHORITY\LocalService		0				
Application Layer Gateway Service	ALG	Stopped	Manual	Own	c:\windows\system32\alg.exe	Normal NT
AUTHORITY\LocalService		0				
Application Management	AppMgmt	Stopped	Manual	Share Process	c:\windows\system32\svchost.exe -k netsvcs	Normal
LocalSystem		0				
Windows Audio	AudioSrv	Stopped	Disabled	Share Process	c:\windows\system32\svchost.exe -k netsvcs	Normal
LocalSystem		0				
Background Intelligent Transfer Service	BITS	Stopped	Manual	Share	c:\windows\system32\svchost.exe -k netsvcs	Normal
LocalSystem		0				
Computer Browser	Browser	Stopped	Disabled	Share Process	c:\windows\system32\svchost.exe -k netsvcs	Normal
LocalSystem		0				
Indexing Service	CiSvc	Stopped	Manual	Share Process	c:\windows\system32\cisvc.exe	Normal LocalSystem 0
ClipBook	ClipSrv	Stopped	Disabled	Own Process	c:\windows\system32\clipsrv.exe	Normal LocalSystem 0
COM+ System Application	COMSysApp	Stopped	Manual	Own Process	c:\windows\system32\dllhost.exe /processid:{02d4b3f1-fd88-11d1-960d-00805fc79235}	Normal LocalSystem 0
Cryptographic Services	CryptSvc	Stopped	Manual	Share Process	c:\windows\system32\svchost.exe -k netsvcs	Normal
LocalSystem		0				
Distributed File System	Dfs	Stopped	Manual	Own Process	c:\windows\system32\dfssvc.exe	Normal LocalSystem 0
DHCP Client	Dhcp	Stopped	Manual	Share Process	c:\windows\system32\svchost.exe -k networkservice	Normal NT
AUTHORITY\NetworkService		0				

```

Logical Disk Manager Administrative Service dmadmin Stopped
Manual Share Process c:\windows\system32\dmadmin.exe /com
Normal LocalSystem 0
Logical Disk Manager dmserver Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
DNS Client Dnscache Stopped Manual Share Process
c:\windows\system32\svchost.exe -k networkservice Normal NT
AUTHORITY\NetworkService 0
Error Reporting Service ERSvc Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Ignore
LocalSystem 0
Event Log Eventlog Running Auto Share Process
c:\windows\system32\services.exe Normal LocalSystem 0
COM+ Event System EventSystem Running Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Help and Support helpsvc Running Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Human Interface Device Access HidServ Stopped Disabled Share
Process c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
HTTP SSL HTTPFilter Stopped Manual Share Process
c:\windows\system32\lsass.exe Normal LocalSystem 0
IMAPI CD-Burning COM Service ImapiService Stopped Disabled Own
Process "c:\windows\system32\imapi.exe" Normal LocalSystem 0
Inter-site Messaging IsmServ Stopped Disabled Own Process
c:\windows\system32\ismserv.exe Normal LocalSystem 0
Kerberos Key Distribution Center kdc Stopped Disabled Share
Process c:\windows\system32\lsass.exe Normal LocalSystem 0
Server lanmanserver Running Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Workstation lanmanworkstation Running Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
License Logging LicenseService Stopped Manual Own Process
c:\windows\system32\llssrv.exe Normal NT
AUTHORITY\NetworkService 0
TCP/IP NetBIOS Helper LmHosts Running Auto Share Process
c:\windows\system32\svchost.exe -k localService Normal NT
AUTHORITY\LocalService 0
Messenger Messenger Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
NetMeeting Remote Desktop Sharing mnmsrvc Stopped Disabled Own
Process c:\windows\system32\mnmsrvc.exe Normal LocalSystem 0
Distributed Transaction Coordinator MSDTC Stopped Manual Own
Process c:\windows\system32\msdtc.exe Normal NT
AUTHORITY\NetworkService 0
Windows Installer MSIServer Stopped Manual Share Process
c:\windows\system32\msiexec.exe /v Normal LocalSystem 0
Microsoft Search MSSEARCH Stopped Manual Share Process
"c:\program files\common files\system\mssearch\bin\mssearch.exe"
Normal LocalSystem 0

```

```

MSSQLSERVER MSSQLSERVER Stopped Manual Own Process
c:\progra~1\microso~1\mssql\bin\sqlservr.exe Normal
LocalSystem 0
MSSQLServerADHelper MSSQLServerADHelper Stopped Manual Own
Process c:\program files\microsoft sql
server\80\tools\bin\sqladhlp.exe Normal LocalSystem 0
Network DDE NetDDE Stopped Disabled Share Process
c:\windows\system32\netdde.exe Normal LocalSystem 0
Network DDE DSDM NetDDEdsdm Stopped Disabled Share Process
c:\windows\system32\netdde.exe Normal LocalSystem 0
Net Logon Netlogon Stopped Manual Share Process
c:\windows\system32\lsass.exe Normal LocalSystem 0
Network Connections Netman Running Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Network Location Awareness (NLA) Nla Running Manual Share
Process c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Intel(R) NMS NMSSvc Stopped Manual Own Process
c:\windows\system32\nmssvc.exe Normal LocalSystem 0
File Replication NtFrs Stopped Manual Own Process
c:\windows\system32\ntfrs.exe Ignore LocalSystem 0
NT LM Security Support Provider NtLmSsp Stopped Manual Share
Process c:\windows\system32\lsass.exe Normal LocalSystem 0
Removable Storage NtmsSvc Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Plug and Play PlugPlay Running Auto Share Process
c:\windows\system32\services.exe Normal LocalSystem 0
IPSEC Services PolicyAgent Stopped Manual Share Process
c:\windows\system32\lsass.exe Normal LocalSystem 0
Protected Storage ProtectedStorage Running Auto Share Process
c:\windows\system32\lsass.exe Normal LocalSystem 0
Remote Access Auto Connection Manager RasAuto Stopped Manual
Share Process c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Remote Access Connection Manager RasMan Running Manual Share
Process c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Remote Desktop Help Session Manager RDSessMgr Stopped Manual Own
Process c:\windows\system32\sessmgr.exe Normal LocalSystem 0
Routing and Remote Access RemoteAccess Stopped Disabled Share
Process c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Remote Registry RemoteRegistry Stopped Manual Share Process
c:\windows\system32\svchost.exe -k regsvc Normal NT
AUTHORITY\LocalService 0
Remote Procedure Call (RPC) Locator RpcLocator Stopped Manual Own
Process c:\windows\system32\locator.exe Normal NT
AUTHORITY\NetworkService 0
Remote Procedure Call (RPC) RpcSs Running Auto Share Process
c:\windows\system32\svchost -k rpcss Normal LocalSystem 0
Resultant Set of Policy Provider RSOPProv Stopped Manual Share
Process c:\windows\system32\rsopprov.exe Normal LocalSystem
0

```

```

Special Administration Console Helper sacsvr Stopped Manual
Share Process c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
Security Accounts Manager SamSs Stopped Manual Share Process
c:\windows\system32\lsass.exe Normal LocalSystem 0
Smart Card SCardSvr Stopped Manual Share Process
c:\windows\system32\scardsvr.exe Ignore NT
AUTHORITY\LocalService 0
Task Scheduler Schedule Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Secondary Logon seclogon Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Ignore
LocalSystem 0
System Event Notification SENS Running Auto Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Internet Connection Firewall (ICF) / Internet Connection Sharing (ICS)
SharedAccess Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Shell Hardware Detection ShellHWDetection Stopped Manual Share
Process c:\windows\system32\svchost.exe -k netsvcs Ignore
LocalSystem 0
Print Spooler Spooler Stopped Manual Own Process
c:\windows\system32\spoolsv.exe Normal LocalSystem 0
SQLSERVERAGENT SQLSERVERAGENT Stopped Manual Own Process
c:\progra~1\microso~1\mssql~1\bin\sqlagent.exe Normal
LocalSystem 0
Windows Image Acquisition (WIA) stisvc Stopped Disabled Share
Process c:\windows\system32\svchost.exe -k imgsvc Normal NT
AUTHORITY\LocalService 0
Microsoft Software Shadow Copy Provider swprv Stopped Manual Own
Process c:\windows\system32\svchost.exe -k swprv Normal
LocalSystem 0
Performance Logs and Alerts SysmonLog Stopped Manual Own
Process c:\windows\system32\smlogsvc.exe Normal NT
Authority\NetworkService 0
Telephony Tapisrv Running Manual Share Process
c:\windows\system32\svchost.exe -k tapisrv Normal
LocalSystem 0
Terminal Services TermService Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k termsvcs Normal
LocalSystem 0
Themes Themes Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Telnet TlntSvr Stopped Disabled Own Process
c:\windows\system32\tlntsvr.exe Normal NT AUTHORITY\LOCAL SERVICE
0
Distributed Link Tracking Server TrkSvr Stopped Disabled Share
Process c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Distributed Link Tracking Client TrkWks Stopped Manual Share
Process c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0

```

```

Terminal Services Session Directory Tssdis Stopped Disabled Own
Process c:\windows\system32\tssdis.exe Normal LocalSystem 0
Upload Manager uploadmgr Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Uninterruptible Power Supply UPS Stopped Manual Own Process
c:\windows\system32\ups.exe Normal LocalSystem 0
Virtual Disk Service vds Stopped Manual Own Process
c:\windows\system32\vds.exe Normal LocalSystem 0
Volume Shadow Copy VSS Stopped Manual Own Process
c:\windows\system32\vssvc.exe Normal LocalSystem 0
Windows Time W32Time Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
WebClient WebClient Stopped Disabled Share Process
c:\windows\system32\svchost.exe -k localServiceNormal NT
AUTHORITY\LocalService 0
WinHTTP Web Proxy Auto-Discovery Service WinHttpAutoProxySvc Stopped
Manual Share Process c:\windows\system32\svchost.exe -k
localService Normal NT AUTHORITY\LocalService 0
Windows Management Instrumentation winmgmt Running Auto Share
Process c:\windows\system32\svchost.exe -k netsvcs Ignore
LocalSystem 0
Portable Media Serial Number WmdmPmSp Stopped Manual Share
Process c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Windows Management Instrumentation Driver Extensions Wmi Stopped
Manual Share Process c:\windows\system32\svchost.exe -k netsvcs
Normal LocalSystem 0
WMI Performance Adapter WmiApSrv Stopped Manual Own Process
c:\windows\system32\wbem\wmiapsrv.exe Normal LocalSystem
0
Automatic Updates wuauclt Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Wireless Configuration WZCSVC Stopped Manual Share Process
c:\windows\system32\svchost.exe -k netsvcs Normal
LocalSystem 0

[Program Groups]

Group Name Name User Name
Accessories Default User:Accessories Default User
Accessories\Accessibility Default User:Accessories\Accessibility
Default User
Accessories\Entertainment Default User:Accessories\Entertainment
Default User
Startup Default User:Startup Default User
Accessories All Users:Accessories All Users
Accessories\Accessibility All Users:Accessories\Accessibility All Users
Accessories\Communications All Users:Accessories\Communications All Users
Accessories\Entertainment All Users:Accessories\Entertainment All Users
Accessories\System Tools All Users:Accessories\System Tools All Users
Administrative Tools All Users:Administrative Tools All Users
Microsoft SQL Server All Users:Microsoft SQL Server All Users
Startup All Users:Startup All Users

```

Accessories NT AUTHORITY\SYSTEM:Accessories NT AUTHORITY\SYSTEM  
 Accessories\Accessibility NT AUTHORITY\SYSTEM:Accessories\Accessibility  
 NT AUTHORITY\SYSTEM  
 Accessories\Entertainment NT AUTHORITY\SYSTEM:Accessories\Entertainment  
 NT AUTHORITY\SYSTEM  
 Startup NT AUTHORITY\SYSTEM:Startup NT AUTHORITY\SYSTEM  
 Accessories ASTERIX\Administrator:Accessories ASTERIX\Administrator

Accessories\Accessibility ASTERIX\Administrator:Accessories\Accessibility  
 ASTERIX\Administrator  
 Accessories\Entertainment ASTERIX\Administrator:Accessories\Entertainment  
 ASTERIX\Administrator  
 Administrative Tools ASTERIX\Administrator:Administrative Tools  
 ASTERIX\Administrator  
 Startup ASTERIX\Administrator:Startup ASTERIX\Administrator

[Startup Programs]

Program	Command	User Name	Location
desktop	desktop.ini	NT AUTHORITY\SYSTEM	Startup
desktop	desktop.ini	ASTERIX\Administrator	Startup
desktop	desktop.ini	.DEFAULT	Startup
desktop	desktop.ini	All Users	Common Startup

[OLE Registration]

Object	Local Server
Sound (OLE2)	sndrec32.exe
Media Clip	mplay32.exe
Video Clip	mplay32.exe /avi
MIDI Sequence	mplay32.exe /mid
Sound	Not Available
Media Clip	Not Available
Windows Media Player 7	Not Available
WordPad Document	"%programfiles%\windows nt\accessories\wordpad.exe"
Windows Media Services DRM Storage object	Not Available

[Windows Error Reporting]

Time Type Details

[Internet Settings]

[Internet Explorer]

[ Following are sub-categories of this main category ]  
 [Summary]

Item	Value
Version	6.0.3663.0
Build	63663
Application Path	C:\Program Files\Internet Explorer
Language	English (United States)
Active Printer	Not Available

Cipher Strength 128-bit  
 Content Advisor Disabled  
 IEAK Install No

[File Versions]

File Version	Size	Date	Path	Company
actxprxy.dll	6.0.3663.0	95 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
advpack.dll	6.0.3663.0	93 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
asctrls.ocx	6.0.3663.0	89 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
browsecl.dll	6.0.3663.0	62 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
browseui.dll	6.0.3663.0	1,000 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
cdfview.dll	6.0.3663.0	141 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
comctl32.dll	5.82.3663.0	560 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
dxtrans.dll	6.3.3663.0	188 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
dxtmsft.dll	6.3.3663.0	332 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
iecont.dll	<File Missing>	Not Available	Not Available	Not Available
iecontlc.dll	<File Missing>	Not Available	Not Available	Not Available
iedkcs32.dll	16.0.3663.0	292 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
iepeers.dll	6.0.3663.0	229 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
iesetup.dll	6.0.3663.0	59 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
ieuinit.inf	Not Available	19 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Not Available
iexplore.exe	6.0.3663.0	90 KB	7/18/2002 2:00:00 PM	C:\Program Files\Internet Explorer Microsoft Corporation
imgutil.dll	6.0.3663.0	30 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
inetcpl.cpl	6.0.3663.0	296 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
inetcplc.dll	6.0.3663.0	108 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
inseng.dll	6.0.3663.0	71 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
mlang.dll	6.0.3663.0	565 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
msencode.dll	2000.7.25.0	92 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Not Available
mshta.exe	6.0.3663.0	27 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation
mshtml.dll	6.0.3663.0	2,628 KB	7/18/2002 2:00:00 PM	C:\WINDOWS\system32 Microsoft Corporation

```

mshtml.tlb 6.0.3663.0 1,319 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
mshtml.ed.dll 6.0.3663.0 424 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation
mshtml.ier.dll 6.0.3663.0 55 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
msident.dll 6.0.3663.0 47 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
msident.ld.dll 6.0.3663.0 15 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
msieftp.dll 6.0.3663.0 232 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation
msrating.dll 6.0.3663.0 132 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation
mstime.dll 6.0.3663.0 490 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
occache.dll 6.0.3663.0 88 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
proctexe.ocx 6.3.3663.0 78 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Intel Corporation
sendmail.dll 6.0.3663.0 54 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
shdoclc.dll 6.0.3663.0 521 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation
shdocvw.dll 6.0.3663.0 1,311 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation
shfolder.dll 6.0.3663.0 23 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
shlwapi.dll 6.0.3663.0 269 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation
tdc.ocx 1.3.0.3130 57 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
url.dll 6.0.3663.0 40 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
urlmon.dll 6.0.3663.0 442 KB 7/18/2002 2:00:00 PM C:\WINDOWS\system32
Microsoft Corporation
webcheck.dll 6.0.3663.0 254 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation
wininet.dll 6.0.3663.0 581 KB 7/18/2002 2:00:00 PM
C:\WINDOWS\system32 Microsoft Corporation

```

[Connectivity]

```

Item Value
Connection Preference Never dial

```

LAN Settings

```

AutoConfigProxy Not Available
AutoProxyDetectMode Disabled
AutoConfigURL
ProxyEnabled
ProxyServer proxy.mch.fsc.net:81
ProxyOverride <local>

```

[Cache]

[ Following are sub-categories of this main category ]  
[Summary]

```

Item Value
Page Refresh Type Automatic
Temporary Internet Files Folder C:\Documents and
Settings\LocalService\Local Settings\Temporary Internet Files
Total Disk Space Not Available
Available Disk Space Not Available
Maximum Cache Size Not Available
Available Cache Size Not Available

```

[List of Objects]

```

Program File Status CodeBase
No cached object information available

```

[Content]

[ Following are sub-categories of this main category ]  
[Summary]

```

Item Value
Content Advisor Disabled

```

[Personal Certificates]

```

Issued To Issued By Validity Signature Algorithm
No personal certificate information available

```

[Other People Certificates]

```

Issued To Issued By Validity Signature Algorithm
No other people certificate information available

```

[Publishers]

```

Name
No publisher information available

```

[Security]

```

Zone Security Level
My Computer Custom
Local intranet Medium-low
Trusted sites Low
Internet Medium
Restricted sites High

```

```

GCFVERSION=2.00;
Begin
BeginGroup
PhysicalDevice0 = Channel=0, Target=0, Size=34700MB, State=Online,

```

```

TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice1 = Channel=1, Target=0, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice2 = Channel=0, Target=1, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice3 = Channel=1, Target=1, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice4 = Channel=0, Target=2, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice5 = Channel=1, Target=2, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice6 = Channel=0, Target=3, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice7 = Channel=1, Target=3, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice8 = Channel=0, Target=4, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice9 = Channel=1, Target=4, Size=34700MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
IntermediateDevice0 = StripeSize=64KB, Raid=1, WriteThrough=1,
Size=34696MB,
(PhysicalDevice0, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks),
(PhysicalDevice1, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks);
IntermediateDevice1 = StripeSize=64KB, Raid=1, WriteThrough=1,
Size=34696MB,
(PhysicalDevice2, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks),
(PhysicalDevice3, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks);
IntermediateDevice2 = StripeSize=64KB, Raid=1, WriteThrough=1,
Size=34696MB,
(PhysicalDevice4, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks),
(PhysicalDevice5, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks);
IntermediateDevice3 = StripeSize=64KB, Raid=1, WriteThrough=1,
Size=34696MB,
(PhysicalDevice6, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks),
(PhysicalDevice7, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks);
IntermediateDevice4 = StripeSize=64KB, Raid=1, WriteThrough=1,
Size=34696MB,
(PhysicalDevice8, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks),
(PhysicalDevice9, StartAddress=0MB/0Blocks,
Size=34696MB/71057408Blocks);
LogicalDevice0 = StripeSize=64KB, Raid=12, WriteThrough=1,
Size=173480MB, BIOSGeometry=8GB,
(IntermediateDevice0, StartAddress=0MB, Size=34696MB),
(IntermediateDevice1, StartAddress=0MB, Size=34696MB),
(IntermediateDevice2, StartAddress=0MB, Size=34696MB),
(IntermediateDevice3, StartAddress=0MB, Size=34696MB),
(IntermediateDevice4, StartAddress=0MB, Size=34696MB);

```

```

EndGroup
BeginControllerParameter
ControllerName = eXtremeRAID 2000;
ControllerType = 28;
FirmwareVersion = 7.01;
CacheLineSize = 8KB;
AutomaticRebuildRate = 50;
BackgroundInitializeRate = 50;
ConsistencyCheckRate = 50;
MORERate = 50;
InitiatorID = 7;
DevicesPerSpin = 2;
SequentialDelay = 6S;
EnableDriveSizing = 1;
EnableClustering = 0;
EnableBGInit = 1;
EnableBiosLoadDelay = 0;
EnableForcedUnitAccess = 0;
DisableBios = 1;
EnableCDROMBoot = 0;
EnableStorageWorks = 0;
EnableSAFTE = 0;
EnableSES = 0;
EnableARM = 0;
EnableOFM = 0;
OEMCode = 16;
StartupOption = 4;
EnableTempOffline = 0;
EnablePatrolRead = 0;
EnableSmartMode = 0;
DlyBtwnIterations = 336;
SmartScanInterval = 0;
EndControllerParameter
End

===== Controller 1 .. 5 =====

GCFVERSION=2.00;
Begin
BeginGroup
PhysicalDevice0 = Channel=0, Target=0, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice1 = Channel=0, Target=1, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice2 = Channel=0, Target=2, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice3 = Channel=0, Target=3, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice4 = Channel=0, Target=4, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice5 = Channel=0, Target=5, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice6 = Channel=0, Target=10, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice7 = Channel=0, Target=11, Size=17300MB, State=Online,
TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;

```



```

(PhysicalDevice14, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice15, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice16, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice17, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice18, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice19, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice20, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice21, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice22, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice23, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks);
IntermediateDevice2 = StripeSize=128KB, Raid=0, WriteThrough=1,
Size=207552MB,
(PhysicalDevice24, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice25, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice26, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice27, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice28, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice29, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice30, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice31, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice32, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice33, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice34, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice35, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks);
IntermediateDevice3 = StripeSize=128KB, Raid=0, WriteThrough=1,
Size=207552MB,
(PhysicalDevice36, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice37, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice38, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice39, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),

```

```

(PhysicalDevice40, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice41, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice42, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice43, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice44, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice45, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice46, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks),
(PhysicalDevice47, StartAddress=0MB/0Blocks,
Size=17296MB/35422208Blocks);
LogicalDevice0 = StripeSize=128KB, Raid=12, WriteThrough=1,
Size=830208MB, BIOSGeometry=8GB,
(IntermediateDevice0, StartAddress=0MB, Size=207552MB),
(IntermediateDevice1, StartAddress=0MB, Size=207552MB),
(IntermediateDevice2, StartAddress=0MB, Size=207552MB),
(IntermediateDevice3, StartAddress=0MB, Size=207552MB);
EndGroup
BeginControllerParameter
ControllerName = eXtremeRAID 2000;
ControllerType = 28;
FirmwareVersion = 7.01;
CacheLineSize = 8KB;
AutomaticRebuildRate = 50;
BackgroundInitializeRate = 50;
ConsistencyCheckRate = 50;
MORERate = 50;
InitiatorID = 7;
DevicesPerSpin = 2;
SequentialDelay = 6S;
EnableDriveSizing = 1;
EnableClustering = 0;
EnableBGInit = 0;
EnableBiosLoadDelay = 0;
EnableForcedUnitAccess = 0;
DisableBios = 1;
EnableCDROMBoot = 0;
EnableStorageWorks = 0;
EnableSAFTE = 0;
EnableSES = 0;
EnableARM = 0;
EnableOFM = 0;
OEMCode = 16;
StartupOption = 4;
EnableTempOffline = 0;
EnablePatrolRead = 0;
EnableSmartMode = 0;
DlyBtwnIterations = 336;
SmartScanInterval = 0;
EndControllerParameter
End

```

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\dac2w2k  
Class Name: <NO CLASS>  
Last Write Time: 10/31/2002 - 8:30 AM  
Value 0  
Name: Group  
Type: REG\_SZ  
Data: SCSI Miniport

Value 1  
Name: Start  
Type: REG\_DWORD  
Data: 0

Value 2  
Name: Tag  
Type: REG\_DWORD  
Data: 0x21

Value 3  
Name: Type  
Type: REG\_DWORD  
Data: 0x1

Value 4  
Name: ErrorControl  
Type: REG\_DWORD  
Data: 0x1

Value 5  
Name: ImagePath  
Type: REG\_EXPAND\_SZ  
Data: system32\DRIVERS\dac2w2k.sys

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\dac2w2k\Parameters  
Class Name: <NO CLASS>  
Last Write Time: 8/20/2002 - 1:47 PM  
Value 0  
Name: BusType  
Type: REG\_DWORD  
Data: 0x8

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\dac2w2k\Parameters\De  
vice  
Class Name: <NO CLASS>  
Last Write Time: 10/29/2002 - 3:19 PM  
Value 0  
Name: DriverParameter  
Type: REG\_SZ

Data: ConfigureSIR=12

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\dac2w2k\Parameters\Pr  
nterface  
Class Name: <NO CLASS>  
Last Write Time: 8/20/2002 - 11:30 AM  
Value 0  
Name: 2  
Type: REG\_DWORD  
Data: 0x1

Value 1  
Name: 5  
Type: REG\_DWORD  
Data: 0x1

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\dac2w2k\Security  
Class Name: <NO CLASS>  
Last Write Time: 8/20/2002 - 11:07 AM  
Value 0  
Name: Security  
Type: REG\_BINARY

Data:  
00000000 01 00 14 80 90 00 00 00 - 9c 00 00 00 14 00 00 00  
.....  
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00  
0.....  
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00  
ÿ.....  
00000030 02 00 60 00 04 00 00 00 - 00 00 14 00 fd 01 02 00  
..`.....ÿ...  
00000040 01 01 00 00 00 00 00 05 - 12 00 00 00 00 00 18 00  
.....  
00000050 ff 01 0f 00 01 02 00 00 - 00 00 00 05 20 00 00 00  
ÿ.....  
00000060 20 02 00 00 00 00 14 00 - 8d 01 02 00 01 01 00 00  
.....  
00000070 00 00 00 05 0b 00 00 00 - 00 00 18 00 fd 01 02 00  
.....ÿ...  
00000080 01 02 00 00 00 00 00 05 - 20 00 00 00 23 02 00 00 .....  
...#...  
00000090 01 01 00 00 00 00 00 05 - 12 00 00 00 01 01 00 00  
.....  
00 00 00 05 12 00 00 00 - .....

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\dac2w2k\Enum  
Class Name: <NO CLASS>  
Last Write Time: 10/31/2002 - 8:30 AM  
Value 0  
Name: 0

```

Type:          REG_SZ
Data:
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2254b0d&0&4038

Value 1
Name:          Count
Type:          REG_DWORD
Data:          0x7

Value 2
Name:          NextInstance
Type:          REG_DWORD
Data:          0x7

Value 3
Name:          1
Type:          REG_SZ
Data:
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1c72a60d&0&4038

Value 4
Name:          2
Type:          REG_SZ
Data:
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1ece4987&0&4028

Value 5
Name:          3
Type:          REG_SZ
Data:
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2f92d4b0&0&4020

Value 6
Name:          4
Type:          REG_SZ
Data:
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2df34b01&0&4018

Value 7
Name:          5
Type:          REG_SZ
Data:
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2bee4042&0&4010

Value 8
Name:          6
Type:          REG_SZ
Data:
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&3ae9bccd&0&4028

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Session Manager\I/O
System
Class Name:    <NO CLASS>
Last Write Time: 8/20/2002 - 2:44 PM

```

```

Value 0
Name:          CountOperations
Type:          REG_DWORD
Data:          0

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Control\Session
Manager\Memory Management
Class Name:    <NO CLASS>
Last Write Time: 8/22/2002 - 3:54 PM

Value 0
Name:          ClearPageFileAtShutdown
Type:          REG_DWORD
Data:          0

Value 1
Name:          DisablePagingExecutive
Type:          REG_DWORD
Data:          0

Value 2
Name:          LargeSystemCache
Type:          REG_DWORD
Data:          0

Value 3
Name:          NonPagedPoolQuota
Type:          REG_DWORD
Data:          0

Value 4
Name:          NonPagedPoolSize
Type:          REG_DWORD
Data:          0

Value 5
Name:          PagedPoolQuota
Type:          REG_DWORD
Data:          0

Value 6
Name:          PagedPoolSize
Type:          REG_DWORD
Data:          0

Value 7
Name:          SecondLevelDataCache
Type:          REG_DWORD
Data:          0

Value 8
Name:          SystemPages
Type:          REG_DWORD
Data:          0x33000

```

Value 9  
Name: PagingFiles  
Type: REG\_MULTI\_SZ  
Data: C:\pagefile.sys 2046 4092

Value 10  
Name: PhysicalAddressExtension  
Type: REG\_DWORD  
Data: 0x1

Value 11  
Name: WriteWatch  
Type: REG\_DWORD  
Data: 0x1

Value 12  
Name: SessionViewSize  
Type: REG\_DWORD  
Data: 0x30

Value 13  
Name: SessionPoolSize  
Type: REG\_DWORD  
Data: 0x4

Value 14  
Name: DontVerifyRandomDrivers  
Type: REG\_DWORD  
Data: 0x1

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Control\Session  
Manager\Memory Management\PrefetchParameters  
Class Name: <NO CLASS>  
Last Write Time: 10/23/2002 - 4:07 PM

Value 0  
Name: VideoInitTime  
Type: REG\_DWORD  
Data: 0x148

Value 1  
Name: EnablePrefetcher  
Type: REG\_DWORD  
Data: 0x2

Value 2  
Name: AppLaunchMaxNumPages  
Type: REG\_DWORD  
Data: 0xfa0

Value 3  
Name: AppLaunchMaxNumSections  
Type: REG\_DWORD  
Data: 0xaa

Value 4  
Name: AppLaunchTimerPeriod  
Type: REG\_BINARY  
Data: 80 69 67 ff ff ff ff ff - .igÿÿÿÿÿ

Value 5  
Name: BootMaxNumPages  
Type: REG\_DWORD  
Data: 0x1f400

Value 6  
Name: BootMaxNumSections  
Type: REG\_DWORD  
Data: 0xff0

Value 7  
Name: BootTimerPeriod  
Type: REG\_BINARY  
Data: 00 f2 d8 f8 ff ff ff ff - .ðøÿÿÿÿÿ

Value 8  
Name: MaxNumActiveTraces  
Type: REG\_DWORD  
Data: 0x8

Value 9  
Name: MaxNumSavedTraces  
Type: REG\_DWORD  
Data: 0x8

Value 10  
Name: RootDirPath  
Type: REG\_SZ  
Data: Prefetch

Value 11  
Name: HostingAppList  
Type: REG\_SZ  
Data: DLLHOST.EXE,MMC.EXE,RUNDLL32.EXE

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\qlvika  
Class Name: <NO CLASS>  
Last Write Time: 10/24/2002 - 10:43 AM

Value 0  
Name: ErrorControl  
Type: REG\_DWORD  
Data: 0x1

Value 1  
Name: start  
Type: REG\_DWORD  
Data: 0x2

Value 2  
Name: type  
Type: REG\_DWORD  
Data: 0x1

Value 3  
Name: Tag  
Type: REG\_DWORD  
Data: 0x1

Value 4  
Name: group  
Type: REG\_SZ  
Data: MVIA

Value 5  
Name: ImagePath  
Type: REG\_EXPAND\_SZ  
Data: system32\DRIVERS\qlvika.sys

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\qlvika\Adapters  
Class Name: <NO CLASS>  
Last Write Time: 8/20/2002 - 2:50 PM

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\qlvika\Adapters\210000E08B072BB0  
Class Name: <NO CLASS>  
Last Write Time: 8/21/2002 - 3:22 PM

Value 0  
Name: IPAddress  
Type: REG\_MULTI\_SZ  
Data: 129.103.192.216

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\qlvika\Parameters  
Class Name: <NO CLASS>  
Last Write Time: 10/7/2002 - 2:43 PM

Value 0  
Name: MaxRegisterMBytes  
Type: REG\_DWORD  
Data: 0x200

Value 1  
Name: MaxRegisterRdmaMBytes  
Type: REG\_DWORD  
Data: 0x200

Value 2  
Name: MaxRegisterRegions  
Type: REG\_DWORD  
Data: 0x1000

Value 3  
Name: MaxVis  
Type: REG\_DWORD  
Data: 0x400

Value 4  
Name: MaxCQs  
Type: REG\_DWORD  
Data: 0x400

Value 5  
Name: MaxCQEntries  
Type: REG\_DWORD  
Data: 0x2000

Value 6  
Name: MaxTransferSize  
Type: REG\_DWORD  
Data: 0x10000

Value 7  
Name: MaxPTags  
Type: REG\_DWORD  
Data: 0x800

Value 8  
Name: IuBuffers  
Type: REG\_DWORD  
Data: 0x100

Value 9  
Name: SendDescQuota  
Type: REG\_DWORD  
Data: 0x8

Value 10  
Name: RecvDescQuota  
Type: REG\_DWORD  
Data: 0x8

Value 11  
Name: SupportPrototypeCards  
Type: REG\_DWORD  
Data: 0

Key Name:  
HKEY\_LOCAL\_MACHINE\SYSTEM\CurrentControlSet\Services\qlvika\Security  
Class Name: <NO CLASS>  
Last Write Time: 8/20/2002 - 12:22 PM

Value 0  
Name: Security  
Type: REG\_BINARY  
Data:

```

00000000  01 00 14 80 90 00 00 00 - 9c 00 00 00 14 00 00 00
.....
00000010  30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00
0.....
00000020  ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00
ÿ.....
00000030  02 00 60 00 04 00 00 00 - 00 00 14 00 fd 01 02 00
..`.....ÿ...
00000040  01 01 00 00 00 00 00 05 - 12 00 00 00 00 00 18 00
.....
00000050  ff 01 0f 00 01 02 00 00 - 00 00 00 05 20 00 00 00
ÿ.....
00000060  20 02 00 00 00 00 14 00 - 8d 01 02 00 01 01 00 00
.....
00000070  00 00 00 05 0b 00 00 00 - 00 00 18 00 fd 01 02 00
.....ÿ...
00000080  01 02 00 00 00 00 00 05 - 20 00 00 00 23 02 00 00
...#...
00000090  01 01 00 00 00 00 00 05 - 12 00 00 00 01 01 00 00
.....
00 00 00 05 12 00 00 00 -
.....

```

```

Key Name:
HKEY_LOCAL_MACHINE\SYSTEM\CurrentControlSet\Services\qlvika\Enum
Class Name: <NO CLASS>
Last Write Time: 10/24/2002 - 10:43 AM
Value 0
  Name: 0
  Type: REG_SZ
  Data: Root\SCSIADAPTER\0000

Value 1
  Name: Count
  Type: REG_DWORD
  Data: 0x1

Value 2
  Name: NextInstance
  Type: REG_DWORD
  Data: 0x1

```

**This section discloses hardware information and the Windows 2000 registry parameters used on the PRIMERGY C200 client systems.**

```

System Information report written at: 10/24/2002 02:21:12 PM
[System Summary]

```

```

Item Value
OS Name Microsoft Windows 2000 Server
Version 5.0.2195 Service Pack 2 Build 2195

```

```

OS Manufacturer Microsoft Corporation
System Name C200CL1
System Manufacturer FUJITSU SIEMENS
System Model D1306
System Type X86-based PC
Processor x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1393 Mhz
Processor x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1393 Mhz
BIOS Version PhoenixBIOS Version 4.06 Rev. 1.03.1306
Windows Directory C:\WINNT
System Directory C:\WINNT\System32
Boot Device \Device\Harddisk0\Partition1
Locale United States
User Name C200CL1\Administrator
Time Zone W. Europe Daylight Time
Total Physical Memory 785,892 KB
Available Physical Memory 684,476 KB
Total Virtual Memory 2,051,744 KB
Available Virtual Memory 1,883,460 KB
Page File Space 1,265,852 KB
Page File C:\pagefile.sys

```

```

System Information report written at: 10/24/2002 02:20:45 PM
[Hardware Resources]

```

[ Following are sub-categories of this main category ]

[Conflicts/Sharing]

```

Resource Device
No conflicted/shared resources

```

[DMA]

```

Channel Device Status
4 Direct memory access controller OK
2 Standard floppy disk controller OK

```

[Forced Hardware]

```

Device PNP Device ID
No Forced Hardware

```

[I/O]

```

Address Range Device Status
0x0000-0x0CF7 PCI bus OK
0x0000-0x0CF7 Direct memory access controller OK
0x0D00-0x0FFF PCI bus OK
0x1000-0x180F PCI bus OK
0x1000-0x180F ATI Technologies Inc. RAGE XL PCI OK
0x03B0-0x03BB ATI Technologies Inc. RAGE XL PCI OK
0x03C0-0x03DF ATI Technologies Inc. RAGE XL PCI OK
0x1400-0x143F Fujitsu Siemens Computers 82559-based Onboard Ethernet
with WoL and AoL OK
0x0A79-0x0A79 ISAPNP Read Data Port OK

```

```

0x0279-0x0279 ISAPNP Read Data Port OK
0x02F4-0x02F7 ISAPNP Read Data Port OK
0x0010-0x001F Motherboard resources OK
0x0022-0x002D Motherboard resources OK
0x0030-0x003F Motherboard resources OK
0x0050-0x0053 Motherboard resources OK
0x0062-0x0063 Motherboard resources OK
0x0065-0x006F Motherboard resources OK
0x0074-0x007F Motherboard resources OK
0x0090-0x009F Motherboard resources OK
0x00A2-0x00B1 Motherboard resources OK
0x00B4-0x00BF Motherboard resources OK
0x00E0-0x00EF Motherboard resources OK
0x0072-0x0073 Motherboard resources OK
0x04D0-0x04D1 Motherboard resources OK
0xF100-0xF10F Motherboard resources OK
0x0080-0x008F Direct memory access controller OK
0x00C0-0x00DF Direct memory access controller OK
0x0020-0x0021 Programmable interrupt controller OK
0x00A0-0x00A1 Programmable interrupt controller OK
0x0070-0x0071 System CMOS/real time clock OK
0x0040-0x0043 System timer OK
0x00F0-0x00FE Numeric data processor OK
0x0061-0x0061 System speaker OK
0x0060-0x0060 Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
OK
0x0064-0x0064 Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
OK
0x03F0-0x03F5 Standard floppy disk controller OK
0x03F7-0x03F7 Standard floppy disk controller OK
0x1800-0x180F Standard Dual Channel PCI IDE Controller OK
0x01F0-0x01F7 Primary IDE Channel OK
0x03F6-0x03F6 Primary IDE Channel OK
0x0170-0x0177 Secondary IDE Channel OK
0x0376-0x0376 Secondary IDE Channel OK
0x1C00-0x1CFF PCI bus OK
0x1C00-0x1CFF Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device OK
0x2000-0x20FF PCI bus OK
0x2000-0x20FF QLogic QLA23xx PCI Fibre Channel Adapter OK

```

[IRQs]

```

IRQ Number Device
9 Microsoft ACPI-Compliant System
30 Fujitsu Siemens Computers 82559-based Onboard Ethernet with WoL and
AoL
8 System CMOS/real time clock
13 Numeric data processor
1 Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
12 PS/2 Compatible Mouse
6 Standard floppy disk controller
15 Secondary IDE Channel
29 Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device
26 QLogic QLA23xx PCI Fibre Channel Adapter

```

[Memory]

```

RangeDevice Status
0xA0000-0xBFFFF PCI bus OK
0xA0000-0xBFFFF ATI Technologies Inc. RAGE XL PCI OK
0xC8000-0xDFFFF PCI bus OK
0xFB000000-0xFC2FFFFF PCI bus OK
0xFB000000-0xFC2FFFFF ATI Technologies Inc. RAGE XL PCI OK
0xFED00000-0xFEDFFFFF PCI bus OK
0xFEE01000-0xFFBFFFFF PCI bus OK
0xFC020000-0xFC020FFF ATI Technologies Inc. RAGE XL PCI OK
0xFC021000-0xFC021FFF Fujitsu Siemens Computers 82559-based Onboard
Ethernet with WoL and AoL OK
0xFC000000-0xFC01FFFF Fujitsu Siemens Computers 82559-based Onboard
Ethernet with WoL and AoL OK
0xFC300000-0xFC6FFFFF PCI bus OK
0xFC300000-0xFC6FFFFF Symbios Ultra3 PCI SCSI Adapter; 53C1010-66
Device OK
0xFC302000-0xFC3023FF Symbios Ultra3 PCI SCSI Adapter; 53C1010-66
Device OK
0xFC700000-0xFCAFFFFF PCI bus OK
0xFC700000-0xFCAFFFFF QLogic QLA23xx PCI Fibre Channel Adapter OK

```

System Information report written at: 10/24/2002 02:20:59 PM  
[Components]

[ Following are sub-categories of this main category ]

[Multimedia]

[ Following are sub-categories of this main category ]

[Audio Codecs]

Codec	Manufacturer	Description	Status	File	Version	Size
c:\winnt\system32\lhacm.acm	Microsoft Corporation		OK			
		C:\WINNT\System32\LHACM.ACM	4.4.3385		33.27 KB (34,064 bytes)	
		2/12/2001 3:47:53 PM				
c:\winnt\system32\msg723.acm	Microsoft Corporation		OK			
		C:\WINNT\System32\MSG723.ACM	4.4.3385		106.77 KB (109,328 bytes)	
		2/12/2001 3:47:52 PM				
c:\winnt\system32\iac25_32.ax	Intel Corporation	Indeo® audio software	OK			
		C:\WINNT\System32\IAC25_32.AX	2.05.53		195.00 KB (199,680 bytes)	
		12/7/1999 1:00:00 PM				
c:\winnt\system32\tsssoft32.acm	DSP GROUP, INC.		OK			
		C:\WINNT\System32\TSSOFT32.ACM	1.01		9.27 KB (9,488 bytes)	
		12/7/1999 1:00:00 PM				
c:\winnt\system32\msadp32.acm	Microsoft Corporation		OK			
		C:\WINNT\System32\MSADP32.ACM	5.00.2134.1		14.77 KB (15,120 bytes)	
		12/7/1999 1:00:00 PM				
c:\winnt\system32\imaadp32.acm	Microsoft Corporation		OK			
		C:\WINNT\System32\IMAADP32.ACM	5.00.2134.1		16.27 KB (16,656 bytes)	
		12/7/1999 1:00:00 PM				
c:\winnt\system32\msgsm32.acm	Microsoft Corporation		OK			
		C:\WINNT\System32\MSGSM32.ACM	5.00.2134.1		22.27 KB (22,800 bytes)	
		12/7/1999 1:00:00 PM				

c:\winnt\system32\msg711.acm Microsoft Corporation OK  
C:\WINNT\System32\MSG711.ACM 5.00.2134.1 10.27 KB (10,512  
bytes) 12/7/1999 1:00:00 PM

[Video Codecs]

CodecManufacturer	Description	Status	File Version	Size
Creation Date				
c:\winnt\system32\ir50_32.dll	Intel Corporation	Indeo® video 5.10		
OK	C:\WINNT\System32\IR50_32.DLL	R.5.10.15.2.55	737.50 KB	(755,200 bytes) 12/7/1999 1:00:00 PM
c:\winnt\system32\msh263.drv	Microsoft Corporation	OK		
C:\WINNT\System32\MSH263.DRV	4.4.3385	252.27 KB (258,320 bytes)		2/12/2001 3:47:24 PM
c:\winnt\system32\iccvid.dll	Radius Inc.	OK		
C:\WINNT\System32\ICCVID.DLL	1.10.0.6	108.00 KB (110,592 bytes)		12/7/1999 1:00:00 PM
c:\winnt\system32\msvidc32.dll	Microsoft Corporation	OK		
C:\WINNT\System32\MSVIDC32.DLL	5.00.2134.1	27.27 KB (27,920 bytes)		12/7/1999 1:00:00 PM
c:\winnt\system32\msh261.drv	Microsoft Corporation	OK		
C:\WINNT\System32\MSH261.DRV	4.4.3385	163.77 KB (167,696 bytes)		2/12/2001 3:47:52 PM
c:\winnt\system32\msrle32.dll	Microsoft Corporation	OK		
C:\WINNT\System32\MSRLE32.DLL	5.00.2134.1	10.77 KB (11,024 bytes)		12/7/1999 1:00:00 PM
c:\winnt\system32\ir32_32.dll	Intel(R) Corporation	OK		
C:\WINNT\System32\IR32_32.DLL	Not Available	194.50 KB (199,168 bytes)		12/7/1999 1:00:00 PM

[CD-ROM]

Item Value  
DriveD:  
Description CD-ROM Drive  
Media Loaded False  
Media Type CD-ROM  
Name MITSUMI CD-ROM FX4830T!B  
Manufacturer (Standard CD-ROM drives)  
Status OK  
Transfer Rate Not Available  
SCSI Target ID 0  
PNP Device ID IDE\CDROMMITSUMI\_CD-  
ROM\_FX4830T!B\_\_\_\_\_R02N\_\_\_\_\5&3858FEE&0&0.0.0

[Sound Device]

Item Value  
No sound devices

[Display]

Item Value  
Name ATI Technologies Inc. RAGE XL PCI

PNP Device ID  
PCI\VEN\_1002&DEV\_4752&SUBSYS\_007A110A&REV\_27\3&13C0B0C5&0&20  
Adapter Type ATI RAGE XL PCI, ATI Technologies Inc. compatible  
Adapter Description ATI Technologies Inc. RAGE XL PCI  
Adapter RAM 8.00 MB (8,388,608 bytes)  
Installed Drivers atidrab.dll  
Driver Version 5.00.2179.1  
INF File display.inf (atirage3 section)  
Color Planes 1  
Color Table Entries 16777216  
Resolution 800 x 600 x 85 hertz  
Bits/Pixel 24

[Infrared]

Item Value  
No infrared devices

[Input]

[ Following are sub-categories of this main category ]

[Keyboard]

Item Value  
Description Standard 101/102-Key or Microsoft Natural PS/2 Keyboard  
Name Enhanced (101- or 102-key)  
Layout 00000409  
PNP Device ID ACPI\PNP0303\5&1413D98F&0  
NumberOfFunctionKeys 12

[Pointing Device]

Item Value  
Hardware Type PS/2 Compatible Mouse  
Number of Buttons 3  
Status OK  
PNP Device ID ACPI\PNP0F13\5&1413D98F&0  
Power Management SupportedFalse  
Double Click Threshold 6  
Handedness Right Handed Operation

[Modem]

Item Value  
No modems

[Network]

[ Following are sub-categories of this main category ]

[Adapter]

Item Value  
Name [00000000] Intel(R) PRO/100+ PCI Adapter  
Adapter Type Not Available  
Product Name Intel(R) PRO/100+ PCI Adapter  
Installed True  
PNP Device ID Not Available  
Last Reset 10/24/2002 3:57:26 PM  
Index0  
Service Name E100B  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled False  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Service Name Not Available

Name [00000001] RAS Async Adapter  
Adapter Type Not Available  
Product Name RAS Async Adapter  
Installed True  
PNP Device ID Not Available  
Last Reset 10/24/2002 3:57:26 PM  
Index1  
Service Name AsyncMac  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled False  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Service Name Not Available

Name [00000002] WAN Miniport (L2TP)  
Adapter Type Not Available  
Product Name WAN Miniport (L2TP)  
Installed True  
PNP Device ID ROOT\MS\_L2TPMINIPORT\0000  
Last Reset 10/24/2002 3:57:26 PM  
Index2  
Service Name Rasl2tp  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled False  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Service Name Rasl2tp  
Driver c:\winnt\system32\drivers\rasl2tp.sys (50800, 5.00.2179.1)

Name [00000003] WAN Miniport (PPTP)  
Adapter Type Wide Area Network (WAN)  
Product Name WAN Miniport (PPTP)  
Installed True  
PNP Device ID ROOT\MS\_PPTPMINIPORT\0000  
Last Reset 10/24/2002 3:57:26 PM  
Index3  
Service Name PptpMiniport  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled False  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address 50:50:54:50:30:30  
Service Name PptpMiniport  
Driver c:\winnt\system32\drivers\raspptp.sys (47856, 5.00.2160.1)

Name [00000004] Direct Parallel  
Adapter Type Not Available  
Product Name Direct Parallel  
Installed True  
PNP Device ID ROOT\MS\_PTMINIPORT\0000  
Last Reset 10/24/2002 3:57:26 PM  
Index4  
Service Name Raspti  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled False  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Service Name Raspti  
Driver c:\winnt\system32\drivers\raspti.sys (16880, 5.00.2146.1)

Name [00000005] WAN Miniport (IP)  
Adapter Type Not Available  
Product Name WAN Miniport (IP)  
Installed True  
PNP Device ID ROOT\MS\_NDISWANIP\0000  
Last Reset 10/24/2002 3:57:26 PM  
Index5  
Service Name NdisWan  
IP Address Not Available  
IP Subnet Not Available  
Default IP Gateway Not Available  
DHCP Enabled False  
DHCP Server Not Available  
DHCP Lease Expires Not Available  
DHCP Lease Obtained Not Available  
MAC Address Not Available  
Service Name NdisWan  
Driver c:\winnt\system32\drivers\ndiswan.sys (90096, 5.00.2195.2779)

Name [00000006] Fujitsu Siemens Computers 82559-based Onboard Ethernet with WoL and AoL  
 Adapter Type Ethernet 802.3  
 Product Name Fujitsu Siemens Computers 82559-based Onboard Ethernet with WoL and AoL  
 Installed True  
 PNP Device ID  
 PCI\VEN\_8086&DEV\_1229&SUBSYS\_004B110A&REV\_09\3&13C0B0C5&0&50  
 Last Reset 10/24/2002 3:57:26 PM  
 Index6  
 Service Name E100B  
 IP Address 129.103.211.1  
 IP Subnet 255.255.255.0  
 Default IP Gateway Not Available  
 DHCP Enabled False  
 DHCP Server Not Available  
 DHCP Lease Expires Not Available  
 DHCP Lease Obtained Not Available  
 MAC Address 00:30:05:19:79:0F  
 Service Name E100B  
 IRQ Number 30  
 I/O Port 0x1400-0x143F  
 Driver c:\winnt\system32\drivers\e100bnt5.sys (139536, 6.01.03.0000)

[Protocol]

Item Value  
 Name MSAFD Tcpip [TCP/IP]  
 ConnectionlessService False  
 GuaranteesDelivery True  
 GuaranteesSequencing True  
 MaximumAddressSize 16 bytes  
 MaximumMessageSize 0 bytes  
 MessageOriented False  
 MinimumAddressSize 16 bytes  
 PseudoStreamOriented False  
 SupportsBroadcasting False  
 SupportsConnectData False  
 SupportsDisconnectData False  
 SupportsEncryption False  
 SupportsExpeditedData True  
 SupportsGracefulClosing True  
 SupportsGuaranteedBandwidth False  
 SupportsMulticasting False

Name MSAFD Tcpip [UDP/IP]  
 ConnectionlessService True  
 GuaranteesDelivery False  
 GuaranteesSequencing False  
 MaximumAddressSize 16 bytes  
 MaximumMessageSize 65467 bytes  
 MessageOriented True  
 MinimumAddressSize 16 bytes  
 PseudoStreamOriented False

SupportsBroadcasting True  
 SupportsConnectData False  
 SupportsDisconnectData False  
 SupportsEncryption False  
 SupportsExpeditedData False  
 SupportsGracefulClosing False  
 SupportsGuaranteedBandwidth False  
 SupportsMulticasting True

Name RSVP UDP Service Provider  
 ConnectionlessService True  
 GuaranteesDelivery False  
 GuaranteesSequencing False  
 MaximumAddressSize 16 bytes  
 MaximumMessageSize 65467 bytes  
 MessageOriented True  
 MinimumAddressSize 16 bytes  
 PseudoStreamOriented False  
 SupportsBroadcasting True  
 SupportsConnectData False  
 SupportsDisconnectData False  
 SupportsEncryption True  
 SupportsExpeditedData False  
 SupportsGracefulClosing False  
 SupportsGuaranteedBandwidth False  
 SupportsMulticasting True

Name RSVP TCP Service Provider  
 ConnectionlessService False  
 GuaranteesDelivery True  
 GuaranteesSequencing True  
 MaximumAddressSize 16 bytes  
 MaximumMessageSize 0 bytes  
 MessageOriented False  
 MinimumAddressSize 16 bytes  
 PseudoStreamOriented False  
 SupportsBroadcasting False  
 SupportsConnectData False  
 SupportsDisconnectData False  
 SupportsEncryption True  
 SupportsExpeditedData True  
 SupportsGracefulClosing True  
 SupportsGuaranteedBandwidth False  
 SupportsMulticasting False

Name MSAFD NetBIOS [\\Device\NetBT\_Tcpip\_{75A03E77-80A6-4DFD-A783-6876E710AB9F}] SEQPACKE 3  
 ConnectionlessService False  
 GuaranteesDelivery True  
 GuaranteesSequencing True  
 MaximumAddressSize 20 bytes  
 MaximumMessageSize 64000 bytes  
 MessageOriented True  
 MinimumAddressSize 20 bytes  
 PseudoStreamOriented False  
 SupportsBroadcasting False

SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{75A03E77-80A6-4DFD-A783-6876E710AB9F}] DATAGRAM 3  
ConnectionlessService True  
GuaranteesDelivery False  
GuaranteesSequencing False  
MaximumAddressSize 20 bytes  
MaximumMessageSize 64000 bytes  
MessageOriented True  
MinimumAddressSize 20 bytes  
PseudoStreamOriented False  
SupportsBroadcasting True  
SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{BAFACDD3-FF58-4244-8343-63E521C918BC}] SEQPACKET 0  
ConnectionlessService False  
GuaranteesDelivery True  
GuaranteesSequencing True  
MaximumAddressSize 20 bytes  
MaximumMessageSize 64000 bytes  
MessageOriented True  
MinimumAddressSize 20 bytes  
PseudoStreamOriented False  
SupportsBroadcasting False  
SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{BAFACDD3-FF58-4244-8343-63E521C918BC}] DATAGRAM 0  
ConnectionlessService True  
GuaranteesDelivery False  
GuaranteesSequencing False  
MaximumAddressSize 20 bytes  
MaximumMessageSize 64000 bytes  
MessageOriented True  
MinimumAddressSize 20 bytes  
PseudoStreamOriented False

SupportsBroadcasting True  
SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}] SEQPACKET 1  
ConnectionlessService False  
GuaranteesDelivery True  
GuaranteesSequencing True  
MaximumAddressSize 20 bytes  
MaximumMessageSize 64000 bytes  
MessageOriented True  
MinimumAddressSize 20 bytes  
PseudoStreamOriented False  
SupportsBroadcasting False  
SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}] DATAGRAM 1  
ConnectionlessService True  
GuaranteesDelivery False  
GuaranteesSequencing False  
MaximumAddressSize 20 bytes  
MaximumMessageSize 64000 bytes  
MessageOriented True  
MinimumAddressSize 20 bytes  
PseudoStreamOriented False  
SupportsBroadcasting True  
SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}] SEQPACKET 2  
ConnectionlessService False  
GuaranteesDelivery True  
GuaranteesSequencing True  
MaximumAddressSize 20 bytes  
MaximumMessageSize 64000 bytes  
MessageOriented True  
MinimumAddressSize 20 bytes

PseudoStreamOriented False  
SupportsBroadcasting False  
SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT\_Tcpip\_{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}] DATAGRAM 2  
ConnectionlessService True  
GuaranteesDelivery False  
GuaranteesSequencing False  
MaximumAddressSize 20 bytes  
MaximumMessageSize 64000 bytes  
MessageOriented True  
MinimumAddressSize 20 bytes  
PseudoStreamOriented False  
SupportsBroadcasting True  
SupportsConnectData False  
SupportsDisconnectData False  
SupportsEncryption False  
SupportsExpeditedData False  
SupportsGracefulClosing False  
SupportsGuaranteedBandwidth False  
SupportsMulticasting False

[WinSock]

Item Value  
File c:\winnt\system32\winsock.dll  
Version 3.10  
Size 2.80 KB (2,864 bytes)  
  
File c:\winnt\system32\wsock32.dll  
Version 5.00.2195.2871  
Size 21.27 KB (21,776 bytes)

[Ports]

[ Following are sub-categories of this main category ]

[Serial]

Item Value  
No serial port information

[Parallel]

Item Value  
No parallel port information

[Storage]

[ Following are sub-categories of this main category ]

[Drives]

Item Value  
DriveA:  
Description 3 1/2 Inch Floppy Drive

DriveC:  
Description Local Fixed Disk  
Compressed False  
File System NTFS  
Size 17.01 GB (18,268,311,552 bytes)  
Free Space 13.71 GB (14,716,776,448 bytes)  
Volume Name  
Volume Serial Number 080A3D50  
Partition Disk #0, Partition #0  
Partition Size 17.01 GB (18,268,314,624 bytes)  
Starting Offset 32256 bytes  
Drive Description Disk drive  
Drive Manufacturer (Standard disk drives)  
Drive Model FUJITSU MAG3182LC SCSI Disk Device  
Drive BytesPerSector 512  
Drive MediaLoaded True  
Drive MediaType Fixed hard disk media  
Drive Partitions 1  
Drive SCSI Bus 0  
Drive SCSI LogicalUnit 0  
Drive SCSI Port 2  
Drive SCISITargetId 0  
Drive SectorsPerTrack 63  
Drive Size 18268346880 bytes  
Drive TotalCylinders 2221  
Drive TotalSectors 35680365  
Drive TotalTracks 566355  
Drive TracksPerCylinder 255

[SCSI]

Item Value  
Name Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device  
Caption Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device  
Driver Sym\_u3  
Status OK  
PNP Device ID  
PCI\VEN\_1000&DEV\_0021&SUBSYS\_6030110A&REV\_01\3&1070020&0&50  
Device ID PCI\VEN\_1000&DEV\_0021&SUBSYS\_6030110A&REV\_01\3&1070020&0&50  
Device Map Not Available  
Index Not Available  
Max Number Controlled Not Available  
IRQ Number 29  
I/O Port 0x1C00-0x1CFF  
Driver c:\winnt\system32\drivers\sym\_u3.sys (37920, SYM\_U3NT-5.08.00)

Name QLogic QLA23xx PCI Fibre Channel Adapter  
Caption QLogic QLA23xx PCI Fibre Channel Adapter  
Driver ql2300  
Status OK  
PNP Device ID  
PCI\VEN\_1077&DEV\_2312&SUBSYS\_010C1077&REV\_02\3&29E81982&0&48  
Device ID PCI\VEN\_1077&DEV\_2312&SUBSYS\_010C1077&REV\_02\3&29E81982&0&48  
Device Map Not Available  
Index Not Available  
Max Number Controlled Not Available  
IRQ Number 26  
I/O Port 0x2000-0x20FF  
Driver c:\winnt\system32\drivers\ql2300.sys (440012, 8.2.0 Beta 3 (W2K  
VI))

Name QLogic VI Kernel Agent driver  
Caption QLogic VI Kernel Agent driver  
Driver qlvika  
Status OK  
PNP Device ID ROOT\SCSIADAPTER\0000  
Device ID ROOT\SCSIADAPTER\0000  
Device Map Not Available  
Index Not Available  
Max Number Controlled Not Available  
Driver c:\winnt\system32\drivers\qlvika.sys (49916, 1.00.14 (W2K))

[Printing]

Name Port Name Server Name  
No printing information

[Problem Devices]

Device PNP Device ID Error Code  
No Problem Devices

[USB]

Device PNP Device ID  
No USB Devices

System Information report written at: 10/24/2002 02:21:12 PM  
[System Summary]

Item Value  
OS Name Microsoft Windows 2000 Server  
Version 5.0.2195 Service Pack 2 Build 2195  
OS Manufacturer Microsoft Corporation  
System Name C200CL1  
System Manufacturer FUJITSU SIEMENS  
System Model D1306  
System Type X86-based PC  
Processor x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1393 Mhz

Processor x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1393 Mhz  
BIOS Version PhoenixBIOS Version 4.06 Rev. 1.03.1306  
Windows Directory C:\WINNT  
System Directory C:\WINNT\System32  
Boot Device \Device\Harddisk0\Partition1  
Locale United States  
User Name C200CL1\Administrator  
Time Zone W. Europe Daylight Time  
Total Physical Memory 785,892 KB  
Available Physical Memory 684,476 KB  
Total Virtual Memory 2,051,744 KB  
Available Virtual Memory 1,883,460 KB  
Page File Space 1,265,852 KB  
Page File C:\pagefile.sys

System Information report written at: 10/24/2002 02:22:04 PM  
[Environment Variables]

Variable	Value	User Name
ComSpec	%SystemRoot%\system32\cmd.exe	<SYSTEM>
Os2LibPath	%SystemRoot%\system32\os2\dll;	<SYSTEM>
Path	%SystemRoot%\system32;%SystemRoot%;%SystemRoot%\System32\Wbem;C:\Program Files\Microsoft SQL Server\80\Tools\BINN <SYSTEM>	
windir	%SystemRoot%	<SYSTEM>
OS	Windows_NT	<SYSTEM>
PROCESSOR_ARCHITECTURE	x86	<SYSTEM>
PROCESSOR_LEVEL	6	<SYSTEM>
PROCESSOR_IDENTIFIER	x86 Family 6 Model 11 Stepping 1, GenuineIntel <SYSTEM>	
PROCESSOR_REVISION	0b01	<SYSTEM>
NUMBER_OF_PROCESSORS	2	<SYSTEM>
PATHEXT	.COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS;.JSE;.WSF;.WSH	<SYSTEM>
TEMP	%SystemRoot%\TEMP	<SYSTEM>
TMP	%SystemRoot%\TEMP	<SYSTEM>
TEMP	%USERPROFILE%\Local Settings\Temp	C200CL1\Administrator
TMP	%USERPROFILE%\Local Settings\Temp	C200CL1\Administrator

System Information report written at: 10/24/2002 02:20:03 PM  
[Services]

Display Name	Name	State	Start	Mode	Service Type	Path	Error	Control
Start Name	Tag	ID						
Alerter	Alerter	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Application Management	AppMgmt	Stopped	Manual	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Computer Browser	Browser	Stopped	Disabled	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Indexing Service	cisvc	Stopped	Manual	Share	Process	c:\winnt\system32\cisvc.exe	Normal	LocalSystem 0
ClipBook	ClipSrv	Stopped	Manual	Own	Process	c:\winnt\system32\clipsrv.exe	Normal	LocalSystem 0
Distributed File System	Dfs	Stopped	Manual	Own	Process	c:\winnt\system32\dfssvc.exe	Normal	LocalSystem 0

```

DHCP Client      Dhcp Stopped Disabled Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Logical Disk Manager Administrative Service dmadmin Stopped
Manual Share Process c:\winnt\system32\dmadmin.exe /com
Normal LocalSystem 0
Logical Disk Manager dmserver Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
DNS Client Dnscache Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Event Log Eventlog Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
COM+ Event System EventSystem Running Auto Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Fax Service Fax Stopped Disabled Own Process
c:\winnt\system32\faxsvc.exe Normal LocalSystem 0
IIS Admin Service IISADMIN Running Manual Share Process
c:\winnt\system32\inet_srv\inetinfo.exe Normal LocalSystem
0
Intersite Messaging IsmServ Stopped Disabled Own Process
c:\winnt\system32\ismserv.exe Normal LocalSystem 0
Kerberos Key Distribution Center kdc Stopped Disabled Share
Process c:\winnt\system32\lsass.exe Normal LocalSystem 0
Server lanmanserver Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Workstation lanmanworkstation Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
License Logging Service LicenseService Stopped Manual Own
Process c:\winnt\system32\llssrv.exe Normal LocalSystem 0
TCP/IP NetBIOS Helper Service LmHosts Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Messenger Messenger Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
NetMeeting Remote Desktop Sharing mnmsrvc Stopped Disabled Own
Process c:\winnt\system32\mnmsrvc.exe Normal LocalSystem 0
Distributed Transaction Coordinator MSDTC Stopped Manual Own
Process c:\winnt\system32\msdtc.exe Normal LocalSystem 0
Windows Installer MSIServer Stopped Manual Share Process
c:\winnt\system32\msiexec.exe /v Normal LocalSystem 0
Network DDE NetDDE Stopped Manual Share Process
c:\winnt\system32\netdde.exe Normal LocalSystem 0
Network DDE DSDM NetDDEdsdm Stopped Manual Share Process
c:\winnt\system32\netdde.exe Normal LocalSystem 0
Net Logon NetLogon Stopped Manual Share Process
c:\winnt\system32\lsass.exe Normal LocalSystem 0
Network Connections Netman Running Manual Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Intel(R) NMS NMSSvc Running Manual Own Process
c:\winnt\system32\nmssvc.exe Normal LocalSystem 0
File Replication NtFrs Stopped Manual Own Process
c:\winnt\system32\ntfrs.exe Ignore LocalSystem 0
NT LM Security Support Provider NtLmSsp Stopped Manual Share
Process c:\winnt\system32\lsass.exe Normal LocalSystem 0

```

```

Removable Storage NtmsSvc Stopped Disabled Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Plug and Play PlugPlay Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
IPSEC Policy Agent PolicyAgent Stopped Manual Share Process
c:\winnt\system32\lsass.exe Normal LocalSystem 0
Protected Storage ProtectedStorage Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Remote Access Auto Connection Manager RasAuto Stopped Manual
Share Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Remote Access Connection Manager RasMan Stopped Manual Share
Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Routing and Remote Access RemoteAccess Stopped Disabled Share
Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Remote Registry Service RemoteRegistry Stopped Manual Own
Process c:\winnt\system32\regsvc.exe Normal LocalSystem 0
Remote Command Service RMSYS Stopped Disabled Own Process
c:\benchmark_422\rsys.exe Normal LocalSystem 0
Remote Procedure Call (RPC) Locator RpcLocator Stopped Manual Own
Process c:\winnt\system32\locator.exe Normal LocalSystem 0
Remote Procedure Call (RPC) RpcSs Running Auto Share Process
c:\winnt\system32\svchost -k rpcss Normal LocalSystem 0
QoS RSVP RSVP Stopped Manual Own Process
c:\winnt\system32\rsvp.exe -s Normal LocalSystem 0
Security Accounts Manager SamSs Stopped Manual Share Process
c:\winnt\system32\lsass.exe Normal LocalSystem 0
Smart Card Helper SCardDrv Stopped Manual Share Process
c:\winnt\system32\scardsvr.exe Ignore LocalSystem 0
Smart Card SCardSvr Stopped Manual Share Process
c:\winnt\system32\scardsvr.exe Ignore LocalSystem 0
Task Scheduler Schedule Stopped Manual Share Process
c:\winnt\system32\mstask.exe Normal LocalSystem 0
RunAs Service seclogon Stopped Manual Share Process
c:\winnt\system32\services.exe Ignore LocalSystem 0
System Event Notification SENS Running Auto Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Internet Connection Sharing SharedAccess Stopped Manual Share
Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Simple Mail Transport Protocol (SMTP) SMTPSVC Stopped Manual
Share Process c:\winnt\system32\inet_srv\inetinfo.exe Normal
LocalSystem 0
Print Spooler Spooler Stopped Manual Own Process
c:\winnt\system32\spoolsv.exe Normal LocalSystem 0
Performance Logs and Alerts SysmonLog Stopped Manual Own
Process c:\winnt\system32\smlogsvc.exe Normal LocalSystem 0
Telephony TapiSrv Running Manual Share Process
c:\winnt\system32\svchost.exe -k tapisrv Normal LocalSystem
0
Terminal Services TermService Stopped Disabled Own Process
c:\winnt\system32\termsrv.exe Normal LocalSystem 0

```

```

Telnet TlntSvr Stopped Disabled Own Process
c:\winnt\system32\tlntsvr.exe Normal LocalSystem 0
Distributed Link Tracking Server TrkSvr Stopped Manual Share
Process c:\winnt\system32\services.exe Normal LocalSystem 0
Distributed Link Tracking Client TrkWks Stopped Manual Share
Process c:\winnt\system32\services.exe Normal LocalSystem 0
Uninterruptible Power Supply UPS Stopped Manual Own Process
c:\winnt\system32\ups.exe Normal LocalSystem 0
Utility Manager UtilMan Stopped Manual Own Process
c:\winnt\system32\utilman.exe Normal LocalSystem 0
Windows Time W32Time Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
World Wide Web Publishing Service W3SVCRunning Auto Share Process
c:\winnt\system32\inet_srv\inetinfo.exe Normal LocalSystem
0
Windows Management Instrumentation WinMgmt Running Auto Own
Process c:\winnt\system32\wbem\winmgmt.exe Ignore LocalSystem
0
Windows Management Instrumentation Driver Extensions Wmi Running
Manual Share Process c:\winnt\system32\services.exe Normal
LocalSystem 0

```

```

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006
Class Name: <NO CLASS>
Last Write Time: 9/19/2002 - 2:29 PM

```

```

Value 0
Name: Adaptive_IFS
Type: REG_SZ
Data: 1

```

```

Value 1
Name: AdaptiveCarrierLoss
Type: REG_SZ
Data: 1

```

```

Value 2
Name: AdaptiveStalledInterrupts
Type: REG_SZ
Data: 1

```

```

Value 3
Name: AdaptiveTransmitMethod
Type: REG_SZ
Data: 1

```

```

Value 4
Name: AlwaysConnectGoal
Type: REG_SZ
Data: 0

```

```

Value 5
Name: ANSAPI
Type: REG_DWORD
Data: 0x2

```

```

Value 6
Name: AutoPowerSaveModeEnabled
Type: REG_SZ
Data: 1

```

```

Value 7
Name: BusNumber
Type: REG_SZ
Data: 0

```

```

Value 8
Name: BusType
Type: REG_SZ
Data: 5

```

```

Value 9
Name: Characteristics
Type: REG_DWORD
Data: 0x84

```

```

Value 10
Name: Coalesce
Type: REG_SZ
Data: 1

```

```

Value 11
Name: CoInstallFlag
Type: REG_DWORD
Data: 0x80000004

```

```

Value 12
Name: ComponentId
Type: REG_SZ
Data: pci\ven_8086&dev_1229&subsys_004b110a

```

```

Value 13
Name: ConfigIFS
Type: REG_SZ
Data: 6

```

```

Value 14
Name: CPUSaver
Type: REG_SZ
Data: 1536

```

```

Value 15
Name: DeviceVxDsPrefix
Type: REG_SZ
Data: e100b

```

```

Value 16
Name: DriverDate
Type: REG_SZ
Data: 2-25-2002

```

Value 17  
 Name: DriverDateData  
 Type: REG\_BINARY  
 Data: 00000000 00 c0 1c 5e 8f bd c1 01 - .À.^.¼Á.

Value 18  
 Name: DriverDesc  
 Type: REG\_SZ  
 Data: Fujitsu Siemens Computers 82559-based Onboard Ethernet with WoL and AoL

Value 19  
 Name: DriverVersion  
 Type: REG\_SZ  
 Data: 6.1.3.0

Value 20  
 Name: EnablePME  
 Type: REG\_SZ  
 Data: 2

Value 21  
 Name: EnablePowerDownOnLinkLoss  
 Type: REG\_SZ  
 Data: 0

Value 22  
 Name: FlowControl  
 Type: REG\_SZ  
 Data: 0

Value 23  
 Name: Force10MbOnD3  
 Type: REG\_SZ  
 Data: 0

Value 24  
 Name: HardwareAddress  
 Type: REG\_SZ  
 Data: 00300519790F

Value 25  
 Name: HPQPriorityLevel  
 Type: REG\_SZ  
 Data: 4

Value 26  
 Name: InfPath  
 Type: REG\_SZ  
 Data: oem0.inf

Value 27  
 Name: InfSection  
 Type: REG\_SZ  
 Data: D101SG.ndi

Value 28  
 Name: InfSectionExt  
 Type: REG\_SZ  
 Data: .NTx86

Value 29  
 Name: IPsecTunnelMode  
 Type: REG\_SZ  
 Data: 1

Value 30  
 Name: LinkBasedLogin  
 Type: REG\_SZ  
 Data: 0

Value 31  
 Name: LogErrorMessage  
 Type: REG\_SZ  
 Data: 1

Value 32  
 Name: LogLinkStateEvent  
 Type: REG\_SZ  
 Data: 1

Value 33  
 Name: MatchingDeviceId  
 Type: REG\_SZ  
 Data: pci\ven\_8086&dev\_1229&subsys\_004b110a

Value 34  
 Name: MaxNumSecAssoc  
 Type: REG\_SZ  
 Data: 64

Value 35  
 Name: MWIEnable  
 Type: REG\_SZ  
 Data: 1

Value 36  
 Name: NetCfgInstanceId  
 Type: REG\_SZ  
 Data: {75A03E77-80A6-4DFD-A783-6876E710AB9F}

Value 37  
 Name: NumCoalesce  
 Type: REG\_SZ  
 Data: 32

Value 38  
 Name: NumRfd  
 Type: REG\_SZ  
 Data: 64

Value 39  
 Name: NumTcb  
 Type: REG\_SZ  
 Data: 32

Value 40  
 Name: Pcnic  
 Type: REG\_SZ  
 Data: 1

Value 41  
 Name: PnPCapabilities  
 Type: REG\_DWORD  
 Data: 0x38

Value 42  
 Name: ProviderName  
 Type: REG\_SZ  
 Data: Intel

Value 43  
 Name: SlotNumber  
 Type: REG\_SZ  
 Data: 10

Value 44  
 Name: SpeedDuplex  
 Type: REG\_SZ  
 Data: 4

Value 45  
 Name: TaggingMode  
 Type: REG\_SZ  
 Data: 0

Value 46  
 Name: TaskOffload  
 Type: REG\_SZ  
 Data: 0

Value 47  
 Name: Threshold  
 Type: REG\_SZ  
 Data: 32

Value 48  
 Name: UcodesW  
 Type: REG\_SZ  
 Data: 1

Value 49  
 Name: WakeOn  
 Type: REG\_SZ  
 Data: 0

Key Name: SOFTWARE\Microsoft\MSSQLServer

Class Name: <NO CLASS>  
 Last Write Time: 2/13/2001 - 10:00 AM

Key Name: SOFTWARE\Microsoft\MSSQLServer\Client  
 Class Name: <NO CLASS>  
 Last Write Time: 3/12/2001 - 3:20 PM

Value 0  
 Name: SharedMemoryOn  
 Type: REG\_DWORD  
 Data: 0

Key Name: SOFTWARE\Microsoft\MSSQLServer\Client\ConnectTo  
 Class Name: <NO CLASS>  
 Last Write Time: 10/8/2002 - 12:31 PM

Key Name: SOFTWARE\Microsoft\MSSQLServer\Client\DB-Lib  
 Class Name: <NO CLASS>  
 Last Write Time: 5/17/2001 - 9:31 AM

Value 0  
 Name: AutoAnsiToOem  
 Type: REG\_SZ  
 Data: OFF

Value 1  
 Name: UseIntlSettings  
 Type: REG\_SZ  
 Data: ON

Key Name: SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib  
 Class Name: <NO CLASS>  
 Last Write Time: 10/8/2002 - 1:09 PM

Value 0  
 Name: Encrypt  
 Type: REG\_DWORD  
 Data: 0

Value 1  
 Name: ProtocolOrder  
 Type: REG\_MULTI\_SZ  
 Data: via

Key Name: SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib>LastConnect  
 Class Name: <NO CLASS>  
 Last Write Time: 10/24/2002 - 10:51 AM

Value 0  
 Name: asterix  
 Type: REG\_SZ  
 Data: -721289208:via:ASTERIX:ASTERIX,1433,0

Key Name:  
SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib\Np  
Class Name: <NO CLASS>  
Last Write Time: 2/13/2001 - 10:02 AM  
Value 0  
Name: DefaultPipe  
Type: REG\_SZ  
Data: sql\query

Key Name:  
SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib\Tcp  
Class Name: <NO CLASS>  
Last Write Time: 2/13/2001 - 10:02 AM  
Value 0  
Name: DefaultPort  
Type: REG\_DWORD  
Data: 0x599

Key Name:  
SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib\VIA  
Class Name: <NO CLASS>  
Last Write Time: 10/9/2002 - 11:32 AM  
Value 0  
Name: DefaultClientNIC  
Type: REG\_SZ  
Data: 0

Value 1  
Name: DefaultServerPort  
Type: REG\_SZ  
Data: 0:1433

Value 2  
Name: RecognizedVendors  
Type: REG\_SZ  
Data: Giganet, ServerNet II,QLogic

Value 3  
Name: Vendor  
Type: REG\_SZ  
Data: Giganet

Key Name: SOFTWARE\Microsoft\MSSQLServer\Client\TDS  
Class Name: <NO CLASS>  
Last Write Time: 10/23/2002 - 2:22 PM  
Value 0  
Name: asterix  
Type: REG\_SZ  
Data: 7.0

Value 1  
Name: h250  
Type: REG\_SZ

Data: 7.0  
Value 2  
Name: h400  
Type: REG\_SZ  
Data: 7.0

Value 3  
Name: mogul  
Type: REG\_SZ  
Data: 7.0

Value 4  
Name: r450  
Type: REG\_SZ  
Data: 7.0

Value 5  
Name: via:asterix,1433,0  
Type: REG\_SZ  
Data: 7.0

Value 6  
Name: via:mogul,1433,0  
Type: REG\_SZ  
Data: 7.0

Key Name: SYSTEM\CurrentControlSet\Services\InetInfo  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 3:45 PM

Key Name: SYSTEM\CurrentControlSet\Services\InetInfo\Parameters  
Class Name: <NO CLASS>  
Last Write Time: 10/29/2002 - 1:47 PM

Value 0  
Name: DispatchEntries  
Type: REG\_MULTI\_SZ  
Data: LDAPSVC  
SMTPSVC

Value 1  
Name: ListenBackLog  
Type: REG\_DWORD  
Data: 0x4650

Value 2  
Name: PoolThreadLimit  
Type: REG\_DWORD  
Data: 0x26c

Value 3  
Name: ThreadTimeout  
Type: REG\_DWORD  
Data: 0x15180

```

Key Name:          SYSTEM\CurrentControlSet\Services\InetInfo\Performance
Class Name:       <NO CLASS>
Last Write Time:  10/31/2002 - 8:26 AM
Value 0
  Name:           Close
  Type:           REG_SZ
  Data:           CloseINFOPerformanceData
Value 1
  Name:           Collect
  Type:           REG_SZ
  Data:           CollectINFOPerformanceData
Value 2
  Name:           First Counter
  Type:           REG_DWORD
  Data:           0x802
Value 3
  Name:           First Help
  Type:           REG_DWORD
  Data:           0x803
Value 4
  Name:           Last Counter
  Type:           REG_DWORD
  Data:           0x842
Value 5
  Name:           Last Help
  Type:           REG_DWORD
  Data:           0x843
Value 6
  Name:           Library
  Type:           REG_SZ
  Data:           infoctrs.dll
Value 7
  Name:           Library Validation Code
  Type:           REG_BINARY
  Data:           00000000 7e 16 f0 b4 0a 95 c0 01 - 10 25 00 00 00 00 00 00
~.đ'..Ä..%.....
Value 8
  Name:           Open
  Type:           REG_SZ
  Data:           OpenINFOPerformanceData
Value 9
  Name:           WbemAdapFileSize
  Type:           REG_DWORD
  Data:           0x2510
Value 10

```

```

Name:             WbemAdapFileTime
Type:             REG_BINARY
Data:             00000000 00 9b 1a af 81 d4 c0 01 - ...-.ôÄ.
Value 11
  Name:           WbemAdapStatus
  Type:           REG_DWORD
  Data:           0
Key Name:         SYSTEM\CurrentControlSet\Services\Tcpip
Class Name:       Class
Last Write Time:  2/12/2001 - 5:40 PM
Value 0
  Name:           Description
  Type:           REG_SZ
  Data:           TCP/IP Protocol Driver
Value 1
  Name:           DisplayName
  Type:           REG_SZ
  Data:           TCP/IP Protocol Driver
Value 2
  Name:           ErrorControl
  Type:           REG_DWORD
  Data:           0x1
Value 3
  Name:           Group
  Type:           REG_SZ
  Data:           PNP_TDI
Value 4
  Name:           ImagePath
  Type:           REG_EXPAND_SZ
  Data:           System32\DRIVERS\tcpip.sys
Value 5
  Name:           Start
  Type:           REG_DWORD
  Data:           0x1
Value 6
  Name:           Tag
  Type:           REG_DWORD
  Data:           0x4
Value 7
  Name:           Type
  Type:           REG_DWORD
  Data:           0x1

```

Key Name: SYSTEM\CurrentControlSet\Services\Tcpip\Enum  
Class Name: <NO CLASS>  
Last Write Time: 9/27/2002 - 11:08 AM  
Value 0  
Name: 0  
Type: REG\_SZ  
Data: Root\LEGACY\_TCPIP\0000

Value 1  
Name: Count  
Type: REG\_DWORD  
Data: 0x1

Value 2  
Name: NextInstance  
Type: REG\_DWORD  
Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\Tcpip\Linkage  
Class Name: <NO CLASS>  
Last Write Time: 6/26/2002 - 10:24 AM  
Value 0  
Name: Bind  
Type: REG\_MULTI\_SZ  
Data: \Device\{75A03E77-80A6-4DFD-A783-6876E710AB9F}  
\Device\{BAFACDD3-FF58-4244-8343-63E521C918BC}  
\Device\NdisWanIp

Value 1  
Name: Export  
Type: REG\_MULTI\_SZ  
Data: \Device\Tcpip\_{75A03E77-80A6-4DFD-A783-6876E710AB9F}  
\Device\Tcpip\_{BAFACDD3-FF58-4244-8343-63E521C918BC}  
\Device\Tcpip\_{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}  
\Device\Tcpip\_{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}

Value 2  
Name: Route  
Type: REG\_MULTI\_SZ  
Data: "{75A03E77-80A6-4DFD-A783-6876E710AB9F}"  
"{BAFACDD3-FF58-4244-8343-63E521C918BC}"  
"NdisWanIp"

Key Name: SYSTEM\CurrentControlSet\Services\Tcpip\Parameters  
Class Name: Class  
Last Write Time: 7/4/2002 - 11:10 AM  
Value 0  
Name: AllowUnqualifiedQuery  
Type: REG\_DWORD  
Data: 0

Value 1  
Name: DataBasePath  
Type: REG\_EXPAND\_SZ  
Data: %SystemRoot%\System32\drivers\etc

Value 2  
Name: DeadGWDetectDefault  
Type: REG\_DWORD  
Data: 0x1

Value 3  
Name: Domain  
Type: REG\_SZ  
Data:

Value 4  
Name: DontAddDefaultGatewayDefault  
Type: REG\_DWORD  
Data: 0

Value 5  
Name: EnableICMPRedirect  
Type: REG\_DWORD  
Data: 0x1

Value 6  
Name: EnableSecurityFilters  
Type: REG\_DWORD  
Data: 0

Value 7  
Name: ForwardBroadcasts  
Type: REG\_DWORD  
Data: 0

Value 8  
Name: Hostname  
Type: REG\_SZ  
Data: C200CL1

Value 9  
Name: IPEnableRouter  
Type: REG\_DWORD  
Data: 0

Value 10  
Name: MaxUserPort  
Type: REG\_DWORD  
Data: 0xffff

Value 11  
Name: NameServer  
Type: REG\_SZ  
Data:

Value 12

Name: NV Hostname  
Type: REG\_SZ  
Data: C200CL1

Value 13  
Name: PrioritizeRecordData  
Type: REG\_DWORD  
Data: 0x1

Value 14  
Name: SearchList  
Type: REG\_SZ  
Data:

Value 15  
Name: UseDomainNameDevolution  
Type: REG\_DWORD  
Data: 0

Key Name:  
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 5:40 PM

Key Name:  
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters\NdisWanIp  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 5:41 PM  
Value 0  
Name: IpConfig  
Type: REG\_MULTI\_SZ  
Data: Tcpip\Parameters\Interfaces\{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}  
5E3D92E4F8AD} Tcpip\Parameters\Interfaces\{FD73BFE5-0643-4705-9572-

Value 1  
Name: IpInterfaces  
Type: REG\_BINARY  
Data: 00000000 14 ce 92 ca c2 2f f3 4f - b6 80 1f 7d f9 59 4e af  
.f.ÊÂ/óO¶..}ùYN  
00000010 e5 bf 73 fd 43 06 05 47 - 95 72 5e 3d 92 e4 f8 ad  
â¿sÿC..G.r^=.ãø-

Value 2  
Name: LLInterface  
Type: REG\_SZ  
Data: WANARP

Value 3  
Name: NumInterfaces  
Type: REG\_DWORD  
Data: 0x2

Key Name:  
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters\{75A03E77-80A6-4DFD-A783-6876E710AB9F}  
Class Name: <NO CLASS>  
Last Write Time: 6/26/2002 - 10:24 AM  
Value 0  
Name: IpConfig  
Type: REG\_MULTI\_SZ  
Data: Tcpip\Parameters\Interfaces\{75A03E77-80A6-4DFD-A783-6876E710AB9F}

Value 1  
Name: LLInterface  
Type: REG\_SZ  
Data:

Key Name:  
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters\{BAFACDD3-FF58-4244-8343-63E521C918BC}  
Class Name: <NO CLASS>  
Last Write Time: 6/26/2002 - 10:20 AM  
Value 0  
Name: IpConfig  
Type: REG\_MULTI\_SZ  
Data: Tcpip\Parameters\Interfaces\{BAFACDD3-FF58-4244-8343-63E521C918BC}

Value 1  
Name: LLInterface  
Type: REG\_SZ  
Data:

Key Name:  
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\DNSRegisteredAdapters  
Class Name: DynDnsRootClass  
Last Write Time: 2/12/2001 - 5:40 PM

Key Name:  
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 5:40 PM

Key Name:  
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{75A03E77-80A6-4DFD-A783-6876E710AB9F}  
Class Name: <NO CLASS>  
Last Write Time: 9/19/2002 - 4:00 PM  
Value 0  
Name: DefaultGateway  
Type: REG\_MULTI\_SZ

Data:

Value 1  
 Name: DefaultGatewayMetric  
 Type: REG\_MULTI\_SZ  
 Data:

Value 2  
 Name: DisableDynamicUpdate  
 Type: REG\_DWORD  
 Data: 0x1

Value 3  
 Name: Domain  
 Type: REG\_SZ  
 Data:

Value 4  
 Name: EnableAdapterDomainNameRegistration  
 Type: REG\_DWORD  
 Data: 0

Value 5  
 Name: EnableDeadGWDetect  
 Type: REG\_DWORD  
 Data: 0x1

Value 6  
 Name: EnableDHCP  
 Type: REG\_DWORD  
 Data: 0

Value 7  
 Name: InterfaceMetric  
 Type: REG\_DWORD  
 Data: 0x1

Value 8  
 Name: IPAddress  
 Type: REG\_MULTI\_SZ  
 Data: 129.103.211.1

Value 9  
 Name: NameServer  
 Type: REG\_SZ  
 Data:

Value 10  
 Name: NTEContextList  
 Type: REG\_MULTI\_SZ  
 Data: 0x00000002

Value 11  
 Name: RawIPAllowedProtocols

Type: REG\_MULTI\_SZ  
 Data: 0

Value 12  
 Name: SubnetMask  
 Type: REG\_MULTI\_SZ  
 Data: 255.255.255.0

Value 13  
 Name: TCPAllowedPorts  
 Type: REG\_MULTI\_SZ  
 Data: 0

Value 14  
 Name: UDPAllowedPorts  
 Type: REG\_MULTI\_SZ  
 Data: 0

Value 15  
 Name: UseZeroBroadcast  
 Type: REG\_DWORD  
 Data: 0

Key Name:  
 SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{BAFACDD3-  
 FF58-4244-8343-63E521C918BC}  
 Class Name: <NO CLASS>  
 Last Write Time: 8/30/2002 - 1:09 PM

Value 0  
 Name: DefaultGateway  
 Type: REG\_MULTI\_SZ  
 Data:

Value 1  
 Name: DefaultGatewayMetric  
 Type: REG\_MULTI\_SZ  
 Data:

Value 2  
 Name: DisableDynamicUpdate  
 Type: REG\_DWORD  
 Data: 0x1

Value 3  
 Name: Domain  
 Type: REG\_SZ  
 Data:

Value 4  
 Name: EnableAdapterDomainNameRegistration  
 Type: REG\_DWORD

Data: 0

Value 5  
 Name: EnableDeadGWDetect  
 Type: REG\_DWORD  
 Data: 0x1

Value 6  
 Name: EnableDHCP  
 Type: REG\_DWORD  
 Data: 0

Value 7  
 Name: InterfaceMetric  
 Type: REG\_DWORD  
 Data: 0x1

Value 8  
 Name: IPAddress  
 Type: REG\_MULTI\_SZ  
 Data: 129.103.182.211

Value 9  
 Name: NameServer  
 Type: REG\_SZ  
 Data:

Value 10  
 Name: NTEContextList  
 Type: REG\_MULTI\_SZ  
 Data:

Value 11  
 Name: RawIPAllowedProtocols  
 Type: REG\_MULTI\_SZ  
 Data: 0

Value 12  
 Name: SubnetMask  
 Type: REG\_MULTI\_SZ  
 Data: 255.255.255.0

Value 13  
 Name: TCPAllowedPorts  
 Type: REG\_MULTI\_SZ  
 Data: 0

Value 14  
 Name: UDPAllowedPorts  
 Type: REG\_MULTI\_SZ  
 Data: 0

Value 15  
 Name: UseZeroBroadcast  
 Type: REG\_DWORD  
 Data: 0

Key Name:  
 SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}  
 Class Name: <NO CLASS>  
 Last Write Time: 2/12/2001 - 5:41 PM

Value 0  
 Name: DefaultGateway  
 Type: REG\_MULTI\_SZ  
 Data:

Value 1  
 Name: DontAddDefaultGateway  
 Type: REG\_DWORD  
 Data: 0

Value 2  
 Name: EnableDeadGWDetect  
 Type: REG\_DWORD  
 Data: 0x1

Value 3  
 Name: EnableDHCP  
 Type: REG\_DWORD  
 Data: 0

Value 4  
 Name: IPAddress  
 Type: REG\_MULTI\_SZ  
 Data: 0.0.0.0

Value 5  
 Name: SubnetMask  
 Type: REG\_MULTI\_SZ  
 Data: 0.0.0.0

Value 6  
 Name: UseZeroBroadcast  
 Type: REG\_DWORD  
 Data: 0

Key Name:  
 SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}  
 Class Name: <NO CLASS>  
 Last Write Time: 2/12/2001 - 5:41 PM

Value 0

```

Name:          DefaultGateway
Type:          REG_MULTI_SZ
Data:

Value 1
Name:          DontAddDefaultGateway
Type:          REG_DWORD
Data:          0

Value 2
Name:          EnableDeadGWDetect
Type:          REG_DWORD
Data:          0x1

Value 3
Name:          EnabledDHCP
Type:          REG_DWORD
Data:          0

Value 4
Name:          IPAddress
Type:          REG_MULTI_SZ
Data:          0.0.0.0

Value 5
Name:          SubnetMask
Type:          REG_MULTI_SZ
Data:          0.0.0.0

Value 6
Name:          UseZeroBroadcast
Type:          REG_DWORD
Data:          0

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\PersistentRoutes
Class Name:    <NO CLASS>
Last Write Time:  2/12/2001 - 5:40 PM

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Winsock
Class Name:    <NO CLASS>
Last Write Time:  2/12/2001 - 5:40 PM
Value 0
Name:          HelperDllName
Type:          REG_EXPAND_SZ
Data:          %SystemRoot%\System32\wshtcpip.dll

Value 1
Name:          Mapping
Type:          REG_BINARY
Data:

```

```

00000000  0b 00 00 00 03 00 00 00 - 02 00 00 00 01 00 00 00
.....
00000010  06 00 00 00 02 00 00 00 - 01 00 00 00 00 00 00 00
.....
00000020  02 00 00 00 00 00 00 00 - 06 00 00 00 00 00 00 00
.....
00000030  00 00 00 00 06 00 00 00 - 00 00 00 00 01 00 00 00
.....
00000040  06 00 00 00 02 00 00 00 - 02 00 00 00 11 00 00 00
.....
00000050  02 00 00 00 02 00 00 00 - 00 00 00 00 02 00 00 00
.....
00000060  00 00 00 00 11 00 00 00 - 00 00 00 00 00 00 00 00
.....
00000070  11 00 00 00 00 00 00 00 - 02 00 00 00 11 00 00 00
.....
00000080  02 00 00 00 03 00 00 00 - 00 00 00 00
.....

```

```

Value 2
Name:          MaxSockAddrLength
Type:          REG_DWORD
Data:          0x10

Value 3
Name:          MinSockAddrLength
Type:          REG_DWORD
Data:          0x10

Value 4
Name:          UseDelayedAcceptance
Type:          REG_DWORD
Data:          0

Key Name:      SYSTEM\CurrentControlSet\Services\Tcpip\Performance
Class Name:    <NO CLASS>
Last Write Time:  9/27/2002 - 11:09 AM
Value 0
Name:          Close
Type:          REG_SZ
Data:          CloseTcpIpPerformanceData

Value 1
Name:          Collect
Type:          REG_SZ
Data:          CollectTcpIpPerformanceData

Value 2
Name:          Library
Type:          REG_SZ
Data:          Perfctrs.dll

Value 3
Name:          Open
Type:          REG_SZ

```

Data: OpenTcpIpPerformanceData

Value 4  
 Name: WbemAdapFileSize  
 Type: REG\_DWORD  
 Data: 0xa310

Value 5  
 Name: WbemAdapFileTime  
 Type: REG\_BINARY  
 Data: 00000000 00 9b 1a af 81 d4 c0 01 - ...-ÔÀ.

Value 6  
 Name: WbemAdapStatus  
 Type: REG\_DWORD  
 Data: 0

Key Name: SYSTEM\CurrentControlSet\Services\Tcpip\Security  
 Class Name: <NO CLASS>  
 Last Write Time: 2/12/2001 - 5:40 PM

Value 0  
 Name: Security  
 Type: REG\_BINARY  
 Data: 00000000 01 00 14 80 a0 00 00 00 - ac 00 00 00 14 00 00 00  
 ....  
 00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00  
 0.....  
 00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00  
 Ÿ.....  
 00000030 02 00 70 00 04 00 00 00 - 00 00 18 00 fd 01 02 00  
 ..p.....Ÿ...  
 00000040 01 01 00 00 00 00 00 05 - 12 00 00 00 02 00 00 00  
 .....  
 00000050 00 00 1c 00 ff 01 0f 00 - 01 02 00 00 00 00 00 05  
 ..Ÿ.....  
 00000060 20 00 00 00 20 02 00 00 - 03 00 00 00 00 00 18 00 ...  
 .....  
 00000070 8d 01 02 00 01 01 00 00 - 00 00 00 05 0b 00 00 00  
 .....  
 00000080 20 02 00 00 00 00 1c 00 - fd 01 02 00 01 02 00 00  
 .....Ÿ.....  
 00000090 00 00 00 05 20 00 00 00 - 23 02 00 00 03 00 00 00 ....  
 ...#.....  
 000000a0 01 01 00 00 00 00 00 05 - 12 00 00 00 01 01 00 00  
 .....  
 000000b0 00 00 00 05 12 00 00 00 - .....

Key Name: SYSTEM\CurrentControlSet\Services\Tcpip\ServiceProvider  
 Class Name: <NO CLASS>  
 Last Write Time: 2/12/2001 - 5:40 PM  
 Value 0

Name: Class  
 Type: REG\_DWORD  
 Data: 0x8

Value 1  
 Name: DnsPriority  
 Type: REG\_DWORD  
 Data: 0x7d0

Value 2  
 Name: HostsPriority  
 Type: REG\_DWORD  
 Data: 0x1f4

Value 3  
 Name: LocalPriority  
 Type: REG\_DWORD  
 Data: 0x1f3

Value 4  
 Name: Name  
 Type: REG\_SZ  
 Data: TCP/IP

Value 5  
 Name: NetbtPriority  
 Type: REG\_DWORD  
 Data: 0x7d1

Value 6  
 Name: ProviderPath  
 Type: REG\_EXPAND\_SZ  
 Data: %SystemRoot%\System32\wsock32.dll

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC  
 Class Name: <NO CLASS>  
 Last Write Time: 8/30/2002 - 1:13 PM

Value 0  
 Name: DependOnGroup  
 Type: REG\_MULTI\_SZ  
 Data:

Value 1  
 Name: DependOnService  
 Type: REG\_MULTI\_SZ  
 Data: IISADMIN

Value 2  
 Name: Description  
 Type: REG\_SZ  
 Data: Provides Web connectivity and administration through the Internet Information Services snap-in.

Value 3

Name: DisplayName  
Type: REG\_SZ

Data: World Wide Web Publishing Service

Value 4  
Name: ErrorControl  
Type: REG\_DWORD  
Data: 0x1

Value 5  
Name: ImagePath  
Type: REG\_EXPAND\_SZ  
Data: C:\WINNT\System32\inetsrv\inetinfo.exe

Value 6  
Name: ObjectName  
Type: REG\_SZ  
Data: LocalSystem

Value 7  
Name: Start  
Type: REG\_DWORD  
Data: 0x2

Value 8  
Name: Type  
Type: REG\_DWORD  
Data: 0x20

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\ASP  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 4:46 PM

Value 0  
Name: NOTE  
Type: REG\_SZ  
Data: This is for backward compatibility only.

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\ASP\Parameters  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 4:46 PM

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\Enum  
Class Name: <NO CLASS>  
Last Write Time: 9/27/2002 - 11:08 AM

Value 0  
Name: 0  
Type: REG\_SZ  
Data: Root\LEGACY\_W3SVC\0000

Value 1  
Name: Count  
Type: REG\_DWORD  
Data: 0x1

Value 2  
Name: NextInstance  
Type: REG\_DWORD  
Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\Parameters  
Class Name: <NO CLASS>  
Last Write Time: 3/2/2001 - 2:38 PM

Value 0  
Name: AcceptExOutstanding  
Type: REG\_DWORD  
Data: 0x28

Value 1  
Name: AccessDeniedMessage  
Type: REG\_SZ  
Data: Error: Access is Denied.

Value 2  
Name: CertMapList  
Type: REG\_SZ  
Data: C:\WINNT\System32\inetsrv\iisrmap.dll

Value 3  
Name: Filter DLLs  
Type: REG\_SZ  
Data:

Value 4  
Name: InstallPath  
Type: REG\_SZ  
Data: C:\WINNT\System32\inetsrv

Value 5  
Name: LogFileDirectory  
Type: REG\_SZ  
Data: C:\WINNT\System32\LogFiles

Value 6  
Name: MajorVersion  
Type: REG\_DWORD  
Data: 0x5

Value 7  
Name: MinorVersion  
Type: REG\_DWORD  
Data: 0

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\ADCLaunch  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 4:47 PM

Key Name:  
SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\ADCLaunch\AdvancedData  
Factory  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 4:47 PM

Key Name:  
SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\ADCLaunch\RDSServer.Da  
taFactory  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 4:47 PM

Key Name:  
SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\Script Map  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 4:57 PM

Key Name:  
SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\Virtual Roots  
Class Name: <NO CLASS>  
Last Write Time: 2/13/2001 - 9:46 AM

Value 0  
Name: /  
Type: REG\_SZ  
Data: c:\inetpub\wwwroot,,205

Value 1  
Name: /IISAdmin  
Type: REG\_SZ  
Data: C:\WINNT\System32\inetsrv\iisadmin,,201

Value 2  
Name: /IISHelp  
Type: REG\_SZ  
Data: c:\winnt\help\iishelp,,201

Value 3  
Name: /IISamples  
Type: REG\_SZ  
Data: c:\inetpub\iissamples,,201

Value 4  
Name: /MSADC  
Type: REG\_SZ  
Data: c:\program files\common files\system\msadc,,205

Value 5  
Name: /Printers  
Type: REG\_SZ  
Data: C:\WINNT\web\printers,,201

Value 6  
Name: /Scripts  
Type: REG\_SZ  
Data: c:\inetpub\scripts,,204

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\Performance  
Class Name: <NO CLASS>  
Last Write Time: 9/27/2002 - 11:09 AM

Value 0  
Name: Close  
Type: REG\_SZ  
Data: CloseW3PerformanceData

Value 1  
Name: Collect  
Type: REG\_SZ  
Data: CollectW3PerformanceData

Value 2  
Name: First Counter  
Type: REG\_DWORD  
Data: 0x844

Value 3  
Name: First Help  
Type: REG\_DWORD  
Data: 0x845

Value 4  
Name: Last Counter  
Type: REG\_DWORD  
Data: 0x8e6

Value 5  
Name: Last Help  
Type: REG\_DWORD  
Data: 0x8e7

Value 6  
Name: Library  
Type: REG\_SZ  
Data: w3ctrs.dll

Value 7  
Name: Library Validation Code  
Type: REG\_BINARY  
Data: 00000000 e0 81 84 b7 0a 95 c0 01 - 10 3d 00 00 00 00 00 00  
à.....À..=.....

Value 8  
Name: Open  
Type: REG\_SZ  
Data: OpenW3PerformanceData

Value 9  
Name: WbemAdapFileSize  
Type: REG\_DWORD  
Data: 0x1d10

Value 10  
Name: WbemAdapFileTime  
Type: REG\_BINARY  
Data: 00000000 00 9b 1a af 81 d4 c0 01 - ...-.ÔÀ.

Value 11  
Name: WbemAdapStatus  
Type: REG\_DWORD  
Data: 0

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\Security  
Class Name: <NO CLASS>  
Last Write Time: 2/12/2001 - 4:46 PM

Value 0  
Name: Security  
Type: REG\_BINARY  
Data: 00000000 01 00 14 80 a0 00 00 00 - ac 00 00 00 14 00 00 00  
.....  
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00  
0.....  
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00  
ÿ.....  
00000030 02 00 70 00 04 00 00 00 - 00 00 18 00 fd 01 02 00  
..p.....ÿ...  
00000040 01 01 00 00 00 00 00 05 - 12 00 00 00 74 00 6f 00  
.....t.o.  
00000050 00 00 1c 00 ff 01 0f 00 - 01 02 00 00 00 00 00 05  
....ÿ.....  
00000060 20 00 00 00 20 02 00 00 - 72 00 73 00 00 00 18 00 ...  
...r.s.....  
00000070 8d 01 02 00 01 01 00 00 - 00 00 00 05 0b 00 00 00  
.....  
00000080 20 02 00 00 00 00 1c 00 - fd 01 02 00 01 02 00 00  
.....ÿ.....  
00000090 00 00 00 05 20 00 00 00 - 23 02 00 00 72 00 73 00 ....  
...#...r.s.  
000000a0 01 01 00 00 00 00 00 05 - 12 00 00 00 01 01 00 00  
.....  
000000b0 00 00 00 05 12 00 00 00 - .....

Key Name: SOFTWARE\Microsoft\TPCC  
Class Name: <NO CLASS>  
Last Write Time: 10/29/2002 - 10:25 AM

Value 0  
Name: COM\_SinglePool  
Type: REG\_SZ  
Data: YES

Value 1  
Name: DB\_Protocol  
Type: REG\_SZ  
Data: ODBC

Value 2  
Name: DbName  
Type: REG\_SZ  
Data: tpcc

Value 3  
Name: DbPassword  
Type: REG\_SZ  
Data:

Value 4  
Name: DbServer  
Type: REG\_SZ  
Data: asterix

Value 5  
Name: DbUser  
Type: REG\_SZ  
Data: sa

Value 6  
Name: MaxConnections  
Type: REG\_DWORD  
Data: 0x4844

Value 7  
Name: MaxPendingDeliveries  
Type: REG\_DWORD  
Data: 0x708

Value 8  
Name: NumberOfDeliveryThreads  
Type: REG\_DWORD  
Data: 0x6

Value 9  
Name: Path  
Type: REG\_SZ  
Data: c:\inetpub\wwwroot\

Value 10  
Name: TxnMonitor  
Type: REG\_SZ  
Data: COM

Key Name: SYSTEM\CurrentControlSet\Services\qlvika  
Class Name: <NO CLASS>  
Last Write Time: 8/15/2002 - 2:40 PM

Value 0  
Name: ErrorControl  
Type: REG\_DWORD  
Data: 0x1

Value 1

Name: group  
 Type: REG\_SZ  
 Data: MVIA

Value 2  
 Name: ImagePath  
 Type: REG\_EXPAND\_SZ  
 Data: System32\DRIVERS\qlvika.sys

Value 3  
 Name: start  
 Type: REG\_DWORD  
 Data: 0x2

Value 4  
 Name: Tag  
 Type: REG\_DWORD  
 Data: 0x1

Value 5  
 Name: type  
 Type: REG\_DWORD  
 Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\qlvika\Adapters  
 Class Name: <NO CLASS>  
 Last Write Time: 8/15/2002 - 2:48 PM

Key Name: SYSTEM\CurrentControlSet\Services\qlvika\Adapters\210000E08B072AB0  
 Class Name: <NO CLASS>  
 Last Write Time: 8/15/2002 - 2:55 PM

Value 0  
 Name: IPAddress  
 Type: REG\_MULTI\_SZ  
 Data: 129.103.192.211

Key Name: SYSTEM\CurrentControlSet\Services\qlvika\Enum  
 Class Name: <NO CLASS>  
 Last Write Time: 10/24/2002 - 1:57 PM

Value 0  
 Name: 0  
 Type: REG\_SZ  
 Data: Root\SCSIADAPTER\0000

Value 1  
 Name: Count  
 Type: REG\_DWORD  
 Data: 0x1

Value 2  
 Name: NextInstance  
 Type: REG\_DWORD

Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\qlvika\Parameters  
 Class Name: <NO CLASS>  
 Last Write Time: 10/7/2002 - 2:39 PM

Value 0  
 Name: IuBuffers  
 Type: REG\_DWORD  
 Data: 0x100

Value 1  
 Name: MaxCQEntries  
 Type: REG\_DWORD  
 Data: 0x2000

Value 2  
 Name: MaxCQs  
 Type: REG\_DWORD  
 Data: 0x400

Value 3  
 Name: MaxPTags  
 Type: REG\_DWORD  
 Data: 0x800

Value 4  
 Name: MaxRegisterMBytes  
 Type: REG\_DWORD  
 Data: 0x200

Value 5  
 Name: MaxRegisterRdmaMBytes  
 Type: REG\_DWORD  
 Data: 0x200

Value 6  
 Name: MaxRegisterRegions  
 Type: REG\_DWORD  
 Data: 0x1000

Value 7  
 Name: MaxTransferSize  
 Type: REG\_DWORD  
 Data: 0x10000

Value 8  
 Name: MaxVIs  
 Type: REG\_DWORD  
 Data: 0x400

Value 9  
 Name: RecvDescQuota  
 Type: REG\_DWORD  
 Data: 0x8

Value 10  
Name: SendDescQuota  
Type: REG\_DWORD  
Data: 0x8

Value 11  
Name: SupportPrototypeCards  
Type: REG\_DWORD  
Data: 0

Key Name: SYSTEM\CurrentControlSet\Services\qlvika\Security  
Class Name: <NO CLASS>  
Last Write Time: 8/15/2002 - 2:40 PM

Value 0  
Name: Security  
Type: REG\_BINARY  
Data:  
00000000 01 00 14 80 a0 00 00 00 - ac 00 00 00 14 00 00 00  
.....  
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00  
0.....  
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00  
ÿ.....  
00000030 02 00 70 00 04 00 00 00 - 00 00 18 00 fd 01 02 00  
..p.....ÿ...  
00000040 01 01 00 00 00 00 05 - 12 00 00 00 72 00 74 00  
.....r.t.  
00000050 00 00 1c 00 ff 01 0f 00 - 01 02 00 00 00 00 00 05  
.....ÿ.....  
00000060 20 00 00 00 20 02 00 00 - 00 00 00 00 00 00 18 00 ...  
.....  
00000070 8d 01 02 00 01 01 00 00 - 00 00 00 05 0b 00 00 00  
.....  
00000080 20 02 00 00 00 00 1c 00 - fd 01 02 00 01 02 00 00  
.....ÿ.....  
00000090 00 00 00 05 20 00 00 00 - 23 02 00 00 00 00 00 00 ....  
...#.....  
000000a0 01 01 00 00 00 00 05 - 12 00 00 00 01 01 00 00  
.....  
000000b0 00 00 00 05 12 00 00 00 - .....

Component Services Configuration:  
COM+ Component TPCC.AllTXns Settings:

- Enable object pooling
- Minimum pool size 88
- Maximum pool size 88
- Creation timeout 60,000
- Enable object construction
- Enable just in time activation
- Concurrency required

**This section discloses the RTE parameters used on the PRIMERGY 870 system.**

Profile: R450\_HTML\_5500  
File Path: F:\R450\R450\_HTML\_5500.pro  
Version: 1.0.1

Number of Engines: 15

Name: DRIVER01  
Description: B210RT4 CL1  
Directory: c:\b210rt4\_cl1.log  
Machine: b210rt4  
Parameter Set: All\_Times3  
Index: 0  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER1424171  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 0

Name: DRIVER02  
Description: B210RT4 CL2  
Directory: c:\b210rt4\_cl2.log  
Machine: b210rt4  
Parameter Set: All\_Times3  
Index: 100000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER2559625  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 1

Name: DRIVER03  
Description: B210RT4 CL3  
Directory: c:\b210rt4\_cl3.log  
Machine: b210rt4  
Parameter Set: All\_Times3  
Index: 200000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER3602875  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 0

Name: DRIVER04  
Description: B210RT5 CL1  
Directory: c:\b210rt5\_cl1.log  
Machine: b210rt5  
Parameter Set: All\_Times3  
Index: 300000000  
Seed: 11063  
Configured Users: 3600  
Pipe Name: DRIVER4642312  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 1

Name: DRIVER05  
Description: B210RT5 CL2  
Directory: c:\b210rt5\_cl2.log  
Machine: b210rt5  
Parameter Set: All\_Times3  
Index: 400000000  
Seed: 11063  
Configured Users: 3600  
Pipe Name: DRIVER5691546  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 0

Name: DRIVER06  
Description: B210RT5 CL3  
Directory: c:\b210rt5\_cl3.log  
Machine: b210rt5  
Parameter Set: All\_Times3  
Index: 500000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER6744125  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 1

Name: DRIVER07  
Description: B210RT6 CL1  
Directory: c:\b210rt6\_cl1.log  
Machine: b210rt6  
Parameter Set: All\_Times3  
Index: 600000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER7781125  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 0

Name: DRIVER08  
Description: B210RT6 CL2  
Directory: c:\b210rt6\_cl2.log  
Machine: b210rt6  
Parameter Set: All\_Times3  
Index: 700000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER8812109  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 1

Name: DRIVER09  
Description: B210RT6 CL3  
Directory: c:\b210rt6\_cl3.log  
Machine: b210rt6  
Parameter Set: All\_Times3  
Index: 800000000  
Seed: 11063  
Configured Users: 3600  
Pipe Name: DRIVER9847031  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 0

Name: DRIVER10  
Description: tuerkis CL1  
Directory: f:\tuerkis\_cl1.log  
Machine: tuerkis  
Parameter Set: All\_Times3  
Index: 900000000  
Seed: 11063  
Configured Users: 3600  
Pipe Name: DRIVER10879078  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 0

Name: DRIVER11  
Description: tuerkis CL2  
Directory: f:\tuerkis\_cl2.log  
Machine: tuerkis  
Parameter Set: All\_Times3  
Index: 1000000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER11911953  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 1

Name: DRIVER12  
Description: tuerkis CL3  
Directory: f:\tuerkis\_cl3.log  
Machine: tuerkis  
Parameter Set: All\_Times3  
Index: 1100000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER12937328  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 2

Name: DRIVER13  
Description: violet CL1  
Directory: c:\violet\_cl1.log  
Machine: violet  
Parameter Set: All\_Times3  
Index: 1200000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER134383562  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 0

Name: DRIVER14  
Description: violet CL2  
Directory: c:\violet\_cl2.log  
Machine: violet  
Parameter Set: All\_Times3  
Index: 1300000000  
Seed: 11063  
Configured Users: 3700  
Pipe Name: DRIVER144579000  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 1

Name: DRIVER15  
Description: violet CL3  
Directory: c:\violet\_cl3.log  
Machine: violet  
Parameter Set: All\_Times3  
Index: 1400000000  
Seed: 11063  
Configured Users: 3600  
Pipe Name: DRIVER155027046  
Connect Rate: 200  
Start Rate: 200  
CLIENT\_NURAND: 233  
CPU: 2

Number of User groups: 15

Driver Engine: DRIVER01  
IIS Server: c200cl1  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 1 - 370  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER02  
IIS Server: c200cl2  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 371 - 740  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER03  
IIS Server: c200cl3  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 741 - 1110  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER04  
IIS Server: c200cl1  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 1111 - 1470  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3600  
District id: 1  
Scale Down: No

Driver Engine: DRIVER05  
IIS Server: c200cl2  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 1471 - 1830

w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3600  
District id: 1  
Scale Down: No

Driver Engine: DRIVER06  
IIS Server: c200cl3  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 1831 - 2200  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER07  
IIS Server: c200cl1  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 2201 - 2570  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER08  
IIS Server: c200cl2  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 2571 - 2940  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER09  
IIS Server: c200cl3  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 2941 - 3300  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3600  
District id: 1  
Scale Down: No

Driver Engine: DRIVER10  
IIS Server: c200cl1

SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 3301 - 3660  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3600  
District id: 1  
Scale Down: No

Driver Engine: DRIVER11  
IIS Server: c200cl2  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 3661 - 4030  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER12  
IIS Server: c200cl3  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 4031 - 4400  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER13  
IIS Server: c200cl1  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 4401 - 4770  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1  
Scale Down: No

Driver Engine: DRIVER14  
IIS Server: c200cl2  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 4771 - 5140  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3700  
District id: 1

Scale Down: No

Driver Engine: DRIVER15  
IIS Server: c200cl3  
SQL Server: asterix  
User: sa  
Protocol: Html  
w\_id Range: 5141 - 5500  
w\_id Max Warehouse: 5500  
Scale: Normal  
User Count: 3600  
District id: 1  
Scale Down: No

Number of Parameter Sets: 2

```
~Default
Default Parameter Set
      Txn   Think   Key   RT   RT   Menu
      Weight Time   Time Delay Fence Delay
5.00  0.10  New Order   10.00  12.05  18.01  0.10
5.00  0.10  Payment    10.00  12.05   3.01  0.10
5.00  0.10  Delivery    1.00   5.05   2.01  0.10
5.00  0.10  Stock Level 1.00   5.05   2.01  0.10
20.00 0.10  Order Status 1.00  10.05   2.01  0.10
5.00  0.10

All_Times3
Run 2H
      Txn   Think   Key   RT   RT   Menu
      Weight Time   Time Delay Fence Delay
5.00  0.10  New Order   44.90  12.05  18.01  0.10
5.00  0.10  Payment    43.02  12.05   3.01  0.10
5.00  0.10  Delivery    4.02   5.05   2.01  0.10
5.00  0.10  Stock Level 4.03   5.05   2.01  0.10
20.00 0.10  Order Status 4.03  10.05   2.01  0.10
5.00  0.10
```

**This section discloses the Microsoft SQL Server 2000 Enterprise Edition SP3 parameters used on the PRIMERGY R450 server system.**

Microsoft SQL Server Startup Parameters:

```
sqlservr -c -x -T3502 -g80
```

where:

```
-c Start SQL Server independently of the Windows NT Service Control Manager
-x Disables the keeping of CPU time and cache-hit ratio statistics
-T3502 Prints a message to the SQL Server log at start and end of each checkpoint
-g80 memory in MB reserved for memory requests outside the buffer pool
```

Microsoft SQL Server Stack Size:

The default stack size for Microsoft SQL Server 2000 was changed using the EDITBIN utility:  
editbin /STACK:131072

```
1> 2> 3> 4> 5> 6> 7> 8> 9> 10> 11>
-- File:      VERSION.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.22
--           Copyright Microsoft, 2001
-- Purpose:   Returns SQL Server version string
```

```
print " "
select convert(char(30), getdate(),9)
print " "
```

```
-----
Oct 31 2002 11:47:05:290AM
```

(1 row affected)

```
1> 2> 3>
select @@version
```

```
-----
-----
-----
Microsoft SQL Server 2000 - 8.00.725 (Intel X86)
Sep 23 2002 13:22:20
Cop
yright (c) 1988-2002 Microsoft Corporation
Enterprise Edition on Windo
ws NT 5.2 (Build 3663: )
```

(1 row affected)

```
1> 2>
1> 2> 3> 4> 5> 6> 7> 8> 9> 10>
-- File:      CONFIG.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.22
--           Copyright Microsoft, 2001
-- Purpose:   Collects SQL Server configuration parameters
```

```
print " "
select convert(char(30), getdate(),9)
print " "
```

```
-----
Oct 22 2002 10:28:45:007AM
```

(1 row affected)

```
1> 2> 3> DBCC execution completed. If DBCC printed error messages, contact your system administrator.
```

Configuration option 'show advanced options' changed from 1 to 1. Run the RECONFIGURE statement to install.

```
sp_configure "show advanced",1
1> 2> reconfigure with override
1> 2> sp_configure
```

name	minimum	maximum	config_value	run_value
affinity mask	-2147483648	2147483647	255	255
allow updates	0	1	0	0
awe enabled	0	1	1	1
c2 audit mode	0	1	0	0
cost threshold for parallelism	0	32767	5	5
Cross DB Ownership Chaining	0	1	0	0
cursor threshold	-1	2147483647	-1	-1
default full-text language	0	2147483647	1033	1033
default language	0	9999	0	0
fill factor (%)	0	100	0	0
index create memory (KB)	704	2147483647	0	0
lightweight pooling	0	1	1	1
locks	5000	2147483647	0	0
max degree of parallelism	0	32	1	1
max server memory (MB)	4	2147483647	2147483647	2147483647
max text repl size (B)	0	2147483647	65536	65536
max worker threads	32	32767	304	304
media retention	0	365	0	0
min memory per query (KB)	512	2147483647	512	512
min server memory (MB)	0	2147483647	0	0
nested triggers	0	1	1	1
network packet size (B)	512	65536	512	512
open objects	0	2147483647	0	0
priority boost	0	1	1	1
query governor cost limit	0	2147483647	0	0
query wait (s)	-1	2147483647	-1	-1
recovery interval (min)	0	32767	116	116
remote access	0	1	1	1
remote login timeout (s)	0	2147483647	20	20
remote proc trans	0	1	0	0
remote query timeout (s)	0	2147483647	600	600
scan for startup procs	0	1	0	0
set working set size	0	1	0	0
show advanced options	0	1	1	1
two digit year cutoff	1753	9999	2049	2049
user connections	0	32767	0	0
user options	0	32767	0	0

1>

## Appendix D – Space Calculation

Note : Numbers are in KBytes unless otherwise specified						
<b>Warehouses</b>	<b>5500</b>	<b>tpmC</b>	68264	<b>tpmC/W</b>	12.41	
<b>Table</b>	<b>Rows</b>	<b>Data</b>	<b>Index</b>	<b>5% Space</b>	<b>8H Space</b>	<b>Total Space</b>
Warehouse	5,500	592	56	32		680
District	55,000	6,112	72	309		6,493
Item	100,000	9,528	72	480		10,080
New-order	49,500,000	782,616	1,808		440,000	1,224,424
History	165,000,000	9,166,680	48		1,820,386	10,987,114
Orders	165,000,000	5,057,472	2,299,800		1,461,053	8,818,325
Customer	165,000,000	120,000,000	7,155,304	6,357,765		133,513,069
Order-line	1,649,998,197	103,124,888	218,280		20,522,525	123,865,693
Stock	550,000,000	176,000,000	328,808	8,816,440		185,145,248
<b>Totals</b>		414,147,888	10,004,248	15,175,027	24,243,963	463,571,126
<b>Segment</b>	<b>LogDev Cnt.</b>	<b>Seg. Size</b>	<b>Needed</b>	<b>Overhead</b>		<b>Not Needed</b>
misc	6	172,032,000	146,361,937	1,463,619		24,206,444
customer/stock	6	319,488,000	321,844,901	3,218,449		(5,575,350)
<b>Totals</b>		491,520,000	468,206,838	4,682,068		18,631,094
<b>Dynamic space</b>	117,349,040	Sum of Data for Order, Order-Line and History				
<b>Static space</b>	326,660,192	Data + Index + 5% Space + Overhead - Dynamic space				
<b>Free space</b>	28,879,674	Total Seg. Size - Dynamic Space - Static Space - Not Needed				
<b>Daily growth</b>	23,303,898	(Dynamic space/W * 62.5) * tpmC				
<b>Daily spread</b>	(6,076,172)	Free space - 1.5 * Daily growth (zero if negative)				
<b>60 day (KB)</b>	1,724,894,059	Static space + 60 (daily growth + daily spread)				
<b>60 day (GB)</b>	1,644.99	60-day space in GB (excludes OS, Paging and RDBMS Logs)				
<b>Log size (MB)</b>	80,000	Total size of log file				
<b>% Log used</b>	61.5505	% of log file used during entire run				
<b>Total N-O Txn</b>	10932869	Total count of N-O transactions during entire run				
<b>Log per N-O txn</b>	4.6120	KB of log per New-Order transaction				
<b>8 Hour Log (GB)</b>	144.12	8 hours of log in GB (excluding space for redundancy)				
<b>Disk Capacity</b>	<b>MB</b>	<b>GB</b>	<b>disks needed</b>	<b>disks priced</b>	<b>GB priced</b>	
18 GB 15000 rpm	17300	16.89		288	4,865.63	
60 day (GB)		1,644.99	97.37	288	4,865.63	
<b>Disk Capacity</b>	<b>MB</b>	<b>GB</b>	<b>disks needed</b>	<b>disks priced</b>		
36 GB 15000 rpm	34700	33.89				
8 Hour Log (RAID 1)		144.12	4.25	5+5		

# Appendix E - Price Quotations

# Appendix F - Attestation Letter

Benchmark Sponsor: Masayoshi TAKEI  
 Director, Development Dept.1<sup>st</sup>  
 IA Server Div.  
 Personal Systems Business Group  
 Fujitsu Limited  
 1405, ohmaru, Inagi-shi, Tokyo 2068503, Japan

January 8, 2003

I remotely verified the TPC Benchmark™ C performance of the following Client/Server configuration:

Platform: **Fujitsu PRIMERGY R450**  
 Operating system: **Microsoft Windows .NET Server 2003 Enterprise Edition**  
 Database Manager: **Microsoft SQL Server 2000 Enterprise Edition SP3**  
 Transaction Manager: **Microsoft COM+ (Included in Windows 2000)**

The results were:

CPU's Speed	Memory	Disks	NewOrder 90% Response Time	tpmC
<b>Server: Fujitsu PRIMERGY R450</b>				
4 x Intel Xeon MP (2.00 GHz)	16 GB Main (2M iL3 SLC Cache per processor)	289 x 18 GB  10 x 36 GB	0.95 Seconds	<b>68,264.47</b>
<b>Three (3) Clients: PRIMERGY C200 (Specification for each)</b>				
2 x Pentium III (1400 MHz)	768 MB Main Cache: 512 KB	1 x 18 GB	n/a	n/a

In my opinion, these performance results were produced in compliance with the TPC's requirements for the benchmark. The following verification items were given special attention:

- The database records were the proper size

- The database was properly scaled and populated
- The required ACID properties were met
- The transactions were correctly implemented
- Input data was generated according to the specified percentages
- The transaction cycle times included the required keying and think times
- The reported response times were correctly measured.
- All 90% response times were under the specified maximums
- At least 90% of all delivery transactions met the 80 Second completion time limit
- The reported measurement interval was 120 minutes (7200 seconds)
- The reported measurement interval was representative of steady state conditions
- One checkpoint was taken during the reported measurement interval
- The repeatability of the measured performance was verified
- The 60 day storage requirement was correctly computed
- The system pricing was verified for major components and maintenance

Respectfully Yours,



François Raab, President



Bradley J. Askins, Auditor

