


TPC Benchmark™ C

Full Disclosure Report for



PRIMERGY R450

**Using Microsoft SQL Server 2000
Enterprise Edition SP2**

**and Microsoft Windows 2000
Advanced Server SP2**

March 12, 2002

First Edition

First Edition March 12, 2002

Fujitsu Siemens believes that the information in this document is accurate as of the publication date. The information in this document is subject to change without notice. We assume no responsibility for any errors that may appear in this document. The pricing information in this document is believed to accurately reflect the current prices as of the publication date. However, we provide no warranty of the pricing information in this document.

Benchmark results are highly dependent upon workload, specific application requirements, system design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC Benchmark™ C should not be used as a substitute for a specific customer application benchmark when critical capacity planning and/or product evaluation decisions are contemplated.

All performance data contained in this report were obtained in a rigorously controlled environment. Results obtained in other operating environments may vary significantly. We do not warrant or represent that a user can or will achieve similar performance expressed in transactions per minute (tpmC) or normalized price/performance (€/tpmC). No warranty of system performance or price/performance is expressed or implied in this report.

Copyright © 2002 Fujitsu Siemens Computers GmbH. All rights reserved.

Permission is hereby granted to reproduce this document in whole or in part provided the copyright notice printed above is set forth in full text on the title page of each item reproduced.

PRIMERGY R450, PRIMERGY 870 and PRIMERGY B210 are trademarks of Fujitsu Siemens Computers GmbH.

Microsoft, Windows 2000, SQL Server and Benchcraft are registered trademarks of Microsoft Corporation.

Pentium®III, Pentium®III XEON and XEON™ are registered trademarks of Intel.

TPC Benchmark™ is a trademark of the Transaction Processing Performance Council (TPC).

Other product names mentioned in this document may be trademarks and/or registered trademarks of their respective companies.

Preface

The Transaction Processing Performance Council (TPC), of which Fujitsu Siemens Computers GmbH is a member, is an organization of computer companies, dedicated to the development of objective, industry-wide performance metrics in the area of transaction processing. Fujitsu Siemens Computers GmbH is involved in this effort, participating on the council and utilizing TPC benchmarks in performance evaluation.

The TPC Benchmark™ C Standard Specification was developed by the Transaction Processing Performance Council. This benchmark exercises the system components necessary to perform tasks associated with that class of on-line transaction processing (OLTP) environments emphasizing a mixture of read-only and update intensive transactions. This is a complex OLTP application environment exercising a breadth of system components associated by such environments characterized by:

- The simultaneous execution of multiple transaction types that span a breadth of complexity
- On-line and deferred transaction execution modes
- Multiple on-line terminal sessions
- Moderate system and application execution time
- Significant disk input/output
- Transaction integrity (ACID properties)
- Non-uniform distribution of data access through primary and secondary keys
- Databases consisting of many tables with a wide variety of sizes, attributes, and relationships
- Contention on data access and update

This benchmark defines four on-line transactions and one deferred transaction, intended to emulate functions that are common to many OLTP applications. However, this benchmark does not reflect the entire range of OLTP requirements. The extent to which a customer can achieve the results reported by a vendor is highly dependent on how closely TPC-C approximates the customer application. The relative performance of systems derived from this benchmark does not necessarily hold for other workloads or environments. Extrapolations to any other environment are not recommended.

Benchmark results are highly dependent upon workload, specific application requirements, system design and implementation. Relative system performance will vary as a result of these and other factors. Therefore, TPC-C should not be used as a substitute for a specific customer application benchmarking when critical capacity planning and/or product evaluation decisions are contemplated.

The performance metric reported by TPC-C is a "business throughput" measuring the number of orders processed per minute. Multiple transactions are used to simulate the business activity of processing an order, and each transaction is subjected to a response time constraint. The performance metric for this benchmark is expressed in transactions-per-minute-C (tpmC). To be compliant with the TPC-C standard, all references to tpmC results must include the tpmC rate, the associated price-per-tpmC, and the availability date of the priced configuration.

Summary

This report documents the TPC Benchmark™ C results achieved by the Fujitsu Siemens Computers GmbH using Microsoft SQL Server 2000 Enterprise Edition SP2 .

The TPC Benchmark™ C tests were run on a PRIMERGY R450 system using the Windows 2000 Advanced Server SP2 operating system.

The results, summarized below, show the number of TPC Benchmark™ C transactions per minute (tpmC) and the price per tpmC (€/tpmC).

Software	Hardware	tpmC	€/tpmC
Microsoft SQL Server 2000 Enterprise Edition SP2 , Windows 2000 Advanced Server SP2	Fujitsu Siemens Computers GmbH PRIMERGY R450	48,906.18	8.84€



PRIMERGY R450
C/S with 3 PRIMERGY L200

TPC-C REV 5.0
 EXECUTIVE SUMMARY

Report Date: March 12, 2002


Total System Cost	TPC-C Throughput	Price/Performance	Availability Date	
€432,481	48,906.18 tpmC	€8.84/tpmC	May 1, 2002	
Processors	Database Manager	Operating System	Other Software	Number of Users
Server 4 Intel Xeon™ MP 1.60 GHz with 1M iL3 Cache Client 3 x 2 Intel Pentium® III 1.26 GHz with 512 KB SLC	Microsoft SQL Server 2000 Enterprise Edition SP2	Microsoft Windows 2000 Advanced Server SP2	Windows 2000 Server, IIS 5.0 and COM+	39,000

Terminals:
39000 users

Client:
3 x PRIMERGY L200
13000 users per client

Server:
PRIMERGY R450
6 SCSI Controller

Storage:
21 x PRIMERGY S30
220 disk



System Components	Qty/Srv.	1 PRIMERGY R450	Qty/Client	3 PRIMERGY L200
Processors	4	Intel Xeon™ MP 1.60 GHz with 1M iL3 Cache	2	Intel Pentium® III 1.26 GHz with 512 KB SLC
Memory	8	GB	512	MB
Disk Controller	6	Mylex eXtremeRAID 2000	1	SCSI Controller
Disk Drives	235	18 GB	1	18 GB
Total GB of Storage	1	3,755 GB		
Tape Drive	1	20 GB DAT		



PRIMERGY R450

TPC-C REV 5.0
EXECUTIVE SUMMARY

C/S with 3 PRIMERGY L200

Report Date: March 12, 2002

Description	Part Number	Third Party	Unit Price	Qty.	Extended Price	3yr Maint. Price
		Brand Pricing				
PRIMERGY R450 GE RS Xeon 1.6GHz 1MB iL3	S26361-K845-V102	1	11,600 Euro	1	11,600 Euro	
Processor Xeon 1.6GHz 1MB iL3	S26361-F2636-E161	1	7,160 Euro	3	21,480 Euro	
Memory 2 GB PC1600 DDR RAM	S26361-F2550-E544	1	2,860 Euro	4	11,440 Euro	
Tape DAT DDS4 20GB	S26361- F2233- E3	1	1,020 Euro	1	1,020 Euro	
Disk 18GB, 10k, U160, hot plug, 1"	SNP: SY- F2336L118- P	1	420 Euro	1	420 Euro	
PCI Gigabit Ethernet Controller	D:RM6T5-CL18	1	3,068 Euro	2	6,136 Euro	
Mylex eXtremeRAID 2000 4x U160 SCSI, BBU	S26361- F2190- E128	1	2,700 Euro	6	16,200 Euro	
CD- ROM, ATAPI 0.5"	SNP: SY- F2313E1- P	1	100 Euro	1	100 Euro	
Keyboard KBPC S2 D	S26381- K297- E120	1	13 Euro	1	13 Euro	
Monitor 151E	S26361- K819- V150	1	160 Euro	1	160 Euro	
PRIMERGY S30 GE RH 2-Channel U160 SCSI	SNP: SY- K638V210- P	1	2,791 Euro	1	2,791 Euro	
PRIMERGY S30 Rack Kit	SNP: SY- F2261E8- P	1	120 Euro	1	120 Euro	
SCSI Cable UHD68(S)	SNP: SY- F2365L20- P	1	104 Euro	2	208 Euro	
3 Year Maintenance Server, 7x24, 4hr Resp.	FSP: GX3S0400AAASR	1				1,200 Euro
Server Hardware Subtotal					71,688 Euro	
DataCenter Rack 38 HU	SNP: SY- K614V101- P	1	1,560 Euro	2	3,120 Euro	
APC-USV 3000VA Rack	SNP: PS- E421E1- P	1	1,740 Euro	2	3,480 Euro	
18GB, 15k, U160, Hot plug, 1"	S26361-F2336-E518	1	674 Euro	234	157,658 Euro	
18GB, 15k, U160, Hot plug, 1", 10%sprare	S26361-F2336-E518	1	674 Euro	24	16,170 Euro	
PRIMERGY S30 GE RH 1-Ch incl. Spare	SNP:SY-K638V230-P	1	2,791 Euro	22	61,408 Euro	
PRIMERGY S30 Rack Kit incl. spare	SNP: SY- F2261E8- P	1	120 Euro	22	2,640 Euro	
SCSI Cable UHD68(S) incl. spare	SNP: SY- F2365L20- P	1	104 Euro	22	2,288 Euro	
3 Year Maintenance Rack, 7x24, 4hr Resp.	FSP: GX3S0400AAASR	1				1,250 Euro
Storage Subtotal					246,763 Euro	
Maint. Server + Storage						2,450 Euro
PRIMERGY L200 GE RS PIII 1.26GHz/ 512KB	S26361- K647- V103	1	2,076 Euro	3	6,228 Euro	
Processor PIII 1.26GHz/ 512KB	S26361- F2599- E526	1	684 Euro	3	2,052 Euro	
Memory 256MB SDRAM PC133 ECC	S26361- F2306- E522	1	220 Euro	6	1,320 Euro	
Disk 18GB, U160, hot plug, 1"	SNP: SY- F2266E118-A	1	420 Euro	3	1,260 Euro	
CD- ROM, ATAPI 0.5"	SNP: SY- F2313E1- P	1	100 Euro	3	300 Euro	
Monitor 151E	S26361- K819- V150	1	160 Euro	3	480 Euro	
Tastatur KBPC S2 D	S26381- K297- E120	1	13 Euro	3	38 Euro	
3 Year Maintenance, 7x24, 4hr Resp.	FSP: GX3S0400AAASR	1	975 Euro	3		2,925 Euro
Client Hardware Subtotal					11,678 Euro	2,925 Euro
Windows Advanced Svr 2000 (open program no level)	MSO:C10-00475	1	2,570 Euro	1	2,570 Euro	
MS SQL-Server 2000 Ent.Edit. Per Proc Lic. (open program level C)	MSO:810-00846	1	19,271 Euro	4	77,085 Euro	
Server Software Subtotal					79,654 Euro	
Windows Svr 2000 (open program no level)	MSO:C11-00821	1	791 Euro	3	2,372 Euro	
VC++ Pro 6.0 Win32	MSO:048-00426	1	434 Euro	1	434 Euro	
Client Software Subtotal					2,805 Euro	
Microsoft Software Support (all above)	SNP:10901600012					10,353 Euro
24x10/0100Mbit Switch (+10% spare)	DES-3225G	2	856 Euro	3	2,568 Euro	
Gigabit Uplink (+10% spare)	DES-3251G	2	532 Euro	3	1,596 Euro	
User Connectivity Subtotal					4,164 Euro	
Total					416,753 Euro	15,728 Euro

1=Fujitsu-Siemens, 2=Buerotechnik Sachsen GmbH

Prices used in TPC benchmarks reflect the actual prices a customer would pay for a one-time purchase of the stated components. Individually negotiated discounts are not permitted. Special prices based on assumptions about past or future purchases are not permitted. All discounts reflect standard pricing policies for the listed components. For complete details, see the pricing section of the TPC benchmark pricing specifications. If you find that the stated prices are not available according to these terms, please inform the TPC at pricing@tpc.org. Thank you.

Three-Year Cost of Ownership: €432,481
tpmC Rating: 48,906.18
€/ tpmC: 8.84

Note: The benchmark results and test methodology were audited by Bradley Askins of InfoSizing

Numerical Quantities Summary

MQTh, computed Maximum Qualified Throughput		48,906.18 tpmC	
Response Times (in seconds)	90th percentile	Average	Maximum
- New-Order	0.56	0.35	5.46
- Payment	0.46	0.26	4.58
- Order-Status	0.48	0.29	5.64
- Delivery (interactive portion)	0.11	0.10	0.46
- Delivery (deferred portion)	0.41	0.25	1.19
- Stock-Level	1.86	1.37	4.84
- Menu	0.11	0.10	1.03
Transaction Mix, in percent of total transactions			
- New-Order			44.90 %
- Payment			43.03 %
- Order-Status			4.01 %
- Delivery			4.03 %
- Stock-Level			4.02 %
Emulation Delay (in seconds)		Response Time	Menu
- New-Order		0.1	0.1
- Payment		0.1	0.1
- Order-Status		0.1	0.1
- Delivery (interactive)		0.1	0.1
- Stock-Level		0.1	0.1
Keying/Think Times (in seconds)	Minimum	Average	Maximum
- New-Order	18.00/0.000	18.02/12.06	18.06/120.52
- Payment	3.00/0.000	3.02/12.05	3.06/120.51
- Order-Status	2.00/0.000	2.02/10.02	2.05/100.50
- Delivery (interactive)	2.00/0.000	2.02/ 5.06	2.04/ 50.51
- Stock-Level	2.00/0.000	2.02/ 5.05	2.04/ 50.51
Test Duration and Checkpointing			
- Ramp-up time		35 minutes	
- Measurement interval		120 minutes	
- Number of checkpoints		4	
- Checkpoint interval		30 minutes	
- Transactions during measurement interval (all types)		13,597,484	

Contents

PREFACE	3
SUMMARY	4
NUMERICAL QUANTITIES SUMMARY	7
CONTENTS	9
INTRODUCTION	12
<i>System Overview.....</i>	<i>12</i>
<i>Full Disclosure.....</i>	<i>12</i>
<i>Report Format.....</i>	<i>12</i>
<i>Additional Copies.....</i>	<i>13</i>
1. GENERAL ITEMS	15
1.1 <i>Application Code.....</i>	<i>15</i>
1.2 <i>Benchmark Sponsor.....</i>	<i>15</i>
1.3 <i>Parameter Settings.....</i>	<i>15</i>
1.4 <i>Configuration Diagrams</i>	<i>15</i>
2. CLAUSE 1 RELATED ITEMS - LOGICAL DATABASE DESIGN.....	18
2.1 <i>Table Definitions.....</i>	<i>18</i>
2.2 <i>Physical Organization of Database.....</i>	<i>18</i>
2.3 <i>Insert and Delete Operations</i>	<i>19</i>
2.4 <i>Database Partitioning</i>	<i>20</i>
2.5 <i>Replication of Tables.....</i>	<i>20</i>
2.6 <i>Additional and/or Duplicated Attributes</i>	<i>20</i>
3. CLAUSE 2 RELATED ITEMS - TRANSACTION AND TERMINAL PROFILES.....	21
3.1 <i>Random Number Generator</i>	<i>21</i>
3.2 <i>Input/Output Screen Layout</i>	<i>21</i>
3.3 <i>Configured Terminal Features.....</i>	<i>21</i>
3.4 <i>Presentation Managers or Intelligent Terminals.....</i>	<i>21</i>
3.5 <i>Transaction Statistics</i>	<i>21</i>
3.6 <i>Queueing Mechanism.....</i>	<i>22</i>
4. CLAUSE 3 RELATED ITEMS - TRANSACTION AND SYSTEM PROPERTIES.....	23
4.1 <i>Atomicity.....</i>	<i>23</i>
4.2 <i>Consistency.....</i>	<i>24</i>
4.3 <i>Isolation.....</i>	<i>24</i>
4.4 <i>Durability</i>	<i>24</i>
5. CLAUSE 4 RELATED ITEMS - SCALING AND DATABASE POPULATION.....	26
5.1 <i>Initial Cardinality of Tables</i>	<i>26</i>
5.2 <i>Distribution of Tables and Log.....</i>	<i>27</i>
5.3 <i>Database Model, Interface, and Access Language.....</i>	<i>27</i>
5.4 <i>Database Partitions/Replications Mapping</i>	<i>28</i>
5.5 <i>60 day space Calculation</i>	<i>28</i>
6. CLAUSE 5 RELATED ITEMS - PERFORMANCE METRICS AND RESPONSE TIME	29

6.1	Measured tpmC	29
6.2	Response Times	29
6.3	Keying and Think Times	29
6.4	Graphs	30
6.5	Steady State Determination	34
6.6	Work Performed	34
6.7	Duration of Checkpoints.....	35
6.8	Duration of Measurement.....	35
6.9	Regulation of Transaction Mix.....	36
6.10	Transaction Mix	36
6.11	Transaction Statistics	36
6.12	Checkpoint Statistics	36
7.	CLAUSE 6 RELATED ITEMS - SUT, DRIVER, AND COMMUNICATION DEFINITION.....	37
7.1	RTE Inputs.....	37
7.2	Lost Connections	37
7.3	Functionality and Performance of Emulated Components.....	37
7.4	Functional Diagrams of the Benchmarked and Proposed Configuration	37
7.5	Network Configurations of the Tested and Proposed Services.....	37
7.6	Network Bandwidth	38
7.7	Operator Intervention.....	38
8.	CLAUSE 7 RELATED ITEMS - PRICING	39
8.1	System Pricing.....	39
8.2	Availability Dates	39
8.3	Throughput and Price/Performance.....	39
8.4	Country Specific Pricing	39
8.5	Usage Pricing.....	40
9.	CLAUSE 8 RELATED ITEMS - AUDIT.....	41
APPENDIX A - APPLICATION SOURCE CODE.....		43
APPENDIX B - DATABASE DETAILS.....		141
	BACKUP.SQL	141
	BACKUPDEV.SQL.....	141
	CREATEDB.SQL.....	141
	DBOPT1.SQL.....	142
	DBOPT2.SQL.....	142
	REMOVEDB.SQL.....	143
	RESTORE.SQL.....	144
	VERIFYTPCCLOAD.SQL	144
	IDXCUSCL.SQL.....	145
	IDXCUSNC.SQL	145
	IDXDISCL.SQL.....	146
	IDXITMCL.SQL	146
	IDXNODCL.SQL.....	146
	IDXODLCL.SQL	146
	IDXORDCL.SQL.....	147
	IDXORDNC.SQL.....	147
	IDXSTKCL.SQL	147
	IDXWARCL.SQL.....	148
	TABLES.SQL.....	148
	DELIVERY.SQL	150
	NEWORD.SQL.....	151
	ORDSTAT.SQL.....	153

<i>PAYMENT.SQL</i>	155
<i>STOCKLEV.SQL</i>	157
<i>VERSION.SQL</i>	157
<i>GETARGS.C</i>	157
<i>RANDOM.C</i>	160
<i>STRINGS.C</i>	162
<i>TIME.C</i>	165
<i>TPCC.H</i>	165
<i>TPCCLDR.C</i>	167
APPENDIX C - TUNABLE PARAMETERS AND OPTIONS	197
APPENDIX D – SPACE CALCULATION	293
APPENDIX E - PRICE QUOTATIONS	294
APPENDIX F - ATTESTATION LETTER	297

Introduction

This is the Full Disclosure Report for the TPC Benchmark™ C running on the Fujitsu Siemens Computers system PRIMERGY R450. It meets the requirements of the TPC Benchmark™ C Standard Revision 5.0.

System Overview	<i>This report documents the compliance of the Fujitsu Siemens Computers GmbH TPC Benchmark™ C tests using Microsoft SQL Server 2000 Enterprise Edition SP2 Relational Database Management System.</i>
------------------------	--

The TPC Benchmark™ C tests were carried out on a PRIMERGY R450. The PRIMERGY R450 is a powerful Server with a motherboard based on the ServerWorks chipset that holds up to 4 Intel Xeon™ MP 1.60 GHz processors with 1M iL3 cache. The Intel® Xeon™ MP Processor family with the Intel® NetBurst™ micro-architecture uses Hyper-Threading Technology to provide additional performance and application scalability to dual-processor and multi-processor servers. Hyper-Threading Technology enables multi-threaded software to execute tasks in parallel within each processor. The system was equipped with 8 GB of ECC DDR RAM memory. 6 of the 8 PCI-Slots were used for SCSI RAID controllers. The client machines were 3 PRIMERGY L200 with 2 Intel Pentium® III 1.26 GHz. They all included 512 MB ECC SDRAM memory and 2 onboard ethernet adapter.

The server operating system was Windows 2000 Advanced Server SP2. The client operating system was Windows 2000 Server SP2.

Full Disclosure	<i>From Clause 8.1 of the TPC Benchmark™ C Standard Specification:</i> The intent of this disclosure is for a customer to be able to replicate the results of this benchmark given the appropriate documentation and products.
------------------------	---

Fujitsu Siemens Computers believes that this full disclosure report meets the stated intention. Fujitsu Siemens Computers has strived to maintain the integrity of the Specification by adhering not only to the letter of the Specification, but also to its spirit.

Report Format	<i>The format of this document follows Clause 8 of the TPC Benchmark™ C specification (TPC Benchmark™ C Standard Specification, Revision 5.0, Transaction Processing Performance Council) which describes the full disclosure report requirements for the test.</i>
----------------------	---

Each section of this report begins with the specification requirement printed in *italic type*. It is followed by plain type text that explains how the test complies with the requirement. Sections which require extensive listings reference appropriate appendices.

Report organization:

- General Items
- Clause 1 Related Items - Logical Database Design
- Clause 2 Related Items - Transaction and Terminal Profiles
- Clause 3 Related Items - Transaction and System Properties
- Clause 4 Related Items - Scaling and Database Population
- Clause 5 Related Items - Performance Metrics and Response Time
- Clause 6 Related Items - SUT, Driver, and Communication Definition
- Clause 7 Related Items - Pricing
- Clause 8 Related Items - Audit
- Appendix A - Application Source Code
- Appendix B - Database Details
- Appendix C - Tunable Parameters and Options
- Appendix D - Space Calculation
- Appendix E - Price Quotations
- Appendix F - Attestation Letter

Additional Copies	<p><i>Additional copies of this report are available upon request from Fujitsu Siemens Computers GmbH:</i></p> <p><i>Fujitsu Siemens Computers ES PS DS 5 PRIMERGY Server Performance Lab Mr. Bathe Heinz-Nixdorf-Ring 1 33106 Paderborn Germany</i></p>
--------------------------	--

1. General Items

1.1 Application Code	<i>The application program (as defined in Clause 2.1.7) must be disclosed. This includes, but is not limited to, the code implementing the five transactions and the terminal input and output functions. [Clause 8.1.1.4]</i>
---------------------------------	--

The source code of the application program is provided in Appendix A - Application Source Code.

1.2 Benchmark Sponsor	<i>A statement identifying the benchmark sponsor(s) and other participating companies must be provided. [Clause 8.1.1.5]</i>
----------------------------------	--

This benchmark was sponsored and executed by Fujitsu Siemens Computers GmbH.
The benchmark was developed and engineered by Fujitsu Siemens Computers GmbH and Microsoft Corporation.
Testing took place at Fujitsu Siemens Computers PRIMERGY benchmark laboratories in Paderborn, Germany.

1.3 Parameter Settings	<i>Settings must be provided for all customer-tunable parameters and options which have been changed from the defaults found in actual products, including but not limited to:</i> <ul style="list-style-type: none"><i>• Database tuning options.</i><i>• Recovery/commit options.</i><i>• Consistency/locking options.</i><i>• Operating system and application configuration parameters.</i> <i>[Clause 8.1.1.6]</i>
-----------------------------------	--

The significant parameters and system configuration files are provided in Appendix C - Tunable Parameters and Options.

1.4 Configuration Diagrams	<i>Diagrams of both measured and priced configurations must be provided, accompanied by a description of the differences. This includes, but is not limited to:</i> <ul style="list-style-type: none"><i>• Number and type of processors.</i><i>• Size of allocated memory, and any specific mapping/partitioning of memory unique to the test.</i><i>• Number and type of disk units (and controllers, if applicable).</i><i>• Number of channels or bus connections to disk units, including their protocol type.</i><i>• Number of LAN (e.g., Ethernet) connections, including routers, workstations, terminals, etc., that were physically used in the test or are incorporated into the pricing structure (see Clause 8.1.8).</i><i>• Type and the run-time execution location of software components (e.g., DBMS, client processes, transaction monitors, software drivers, etc.).</i> <i>[Clause 8.1.1.7]</i>
---------------------------------------	---

Table 1: SUT Configuration PRIMERGY R450

4	Intel Xeon™ MP 1.60 GHz with 1M iL3 Cache
8	GB memory
6	Mylex eXtremRAID 2000 SCSI controllers
0	disks 9 GB measured
235	disks 18 GB measured
0	disks 36 GB measured
0	disks 9 GB priced
235	disks 18 GB priced
0	disks 36 GB priced
1	LAN

Table 2: Client Configuration PRIMERGY L200

2	Intel Pentium® III 1.26 GHz with 512 KB Second Level Cache
512	MB memory
1	SCSI controller
1	disk 18 GB
2	onboard LAN

The benchmarked and priced system configurations are shown in Figure 1 and Figure 2 in accordance with Clause 8.1.1.7.

Figure 1: Benchmark System Configuration PRIMERGY R450





Figure 2: Priced System Configuration PRIMERGY R450



2. Clause 1 Related Items - Logical Database Design

2.1 Table Definitions	<i>Listings must be provided for all table definition statements and all other statements used to set-up the database. [Clause 8.1.2.1]</i>
----------------------------------	---

The programs that defined, created, and populated the Microsoft SQL Server 2000 Enterprise Edition SP2 database for this TPC benchmark™ C are listed in Appendix B - Database Details.

2.2 Physical Organization of Database	<i>The physical organization of tables and indices, within the database, must be disclosed. [Clause 8.1.2.2]</i>
--	--

Table 3: Physical Organization of the Database

Controller	Channel 0	Channel 1	Channel 2	Channel 3	RAID	Drive
eXtremeRAID 2000 #0	0-0 1-0 2-0 3-0 4-0 5-0 6-0 7-0	0-1 1-1 2-1 3-1 4-1 5-1 6-1 7-1			SPAN 0 to 1 RAID1	L:
eXtremeRAID 2000 #1	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11	SPAN 0 to 3 RAID0	E: N: X:
eXtremeRAID 2000 #2	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11	SPAN 0 to 3 RAID0	F: O: Y:
eXtremeRAID 2000 #3	0-0 0-1	1-0 1-1	2-0 2-1	3-0 3-1	SPAN 0 to 3 RAID0	G: P:

	0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11	1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11	2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11	3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11		Z:
eXtremeRAID 2000 #4	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11	SPAN 0 to 3 RAID0	H: Q: W:
eXtremeRAID 2000 #5	0-0 0-1 0-2 0-3 0-4 0-5 0-6 0-8 0-9 0-10 0-11	1-0 1-1 1-2 1-3 1-4 1-5 1-6 1-8 1-9 1-10 1-11	2-0 2-1 2-2 2-3 2-4 2-5 2-6 2-8 2-9 2-10 2-11	3-0 3-1 3-2 3-3 3-4 3-5 3-6 3-8 3-9 3-10 3-11	SPAN 0 to 3 RAID0	I: R: V:

All controllers were configured with write cache disabled. Write cache was enabled on the log drives and disabled on the data drives. Disk types are Seagate ST318452 LC 18 GB with 15000 rpm.

Space was allocated to Microsoft SQL Server 2000 Enterprise Edition SP2 on SUT disks according to the data in section 5.2. The size of the datafile on each disk drive was calculated to provide even distribution on load across the disk drives. The Windows Disk Manager was used to create raw devices for data/log and NTFS partitions for dump devices. For further information see Appendix B (Disk Usage) and Figure 4 in 5.2 (Distribution of Tables and Log). No attempt was made to alter the default physical organization of the database tables and indices chosen by Microsoft SQL Server 2000 Enterprise Edition SP2 .

2.3 Insert and Delete Operations	<i>It must be ascertained that insert and/or delete operations to any of the tables can occur concurrently with the TPC-C transaction mix. Furthermore, any restriction in the SUT database implementation that precludes inserts beyond the limits defined in Clause 1.4.11 must be disclosed. This includes the maximum number of rows that can be inserted and the maximum key value for these new rows. [Clause 8.1.2.3]</i>
---	--

There were no restrictions on insert and delete operations to any tables.

2.4 Database Partitioning	<i>While there are a few restrictions placed upon horizontal or vertical partitioning of tables and rows in the TPC benchmark™ C (see Clause 1.6), any such partitioning must be disclosed. [Clause 8.1.2.4]</i>
--------------------------------------	--

There was no partitioning used in this implementation.

2.5 Replication of Tables	<i>Replication of tables, if used, must be disclosed (see Clause 1.4.6). [Clause 8.1.2.5]</i>
--------------------------------------	---

Replication of tables was not used in this implementation.

2.6 Additional and/or Duplicated Attributes	<i>Additional and/or duplicated attributes in any table must be disclosed along with a statement on the impact on performance (see Clause 1.4.7). [Clause 8.1.2.6]</i>
--	--

No additional and/or duplicated attributes were used.

3. Clause 2 Related Items - Transaction and Terminal Profiles

3.1 Random Number Generator	<i>The method of verification for the random number generation must be described. [Clause 8.1.3.1]</i>
--	--

The random number generation was done in Microsoft BenchCraft, which was audited independently.

3.2 Input/Output Screen Layout	<i>The actual layouts of the terminal input/output screens must be disclosed. [Clause 8.1.3.2]</i>
---	--

The screen layout corresponded exactly to those of the TPC-C Standard Specification (specified in Clause 2.4.3, 2.5.3, 2.6.3, 2.7.3, and 2.8.3).

3.3 Configured Terminal Features	<i>The method used to verify that the emulated terminals provide all the features described in Clause 2.2.2.4 must be explained. Although not specifically priced, the type and model of the terminals used for the demonstration in 8.1.3.3 must be disclosed and commercially available (including supporting software and maintenance). [Clause 8.1.3.3]</i>
---	---

All of the requirements in clause 2.2.2.4. are supported. This was verified by manually exercising each specification on a PRIMERGY 870.

3.4 Presentation Managers or Intelligent Terminals	<i>Any usage of presentation managers or intelligent terminals must be explained. [Clause 8.1.3.4]</i>
---	--

Application code running on the client machines implemented the TPC-C user interface. No presentation manager software or intelligent terminal features were used. The source code for the forms application is listed in Appendix A - Application Source Code.

3.5 Transaction Statistics	<i>The numerical quantities which are required are listed in the following table. [Clause 8.1.3.5 to 8.1.3.11]</i>
---------------------------------------	--

Table 4: Transaction Statistics

	Statistics	Percentage
New-Order	Home order-lines	99.00%
	Remote order-lines	1.00%
	Rolled back transactions	0.99%
	Average items per order	10.00
Payment	Home transactions	85.00%
	Remote transactions	15.00%
	Non-primary key access	60.01%
Order-Status	Non-primary key access	60.05
Delivery	Skipped transactions	0
Transaction Mix	New-Order	44.90 %
	Payment	43.03 %
	Order-Status	4.01 %
	Delivery	4.03 %
	Stock-Level	4.02 %

3.6 Queueing Mechanism

The queuing mechanism used to defer the execution of the Delivery transaction must be disclosed. [Clause 8.1.12]

Deferred deliveries are queued by making an entry in an array within the client application process (tpcc.dll). The queued delivery transactions are processed and logged asynchronously by background threads within the application.

The source code is listed in Appendix A - Application Source Code.

4. Clause 3 Related Items - Transaction and System Properties

ACID Tests	<i>The results of the ACID tests must disclosed along with a description of how the ACID requirements were met. This includes disclosing which case was followed for the execution of Isolation Test 7. [Clause 8.1.4.1]</i>
-------------------	--

All ACID tests were performed successfully. The following sections describe the requirements of each of the tests as described in Clause 3 and the approach used to satisfy them.

All ACID tests were performed on the PRIMERGY R450 system using the fully scaled database, except for the test of durable media failure.

The durability test was performed on a database scaled to 15 warehouses. This test would also pass on a fully scaled database.

4.1 Atomicity	<i>The system under test must guarantee that database transactions are atomic; the system will either perform all individual operations on the data, or will assure that no partially-completed operations leave any effects on the data. [Clause 3.2.1]</i>
----------------------	--

Commit Transaction	Perform the Payment transaction for a randomly selected warehouse, district, and customer (by customer number as specified in Clause 2.5.1.2) and verify that the records in the CUSTOMER, DISTRICT, and WAREHOUSE tables have been changed appropriately. [Clause 3.2.2.1]
---------------------------	---

The following steps demonstrated atomicity for completed (COMMIT) transactions:

- A row was randomly selected from the warehouse, district and customer table.
- the current balance was noted.
- A payment transaction was executed with the above identifiers and a known amount.
- The transaction was committed.
- It was verified, that the rows contain the correct updated balances.

Rollback Transaction	Perform the Payment transaction for a randomly selected warehouse, district, and customer (by customer number as specified in Clause 2.5.1.2) and substitute a ROLLBACK of the transaction for the COMMIT of the transaction. Verify that the records in the CUSTOMER, DISTRICT, and WAREHOUSE tables have NOT been changed. [Clause 3.2.2.2]
-----------------------------	---

The following steps demonstrated atomicity for aborted (ROLLBACK) transactions:

- A row was randomly selected from the warehouse, district and customer table.
- the current balance was noted.
- A payment transaction was executed with the above identifiers and a known amount.
- The transaction was rolled back.
- It was verified, that the rows contain the original balances.

**4.2
Consistency**

Consistency is the property of the application that requires any execution of a database transaction to take the database from one consistent state to another, assuming that the database is initially in a consistent state. [Clause 3.3.1]

Consistency conditions 1 - 4 were tested by issuing queries to the database. The results of the queries verified that the database was consistent for all these tests. The tests were performed before and after the performance run on the same database that was used for the benchmark.

**4.3
Isolation**

Operations of concurrent transactions must yield results which are indistinguishable from the results which would be obtained by forcing each transaction to be serially executed to completion in some order.

We ran all of the seven isolation tests as described in clause 3.4.2.1 to 3.4.2.7 and additionally the two phantom protection tests. The tests were executed using shell scripts to issue queries to the database. The results of the queries verified that the required isolation had been met.

**4.4
Durability**

The tested system must guarantee durability: the ability to preserve the effects of committed transactions and insure database consistency after recovery from any one of the failures listed in Clause 3.5.3. [Clause 3.5]

List of single failures

1 Permanent irrecoverable failure of any single durable medium containing TPC-C database tables or recovery log data

2 Instantaneous interruption (system crash / system hang) in processing which requires system reboot to recover

3 Failure of all or part of memory (loss of contents).

[Clause 3.5.3]

The intent of these tests is to demonstrate that all transactions whose output messages have been received at the terminal or RTE have in fact been committed in spite of any single failure from the list in Clause 3.5.3 and that all consistency conditions are still met after the database is recovered.

It is required that the system crash test(s) and the loss of memory test(s) described in Clause 3.5.3.2 and 3.5.3.3 be performed under full terminal load and a fully scaled database. The durable media failure test(s) described in Clause 3.5.3.1 may be performed on a subset of the SUT configuration and database. For the SUT subset, all multiple hardware components, such as processors and disk / controllers in the full SUT configuration, must be represented by the greater of 10% of the configuration or two of each of the multiple hardware components. The database must be scaled to at least 10% of the fully scaled database, with a minimum of two warehouses. ... Furthermore, the standard driving mechanism must be used in this test. The test sponsor must state that to the best of their knowledge, a fully scaled test would also pass all durability tests. [Clause 3.5.4]

The failure of all or part of memory test and the system crash test were combined with the loss of log disk and performed under full load and by using a fully scaled database.

The full hardware configuration of the SUT (in accordance with Clause 3.5.4) and the same test procedure was used during all durability tests, except the test for loss of data.

- The current count of the total number of orders was determined by summing up the D_NEXT_O_ID fields of all rows in the DISTRICT table before the test.

- After 6 min in steady state we pulled off one of the log disks. As we use hardware-mirrored diskpairs with the SCSI-controller, execution continued.
- After additional 6 min we powered of the server to emulate the loss of memory. After server system reboot, SQL-Server starts with recovering the database tpcc. After completion, we computed the sum of D_NEXT_O_ID from district. Client and RTE systems were interrupted and evaluation started on the RTE. The difference of all D_NEXT_O_ID between RTE an server was in the permitted scope.

The durable media failure test for loss of data disk was performed with 44 of the 132 data disks and a database scaled to 15 warehouses under the load of 150 users. We used one RTE and one client system. To the best of the test sponsor's knowledge, a fully loaded and fully scaled database would also pass this durability test.

- The database was backed up.
- The current count of the total number of orders was determined by summing up the D_NEXT_O_ID fields of all rows in the DISTRICT table before the test.
- After 5 min in steady state we pulled of one of the data disks.
- SQL-Server recognized the loss of a device. We dumped the transaction log and removed the database with dropdevice. Then we shut down SQL-Server and the system.
- We replaced the disk and made it online.
- We restarted SQL-Server, no tpcc database and none of its devices were present. We recreated the database, loaded dump and load transaction log
- After completion, we computed the sum of D_NEXT_O_ID from district.
- Client and RTE systems were interrupted and evaluation started on the RTE. The difference of all D_NEXT_O_ID between RTE an server was in the permitted scope.

5. Clause 4 Related Items - Scaling and Database Population

5.1 Initial Cardinality of Tables	<i>The cardinality (e.g., the number of rows) of each table, as it existed at the start of the benchmark run (see Clause 4.2), must be disclosed. If the database was over-scaled and inactive rows of the WAREHOUSE table were deleted (see Clause 4.2.2), the cardinality of the WAREHOUSE table as initially configured and the number of rows deleted must be disclosed. [Clause 8.1.5.1]</i>
--	---

The database for the PRIMERGY R450 system was scaled for 3900 warehouses. The performance run used 3900 warehouses. In accordance with Clause 4.2, the following number of records were loaded in the specified tables:

Table 5: Number of Rows

Table	Number of Records
Warehouse	3900
District	39,000
Customer	171,000,000
History	171,000,001
Order	117,000,000
New-Order	35,100,000
Order-Line	1,169,996,242
Stock	390,000,000
Item	100,000
Deleted Warehouses	00

The following constant values were used during the database build and benchmark test for the NURand function:

Table 6: C_LAST value

Constant C	Value
C_LAST (build)	123
C_LAST (run)	233

**5.2
Distribution of Tables and Log**

The distribution of tables and logs across all media must be explicitly depicted for the tested and priced systems. [Clause 8.1.5.2]

Table 7: Logical Organization of the Database

Disk	Controller	Disktype	RAID Configuration	Drive Letter	Size MB	Filegroup or Filesystem
0	Symbios (onboard)	18 GB	-	System C:	9000	NTFS
1	eXtremeRAID 2000 #0	14 x 18 GB	RAID 1	L:	90000	log
2	eXtremeRAID 2000 #1	44 x 18 GB	RAID 0	E: N: X:	45000 25000 200000	cs1 misc1 backup1
3	eXtremeRAID 2000 #2	44 x 18 GB	RAID 0	F: O: Y:	45000 25000 200000	cs2 misc2 backup2
4	eXtremeRAID 2000 #3	44 x 18 GB	RAID 0	G: P: Z:	45000 25000 200000	cs3 misc3 backup3
5	eXtremeRAID 2000 #4	44 x 18 GB	RAID 0	H: Q: W:	45000 25000 200000	cs4 misc4 backup4
6	eXtremeRAID 2000 #5	44 x 18 GB	RAID 0	I: R: V:	45000 25000 200000	cs5 misc5 backup5

**5.3
Database Model, Interface, and Access Language**

A statement must be provided that describes:

1. *The data model implemented by the DBMS used (e.g., relational, network, hierarchical)*
2. *The database interface (e.g., embedded, call level) and access language (e.g., SQL, DL/1, COBOL read/write) used to implement the TPC-C transactions. If more than one interface/access language is used to implement TPC-C, each interface / access language must be described and a list of which interface/access language is used with which transaction type must be disclosed.*

[Clause 8.1.5.3]

Microsoft SQL Server 2000 Enterprise Edition SP2 is a Relational DataBase Management System. The interface used was Microsoft SQL Server 2000 Enterprise Edition SP2 stored procedures accessed with Remote Procedure Calls embedded in C code.

5.4 Database Partitions/Replications Mapping	<i>The mapping of database partitions/replications must be explicitly described. [Clause 8.1.5.4]</i>
---	---

There was no partitioning and/or replication used in this implementation.

5.5 60 day space Calculation	<i>Details of the 60-day space computations along with proof that the database is configured to sustain 8 hours of growth for the dynamic tables (Order, Order-Line, and History) must be disclosed (see Clause 4.2.3). [Clause 8.1.5.5]</i>
---	--

Calculations of space requirements in the priced configurations for the 60-day period are provided in Appendix D – Space Calculation.

6. Clause 5 Related Items - Performance Metrics and Response Time

6.1 Measured tpmC	<i>Measured tpmC must be reported. [Clause 8.1.6.1]</i>
------------------------------------	---

During the 120 minutes measurement period on the PRIMERGY R450 the throughput measured was 48,906.18 tpmC.

6.2 Response Times	<i>Ninetieth percentile, maximum and average response times must be reported for all transaction types as well as for the Menu response time. [Clause 8.1.6.2]</i>
-------------------------------------	--

Table 8: Response Times

Type	Average	Maximum	90 Percentile
New-Order	0.35	5.46	0.56
Payment	0.26	4.58	0.46
Order-Status	0.29	5.64	0.48
Interactive Delivery	0.10	0.46	0.11
Deferred Delivery	0.25	1.19	0.41
Stock-Level	1.37	4.84	1.86
Menu	0.10	1.03	0.11

6.3 Keying and Think Times	<i>The minimum, the average, and the maximum keying and think times must be reported for each transaction type. [Clause 8.1.6.3]</i>
---	--

Table 9: Keying Times

Keying Times			
Type	Average	Maximum	Minimum
New-Order	18.02	18.06	18.00
Payment	3.02	3.06	3.00
Order-Status	2.02	2.05	2.00
Delivery	2.02	2.04	2.00
Stock-Level	2.02	2.04	2.00

Table 10: Think Times

Think Times			
Type	Average	Maximum	Minimum
New-Order	12.06	120.52	0.000
Payment	12.05	120.51	0.000
Order-Status	10.02	100.50	0.000
Delivery	5.06	50.51	0.000
Stock-Level	5.05	50.51	0.000

**6.4
Graphs**

Response Time frequency distribution curves (see Clause 5.6.1) must be reported for each transaction type. [Clause 8.1.6.4]

The performance curve for response times versus throughput (see Clause 5.6.2) must be reported for the New-Order transaction. [Clause 8.1.6.5]

Think Time frequency distribution curves (see Clause 5.6.3) must be reported for each transaction type. [Clause 8.1.6.6]

A graph of throughput versus elapsed time (see Clause 5.6.5) must be reported for the New-Order transaction. [Clause 8.1.6.8]

Figure 3: New-Order Response Time Distribution




FIGURE 4: PAYMENT RESPONSE TIME DISTRIBUTION




Figure 5: Order-Status Response Time Distribution




Figure 6: Delivery Response Time Distribution




Figure 7: Stock-Level Response Time Distribution




Figure 8: Response Time Versus Throughput




Figure 9: New-Order Think Time Distribution





Figure 10: Throughput Versus elapsed Time



**6.5
Steady State
Determination**

The method used to determine that the SUT had reached a steady state prior to commencing the measurement interval (see Clause 5.5) must be described. [Clause 8.1.6.9]

In all test runs, steady state was achieved before the measurement period began. Steady state was determined to occur based on a visual inspection of tpmC versus time (see graph in section 6.4).

The graph in section 6.4 illustrates that the measurement period was within the steady state period for the run. One checkpoint occurred before and four during the measurement period.

**6.6
Work Performed**

A description of how the work normally performed during a sustained test (for example checkpointing, writing redo/undo log records, etc.), actually occurred during the measurement interval must be reported. [Clause 8.1.6.10]

The RTE generated the required input data to choose a transaction from the menu. This data was timestamped and captured in RTE log files before being transmitted. There was one log file for each user. The input screen for the requested transaction was returned and it was also captured and timestamped in the RTE log files. The difference between these two timestamps was the menu response time.

The RTE generated the required input data for the chosen transaction. It waited to complete the minimum required key time before transmitting the input screen. The transmission was timestamped and captured in RTE log files. The return of the screen with the required response data was timestamped and captured in the RTE log files. The difference between these two timestamps was the response time for that transaction.

The RTE then waited the required think time interval before repeating the process starting at selecting a transaction from the menu.

The RTE transmissions were sent to Internet Information Server running on the client machines through Ethernet LANs. Internet Information Server handled all screen I/O as well as all requests to the database on the server.

Internet Information Server communicated with the database server over COM+ which was used as transaction monitor.

All database operations like update, select, delete and insert are performed by one of the TPC-C back end programs. The TPC-C backend program commits the transaction after all the corresponding operations are done.

Modified database buffers are migrated to disk a least-recently-used basis independent of transaction commits. In addition, every block modification is protected by log records. Asynchronously the log buffers are flushed to a log file on disk either when the transaction is committed or when the log buffer's fill state reaches it's limit. The log buffer's always flushed by a commit before it become full.

To perform checkpoints at specific intervals, we wrote a script to schedule multiple checkpoints at specific intervals. By setting the trace flag #3502, SQL Server logged the checkpoint beginning and ending time in the ERRORLOG file. The script included a wait time between each checkpoint equal to the measurement interval which was 120 minutes. The checkpoint script was started manually after the RTE had all users logged in and sending transactions.

At each checkpoint, Microsoft SQL Server wrote to disk all memory pages that had been updated but not yet physically written to disk. Upon completion of the checkpoint, Microsoft SQL Server wrote a special record to the recovery log to indicate that all disk operations had been satisfied to this point.

6.7 Duration of Checkpoints	<i>The start time and duration in seconds of at least the four (4) longest checkpoints during the MeasurementInterval must be disclosed (see Clause 5.5.2.2 (2)). [Clause 8.1.6.11]</i>
--	---

There was one checkpoint before measurement and four checkpoints during measurement. Starttime and duration of these four checkpoints is listed in the following table:

Table 11: Duration of Checkpoints

Measurement		duration	
Start =	End =	minutes	seconds
9:19:40	11:19:40	120	7200
4 Checkpoints		duration	
Start =	End =	minutes	seconds
09:33:32	09:47:32	14:00	840
10:03:31	10:17:31	14:00	840
10:33:30	10:47:30	14:00	840
11:03:29	11:17:29	14:00	840

6.8 Duration of Measurement	<i>A statement of the duration of the measurement interval for the reported Maximum Qualified Throughput (tpmC) must be included. [Clause 8.1.6.12]</i>
--	---

The measurement interval of the PRIMERGY R450 system test was 120 minutes.

**6.9
Regulation of Transaction Mix**

The method of regulation of the transaction mix (e.g., card decks or weighted random distribution) must be described. If weighted distribution is used and the RTE adjusts the weights associated with each transaction type, the maximum adjustments to the weight from the initial value must be disclosed. [Clause 8.1.6.13]

The transaction mix was regulated by weighted distribution. The chosen weights meet the required minimum percentages of the mix which are described in Clause 5.2.3 of the Standard Specifications. No adjustments were made by the RTE.

**6.10
Transaction Mix**

The percentage of the total mix for each transaction type must be disclosed. [Clause 8.1.6.14]

Table 12: Transaction Mix

	Percentage
New-Order	44.90 %
Payment	43.03 %
Order-Status	4.01 %
Delivery	4.03 %
Stock-Level	4.02 %

**6.11
Transaction Statistics**

The percentage of New-Order transactions rolled back as a result of invalid item number must be disclosed. [Clause 8.1.6.15]

The average number of order-lines entered per New-Order transaction must be disclosed. [Clause 8.1.6.16]

The percentage of remote order-lines entered per New-Order transaction must be disclosed. [Clause 8.1.6.17]

The percentage of remote Payment transactions must be disclosed. [Clause 8.1.6.18]

The percentage of customer selections by customer last name in the Payment and Order-Status transactions must be disclosed. [Clause 8.1.6.19]

The percentage of Delivery transactions skipped due to there being fewer than necessary orders in the New-Order table must be disclosed. [Clause 8.1.6.20]

The numerical quantities which are required in Clause 8.1.6.15 to 8.1.6.20 are already listed in a table above (see section 3.5).

**6.12
Checkpoint Statistics**

The number of checkpoints in the Measurement Interval, the time in seconds from the start of the Measurement Interval to the first checkpoint and the Checkpoint Interval must be disclosed. [Clause 8.1.6.21]

The numerical quantities which are required in Clause 8.1.6.21 are already listed above (see section 6.7).

7. Clause 6 Related Items - SUT, Driver, and Communication Definition

7.1 RTE Inputs	<i>If the RTE is commercially available, then its inputs must be specified. Otherwise, a description must be supplied of what inputs (e.g., scripts) to the RTE had been used. [Clause 8.1.7.1]</i>
---------------------------	---

Microsoft Benchcraft was used as the RTE to emulate the terminals. Its input parameters are shown in Appendix C - Tunable Parameters and Options.

We used COM+ to simulate terminal users, generate random data, record response times and statistical data. Its input parameters are shown in Appendix C - Tunable Parameters and Options.

7.2 Lost Connections	<i>The number of terminal connections lost during the Measurement Interval must be disclosed (see Clause 6.6.2). [Clause 8.1.7.3]</i>
---------------------------------	---

There were no lost connections during measurement interval.

7.3 Functionality and Performance of Emulated Components	<i>It must be demonstrated that the functionality and performance of the components being emulated in the Driver System are equivalent to that of the priced system. The results of the test described in Clause 6.6.3.4 must be disclosed. [Clause 8.1.7.3]</i>
---	--

The Driver System consisted of a PRIMERGY 870. This driver was attached to the client machine through a 100 Mbps ethernet LAN and switch. Since this is exactly the same connectivity as configured in the priced system, no component was emulated. Therefore, the test described in Clause 6.6.3.4 was not required.

7.4 Functional Diagrams of the Benchmarked and Proposed Configuration	<i>A complete functional diagram of both the benchmark configuration and the configuration of the proposed (target) system must be disclosed. A detailed list of all software and hardware functionality being performed on the Driver System, and its interface to the SUT must be disclosed (see Clause 6.6.3.6). [Clause 8.1.7.4]</i>
--	--

Figure 1 and Figure 2 in section 1.4 show the functional diagrams of the benchmark configuration and the priced configuration.

7.5 Network Configurations of the Tested and Proposed Services	<i>The network configurations of both the tested services and the proposed (target) services which are being represented and a thorough explanation of exactly which parts of the proposed configuration are being replaced with the Driver System must be disclosed (see Clause 6.6.4). [Clause 8.1.7.5]</i>
---	---

Figure 1 and Figure 2 in section 1.4 show the network setup of both configurations. The driver replaces the workstations.

In both configurations one 100Mbps ethernet LAN segment was used to connect the server with the 3 clients and 100Mbps LAN with switch to connect the RTE systems or 39,00 workstations to the clients.

7.6 Network Bandwidth	<i>The bandwidth of the network(s) used in the tested / priced configuration must be disclosed. [Clause 8.1.7.6]</i>
----------------------------------	--

The ethernet used in the local area network (LAN) between the emulated user system and the front-end system complies with the IEEE 802.3 standard. Its bandwidth is 100 Mbps. Between front-end and SUT the bandwidth is 100 Mbps.

7.7 Operator Intervention	<i>If the configuration requires operator intervention (see Clause 6.6.6), the mechanism and the frequency of this intervention must be disclosed. [Clause 8.1.7.7]</i>
--------------------------------------	---

The PRIMERGY R450 requires no operator intervention to sustain the reported throughput.

8. Clause 7 Related Items - Pricing

8.1 System Pricing	<p><i>A detailed list of hardware and software used in the priced system must be reported. Each separately orderable item must have vendor part number, description, and release/revision level, and either general availability status or committed delivery date. If package-pricing is used, vendor part number of the package and a description uniquely identifying each of the components of the package must be disclosed. Pricing source(s) and effective date(s) of price(s) must also be reported. [Clause 8.1.8.1]</i></p> <p><i>The total 3-year price of the entire configuration must be reported, including: hardware, software, and maintenance charges. Separate component pricing is recommended. The basis of all discounts used must be disclosed. [Clause 8.1.8.2]</i></p>
-------------------------------	---

The details of the hardware and software are reported in the summary in front of this report. The spreadsheet used to determine the 3-year price and the spreadsheet used to describe the priced configuration can be found in Appendix E - Price Quotations.

8.2 Availability Dates	<p><i>The committed delivery date for general availability (availability date) of products used in the price calculations must be reported. When the priced system includes products with different availability dates, the reported availability date for the priced system must be the date at which all components are committed to be available. This single date must be reported on the first page of the Executive Summary. All availability dates, whether for individual components or for the SUT as a whole, must be disclosed to a precision of one day. [Clause 8.1.8.3]</i></p>
-----------------------------------	---

All hardware and software components used in the price calculations of the PRIMERGY R450 system will be generally available from Fujitsu Siemens Computers GmbH as of May 1, 2002.

8.3 Throughput and Price/Performance	<p><i>A statement of the measured tpmC, as well as the respective calculations for 3-year pricing, price/performance (price/tpmC), and the availability date must be included. [Clause 8.1.8.4]</i></p>
---	---

PRIMERGY R450 system was measured at 48,906.18 tpmC with Microsoft SQL Server 2000 Enterprise Edition SP2 with a 3-year system price of €432,481. The respective price/performance for the PRIMERGY R450 is €8.84/tpmC. The priced PRIMERGY R450 will be available as of May 1, 2002.

8.4 Country Specific Pricing	<p><i>Additional Clause 7 related items may be included in the Full Disclosure Report for each country specific priced configuration. Country specific pricing is subject to Clause 7.1.7 [Clause 8.1.8.5]</i></p>
---	--

The system is being priced for Germany.

8.5 Usage Pricing

For any usage pricing, the sponsor must disclose:

- *Usage level at which the component was priced.*
- *A statement of the company policy allowing such pricing.*

[Clause 8.1.8.6]

The component pricing based on usage is shown below:

- One Microsoft SQL Server 2000 Enterprise Edition SP2
- One Windows 2000 Advanced Server SP2
- 3 Microsoft Windows 2000 Server SP2 license (includes 5 client access licenses)
- One Microsoft Visual C++ Professional 6.0

9. Clause 8 Related Items - Audit

9.1 Auditor	<p><i>The auditor's name, address, phone number, and a copy of the auditor's attestation letter indicating compliance must be included in the Full Disclosure Report.</i></p> <p><i>A review of the pricing model is required to ensure that all components required are priced (see Clause 9.2.8). The auditor is not required to review the final Full Disclosure Report or the final pricing prior to issuing the attestation letter. [Clause 8.1.9]</i></p>
------------------------	---

The benchmark test of the PRIMERGY R450 system with Microsoft SQL Server 2000 Enterprise Edition SP2 was independently audited by:

Bradley Askins, TPC certified auditors of Infosizing.
The attestation letter is included in Appendix F.

Requests for this TPC-C Full Disclosure Report should be sent to:

Transaction Processing Performance Council
c/o Shanley Public Relations
777 North First Street, Suite 6000
San Jose, CA 95112-6311

or

FUJITSU SIEMENS COMPUTERS
EP PS DS5
PRIMERGY Server Performance Lab
Mr. Bathe
Heinz-Nixdorf-Ring 1
33106 Paderborn
Germany

Appendix A - Application Source Code

```
LIBRARY TPCC.DLL
```

```
EXPORTS
```

```
    GetExtensionVersion @1
    HttpExtensionProc   @2
    TerminateExtension  @3
```

```
/* FILE:      TPCC.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE:  Header file for ISAPI TPCC.DLL, defines structures and
functions used in the isapi tpcc.dll.
 *
 */
```

```
//VERSION RESOURCE DEFINES
```

```
#define _APS_NEXT_RESOURCE_VALUE      101
#define _APS_NEXT_COMMAND_VALUE      40001
#define _APS_NEXT_CONTROL_VALUE      1000
#define _APS_NEXT_SYMED_VALUE        101
```

```
#define TP_MAX_RETRIES                50
```

```
//note that the welcome form must be processed first as terminal ids
assigned here, once the
//terminal id is assigned then the forms can be processed in any order.
#define WELCOME_FORM                  1          //beginning form no
term id assigned, form id
#define MAIN_MENU_FORM                2          //term id
assigned main menu form id
#define NEW_ORDER_FORM                3          //new order
form id
#define PAYMENT_FORM                  4          //payment form id
#define DELIVERY_FORM                 5          //delivery
form id
#define ORDER_STATUS_FORM             6          //order status id
#define STOCK_LEVEL_FORM              7          //stock level form
id
```

```
//This macro is used to prevent the compiler error unused formal parameter
#define UNUSEDPARAM(x) (x = x)
```

```
//This structure defines the data necessary to keep distinct for each
terminal or client connection.
typedef struct _CLIENTDATA
{
    int          iNextFree;                //index of next free element
or -1 if this entry in use.
    int          w_id;                    //warehouse id assigned at
welcome form
    int          d_id;                    //district id assigned at
welcome form

    int          iSyncId;                 //synchronization id
    int          iTickCount;              //time of last access;

    CTPCC_BASE *pTxn;

} CLIENTDATA, *PCLIENTDATA;
```

```
//This structure is used to define the operational interface for terminal id
support
typedef struct _TERM
{
    int          iNumEntries;              //total allocated
terminal array entries
    int          iFreeList;                //next available
terminal array element or -1 if none
    int          iMasterSyncId;           //synchronization id
    CLIENTDATA *pClientData;              //pointer to allocated
client data
} TERM;

typedef TERM *PTERM;                       //pointer to terminal
structure type
```

```
enum WEBERROR
{
    NO_ERR,
    ERR_COMMAND_UNDEFINED,
    ERR_D_ID_INVALID,
```

```

ERR_DELIVERY_CARRIER_ID_RANGE,
ERR_DELIVERY_CARRIER_INVALID,
ERR_DELIVERY_MISSING_OCD_KEY,
ERR_DELIVERY_THREAD_FAILED,
ERR_GETPROCADDR_FAILED,
ERR_HTML_ILL_FORMED,
ERR_INVALID_SYNC_CONNECTION,
ERR_INVALID_TERMID,
ERR_LOADDLL_FAILED,
ERR_MAX_CONNECTIONS_EXCEEDED,
ERR_MEM_ALLOC_FAILED,
ERR_MISSING_REGISTRY_ENTRIES,
ERR_NEWORDER_CUSTOMER_INVALID,
ERR_NEWORDER_CUSTOMER_KEY,
ERR_NEWORDER_DISTRICT_INVALID,
ERR_NEWORDER_FORM_MISSING_DID,
ERR_NEWORDER_ITEMID_INVALID,
ERR_NEWORDER_ITEMID_RANGE,
ERR_NEWORDER_ITEMID_WITHOUT_SUPPW,
ERR_NEWORDER_MISSING_IID_KEY,
ERR_NEWORDER_MISSING_QTY_KEY,
ERR_NEWORDER_MISSING_SUPPW_KEY,
ERR_NEWORDER_NOITEMS_ENTERED,
ERR_NEWORDER_QTY_INVALID,
ERR_NEWORDER_QTY_RANGE,
ERR_NEWORDER_QTY_WITHOUT_SUPPW,
ERR_NEWORDER_SUPPW_INVALID,
ERR_NO_SERVER_SPECIFIED,
ERR_ORDERSTATUS_CID_AND_CLT,
ERR_ORDERSTATUS_CID_INVALID,
ERR_ORDERSTATUS_CLT_RANGE,
ERR_ORDERSTATUS_DID_INVALID,
ERR_ORDERSTATUS_MISSING_CID_CLT,
ERR_ORDERSTATUS_MISSING_CID_KEY,
ERR_ORDERSTATUS_MISSING_CLT_KEY,
ERR_ORDERSTATUS_MISSING_DID_KEY,
ERR_PAYMENT_CDI_INVALID,
ERR_PAYMENT_CID_AND_CLT,
ERR_PAYMENT_CUSTOMER_INVALID,
ERR_PAYMENT_CWI_INVALID,
ERR_PAYMENT_DISTRICT_INVALID,
ERR_PAYMENT_HAM_INVALID,
ERR_PAYMENT_HAM_RANGE,
ERR_PAYMENT_LAST_NAME_TO_LONG,
ERR_PAYMENT_MISSING_CDI_KEY,
ERR_PAYMENT_MISSING_CID_CLT,
ERR_PAYMENT_MISSING_CID_KEY,
ERR_PAYMENT_MISSING_CLT,
ERR_PAYMENT_MISSING_CLT_KEY,
ERR_PAYMENT_MISSING_CWI_KEY,
ERR_PAYMENT_MISSING_DID_KEY,
ERR_PAYMENT_MISSING_HAM_KEY,
ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY,

```

```

ERR_STOCKLEVEL_THRESHOLD_INVALID,
ERR_STOCKLEVEL_THRESHOLD_RANGE,
ERR_VERSION_MISMATCH,
ERR_W_ID_INVALID
};

class CWEBCLNT_ERR : public CBaseErr
{
public:
    CWEBCLNT_ERR(WEBERROR Err)
    {
        m_Error = Err;
        m_szTextDetail = NULL;
        m_SystemErr = 0;
        m_szErrorText = NULL;
    };

    CWEBCLNT_ERR(WEBERROR Err, char *szTextDetail, DWORD dwSystemErr)
    {
        m_Error = Err;
        m_szTextDetail = new char[strlen(szTextDetail)+1];
        strcpy( m_szTextDetail, szTextDetail );
        m_SystemErr = dwSystemErr;
        m_szErrorText = NULL;
    };

    ~CWEBCLNT_ERR()
    {
        if ( m_szTextDetail != NULL)
            delete [] m_szTextDetail;
        if ( m_szErrorText != NULL)
            delete [] m_szErrorText;
    };

    WEBERROR    m_Error;
    char        *m_szTextDetail;    //
    char        *m_szErrorText;
    DWORD       m_SystemErr;

    int ErrorType() {return ERR_TYPE_WEBDLL;};
    int ErrorNum() {return m_Error;};
    char *ErrorText();
};

//These constants have already been defined in engstut.h, but since we do
//not want to include it in the delisrv executable
#define TXN_EVENT_START    2
#define TXN_EVENT_STOP    4
#define TXN_EVENT_WARNING 6    //used to record a warning into the log

//function prototypes

```

```

BOOL APIENTRY DllMain(HANDLE hModule, DWORD ul_reason_for_call, LPVOID
lpReserved);
void WriteMessageToEventLog(LPTSTR lpszMsg);
void ProcessQueryString(EXTENSION_CONTROL_BLOCK *pECB, int *pCmd, int
*pFormId, int *pTermId, int *pSyncId);
void WelcomeForm(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer);
void SubmitCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer);
void BeginCmd(EXTENSION_CONTROL_BLOCK *pECB, int iFormId, int iTermId);
void ProcessCmd(EXTENSION_CONTROL_BLOCK *pECB, int iFormId, int iTermId);
void StatsCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer);
void ErrorMessage(EXTENSION_CONTROL_BLOCK *pECB, int iError, int iErrorType,
char *szMsg, int iTermId);
void GetKeyValue(char **pQueryString, char *pKey, char *pValue, int iMax,
WEBERROR err);
int GetIntKeyValue(char **pQueryString, char *pKey, WEBERROR NoKeyErr,
WEBERROR NotIntErr);
void TermInit(void);
void TermDeleteAll(void);
int TermAdd(void);
void TermDelete(int id);
void ErrorForm(EXTENSION_CONTROL_BLOCK *pECB, int iType, int iErrorNum, int
iTermId, int iSyncId, char *szErrorText, char *szBuffer );
void MakeMainMenuForm(int iTermId, int iSyncId, char *szForm);
void MakeStockLevelForm(int iTermId, STOCK_LEVEL_DATA *pStockLevelData, BOOL
bInput, char *szForm);
void MakeNewOrderForm(int iTermId, NEW_ORDER_DATA *pNewOrderData, BOOL
bInput, char *szForm);
void MakePaymentForm(int iTermId, PAYMENT_DATA *pPaymentData, BOOL bInput,
char *szForm);
void MakeOrderStatusForm(int iTermId, ORDER_STATUS_DATA *pOrderStatusData,
BOOL bInput, char *szForm);
void MakeDeliveryForm(int iTermId, DELIVERY_DATA *pDeliveryData, BOOL
bInput, char *szForm);
void ProcessNewOrderForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer);
void ProcessPaymentForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer);
void ProcessOrderStatusForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer);
void ProcessDeliveryForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer);
void ProcessStockLevelForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer);
void GetNewOrderData(LPSTR lpszQueryString, NEW_ORDER_DATA *pNewOrderData);
void GetPaymentData(LPSTR lpszQueryString, PAYMENT_DATA *pPaymentData);
void GetOrderStatusData(LPSTR lpszQueryString, ORDER_STATUS_DATA
*pOrderStatusData);
BOOL PostDeliveryInfo(short w_id, short o_carrier_id);
BOOL IsNumeric(char *ptr);
BOOL IsDecimal(char *ptr);
void DeliveryWorkerThread(void *ptr);

```

```

//Microsoft Developer Studio generated resource script.
//
#include "resource.h"

#define APSTUDIO_READONLY_SYMBOLS
////////////////////////////////////
//
//
// Generated from the TEXTINCLUDE 2 resource.
//
#include "afxres.h"

////////////////////////////////////
//
//
#undef APSTUDIO_READONLY_SYMBOLS

////////////////////////////////////
//
//
// English (U.S.) resources

#if !defined(AFX_RESOURCE_DLL) || defined(AFX_TARG_ENU)
#ifdef _WIN32
LANGUAGE LANG_ENGLISH, SUBLANG_ENGLISH_US
#pragma code_page(1252)
#endif // _WIN32

#ifdef _MAC
////////////////////////////////////
//
//
// Version
//

VS_VERSION_INFO VERSIONINFO
FILEVERSION 0,4,0,0
PRODUCTVERSION 0,4,0,0
FILEFLAGSMASK 0x3fL
#ifdef _DEBUG
FILEFLAGS 0x1L
#else
FILEFLAGS 0x0L
#endif
#endif
FILEOS 0x40004L
FILETYPE 0x2L
FILESUBTYPE 0x0L
BEGIN
    BLOCK "StringFileInfo"
    BEGIN
        BLOCK "040904b0"
        BEGIN
            VALUE "Comments", "TPC-C HTML DLL Server (DBLIB)\0"
            VALUE "CompanyName", "Microsoft\0"
            VALUE "FileDescription", "TPC-C HTML DLL Server (DBLIB)\0"

```

```

        VALUE "FileVersion", "0, 4, 0, 0\0"
        VALUE "InternalName", "tpcc\0"
        VALUE "LegalCopyright", "Copyright © 1997\0"
        VALUE "OriginalFilename", "tpcc.dll\0"
        VALUE "ProductName", "Microsoft tpcc\0"
        VALUE "ProductVersion", "0, 4, 0, 0\0"
    END
END
BLOCK "VarFileInfo"
BEGIN
    VALUE "Translation", 0x409, 1200
END
END
#endif // !_MAC

#ifdef APSTUDIO_INVOKED
////////////////////////////////////
/
//
// TEXTINCLUDE
//

1 TEXTINCLUDE DISCARDABLE
BEGIN
    "resource.h\0"
END

2 TEXTINCLUDE DISCARDABLE
BEGIN
    "#include "afxres.h"\r\n"
    "\0"
END

3 TEXTINCLUDE DISCARDABLE
BEGIN
    "\r\n"
    "\0"
END

#endif // APSTUDIO_INVOKED

////////////////////////////////////
/
//
// Dialog
//

IDD_DIALOG1 DIALOG DISCARDABLE 0, 0, 186, 95
STYLE DS_MODALFRAME | WS_POPUP | WS_CAPTION | WS_SYSMENU
CAPTION "Dialog"

```

```

FONT 8, "MS Sans Serif"
BEGIN
    DEFPUSHBUTTON "OK",IDOK,129,7,50,14
    PUSHBUTTON "Cancel",IDCANCEL,129,24,50,14
END

////////////////////////////////////
/
//
// DESIGNINFO
//

#ifdef APSTUDIO_INVOKED
GUIDELINES DESIGNINFO DISCARDABLE
BEGIN
    IDD_DIALOG1, DIALOG
    BEGIN
        LEFTMARGIN, 7
        RIGHTMARGIN, 179
        TOPMARGIN, 7
        BOTTOMMARGIN, 88
    END
END
#endif // APSTUDIO_INVOKED

#endif // English (U.S.) resources
////////////////////////////////////
/

#ifdef APSTUDIO_INVOKED
////////////////////////////////////
/
//
// Generated from the TEXTINCLUDE 3 resource.
//

////////////////////////////////////
/
#endif // not APSTUDIO_INVOKED

/* FILE: TPCC.C
* Microsoft TPC-C Kit Ver. 4.20.000
* Copyright Microsoft, 1999
* All Rights Reserved
*
* Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
*

```

```

* PURPOSE: Main module for TPCC.DLL which is an ISAPI service dll.
* Contact: Charles Levine (clevine@microsoft.com)
*
* Change history:
* 4.20.000 - reworked error handling; added options for COM and
Encina txn monitors
*/

#include <windows.h>
#include <process.h>
#include <tchar.h>
#include <stdio.h>
#include <stdarg.h>
#include <malloc.h>
#include <stdlib.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>
#include <io.h>
#include <assert.h>

#include <sqltypes.h>

#ifdef ICECAP
#include <icapexp.h>
#endif

#include "..\..\common\src\trans.h" //tpckit transaction header
contains definitions of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "..\..\common\src\ReadRegistry.h"

#include "..\..\common\txnlog\include\rtetime.h"
#include "..\..\common\txnlog\include\spinlock.h"
#include "..\..\common\txnlog\include\txnlog.h"

// Database layer includes
#include "..\..\db_dblib_dll\src\tpcc_dblib.h" // DBLIB implementation
of TPC-C txns
#include "..\..\db_odbc_dll\src\tpcc_odbc.h" // ODBC implementation
of TPC-C txns

// Txn monitor layer includes
#include "..\..\tm_com_dll\src\tpcc_com.h" // COM Services
implementation on TPC-C txns
#include "..\..\tm_tuxedo_dll\src\tpcc_tux.h" // interface to Tuxedo
libraries
#include "..\..\tm_encina_dll\src\tpcc_enc.h" // interface to Encina
libraries

#include "httpext.h" //ISAPI DLL information header

```

```

#include "tpcc.h" //this dlls specific structure,
value e.t. header.

#define LEN_ERR_STRING 256

// defines for Make<Txn>Form calls to distinguish input and output flavors
#define OUTPUT_FORM 0
#define INPUT_FORM 1

char szMyComputerName[MAX_COMPUTERNAME_LENGTH+1];

//Terminal client id structure
TERM Term = { 0, 0, 0, NULL };

// The WEBCLIENT_VERSION string specifies the version level of this web
client interface.
// The RTE must be synchronized with the interface level on login, otherwise
the login
// will fail. This is a sanity check to catch problems resulting from
mismatched versions
// of the RTE and web client.
#define WEBCLIENT_VERSION "410"

static CRITICAL_SECTION TermCriticalSection;

static HINSTANCE hLibInstanceTm = NULL;
static HINSTANCE hLibInstanceDb = NULL;

TYPE_CTPCC_DBLIB *pCTPCC_DBLIB_new;
TYPE_CTPCC_ODBC *pCTPCC_ODBC_new;
TYPE_CTPCC_TUXEDO *pCTPCC_TUXEDO_new;
TYPE_CTPCC_ENCINA *pCTPCC_ENCINA_new;
TYPE_CTPCC_ENCINA *pCTPCC_ENCINA_post_init;
TYPE_CTPCC_COM *pCTPCC_COM_new;

// For deferred Delivery txns:
CTxnLog *txnDelilog = NULL; //used to log
delivery transaction information

HANDLE hWorkerSemaphore = INVALID_HANDLE_VALUE;
HANDLE hDoneEvent = INVALID_HANDLE_VALUE;
HANDLE *pDeliHandles = NULL;

// configuration settings from registry
TPCCREGISTRYDATA Reg;

DWORD dwNumDeliveryThreads = 4;
CRITICAL_SECTION DelBuffCriticalSection; //critical section
for delivery transactions cache
DELIVERY_TRANSACTION *pDelBuff = NULL;

```

```

DWORD          dwDelBuffSize      = 100;          // size of
circular buffer for delivery txns
DWORD          dwDelBuffFreeCount;                // number of
buffers free
DWORD          dwDelBuffBusyIndex = 0;           // index position
of entry waiting to be delivered
DWORD          dwDelBuffFreeIndex = 0;           // index position
of unused entry

#include "..\..\common\src\ReadRegistry.cpp"

/* FUNCTION: DllMain
 *
 * PURPOSE:   This function is the entry point for the DLL. This
implementation is based on the
 *           fact that DLL_PROCESS_ATTACH is only called from the inet
service once.
 *
 * ARGUMENTS: HANDLE    hModule          module handle
 *             DWORDul_reason_for_call  reason for call
 *             LPVOID    lpReserved      reserved for future use
 *
 * RETURNS:   BOOL FALSE                 errors ocured in
initialization
 *           TRUE                        DLL successfully
initialized
 */

BOOL APIENTRY DllMain(HANDLE hModule, DWORD ul_reason_for_call, LPVOID
lpReserved)
{
    DWORD i;
    char szEvent[LEN_ERR_STRING] = "\0";
    char szLogFile[128];
    char szDllName[128];

// debugging...
// DebugBreak();

    try
    {
        switch( ul_reason_for_call )
        {
            case DLL_PROCESS_ATTACH:
                {
                    DWORD dwSize = MAX_COMPUTERNAME_LENGTH+1;
                    GetComputerName(szMyComputerName, &dwSize);
                    szMyComputerName[dwSize] = 0;
                }

                DisableThreadLibraryCalls((HMODULE)hModule);
                InitializeCriticalSection(&TermCriticalSection);
            }
        }
    }
}

```

```

        if ( ReadTPCCRegistrySettings( &Reg ) )
            throw new CWEBCLNT_ERR(
ERR_MISSING_REGISTRY_ENTRIES );

        dwDelBuffSize = min( Reg.dwMaxPendingDeliveries, 10000
); // min with 10000 as a sanity constraint
        dwNumDeliveryThreads = min(
Reg.dwNumberOfDeliveryThreads, 100 ); // min with 100 as a sanity
constraint

        TermInit();

        // load DLL for txn monitor
        if (Reg.eTxnMon == TUXEDO)
        {
            strcpy( szDllName, Reg.szPath );
            strcat( szDllName, "tpcc_tuxedo.dll");
            hLibInstanceTm = LoadLibrary( szDllName );
            if (hLibInstanceTm == NULL)
                throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

            // get function pointer to wrapper for class
            constructor
                pCTPCC_TUXEDO_new = (TYPE_CTPCC_TUXEDO*)
GetProcAddress(hLibInstanceTm, "CTPCC_TUXEDO_new");
            if (pCTPCC_TUXEDO_new == NULL)
                throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
        }
        else if (Reg.eTxnMon == ENCINA)
        {
            strcpy( szDllName, Reg.szPath );
            strcat( szDllName, "tpcc_encina.dll");
            hLibInstanceTm = LoadLibrary( szDllName );
            if (hLibInstanceTm == NULL)
                throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

            // get function pointer to wrapper for class
            constructor
                pCTPCC_ENCINA_new = (TYPE_CTPCC_ENCINA*)
GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_new");
                pCTPCC_ENCINA_post_init = (TYPE_CTPCC_ENCINA*)
GetProcAddress(hLibInstanceTm, "CTPCC_ENCINA_post_init");
            if (pCTPCC_ENCINA_new == NULL)
                throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
        }
        else if (Reg.eTxnMon == COM)
        {
            strcpy( szDllName, Reg.szPath );
            strcat( szDllName, "tpcc_com.dll");
            hLibInstanceTm = LoadLibrary( szDllName );
        }
    }
}

```

```

        if (hLibInstanceTm == NULL)
            throw new CWEBCLNT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

        // get function pointer to wrapper for class
constructor
        pCTPCC_COM_new = (TYPE_CTPCC_COM*)
GetProcAddress(hLibInstanceTm, "CTPCC_COM_new");
        if (pCTPCC_COM_new == NULL)
            throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
    }

    // load DLL for database connection
    if ((Reg.eTxnMon == None) || (dwNumDeliveryThreads >
0))
    {
        if (Reg.eDB_Protocol == DBLIB)
        {
            strcpy( szDllName, Reg.szPath );
            strcat( szDllName, "tpcc_dblib.dll");
            hLibInstanceDb = LoadLibrary( szDllName );
            if (hLibInstanceDb == NULL)
                throw new CWEBCLNT_ERR(
ERR_LOADDLL_FAILED, szDllName, GetLastError() );

            // get function pointer to wrapper for class
constructor
            pCTPCC_DBLIB_new = (TYPE_CTPCC_DBLIB*)
GetProcAddress(hLibInstanceDb, "CTPCC_DBLIB_new");
            if (pCTPCC_DBLIB_new == NULL)
                throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
        }
        else if (Reg.eDB_Protocol == ODBC)
        {
            strcpy( szDllName, Reg.szPath );
            strcat( szDllName, "tpcc_odbc.dll");
            hLibInstanceDb = LoadLibrary( szDllName );
            if (hLibInstanceDb == NULL)
                throw new CWEBCLNT_ERR(
ERR_LOADDLL_FAILED, szDllName, GetLastError() );

            // get function pointer to wrapper for class
constructor
            pCTPCC_ODBC_new = (TYPE_CTPCC_ODBC*)
GetProcAddress(hLibInstanceDb, "CTPCC_ODBC_new");
            if (pCTPCC_ODBC_new == NULL)
                throw new CWEBCLNT_ERR(
ERR_GETPROCADDR_FAILED, szDllName, GetLastError() );
        }
    }
}

```

```

        if (dwNumDeliveryThreads)
        {
            // for deferred delivery txns:
            hDoneEvent = CreateEvent( NULL, TRUE /* manual
reset */, FALSE /* initially not signalled */, NULL );

            InitializeCriticalSection(&DelBuffCriticalSection);
            hWorkerSemaphore = CreateSemaphore( NULL, 0,
dwDelBuffSize, NULL );
            dwDelBuffFreeCount = dwDelBuffSize;

            InitJulianTime(NULL);

            // create unique log file name based on delilog-
yymmdd-hhmm.log
            SYSTEMTIME Time;
            GetLocalTime( &Time );
            wsprintf( szLogFile, "%sdelivery-%2.2d%2.2d%2.2d-
%2.2d%2.2d.log",
                    Reg.szPath, Time.wYear % 100,
Time.wMonth, Time.wDay, Time.wHour, Time.wMinute );
            txnDelilog = new CTxnLog(szLogFile,
TXN_LOG_WRITE);

            //write event into txn log for START
            txnDelilog->WriteCtrlRecToLog(TXN_EVENT_START,
szMyComputerName, sizeof(szMyComputerName));

            // allocate structures for delivery buffers and
thread mgmt
            pDeliHandles = new HANDLE[dwNumDeliveryThreads];
            pDelBuff = new
DELIVERY_TRANSACTION[dwDelBuffSize];
            // launch DeliveryWorkerThread to perform actual
delivery txns
            for(i=0; i<dwNumDeliveryThreads; i++)
            {
                pDeliHandles[i] = (HANDLE) _beginthread(
DeliveryWorkerThread, 0, NULL );
                if (pDeliHandles[i] == INVALID_HANDLE_VALUE)
                    throw new CWEBCLNT_ERR(
ERR_DELIVERY_THREAD_FAILED );
            }
        }

        break;

    case DLL_PROCESS_DETACH:
        if (dwNumDeliveryThreads)
        {
            if (txnDelilog != NULL)
            {
                //write event into txn log for STOP

```

```

        txnDelilog->WriteCtrlRecToLog(TXN_EVENT_STOP,
szMyComputerName, sizeof(szMyComputerName));

        // This will do a clean shutdown of the
delivery log file

        CTxnLog *txnDelilogLocal = txnDelilog;
        txnDelilog= NULL;
        delete txnDelilogLocal;
    }

    delete [] pDeliHandles;
    delete [] pDelBuff;

    CloseHandle( hWorkerSemaphore );
    CloseHandle( hDoneEvent );
    DeleteCriticalSection(&DelBuffCriticalSection);
}

DeleteCriticalSection(&TermCriticalSection);

if (hLibInstanceTm != NULL)
    FreeLibrary( hLibInstanceTm );
hLibInstanceTm = NULL;

if (hLibInstanceDb != NULL)
    FreeLibrary( hLibInstanceDb );
hLibInstanceDb = NULL;

Sleep(500);
break;

default:
    /* nothing */;
}
}
catch (CBaseErr *e)
{
    WriteMessageToEventLog( e->ErrorText() );
    delete e;
    TerminateExtension(0);
    return FALSE;
}
catch (...)
{
    WriteMessageToEventLog(TEXT("Unhandled exception. DLL could not
load."));
    TerminateExtension(0);
    return FALSE;
}

return TRUE;
}

```

```

/* FUNCTION: GetExtensionVersion
*
* PURPOSE:      This function is called by the inet service when the DLL is
first loaded.
*
* ARGUMENTS:   HSE_VERSION_INFO *pVerpassed in structure in which to
place expected version number.
*
* RETURNS:     TRUE inet service expected return value.
*/

BOOL WINAPI GetExtensionVersion(HSE_VERSION_INFO *pVer)
{
    pVer->dwExtensionVersion = MAKELONG(HSE_VERSION_MINOR,
HSE_VERSION_MAJOR);
    lstrcpy(pVer->lpszExtensionDesc, "TPC-C Server.",
HSE_MAX_EXT_DLL_NAME_LEN);

    // TODO: why do we need this here instead of in the DLL attach?
    if (Reg.eTxnMon == ENCINA)
        pCTPCC_ENCINA_post_init();

    return TRUE;
}

/* FUNCTION: TerminateExtension
*
* PURPOSE:     This function is called by the inet service when the DLL is
about to be unloaded.
*
*             Release all resources in anticipation of being unloaded.
*
* RETURNS:     TRUE inet service expected return value.
*/

BOOL WINAPI TerminateExtension( DWORD dwFlags )
{
    if (pDeliHandles)
    {
        SetEvent( hDoneEvent );
        for(DWORD i=0; i<dwNumDeliveryThreads; i++)
            WaitForSingleObject( pDeliHandles[i], INFINITE );
    }

    TermDeleteAll();
    return TRUE;
}

/* FUNCTION: HttpExtensionProc
*
* PURPOSE:     This function is the main entry point for the TPCC DLL. The
internet service

```

```

*          calls this function passing in the http string.
*
* ARGUMENTS:  EXTENSION_CONTROL_BLOCK   *pECBstructure pointer to passed
in internet
*
*                                     service
information.
*
* RETURNS:    DWORDHSE_STATUS_SUCCESS
             connection can be dropped if error
*
*             HSE_STATUS_SUCCESS_AND_KEEP_CONN   keep
connect valid comment sent
*
* COMMENTS:   None
*
*/

DWORD WINAPI HttpExtensionProc(EXTENSION_CONTROL_BLOCK *pECB)
{
    int          iCmd, FormId, TermId, iSyncId;
    char         szBuffer[4096];

    int          lpbSize;
    static char  szHeader[] = "200 Ok";
    DWORD        dwSize = 6;          // initial value is strlen(szHeader)
    char         szHeader1[4096];

#ifdef ICECAP
    StartCAP();
#endif

    try
    {
        //process http query
        ProcessQueryString(pECB, &iCmd, &FormId, &TermId, &iSyncId);

        if (TermId != 0)
        {
            if ( TermId < 0 || TermId >= Term.iNumEntries ||
Term.pClientData[TermId].iNextFree != -1 )
            {
                // debugging...
                char szTmp[128];
                wsprintf( szTmp, "Invalid term ID; TermId = %d", TermId
);

                WriteMessageToEventLog( szTmp );

                throw new CWEBCLNT_ERR( ERR_INVALID_TERMID );
            }

            //must have a valid syncid here since termid is valid
            if (iSyncId != Term.pClientData[TermId].iSyncId)
                throw new CWEBCLNT_ERR( ERR_INVALID_SYNC_CONNECTION );

```

```

        //set use time
        Term.pClientData[TermId].iTickCount = GetTickCount();
    }

    switch(iCmd)
    {
    case 0:
        WelcomeForm(pECB, szBuffer);
        break;
    case 1:
        switch( FormId )
        {
            case WELCOME_FORM:
            case MAIN_MENU_FORM:
                break;
            case NEW_ORDER_FORM:
                ProcessNewOrderForm(pECB, TermId, szBuffer);
                break;
            case PAYMENT_FORM:
                ProcessPaymentForm(pECB, TermId, szBuffer);
                break;
            case DELIVERY_FORM:
                ProcessDeliveryForm(pECB, TermId, szBuffer);
                break;
            case ORDER_STATUS_FORM:
                ProcessOrderStatusForm(pECB, TermId, szBuffer);
                break;
            case STOCK_LEVEL_FORM:
                ProcessStockLevelForm(pECB, TermId, szBuffer);
                break;
        }
        break;
    case 2:
        // new-order selected from menu; display new-order input form
        MakeNewOrderForm(TermId, NULL, INPUT_FORM, szBuffer);
        break;
    case 3:
        // payment selected from menu; display payment input form
        MakePaymentForm(TermId, NULL, INPUT_FORM, szBuffer);
        break;
    case 4:
        // delivery selected from menu; display delivery input form
        MakeDeliveryForm(TermId, NULL, INPUT_FORM, szBuffer);
        break;
    case 5:
        // order-status selected from menu; display order-status
input form
        MakeOrderStatusForm(TermId, NULL, INPUT_FORM, szBuffer);
        break;
    case 6:

```

```

        // stock-level selected from menu; display stock-level input
form
        MakeStockLevelForm(TermId, NULL, INPUT_FORM, szBuffer);
        break;
    case 7:
        // ExitCmd
        TermDelete(TermId);
        WelcomeForm(pECB, szBuffer);
        break;
    case 8:
        SubmitCmd(pECB, szBuffer);
        break;
    case 9:
        // menu
        MakeMainMenuForm(TermId, Term.pClientData[TermId].iSyncId,
szBuffer);
        break;
    case 10:
        // CMD=Clear
        // resets all connections; should only be used when no other
connections are active
        TermDeleteAll();
        TermInit();
        WelcomeForm(pECB, szBuffer);
        break;
    case 11: // CMD=Stats
        StatsCmd(pECB, szBuffer);
        break;
    }
}
catch (CBaseErr *e)
{
    ErrorForm( pECB, e->ErrorType(), e->ErrorNum(), TermId, iSyncId,
e->ErrorText(), szBuffer );
    delete e;
}
catch (...)
{
    ErrorForm( pECB, ERR_TYPE_WEBDLL, 0, TermId, iSyncId, "Error:
Unhandled exception in Web Client.", szBuffer );
}

#ifdef ICECAP
    StopCAP();
#endif

    lpbSize = strlen(szBuffer);
    wsprintf(szHeader1,
        "Content-Type: text/html\r\n"
        "Content-Length: %d\r\n"
        "Connection: Keep-Alive\r\n\r\n" , lpbSize);
    strcat( szHeader1, szBuffer );

```

```

        (*pECB->ServerSupportFunction)(pECB->ConnID,
HSE_REQ_SEND_RESPONSE_HEADER, szHeader, (LPDWORD) &dwSize,
(LPDWORD)szHeader1);

```

```

        //finish up and keep connection
        pECB->dwHttpStatusCode = 200;
        return HSE_STATUS_SUCCESS_AND_KEEP_CONN;
    }

```

```

void WriteMessageToEventLog(LPTSTR lpszMsg)
{

```

```

    TCHAR    szMsg[256];
    HANDLE   hEventSource;
    LPTSTR   lpszStrings[2];

```

```

    // Use event logging to log the error.
    //
    hEventSource = RegisterEventSource(NULL, TEXT("TPCC.DLL"));

```

```

    _stprintf(szMsg, TEXT("Error in TPCC.DLL: "));
    lpszStrings[0] = szMsg;
    lpszStrings[1] = lpszMsg;

```

```

    if (hEventSource != NULL)
    {

```

```

        ReportEvent(hEventSource, // handle of event source
            EVENTLOG_ERROR_TYPE, // event type
            0, // event category
            0, // event ID
            NULL, // current user's SID
            2, // strings in lpszStrings
            0, // no bytes of raw data
            (LPCTSTR *)lpszStrings, // array of error strings
            NULL); // no raw data

```

```

        (VOID) DeregisterEventSource(hEventSource);
    }
}

```

```

/* FUNCTION: DeliveryWorkerThread

```

```

 *
 * PURPOSE: This function processes deferred delivery txns. There are
typically several
 * threads running this routine. The number of threads is
determined by an entry
 * read from the registry. The thread waits for work by waiting
on semaphore.
 * When a delivery txn is posted, the semaphore is released.
After processing

```

```

*           the delivery txn, information is logged to record the txn
status and execution
*           time.
*/

/*static*/ void DeliveryWorkerThread(void *ptr)
{
    CTPCC_BASE      *pTxn = NULL;

    DELIVERY_TRANSACTION      delivery;
    PDELIVERY_DATA            pDeliveryData;
    TXN_RECORD_TPCC_DELIV_DEF txnDeliRec;

    DWORD              index;
    HANDLE              handles[2];

    SYSTEMTIME         trans_end;      //delivery transaction finished time
    SYSTEMTIME         trans_start;    //delivery transaction start time

    assert(txnDelilog != NULL);

    try
    {
        if (Reg.eDB_Protocol == ODBC)
            pTxn = pCTPCC_ODBC_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
        else if (Reg.eDB_Protocol == DBLIB)
            pTxn = pCTPCC_DBLIB_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
        pDeliveryData = pTxn->BuffAddr_Delivery();
    }
    catch (CBaseErr *e)
    {
        char szTmp[1024];
        wsprintf( szTmp, "Error in Delivery Txn thread. Could not connect
to database. "
                "%s. Server=%s, User=%s, Password=%s, Database=%s",
                e->ErrorText(), Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, Reg.szDbName );
        WriteMessageToEventLog( szTmp );
        delete e;
        goto ErrorExit;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception caught in
DeliveryWorkerThread."));
        goto ErrorExit;
    }

    while (TRUE)
    {
        try

```

```

        {
            //while delivery thread running, i.e. user has not requested
termination
            while (TRUE)
            {
                // need to wait for multiple objects: program exit or
worker semaphore;
                handles[0] = hDoneEvent;
                handles[1] = hWorkerSemaphore;
                index = WaitForMultipleObjects( 2, &handles[0], FALSE,
INFINITE );

                if (index == WAIT_OBJECT_0)
                    goto ErrorExit;

                ZeroMemory(&txnDeliRec, sizeof(txnDeliRec));
                txnDeliRec.TxnType = TXN_REC_TYPE_TPCC_DELIV_DEF;

                // make a local copy of current entry from delivery
buffer and increment buffer index
                EnterCriticalSection(&DelBuffCriticalSection);
                delivery = *(pDelBuff+dwDelBuffBusyIndex);
                dwDelBuffFreeCount++;
                dwDelBuffBusyIndex++;
                if (dwDelBuffBusyIndex == dwDelBuffSize) // wrap-
around if at end of buffer
                    dwDelBuffBusyIndex = 0;

                LeaveCriticalSection(&DelBuffCriticalSection);

                pDeliveryData->w_id = delivery.w_id;
                pDeliveryData->o_carrier_id = delivery.o_carrier_id;

                txnDeliRec.w_id = pDeliveryData->w_id;
                txnDeliRec.o_carrier_id = pDeliveryData->o_carrier_id;
                txnDeliRec.TxnStartT0 = Get64BitTime(&delivery.queue);

                GetLocalTime( &trans_start );
                pTxn->Delivery();
                GetLocalTime( &trans_end );

                //log txn
                txnDeliRec.TxnStatus = ERR_SUCCESS;
                for (int i=0; i<10; i++)
                    txnDeliRec.o_id[i] = pDeliveryData->o_id[i];
                txnDeliRec.DeltaT4 = (int)(Get64BitTime(&trans_end) -
txnDeliRec.TxnStartT0);
                txnDeliRec.DeltaTxnExec =
(int)(Get64BitTime(&trans_end) - Get64BitTime(&trans_start));

                if (txnDelilog != NULL)
                    txnDelilog->WriteToLog(&txnDeliRec);
            }
        }
    }
}

```

```

catch (CBaseErr *e)
{
    char szTmp[1024];
    wsprintf( szTmp, "Error in Delivery Txn thread.  %s", e-
>ErrorText() );
    WriteMessageToEventLog( szTmp );

    // log the error txn
    txnDeliRec.TxnStatus = e->ErrorType();
    if (txnDelilog != NULL)
        txnDelilog->WriteToLog(&txnDeliRec);

    delete e;
}
catch (...)
{
    // unhandled exception; shouldn't happen; not much we can
do...
    WriteMessageToEventLog(TEXT("Unhandled exception caught in
DeliveryWorkerThread."));
}
}

ErrorExit:
    delete pTxn;
    _endthread();
}

/* FUNCTION: PostDeliveryInfo
*
* PURPOSE:      This function enters the delivery txn into the deferred
delivery buffer.
*
* RETURNS:      BOOL FALSE delivery information posted successfully
                TRUE error cannot post delivery info
*/

BOOL PostDeliveryInfo(short w_id, short o_carrier_id)
{
    BOOL bError;

    EnterCriticalSection(&DelBuffCriticalSection);
    if (dwDelBuffFreeCount > 0)
    {
        bError = FALSE;
        (pDelBuff+dwDelBuffFreeIndex)->w_id      = w_id;
        (pDelBuff+dwDelBuffFreeIndex)->o_carrier_id = o_carrier_id;
        GetLocalTime(&(pDelBuff+dwDelBuffFreeIndex)->queue);

        dwDelBuffFreeCount--;
        dwDelBuffFreeIndex++;
        if (dwDelBuffFreeIndex == dwDelBuffSize)

```

```

        dwDelBuffFreeIndex = 0;          // wrap-around if at end of
buffer
    }
    else
        // No free buffers.  Return an error, which indicates that the
delivery buffer is full.
        // Most likely, the number of delivery worker threads needs to be
increased to keep up
        // with the txn rate.
        bError = TRUE;
    LeaveCriticalSection(&DelBuffCriticalSection);

    if (!bError)
        // increment worker semaphore to wake up a worker thread
        ReleaseSemaphore( hWorkerSemaphore, 1, NULL );

    return bError;
}

/* FUNCTION: ProcessQueryString
*
* PURPOSE:      This function extracts the relevent information out of the
http command passed in from
*               the browser.
*
* COMMENTS:     If this is the initial connection i.e. client is at welcome
screen then
*               there will not be a terminal id or current form id.  If
this is the case
*               then the pTermid and pFormid return values are
undefined.
*/

void ProcessQueryString(EXTENSION_CONTROL_BLOCK *pECB, int *pCmd, int
*pFormId, int *pTermId, int *pSyncId)
{
    char *ptr = pECB->lpszQueryString;
    char szBuffer[25];
    int i;

    //allowable client command strings i.e. CMD=command
    static char *szCmds[] =
    {
        "Process", "..NewOrder..", "..Payment..", "..Delivery..",
"..Order-Status..", "..Stock-Level..",
        "..Exit..", "Submit", "Menu", "Clear", "Stats", ""
    };

    *pCmd = 0;          // default is the login screen
    *pTermId = 0;

    // if no params (i.e., empty query string), then return login screen
    if (strlen(pECB->lpszQueryString) == 0)

```

```

return;

// parse FORMID, TERMID, and SYNCID
*pFormId = GetIntKeyValue(&ptr, "FORMID", NO_ERR, NO_ERR);
*pTermId = GetIntKeyValue(&ptr, "TERMID", NO_ERR, NO_ERR);
*pSyncId = GetIntKeyValue(&ptr, "SYNCID", NO_ERR, NO_ERR);

// parse CMD
GetKeyValue(&ptr, "CMD", szBuffer, sizeof(szBuffer),
ERR_COMMAND_UNDEFINED);

// see which command it matches
for(i=0; ; i++)
{
    if (szCmds[i][0] == 0)
        // no more; no match; return error
        throw new CWEBCLNT_ERR( ERR_COMMAND_UNDEFINED );
    if ( !strcmp(szCmds[i], szBuffer) )
    {
        *pCmd = i+1;
        break;
    }
}

/* FUNCTION: void WelcomeForm
 *
 */

void WelcomeForm(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer)
{
    char szTmp[1024];

    //welcome to tpc-c html form buffer, this is first form client sees.
    strcpy( szBuffer, "<HTML><HEAD><TITLE>TPC-C Web
Client</TITLE></HEAD><BODY>"
" <B><BIG>Microsoft TPC-C Web Client (ver
4.20)</BIG></B> <BR> <BR>"
" <font face=\"Courier New\"><PRE>"
"Compiled: \"__DATE__\", \"__TIME__\" <BR>"
"Source: \"__FILE__\" (\"__TIMESTAMP__\") <BR>"
" </PRE></font>"
" <FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
" <INPUT TYPE=\"hidden\" NAME=\"STATUSID\""
VALUE=\"0\">"
" <INPUT TYPE=\"hidden\" NAME=\"ERROR\""
VALUE=\"0\">"
" <INPUT TYPE=\"hidden\" NAME=\"FORMID\""
VALUE=\"1\">"
" <INPUT TYPE=\"hidden\" NAME=\"TERMID\""
VALUE=\"0\">"
" <INPUT TYPE=\"hidden\" NAME=\"SYNCID\""
VALUE=\"0\">"

```

```

" <INPUT TYPE=\"hidden\" NAME=\"VERSION\""
VALUE=\"\" WEBCLIENT_VERSION "\>"
);

sprintf( szTmp, "Configuration Settings: <BR><font face=\"Courier New\""
color=\"blue\"><PRE>"
"Txn Monitor = <B>%s</B><BR>"
"Database protocol = <B>%s</B><BR>"
"Max Connections = <B>%d</B><BR>"
"# of Delivery Threads = <B>%d</B><BR>"
"Max Pending Deliveries = <B>%d</B><BR>"
, szTxnMonNames[Reg.eTxnMon], szDBNames[Reg.eDB_Protocol],
Reg.dwMaxConnections, dwNumDeliveryThreads, dwDelBuffSize );
strcat( szBuffer, szTmp);

if (Reg.eTxnMon == COM)
{
    sprintf( szTmp, "COM Single Pool = <B>%s</B><BR>",
Reg.bCOM_SinglePool ? "YES" : "NO" );
    strcat( szBuffer, szTmp);
}
strcat( szBuffer, "</PRE></font>");

if (Reg.eTxnMon == None)
    // connection options may be specified when not using a txn
monitor
    sprintf( szTmp, "Please enter your database options for this
connection:<BR>"
" <font face=\"Courier New\""
color=\"blue\"><PRE>"
"DB Server = <INPUT NAME=\"db_server\""
SIZE=20 VALUE=\"%s\"><BR>"
"DB User ID = <INPUT NAME=\"db_user\""
SIZE=20 VALUE=\"%s\"><BR>"
"DB Password = <INPUT NAME=\"db_passwd\""
SIZE=20 VALUE=\"%s\"><BR>"
"DB Name = <INPUT NAME=\"db_name\""
SIZE=20 VALUE=\"%s\"><BR>"
" </PRE></font>"
, Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
Reg.szDbName );
else
    // if using a txn monitor, connection options are determined from
registry; can't
    // set per user. show options fyi
    sprintf( szTmp, "Database options which will be used by the
transaction monitor:<BR>"
" <font face=\"Courier New\""
color=\"blue\"><PRE>"
"DB Server = <B>%s</B><BR>"
"DB User ID = <B>%s</B><BR>"
"DB Password = <B>%s</B><BR>"
"DB Name = <B>%s</B><BR>"

```

```

        "</PRE></font>"
        , Reg.szDbServer, Reg.szDbUser, Reg.szDbPassword,
Reg.szDbName );
    strcat( szBuffer, szTmp);

    sprintf( szTmp, "Please enter your Warehouse and District for this
session:<BR>"
        "<font face=\"Courier New\" color=\"blue\"><PRE>"
);
    strcat( szBuffer, szTmp);
    strcat( szBuffer,
        "Warehouse ID = <INPUT NAME=\"w_id\" SIZE=4><BR>"
        "District ID = <INPUT NAME=\"d_id\"
        SIZE=2><BR>"
        "</PRE></font><HR>"
        "<INPUT TYPE=\"submit\" NAME=\"CMD\"
        VALUE=\"Submit\">"
);
}

/* FUNCTION: SubmitCmd
 *
 * PURPOSE: This function allocated a new terminal id in the Term
structure array.
 *
 */

void SubmitCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer)
{
    int iNewTerm;
    char *ptr = pECB->lpszQueryString;

    char szVersion[32] = { 0 };
    char szServer[32] = { 0 };
    char szUser[32] = "sa";
    char szPassword[32] = { 0 };
    char szDatabase[32] = "tpcc";

    // validate version field; the version field ensures that the RTE is
synchronized with the web client
    GetKeyValue(&ptr, "VERSION", szVersion, sizeof(szVersion),
ERR_VERSION_MISMATCH);
    if ( strcmp( szVersion, WEBCCLIENT_VERSION ) )
        throw new CWEBCLNT_ERR( ERR_VERSION_MISMATCH );

    if (Reg.eTxnMon == None)
    {
        // parse Server name
        GetKeyValue(&ptr, "db_server", szServer, sizeof(szServer),
ERR_NO_SERVER_SPECIFIED);
        // parse User name
        GetKeyValue(&ptr, "db_user", szUser, sizeof(szUser), NO_ERR);
        // parse Password

```

```

        GetKeyValue(&ptr, "db_passwd", szPassword, sizeof(szPassword),
NO_ERR);
        // parse Database name
        GetKeyValue(&ptr, "db_name", szDatabase, sizeof(szDatabase),
NO_ERR);
    }

    // parse warehouse ID
    int w_id = GetIntKeyValue(&ptr, "w_id", ERR_HTML_ILL_FORMED,
ERR_W_ID_INVALID);
    if ( w_id < 1 )
        throw new CWEBCLNT_ERR( ERR_W_ID_INVALID );

    // parse district ID
    int d_id = GetIntKeyValue(&ptr, "d_id", ERR_HTML_ILL_FORMED,
ERR_D_ID_INVALID);
    if ( d_id < 1 || d_id > 10 )
        throw new CWEBCLNT_ERR( ERR_D_ID_INVALID );

    iNewTerm = TermAdd();

    Term.pClientData[iNewTerm].w_id = w_id;
    Term.pClientData[iNewTerm].d_id = d_id;

    try
    {
        if (Reg.eTxnMon == TUXEDO)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_TUXEDO_new();
        else if (Reg.eTxnMon == ENCINA)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_ENCINA_new();
        else if (Reg.eTxnMon == COM)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_COM_new(
Reg.bCOM_SinglePool );
        else if (Reg.eDB_Protocol == ODBC)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_ODBC_new( szServer,
szUser, szPassword, szMyComputerName, szDatabase );
        else if (Reg.eDB_Protocol == DBLIB)
            Term.pClientData[iNewTerm].pTxn = pCTPCC_DBLIB_new( szServer,
szUser, szPassword, szMyComputerName, szDatabase );
    }
    catch (...)
    {
        TermDelete(iNewTerm);
        throw; // pass exception upward
    }

    MakeMainMenuForm(iNewTerm, Term.pClientData[iNewTerm].iSyncId,
szBuffer);
}

/* FUNCTION: StatsCmd
 *

```

```

* PURPOSE:      This function returns to the browser the total number of
active terminal ids.
*              This routine is for development/debugging purposes.
*
*/

```

```

void StatsCmd(EXTENSION_CONTROL_BLOCK *pECB, char *szBuffer)
{
    int i;
    int iTot;

    EnterCriticalSection(&TermCriticalSection);

    iTot = 0;
    for(i=0; i<Term.iNumEntries; i++)
    {
        if (Term.pClientData[i].iNextFree == -1)
            iTot++;
    }

    LeaveCriticalSection(&TermCriticalSection);

    wsprintf( szBuffer,
              "<HTML><HEAD><TITLE>TPC-C Web Client Stats</TITLE></HEAD>"
              "<BODY><B><BIG> Total Active Connections: %d"
              "</BIG></B><BR></BODY></HTML>"
              , iTot );
}

```

```

char *CWEBCLNT_ERR::ErrorText()
{
    static SERRORMSG errorMsgs[] =
    {
        { ERR_COMMAND_UNDEFINED, "Command undefined." },
        { ERR_D_ID_INVALID, "District ID Must be 1 to 10." },
        { ERR_DELIVERY_CARRIER_ID_RANGE, "ID out of range must be 1 - 10." },
        { ERR_DELIVERY_CARRIER_INVALID, "ID invalid must be numeric 1 - 10." },
        { ERR_DELIVERY_MISSING_OCD_KEY, "Carrier ID key \"OCD*\"." },
        { ERR_DELIVERY_THREAD_FAILED, "start delivery worker thread." },
        { ERR_GETPROCADDR_FAILED, "map proc in DLL. GetProcAddr error. DLL=" },
        { ERR_HTML_ILL_FORMED, "is missing from HTML string." },
        { ERR_INVALID_SYNC_CONNECTION, "Sync ID." },
        { ERR_INVALID_TERMID, "Terminal ID." }
    },
}

```

```

failed. DLL="
{ ERR_LOADDLL_FAILED, "Load of DLL" },
{ ERR_MAX_CONNECTIONS_EXCEEDED, "No connections" },
available. Max Connections is probably too low." },
{ ERR_MISSING_REGISTRY_ENTRIES, "Required registry" },
entries are missing. Rerun INSTALL to correct." },
{ ERR_NEWORDER_CUSTOMER_INVALID, "New Order customer" },
id invalid data type, range = 1 to 3000." },
{ ERR_NEWORDER_CUSTOMER_KEY, "New Order missing" },
Customer key \"CID*\"." },
{ ERR_NEWORDER_DISTRICT_INVALID, "New Order District" },
ID Invalid range 1 - 10." },
{ ERR_NEWORDER_FORM_MISSING_DID, "New Order missing" },
District key \"DID*\"." },
{ ERR_NEWORDER_ITEMID_INVALID, "New Order Item Id" },
is wrong data type, must be numeric." },
{ ERR_NEWORDER_ITEMID_RANGE, "New Order Item Id" },
is out of range. Range = 1 to 999999." },
{ ERR_NEWORDER_ITEMID_WITHOUT_SUPPW, "New Order Item_Id" },
field entered without a corresponding Supp_W." },
{ ERR_NEWORDER_MISSING_IID_KEY, "New Order missing" },
Item Id key \"IID*\"." },
{ ERR_NEWORDER_MISSING_QTY_KEY, "New Order Missing" },
Qty key \"Qty##*\"." },
{ ERR_NEWORDER_MISSING_SUPPW_KEY, "New Order missing" },
Supp_W key \"SP##*\"." },
{ ERR_NEWORDER_NOITEMS_ENTERED, "New Order No order" },
lines entered." },
{ ERR_NEWORDER_QTY_INVALID, "New Order Qty" },
invalid must be numeric range 1 - 99." },
{ ERR_NEWORDER_QTY_RANGE, "New Order" },
Qty is out of range. Range = 1 to 99." },
{ ERR_NEWORDER_QTY_WITHOUT_SUPPW, "New Order Qty" },
field entered without a corresponding Supp_W." },
{ ERR_NEWORDER_SUPPW_INVALID, "New Order" },
Supp_W invalid data type must be numeric." },
{ ERR_NO_SERVER_SPECIFIED, "No Server name" },
specified." },
{ ERR_ORDERSTATUS_CID_AND_CLT, "Order Status Only" },
Customer ID or Last Name may be entered, not both." },
{ ERR_ORDERSTATUS_CID_INVALID, "Order Status" },
Customer ID invalid, range must be numeric 1 - 3000." },
{ ERR_ORDERSTATUS_CLT_RANGE, "Order Status" },
Customer last name longer than 16 characters." },
{ ERR_ORDERSTATUS_DID_INVALID, "Order Status" },
District invalid, value must be numeric 1 - 10." },
{ ERR_ORDERSTATUS_MISSING_CID_CLT, "Order Status" },
Either Customer ID or Last Name must be entered." },
{ ERR_ORDERSTATUS_MISSING_CID_KEY, "Order Status" },
missing Customer key \"CID*\"." },
{ ERR_ORDERSTATUS_MISSING_CLT_KEY, "Order Status" },
missing Customer Last Name key \"CLT*\"." },
}

```

```

    { ERR_ORDERSTATUS_MISSING_DID_KEY, "Order Status
missing District key \"DID*\".\"",
    { ERR_PAYMENT_CDI_INVALID, "Payment Customer
district invalid must be numeric." },
    { ERR_PAYMENT_CID_AND_CLT, "Payment Only
Customer ID or Last Name may be entered, not both." },
    { ERR_PAYMENT_CUSTOMER_INVALID, "Payment Customer
data type invalid, must be numeric." },
    { ERR_PAYMENT_CWI_INVALID, "Payment Customer
Warehouse invalid, must be numeric." },
    { ERR_PAYMENT_DISTRICT_INVALID, "Payment District
ID is invalid, must be 1 - 10." },
    { ERR_PAYMENT_HAM_INVALID, "Payment Amount
invalid data type must be numeric." },
    { ERR_PAYMENT_HAM_RANGE, "Payment
Amount out of range, 0 - 9999.99." },
    { ERR_PAYMENT_LAST_NAME_TO_LONG, "Payment Customer
last name longer than 16 characters." },
    { ERR_PAYMENT_MISSING_CDI_KEY, "Payment missing
Customer district key \"CDI*\".\"",
    { ERR_PAYMENT_MISSING_CID_CLT, "Payment Either
Customer ID or Last Name must be entered." },
    { ERR_PAYMENT_MISSING_CID_KEY, "Payment missing
Customer Key \"CID*\".\"",
    { ERR_PAYMENT_MISSING_CLT_KEY, "Payment missing
Customer Last Name key \"CLT*\".\"",
    { ERR_PAYMENT_MISSING_CWI_KEY, "Payment missing
Customer Warehouse key \"CWI*\".\"",
    { ERR_PAYMENT_MISSING_DID_KEY, "Payment missing
District Key \"DID*\".\"",
    { ERR_PAYMENT_MISSING_HAM_KEY, "Payment missing
Amount key \"HAM*\".\"",
    { ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY, "Stock Level;
missing Threshold key \"TT*\".\"",
    { ERR_STOCKLEVEL_THRESHOLD_INVALID, "Stock Level;
Threshold value must be in the range = 1 - 99." },
    { ERR_STOCKLEVEL_THRESHOLD_RANGE, "Stock Level
Threshold out of range, range must be 1 - 99." },
    { ERR_VERSION_MISMATCH, "Invalid
version field. RTE and Web Client are probably out of sync." },
    { ERR_W_ID_INVALID, "Invalid
Warehouse ID." },
    { 0, "" },
};

char szTmp[256];
int i = 0;
while (TRUE)
{
    if (errorMsgs[i].szMsg[0] == 0)
    {

```

```

        strcpy( szTmp, "Unknown error number." );
        break;
    }
    if (m_Error == errorMsgs[i].iError)
    {
        strcpy( szTmp, errorMsgs[i].szMsg );
        break;
    }
    i++;
}

if (m_szTextDetail)
    strcat( szTmp, m_szTextDetail );
if (m_SystemErr)
    sprintf( szTmp+strlen(szTmp), " Error=%d", m_SystemErr );

m_szErrorText = new char[strlen(szTmp)+1];
strcpy( m_szErrorText, szTmp );
return m_szErrorText;
}

/* FUNCTION: GetKeyValue
 *
 * PURPOSE: This function parses a http formatted string for specific key
values.
 *
 * ARGUMENTS: char *pQueryString http string from client
browser char *pKey key value to look for
char *pValue character array
into which to place key's value
int iMax maximum length of
key value array.
* WEBERROR err error value to
throw
 *
 * RETURNS: nothing.
 *
 * ERROR: if (the pKey value is not found) then
 * if (err == 0)
 * return (empty string)
 * else
 * throw CWEBCLNT_ERR(err)
 *
 * COMMENTS: http keys are formatted either KEY=value& or KEY=value\0.
This DLL formats
 * TPC-C input fields in such a manner that the keys can
be extracted in the
 * above manner.
 */

```

```

void GetKeyValue(char **pQueryString, char *pKey, char *pValue, int iMax,
WEBERROR err)
{
    char *ptr;

    if ( !(ptr=strstr(*pQueryString, pKey)) )
        goto ErrorExit;
    ptr += strlen(pKey);
    if ( *ptr != '=' )
        goto ErrorExit;
    ptr++;

    iMax--; // one position is for terminating null
    while( *ptr && *ptr != '&' && iMax)
    {
        *pValue++ = *ptr++;
        iMax--;
    }
    *pValue = 0; // terminating null

    *pQueryString = ptr;
    return;

ErrorExit:
    if (err != NO_ERR)
        throw new CWEBCLNT_ERR( err );
    *pValue = 0; // return empty result string
}

/* FUNCTION: GetIntKeyValue
 *
 * PURPOSE:      This function parses a http formatted string for a specific
key value.
 *
 * ARGUMENTS:   char          *pQueryString  http string from client
browser
 *              char          *pKey          key value to look for
 *              WEBERROR      NoKeyErr      error value to throw if
key not found
 *              WEBERROR      NotIntErr     error value to throw if
value not numeric
 *
 * RETURNS:     integer
 *
 * ERROR:       if (the pKey value is not found) then
 *               if (NoKeyErr != NO_ERR)
 *                   throw CWEBCLNT_ERR(err)
 *               else
 *                   return 0
 *               else if (non-numeric char found) then
 *                   if (NotIntErr != NO_ERR) then
 *                       throw CWEBCLNT_ERR(err)
 *                   else

```

```

return 0
 *
 * COMMENTS:     http keys are formatted either KEY=value& or KEY=value\0.
This DLL formats
 *              TPC-C input fields in such a manner that the keys can
be extracted in the
 *              above manner.
 */

int GetIntKeyValue(char **pQueryString, char *pKey, WEBERROR NoKeyErr,
WEBERROR NotIntErr)
{
    char *ptr0;
    char *ptr;

    if ( !(ptr=strstr(*pQueryString, pKey)) )
        goto ErrorNoKey;
    ptr += strlen(pKey);
    if ( *ptr != '=' )
        goto ErrorNoKey;
    ptr++;

    ptr0 = ptr; // remember starting point
    // scan string until a terminator (null or &) or a non-digit
    while( *ptr && *ptr != '&' && isdigit(*ptr) )
        ptr++;

    // make sure we stopped scanning for the right reason
    if ((ptr0 == ptr) || (*ptr && *ptr != '&'))
    {
        if (NotIntErr != NO_ERR)
            throw new CWEBCLNT_ERR( NoKeyErr );
        return 0;
    }

    *pQueryString = ptr;
    return atoi(ptr0);

ErrorNoKey:
    if (NoKeyErr != NO_ERR)
        throw new CWEBCLNT_ERR( NoKeyErr );
    return 0;
}

/* FUNCTION: TermInit
 *
 * PURPOSE:      This function initializes the client terminal structure; it
is called when the TPCC.DLL
 *              is first loaded by the inet service.
 *
 */

void TermInit(void)

```

```

{
    EnterCriticalSection(&TermCriticalSection);

    Term.iMasterSyncId    = 1;
    Term.iNumEntries      = Reg.dwMaxConnections+1;

    Term.pClientData      = NULL;
    Term.pClientData      = (PCLIENTDATA)malloc(Term.iNumEntries *
sizeof(CLIENTDATA));
    if (Term.pClientData == NULL)
    {
        LeaveCriticalSection(&TermCriticalSection);
        throw new CWEBCLNT_ERR( ERR_MEM_ALLOC_FAILED );
    }

    ZeroMemory( Term.pClientData, Term.iNumEntries * sizeof(CLIENTDATA) );

    Term.iFreeList        = Term.iNumEntries-1;
    // build free list
    // note: Term.pClientData[0].iNextFree gets set to -1, which marks it
as "in use".
    // This is intentional, as the zero entry is used as an anchor
and never
    // allocated as an actual terminal.
    for(int i=0; i<Term.iNumEntries; i++)
        Term.pClientData[i].iNextFree = i-1;

    LeaveCriticalSection(&TermCriticalSection);
}

/* FUNCTION: TermDeleteAll
 *
 * PURPOSE:      This function frees allocated resources associated with the
terminal structure.
 *
 * ARGUMENTS:    none
 *
 * RETURNS:      None
 *
 * COMMENTS:     This function is called only when the inet service unloads
the TPCC.DLL
 *
 */

void TermDeleteAll(void)
{
    EnterCriticalSection(&TermCriticalSection);

    for(int i=1; i<Term.iNumEntries; i++)
    {
        if (Term.pClientData[i].iNextFree == -1)
            delete Term.pClientData[i].pTxn;
    }
}

```

```

    Term.iFreeList        = 0;
    Term.iNumEntries      = 0;
    if ( Term.pClientData )
        free(Term.pClientData);
    Term.pClientData      = NULL;

    LeaveCriticalSection(&TermCriticalSection);
}

/* FUNCTION: TermAdd
 *
 * PURPOSE:      This function assigns a terminal id which is used to identify
a client browser.
 *
 * RETURNS:      int          assigned terminal id
 *
 */

int TermAdd(void)
{
    DWORD i;
    int    iNewTerm, iTickCount;

    if (Term.iNumEntries == 0)
        return -1;

    EnterCriticalSection(&TermCriticalSection);
    if (Term.iFreeList != 0)
    {
        // position is available
        iNewTerm = Term.iFreeList;
        Term.iFreeList = Term.pClientData[iNewTerm].iNextFree;
        Term.pClientData[iNewTerm].iNextFree = -1; // indicates this
position is in use
    }
    else
    {
        // no open slots, so find the slot that hasn't been used in the
longest time and reuse it
        for(iNewTerm=1, i=1, iTickCount=0x7FFFFFFF;
i<Reg.dwMaxConnections; i++)
        {
            if (iTickCount > Term.pClientData[i].iTickCount)
            {
                iTickCount = Term.pClientData[i].iTickCount;
                iNewTerm = i;
            }
        }
        // if oldest term is less than one minute old, it probably means
that more connections
        // are being attempted than were specified as "Max Connections" at
install. In this case,
        // do not bump existing connection; instead, return error to
requestor.
    }
}

```

```

    if ((GetTickCount() - iTickCount) < 60000)
    {
        LeaveCriticalSection(&TermCriticalSection);
        throw new CWEBCLNT_ERR( ERR_MAX_CONNECTIONS_EXCEEDED );
    }
}

Term.pClientData[iNewTerm].iTickCount = GetTickCount();
Term.pClientData[iNewTerm].iSyncId = Term.iMasterSyncId++;
Term.pClientData[iNewTerm].pTxn = NULL;

LeaveCriticalSection(&TermCriticalSection);
return iNewTerm;
}

/* FUNCTION: TermDelete
 *
 * PURPOSE:      This function makes a terminal entry in the Term array
available for reuse.
 *
 * ARGUMENTS:   int          id          Terminal id of
client exiting
 *
 */

void TermDelete(int id)
{
    if ( id > 0 && id < Term.iNumEntries )
    {
        delete Term.pClientData[id].pTxn;

        // put onto free list
        EnterCriticalSection(&TermCriticalSection);

        Term.pClientData[id].iNextFree = Term.iFreeList;
        Term.iFreeList = id;

        LeaveCriticalSection(&TermCriticalSection);
    }
}

/* FUNCTION: MakeErrorForm
 */

void ErrorForm(EXTENSION_CONTROL_BLOCK *pECB, int iType, int iErrorNum, int
iTermId, int iSyncId, char *szErrorText, char *szBuffer )
{
    wsprintf(szBuffer,
        "<HTML><HEAD><TITLE>TPC-C Error</TITLE></HEAD><BODY>"
        "<FORM ACTION=\\\"tpcc.dll\\\" METHOD=\\\"GET\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"STATUSID\\\" VALUE=\\\"%d\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"ERROR\\\" VALUE=\\\"%d\\\">"

```

```

        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"FORMID\\\" VALUE=\\\"%d\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"TERMINID\\\" VALUE=\\\"%d\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"SYNCID\\\" VALUE=\\\"%d\\\">"
        "<BOLD>An Error Occurred</BOLD><BR><BR>"
        "%s"
        "<BR><BR><HR>"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..NewOrder..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Payment..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Delivery..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Order-Status..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Stock-Level..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Exit..\\\">"
        "</FORM></BODY></HTML>"
        , iType, iErrorNum, MAIN_MENU_FORM, iTermId, iSyncId, szErrorText
    );
}

/* FUNCTION: MakeMainMenuForm
 */

void MakeMainMenuForm(int iTermId, int iSyncId, char *szForm)
{
    wsprintf(szForm,
        "<HTML><HEAD><TITLE>TPC-C Main Menu</TITLE></HEAD><BODY>"
        "Select Desired Transaction.<BR><HR>"
        "<FORM ACTION=\\\"tpcc.dll\\\" METHOD=\\\"GET\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"STATUSID\\\" VALUE=\\\"0\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"ERROR\\\" VALUE=\\\"0\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"FORMID\\\" VALUE=\\\"%d\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"TERMINID\\\" VALUE=\\\"%d\\\">"
        "<INPUT TYPE=\\\"hidden\\\" NAME=\\\"SYNCID\\\" VALUE=\\\"%d\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..NewOrder..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Payment..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Delivery..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Order-Status..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Stock-Level..\\\">"
        "<INPUT TYPE=\\\"submit\\\" NAME=\\\"CMD\\\" VALUE=\\\"..Exit..\\\">"
        "</FORM></BODY></HTML>"
        , MAIN_MENU_FORM, iTermId, iSyncId);
}

/* FUNCTION: MakeStockLevelForm
 *
 * PURPOSE:      This function constructs the Stock Level HTML page.
 *
 * COMMENTS:     The internal client buffer is created when the terminal id is
assigned and should not
                be freed except when the client terminal id is no
longer needed.
 */

void MakeStockLevelForm(int iTermId, STOCK_LEVEL_DATA *pStockLevelData, BOOL
bInput, char *szForm)

```

```

{
    int c;

    c = wsprintf(szForm,
        "<HTML><HEAD><TITLE>TPC-C Stock Level</TITLE></HEAD><FORM
ACTION=\\"tpcc.dll\\" METHOD=\\"GET\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"STATUSID\\" VALUE=\\"0\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"ERROR\\" VALUE=\\"0\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"FORMID\\" VALUE=\\"%d\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"TERMINID\\" VALUE=\\"%d\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"SYNCID\\" VALUE=\\"%d\\">"
        "<PRE><font face=\\"Courier\\">"
Stock-Level<BR>"
        "Warehouse: %4.4d District: %2.2d<BR> <BR>",
        STOCK_LEVEL_FORM, iTermId, Term.pClientData[iTermId].iSyncId,
        Term.pClientData[iTermId].w_id, Term.pClientData[iTermId].d_id);

    if ( bInput )
    {
        strcpy(szForm+c,
            "Stock Level Threshold: <INPUT NAME=\\"TT*\\" SIZE=2><BR> <BR>"
            "low stock: </font><BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>"
<BR> <BR>"
            " <BR> <BR> <BR> <BR> <BR> <BR> <BR></PRE><HR>"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"Process\\">"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"Menu\\">"
            "</FORM></HTML> " );
    }
    else
    {
        wsprintf(szForm+c,
            "Stock Level Threshold: %2.2d<BR> <BR>"
            "low stock: %3.3d</font> <BR> <BR> <BR> <BR> <BR> <BR> <BR>"
<BR> <BR>"
            " <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR></PRE><HR>"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"..NewOrder..\\">"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"..Payment..\\">"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"..Delivery..\\">"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"..Order-
Status..\\">"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"..Stock-
Level..\\">"
            "<INPUT TYPE=\\"submit\\" NAME=\\"CMD\\" VALUE=\\"..Exit..\\">"
            "</FORM></HTML>"
            , pStockLevelData->threshold, pStockLevelData->low_stock);
    }
}

/* FUNCTION: MakeNewOrderForm
*
* COMMENTS: The internal client buffer is created when the terminal id is
assigned and should not

```

```

*
* be freed except when the client terminal id is no
longer needed.
*/

void MakeNewOrderForm(int iTermId, NEW_ORDER_DATA *pNewOrderData, BOOL
bInput, char *szForm)
{
    int i, c;
    BOOL bValid;
    static char szBR[] = " <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR> <BR> <BR> <BR> <BR> <BR> <BR>";

    if (!bInput)
        assert( pNewOrderData->exec_status_code == eOK || pNewOrderData-
>exec_status_code == eInvalidItem );

    bValid = (bInput || (pNewOrderData->exec_status_code == eOK));

    c = wsprintf(szForm,
        "<HTML><HEAD><TITLE>TPC-C New Order</TITLE></HEAD><BODY>"
        "<FORM ACTION=\\"tpcc.dll\\" METHOD=\\"GET\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"STATUSID\\" VALUE=\\"%d\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"ERROR\\" VALUE=\\"0\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"FORMID\\" VALUE=\\"%d\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"TERMINID\\" VALUE=\\"%d\\">"
        "<INPUT TYPE=\\"hidden\\" NAME=\\"SYNCID\\" VALUE=\\"%d\\">"
        "<PRE><font face=\\"Courier\\">"
New Order<BR>"
        , bValid ? 0 : ERR_BAD_ITEM_ID, NEW_ORDER_FORM, iTermId,
        Term.pClientData[iTermId].iSyncId);

    if ( bInput )
    {
        c += wsprintf(szForm+c, "Warehouse: %4.4d ",
        Term.pClientData[iTermId].w_id );

        strcpy( szForm+c,
            "District: <INPUT NAME=\\"DID*\\" SIZE=1>"
Date:<BR>"
            "Customer: <INPUT NAME=\\"CID*\\" SIZE=4> Name:"
Credit: %Disc:<BR>"
            "Order Number: Number of Lines: W_tax:"
D_tax:<BR> <BR>"
            " Supp_W Item_Id Item Name Qty Stock B/G"
Price Amount<BR>"
            " <INPUT NAME=\\"SP00*\\" SIZE=4> <INPUT NAME=\\"IID00*\\"
SIZE=6> <INPUT NAME=\\"Qty00*\\" SIZE=1><BR>"
            " <INPUT NAME=\\"SP01*\\" SIZE=4> <INPUT NAME=\\"IID01*\\"
SIZE=6> <INPUT NAME=\\"Qty01*\\" SIZE=1><BR>"
            " <INPUT NAME=\\"SP02*\\" SIZE=4> <INPUT NAME=\\"IID02*\\"
SIZE=6> <INPUT NAME=\\"Qty02*\\" SIZE=1><BR>"
            " <INPUT NAME=\\"SP03*\\" SIZE=4> <INPUT NAME=\\"IID03*\\"
SIZE=6> <INPUT NAME=\\"Qty03*\\" SIZE=1><BR>"

```

```

" <INPUT NAME=\"SP04*\" SIZE=4> <INPUT NAME=\"IID04*\"
SIZE=6> <INPUT NAME=\"Qty04*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP05*\" SIZE=4> <INPUT NAME=\"IID05*\"
SIZE=6> <INPUT NAME=\"Qty05*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP06*\" SIZE=4> <INPUT NAME=\"IID06*\"
SIZE=6> <INPUT NAME=\"Qty06*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP07*\" SIZE=4> <INPUT NAME=\"IID07*\"
SIZE=6> <INPUT NAME=\"Qty07*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP08*\" SIZE=4> <INPUT NAME=\"IID08*\"
SIZE=6> <INPUT NAME=\"Qty08*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP09*\" SIZE=4> <INPUT NAME=\"IID09*\"
SIZE=6> <INPUT NAME=\"Qty09*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP10*\" SIZE=4> <INPUT NAME=\"IID10*\"
SIZE=6> <INPUT NAME=\"Qty10*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP11*\" SIZE=4> <INPUT NAME=\"IID11*\"
SIZE=6> <INPUT NAME=\"Qty11*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP12*\" SIZE=4> <INPUT NAME=\"IID12*\"
SIZE=6> <INPUT NAME=\"Qty12*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP13*\" SIZE=4> <INPUT NAME=\"IID13*\"
SIZE=6> <INPUT NAME=\"Qty13*\" SIZE=1><BR>\"
" <INPUT NAME=\"SP14*\" SIZE=4> <INPUT NAME=\"IID14*\"
SIZE=6> <INPUT NAME=\"Qty14*\" SIZE=1><BR>\"
"Execution Status:
Total:<BR>\"
</font></PRE><HR>\"
<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Process\">
<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">
</FORM></HTML>\"
);
}
else
{
c += wsprintf(szForm+c, \"Warehouse: %4.4d District: %2.2d
Date: \",
pNewOrderData->w_id,
pNewOrderData->d_id);

if ( bValid )
{
c += wsprintf(szForm+c, \"%2.2d-%2.2d-%4.4d
%2.2d:%2.2d:%2.2d\",
pNewOrderData->o_entry_d.day,
pNewOrderData->o_entry_d.month,
pNewOrderData->o_entry_d.year,
pNewOrderData->o_entry_d.hour,
pNewOrderData->o_entry_d.minute,
pNewOrderData->o_entry_d.second);
}

c += wsprintf(szForm+c, \"<BR>Customer: %4.4d Name: %-16s
Credit: %-2s \",
pNewOrderData->c_id, pNewOrderData->c_last, pNewOrderData-
>c_credit);

```

```

if ( bValid )
{
c += sprintf(szForm+c,
\"%%Disc: %5.2f <BR>\"
\"Order Number: %8.8d Number of Lines: %2.2d
W_tax: %5.2f D_tax: %5.2f <BR> <BR>\"
\" Supp_W Item_Id Item Name
Qty Stock B/G Price Amount<BR>\",
100.0*pNewOrderData->c_discount,
pNewOrderData->o_id,
pNewOrderData->o_ol_cnt,
100.0 * pNewOrderData->w_tax,
100.0 * pNewOrderData->d_tax);

for(i=0; i<pNewOrderData->o_ol_cnt; i++)
{
c += sprintf(szForm+c, \" %4.4d %6.6d %24s %2.2d
%3.3d %1.1s $%6.2f $%7.2f <BR>\",
pNewOrderData->OL[i].ol_supply_w_id,
pNewOrderData->OL[i].ol_i_id,
pNewOrderData->OL[i].ol_i_name,
pNewOrderData->OL[i].ol_quantity,
pNewOrderData->OL[i].ol_stock,
pNewOrderData->OL[i].ol_brand_generic,
pNewOrderData->OL[i].ol_i_price,
pNewOrderData->OL[i].ol_amount );
}
}
else
{
c += wsprintf(szForm+c,
\"%%Disc:<BR>\"
\"Order Number: %8.8d Number of Lines:
W_tax: D_tax:<BR> <BR>\"
\" Supp_W Item_Id Item Name Qty Stock
B/G Price Amount<BR>\"
, pNewOrderData->o_id);

i = 0;

strncpy( szForm+c, szBR, (15-i)*5 );
c += (15-i)*5;

if ( bValid )
c += sprintf(szForm+c, \"Execution Status: Transaction
committed. Total: $%8.2f \",
pNewOrderData->total_amount);
else
c += wsprintf(szForm+c, \"Execution Status: Item number is not
valid. Total:\");
}

```

```

strcpy(szForm+c,
" <BR></font></PRE><HR>"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..NewOrder..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Payment..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Delivery..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Order-
Status..\">"
Level..\">"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Stock-
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Exit..\">"
"</FORM></HTML>"
);
}
}
/* FUNCTION: MakePaymentForm
*
* COMMENTS: The internal client buffer is created when the terminal id is
assigned and should not
* be freed except when the client terminal id is no
longer needed.
*/

void MakePaymentForm(int iTermId, PAYMENT_DATA *pPaymentData, BOOL bInput,
char *szForm)
{
int c;

c = sprintf(szForm,
"<HTML><HEAD><TITLE>TPC-C Payment</TITLE></HEAD><BODY>"
"<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
"<INPUT TYPE=\"hidden\" NAME=\"STATUSID\" VALUE=\"0\">"
"<INPUT TYPE=\"hidden\" NAME=\"ERROR\" VALUE=\"0\">"
"<INPUT TYPE=\"hidden\" NAME=\"FORMID\" VALUE=\"%d\">"
"<INPUT TYPE=\"hidden\" NAME=\"TERMINID\" VALUE=\"%d\">"
"<INPUT TYPE=\"hidden\" NAME=\"SYNCID\" VALUE=\"%d\">"
"<PRE><font face=\"Courier\">"
Payment<BR>"
"Date: "
, PAYMENT_FORM, iTermId, Term.pClientData[iTermId].iSyncId);

if ( !bInput )
{
c += sprintf(szForm+c, "%2.2d-%2.2d-%4.4d %2.2d:%2.2d:%2.2d",
pPaymentData->h_date.day,
pPaymentData->h_date.month,
pPaymentData->h_date.year,
pPaymentData->h_date.hour,
pPaymentData->h_date.minute,
pPaymentData->h_date.second);
}

if ( bInput )

```

```

{
c += sprintf(szForm+c,
"<BR> <BR>Warehouse: %4.4d"
" District: <INPUT NAME=\"DID*\"
SIZE=1><BR> <BR> <BR> <BR> <BR>"
"Customer: <INPUT NAME=\"CID*\" SIZE=4>"
"Cust-Warehouse: <INPUT NAME=\"CWI*\" SIZE=4> "
"Cust-District: <INPUT NAME=\"CDI*\" SIZE=1><BR>"
"Name: <INPUT NAME=\"CLT*\" SIZE=16>"
Since:<BR>"
"
Credit:<BR>"
"
Disc:<BR>"
Phone:<BR>"
<BR>"
"Amount Paid: $<INPUT NAME=\"HAM*\" SIZE=7> New
Cust-Balance:<BR>"
"Credit Limit:<BR> <BR>Cust-Data: <BR> <BR> <BR> <BR>
<BR></font></PRE><HR>"
"<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Process\"><INPUT
TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">"
"</BODY></FORM></HTML>"
, Term.pClientData[iTermId].w_id);
}
else
{
c += sprintf(szForm+c,
"<BR> <BR>Warehouse: %4.4d"
" District:
%2.2d<BR>"
"%-20s %-20s<BR>"
"%-20s %-20s<BR>"
"%-20s %-2s %5.5s-%4.4s %-20s %-2s %5.5s-%4.4s<BR>"
<BR>"
"Customer: %4.4d Cust-Warehouse: %4.4d Cust-District:
%2.2d<BR>"
"Name: %-16s %-2s %-16s Since: %2.2d-%2.2d-%4.4d<BR>"
" %-20s Credit: %-2s<BR>"
, Term.pClientData[iTermId].w_id, pPaymentData->d_id
, pPaymentData->w_street_1, pPaymentData->d_street_1
, pPaymentData->w_street_2, pPaymentData->d_street_2
, pPaymentData->w_city, pPaymentData->w_state, pPaymentData-
>w_zip, pPaymentData->w_zip+5
, pPaymentData->d_city, pPaymentData->d_state, pPaymentData-
>d_zip, pPaymentData->d_zip+5
, pPaymentData->c_id, pPaymentData->c_w_id, pPaymentData-
>c_d_id
, pPaymentData->c_first, pPaymentData->c_middle,
pPaymentData->c_last
, pPaymentData->c_since.day, pPaymentData->c_since.month,
pPaymentData->c_since.year
, pPaymentData->c_street_1, pPaymentData->c_credit
);
}
}

```

```

c += sprintf(szForm+c,
             "          %-20s                %%Disc:  %5.2f<BR>",
             pPaymentData->c_street_2, 100.0*pPaymentData->c_discount);

c += wsprintf(szForm+c,
              "          %-20s %-2s %5.5s-%4.4s          Phone:  %6.6s-%3.3s-
%3.3s-%4.4s<BR> <BR>",
              pPaymentData->c_city, pPaymentData->c_state, pPaymentData-
->c_zip, pPaymentData->c_zip+5,
              pPaymentData->c_phone, pPaymentData->c_phone+6, pPaymentData-
->c_phone+9, pPaymentData->c_phone+12 );

c += sprintf(szForm+c,
             "Amount Paid:          $%7.2f          New Cust-Balance:
$%14.2f<BR>"
             "Credit Limit:   $%13.2f<BR> <BR>"
             , pPaymentData->h_amount, pPaymentData->c_balance
             , pPaymentData->c_credit_lim
             );

if ( pPaymentData->c_credit[0] == 'B' && pPaymentData->c_credit[1]
== 'C' )
    c += wsprintf(szForm+c,
                  "Cust-Data:  %-50.50s<BR>          %-50.50s<BR>
%-50.50s<BR>          %-50.50s<BR>",
                  pPaymentData->c_data, pPaymentData->c_data+50,
pPaymentData->c_data+100, pPaymentData->c_data+150 );
    else
        strcpy(szForm+c, "Cust-Data: <BR> <BR> <BR> <BR>");

        strcat(szForm, " <BR></font></PRE><HR>"
        " <INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..NewOrder..\">"
        " <INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..Payment..\">"
        " <INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..Delivery..\">"
        " <INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..Order-Status..\">"
        " <INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..Stock-Level..\">"
        " <INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..Exit..\">"
        " </BODY></FORM></HTML>");
    }
}

/* FUNCTION: MakeOrderStatusForm
*
* COMMENTS:   The internal client buffer is created when the terminal id is
assigned and should not

```

```

*
* be freed except when the client terminal id is no
longer needed.
*/

void MakeOrderStatusForm(int iTermId, ORDER_STATUS_DATA *pOrderStatusData,
BOOL bInput, char *szForm)
{
    int i, c;
    static char szBR[] = " <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR> <BR> <BR> <BR> <BR> <BR> <BR>";

    c = wsprintf(szForm,
                 "<HTML><HEAD><TITLE>TPC-C Order-Status</TITLE></HEAD><BODY>"
                 "<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
                 "<INPUT TYPE=\"hidden\" NAME=\"STATUSID\" VALUE=\"0\">"
                 "<INPUT TYPE=\"hidden\" NAME=\"ERROR\" VALUE=\"0\">"
                 "<INPUT TYPE=\"hidden\" NAME=\"FORMID\" VALUE=\"%d\">"
                 "<INPUT TYPE=\"hidden\" NAME=\"TERMINID\" VALUE=\"%d\">"
                 "<INPUT TYPE=\"hidden\" NAME=\"SYNCID\" VALUE=\"%d\">"
                 "<PRE><font face=\"Courier\">"
Order-Status<BR>"
                 "Warehouse: %4.4d ",
                 ORDER_STATUS_FORM, iTermId, Term.pClientData[iTermId].iSyncId,
Term.pClientData[iTermId].w_id);

    if ( bInput )
    {
        strcpy(szForm+c,
               "District: <INPUT NAME=\"DID*\" SIZE=1><BR>"
               "Customer: <INPUT NAME=\"CID*\" SIZE=4> Name:
<INPUT NAME=\"CLT*\" SIZE=23><BR>"
               "Cust-Balance:<BR> <BR>"
               "Order-Number:          Entry-Date:
Carrier-Number:<BR>"
               "Supply-W      Item-Id      Qty      Amount      Delivery-
Date<BR> <BR> <BR> <BR> <BR>"
               " <BR> <BR>
<BR></font></PRE>"
               "<HR><INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"Process\"><INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">"
               "</BODY></FORM></HTML> " );
    }
    else
    {
        c += wsprintf(szForm+c,
                     "District: %2.2d<BR>"
                     "Customer: %4.4d Name: %-16s %-2s %-16s<BR>",
                     pOrderStatusData->d_id, pOrderStatusData->c_id,
pOrderStatusData->c_first, pOrderStatusData->c_middle,
pOrderStatusData->c_last);

        c += sprintf(szForm+c, "Cust-Balance: $%9.2f<BR> <BR>",
pOrderStatusData->c_balance);
    }
}

```

```

    c += sprintf(szForm+c,
        "Order-Number: %8.8d  Entry-Date: %2.2d-%2.2d-%4.4d
%2.2d:%2.2d:%2.2d  Carrier-Number: %2.2d<BR>"
        "Supply-W  Item-Id  Qty  Amount  Delivery-
Date<BR>",
        pOrderStatusData->o_id,
        pOrderStatusData->o_entry_d.day,
        pOrderStatusData->o_entry_d.month,
        pOrderStatusData->o_entry_d.year,
        pOrderStatusData->o_entry_d.hour,
        pOrderStatusData->o_entry_d.minute,
        pOrderStatusData->o_entry_d.second,
        pOrderStatusData->o_carrier_id);

for(i=0; i< pOrderStatusData->o_ol_cnt; i++)
{
    c += sprintf(szForm+c, " %4.4d %6.6d %2.2d
%8.2f %2.2d-%2.2d-%4.4d<BR>",
        pOrderStatusData->OL[i].ol_supply_w_id,
        pOrderStatusData->OL[i].ol_i_id,
        pOrderStatusData->OL[i].ol_quantity,
        pOrderStatusData->OL[i].ol_amount,
        pOrderStatusData->OL[i].ol_delivery_d.day,
        pOrderStatusData->OL[i].ol_delivery_d.month,
        pOrderStatusData->OL[i].ol_delivery_d.year);
}

strncpy( szForm+c, szBR, (15-i)*5 );
c += (15-i)*5;

strncpy(szForm+c,
    "</font></PRE><HR><INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..NewOrder..\">"
    "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Payment..\">"
    "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Delivery..\">"
    "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Order-
Status..\">"
    "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Stock-
Level..\">"
    "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Exit..\">"
    "</BODY></FORM></HTML>" );
}

/* FUNCTION: MakeDeliveryForm
*
* COMMENTS: The internal client buffer is created when the terminal id is
assigned and should not
* be freed except when the client terminal id is no
longer needed.
*/

```

```

void MakeDeliveryForm(int iTermId, DELIVERY_DATA *pDeliveryData, BOOL
bInput, char *szForm)
{
    int c;

    c = sprintf(szForm,
        "<HTML><HEAD><TITLE>TPC-C Delivery</TITLE></HEAD><BODY>"
        "<FORM ACTION=\"tpcc.dll\" METHOD=\"GET\">"
        "<INPUT TYPE=\"hidden\" NAME=\"STATUSID\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"ERROR\" VALUE=\"0\">"
        "<INPUT TYPE=\"hidden\" NAME=\"FORMID\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"TERMIN\" VALUE=\"%d\">"
        "<INPUT TYPE=\"hidden\" NAME=\"SYNCID\" VALUE=\"%d\">"
        "<PRE><font face=\"Courier\">"
Delivery<BR>"
        "Warehouse: %4.4d<BR> <BR>",
        (!bInput && (pDeliveryData->exec_status_code != eOK)) ?
ERR_TYPE_DELIVERY_POST : 0,
        DELIVERY_FORM, iTermId, Term.pClientData[iTermId].iSyncId,
Term.pClientData[iTermId].w_id);

    if ( bInput )
    {
        strcpy( szForm+c,
            "Carrier Number: <INPUT NAME=\"OCD\" SIZE=1><BR> <BR>"
            "Execution Status: <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR>"
            " <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> </font></PRE><HR>"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Process\">"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"Menu\">"
            "</BODY></FORM></HTML>" );
    }
    else
    {
        sprintf( szForm+c,
            "Carrier Number: %2.2d<BR> <BR>"
            "Execution Status: %s <BR> <BR> <BR> <BR> <BR> <BR> <BR>
<BR>"
            " <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> <BR> </font></PRE>"
            "<HR><INPUT TYPE=\"submit\" NAME=\"CMD\"
VALUE=\"..NewOrder..\">"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Payment..\">"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Delivery..\">"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Order-
Status..\">"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Stock-
Level..\">"
            "<INPUT TYPE=\"submit\" NAME=\"CMD\" VALUE=\"..Exit..\">"
            "</BODY></FORM></HTML>" );

        , pDeliveryData->o_carrier_id,
        (pDeliveryData->exec_status_code == eOK) ? "Delivery has been
queued." : "Delivery Post Failed "
    );
}

```

```

    }
}

/* FUNCTION: ProcessNewOrderForm
 *
 * PURPOSE:      This function gets and validates the input data from the new
order form
 *              filling in the required input variables. it then calls the
SQLNewOrder
 *              transaction, constructs the output form and writes it back to
client
 *              browser.
 */

void ProcessNewOrderForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    PNEW_ORDER_DATA    pNewOrder;

    pNewOrder = Term.pClientData[iTermId].pTxn->BuffAddr_NewOrder();

    ZeroMemory(pNewOrder, sizeof(NEW_ORDER_DATA));
    pNewOrder->w_id = Term.pClientData[iTermId].w_id;
    GetNewOrderData(pECB->lpszQueryString, pNewOrder);

    Term.pClientData[iTermId].pTxn->NewOrder();

    pNewOrder = Term.pClientData[iTermId].pTxn->BuffAddr_NewOrder();
    MakeNewOrderForm(iTermId, pNewOrder, OUTPUT_FORM, szBuffer );
}

/* FUNCTION: void ProcessPaymentForm
 *
 * PURPOSE:      This function gets and validates the input data from the
payment form
 *              filling in the required input variables. It then calls the
SQLPayment
 *              transaction, constructs the output form and writes it back to
client
 *              browser.
 *
 * ARGUMENTS:    EXTENSION_CONTROL_BLOCK *pECBpassed in structure pointer
from inetsrv.
 *              int iTermId client
browser terminal id
 */

void ProcessPaymentForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    PPAYMENT_DATA    pPayment;

```

```

    pPayment = Term.pClientData[iTermId].pTxn->BuffAddr_Payment();
    ZeroMemory(pPayment, sizeof(PAYMENT_DATA));
    pPayment->w_id = Term.pClientData[iTermId].w_id;
    GetPaymentData(pECB->lpszQueryString, pPayment);

    Term.pClientData[iTermId].pTxn->Payment();

    pPayment = Term.pClientData[iTermId].pTxn->BuffAddr_Payment();
    MakePaymentForm(iTermId, pPayment, OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessOrderStatusForm
 *
 * PURPOSE:      This function gets and validates the input data from the
Order Status
 *              form filling in the required input variables. It then calls
the
 *              SQLOrderStatus transaction, constructs the output form and
writes it
 *              back to client browser.
 *
 * ARGUMENTS:    EXTENSION_CONTROL_BLOCK *pECBpassed in structure pointer
from inetsrv.
 *              int iTermId client
browser terminal id
 */

void ProcessOrderStatusForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    PORDER_STATUS_DATA    pOrderStatus;

    pOrderStatus = Term.pClientData[iTermId].pTxn->BuffAddr_OrderStatus();
    ZeroMemory(pOrderStatus, sizeof(ORDER_STATUS_DATA));
    pOrderStatus->w_id = Term.pClientData[iTermId].w_id;
    GetOrderStatusData(pECB->lpszQueryString, pOrderStatus);

    Term.pClientData[iTermId].pTxn->OrderStatus();

    pOrderStatus = Term.pClientData[iTermId].pTxn->BuffAddr_OrderStatus();
    MakeOrderStatusForm(iTermId, pOrderStatus, OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessDeliveryForm
 *
 * PURPOSE:      This function gets and validates the input data from the
delivery form
 *              filling in the required input variables. It then calls the
PostDeliveryInfo
 *              Api, The client is then informed that the transaction has
been posted.
 */

```

```

* ARGUMENTS:  EXTENSION_CONTROL_BLOCK  *pECBpassed in structure pointer
from inetsrv.
*
*          int          iTermId  client
browser terminal id
*/

void ProcessDeliveryForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    char *ptr = pECB->lpszQueryString;

    PDELIVERY_DATA pDelivery;

    pDelivery = Term.pClientData[iTermId].pTxn->BuffAddr_Delivery();
    ZeroMemory(pDelivery, sizeof(DELIVERY_DATA));
    pDelivery->w_id = Term.pClientData[iTermId].w_id;

    pDelivery->o_carrier_id = GetIntKeyValue(&ptr, "OCD*",
ERR_DELIVERY_MISSING_OCD_KEY, ERR_DELIVERY_CARRIER_INVALID);
    if ( pDelivery->o_carrier_id > 10 || pDelivery->o_carrier_id < 1 )
        throw new CWEBCLNT_ERR( ERR_DELIVERY_CARRIER_ID_RANGE );

    if (dwNumDeliveryThreads)
    {
        //post delivery info
        if ( PostDeliveryInfo(pDelivery->w_id, pDelivery->o_carrier_id) )
            pDelivery->exec_status_code = eDeliveryFailed;
        else
            pDelivery->exec_status_code = eOK;
    }
    else // delivery is done synchronously if no delivery threads
    configured
        Term.pClientData[iTermId].pTxn->Delivery();

    pDelivery = Term.pClientData[iTermId].pTxn->BuffAddr_Delivery();
    MakeDeliveryForm(iTermId, pDelivery, OUTPUT_FORM, szBuffer);
}

/* FUNCTION: ProcessStockLevelForm
*
* PURPOSE:    This function gets and validates the input data from the
Stock Level
*
*            form filling in the required input variables. It then calls
the
*            SQLStockLevel transaction, constructs the output form and
writes it
*            back to client browser.
*
* ARGUMENTS:  EXTENSION_CONTROL_BLOCK  *pECBpassed in structure pointer
from inetsrv.
*
*          int          iTermId  client
browser terminal id

```

```

*
*/
void ProcessStockLevelForm(EXTENSION_CONTROL_BLOCK *pECB, int iTermId, char
*szBuffer)
{
    char *ptr = pECB->lpszQueryString;

    PSTOCK_LEVEL_DATA pStockLevel;

    pStockLevel = Term.pClientData[iTermId].pTxn->BuffAddr_StockLevel();
    ZeroMemory( pStockLevel, sizeof(STOCK_LEVEL_DATA) );

    pStockLevel->w_id = Term.pClientData[iTermId].w_id;
    pStockLevel->d_id = Term.pClientData[iTermId].d_id;

    pStockLevel->threshold = GetIntKeyValue(&ptr, "TT*",
ERR_STOCKLEVEL_MISSING_THRESHOLD_KEY, ERR_STOCKLEVEL_THRESHOLD_INVALID);
    if ( pStockLevel->threshold >= 100 || pStockLevel->threshold < 0 )
        throw new CWEBCLNT_ERR( ERR_STOCKLEVEL_THRESHOLD_RANGE );

    Term.pClientData[iTermId].pTxn->StockLevel();

    pStockLevel = Term.pClientData[iTermId].pTxn->BuffAddr_StockLevel();
    MakeStockLevelForm(iTermId, pStockLevel, OUTPUT_FORM, szBuffer);
}

/* FUNCTION: GetNewOrderData
*
* PURPOSE:    This function extracts and validates the new order form data
from an http command string.
*
* ARGUMENTS:  LPSTR          lpszQueryString  client browser http
command string
*
*            NEW_ORDER_DATA  *pNewOrderData  pointer to new
order data structure
*
*/

void GetNewOrderData(LPSTR lpszQueryString, NEW_ORDER_DATA *pNewOrderData)
{
    char szTmp[26];
    int i;
    short items;
    int ol_i_id, ol_quantity;
    char *ptr = lpszQueryString;

    static char szSP[MAX_OL_NEW_ORDER_ITEMS][6] =
    { "SP00*", "SP01*", "SP02*", "SP03*", "SP04*",
      "SP05*", "SP06*", "SP07*", "SP08*", "SP09*",
      "SP10*", "SP11*", "SP12*", "SP13*", "SP14*" };
    static char szIID[MAX_OL_NEW_ORDER_ITEMS][7] =
    { "IID00*", "IID01*", "IID02*", "IID03*", "IID04*",

```

```

        "IID05*", "IID06*", "IID07*", "IID08*", "IID09*",
        "IID10*", "IID11*", "IID12*", "IID13*", "IID14*" };
static char szQty[MAX_OL_NEW_ORDER_ITEMS][7] =
{ "Qty00*", "Qty01*", "Qty02*", "Qty03*", "Qty04*",
  "Qty05*", "Qty06*", "Qty07*", "Qty08*", "Qty09*",
  "Qty10*", "Qty11*", "Qty12*", "Qty13*", "Qty14*" };

    pNewOrderData->d_id = GetIntKeyValue(&ptr, "DID",
ERR_NEWORDER_FORM_MISSING_DID, ERR_NEWORDER_DISTRICT_INVALID);
    pNewOrderData->c_id = GetIntKeyValue(&ptr, "CID",
ERR_NEWORDER_CUSTOMER_KEY, ERR_NEWORDER_CUSTOMER_INVALID);

    for(i=0, items=0; i<MAX_OL_NEW_ORDER_ITEMS; i++)
    {
        GetKeyValue(&ptr, szSP[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_SUPPW_KEY);
        if ( szTmp[0] )
        {
            if ( !IsNumeric(szTmp) )
                throw new CWEBCLNT_ERR( ERR_NEWORDER_SUPPW_INVALID );
            pNewOrderData->OL[items].ol_supply_w_id = (short)atoi(szTmp);

            ol_i_id = pNewOrderData->OL[items].ol_i_id =
                GetIntKeyValue(&ptr, szIID[i],
ERR_NEWORDER_MISSING_IID_KEY, ERR_NEWORDER_ITEMID_INVALID);
            if ( ol_i_id > 999999 || ol_i_id < 1 )
                throw new CWEBCLNT_ERR( ERR_NEWORDER_ITEMID_RANGE );

            ol_quantity = pNewOrderData->OL[items].ol_quantity =
                GetIntKeyValue(&ptr, szQty[i],
ERR_NEWORDER_MISSING_QTY_KEY, ERR_NEWORDER_QTY_INVALID);
            if ( ol_quantity > 99 || ol_quantity < 1 )
                throw new CWEBCLNT_ERR( ERR_NEWORDER_QTY_RANGE );

            items++;
        }
        else
        {
            // nothing entered for supply warehouse, so item id and qty
            must also be blank
            GetKeyValue(&ptr, szIID[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_IID_KEY);
            if ( szTmp[0] )
                throw new CWEBCLNT_ERR(
ERR_NEWORDER_ITEMID_WITHOUT_SUPPW );

            GetKeyValue(&ptr, szQty[i], szTmp, sizeof(szTmp),
ERR_NEWORDER_MISSING_QTY_KEY);
            if ( szTmp[0] )
                throw new CWEBCLNT_ERR( ERR_NEWORDER_QTY_WITHOUT_SUPPW
);
        }
    }
    if ( items == 0 )

```

```

        throw new CWEBCLNT_ERR( ERR_NEWORDER_NOITEMS_ENTERED );

    pNewOrderData->o_ol_cnt = items;
}

/* FUNCTION: GetPaymentData
 *
 * PURPOSE:      This function extracts and validates the payment form data
from an http command string.
 *
 * ARGUMENTS:   LPSTR          lpszQueryString      client browser http
command string
 *              PAYMENT_DATA  *pPaymentData        pointer to payment
data structure
 */

void GetPaymentData(LPSTR lpszQueryString, PAYMENT_DATA *pPaymentData)
{
    char szTmp[26];
    char *ptr = lpszQueryString;
    BOOL bCustIdBlank;

    pPaymentData->d_id = GetIntKeyValue(&ptr, "DID",
ERR_PAYMENT_MISSING_DID_KEY, ERR_PAYMENT_DISTRICT_INVALID);

    GetKeyValue(&ptr, "CID", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_CID_KEY);
    if ( szTmp[0] == 0 )
    {
        bCustIdBlank = TRUE;
        pPaymentData->c_id = 0;
    }
    else
    {
        // parse customer id and verify that last name was NOT entered
        bCustIdBlank = FALSE;
        if ( !IsNumeric(szTmp) )
            throw new CWEBCLNT_ERR( ERR_PAYMENT_CUSTOMER_INVALID );
        pPaymentData->c_id = atoi(szTmp);
    }

    pPaymentData->c_w_id = GetIntKeyValue(&ptr, "CWI",
ERR_PAYMENT_MISSING_CWI_KEY, ERR_PAYMENT_CWI_INVALID);
    pPaymentData->c_d_id = GetIntKeyValue(&ptr, "CDI",
ERR_PAYMENT_MISSING_CDI_KEY, ERR_PAYMENT_CDI_INVALID);

    if ( bCustIdBlank )
    {
        // customer id is blank, so last name must be entered
        GetKeyValue(&ptr, "CLT", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_CLT_KEY);
        if ( szTmp[0] == 0 )
            throw new CWEBCLNT_ERR( ERR_PAYMENT_MISSING_CID_CLT );

        _strupr( szTmp );
    }
}

```

```

    if ( strlen(pPaymentData->c_last) > LAST_NAME_LEN )
        throw new CWEBCLNT_ERR( ERR_PAYMENT_LAST_NAME_TO_LONG );
    strcpy(pPaymentData->c_last, szTmp);
}
else
{
    // parse customer id and verify that last name was NOT entered
    GetKeyValue(&ptr, "CLT*", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_CLT_KEY);
    if ( szTmp[0] != 0 )
        throw new CWEBCLNT_ERR( ERR_PAYMENT_CID_AND_CLT );
}

    GetKeyValue(&ptr, "HAM*", szTmp, sizeof(szTmp),
ERR_PAYMENT_MISSING_HAM_KEY);
    if (!IsDecimal(szTmp))
        throw new CWEBCLNT_ERR( ERR_PAYMENT_HAM_INVALID );
    pPaymentData->h_amount = atof(szTmp);
    if ( pPaymentData->h_amount >= 10000.00 || pPaymentData->h_amount < 0 )
        throw new CWEBCLNT_ERR( ERR_PAYMENT_HAM_RANGE );
}

/* FUNCTION: GetOrderStatusData
 *
 * PURPOSE:      This function extracts and validates the payment form data
from an http command string.
 *
 */
void GetOrderStatusData(LPSTR lpszQueryString, ORDER_STATUS_DATA
*pOrderStatusData)
{
    char szTmp[26];
    char *ptr = lpszQueryString;

    pOrderStatusData->d_id = GetIntKeyValue(&ptr, "DID*",
ERR_ORDERSTATUS_MISSING_DID_KEY, ERR_ORDERSTATUS_DID_INVALID);

    GetKeyValue(&ptr, "CID*", szTmp, sizeof(szTmp),
ERR_ORDERSTATUS_MISSING_CID_KEY);
    if ( szTmp[0] == 0 )
    {
        // customer id is blank, so last name must be entered
        pOrderStatusData->c_id = 0;
        GetKeyValue(&ptr, "CLT*", szTmp, sizeof(szTmp),
ERR_ORDERSTATUS_MISSING_CLT_KEY);
        if ( szTmp[0] == 0 )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_MISSING_CID_CLT );

        _strupr( szTmp );
        if ( strlen(pOrderStatusData->c_last) > LAST_NAME_LEN )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_CLT_RANGE );
        strcpy(pOrderStatusData->c_last, szTmp);
    }
    else
    {
        // parse customer id and verify that last name was NOT entered

```

```

        if ( !IsNumeric(szTmp) )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_CID_INVALID );
        pOrderStatusData->c_id = atoi(szTmp);
        GetKeyValue(&ptr, "CLT*", szTmp, sizeof(szTmp),
ERR_ORDERSTATUS_MISSING_CLT_KEY);
        if ( szTmp[0] != 0 )
            throw new CWEBCLNT_ERR( ERR_ORDERSTATUS_CID_AND_CLT );
    }
}

/* FUNCTION: BOOL IsNumeric(char *ptr)
 *
 * PURPOSE:      This function determines if a string is numeric. It fails if
any characters other
 *
 *               than numeric and null terminator are present.
 *
 * ARGUMENTS:   char          *ptr pointer to string to check.
 *
 * RETURNS:     BOOL FALSE if string is not all numeric
 *              TRUE  if string contains only numeric
characters i.e. '0' - '9'
 */
BOOL IsNumeric(char *ptr)
{
    if ( *ptr == 0 )
        return FALSE;

    while( *ptr && isdigit(*ptr) )
        ptr++;
    return ( !*ptr );
}

/* FUNCTION: BOOL IsDecimal(char *ptr)
 *
 * PURPOSE:      This function determines if a string is a non-negative
decimal value.
 *
 *               It fails if any characters other than a series of numbers
followed by
 *
 *               a decimal point, another series of numbers, and a null
terminator are present.
 *
 * ARGUMENTS:   char          *ptr pointer to string to check.
 *
 * RETURNS:     BOOL FALSE if string is not a valid non-negative decimal
value
 *              TRUE  if string is OK
 */
BOOL IsDecimal(char *ptr)
{
    char *dotptr;

```

```

BOOL bValid;

if ( *ptr == 0 )
    return FALSE;

// find decimal point
dotptr = strchr( ptr, '.' );
if (dotptr == NULL)
    // no decimal point, so just check for numeric
    return IsNumeric(ptr);
*dotptr = 0; // temporarily replace decimal with a terminator

if ( *ptr != 0 )
    bValid = IsNumeric(ptr);
// string starts with decimal point
else if (*(dotptr+1) == 0)
    return FALSE; // nothing but a decimal point is bad
else
    bValid = TRUE;

if (*(dotptr+1) != 0)
    // check text after decimal point
    bValid &= IsNumeric(dotptr+1);

*dotptr = '.'; // replace decimal point
return bValid;
}

//{{NO_DEPENDENCIES}}
// Microsoft Developer Studio generated include file.
// Used by tpcc.rc
//
#define IDD_DIALOG1                101

// Next default values for new objects
//
#ifdef APSTUDIO_INVOKED
#ifndef APSTUDIO_READONLY_SYMBOLS
#define _APS_NEXT_RESOURCE_VALUE    102
#define _APS_NEXT_COMMAND_VALUE    40001
#define _APS_NEXT_CONTROL_VALUE    1000
#define _APS_NEXT_SYMED_VALUE      101
#endif
#endif

/* FILE:      READREGISTRY.CPP
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not yet audited
 *
 * PURPOSE:   Implementation for TPC-C Tuxedo class.

```

```

 * Contact: Charles Levine (clevine@microsoft.com)
 *
 * Change history:
 *   4.20.000 - first version
 */

/* FUNCTION: ReadTPCCRegistrySettings
 *
 * PURPOSE:   This function reads the NT registry for startup parameters.
There parameters are
 *           under the TPCC key.
 *
 * RETURNS FALSE = no errors
 *           TRUE  = error reading registry
 */
BOOL ReadTPCCRegistrySettings( TPCCREGISTRYDATA *pReg )
{
    HKEY hKey;
    DWORD size;
    DWORD type;
    DWORD dwTmp;
    char szTmp[256];

    if ( RegOpenKeyEx(HKEY_LOCAL_MACHINE, "SOFTWARE\\Microsoft\\TPCC", 0,
KEY_READ, &hKey) != ERROR_SUCCESS )
        return TRUE;

    // determine database protocol to use; may be either ODBC or DBLIB
    pReg->eDB_Protocol = Unspecified;
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "DB_Protocol", 0, &type, (BYTE *)&szTmp,
&size) == ERROR_SUCCESS )
    {
        if ( !strcmp(szTmp, szDBNames[ODBC]) )
            pReg->eDB_Protocol = ODBC;
        else if ( !strcmp(szTmp, szDBNames[DBLIB]) )
            pReg->eDB_Protocol = DBLIB;
    }

    pReg->eTxnMon = None;
    // determine txn monitor to use; may be either TUXEDO, or blank
    size = sizeof(szTmp);
    if ( RegQueryValueEx(hKey, "TxnMonitor", 0, &type, (BYTE *)&szTmp,
&size) == ERROR_SUCCESS )
    {
        if ( !strcmp(szTmp, szTxnMonNames[TUXEDO]) )
            pReg->eTxnMon = TUXEDO;
        else if ( !strcmp(szTmp, szTxnMonNames[ENCINA]) )
            pReg->eTxnMon = ENCINA;
        else if ( !strcmp(szTmp, szTxnMonNames[COM]) )
            pReg->eTxnMon = COM;
    }
}

```

```

pReg->bCOM_SinglePool = FALSE;
size = sizeof(szTmp);
if ( RegQueryValueEx(hKey, "COM_SinglePool", 0, &type, (BYTE *)&szTmp,
&size) == ERROR_SUCCESS )
{
    if ( !strcmp(szTmp, "YES") )
        pReg->bCOM_SinglePool = TRUE;
}

pReg->dwMaxConnections = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey, "MaxConnections", 0, &type,
(LPBYTE)&dwTmp, &size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwMaxConnections = dwTmp;

pReg->dwMaxPendingDeliveries = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey, "MaxPendingDeliveries", 0, &type,
(LPBYTE)&dwTmp, &size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwMaxPendingDeliveries = dwTmp;

pReg->dwNumberOfDeliveryThreads = 0;
size = sizeof(dwTmp);
if ( ( RegQueryValueEx(hKey, "NumberOfDeliveryThreads", 0, &type,
(LPBYTE)&dwTmp, &size) == ERROR_SUCCESS )
    && (type == REG_DWORD) )
    pReg->dwNumberOfDeliveryThreads = dwTmp;

size = sizeof( pReg->szPath );
if ( RegQueryValueEx(hKey, "Path", 0, &type, (BYTE *)&pReg->szPath,
&size) != ERROR_SUCCESS )
    pReg->szPath[0] = 0;

size = sizeof( pReg->szDbServer );
if ( RegQueryValueEx(hKey, "DbServer", 0, &type, (BYTE *)&pReg-
>szDbServer, &size) != ERROR_SUCCESS )
    pReg->szDbServer[0] = 0;

size = sizeof( pReg->szDbName );
if ( RegQueryValueEx(hKey, "DbName", 0, &type, (BYTE *)&pReg->szDbName,
&size) != ERROR_SUCCESS )
    pReg->szDbName[0] = 0;

size = sizeof( pReg->szDbUser );
if ( RegQueryValueEx(hKey, "DbUser", 0, &type, (BYTE *)&pReg->szDbUser,
&size) != ERROR_SUCCESS )
    pReg->szDbUser[0] = 0;

size = sizeof( pReg->szDbPassword );

```

```

    if ( RegQueryValueEx(hKey, "DbPassword", 0, &type, (BYTE *)&pReg-
>szDbPassword, &size) != ERROR_SUCCESS )
        pReg->szDbPassword[0] = 0;

    RegCloseKey(hKey);

    return FALSE;
}

/* FILE:      ReadRegistry.h
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not audited
 *
 * PURPOSE:   Header for registry related code.
 *
 * Change history:
 *           4.20.000 - first version
 */

enum DBPROTOCOL { Unspecified, ODBC, DBLIB };
const char *szDBNames[] = { "Unspecified", "ODBC", "DBLIB" };

enum TXNMON { None, TUXEDO, ENCINA, COM };
const char *szTxnMonNames[] = { "NONE", "TUXEDO", "ENCINA", "COM" };

//This structure defines the data necessary to keep distinct for each
terminal or client connection.
typedef struct _TPCCREGISTRYDATA
{
    enum DBPROTOCOL eDB_Protocol;
    enum TXNMON eTxnMon;
    BOOL bCOM_SinglePool;
    DWORD dwMaxConnections;
    DWORD dwMaxPendingDeliveries;
    DWORD dwNumberOfDeliveryThreads;
    char szPath[128];
    char szDbServer[32];
    char szDbName[32];
    char szDbUser[32];
    char szDbPassword[32];
} TPCCREGISTRYDATA, *PTPCCREGISTRYDATA;

BOOL ReadTPCCRegistrySettings( TPCCREGISTRYDATA *pReg );

/* FILE:      ERROR.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *

```

```

*           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
*
*   PURPOSE:  Header file for error exception classes.
*
*   Change history:
*       4.20.000 - updated rev number to match kit
*       4.21.000 - fixed bug: ~CBaseErr needed to be declared virtual
*/

#pragma once

#ifndef _INC_STRING
#include <string.h>
#endif

const int m_szMsg_size = 512;
const int m_szApp_size = 64;
const int m_szLoc_size = 64;

//error message structure used in ErrorText routines
typedef struct _SERRORMSG
{
    int          iError;                //error id of message
    char szMsg[256];                  //message to sent to browser
} SERRORMSG;

#define ERR_FATAL_LEVEL          1
#define ERR_WARNING_LEVEL       2
#define ERR_INFORMATION_LEVEL   3

#define ERR_TYPE_LOGIC          -1      //logic
error in program; internal error
#define ERR_SUCCESS              0
//success (a non-error error)
#define ERR_BAD_ITEM_ID         1
//expected abort record in txnRecord
#define ERR_TYPE_DELIVERY_POST  2      //expected
delivery post failed
#define ERR_TYPE_WEBDLL         3      //tpcc
web generated error
#define ERR_TYPE_SQL            4      //sql
server generated error
#define ERR_TYPE_DBLIB         5      //dblib
generated error
#define ERR_TYPE_ODBC          6      //odbc
generated error
#define ERR_TYPE_SOCKET        7      //error
on communication socket client rte only
#define ERR_TYPE_DEADLOCK      8      //dblib and
odbc only deadlock condition

```

```

#define ERR_TYPE_COM           9      //error from
COM call
#define ERR_TYPE_TUXEDO       10      //tuxedo
error
#define ERR_TYPE_OS          11      //operating system error
#define ERR_TYPE_MEMORY      12      //memory
allocation error
#define ERR_TYPE_TPCC_ODBC   13      //error from
tpcc odbc txn module
#define ERR_TYPE_TPCC_DBLIB  14      //error
from tpcc dblib txn module
#define ERR_TYPE_DELISRV     15      //delivery
server error
#define ERR_TYPE_TXNLOG      16      //txn
log error
#define ERR_TYPE_BCONN       17      //Benchcraft connection class
#define ERR_TYPE_TPCC_CONN   18      //Benchcraft
connection class
#define ERR_TYPE_ENCINA      19      //Encina
error
#define ERR_TYPE_COMPONENT   20      //error from
COM component
#define ERR_TYPE_RTE         21      //Benchcraft
rte
#define ERR_TYPE_AUTOMATION  22      //Benchcraft automation errors

class CBaseErr
{
public:
    char *m_szApp;
    char *m_szMsg;
    char *m_szLoc; // code location where the error occurred
    int    m_idMsg;

    CBaseErr(void)
    {
        m_idMsg          = 0;
        m_szMsg          = new char[m_szMsg_size];
        m_szApp          = new char[m_szApp_size];
        m_szLoc          = NULL;

        m_szMsg[0] = 0;
        m_szApp[0] = 0;

        GetModuleFileName(GetModuleHandle(NULL), m_szApp, m_szApp_size);
    }

    virtual ~CBaseErr(void)
    {

```

```

    if (m_szMsg)
        delete [] m_szMsg;
    if (m_szApp)
        delete [] m_szApp;
    if (m_szLoc)
        delete [] m_szLoc;
};

CBaseErr(int idMsg)
{
    m_idMsg         = idMsg;
    m_szApp         = new char[m_szApp_size];
    m_szMsg         = new char[m_szMsg_size];
    m_szLoc         = NULL;

    GetModuleFileName(GetModuleHandle(NULL), m_szApp, m_szApp_size);
    LoadString(GetModuleHandle(NULL), idMsg, m_szMsg, m_szMsg_size);
}

CBaseErr(LPCTSTR szMsg)
{
    m_idMsg         = 0;
    m_szApp         = new char[m_szApp_size];
    m_szMsg         = new char[m_szMsg_size];
    m_szLoc         = NULL;

    GetModuleFileName(GetModuleHandle(NULL), m_szApp, m_szApp_size);
    strcpy(m_szMsg, szMsg);
}

void SetError(char *szMsg, LPCTSTR szLocation)
{
    if (szMsg != NULL)
        strcpy(m_szMsg, szMsg);
    else
        m_szMsg[0] = 0;

    if (szLocation != NULL)
    {
        delete [] m_szLoc;
        m_szLoc = new char[strlen(szLocation)+1];
        strcpy(m_szLoc, szLocation);
    }
    else
    {
        delete [] m_szLoc;
        m_szLoc = NULL;
    }
}

virtual void Draw(HWND hwnd, LPCTSTR szStr = NULL)
{
    int            j;

```

```

    char szTmp[512];

    if (szStr)
        j = wsprintf(szTmp, "%s\n", szStr);
    if (m_szLoc)
        j += wsprintf(szTmp+j, "Location=%s\n", m_szLoc);
    if (m_szMsg)
        j += wsprintf(szTmp+j, "%s\n", m_szMsg);

    ::MessageBox(hwnd, szTmp, m_szApp, MB_OK);
}

char *GetApp(void) { return m_szApp; }
char *GetMsg(void) { return m_szMsg; }
char *GetLocation(void) { return m_szLoc; }

virtual int ErrorType() = 0; // a value which distinguishes the kind
of error that occurred
virtual int ErrorNum() = 0; // an error value specific to the
error type
virtual char *ErrorText() = 0; // a string (i.e., human readable)
representation of the error
};

class CSocketErr : public CBaseErr
{
public:
    enum Action
    {
        eNone,
        eSend,
        eSocket,
        eConnect
    };

    CSocketErr(Action eAction, LPCTSTR szLocation);
    CSocketErr(int iError) { m_errId = iError; };
    int m_errId;
    Action m_eAction;

    int ErrorType() { return ERR_TYPE_SOCKET; };
    int ErrorNum() { return m_errId; };
    char *ErrorText(void);
};

class CSystemErr : public CBaseErr
{
public:
    enum Action
    {
        eNone,
        eTransactNamedPipe,

```

```

eWaitNamedPipe,
eSetNamedPipeHandleState,
eCreateFile,
eCreateProcess,
eCallNamedPipe,
eCreateEvent,
eCreateThread,
eVirtualAlloc,
eReadFile,
eWriteFile,
eMapViewOfFile,
eCreateFileMapping,
eInitializeSecurityDescriptor,
eSetSecurityDescriptorDacl,
eCreateNamedPipe,
eConnectNamedPipe,
eWaitForSingleObject,
eRegOpenKeyEx,
eRegQueryValueEx,
};

CSystemErr(Action eAction, LPCTSTR szLocation);

void Draw(HWND hwnd, LPCTSTR szStr = NULL);

int      m_errId;
Action  m_eAction;

int ErrorType() { return ERR_TYPE_OS;}
int ErrorNum() { return m_errId;}
char *ErrorText() { return m_szMsg; }
};

class CMemoryErr : public CBaseErr
{
public:
    CMemoryErr(void);

    int ErrorType() { return ERR_TYPE_MEMORY;}
    int ErrorNum() { return 0;}
    char *ErrorText() { return "Insufficient Memory to continue.";}
};

/* FILE:      TRANS.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 * PURPOSE:  Header file for TPC-C structure templates.
 *
 */

```

```

 * Change history:
 *       4.20.000 - updated rev number to match kit
 */
#pragma once

// String length constants
#define SERVER_NAME_LEN      20
#define DATABASE_NAME_LEN   20
#define USER_NAME_LEN       20
#define PASSWORD_LEN        20
#define TABLE_NAME_LEN     20
#define I_DATA_LEN          50
#define I_NAME_LEN          24
#define BRAND_LEN           1
#define LAST_NAME_LEN       16
#define W_NAME_LEN          10
#define ADDRESS_LEN         20
#define STATE_LEN           2
#define ZIP_LEN              9
#define S_DIST_LEN          24
#define S_DATA_LEN          50
#define D_NAME_LEN          10
#define FIRST_NAME_LEN      16
#define MIDDLE_NAME_LEN     2
#define PHONE_LEN           16
#define DATETIME_LEN        30
#define CREDIT_LEN          2
#define C_DATA_LEN          250
#define H_DATA_LEN          24
#define DIST_INFO_LEN       24
#define MAX_OL_NEW_ORDER_ITEMS 15
#define MAX_OL_ORDER_STATUS_ITEMS 15
#define STATUS_LEN          25
#define OL_DIST_INFO_LEN    24

// TIMESTAMP_STRUCT is provided by the ODBC header file sqltypes.h, but is
not available
// when compiling with dblink, so redefined here. Note: we are using the
symbol "__SQLTYPES"
// (declared in sqltypes.h) as a way to determine if TIMESTAMP_STRUCT has
been declared.
#ifndef __SQLTYPES
    typedef struct
    {
        short          /* SQLSMALLINT */    year;
        unsigned short /* SQLUSMALLINT */   month;
        unsigned short /* SQLUSMALLINT */   day;
        unsigned short /* SQLUSMALLINT */   hour;
        unsigned short /* SQLUSMALLINT */   minute;
        unsigned short /* SQLUSMALLINT */   second;
        unsigned long  /* SQLINTEGER */     fraction;
    } TIMESTAMP_STRUCT;
#endif

```

```

// possible values for exec_status_code after transaction completes
enum EXEC_STATUS
{
    eOK,           // 0 "Transaction committed."
    eInvalidItem, // 1 "Item number is not valid."
    eDeliveryFailed // 2 "Delivery Post Failed."
};

// transaction structures
typedef struct
{
    // input params
    short          ol_supply_w_id;
    long           ol_i_id;
    short          ol_quantity;

    // output params
    char           ol_i_name[I_NAME_LEN+1];
    char           ol_brand_generic[BRAND_LEN+1];
    double         ol_i_price;
    double         ol_amount;
    short          ol_stock;
} OL_NEW_ORDER_DATA;

typedef struct
{
    // input params
    short          w_id;
    short          d_id;
    long           c_id;
    short          o_ol_cnt;

    // output params
    EXEC_STATUS    exec_status_code;
    char           c_last[LAST_NAME_LEN+1];
    char           c_credit[CREDIT_LEN+1];
    double         c_discount;
    double         w_tax;
    double         d_tax;
    long           o_id;
    short          o_commit_flag;
    TIMESTAMP_STRUCT o_entry_d;
    short          o_all_local;
    double         total_amount;
    OL_NEW_ORDER_DATA OL[MAX_OL_NEW_ORDER_ITEMS];
} NEW_ORDER_DATA, *PNEW_ORDER_DATA;

typedef struct
{
    // input params
    short          w_id;
    short          d_id;
    long           c_id;

```

```

    short          c_d_id;
    short          c_w_id;
    double         h_amount;
    char           c_last[LAST_NAME_LEN+1];

    // output params
    EXEC_STATUS    exec_status_code;
    TIMESTAMP_STRUCT h_date;
    char           w_street_1[ADDRESS_LEN+1];
    char           w_street_2[ADDRESS_LEN+1];
    char           w_city[ADDRESS_LEN+1];
    char           w_state[STATE_LEN+1];
    char           w_zip[ZIP_LEN+1];
    char           d_street_1[ADDRESS_LEN+1];
    char           d_street_2[ADDRESS_LEN+1];
    char           d_city[ADDRESS_LEN+1];
    char           d_state[STATE_LEN+1];
    char           d_zip[ZIP_LEN+1];
    char           c_first[FIRST_NAME_LEN+1];
    char           c_middle[MIDDLE_NAME_LEN + 1];
    char           c_street_1[ADDRESS_LEN+1];
    char           c_street_2[ADDRESS_LEN+1];
    char           c_city[ADDRESS_LEN+1];
    char           c_state[STATE_LEN+1];
    char           c_zip[ZIP_LEN+1];
    char           c_phone[PHONE_LEN+1];
    TIMESTAMP_STRUCT c_since;
    char           c_credit[CREDIT_LEN+1];
    double         c_credit_lim;
    double         c_discount;
    double         c_balance;
    char           c_data[200+1];
} PAYMENT_DATA, *PPAYMENT_DATA;

typedef struct
{
    long           ol_i_id;
    short          ol_supply_w_id;
    short          ol_quantity;
    double         ol_amount;
    TIMESTAMP_STRUCT ol_delivery_d;
} OL_ORDER_STATUS_DATA;

typedef struct
{
    // input params
    short          w_id;
    short          d_id;
    long           c_id;
    char           c_last[LAST_NAME_LEN+1];

    // output params
    EXEC_STATUS    exec_status_code;
    char           c_first[FIRST_NAME_LEN+1];

```

```

    char            c_middle[MIDDLE_NAME_LEN+1];
    double          c_balance;
    long           o_id;
    TIMESTAMP_STRUCT o_entry_d;
    short          o_carrier_id;
    OL_ORDER_STATUS_DATA OL[MAX_OL_ORDER_STATUS_ITEMS];
    short          o_ol_cnt;
} ORDER_STATUS_DATA, *PORDER_STATUS_DATA;

typedef struct
{
    // input params
    short          w_id;
    short          o_carrier_id;

    // output params
    EXEC_STATUS    exec_status_code;
    SYSTEMTIME     queue_time;
    long           o_id[10];        // id's of delivered orders for
    districts 1 to 10
} DELIVERY_DATA, *PDELIVERY_DATA;

//This structure is used for posting delivery transactions and for writing
them to the delivery server.
typedef struct _DELIVERY_TRANSACTION
{
    SYSTEMTIME queue;                //time delivery transaction queued
    short      w_id;                //delivery warehouse
    short      o_carrier_id;        //carrier id
} DELIVERY_TRANSACTION;

typedef struct
{
    // input params
    short          w_id;
    short          d_id;
    short          threshold;

    // output params
    EXEC_STATUS    exec_status_code;
    long           low_stock;
} STOCK_LEVEL_DATA, *PSTOCK_LEVEL_DATA;

/* FILE:      TXN_BASE.H
 *
 *      Microsoft TPC-C Kit Ver. 4.20.000
 *      Copyright Microsoft, 1999
 *      All Rights Reserved
 *
 *      Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 *      PURPOSE:  Header file for TPC-C txn class implementation.
 *
 *      Change history:

```

```

 *      4.20.000 - updated rev number to match kit
 */

#pragma once

// need to declare functions for import, unless define has already been
created
// by the DLL's .cpp module for export.
#ifndef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class DllDecl CTPCC_BASE
{
public:
    CTPCC_BASE(void) {};
    virtual ~CTPCC_BASE(void) {};

    virtual PNEW_ORDER_DATA      BuffAddr_NewOrder()      = 0;
    virtual PPAYMENT_DATA        BuffAddr_Payment()        = 0;
    virtual PDELIVERY_DATA       BuffAddr_Delivery()       = 0;
    virtual PSTOCK_LEVEL_DATA     BuffAddr_StockLevel()     = 0;
    virtual PORDER_STATUS_DATA    BuffAddr_OrderStatus()   = 0;

    virtual void NewOrder        () = 0;
    virtual void Payment         () = 0;
    virtual void Delivery        () = 0;
    virtual void StockLevel      () = 0;
    virtual void OrderStatus     () = 0;
};

/* FILE:      TPCC_DBLIB.CPP
 *
 *      Microsoft TPC-C Kit Ver. 4.20.000
 *      Copyright Microsoft, 1999
 *      All Rights Reserved
 *
 *      Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 *      PURPOSE:  Implements dblib calls for TPC-C txns.
 *      Contact:  Charles Levine (clevine@microsoft.com)
 *
 *      Change history:
 *      4.20.000 - updated rev number to match kit
 *      4.10.001 - not deleting error class in catch handler on deadlock
retry;
 *
 *      not a functional bug, but a memory leak
 *      - had to tweak some declarations to compile with
latest SDK; no functional change
 */

#include <windows.h>
#include <stdio.h>

```

```

#include <assert.h>

#define DBNTWIN32
#include <sqlfront.h>
#include <sqlldb.h>

#ifdef ICECAP
#include <icapexp.h>
#endif

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\error.h"
#include "..\..\common\src\trans.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_dblib.h"

#define DEFCLPACKSIZE 4096

// version string; must match return value from tpcc_version stored proc
const char sVersion[] = "4.10.000";

const iMaxRetries = 10; // how many retries on deadlock
static long iConnectionCount = 0; // number of current dblib connections

const int iErrOleDbProvider = 7312;
const char sErrTimeoutExpired[] = "Timeout expired";

BOOL APIENTRY DllMain(HMODULE hModule, DWORD ul_reason_for_call, LPVOID lpReserved)
{
    switch( ul_reason_for_call )
    {
        case DLL_PROCESS_ATTACH:
            DisableThreadLibraryCalls(hModule);
            dbinit(); // initialize dblib
            break;

        case DLL_PROCESS_DETACH:
            dbexit(); // close all dblib structures/connections
            break;

        default:
            /* nothing */;
    }
    return TRUE;
}

int err_handler(DBPROCESS *dbproc, int severity, int dberr, int oserr,
LPCSTR dberrstr, LPCSTR oserrstr)
{

```

```

CTPCC_DBLIB *pConn;

assert(dbproc != NULL);
pConn = (CTPCC_DBLIB*)dbgetuserdata(dbproc);

if (pConn != NULL)
{
    pConn->SetDbLibError( severity, dberr, oserr, dberrstr, oserrstr
);
}
return INT_CANCEL;
}

/* FUNCTION: int msg_handler(DBPROCESS *dbproc, DBINT msgno, int msgstate,
int severity, char *msgtext)
*
* PURPOSE: This function handles DB-Library SQL Server error messages
*
* ARGUMENTS: DBPROCESS *dbproc DBPROCESS id pointer
* int msgno message number
* int msgstate message state
* int severity message severity
* char *msgtext printable message
description
*
* RETURNS: int INT_CONTINUE continue if error
is SQLETIME else INT_CANCEL action
* INT_CANCEL cancel operation
*
* COMMENTS: This function also sets the dead lock dbproc variable if
necessary.
*
*/

// typedef INT (SQLAPI *DBMSGHANDLE_PROC)(PDBPROCESS, DBINT, INT, INT,
LPCSTR, LPCSTR, LPCSTR, DBUSMALLINT);

int msg_handler(DBPROCESS *dbproc, DBINT msgno, int msgstate, int severity,
LPCSTR msgtext, LPCSTR srvname, LPCSTR procname,
DBUSMALLINT line)
{
    CTPCC_DBLIB *pConn;

    assert(dbproc != NULL);
    pConn = (CTPCC_DBLIB*)dbgetuserdata(dbproc);

    if (pConn != NULL)
    {
        pConn->SetSqlError( msgno, msgstate, severity, msgtext );
    }

    return 0;
}

```

```

/* FUNCTION: void UtilStrCpy(char * pDest, char * pSrc, int n)
 *
 * PURPOSE: This function copies n characters from string pSrc to pDst
and places a
 *
 * null character at the end of the destination string.
 *
 * ARGUMENTS: char *pDest destination string pointer
 * char *pSrc source string pointer
 * int n number of characters to
copy
 *
 * RETURNS: None
 *
 * COMMENTS: Unlike strncpy this function ensures that the result string
is
 *
 * always null terminated.
 */

```

```

inline static void UtilStrCpy(char * pDest, const BYTE * pSrc, int n)
{
    strncpy(pDest, (char *)pSrc, n);
    pDest[n] = '\0';

    return;
}

```

```

/* FUNCTION: CTPCC_DBLIB_ERR::ErrorText
 *
 */

```

```

char* CTPCC_DBLIB_ERR::ErrorText(void)
{
    int i;

    static SERRORMSG errorMsgs[] =
    {
        { ERR_WRONG_SP_VERSION, "Wrong version of stored procs on
database server" },
        { ERR_INVALID_CUST, "Invalid Customer id,name." },
        { ERR_NO_SUCH_ORDER, "No orders found for customer." },
        { ERR_RETRIED_TRANS, "Retries before transaction succeeded." },
        { 0, "" }
    };

    static char szNotFound[] = "Unknown error number.";

    for(i=0; errorMsgs[i].szMsg[0]; i++)

```

```

    {
        if ( m_errno == errorMsgs[i].iError )
            break;
    }
    if ( !errorMsgs[i].szMsg[0] )
        return szNotFound;
    else
        return errorMsgs[i].szMsg;
}

// wrapper routine for class constructor
__declspec(dllexport) CTPCC_DBLIB* CTPCC_DBLIB_new(
    LPCSTR szServer, // name of SQL server
    LPCSTR szUser, // user name for login
    LPCSTR szPassword, // password for login
    LPCSTR szHost, // workstation name; shows up in sp_who; max
30 chars, only first 10 kept by SQL Server
    LPCSTR szDatabase ) // name of database to use
{
    return new CTPCC_DBLIB( szServer, szUser, szPassword, szHost,
szDatabase );
}

CTPCC_DBLIB::CTPCC_DBLIB (
    LPCSTR szServer, // name of SQL server
    LPCSTR szUser, // user name for login
    LPCSTR szPassword, // password for login
    LPCSTR szHost, // workstation name; shows up in sp_who; max
30 chars, only first 10 kept by SQL Server
    LPCSTR szDatabase ) // name of database to use
{
    LOGINREC *login;
    const BYTE *pData;

    // initialization
    m_dbproc = NULL;
    m_DbLibErr = (CDBLIBERR*)NULL;
    m_SqlErr = (CSQLERR*)NULL;

    m_MaxRetries = 10; // how many retries on deadlock

    // increase max number of connections if getting close
    if ( dbgetmaxprocs() < (iConnectionCount+5) )
    {
        if ( dbsetmaxprocs(iConnectionCount+10) == FAIL )
            ThrowError(CDBLIBERR::eDbSetMaxProcs);
    }

    // allocate a login structure
    login = dblogin();
    if (login == NULL)
        ThrowError(CDBLIBERR::eLogin);
}

```

```

InterlockedIncrement( &iConnectionCount );

// register error and message handler functions
if (dbprocerrhandle(login, err_handler) == NULL)
    ThrowError(CDBLIBERR::eDbProcHandler);

if (dbprocmsghandle(login, msg_handler) == NULL)
    ThrowError(CDBLIBERR::eDbProcHandler);

DBSETLUSER(login, szUser);
DBSETLPWD(login, szPassword);
DBSETLHOST(login, szHost);
DBSETLPACKET(login, (unsigned short)DEFCLPACKSIZE);
DBSETLVERSION(login, DBVER60); // use dblink ver 6.0 client
behavior

// set time to wait for login
if (dbsetlogintime(60) == FAIL)
    ThrowError(CDBLIBERR::eDbSet);

// set time to wait for statement execution
if (dbsettime(180) == FAIL)
    ThrowError(CDBLIBERR::eDbSet);

m_dbproc = dbopen(login, szServer);

// deallocate login structure before checking for success
dbfreelogin( login );

if (m_dbproc == NULL)
    ThrowError(CDBLIBERR::eDbOpen);

// save address of class instance so that the message and error handler
// can get to data.
dbsetuserdata(m_dbproc, (LPVOID)this);

// Use the the right database
if (dbuse(m_dbproc, szDatabase) == FAIL)
    ThrowError(CDBLIBERR::eDbUse);

dbcmd(m_dbproc, "set nocount on "); // do not return row
counts
dbcmd(m_dbproc, "set XACT_ABORT ON"); // rollback transaction
on abort

if (dbsqlexec(m_dbproc) == FAIL)
    ThrowError(CDBLIBERR::eDbSqlExec);

DiscardNextResults(2);

// verify that version of stored procs on server is correct
dbrpcinit(m_dbproc, "tpcc_version", 0);

```

```

if (dbrpcexec(m_dbproc) == FAIL)
    ThrowError(CDBLIBERR::eDbRpcExec);

if (dbresults(m_dbproc) != SUCCEED)
    ThrowError(CDBLIBERR::eDbResults);

if (dbnextrow(m_dbproc) != REG_ROW)
    ThrowError(CDBLIBERR::eDbNextRow);

char szSrvVersion[16];
pData=dbdata(m_dbproc, 1);
if (pData)
    UtilStrCpy(szSrvVersion, pData, dbdatlen(m_dbproc, 1));
else
    szSrvVersion[0]=0;
if (strcmp(szSrvVersion,sVersion))
    throw new CTPCC_DBLIB_ERR( CTPCC_DBLIB_ERR::ERR_WRONG_SP_VERSION
);

DiscardNextRows(0);
DiscardNextResults(0);
}

CTPCC_DBLIB::~~CTPCC_DBLIB( void )
{
    // close db connection and deallocate resources
    dbclose(m_dbproc);
    InterlockedDecrement( &iConnectionCount );
    if (m_DbLibErr != NULL)
        delete m_DbLibErr;
    if (m_SqlErr != NULL)
        delete m_SqlErr;
}

void CTPCC_DBLIB::SetDbLibError(int severity, int dberr, int oserr, LPCSTR
dberrstr, LPCSTR oserrstr)
{
    delete m_DbLibErr;
    m_DbLibErr = new CDBLIBERR(CDBLIBERR::eUnknown, severity, dberr,
oserr);

    if (dberrstr != NULL)
    {
        m_DbLibErr->m_dberrstr = new char[ strlen(dberrstr)+1 ];
        strcpy( m_DbLibErr->m_dberrstr, dberrstr );
    }

    if (oserrstr != NULL)
    {
        m_DbLibErr->m_oserrstr = new char[ strlen(oserrstr)+1 ];

```

```

        strcpy( m_DbLibErr->m_oserrstr, oserrstr );
    }
}

void CTPCC_DBLIB::SetSqlError( int /*DBINT*/ msgno, int msgstate, int
severity, LPCSTR msgtext )
{
    if (m_SqlErr == NULL)
        m_SqlErr = new CSQLERR();

    m_SqlErr->m_msgno = msgno;
    m_SqlErr->m_msgstate = msgstate;
    m_SqlErr->m_severity = severity;

    delete [] m_SqlErr->m_msgtext;
    if (msgtext != NULL)
    {
        m_SqlErr->m_msgtext = new char[ strlen(msgtext)+1 ];
        strcpy( m_SqlErr->m_msgtext, msgtext );
    }
}

void CTPCC_DBLIB::ThrowError( CDBLIBERR::ACTION eAction )
{
    // discard anything still in return buffer
    DiscardNextRows(-1);
    DiscardNextResults(-1);

    // check for SQL Server error first; if yes, throw it and ignore any
    DBLib error.
    if (m_SqlErr != NULL)
    {
        CSQLERR      *pSqlErr;
        pSqlErr = m_SqlErr;
        m_SqlErr = NULL;      // clear our pointer to instance; catch
handler will delete
        throw pSqlErr;
    }

    CDBLIBERR *pDbLibErr;
    if (m_DbLibErr == NULL)
        // this case isn't expected to happen, since it means that an
error was returned
        // but the error handlers were not called.
        pDbLibErr = new CDBLIBERR(eAction);
    else
    {
        pDbLibErr = m_DbLibErr;
        pDbLibErr->m_eAction = eAction;
        m_DbLibErr = NULL;      // clear our pointer to instance; catch
handler will delete
    }
}

```

```

        throw pDbLibErr;
    }

    // Read and discard rows until no more. Throw an exception if number of
rows read doesn't
// match number of rows expected. The row count will be ignored if the
expected count value
// passed in is negative. A typical use of this routine is to verify that
there are no more
// rows to be read.
void CTPCC_DBLIB::DiscardNextRows(int iExpectedCount)
{
    int      iRowsRead = 0;
    RETCODE  rc;

    while (TRUE)
    {
        rc = dbnextrow(m_dbproc);
        if (rc == NO_MORE_ROWS)
            break;
        if (rc == FAIL)
        {
            if (iExpectedCount >= 0)
                ThrowError(CDBLIBERR::eDbNextRow);
            else
                break;
        }
        iRowsRead++;
    }

    if ((iExpectedCount >= 0) &&
        (iExpectedCount != iRowsRead))
        ThrowError(CDBLIBERR::eWrongRowCount);
}

    // Read and discard results until no more. Throw an exception if number of
result sets read doesn't
// match number expected. The result set count will be ignored if the
expected count value
// passed in is negative. A typical use of this routine is to verify that
there are no more
// result sets to be read.
void CTPCC_DBLIB::DiscardNextResults(int iExpectedCount)
{
    int      iResultsRead = 0;
    RETCODE  rc;

    while (TRUE)
    {
        rc = dbresults(m_dbproc);
        if (rc == NO_MORE_RESULTS)
            break;
    }
}

```

```

        if (rc == FAIL)
        {
            if (iExpectedCount >= 0)
                ThrowError(CDBLIBERR::eDbResults);
            else
                break;
        }

        DiscardNextRows(-1);
        iResultsRead++;
    }

    if ((iExpectedCount >= 0) &&
        (iExpectedCount != iResultsRead))
        ThrowError(CDBLIBERR::eWrongRowCount);
}

void CTPCC_DBLIB::StockLevel()
{
    int          iTryCount = 0;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_stocklevel", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&_txn.StockLevel.w_id); // @w_id smallint
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&_txn.StockLevel.d_id); // @d_id tinyint
            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&_txn.StockLevel.threshold); // @threshold smallint

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            if (dbresults(m_dbproc) != SUCCEED)
                ThrowError(CDBLIBERR::eDbResults);

            if (dbnextrow(m_dbproc) != REG_ROW)
                ThrowError(CDBLIBERR::eDbNextRow);

            if (pData=dbdata(m_dbproc, 1))
                m_txn.StockLevel.low_stock = *((long *) pData);

            DiscardNextRows(0);
            DiscardNextResults(0);

            m_txn.StockLevel.exec_status_code = eOK;
        }
    }
}

```

```

        return;
    }
    catch (CSQLERR *e)
    {
        if ((e->m_msgno == 1205 ||
            (e->m_msgno == iErrOleDbProvider &&
            strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
            (++iTryCount <= iMaxRetries))
        {
            // hit deadlock; backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
        else
            throw;
    }
} // while (TRUE)

//if (iTryCount)
// throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::NewOrder()
{
    int          i;
    DBINT        commit_flag;
    DBDATETIME  datetime;
    DBDATEREC   daterec;

    int          iTryCount = 0;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_neworder", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&_txn.NewOrder.w_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&_txn.NewOrder.d_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&_txn.NewOrder.c_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&_txn.NewOrder.o_ol_cnt);

            // check whether any order lines are for a remote warehouse
            m_txn.NewOrder.o_all_local = 1;
        }
    }
}

```

```

        for (i = 0; i < m_txn.NewOrder.o_ol_cnt; i++)
        {
            if (m_txn.NewOrder.OL[i].ol_supply_w_id !=
m_txn.NewOrder.w_id)
            {
                m_txn.NewOrder.o_all_local = 0; // at least one
remote warehouse
                break;
            }
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.NewOrder.o_all_local);

            for (i = 0; i < m_txn.NewOrder.o_ol_cnt; i++)
            {
                dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.NewOrder.OL[i].ol_i_id);
                dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.NewOrder.OL[i].ol_supply_w_id);
                dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.NewOrder.OL[i].ol_quantity);
            }

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            // Get order line results
            m_txn.NewOrder.total_amount = 0;
            for (i = 0; i < m_txn.NewOrder.o_ol_cnt; i++)
            {
                if (dbresults(m_dbproc) != SUCCEED)
                    ThrowError(CDBLIBERR::eDbResults);

                if (dbnumcols(m_dbproc) != 5)
                    ThrowError(CDBLIBERR::eWrongNumCols);

                if (dbnextrow(m_dbproc) != REG_ROW)
                    ThrowError(CDBLIBERR::eDbNextRow);

                if (pData=dbdata(m_dbproc, 1))
                    UtilStrCpy(m_txn.NewOrder.OL[i].ol_i_name, pData,
dbdatlen(m_dbproc, 1));
                if (pData=dbdata(m_dbproc, 2))
                    m_txn.NewOrder.OL[i].ol_stock = (*(DBSMALLINT *)
pData);
                if (pData=dbdata(m_dbproc, 3))
                    UtilStrCpy(m_txn.NewOrder.OL[i].ol_brand_generic,
pData, dbdatlen(m_dbproc, 3));
                if (pData=dbdata(m_dbproc, 4))
                    dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 4),

```

```

SQLFLT8, (BYTE *)&m_txn.NewOrder.OL[i].ol_i_price,
8);
                if (pData=dbdata(m_dbproc, 5))
                    dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 5),
SQLFLT8, (BYTE *)&m_txn.NewOrder.OL[i].ol_amount,
8);

                m_txn.NewOrder.total_amount =
m_txn.NewOrder.total_amount + m_txn.NewOrder.OL[i].ol_amount;

                DiscardNextRows(0);
            }

            // get remaining values for w_tax, d_tax, o_id, c_last,
c_discount, c_credit, o_entry_d, commit_flag
            if (dbresults(m_dbproc) != SUCCEED)
                ThrowError(CDBLIBERR::eDbResults);

            if (dbnextrow(m_dbproc) != REG_ROW)
                ThrowError(CDBLIBERR::eDbNextRow);

            if (dbnumcols(m_dbproc) != 8)
                ThrowError(CDBLIBERR::eWrongNumCols);

            if (pData=dbdata(m_dbproc, 1))

                dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 1), SQLFLT8, (BYTE *)&m_txn.NewOrder.w_tax, 8);
                if (pData=dbdata(m_dbproc, 2))

                    dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 2), SQLFLT8, (BYTE *)&m_txn.NewOrder.d_tax, 8);
                    if (pData=dbdata(m_dbproc, 3))
                        m_txn.NewOrder.o_id = (*(DBINT *) pData);
                    if (pData=dbdata(m_dbproc, 4))
                        UtilStrCpy(m_txn.NewOrder.c_last, pData,
dbdatlen(m_dbproc, 4));
                    if (pData=dbdata(m_dbproc, 5))
                        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 5), SQLFLT8, (BYTE *)&m_txn.NewOrder.c_discount, 8);
                    if (pData=dbdata(m_dbproc, 6))
                        UtilStrCpy(m_txn.NewOrder.c_credit, pData,
dbdatlen(m_dbproc, 6));
                    if (pData=dbdata(m_dbproc, 7))
                    {
                        datetime = (*(DBDATETIME *) pData);
                        dbdatecrack(m_dbproc, &daterec, &datetime);
                        m_txn.NewOrder.o_entry_d.year = daterec.year;
                        m_txn.NewOrder.o_entry_d.month = daterec.month;
                        m_txn.NewOrder.o_entry_d.day = daterec.day;

```

```

        m_txn.NewOrder.o_entry_d.hour   = daterec.hour;
        m_txn.NewOrder.o_entry_d.minute = daterec.minute;
        m_txn.NewOrder.o_entry_d.second = daterec.second;
    }
    if (pData=dbdata(m_dbproc, 8))
        commit_flag = (*(DBTINYINT *) pData);

    DiscardNextRows(0);
    DiscardNextResults(0);

    if (commit_flag == 1)
    {
        m_txn.NewOrder.total_amount *= ((1 +
m_txn.NewOrder.w_tax + m_txn.NewOrder.d_tax) * (1 -
m_txn.NewOrder.c_discount));
        m_txn.NewOrder.exec_status_code = eOK;
    }
    else
        m_txn.NewOrder.exec_status_code = eInvalidItem;

    return;
}
catch (CSQLErr *e)
{
    if ((e->m_msgno == 1205 ||
        (e->m_msgno == iErrOleDbProvider &&
         strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
        (++iTryCount <= iMaxRetries))
    {
        // hit deadlock; backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }
    else
        throw;
}
} // while (TRUE)

// if (iTryCount)
//     throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::Payment()
{
    DBDATETIME datetime;
    DBDATEREC daterec;

    int          iTryCount = 0;
    const BYTE *pData;

```

```

ResetError();

while (TRUE)
{
    try
    {
        dbrpcinit(m_dbproc, "tpcc_payment", 0);

        dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.Payment.w_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.Payment.c_w_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLFLT8, -1, -1, (BYTE *)
&m_txn.Payment.h_amount);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Payment.d_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Payment.c_d_id);
        dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.Payment.c_id);

        // if customer id is zero, then payment is by name
        if (m_txn.Payment.c_id == 0)
            dbrpcparam(m_dbproc, NULL, 0, SQLCHAR, -1,
strlen(m_txn.Payment.c_last), (unsigned char *)m_txn.Payment.c_last);

        if (dbrpcexec(m_dbproc) == FAIL)
            ThrowError(CDBLIBERR::eDbRpcExec);

        if (dbresults(m_dbproc) != SUCCEED)
            ThrowError(CDBLIBERR::eDbResults);

        if (dbnextrow(m_dbproc) != REG_ROW)
            ThrowError(CDBLIBERR::eDbNextRow);

        if (dbnumcols(m_dbproc) != 27)
            ThrowError(CDBLIBERR::eWrongNumCols);

        if (pData=dbdata(m_dbproc, 1))
            m_txn.Payment.c_id = (*(DBINT *) pData);
        if (pData=dbdata(m_dbproc, 2))
            UtilStrCpy(m_txn.Payment.c_last, pData,
dbdatlen(m_dbproc, 2));
        if (pData=dbdata(m_dbproc, 3))
        {
            datetime = (*(DBDATETIME *) pData);
            dbdatecrack(m_dbproc, &daterec, &datetime);
            m_txn.Payment.h_date.year   = daterec.year;
            m_txn.Payment.h_date.month = daterec.month;
            m_txn.Payment.h_date.day   = daterec.day;
            m_txn.Payment.h_date.hour  = daterec.hour;
            m_txn.Payment.h_date.minute = daterec.minute;
            m_txn.Payment.h_date.second = daterec.second;

```

```

    }
    if (pData=dbdata(m_dbproc, 4))
        UtilStrCpy(m_txn.Payment.w_street_1, pData,
dbdatlen(m_dbproc, 4));
    if (pData=dbdata(m_dbproc, 5))
        UtilStrCpy(m_txn.Payment.w_street_2, pData,
dbdatlen(m_dbproc, 5));
    if (pData=dbdata(m_dbproc, 6))
        UtilStrCpy(m_txn.Payment.w_city, pData,
dbdatlen(m_dbproc, 6));
    if (pData=dbdata(m_dbproc, 7))
        UtilStrCpy(m_txn.Payment.w_state, pData,
dbdatlen(m_dbproc, 7));
    if (pData=dbdata(m_dbproc, 8))
        UtilStrCpy(m_txn.Payment.w_zip, pData,
dbdatlen(m_dbproc, 8));
    if (pData=dbdata(m_dbproc, 9))
        UtilStrCpy(m_txn.Payment.d_street_1, pData,
dbdatlen(m_dbproc, 9));
    if (pData=dbdata(m_dbproc, 10))
        UtilStrCpy(m_txn.Payment.d_street_2, pData,
dbdatlen(m_dbproc, 10));
    if (pData=dbdata(m_dbproc, 11))
        UtilStrCpy(m_txn.Payment.d_city, pData,
dbdatlen(m_dbproc, 11));
    if (pData=dbdata(m_dbproc, 12))
        UtilStrCpy(m_txn.Payment.d_state, pData,
dbdatlen(m_dbproc, 12));
    if (pData=dbdata(m_dbproc, 13))
        UtilStrCpy(m_txn.Payment.d_zip, pData,
dbdatlen(m_dbproc, 13));
    if (pData=dbdata(m_dbproc, 14))
        UtilStrCpy(m_txn.Payment.c_first, pData,
dbdatlen(m_dbproc, 14));
    if (pData=dbdata(m_dbproc, 15))
        UtilStrCpy(m_txn.Payment.c_middle, pData,
dbdatlen(m_dbproc, 15));
    if (pData=dbdata(m_dbproc, 16))
        UtilStrCpy(m_txn.Payment.c_street_1, pData,
dbdatlen(m_dbproc, 16));
    if (pData=dbdata(m_dbproc, 17))
        UtilStrCpy(m_txn.Payment.c_street_2, pData,
dbdatlen(m_dbproc, 17));
    if (pData=dbdata(m_dbproc, 18))
        UtilStrCpy(m_txn.Payment.c_city, pData,
dbdatlen(m_dbproc, 18));
    if (pData=dbdata(m_dbproc, 19))
        UtilStrCpy(m_txn.Payment.c_state, pData,
dbdatlen(m_dbproc, 19));
    if (pData=dbdata(m_dbproc, 20))
        UtilStrCpy(m_txn.Payment.c_zip, pData,
dbdatlen(m_dbproc, 20));
    if (pData=dbdata(m_dbproc, 21))

```

```

        UtilStrCpy(m_txn.Payment.c_phone, pData,
dbdatlen(m_dbproc, 21));
    if (pData=dbdata(m_dbproc, 22))
    {
        datetime = *((DBDATETIME *) pData);
        dbdatecrack(m_dbproc, &daterec, &datetime);
        m_txn.Payment.c_since.year = daterec.year;
        m_txn.Payment.c_since.month = daterec.month;
        m_txn.Payment.c_since.day = daterec.day;
        m_txn.Payment.c_since.hour = daterec.hour;
        m_txn.Payment.c_since.minute = daterec.minute;
        m_txn.Payment.c_since.second = daterec.second;
    }
    if (pData=dbdata(m_dbproc, 23))
        UtilStrCpy(m_txn.Payment.c_credit, pData,
dbdatlen(m_dbproc, 23));
    if (pData=dbdata(m_dbproc, 24))
        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 24), SQLFLT8, (BYTE *)&m_txn.Payment.c_credit_lim, 8);
    if (pData=dbdata(m_dbproc, 25))
        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 25), SQLFLT8, (BYTE *)&m_txn.Payment.c_discount, 8);
    if (pData=dbdata(m_dbproc, 26))
        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc, 26), SQLFLT8, (BYTE *)&m_txn.Payment.c_balance, 8);
    if (pData=dbdata(m_dbproc, 27))
        UtilStrCpy(m_txn.Payment.c_data, pData,
dbdatlen(m_dbproc, 27));

        DiscardNextRows(0);
        DiscardNextResults(0);

        if (m_txn.Payment.c_id == 0)
            throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_INVALID_CUST );
        else
            m_txn.Payment.exec_status_code = eOK;

        return;
    }
    catch (CSQLERR *e)
    {
        if ((e->m_msgno == 1205 ||
            (e->m_msgno == iErrOleDbProvider &&
            strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
            (++iTryCount <= iMaxRetries))
        {
            // hit deadlock; backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
        else

```

```

        throw;
    }
} // while (TRUE)

// if (iTryCount)
//     throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::OrderStatus()
{
    int          i;
    DBDATETIME  datetime;
    DBDATEREC   daterec;

    int          iTryCount = 0;
    RETCODE     rc;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_orderstatus", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.OrderStatus.w_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.OrderStatus.d_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT4, -1, -1, (BYTE *)
&m_txn.OrderStatus.c_id);

            // if customer id is zero, then order status is by name
            if (m_txn.OrderStatus.c_id == 0)
                dbrpcparam(m_dbproc, NULL, 0, SQLCHAR, -1,
strlen(m_txn.OrderStatus.c_last), (unsigned char
*)m_txn.OrderStatus.c_last);

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            // Get order lines
            if (dbresults(m_dbproc) != SUCCEED)
            {
                if ((m_DbLibErr == NULL) && (m_SqlErr == NULL))
                    throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_NO_SUCH_ORDER );
                else

```

```

                ThrowError(CDBLIBERR::eDbResults);
            }

            if (dbnumcols(m_dbproc) != 5)
                ThrowError(CDBLIBERR::eWrongNumCols);

            i = 0;
            while (TRUE)
            {
                rc = dbnextrow(m_dbproc);
                if (rc == NO_MORE_ROWS)
                    break;
                if (rc != REG_ROW)
                    ThrowError(CDBLIBERR::eDbNextRow);

                if(pData=dbdata(m_dbproc, 1))
                    m_txn.OrderStatus.OL[i].ol_supply_w_id =
(*DBSMALLINT *) pData);
                if(pData=dbdata(m_dbproc, 2))
                    m_txn.OrderStatus.OL[i].ol_i_id = (*(DBINT *)
pData);
                if(pData=dbdata(m_dbproc, 3))
                    m_txn.OrderStatus.OL[i].ol_quantity =
(*DBSMALLINT *) pData);
                if(pData=dbdata(m_dbproc, 4))
                    dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,4),
                                SQLFLT8, (BYTE
*)&m_txn.OrderStatus.OL[i].ol_amount, 8);
                if(pData=dbdata(m_dbproc, 5))
                {
                    datetime = (*(DBDATETIME *) pData);
                    dbdatecrack(m_dbproc, &daterec, &datetime);
                    m_txn.OrderStatus.OL[i].ol_delivery_d.year =
daterec.year;
                    m_txn.OrderStatus.OL[i].ol_delivery_d.month =
daterec.month;
                    m_txn.OrderStatus.OL[i].ol_delivery_d.day =
daterec.day;
                    m_txn.OrderStatus.OL[i].ol_delivery_d.hour =
daterec.hour;
                    m_txn.OrderStatus.OL[i].ol_delivery_d.minute =
daterec.minute;
                    m_txn.OrderStatus.OL[i].ol_delivery_d.second =
daterec.second;
                }
                i++;
            }
            m_txn.OrderStatus.o_ol_cnt = i;

            if (dbresults(m_dbproc) != SUCCEED)
                ThrowError(CDBLIBERR::eDbResults);

```

```

    if (dbnextrow(m_dbproc) != REG_ROW)
        ThrowError(CDBLIBERR::eDbNextRow);

    if (dbnumcols(m_dbproc) != 8)
        ThrowError(CDBLIBERR::eWrongNumCols);

    if (pData=dbdata(m_dbproc, 1))
        m_txn.OrderStatus.c_id = (*(DBINT *) pData);
    if (pData=dbdata(m_dbproc, 2))
        UtilStrCpy(m_txn.OrderStatus.c_last, pData,
dbdatlen(m_dbproc,2));
    if (pData=dbdata(m_dbproc, 3))
        UtilStrCpy(m_txn.OrderStatus.c_first, pData,
dbdatlen(m_dbproc,3));
    if (pData=dbdata(m_dbproc, 4))
        UtilStrCpy(m_txn.OrderStatus.c_middle, pData,
dbdatlen(m_dbproc, 4));
    if (pData=dbdata(m_dbproc, 5))
    {
        datetime = *((DBDATETIME *) pData);
        dbdatecrack(m_dbproc, &daterec, &datetime);
        m_txn.OrderStatus.o_entry_d.year   = daterec.year;
        m_txn.OrderStatus.o_entry_d.month = daterec.month;
        m_txn.OrderStatus.o_entry_d.day    = daterec.day;
        m_txn.OrderStatus.o_entry_d.hour   = daterec.hour;
        m_txn.OrderStatus.o_entry_d.minute = daterec.minute;
        m_txn.OrderStatus.o_entry_d.second = daterec.second;
    }
    if (pData=dbdata(m_dbproc, 6))
        m_txn.OrderStatus.o_carrier_id = (*(DBSMALLINT *)
pData);
    if (pData=dbdata(m_dbproc, 7))
        dbconvert(m_dbproc, SQLNUMERIC, (LPCBYTE)pData,
dbdatlen(m_dbproc,7),
                SQLFLT8, (BYTE
*)&m_txn.OrderStatus.c_balance, 8);
    if (pData=dbdata(m_dbproc, 8))
        m_txn.OrderStatus.o_id = (*(DBINT *) pData);

    DiscardNextRows(0);
    DiscardNextResults(0);

    if (m_txn.OrderStatus.o_ol_cnt == 0)
        throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_NO_SUCH_ORDER );
    else if (m_txn.OrderStatus.c_id == 0 &&
m_txn.OrderStatus.c_last[0] == 0)
        throw new CTPCC_DBLIB_ERR(
CTPCC_DBLIB_ERR::ERR_INVALID_CUST );
    else
        m_txn.OrderStatus.exec_status_code = eOK;

```

```

        return;
    }
    catch (CSQLERR *e)
    {
        if ((e->m_msgno == 1205 ||
            (e->m_msgno == iErrOleDbProvider &&
            strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
            (++iTryCount <= iMaxRetries))
        {
            // hit deadlock; backoff for increasingly longer period
            delete e;
            Sleep(10 * iTryCount);
        }
        else
            throw;
    }
    // while (TRUE)
}

// if (iTryCount)
// throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
iTryCount);
}

void CTPCC_DBLIB::Delivery()
{
    int i;
    int iTryCount = 0;
    const BYTE *pData;

    ResetError();

    while (TRUE)
    {
        try
        {
            dbrpcinit(m_dbproc, "tpcc_delivery", 0);

            dbrpcparam(m_dbproc, NULL, 0, SQLINT2, -1, -1, (BYTE *)
&m_txn.Delivery.w_id);
            dbrpcparam(m_dbproc, NULL, 0, SQLINT1, -1, -1, (BYTE *)
&m_txn.Delivery.o_carrier_id);

            if (dbrpcexec(m_dbproc) == FAIL)
                ThrowError(CDBLIBERR::eDbRpcExec);

            if (dbresults(m_dbproc) != SUCCEED)
                ThrowError(CDBLIBERR::eDbResults);

            if (dbnextrow(m_dbproc) != REG_ROW)
                ThrowError(CDBLIBERR::eDbNextRow);

```

```

        if (dbnumcols(m_dbproc) != 10)
            ThrowError(CDBLIBERR::eWrongNumCols);

    for (i=0; i<10; i++)
    {
        if (pData = dbdata(m_dbproc, i+1))
            m_txn.Delivery.o_id[i] = *((DBINT *)pData);
    }

    DiscardNextRows(0);
    DiscardNextResults(0);

    m_txn.Delivery.exec_status_code = eOK;
    return;
}
catch (CSQLERR *e)
{
    if ((e->m_msgno == 1205 ||
        (e->m_msgno == iErrOleDbProvider &&
         strstr(e->m_msgtext, sErrTimeoutExpired) != NULL)) &&
        (++iTryCount <= iMaxRetries))
    {
        // hit deadlock; backoff for increasingly longer period
        delete e;
        Sleep(10 * iTryCount);
    }
    else
        throw;
}
} // while (TRUE)

// if (iTryCount)
// throw new CTPCC_DBLIB_ERR(CTPCC_DBLIB_ERR::ERR_RETRIED_TRANS,
// iTryCount);
}

void CTPCC_DBLIB::ResetError()
{
    if (m_DbLibErr != NULL)
    {
        delete m_DbLibErr;
        m_DbLibErr = (CDBLIBERR*)NULL;
    }

    if (m_SqlErr != NULL)
    {
        delete m_SqlErr;
        m_SqlErr = (CSQLERR*)NULL;
    }
    return;
}

/* FILE: TPCC_DBLIB.H

```

```

*           Microsoft TPC-C Kit Ver. 4.20.000
*           Copyright Microsoft, 1999
*           All Rights Reserved
*
*           Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
*
* PURPOSE:  Header file for TPC-C txn class implementation.
*
* Change history:
*           4.20.000 - updated rev number to match kit
*/
#pragma once

#ifndef PDBPROCESS
#define DBPROCESS void // dbprocess structure type
typedef DBPROCESS * PDBPROCESS;
#endif

// need to declare functions for import, unless define has already been
created
// by the DLL's .cpp module for export.
#ifndef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class CSQLERR : public CBaseErr
{
public:
    CSQLERR(void)
    {
        m_msgno = 0;
        m_msgstate = 0;
        m_severity = 0;
        m_msgtext = NULL;
    };

    ~CSQLERR()
    {
        delete [] m_msgtext;
    };

    int m_msgno;
    int m_msgstate;
    int m_severity;
    char *m_msgtext;

    int ErrorType() {return ERR_TYPE_SQL;};
    int ErrorNum() {return m_msgno;};
    char *ErrorText() {return m_msgtext;};
};

```

```

class CDBLIBERR : public CBaseErr
{
public:
    enum ACTION
    {
        eNone,
        eUnknown,
        eLogin,           // error from dblogin
        eDbOpen,         // error from dbopen
        eDbUse,           // error from dbuse
        eDbSqlExec,      // error from dbsqlexec
        eDbSet,          // error from one of the dbset*
        eDbNextRow,      // error from dbnextrow
        eWrongRowCount, // more or less rows returned than
        eWrongNumCols,  // more or less columns returned than
        eDbResults,     // error from dbresults
        eDbRpcExec,     // error from dbrpcexec
        eDbSetMaxProcs, // error from dbsetmaxprocs
        eDbProcHandler  // error from either dbprocerrhandle or
    };
    routines
    expected
    expected
    dbprocmsghandle
};

CDBLIBERR(ACTION eAction, int severity = 0, int dberror = 0, int
oserr = 0)
{
    m_eAction = eAction;
    m_severity = severity;
    m_dberror = dberror;
    m_oserr = oserr;

    m_dberrstr = NULL;
    m_oserrstr = NULL;
};

~CDBLIBERR()
{
    delete [] m_dberrstr;
    delete [] m_oserrstr;
};

ACTION    m_eAction;
int       m_severity;
int       m_dberror;
int       m_oserr;
char     *m_dberrstr;
char     *m_oserrstr;

int ErrorType() {return ERR_TYPE_DBLIB;};
int ErrorNum() {return m_dberror;};

```

```

char *ErrorText() {return m_dberrstr;};
};

class CTPCC_DBLIB_ERR : public CBaseErr
{
public:
    enum CTPCC_DBLIB_ERRS
    {
        ERR_WRONG_SP_VERSION = 1, // "Wrong version of stored procs
on database server"
        ERR_INVALID_CUST,         // "Invalid Customer
id,name."
        ERR_NO_SUCH_ORDER,       // "No orders found for
customer."
        ERR_RETRIED_TRANS,      // "Retries before
transaction succeeded."
    };

    CTPCC_DBLIB_ERR( int iErr ) { m_errno = iErr; m_iTryCount = 0; };

    CTPCC_DBLIB_ERR( int iErr, int iTryCount ) { m_errno = iErr;
m_iTryCount = iTryCount; };

    int     m_errno;
    int     m_iTryCount;

    int ErrorType() {return ERR_TYPE_TPCC_DBLIB;};
    int ErrorNum() {return m_errno;};

    char *ErrorText();
};

class DllDecl CTPCC_DBLIB : public CTPCC_BASE
{
private:
    // declare variables and private functions here...
    PDBPROCESS m_dbproc;
    CDBLIBERR *m_DbLibErr; // not allocated until needed
(maybe never)
    CSQLERR *m_SqlErr; // not allocated until needed
(maybe never)
    int     m_MaxRetries; // retry count on deadlock

    void DiscardNextRows(int iExpectedCount);
    void DiscardNextResults(int iExpectedCount);
    void ThrowError( CDBLIBERR::ACTION eAction );
    void ResetError();

    union
    {
        NEW_ORDER_DATA    NewOrder;
        PAYMENT_DATA      Payment;
    };
};

```

```

        DELIVERY_DATA      Delivery;
        STOCK_LEVEL_DATA   StockLevel;
        ORDER_STATUS_DATA  OrderStatus;
    }
        m_txn;

public:
    CTPCC_DBLIB(LPCSTR szServer, LPCSTR szUser, LPCSTR szPassword,
LPCSTR szHost, LPCSTR szDatabase );
    ~CTPCC_DBLIB(void);

    inline PNEW_ORDER_DATA      BuffAddr_NewOrder()      { return
&m_txn.NewOrder;      };
    inline PPAYMENT_DATA        BuffAddr_Payment()        { return
&m_txn.Payment;      };
    inline PDELIVERY_DATA       BuffAddr_Delivery()       { return
&m_txn.Delivery;     };
    inline PSTOCK_LEVEL_DATA    BuffAddr_StockLevel()    { return
&m_txn.StockLevel;   };
    inline PORDER_STATUS_DATA   BuffAddr_OrderStatus()   { return
&m_txn.OrderStatus; };

    void NewOrder      ();
    void Payment       ();
    void Delivery      ();
    void StockLevel    ();
    void OrderStatus   ();

    // these are public because they must be called from the dblink
err_handler and msg_hangler
    // outside of the class
    void SetDbLibError(int severity, int dberr, int oserr, LPCSTR
dberrstr, LPCSTR oserrstr);
    void SetSqlError( int msgno, int msgstate, int severity, LPCSTR
msgtext );
};

extern "C" DllDecl CTPCC_DBLIB* CTPCC_DBLIB_new
( LPCSTR szServer, LPCSTR szUser, LPCSTR szPassword, LPCSTR szHost,
LPCSTR szDatabase );

typedef CTPCC_DBLIB* (TYPE_CTPCC_DBLIB)(LPCSTR, LPCSTR, LPCSTR, LPCSTR,
LPCSTR);

/* FILE:      TPC_C_COM.CPP
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not yet audited
 *
 * PURPOSE:   Source file for TPC-C COM+ class implementation.

```

```

 * Contact: Charles Levine (clevine@microsoft.com)
 *
 * Change history:
 * 4.20.000 - first version
 */

// needed for CoinitializeEx
#define _WIN32_WINNT 0x0400

#include <windows.h>

// need to declare functions for export
#define DllDecl __declspec( dllexport )

#include "..\..\common\src\trans.h" //tpckit transaction header
contains definitions of structures specific to TPC-C
#include "..\..\common\src\error.h"
#include "..\..\common\src\txn_base.h"
#include "tpcc_com.h"

#include "..\..\tpcc_com_ps\src\tpcc_com_ps_i.c"
#include "..\..\tpcc_com_all\src\tpcc_com_all_i.c"

// wrapper routine for class constructor
__declspec(dllexport) CTPCC_COM* CTPCC_COM_new(BOOL bSinglePool)
{
    return new CTPCC_COM(bSinglePool);
}

CTPCC_COM::CTPCC_COM(BOOL bSinglePool)
{
    HRESULT hr = NULL;
    long lRet = 0;
    ULONG ulTmpSize = 0;

    m_pTxn = NULL;
    m_pNewOrder = NULL;
    m_pPayment = NULL;
    m_pStockLevel = NULL;
    m_pOrderStatus = NULL;

    m_bSinglePool = bSinglePool;

    ulTmpSize = (ULONG) sizeof(COM_DATA);
    VariantInit(&m_vTxn);
    m_vTxn.vt = VT_SAFEARRAY;

    m_vTxn.parray = SafeArrayCreateVector(VT_UI1, ulTmpSize, ulTmpSize);
    if (!m_vTxn.parray)
        throw new CCOMERR( E_FAIL );

    memset((void*)m_vTxn.parray->pvData, 0, ulTmpSize);
    m_pTxn = (COM_DATA*)m_vTxn.parray->pvData;

```

```

hr = CoInitializeEx(NULL, COINIT_MULTITHREADED);
if (FAILED(hr))
{
    throw new CCOMERR( hr );
}

// create components
if (m_bSinglePool)
{
    hr = CoCreateInstance(CLSID_TPCC, NULL, CLSCTX_SERVER, IID_ITPCC,
(void **) &m_pNewOrder);
    if (FAILED(hr))
        throw new CCOMERR(hr);

    // all txns will use same component
    m_pPayment = m_pNewOrder;
    m_pStockLevel = m_pNewOrder;
    m_pOrderStatus = m_pNewOrder;
}
else
{
    // use different components for each txn

    hr = CoCreateInstance(CLSID_NewOrder, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pNewOrder);
    if (FAILED(hr))
        throw new CCOMERR(hr);

    hr = CoCreateInstance(CLSID_Payment, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pPayment);
    if (FAILED(hr))
        throw new CCOMERR(hr);

    hr = CoCreateInstance(CLSID_StockLevel, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pStockLevel);
    if (FAILED(hr))
        throw new CCOMERR(hr);

    hr = CoCreateInstance(CLSID_OrderStatus, NULL, CLSCTX_SERVER,
IID_ITPCC, (void **) &m_pOrderStatus);
    if (FAILED(hr))
        throw new CCOMERR(hr);
}

// call setcomplete to release each component back into pool
hr = m_pNewOrder->CallSetComplete();
if (FAILED(hr))
    throw new CCOMERR(hr);

if (!m_bSinglePool)
{
    hr = m_pPayment->CallSetComplete();
}

```

```

    if (FAILED(hr))
        throw new CCOMERR(hr);

    hr = m_pStockLevel->CallSetComplete();
    if (FAILED(hr))
        throw new CCOMERR(hr);

    hr = m_pOrderStatus->CallSetComplete();
    if (FAILED(hr))
        throw new CCOMERR(hr);
}

CTPCC_COM::~CTPCC_COM()
{
    if (m_pTxn)
        SafeArrayDestroy(m_vTxn.parray);

    ReleaseInterface(m_pNewOrder);
    if (!m_bSinglePool)
    {
        ReleaseInterface(m_pPayment);
        ReleaseInterface(m_pStockLevel);
        ReleaseInterface(m_pOrderStatus);
    }
    CoUninitialize();
}

void CTPCC_COM::NewOrder()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pNewOrder->NewOrder(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray-
>rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

void CTPCC_COM::Payment()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pPayment->Payment(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray-
>rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);
}

```

```

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

void CTPCC_COM::StockLevel()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pStockLevel->StockLevel(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

void CTPCC_COM::OrderStatus()
{
    VARIANT    vTxn_out;

    HRESULT hr = m_pOrderStatus->OrderStatus(m_vTxn, &vTxn_out);
    if (FAILED(hr))
        throw new CCOMERR( hr );
    memcpy(m_pTxn, (void *)vTxn_out.parray->pvData, vTxn_out.parray->rgsabound[0].cElements);
    SafeArrayDestroy(vTxn_out.parray);

    if ( m_pTxn->ErrorType != ERR_SUCCESS )
        throw new CCOMERR( m_pTxn->ErrorType, m_pTxn->error );
}

/* FILE:      TPCC_COM.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not yet audited
 *
 * PURPOSE:   Header file for TPC-C COM+ class implementation.
 *
 * Change history:
 * 4.20.000 - first version
 */

#pragma once

#include <stdio.h>
#include "..\..\tpcc_com_ps\src\tpcc_com_ps.h"

```

```

// need to declare functions for import, unless define has already been
// created
// by the DLL's .cpp module for export.
#ifdef DllDecl
#define DllDecl __declspec( dllimport )
#endif

class CCOMERR : public CBaseErr
{
private:
    char m_szErrorText[64];

public:
    // use this interface for genuine COM errors
    CCOMERR( HRESULT hr )
    {
        m_hr = hr;
        m_iErrorType = 0;
        m_iError = 0;
    }

    // use this interface to impersonate a non-COM error type
    CCOMERR( int iErrorType, int iError )
    {
        m_iErrorType = iErrorType;
        m_iError = iError;
        m_hr = S_OK;
    }

    int    m_hr;
    int    m_iErrorType;
    int    m_iError;

    // A CCOMERR class can impersonate another class, which happens if
    // the error
    // was not actually a COM Services error, but was simply
    // transmitted back via COM.
    int ErrorType()
    {
        if (m_iErrorType == 0)
            return ERR_TYPE_COM;
        else
            return m_iErrorType;
    }

    int ErrorNum() {return m_hr;}

    char *ErrorText()
    {
        if (m_hr == S_OK)
            sprintf( m_szErrorText, "Error: Class %d, error # %d",
                m_iErrorType, m_iError );
        else

```

```

        sprintf( m_szErrorText, "Error: COM HRESULT %x", m_hr
);
        return m_szErrorText;
    }
};

class DllDecl CTPCC_COM : public CTPCC_BASE
{
private:
    BOOL m_bSinglePool;

    // COM Interface pointers
    ITPCC*      m_pNewOrder;
    ITPCC*      m_pPayment;
    ITPCC*      m_pStockLevel;
    ITPCC*      m_pOrderStatus;

    struct COM_DATA
    {
        int ErrorType;
        int error;
        union
        {
            NEW_ORDER_DATA      NewOrder;
            PAYMENT_DATA         Payment;
            DELIVERY_DATA        Delivery;
            STOCK_LEVEL_DATA     StockLevel;
            ORDER_STATUS_DATA    OrderStatus;
        } u;
    } *m_pTxn;

    VARIANT m_vTxn;
public:
    CTPCC_COM(BOOL bSinglePool);
    ~CTPCC_COM(void);

    inline PNEW_ORDER_DATA      BuffAddr_NewOrder()      { return
&m_pTxn->u.NewOrder; };
    inline PPAYMENT_DATA        BuffAddr_Payment()      { return
&m_pTxn->u.Payment; };
    inline PDELIVERY_DATA       BuffAddr_Delivery()     { return
&m_pTxn->u.Delivery; };
    inline PSTOCK_LEVEL_DATA    BuffAddr_StockLevel()   { return
&m_pTxn->u.StockLevel; };
    inline PORDER_STATUS_DATA   BuffAddr_OrderStatus()  { return
&m_pTxn->u.OrderStatus; };

    void NewOrder      ();
    void Payment       ();
    void StockLevel    ();
    void OrderStatus   ();
    void Delivery      () { throw new CCOMERR(E_NOTIMPL); } // not
supported

```

```

};

inline void ReleaseInterface(IUnknown *pUnk)
{
    if (pUnk)
    {
        pUnk->Release();
        pUnk = NULL;
    }
}

// wrapper routine for class constructor
extern "C" __declspec(dllexport) CTPCC_COM* CTPCC_COM_new(BOOL);

typedef CTPCC_COM* (TYPE_CTPCC_COM)(BOOL);

/* FILE:      METHODS.H
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not yet audited
 *
 * PURPOSE:   Header file for COM components.
 *
 * Change history:
 * 4.20.000 - first version
 */

enum COMPONENT_ERROR
{
    ERR_MISSING_REGISTRY_ENTRIES = 1,
    ERR_LOADDLL_FAILED,
    ERR_GETPROCADDR_FAILED,
    ERR_UNKNOWN_DB_PROTOCOL
};

class CCOMPONENT_ERR : public CBaseErr
{
public:
    CCOMPONENT_ERR(COMPONENT_ERROR Err)
    {
        m_Error = Err;
        m_szTextDetail = NULL;
        m_SystemErr = 0;
        m_szErrorText = NULL;
    };

    CCOMPONENT_ERR(COMPONENT_ERROR Err, char *szTextDetail, DWORD
dwSystemErr)

```

```

{
    m_Error = Err;
    m_szTextDetail = new char[strlen(szTextDetail)+1];
    strcpy( m_szTextDetail, szTextDetail );
    m_SystemErr = dwSystemErr;
    m_szErrorText = NULL;
};

~CCOMPONENT_ERR()
{
    if (m_szTextDetail != NULL)
        delete [] m_szTextDetail;
    if (m_szErrorText != NULL)
        delete [] m_szErrorText;
};

COMPONENT_ERROR m_Error;
char            *m_szTextDetail;
char            *m_szErrorText;
DWORD          m_SystemErr;

int ErrorType() {return ERR_TYPE_COMPONENT;};
int ErrorNum() {return m_Error;};
char *ErrorText();
};

static void WriteMessageToEventLog(LPTSTR lpszMsg);

////////////////////////////////////
/
// CTPCC_Common
class CTPCC_Common :
    public ITPCC,
    public IObjectControl,
    public IObjectConstruct,
    public CComObjectRootEx<CComSingleThreadModel>
{
public:
BEGIN_COM_MAP(CTPCC_Common)
    COM_INTERFACE_ENTRY(ITPCC)
    COM_INTERFACE_ENTRY(IObjectControl)
    COM_INTERFACE_ENTRY(IObjectConstruct)
END_COM_MAP()

    CTPCC_Common();
    ~CTPCC_Common();

// ITPCC
public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn);
    HRESULT __stdcall Payment(          int* iSize, UCHAR** txn);

```

```

    HRESULT __stdcall Delivery(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;};
    HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn);
    HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn);

    HRESULT __stdcall CallSetComplete();

// IObjectControl
    STDMETHODCALLTYPE CanBePooled() { return m_bCanBePooled; }
    STDMETHODCALLTYPE Activate() { return S_OK; } // we don't support COM
Services transactions (no enlistment)
    STDMETHODCALLTYPE Deactivate() { /* nothing to do */ }

// IObjectConstruct
    STDMETHODCALLTYPE Construct(IDispatch * pUnk);

// helper methods
private:
    BOOL            m_bCanBePooled;
    CTPCC_BASE *m_pTxn;

    struct COM_DATA
    {
        int retval;
        int error;
        union
        {
            NEW_ORDER_DATA          NewOrder;
            PAYMENT_DATA             Payment;
            DELIVERY_DATA            Delivery;
            STOCK_LEVEL_DATA         StockLevel;
            ORDER_STATUS_DATA        OrderStatus;
        } u;
    };
};

////////////////////////////////////
/
// CTPCC
class CTPCC :
    public CTPCC_Common,
    public CComCoClass<CTPCC, &CLSID_TPCC>
{
public:
DECLARE_REGISTRY_RESOURCEID(IDR_TPCC)

BEGIN_COM_MAP(CTPCC)
    COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
    COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
END_COM_MAP()
};

```

```

////////////////////////////////////
/
// CNewOrder
class CNewOrder :
    public CTPCC_Common,
    public CComCoClass<CNewOrder, &CLSID_NewOrder>
{
public:
DECLARE_REGISTRY_RESOURCEID(IDR_NEWORDER)

BEGIN_COM_MAP(CNewOrder)
    COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
    COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
END_COM_MAP()

// ITPCC
public:
// HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall Payment(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
};

////////////////////////////////////
/////
// COrderStatus
class COrderStatus :
    public CTPCC_Common,
    public CComCoClass<COrderStatus, &CLSID_OrderStatus>
{
public:
DECLARE_REGISTRY_RESOURCEID(IDR_ORDERSTATUS)

BEGIN_COM_MAP(COrderStatus)
    COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
    COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
END_COM_MAP()

// ITPCC
public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall Payment(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
};

```

```

// HRESULT __stdcall OrderStatus( int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
};

////////////////////////////////////
/
// CPayment
class CPayment :
    public CTPCC_Common,
    public CComCoClass<CPayment, &CLSID_Payment>
{
public:
DECLARE_REGISTRY_RESOURCEID(IDR_PAYMENT)

BEGIN_COM_MAP(CPayment)
    COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
    COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
END_COM_MAP()

// ITPCC
public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    // HRESULT __stdcall Payment(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall StockLevel(      int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall OrderStatus(     int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
};

////////////////////////////////////
/
// CStockLevel
class CStockLevel :
    public CTPCC_Common,
    public CComCoClass<CStockLevel, &CLSID_StockLevel>
{
public:
DECLARE_REGISTRY_RESOURCEID(IDR_STOCKLEVEL)

BEGIN_COM_MAP(CStockLevel)
    COM_INTERFACE_ENTRY2(IUnknown, CComObjectRootEx)
    COM_INTERFACE_ENTRY_CHAIN(CTPCC_Common)
END_COM_MAP()

// ITPCC
public:
    HRESULT __stdcall NewOrder(          int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
};

```

```

    HRESULT __stdcall Payment(    int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
//    HRESULT __stdcall StockLevel( int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
    HRESULT __stdcall OrderStatus( int* iSize, UCHAR** txn) {return
E_NOTIMPL;}
};

//{{NO_DEPENDENCIES}}
// Microsoft Developer Studio generated include file.
// Used by tpcc_com_all.rc
//
#define IDS_PROJNAME            100
#define IDR_TPCC                101
#define IDR_NEWORDER            102
#define IDR_ORDERSTATUS         103
#define IDR_PAYMENT             104
#define IDR_STOCKLEVEL          105

// Next default values for new objects
//
#ifdef APSTUDIO_INVOKED
#ifndef APSTUDIO_READONLY_SYMBOLS
#define _APS_NEXT_RESOURCE_VALUE        202
#define _APS_NEXT_COMMAND_VALUE        32768
#define _APS_NEXT_CONTROL_VALUE        201
#define _APS_NEXT_SYMED_VALUE          106
#endif
#endif

/*    FILE:      TPCC_COM_ALL.CPP
 *              Microsoft TPC-C Kit Ver. 4.20.000
 *              Copyright Microsoft, 1999
 *
 *              All Rights Reserved
 *
 *              Version 4.10.000 audited by Richard Gimarc, Performance
Metrics, 3/17/99
 *
 *    PURPOSE:   Implementation for TPC-C Tuxedo class.
 *    Contact:   Charles Levine (clevine@microsoft.com)
 *
 *    Change history:
 *              4.20.000 - updated rev number to match kit
 */

#define STRICT
#define _WIN32_WINNT 0x0400
#define _ATL_APARTMENT_THREADED

#include <stdio.h>
#include <atlbase.h>
//You may derive a class from CComModule and use it if you want to override

```

```

//something, but do not change the name of _Module
extern CComModule _Module;

#include <atlcom.h>
#include <initguid.h>
#include <transact.h>
#include <atlimpl.cpp>
#include <comsvcs.h>

#include <sqltypes.h>
#include <sql.h>
#include <sqlext.h>

#include "tpcc_com_ps.h"
#include "..\..\common\src\trans.h" //tpckit
transaction header contains definitions of structures specific to TPC-C
#include "..\..\common\src\txn_base.h"
#include "..\..\common\src\error.h"
#include "..\..\common\src\ReadRegistry.h"
#include "..\..\db_dblib_dll\src\tpcc_dblib.h" // DBLIB implementation
of TPC-C txns
#include "..\..\db_odbc_dll\src\tpcc_odbc.h" // ODBC implementation
of TPC-C txns

#include "resource.h"
#include "tpcc_com_all.h"
#include "tpcc_com_all_i.c"
#include "Methods.h"
#include "..\..\tpcc_com_ps\src\tpcc_com_ps_i.c"
#include "..\..\common\src\ReadRegistry.cpp"

CComModule _Module;

BEGIN_OBJECT_MAP(ObjectMap)
    OBJECT_ENTRY(CLSID_TPCC, CTPCC)
    OBJECT_ENTRY(CLSID_NewOrder, CNewOrder)
    OBJECT_ENTRY(CLSID_OrderStatus, COrderStatus)
    OBJECT_ENTRY(CLSID_Payment, CPayment)
    OBJECT_ENTRY(CLSID_StockLevel, CStockLevel)
END_OBJECT_MAP()

// configuration settings from registry
TPCCREGISTRYDATA    Reg;
char                szMyComputerName[MAX_COMPUTERNAME_LENGTH+1];

static HINSTANCE hLibInstanceDb = NULL;

TYPE_CTPCC_DBLIB    *pCTPCC_DBLIB_new;
TYPE_CTPCC_ODBC     *pCTPCC_ODBC_new;

```

```

////////////////////////////////////
/
// DLL Entry Point

extern "C"
BOOL WINAPI DllMain(HINSTANCE hInstance, DWORD dwReason, LPVOID
/*lpReserved*/)
{
    char szDllName[128];

    try
    {
        if (dwReason == DLL_PROCESS_ATTACH)
        {
            _Module.Init(ObjectMap, hInstance);
            DisableThreadLibraryCalls(hInstance);

            DWORD dwSize = MAX_COMPUTERNAME_LENGTH+1;
            GetComputerName(szMyComputerName, &dwSize);
            szMyComputerName[dwSize] = 0;

            if ( ReadTPCCRegistrySettings( &Reg ) )
                throw new CCOMPONENT_ERR( ERR_MISSING_REGISTRY_ENTRIES
);

            if (Reg.eDB_Protocol == DBLIB)
            {
                strcpy( szDllName, Reg.szPath );
                strcat( szDllName, "tpcc_dblib.dll");
                hLibInstanceDb = LoadLibrary( szDllName );
                if (hLibInstanceDb == NULL)
                    throw new CCOMPONENT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );

                // get function pointer to wrapper for class
            constructor
                pCTPCC_DBLIB_new = (TYPE_CTPCC_DBLIB*)
GetProcAddress(hLibInstanceDb, "CTPCC_DBLIB_new");
                if (pCTPCC_DBLIB_new == NULL)
                    throw new CCOMPONENT_ERR( ERR_GETPROCADDR_FAILED,
szDllName, GetLastError() );
            }
            else if (Reg.eDB_Protocol == ODBC)
            {
                strcpy( szDllName, Reg.szPath );
                strcat( szDllName, "tpcc_odbc.dll");
                hLibInstanceDb = LoadLibrary( szDllName );
                if (hLibInstanceDb == NULL)
                    throw new CCOMPONENT_ERR( ERR_LOADDLL_FAILED,
szDllName, GetLastError() );
            }
        }
    }
}

```

```

// get function pointer to wrapper for class
constructor
    pCTPCC_ODBC_new = (TYPE_CTPCC_ODBC*)
GetProcAddress(hLibInstanceDb, "CTPCC_ODBC_new");
    if (pCTPCC_ODBC_new == NULL)
        throw new CCOMPONENT_ERR( ERR_GETPROCADDR_FAILED,
szDllName, GetLastError() );
    }
    else
        throw new CCOMPONENT_ERR( ERR_UNKNOWN_DB_PROTOCOL );
}
else if (dwReason == DLL_PROCESS_DETACH)
    _Module.Term();
}
catch (CBaseErr *e)
{
    WriteMessageToEventLog(e->ErrorText());
    delete e;
    return FALSE;
}
catch (...)
{
    WriteMessageToEventLog(TEXT("Unhandled exception in object
DllMain"));
    return FALSE;
}

return TRUE; // OK
}

////////////////////////////////////
/
// Used to determine whether the DLL can be unloaded by OLE
STDAPI DllCanUnloadNow(void)
{
    return (_Module.GetLockCount()==0) ? S_OK : S_FALSE;
}

////////////////////////////////////
/
// Returns a class factory to create an object of the requested type
STDAPI DllGetClassObject(REFCLSID rclsid, REFIID riid, LPVOID* ppv)
{
    return _Module.GetClassObject(rclsid, riid, ppv);
}

////////////////////////////////////
/
// DllRegisterServer - Adds entries to the system registry

```

```

STDAPI DllRegisterServer(void)
{
    // registers object, typelib and all interfaces in typelib
    return _Module.RegisterServer(TRUE);
}

////////////////////////////////////
// DllUnregisterServer - Removes entries from the system registry

STDAPI DllUnregisterServer(void)
{
    _Module.UnregisterServer();
    return S_OK;
}

static void WriteMessageToEventLog(LPTSTR lpszMsg)
{
    TCHAR    szMsg[256];
    HANDLE   hEventSource;
    LPTSTR   lpszStrings[2];

    // Use event logging to log the error.
    //
    hEventSource = RegisterEventSource(NULL, TEXT("tpcc_com_all.dll"));

    _stprintf(szMsg, TEXT("Error in COM+ TPC-C Component: "));
    lpszStrings[0] = szMsg;
    lpszStrings[1] = lpszMsg;

    if (hEventSource != NULL)
    {
        ReportEvent(hEventSource, // handle of event source
            EVENTLOG_ERROR_TYPE, // event type
            0, // event category
            0, // event ID
            NULL, // current user's SID
            2, // strings in lpszStrings
            0, // no bytes of raw data
            (LPCWSTR *)lpszStrings, // array of error strings
            NULL); // no raw data

        (VOID) DeregisterEventSource(hEventSource);
    }
}

inline void ReleaseInterface(IUnknown *pUnk)
{
    if (pUnk)
    {
        pUnk->Release();
        pUnk = NULL;
    }
}

```

```

}

/* FUNCTION: CCOMPONENT_ERR::ErrorText
 *
 */

char* CCOMPONENT_ERR::ErrorText(void)
{
    static SERRORMSG errorMsgs[] =
    {
        { ERR_MISSING_REGISTRY_ENTRIES, "Required entries missing from
registry." },
        { ERR_LOADDLL_FAILED, "Load of DLL failed. DLL="
},
        { ERR_GETPROCADDR_FAILED, "Could not map proc in DLL.
GetProcAddr error. DLL=" },
        { ERR_UNKNOWN_DB_PROTOCOL, "Unknown database protocol
specified in registry." },
        { 0, "" }
    };

    char szTmp[256];
    int i = 0;
    while (TRUE)
    {
        if (errorMsgs[i].szMsg[0] == 0)
        {
            strcpy( szTmp, "Unknown error number." );
            break;
        }
        if (m_Error == errorMsgs[i].iError)
        {
            strcpy( szTmp, errorMsgs[i].szMsg );
            break;
        }
        i++;
    }

    if (m_szTextDetail)
        strcat( szTmp, m_szTextDetail );
    if (m_SystemErr)
        wsprintf( szTmp+strlen(szTmp), " Error=%d", m_SystemErr );

    m_szErrorText = new char[strlen(szTmp)+1];
    strcpy( m_szErrorText, szTmp );
    return m_szErrorText;
}

CTPCC_Common::CTPCC_Common()
{

```

```

        m_pTxn = NULL;
        m_bCanBePooled = TRUE;
    }

CTPCC_Common::~CTPCC_Common()
{
    if (m_pTxn)
        delete m_pTxn;
}

HRESULT CTPCC_Common::CallSetComplete()
{
    IObjectContext* pObjectContext = NULL;

    // get our object context
    HRESULT hr = CoGetObjectContext( IID_IObjectContext, (void
**) &pObjectContext );
    pObjectContext->SetComplete();
    ReleaseInterface(pObjectContext);
    return hr;
}

//
// called by the ctor activator
//
STDMETHODIMP CTPCC_Common::Construct(IDispatch * pUnk)
{
    // Code to access construction string, if needed later...
    // if (!pUnk)
    //     return E_UNEXPECTED;
    // IObjectConstructString * pString = NULL;
    // HRESULT hr = pUnk->QueryInterface(IID_IObjectConstructString,
(void **) &pString);
    // pString->Release();

    try
    {
        if (Reg.eDB_Protocol == ODBC)
            m_pTxn = pCTPCC_ODBC_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
        else if (Reg.eDB_Protocol == DBLIB)
            m_pTxn = pCTPCC_DBLIB_new( Reg.szDbServer, Reg.szDbUser,
Reg.szDbPassword, szMyComputerName, Reg.szDbName );
    }
    catch (CBaseErr *e)
    {
        WriteMessageToEventLog(e->ErrorText());
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
}
}

```

```

        WriteMessageToEventLog(TEXT("Unhandled exception in object
::Construct"));
        return E_FAIL;
    }

    return S_OK;
}

HRESULT CTPCC_Common::NewOrder(int* iSize, UCHAR **txn)
{
    PNEW_ORDER_DATA pNewOrder;
    COM_DATA *pData;

    try
    {
        pData = (COM_DATA*) *txn;
        pNewOrder = m_pTxn->BuffAddr_NewOrder();

        memcpy(pNewOrder, &pData->u.NewOrder, sizeof(NEW_ORDER_DATA));
        m_pTxn->NewOrder();
        memcpy( &pData->u.NewOrder, pNewOrder, sizeof(NEW_ORDER_DATA));

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database connection; if yes, component is toast
        if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
            ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==
10054)) )
            m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception. "));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

HRESULT CTPCC_Common::Payment(int* iSize, UCHAR** txn)
{
    PPAYMENT_DATA pPayment;
}

```

```

COM_DATA      *pData;

try
{
    pData = (COM_DATA*)*txn;
    pPayment = m_pTxn->BuffAddr_Payment();

    memcpy(pPayment, &pData->u.Payment, sizeof(PAYMENT_DATA) );
    m_pTxn->Payment();
    memcpy( &pData->u.Payment, pPayment, sizeof(PAYMENT_DATA) );

    pData->retval = ERR_SUCCESS;
    pData->error = 0;
    return S_OK;
}
catch (CBaseErr *e)
{
    // check for lost database connection; if yes, component is toast
    if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
        ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==
10054)) )
        m_bCanBePooled = FALSE;

    pData->retval = e->ErrorType();
    pData->error = e->ErrorNum();
    delete e;
    return E_FAIL;
}
catch (...)
{
    WriteMessageToEventLog(TEXT("Unhandled exception."));
    pData->retval = ERR_TYPE_LOGIC;
    pData->error = 0;
    m_bCanBePooled = FALSE;
    return E_FAIL;
}
}

HRESULT CTPCC_Common::StockLevel(int* iSize, UCHAR** txn)
{
    PSTOCK_LEVEL_DATA    pStockLevel;
    COM_DATA              *pData;

    try
    {
        pData = (COM_DATA*)*txn;
        pStockLevel = m_pTxn->BuffAddr_StockLevel();

        memcpy(pStockLevel, &pData->u.StockLevel, sizeof(STOCK_LEVEL_DATA)
);
    }
    m_pTxn->StockLevel();
};

```

```

        memcpy( &pData->u.StockLevel, pStockLevel,
sizeof(STOCK_LEVEL_DATA) );

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {
        // check for lost database connection; if yes, component is toast
        if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
            ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==
10054)) )
            m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception."));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

HRESULT CTPCC_Common::OrderStatus(int* iSize, UCHAR** txn)
{
    PORDER_STATUS_DATA    pOrderStatus;
    COM_DATA              *pData;

    try
    {
        pData = (COM_DATA*)*txn;
        pOrderStatus = m_pTxn->BuffAddr_OrderStatus();

        memcpy(pOrderStatus, &pData->u.OrderStatus,
sizeof(ORDER_STATUS_DATA) );
        m_pTxn->OrderStatus();
        memcpy( &pData->u.OrderStatus, pOrderStatus,
sizeof(ORDER_STATUS_DATA) );

        pData->retval = ERR_SUCCESS;
        pData->error = 0;
        return S_OK;
    }
    catch (CBaseErr *e)
    {

```

```

        // check for lost database connection; if yes, component is toast
        if ( ((e->ErrorType() == ERR_TYPE_DBLIB) && (e->ErrorNum() ==
10005)) ||
            ((e->ErrorType() == ERR_TYPE_ODBC) && (e->ErrorNum() ==
10054)) )
            m_bCanBePooled = FALSE;

        pData->retval = e->ErrorType();
        pData->error = e->ErrorNum();
        delete e;
        return E_FAIL;
    }
    catch (...)
    {
        WriteMessageToEventLog(TEXT("Unhandled exception.));
        pData->retval = ERR_TYPE_LOGIC;
        pData->error = 0;
        m_bCanBePooled = FALSE;
        return E_FAIL;
    }
}

; tpcc_com_all.def : Declares the module parameters.

LIBRARY      "tpcc_com_all.dll"

EXPORTS
    DllCanUnloadNow      @1 PRIVATE
    DllGetClassObject    @2 PRIVATE
    DllRegisterServer    @3 PRIVATE
    DllUnregisterServer  @4 PRIVATE

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the definitions for the interfaces */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:20 2000
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
    Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
    error checks: allocation ref bounds_check enum stub_data
    VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

/* verify that the <rpcndr.h> version is high enough to compile this file*/
#endifdef __REQUIRED_RPCNDR_H_VERSION__

```

```

#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

#include "rpc.h"
#include "rpcndr.h"

#ifndef __tpcc_com_all_h__
#define __tpcc_com_all_h__

/* Forward Declarations */

#ifndef __TPCC_FWD_DEFINED__
#define __TPCC_FWD_DEFINED__

#ifdef __cplusplus
typedef class TPCC TPCC;
#else
typedef struct TPCC TPCC;
#endif /* __cplusplus */

#endif /* __TPCC_FWD_DEFINED__ */

#ifndef __NewOrder_FWD_DEFINED__
#define __NewOrder_FWD_DEFINED__

#ifdef __cplusplus
typedef class NewOrder NewOrder;
#else
typedef struct NewOrder NewOrder;
#endif /* __cplusplus */

#endif /* __NewOrder_FWD_DEFINED__ */

#ifndef __OrderStatus_FWD_DEFINED__
#define __OrderStatus_FWD_DEFINED__

#ifdef __cplusplus
typedef class OrderStatus OrderStatus;
#else
typedef struct OrderStatus OrderStatus;
#endif /* __cplusplus */

#endif /* __OrderStatus_FWD_DEFINED__ */

#ifndef __Payment_FWD_DEFINED__
#define __Payment_FWD_DEFINED__

#ifdef __cplusplus
typedef class Payment Payment;
#else

```

```

typedef struct Payment Payment;
#endif /* __cplusplus */

#endif /* __Payment_FWD_DEFINED__ */

#ifdef __StockLevel_FWD_DEFINED__
#define __StockLevel_FWD_DEFINED__

#ifdef __cplusplus
typedef class StockLevel StockLevel;
#else
typedef struct StockLevel StockLevel;
#endif /* __cplusplus */

#endif /* __StockLevel_FWD_DEFINED__ */

/* header files for imported files */
#include "oaidl.h"
#include "ocidl.h"
#include "tpcc_com_ps.h"

#ifdef __cplusplus
extern "C"{
#endif

void __RPC_FAR * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void __RPC_FAR * );

/* interface __MIDL_itf_tpcc_com_all_0000 */
/* [local] */

extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_all_0000_v0_0_c_ifspec;
extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_all_0000_v0_0_s_ifspec;

#ifdef __TPCCLib_LIBRARY_DEFINED__
#define __TPCCLib_LIBRARY_DEFINED__

/* library TPCCLib */
/* [helpstring][version][uuid] */

EXTERN_C const IID LIBID_TPCCLib;

```

```

EXTERN_C const CLSID CLSID_TPCC;

#ifdef __cplusplus
class DECLSPEC_UUID("122A3128-2520-11D3-BA71-00C04FBFE08B")
TPCC;
#endif

EXTERN_C const CLSID CLSID_NewOrder;

#ifdef __cplusplus
class DECLSPEC_UUID("975BAABF-84A7-11D2-BA47-00C04FBFE08B")
NewOrder;
#endif

EXTERN_C const CLSID CLSID_OrderStatus;

#ifdef __cplusplus
class DECLSPEC_UUID("266836AD-A50D-11D2-BA4E-00C04FBFE08B")
OrderStatus;
#endif

EXTERN_C const CLSID CLSID_Payment;

#ifdef __cplusplus
class DECLSPEC_UUID("CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B")
Payment;
#endif

EXTERN_C const CLSID CLSID_StockLevel;

#ifdef __cplusplus
class DECLSPEC_UUID("2668369E-A50D-11D2-BA4E-00C04FBFE08B")
StockLevel;
#endif
#endif /* __TPCCLib_LIBRARY_DEFINED__ */

/* Additional Prototypes for ALL interfaces */

/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif

#endif

```

```

/* FILE:      TPCC.IDL
 *           Microsoft TPC-C Kit Ver. 4.20.000
 *           Copyright Microsoft, 1999
 *           All Rights Reserved
 *
 *           not yet audited
 *
 * PURPOSE:   IDL source for TPCC.dll. This file is processed by the MIDL
tool to
 *           produce the type library (TPCC.tlb) and marshalling
code.
 *
 * Change history:
 *   4.20.000 - first version
 */

```

```

interface TPCC;
interface NewOrder;
interface OrderStatus;
interface Payment;
interface StockLevel;

```

```

import "oidl.idl";
import "ocidl.idl";
import "..\tpcc_com_ps\src\tpcc_com_ps.idl";

```

```

[
    uuid(122A3117-2520-11D3-BA71-00C04FBFE08B),
    version(1.0),
    helpstring("TPC-C 1.0 Type Library")
]
library TPCCLib
{
    importlib("stdole32.tlb");
    importlib("stdole2.tlb");

    [
        uuid(122A3128-2520-11D3-BA71-00C04FBFE08B),
        helpstring("All Txns Class")
    ]
    coclass TPCC
    {
        [default] interface ITPCC;
    };

    [
        uuid(975BAABF-84A7-11D2-BA47-00C04FBFE08B),
        helpstring("NewOrder Class")
    ]
    coclass NewOrder
    {

```

```

        [default] interface ITPCC;
    };

    [
        uuid(266836AD-A50D-11D2-BA4E-00C04FBFE08B),
        helpstring("OrderStatus Class")
    ]
    coclass OrderStatus
    {
        [default] interface ITPCC;
    };

    [
        uuid(CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B),
        helpstring("Payment Class")
    ]
    coclass Payment
    {
        [default] interface ITPCC;
    };

    [
        uuid(2668369E-A50D-11D2-BA4E-00C04FBFE08B),
        helpstring("StockLevel Class")
    ]
    coclass StockLevel
    {
        [default] interface ITPCC;
    };
};

```

```

};

//Microsoft Developer Studio generated resource script.
//
#include "resource.h"

#define APSTUDIO_READONLY_SYMBOLS
////////////////////////////////////
/
//
// Generated from the TEXTINCLUDE 2 resource.
//
#include "winres.h"

////////////////////////////////////
/
#undef APSTUDIO_READONLY_SYMBOLS
////////////////////////////////////
/

```

```

// English (U.S.) resources

#if !defined(AFX_RESOURCE_DLL) || defined(AFX_TARG_ENU)
#ifdef _WIN32
LANGUAGE LANG_ENGLISH, SUBLANG_ENGLISH_US
#pragma code_page(1252)
#endif // _WIN32

#ifdef APSTUDIO_INVOKED
////////////////////////////////////
/
//
// TEXTINCLUDE
//

1 TEXTINCLUDE DISCARDABLE
BEGIN
    "resource.h\0"
END

2 TEXTINCLUDE DISCARDABLE
BEGIN
    "#include "winres.h"\r\n"
    "\0"
END

3 TEXTINCLUDE DISCARDABLE
BEGIN
    "1 TYPELIB "tpcc_com_all.tlb"\r\n"
    "\0"
END

#endif // APSTUDIO_INVOKED

#ifdef _MAC
////////////////////////////////////
/
//
// Version
//

VS_VERSION_INFO VERSIONINFO
FILEVERSION 1,0,0,1
PRODUCTVERSION 1,0,0,1
FILEFLAGSMASK 0x3fL
#ifdef _DEBUG
FILEFLAGS 0x1L
#else
FILEFLAGS 0x0L
#endif
FILEOS 0x4L
FILETYPE 0x2L

```

```

FILESUBTYPE 0x0L
BEGIN
    BLOCK "StringFileInfo"
    BEGIN
        BLOCK "040904B0"
        BEGIN
            VALUE "CompanyName", "\0"
            VALUE "FileDescription", "tpcc_com_all Module\0"
            VALUE "FileVersion", "1, 0, 0, 1\0"
            VALUE "InternalName", "TPCCNEWORDER\0"
            VALUE "LegalCopyright", "Copyright 1997\0"
            VALUE "OriginalFilename", "tpcc_com_all.DLL\0"
            VALUE "ProductName", "tpcc_com_all Module\0"
            VALUE "ProductVersion", "1, 0, 0, 1\0"
            VALUE "OLESelfRegister", "\0"
        END
    END
    BLOCK "VarFileInfo"
    BEGIN
        VALUE "Translation", 0x409, 1200
    END
END

#endif // !_MAC

////////////////////////////////////
/
//
// REGISTRY
//

IDR_TPCC                REGISTRY DISCARDABLE    "tpcc_com_all.rgs"
IDR_NEWORDER            REGISTRY DISCARDABLE    "tpcc_com_no.rgs"
IDR_ORDERSTATUS        REGISTRY DISCARDABLE    "tpcc_com_os.rgs"
IDR_PAYMENT             REGISTRY DISCARDABLE    "tpcc_com_pay.rgs"
IDR_STOCKLEVEL         REGISTRY DISCARDABLE    "tpcc_com_sl.rgs"

////////////////////////////////////
/
//
// String Table
//

STRINGTABLE DISCARDABLE
BEGIN
    IDS_PROJNAME          "tpcc_com_all"
END

#endif // English (U.S.) resources
////////////////////////////////////
/

```

```

#ifdef APSTUDIO_INVOKED
//
//
// Generated from the TEXTINCLUDE 3 resource.
//
1 TYPELIB "tpcc_com_all.tlb"

//
//
#endif // not APSTUDIO_INVOKED

HKCR
{
    TPCC.AllTxns.1 = s 'All Txns Class'
    {
        CLSID = s '{122A3128-2520-11D3-BA71-00C04FBFE08B}'
    }
    TPCC.AllTxns = s 'TPCC Class'
    {
        CurVer = s 'TPCC.AllTxns.1'
    }
    NoRemove CLSID
    {
        ForceRemove {122A3128-2520-11D3-BA71-00C04FBFE08B} = s 'TPCC
Class'
        {
            ProgID = s 'TPCC.AllTxns.1'
            VersionIndependentProgID = s 'TPCC.AllTxns'
            InprocServer32 = s '%MODULE%'
            {
                val ThreadingModel = s 'Both'
            }
        }
    }
}

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */

/* link this file in with the server and any clients */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:20 2000
*/
/* Compiler settings for .\src\tpcc_com_all.idl:
Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext

```

```

error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany), __declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#ifdef _M_IA64 && !defined(_M_AXP64)

#ifdef __cplusplus
extern "C" {
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

```

```

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
LIBID_TPCCLib,0x122A3117,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x
8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_TPCC,0x122A3128,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x8B)
;

MIDL_DEFINE_GUID(CLSID,
CLSID_NewOrder,0x975BAABF,0x84A7,0x11D2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0
x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_OrderStatus,0x266836AD,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE
0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_Payment,0xCD02F7EF,0xA4FA,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x
8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_StockLevel,0x2668369E,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0
,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* !defined(_M_IA64) && !defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */

/* link this file in with the server and any clients */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:20 2000
*/
/* Compiler settings for .\src\tpcc_com_all.idl:

```

```

Oicf (OptLev=i2), W1, Zp8, env=Win64 (32b run,appending), ms_ext, c_ext,
robust
error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
__declspec(uuid()), __declspec(selectany), __declspec(novtable)
DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#if defined(_M_IA64) || defined(_M_AXP64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
    DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \

```

```

        const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}
#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
LIBID_TPCCLib,0x122A3117,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x
8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_TPCC,0x122A3128,0x2520,0x11D3,0xBA,0x71,0x00,0xC0,0x4F,0xBF,0xE0,0x8B)
;

MIDL_DEFINE_GUID(CLSID,
CLSID_NewOrder,0x975BAABF,0x84A7,0x11D2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0
x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_OrderStatus,0x266836AD,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE
0,0x8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_Payment,0xCD02F7EF,0xA4FA,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0,0x
8B);

MIDL_DEFINE_GUID(CLSID,
CLSID_StockLevel,0x2668369E,0xA50D,0x11D2,0xBA,0x4E,0x00,0xC0,0x4F,0xBF,0xE0
,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* defined(_M_IA64) || defined(_M_AXP64)*/

HKCR
{
    TPCC.NewOrder.1 = s 'NewOrder Class'
    {
        CLSID = s '{975BAABF-84A7-11D2-BA47-00C04FBFE08B}'
    }
    TPCC.NewOrder = s 'NewOrder Class'
    {
        CurVer = s 'TPCC.NewOrder.1'
    }
}

```

```

    }
    NoRemove CLSID
    {
        ForceRemove {975BAABF-84A7-11D2-BA47-00C04FBFE08B} = s 'NewOrder
Class'
    {
        ProgID = s 'TPCC.NewOrder.1'
        VersionIndependentProgID = s 'TPCC.NewOrder'
        InprocServer32 = s '%MODULE%'
        {
            val ThreadingModel = s 'Both'
        }
    }
}

HKCR
{
    TPCC.OrderStatus.1 = s 'OrderStatus Class'
    {
        CLSID = s '{266836AD-A50D-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.OrderStatus = s 'OrderStatus Class'
    {
        CurVer = s 'TPCC.OrderStatus.1'
    }
    NoRemove CLSID
    {
        ForceRemove {266836AD-A50D-11D2-BA4E-00C04FBFE08B} = s
'OrderStatus Class'
    {
        ProgID = s 'TPCC.OrderStatus.1'
        VersionIndependentProgID = s 'TPCC.OrderStatus'
        InprocServer32 = s '%MODULE%'
        {
            val ThreadingModel = s 'Both'
        }
    }
}
}

HKCR
{
    TPCC.Payment.1 = s 'Payment Class'
    {
        CLSID = s '{CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.Payment = s 'Payment Class'
    {
        CurVer = s 'TPCC.Payment.1'
    }
    NoRemove CLSID
    {

```

```

Class' ForceRemove {CD02F7EF-A4FA-11D2-BA4E-00C04FBFE08B} = s 'Payment
{
    ProgID = s 'TPCC.Payment.1'
    VersionIndependentProgID = s 'TPCC.Payment'
    InprocServer32 = s '%MODULE%'
    {
        val ThreadingModel = s 'Both'
    }
}
}

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the definitions for the interfaces */

/* File created by MIDL compiler version 5.03.0280 */
/* at Mon Jan 24 20:00:07 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
    Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
    error checks: allocation ref bounds_check enum stub_data
    VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

/* verify that the <rpcndr.h> version is high enough to compile this file*/
#ifndef __REQUIRED_RPCNDR_H_VERSION__
#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

#include "rpc.h"
#include "rpcndr.h"

#ifndef __RPCNDR_H_VERSION__
#error this stub requires an updated version of <rpcndr.h>
#endif // __RPCNDR_H_VERSION__

#ifndef COM_NO_WINDOWS_H
#include "windows.h"
#include "ole2.h"
#endif /*COM_NO_WINDOWS_H*/

#ifndef __tpcc_com_ps_h__
#define __tpcc_com_ps_h__

/* Forward Declarations */

```

```

#ifndef __ITPCC_FWD_DEFINED__
#define __ITPCC_FWD_DEFINED__
typedef interface ITPCC ITPCC;
#endif /* __ITPCC_FWD_DEFINED__ */

/* header files for imported files */
#include "oaidl.h"
#include "ocidl.h"

#ifdef __cplusplus
extern "C"{
#endif

void __RPC_FAR * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void __RPC_FAR * );

#ifndef __ITPCC_INTERFACE_DEFINED__
#define __ITPCC_INTERFACE_DEFINED__

/* interface ITPCC */
/* [unique][helpstring][uuid][object] */

EXTERN_C const IID IID_ITPCC;

#if defined(__cplusplus) && !defined(CINTERFACE)

    MIDL_INTERFACE("FEEE6AA2-84B1-11d2-BA47-00C04FBFE08B")
    ITPCC : public IUnknown
    {
    public:
        virtual HRESULT __stdcall NewOrder(
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            *__RPC_FAR *txn) = 0;

        virtual HRESULT __stdcall Payment(
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            *__RPC_FAR *txn) = 0;

        virtual HRESULT __stdcall Delivery(
            /* [in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][in] */ unsigned char __RPC_FAR
            *__RPC_FAR *txn) = 0;

        virtual HRESULT __stdcall StockLevel(
            /* [out][in] */ int __RPC_FAR *iSize,
            /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
            *__RPC_FAR *txn) = 0;

```

```

    virtual HRESULT __stdcall OrderStatus(
        /* [out][in] */ int __RPC_FAR *iSize,
        /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
*_RPC_FAR *txn) = 0;

    virtual HRESULT __stdcall CallSetComplete( void) = 0;
};

#else /* C style interface */

typedef struct ITPCCVtbl
{
    BEGIN_INTERFACE

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *QueryInterface )(
        ITPCC __RPC_FAR * This,
        /* [in] */ REFIID riid,
        /* [iid_is][out] */ void __RPC_FAR *__RPC_FAR *ppvObject);

    ULONG ( STDMETHODCALLTYPE __RPC_FAR *AddRef )(
        ITPCC __RPC_FAR * This);

    ULONG ( STDMETHODCALLTYPE __RPC_FAR *Release )(
        ITPCC __RPC_FAR * This);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *NewOrder )(
        ITPCC __RPC_FAR * This,
        /* [out][in] */ int __RPC_FAR *iSize,
        /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
*_RPC_FAR *txn);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Payment )(
        ITPCC __RPC_FAR * This,
        /* [out][in] */ int __RPC_FAR *iSize,
        /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
*_RPC_FAR *txn);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Delivery )(
        ITPCC __RPC_FAR * This,
        /* [in] */ int __RPC_FAR *iSize,
        /* [size_is][size_is][in] */ unsigned char __RPC_FAR *__RPC_FAR
*txn);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *StockLevel )(
        ITPCC __RPC_FAR * This,
        /* [out][in] */ int __RPC_FAR *iSize,
        /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
*_RPC_FAR *txn);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *OrderStatus )(
        ITPCC __RPC_FAR * This,
        /* [out][in] */ int __RPC_FAR *iSize,

```

```

        /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR
*_RPC_FAR *txn);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *CallSetComplete )(
        ITPCC __RPC_FAR * This);

    END_INTERFACE
} ITPCCVtbl;

interface ITPCC
{
    CONST_VTBL struct ITPCCVtbl __RPC_FAR *lpVtbl;
};

#ifdef COBJMACROS

#define ITPCC_QueryInterface(This,riid,ppvObject) \
    (This->lpVtbl -> QueryInterface(This,riid,ppvObject))

#define ITPCC_AddRef(This) \
    (This->lpVtbl -> AddRef(This))

#define ITPCC_Release(This) \
    (This->lpVtbl -> Release(This))

#define ITPCC_NewOrder(This,iSize,txn) \
    (This->lpVtbl -> NewOrder(This,iSize,txn))

#define ITPCC_Payment(This,iSize,txn) \
    (This->lpVtbl -> Payment(This,iSize,txn))

#define ITPCC_Delivery(This,iSize,txn) \
    (This->lpVtbl -> Delivery(This,iSize,txn))

#define ITPCC_StockLevel(This,iSize,txn) \
    (This->lpVtbl -> StockLevel(This,iSize,txn))

#define ITPCC_OrderStatus(This,iSize,txn) \
    (This->lpVtbl -> OrderStatus(This,iSize,txn))

#define ITPCC_CallSetComplete(This) \
    (This->lpVtbl -> CallSetComplete(This))

#endif /* COBJMACROS */

#endif /* C style interface */

```

```

HRESULT __stdcall ITPCC_NewOrder_Proxy(
    ITPCC __RPC_FAR * This,
    /* [out][in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
    *txn);

void __RPC_STUB ITPCC_NewOrder_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Payment_Proxy(
    ITPCC __RPC_FAR * This,
    /* [out][in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
    *txn);

void __RPC_STUB ITPCC_Payment_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Delivery_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][in] */ unsigned char __RPC_FAR *__RPC_FAR *txn);

void __RPC_STUB ITPCC_Delivery_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_StockLevel_Proxy(
    ITPCC __RPC_FAR * This,
    /* [out][in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
    *txn);

void __RPC_STUB ITPCC_StockLevel_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,

```

```

    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_OrderStatus_Proxy(
    ITPCC __RPC_FAR * This,
    /* [out][in] */ int __RPC_FAR *iSize,
    /* [size_is][size_is][out][in] */ unsigned char __RPC_FAR *__RPC_FAR
    *txn);

void __RPC_STUB ITPCC_OrderStatus_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_CallSetComplete_Proxy(
    ITPCC __RPC_FAR * This);

void __RPC_STUB ITPCC_CallSetComplete_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

#endif /* __ITPCC_INTERFACE_DEFINED__ */

/* Additional Prototypes for ALL interfaces */
/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif

#endif

HKCR
{
    TPCC.StockLevel.1 = s 'StockLevel Class'
    {
        CLSID = s '{2668369E-A50D-11D2-BA4E-00C04FBFE08B}'
    }
    TPCC.StockLevel = s 'StockLevel Class'
    {
        CurVer = s 'TPCC.StockLevel.1'
    }

```

```

}
NoRemove CLSID
{
    ForceRemove {2668369E-A50D-11D2-BA4E-00C04FBFE08B} = s 'StockLevel
Class'
{
    ProgID = s 'TPCC.StockLevel.1'
    VersionIndependentProgID = s 'TPCC.StockLevel'
    InprocServer32 = s '%MODULE%'
    {
        val ThreadingModel = s 'Both'
    }
}
}
}

```

```

/*****
DllData file -- generated by MIDL compiler

DO NOT ALTER THIS FILE

This file is regenerated by MIDL on every IDL file compile.

To completely reconstruct this file, delete it and rerun MIDL
on all the IDL files in this DLL, specifying this file for the
/dlldata command line option

```

```

*****/

```

```

#include <rpcproxy.h>

```

```

#ifdef __cplusplus
extern "C" {
#endif

```

```

EXTERN_PROXY_FILE( tpcc_com_ps )

```

```

PROXYFILE_LIST_START
/* Start of list */
REFERENCE_PROXY_FILE( tpcc_com_ps ),
/* End of list */
PROXYFILE_LIST_END

```

```

DLLDATA_ROUTINES( aProxyFileList, GET_DLL_CLSID )

```

```

#ifdef __cplusplus
} /*extern "C" */
#endif

```

```

/* end of generated dlldata file */

```

```

LIBRARY      "tpcc_com_ps"

DESCRIPTION  'Proxy/Stub DLL'

EXPORTS
    DllGetClassObject      @1 PRIVATE
    DllCanUnloadNow        @2 PRIVATE
    GetProxyDllInfo        @3 PRIVATE
    DllRegisterServer      @4 PRIVATE
    DllUnregisterServer    @5 PRIVATE

```

```

#pragma warning( disable: 4049 ) /* more than 64k source lines */

```

```

/* this ALWAYS GENERATED file contains the definitions for the interfaces */

```

```

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/

```

```

/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
    __declspec(uuid()), __declspec(selectany), __declspec(novtable)
    DECLSPEC_UUID(), MIDL_INTERFACE()
*/

```

```

//@@MIDL_FILE_HEADING(  )

```

```

/* verify that the <rpcndr.h> version is high enough to compile this file*/
#ifdef __REQUIRED_RPCNDR_H_VERSION__
#define __REQUIRED_RPCNDR_H_VERSION__ 440
#endif

```

```

#include "rpc.h"
#include "rpcndr.h"

```

```

#ifdef __RPCNDR_H_VERSION__
#error this stub requires an updated version of <rpcndr.h>
#endif // __RPCNDR_H_VERSION__

```

```

#ifdef COM_NO_WINDOWS_H
#include "windows.h"
#include "ole2.h"
#endif /*COM_NO_WINDOWS_H*/

```

```

#ifdef __tpcc_com_ps_h__
#define __tpcc_com_ps_h__

```

```

/* Forward Declarations */

```

```

#ifndef __ITPCC_FWD_DEFINED__
#define __ITPCC_FWD_DEFINED__
typedef interface ITPCC ITPCC;
#endif /* __ITPCC_FWD_DEFINED__ */

/* header files for imported files */
#include "oidl.h"
#include "ocidl.h"

#ifdef __cplusplus
extern "C"{
#endif

void __RPC_FAR * __RPC_USER MIDL_user_allocate(size_t);
void __RPC_USER MIDL_user_free( void __RPC_FAR * );

/* interface __MIDL_itf_tpcc_com_ps_0000 */
/* [local] */

extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_ps_0000_v0_0_c_ifspec;
extern RPC_IF_HANDLE __MIDL_itf_tpcc_com_ps_0000_v0_0_s_ifspec;

#ifndef __ITPCC_INTERFACE_DEFINED__
#define __ITPCC_INTERFACE_DEFINED__

/* interface ITPCC */
/* [unique][helpstring][uuid][oleautomation][object] */

EXTERN_C const IID IID_ITPCC;

#if defined(__cplusplus) && !defined(CINTERFACE)

MIDL_INTERFACE("FEEE6AA2-84B1-11d2-BA47-00C04FBFE08B")
ITPCC : public IUnknown
{
public:
    virtual HRESULT __stdcall NewOrder(
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

    virtual HRESULT __stdcall Payment(
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

    virtual HRESULT __stdcall Delivery(
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

```

```

    virtual HRESULT __stdcall StockLevel(
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

    virtual HRESULT __stdcall OrderStatus(
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out) = 0;

    virtual HRESULT __stdcall CallSetComplete( void) = 0;

};

#else /* C style interface */

typedef struct ITPCCVtbl
{
    BEGIN_INTERFACE

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *QueryInterface )(
        ITPCC __RPC_FAR * This,
        /* [in] */ REFIID riid,
        /* [iid_is][out] */ void __RPC_FAR *__RPC_FAR *ppvObject);

    ULONG ( STDMETHODCALLTYPE __RPC_FAR *AddRef )(
        ITPCC __RPC_FAR * This);

    ULONG ( STDMETHODCALLTYPE __RPC_FAR *Release )(
        ITPCC __RPC_FAR * This);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *NewOrder )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Payment )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *Delivery )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *StockLevel )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,
        /* [out] */ VARIANT __RPC_FAR *txn_out);

    HRESULT ( STDMETHODCALLTYPE __RPC_FAR *OrderStatus )(
        ITPCC __RPC_FAR * This,
        /* [in] */ VARIANT txn_in,

```

```

        /* [out] */ VARIANT __RPC_FAR *txn_out);

HRESULT ( __stdcall __RPC_FAR *CallSetComplete )(
    ITPCC __RPC_FAR * This);

    END_INTERFACE
} ITPCCVtbl;

interface ITPCC
{
    CONST_VTBL struct ITPCCVtbl __RPC_FAR *lpVtbl;
};

#ifdef COBJMACROS

#define ITPCC_QueryInterface(This,riid,ppvObject) \
    (This)->lpVtbl -> QueryInterface(This,riid,ppvObject)

#define ITPCC_AddRef(This) \
    (This)->lpVtbl -> AddRef(This)

#define ITPCC_Release(This) \
    (This)->lpVtbl -> Release(This)

#define ITPCC_NewOrder(This,txn_in,txn_out) \
    (This)->lpVtbl -> NewOrder(This,txn_in,txn_out)

#define ITPCC_Payment(This,txn_in,txn_out) \
    (This)->lpVtbl -> Payment(This,txn_in,txn_out)

#define ITPCC_Delivery(This,txn_in,txn_out) \
    (This)->lpVtbl -> Delivery(This,txn_in,txn_out)

#define ITPCC_StockLevel(This,txn_in,txn_out) \
    (This)->lpVtbl -> StockLevel(This,txn_in,txn_out)

#define ITPCC_OrderStatus(This,txn_in,txn_out) \
    (This)->lpVtbl -> OrderStatus(This,txn_in,txn_out)

#define ITPCC_CallSetComplete(This) \
    (This)->lpVtbl -> CallSetComplete(This)

#endif /* COBJMACROS */

#endif /* C style interface */

```

```

HRESULT __stdcall ITPCC_NewOrder_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_NewOrder_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Payment_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_Payment_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_Delivery_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_Delivery_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_StockLevel_Proxy(
    ITPCC __RPC_FAR * This,
    /* [in] */ VARIANT txn_in,
    /* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_StockLevel_Stub(
    IRpcStubBuffer *This,
    IRpcChannelBuffer *_pRpcChannelBuffer,
    PRPC_MESSAGE _pRpcMessage,
    DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_OrderStatus_Proxy(

```

```

ITPCC __RPC_FAR * This,
/* [in] */ VARIANT txn_in,
/* [out] */ VARIANT __RPC_FAR *txn_out);

void __RPC_STUB ITPCC_OrderStatus_Stub(
IRpcStubBuffer *This,
IRpcChannelBuffer *_pRpcChannelBuffer,
PRPC_MESSAGE _pRpcMessage,
DWORD *_pdwStubPhase);

HRESULT __stdcall ITPCC_CallSetComplete_Proxy(
ITPCC __RPC_FAR * This);

void __RPC_STUB ITPCC_CallSetComplete_Stub(
IRpcStubBuffer *This,
IRpcChannelBuffer *_pRpcChannelBuffer,
PRPC_MESSAGE _pRpcMessage,
DWORD *_pdwStubPhase);

#endif /* __ITPCC_INTERFACE_DEFINED__ */

/* Additional Prototypes for ALL interfaces */

unsigned long __RPC_USER VARIANT_UserSize( unsigned long
__RPC_FAR *, unsigned long , VARIANT __RPC_FAR * );
unsigned char __RPC_FAR * __RPC_USER VARIANT_UserMarshal( unsigned long
__RPC_FAR *, unsigned char __RPC_FAR *, VARIANT __RPC_FAR * );
unsigned char __RPC_FAR * __RPC_USER VARIANT_UserUnmarshal( unsigned long
__RPC_FAR *, unsigned char __RPC_FAR *, VARIANT __RPC_FAR * );
void __RPC_USER VARIANT_UserFree( unsigned long
__RPC_FAR *, VARIANT __RPC_FAR * );

/* end of Additional Prototypes */

#ifdef __cplusplus
}
#endif

#endif

/* FILE: ITPCC.IDL
* Microsoft TPC-C Kit Ver. 4.20.000
* Copyright Microsoft, 1999
* All Rights Reserved
*
*/

```

```

* not yet audited
*
* PURPOSE: Defines the interface used by TPCC. This interface can be
implemented by C++ components.
*
* Change history:
* 4.20.000 - first version
*/

// Forward declare all types defined
interface ITPCC;
import "oaidl.idl";
import "ocidl.idl";

[
object,
oleautomation,
uuid(FEEE6AA2-84B1-11d2-BA47-00C04FBFE08B),
helpstring("ITPCC Interface"),
pointer_default(unique)
]
interface ITPCC : IUnknown
{
    HRESULT __stdcall NewOrder
        (
            [in] VARIANT txn_in,
            [out] VARIANT *txn_out
        );

    HRESULT __stdcall Payment
        (
            [in] VARIANT txn_in,
            [out] VARIANT *txn_out
        );

    HRESULT __stdcall Delivery
        (
            [in] VARIANT txn_in,
            [out] VARIANT *txn_out
        );

    HRESULT __stdcall StockLevel
        (
            [in] VARIANT txn_in,
            [out] VARIANT *txn_out
        );

    HRESULT __stdcall OrderStatus
        (
            [in] VARIANT txn_in,
            [out] VARIANT *txn_out
        );
}

```

```

        HRESULT STDMETHODCALLTYPE CallSetComplete
        (
        );

}; // interface ITPCC

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */

/* link this file in with the server and any clients */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
   Oicf (OptLev=i2), W1, Zp8, env=Win32 (32b run), ms_ext, c_ext
   error checks: allocation ref bounds_check enum stub_data
   VC __declspec() decoration level:
       __declspec(uuid()), __declspec(selectany), __declspec(novtable)
       DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING(  )

#if !defined(_M_IA64) && !defined(_M_AXP64)

#ifdef __cplusplus
extern "C"{
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
        DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

```

```

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
        const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

MIDL_DEFINE_GUID(IID,
IID_ITPCC,0xFEEE6AA2,0x84B1,0x11d2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* !defined(_M_IA64) && !defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the IIDs and CLSIDs */

/* link this file in with the server and any clients */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
   Oicf (OptLev=i2), W1, Zp8, env=Win64 (32b run,appending), ms_ext, c_ext,
   robust
   error checks: allocation ref bounds_check enum stub_data
   VC __declspec() decoration level:

```

```

        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#if defined(_M_IA64) || defined(_M_AXP64)

#ifdef __cplusplus
extern "C" {
#endif

#include <rpc.h>
#include <rpcndr.h>

#ifdef _MIDL_USE_GUIDDEF_

#ifndef INITGUID
#define INITGUID
#include <guiddef.h>
#undef INITGUID
#else
#include <guiddef.h>
#endif

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
        DEFINE_GUID(name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8)

#else // !_MIDL_USE_GUIDDEF_

#ifndef __IID_DEFINED__
#define __IID_DEFINED__

typedef struct _IID
{
    unsigned long x;
    unsigned short s1;
    unsigned short s2;
    unsigned char c[8];
} IID;

#endif // __IID_DEFINED__

#ifndef CLSID_DEFINED
#define CLSID_DEFINED
typedef IID CLSID;
#endif // CLSID_DEFINED

#define MIDL_DEFINE_GUID(type,name,l,w1,w2,b1,b2,b3,b4,b5,b6,b7,b8) \
        const type name = {l,w1,w2,{b1,b2,b3,b4,b5,b6,b7,b8}}

#endif !_MIDL_USE_GUIDDEF_

```

```

MIDL_DEFINE_GUID(IID,
IID_ITPCC,0xFEEE6AA2,0x84B1,0x11d2,0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B);

#undef MIDL_DEFINE_GUID

#ifdef __cplusplus
}
#endif

#endif /* defined(_M_IA64) || defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the proxy stub code */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000
*/
/* Compiler settings for .\src\tpcc_com_ps.idl:
Oicf (OptLev=i2), Wl, Zp8, env=Win32 (32b run), ms_ext, c_ext
error checks: allocation ref bounds_check enum stub_data
VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#if !defined(_M_IA64) && !defined(_M_AXP64)
#define USE_STUBLESS_PROXY

/* verify that the <rpcproxy.h> version is high enough to compile this
file*/
#ifdef __REDQ_RPCPROXY_H_VERSION__
#define __REQUIRED_RPCPROXY_H_VERSION__ 440
#endif

#include "rpcproxy.h"
#ifdef __RPCPROXY_H_VERSION__
#error this stub requires an updated version of <rpcproxy.h>
#endif // __RPCPROXY_H_VERSION__

#include "tpcc_com_ps.h"

#define TYPE_FORMAT_STRING_SIZE 997
#define PROC_FORMAT_STRING_SIZE 193

```

```

#define TRANSMIT_AS_TABLE_SIZE    0
#define WIRE_MARSHAL_TABLE_SIZE  1

typedef struct _MIDL_TYPE_FORMAT_STRING
{
    short          Pad;
    unsigned char  Format[ TYPE_FORMAT_STRING_SIZE ];
} MIDL_TYPE_FORMAT_STRING;

typedef struct _MIDL_PROC_FORMAT_STRING
{
    short          Pad;
    unsigned char  Format[ PROC_FORMAT_STRING_SIZE ];
} MIDL_PROC_FORMAT_STRING;

extern const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString;
extern const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString;

/* Standard interface: __MIDL_itf_tpcc_com_ps_0000, ver. 0.0,
   GUID={0x00000000,0x0000,0x0000,{0x00,0x00,0x00,0x00,0x00,0x00,0x00,0x00}}
*/

/* Object interface: IUnknown, ver. 0.0,
   GUID={0x00000000,0x0000,0x0000,{0xC0,0x00,0x00,0x00,0x00,0x00,0x00,0x46}}
*/

/* Object interface: ITPCC, ver. 0.0,
   GUID={0xFE6AA2,0x84B1,0x11d2,{0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B}}
*/

extern const MIDL_STUB_DESC Object_StubDesc;

extern const MIDL_SERVER_INFO ITPCC_ServerInfo;

#pragma code_seg(".orpc")
static const unsigned short ITPCC_FormatStringOffsetTable[] =
{
    0,
    34,
    68,
    102,
    136,
    170
};

static const MIDL_SERVER_INFO ITPCC_ServerInfo =
{

```

```

    &Object_StubDesc,
    0,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0,
    0,
    0
};

static const MIDL_STUBLESS_PROXY_INFO ITPCC_ProxyInfo =
{
    &Object_StubDesc,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0
};

CINTERFACE_PROXY_VTABLE(9) _ITPCCProxyVtbl =
{
    &ITPCC_ProxyInfo,
    &IID_ITPCC,
    IUnknown_QueryInterface_Proxy,
    IUnknown_AddRef_Proxy,
    IUnknown_Release_Proxy ,
    (void *)-1 /* ITPCC::NewOrder */ ,
    (void *)-1 /* ITPCC::Payment */ ,
    (void *)-1 /* ITPCC::Delivery */ ,
    (void *)-1 /* ITPCC::StockLevel */ ,
    (void *)-1 /* ITPCC::OrderStatus */ ,
    (void *)-1 /* ITPCC::CallSetComplete */
};

const CInterfaceStubVtbl _ITPCCStubVtbl =
{
    &IID_ITPCC,
    &ITPCC_ServerInfo,
    9,
    0, /* pure interpreted */
    CStdStubBuffer_METHODS
};

extern const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE ];

static const MIDL_STUB_DESC Object_StubDesc =
{
    0,
    NdrOleAllocate,
    NdrOleFree,
    0,

```

```

0,
0,
0,
0,
__MIDL_TypeFormatString.Format,
1, /* -error bounds_check flag */
0x20000, /* Ndr library version */
0,
0x5030118, /* MIDL Version 5.3.280 */
0,
UserMarshalRoutines,
0, /* notify & notify_flag routine table */
0x1, /* MIDL flag */
0, /* Reserved3 */
0, /* Reserved4 */
0 /* Reserved5 */
};

#pragma data_seg(".rdata")

static const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE ] =
{
    {
        VARIANT_UserSize
        ,VARIANT_UserMarshal
        ,VARIANT_UserUnmarshal
        ,VARIANT_UserFree
    }
};

#if !defined(__RPC_WIN32__)
#error Invalid build platform for this stub.
#endif

#if !(TARGET_IS_NT40_OR_LATER)
#error You need a Windows NT 4.0 or later to run this stub because it uses
these features:
#error -Oif or -Oicf, [wire_marshall] or [user_marshall] attribute.
#error However, your C/C++ compilation flags indicate you intend to run this
app on earlier systems.
#error This app will die there with the RPC_X_WRONG_STUB_VERSION error.
#endif

static const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString =
{
    0,
    {

```

```

/* Procedure NewOrder */

0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 2 */ NdrFcLong( 0x0 ), /* 0 */
/* 6 */ NdrFcShort( 0x3 ), /* 3 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 8 */ NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#else
NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#else
NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
/* 10 */ NdrFcShort( 0x0 ), /* 0 */
/* 12 */ NdrFcShort( 0x8 ), /* 8 */
/* 14 */ 0x7, /* Oi2 Flags: srv must size, clt must size, has
return, */
0x3, /* 3 */

/* Parameter txn_in */

/* 16 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 18 */ NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#else
NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 20 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Parameter txn_out */

/* 22 */ NdrFcShort( 0x4113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=16 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 24 */ NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else

```

```

        NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#else
        NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#else
        NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 26 */ NdrFcShort( 0x3da ), /* Type Offset=986 */

        /* Return value */

/* 28 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 30 */ NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
        NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#endif
#else
        NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
        NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 32 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

        /* Procedure Payment */

/* 34 */ 0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */
/* 36 */ NdrFcLong( 0x0 ), /* 0 */
/* 40 */ NdrFcShort( 0x4 ), /* 4 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 42 */ NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
        NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#else
        NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#else
        NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
/* 44 */ NdrFcShort( 0x0 ), /* 0 */
/* 46 */ NdrFcShort( 0x8 ), /* 8 */
/* 48 */ 0x7, /* Oi2 Flags: srv must size, clt must size, has
return, */
        0x3, /* 3 */

```

```

        /* Parameter txn_in */

/* 50 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 52 */ NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
        NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
        NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#else
        NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 54 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

        /* Parameter txn_out */

/* 56 */ NdrFcShort( 0x4113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=16 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 58 */ NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
        NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#endif
#else
        NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#else
        NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 60 */ NdrFcShort( 0x3da ), /* Type Offset=986 */

        /* Return value */

/* 62 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 64 */ NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
        NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#endif
#else
        NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
        NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#endif

```

```

        NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 66 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

/* Procedure Delivery */

/* 68 */ 0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */
/* 70 */ NdrFcLong( 0x0 ), /* 0 */
/* 74 */ NdrFcShort( 0x5 ), /* 5 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 76 */ NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
        NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#else
        NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#else
        NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
/* 78 */ NdrFcShort( 0x0 ), /* 0 */
/* 80 */ NdrFcShort( 0x8 ), /* 8 */
/* 82 */ 0x7, /* Oi2 Flags: srv must size, clt must size, has
return, */
        0x3, /* 3 */

/* Parameter txn_in */

/* 84 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 86 */ NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
        NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
        NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#else
        NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 88 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Parameter txn_out */

/* 90 */ NdrFcShort( 0x4113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=16 */

```

```

#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 92 */ NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
        NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#endif
#else
        NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#else
        NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 94 */ NdrFcShort( 0x3da ), /* Type Offset=986 */

/* Return value */

/* 96 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 98 */ NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
        NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#endif
#else
        NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
        NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 100 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

/* Procedure StockLevel */

/* 102 */ 0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */
/* 104 */ NdrFcLong( 0x0 ), /* 0 */
/* 108 */ NdrFcShort( 0x6 ), /* 6 */
#ifndef _ALPHA_
#ifndef _PPC_
#if !defined(_MIPS_)
/* 110 */ NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
        NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#else
        NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#else
        NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
#endif
#endif

```

```

/* 112 */ NdrFcShort( 0x0 ), /* 0 */
/* 114 */ NdrFcShort( 0x8 ), /* 8 */
/* 116 */ 0x7, /* Oi2 Flags: srv must size, clt must size, has
return, */
        0x3, /* 3 */

        /* Parameter txn_in */

/* 118 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 120 */ NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
        NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
        NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#else
        NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 122 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

        /* Parameter txn_out */

/* 124 */ NdrFcShort( 0x4113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=16 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 126 */ NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
        NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#endif
#else
        NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#else
        NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 128 */ NdrFcShort( 0x3da ), /* Type Offset=986 */

        /* Return value */

/* 130 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 132 */ NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
        NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */

```

```

#endif
#else
        NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
        NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 134 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

        /* Procedure OrderStatus */

/* 136 */ 0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */
/* 138 */ NdrFcLong( 0x0 ), /* 0 */
/* 142 */ NdrFcShort( 0x7 ), /* 7 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 144 */ NdrFcShort( 0x1c ), /* x86 Stack size/offset = 28 */
#else
        NdrFcShort( 0x20 ), /* MIPS Stack size/offset = 32 */
#endif
#endif
#else
        NdrFcShort( 0x20 ), /* PPC Stack size/offset = 32 */
#endif
#endif
        NdrFcShort( 0x28 ), /* Alpha Stack size/offset = 40 */
/* 146 */ NdrFcShort( 0x0 ), /* 0 */
/* 148 */ NdrFcShort( 0x8 ), /* 8 */
/* 150 */ 0x7, /* Oi2 Flags: srv must size, clt must size, has
return, */
        0x3, /* 3 */

        /* Parameter txn_in */

/* 152 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 154 */ NdrFcShort( 0x4 ), /* x86 Stack size/offset = 4 */
#else
        NdrFcShort( 0x8 ), /* MIPS Stack size/offset = 8 */
#endif
#endif
#else
        NdrFcShort( 0x8 ), /* PPC Stack size/offset = 8 */
#endif
#else
        NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 156 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

```

```

/* Parameter txn_out */

/* 158 */ NdrFcShort( 0x4113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=16 */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 160 */ NdrFcShort( 0x14 ), /* x86 Stack size/offset = 20 */
#else
NdrFcShort( 0x18 ), /* MIPS Stack size/offset = 24 */
#endif
#endif
#else
NdrFcShort( 0x18 ), /* PPC Stack size/offset = 24 */
#endif
#else
NdrFcShort( 0x18 ), /* Alpha Stack size/offset = 24 */
#endif
/* 162 */ NdrFcShort( 0x3da ), /* Type Offset=986 */

/* Return value */

/* 164 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
#ifdef _PPC_
#if !defined(_MIPS_)
/* 166 */ NdrFcShort( 0x18 ), /* x86 Stack size/offset = 24 */
#else
NdrFcShort( 0x1c ), /* MIPS Stack size/offset = 28 */
#endif
#endif
#else
NdrFcShort( 0x1c ), /* PPC Stack size/offset = 28 */
#endif
#else
NdrFcShort( 0x20 ), /* Alpha Stack size/offset = 32 */
#endif
/* 168 */ 0x8, /* FC_LONG */
0x0, /* 0 */

/* Procedure CallSetComplete */

/* 170 */ 0x33, /* FC_AUTO_HANDLE */
0x6c, /* Old Flags: object, Oi2 */
/* 172 */ NdrFcLong( 0x0 ), /* 0 */
/* 176 */ NdrFcShort( 0x8 ), /* 8 */
#ifdef _ALPHA_
/* 178 */ NdrFcShort( 0x8 ), /* x86, MIPS, PPC Stack size/offset = 8 */
#else
NdrFcShort( 0x10 ), /* Alpha Stack size/offset = 16 */
#endif
/* 180 */ NdrFcShort( 0x0 ), /* 0 */
/* 182 */ NdrFcShort( 0x8 ), /* 8 */
/* 184 */ 0x4, /* Oi2 Flags: has return, */

```

```

0x1, /* 1 */

/* Return value */

/* 186 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 188 */ NdrFcShort( 0x4 ), /* x86, MIPS, PPC Stack size/offset = 4 */
#else
NdrFcShort( 0x8 ), /* Alpha Stack size/offset = 8 */
#endif
/* 190 */ 0x8, /* FC_LONG */
0x0, /* 0 */

0x0
}
};

static const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString =
{
0,
{
NdrFcShort( 0x0 ), /* 0 */
/* 2 */
0x12, 0x0, /* FC_UP */
/* 4 */ NdrFcShort( 0x3b0 ), /* Offset= 944 (948) */
/* 6 */
0x2b, /* FC_NON_ENCAPSULATED_UNION */
0x9, /* FC_ULONG */
/* 8 */ 0x7, /* Corr desc: FC_USHORT */
0x0, /* */
/* 10 */ NdrFcShort( 0xffff8 ), /* -8 */
/* 12 */ NdrFcShort( 0x2 ), /* Offset= 2 (14) */
/* 14 */ NdrFcShort( 0x10 ), /* 16 */
/* 16 */ NdrFcShort( 0x2b ), /* 43 */
/* 18 */ NdrFcLong( 0x3 ), /* 3 */
/* 22 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 24 */ NdrFcLong( 0x11 ), /* 17 */
/* 28 */ NdrFcShort( 0x8001 ), /* Simple arm type: FC_BYTE */
/* 30 */ NdrFcLong( 0x2 ), /* 2 */
/* 34 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 36 */ NdrFcLong( 0x4 ), /* 4 */
/* 40 */ NdrFcShort( 0x800a ), /* Simple arm type: FC_FLOAT */
/* 42 */ NdrFcLong( 0x5 ), /* 5 */
/* 46 */ NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 48 */ NdrFcLong( 0xb ), /* 11 */
/* 52 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 54 */ NdrFcLong( 0xa ), /* 10 */
/* 58 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 60 */ NdrFcLong( 0x6 ), /* 6 */
/* 64 */ NdrFcShort( 0xd6 ), /* Offset= 214 (278) */
/* 66 */ NdrFcLong( 0x7 ), /* 7 */
/* 70 */ NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 72 */ NdrFcLong( 0x8 ), /* 8 */

```

```

/* 76 */ NdrFcShort( 0xd0 ), /* Offset= 208 (284) */
/* 78 */ NdrFcLong( 0xd ), /* 13 */
/* 82 */ NdrFcShort( 0xe2 ), /* Offset= 226 (308) */
/* 84 */ NdrFcLong( 0x9 ), /* 9 */
/* 88 */ NdrFcShort( 0xee ), /* Offset= 238 (326) */
/* 90 */ NdrFcLong( 0x2000 ), /* 8192 */
/* 94 */ NdrFcShort( 0xfa ), /* Offset= 250 (344) */
/* 96 */ NdrFcLong( 0x24 ), /* 36 */
/* 100 */ NdrFcShort( 0x308 ), /* Offset= 776 (876) */
/* 102 */ NdrFcLong( 0x4024 ), /* 16420 */
/* 106 */ NdrFcShort( 0x302 ), /* Offset= 770 (876) */
/* 108 */ NdrFcLong( 0x4011 ), /* 16401 */
/* 112 */ NdrFcShort( 0x300 ), /* Offset= 768 (880) */
/* 114 */ NdrFcLong( 0x4002 ), /* 16386 */
/* 118 */ NdrFcShort( 0x2fe ), /* Offset= 766 (884) */
/* 120 */ NdrFcLong( 0x4003 ), /* 16387 */
/* 124 */ NdrFcShort( 0x2fc ), /* Offset= 764 (888) */
/* 126 */ NdrFcLong( 0x4004 ), /* 16388 */
/* 130 */ NdrFcShort( 0x2fa ), /* Offset= 762 (892) */
/* 132 */ NdrFcLong( 0x4005 ), /* 16389 */
/* 136 */ NdrFcShort( 0x2f8 ), /* Offset= 760 (896) */
/* 138 */ NdrFcLong( 0x400b ), /* 16395 */
/* 142 */ NdrFcShort( 0x2e6 ), /* Offset= 742 (884) */
/* 144 */ NdrFcLong( 0x400a ), /* 16394 */
/* 148 */ NdrFcShort( 0x2e4 ), /* Offset= 740 (888) */
/* 150 */ NdrFcLong( 0x4006 ), /* 16390 */
/* 154 */ NdrFcShort( 0x2ea ), /* Offset= 746 (900) */
/* 156 */ NdrFcLong( 0x4007 ), /* 16391 */
/* 160 */ NdrFcShort( 0x2e0 ), /* Offset= 736 (896) */
/* 162 */ NdrFcLong( 0x4008 ), /* 16392 */
/* 166 */ NdrFcShort( 0x2e2 ), /* Offset= 738 (904) */
/* 168 */ NdrFcLong( 0x400d ), /* 16397 */
/* 172 */ NdrFcShort( 0x2e0 ), /* Offset= 736 (908) */
/* 174 */ NdrFcLong( 0x4009 ), /* 16393 */
/* 178 */ NdrFcShort( 0x2de ), /* Offset= 734 (912) */
/* 180 */ NdrFcLong( 0x6000 ), /* 24576 */
/* 184 */ NdrFcShort( 0x2dc ), /* Offset= 732 (916) */
/* 186 */ NdrFcLong( 0x400c ), /* 16396 */
/* 190 */ NdrFcShort( 0x2da ), /* Offset= 730 (920) */
/* 192 */ NdrFcLong( 0x10 ), /* 16 */
/* 196 */ NdrFcShort( 0x8002 ), /* Simple arm type: FC_CHAR */
/* 198 */ NdrFcLong( 0x12 ), /* 18 */
/* 202 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 204 */ NdrFcLong( 0x13 ), /* 19 */
/* 208 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 210 */ NdrFcLong( 0x16 ), /* 22 */
/* 214 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 216 */ NdrFcLong( 0x17 ), /* 23 */
/* 220 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 222 */ NdrFcLong( 0xe ), /* 14 */
/* 226 */ NdrFcShort( 0x2be ), /* Offset= 702 (928) */
/* 228 */ NdrFcLong( 0x400e ), /* 16398 */
/* 232 */ NdrFcShort( 0x2c4 ), /* Offset= 708 (940) */

```

```

/* 234 */ NdrFcLong( 0x4010 ), /* 16400 */
/* 238 */ NdrFcShort( 0x2c2 ), /* Offset= 706 (944) */
/* 240 */ NdrFcLong( 0x4012 ), /* 16402 */
/* 244 */ NdrFcShort( 0x280 ), /* Offset= 640 (884) */
/* 246 */ NdrFcLong( 0x4013 ), /* 16403 */
/* 250 */ NdrFcShort( 0x27e ), /* Offset= 638 (888) */
/* 252 */ NdrFcLong( 0x4016 ), /* 16406 */
/* 256 */ NdrFcShort( 0x278 ), /* Offset= 632 (888) */
/* 258 */ NdrFcLong( 0x4017 ), /* 16407 */
/* 262 */ NdrFcShort( 0x272 ), /* Offset= 626 (888) */
/* 264 */ NdrFcLong( 0x0 ), /* 0 */
/* 268 */ NdrFcShort( 0x0 ), /* Offset= 0 (268) */
/* 270 */ NdrFcLong( 0x1 ), /* 1 */
/* 274 */ NdrFcShort( 0x0 ), /* Offset= 0 (274) */
/* 276 */ NdrFcShort( 0xffffffff ), /* Offset= -1 (275) */
/* 278 */
        0x15, /* FC_STRUCT */
        0x7, /* 7 */
/* 280 */ NdrFcShort( 0x8 ), /* 8 */
/* 282 */ 0xb, /* FC_HYPER */
        0x5b, /* FC_END */
/* 284 */
        0x12, 0x0, /* FC_UP */
/* 286 */ NdrFcShort( 0xc ), /* Offset= 12 (298) */
/* 288 */
        0x1b, /* FC_CARRAY */
        0x1, /* 1 */
/* 290 */ NdrFcShort( 0x2 ), /* 2 */
/* 292 */ 0x9, /* Corr desc: FC_ULONG */
        0x0, /* */
/* 294 */ NdrFcShort( 0xfffc ), /* -4 */
/* 296 */ 0x6, /* FC_SHORT */
        0x5b, /* FC_END */
/* 298 */
        0x17, /* FC_CSTRUCT */
        0x3, /* 3 */
/* 300 */ NdrFcShort( 0x8 ), /* 8 */
/* 302 */ NdrFcShort( 0xffffffff2 ), /* Offset= -14 (288) */
/* 304 */ 0x8, /* FC_LONG */
        0x8, /* FC_LONG */
/* 306 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 308 */
        0x2f, /* FC_IP */
        0x5a, /* FC_CONSTANT_IID */
/* 310 */ NdrFcLong( 0x0 ), /* 0 */
/* 314 */ NdrFcShort( 0x0 ), /* 0 */
/* 316 */ NdrFcShort( 0x0 ), /* 0 */
/* 318 */ 0xc0, /* 192 */
        0x0, /* 0 */
/* 320 */ 0x0, /* 0 */
        0x0, /* 0 */
/* 322 */ 0x0, /* 0 */

```

```

/* 324 */ 0x0, /* 0 */
/* 326 */ 0x46, /* 70 */
/* 328 */ 0x2f, /* FC_IP */
/* 328 */ 0x5a, /* FC_CONSTANT_IID */
/* 328 */ NdrFcLong( 0x20400 ), /* 132096 */
/* 332 */ NdrFcShort( 0x0 ), /* 0 */
/* 334 */ NdrFcShort( 0x0 ), /* 0 */
/* 336 */ 0xc0, /* 192 */
/* 338 */ 0x0, /* 0 */
/* 340 */ 0x0, /* 0 */
/* 342 */ 0x0, /* 0 */
/* 344 */ 0x46, /* 70 */
/* 346 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 348 */ NdrFcShort( 0x2 ), /* Offset= 2 (348) */
/* 350 */ 0x12, 0x0, /* FC_UP */
/* 352 */ NdrFcShort( 0x1fc ), /* Offset= 508 (858) */
/* 354 */ 0x2a, /* FC_ENCAPSULATED_UNION */
/* 354 */ 0x49, /* 73 */
/* 356 */ NdrFcShort( 0x18 ), /* 24 */
/* 358 */ NdrFcShort( 0xa ), /* 10 */
/* 362 */ NdrFcLong( 0x8 ), /* 8 */
/* 364 */ NdrFcShort( 0x58 ), /* Offset= 88 (450) */
/* 366 */ NdrFcLong( 0xd ), /* 13 */
/* 368 */ NdrFcShort( 0x78 ), /* Offset= 120 (488) */
/* 370 */ NdrFcLong( 0x9 ), /* 9 */
/* 374 */ NdrFcShort( 0x94 ), /* Offset= 148 (522) */
/* 376 */ NdrFcLong( 0xc ), /* 12 */
/* 380 */ NdrFcShort( 0xbc ), /* Offset= 188 (568) */
/* 382 */ NdrFcLong( 0x24 ), /* 36 */
/* 386 */ NdrFcShort( 0x114 ), /* Offset= 276 (662) */
/* 388 */ NdrFcLong( 0x800d ), /* 32781 */
/* 392 */ NdrFcShort( 0x130 ), /* Offset= 304 (696) */
/* 394 */ NdrFcLong( 0x10 ), /* 16 */
/* 398 */ NdrFcShort( 0x148 ), /* Offset= 328 (726) */
/* 400 */ NdrFcLong( 0x2 ), /* 2 */
/* 404 */ NdrFcShort( 0x160 ), /* Offset= 352 (756) */
/* 406 */ NdrFcLong( 0x3 ), /* 3 */
/* 410 */ NdrFcShort( 0x178 ), /* Offset= 376 (786) */
/* 412 */ NdrFcLong( 0x14 ), /* 20 */
/* 416 */ NdrFcShort( 0x190 ), /* Offset= 400 (816) */
/* 418 */ NdrFcShort( 0xffffffff ), /* Offset= -1 (417) */
/* 420 */ 0x1b, /* FC_CARRAY */
/* 422 */ 0x3, /* 3 */
/* 422 */ NdrFcShort( 0x4 ), /* 4 */

```

```

/* 424 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 426 */ 0x0, /* */
/* 426 */ NdrFcShort( 0x0 ), /* 0 */
/* 428 */ 0x4b, /* FC_PP */
/* 428 */ 0x5c, /* FC_PAD */
/* 430 */ 0x48, /* FC_VARIABLE_REPEAT */
/* 430 */ 0x49, /* FC_FIXED_OFFSET */
/* 432 */ NdrFcShort( 0x4 ), /* 4 */
/* 434 */ NdrFcShort( 0x0 ), /* 0 */
/* 436 */ NdrFcShort( 0x1 ), /* 1 */
/* 438 */ NdrFcShort( 0x0 ), /* 0 */
/* 440 */ NdrFcShort( 0x0 ), /* 0 */
/* 442 */ 0x12, 0x0, /* FC_UP */
/* 444 */ NdrFcShort( 0xfffff6e ), /* Offset= -146 (298) */
/* 446 */ 0x5b, /* FC_END */
/* 448 */ 0x8, /* FC_LONG */
/* 448 */ 0x5c, /* FC_PAD */
/* 448 */ 0x5b, /* FC_END */
/* 450 */ 0x16, /* FC_PSTRUCT */
/* 450 */ 0x3, /* 3 */
/* 452 */ NdrFcShort( 0x8 ), /* 8 */
/* 454 */ 0x4b, /* FC_PP */
/* 454 */ 0x5c, /* FC_PAD */
/* 456 */ 0x46, /* FC_NO_REPEAT */
/* 456 */ 0x5c, /* FC_PAD */
/* 458 */ NdrFcShort( 0x4 ), /* 4 */
/* 460 */ NdrFcShort( 0x4 ), /* 4 */
/* 462 */ 0x11, 0x0, /* FC_RP */
/* 464 */ NdrFcShort( 0xfffffd4 ), /* Offset= -44 (420) */
/* 466 */ 0x5b, /* FC_END */
/* 468 */ 0x8, /* FC_LONG */
/* 468 */ 0x5b, /* FC_END */
/* 470 */ 0x21, /* FC_BOGUS_ARRAY */
/* 470 */ 0x3, /* 3 */
/* 472 */ NdrFcShort( 0x0 ), /* 0 */
/* 474 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 474 */ 0x0, /* */
/* 476 */ NdrFcShort( 0x0 ), /* 0 */
/* 478 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 482 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
/* 482 */ 0x0, /* 0 */
/* 484 */ NdrFcShort( 0xfffff50 ), /* Offset= -176 (308) */

```

```

/* 486 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 488 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x3,        /* 3 */
/* 490 */ NdrFcShort( 0x8 ), /* 8 */
/* 492 */ NdrFcShort( 0x0 ), /* 0 */
/* 494 */ NdrFcShort( 0x6 ), /* Offset= 6 (500) */
/* 496 */ 0x8,        /* FC_LONG */
          0x36,      /* FC_POINTER */
/* 498 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 500 */
          0x11, 0x0, /* FC_RP */
/* 502 */ NdrFcShort( 0xfffffe0 ), /* Offset= -32 (470) */
/* 504 */
          0x21,      /* FC_BOGUS_ARRAY */
          0x3,        /* 3 */
/* 506 */ NdrFcShort( 0x0 ), /* 0 */
/* 508 */ 0x19,      /* Corr desc: field pointer, FC_ULONG */
          0x0,        /* */
/* 510 */ NdrFcShort( 0x0 ), /* 0 */
/* 512 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 516 */ 0x4c,      /* FC_EMBEDDED_COMPLEX */
          0x0,        /* 0 */
/* 518 */ NdrFcShort( 0xfffff40 ), /* Offset= -192 (326) */
/* 520 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 522 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x3,        /* 3 */
/* 524 */ NdrFcShort( 0x8 ), /* 8 */
/* 526 */ NdrFcShort( 0x0 ), /* 0 */
/* 528 */ NdrFcShort( 0x6 ), /* Offset= 6 (534) */
/* 530 */ 0x8,        /* FC_LONG */
          0x36,      /* FC_POINTER */
/* 532 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 534 */
          0x11, 0x0, /* FC_RP */
/* 536 */ NdrFcShort( 0xfffffe0 ), /* Offset= -32 (504) */
/* 538 */
          0x1b,      /* FC_CARRAY */
          0x3,        /* 3 */
/* 540 */ NdrFcShort( 0x4 ), /* 4 */
/* 542 */ 0x19,      /* Corr desc: field pointer, FC_ULONG */
          0x0,        /* */
/* 544 */ NdrFcShort( 0x0 ), /* 0 */
/* 546 */
          0x4b,      /* FC_PP */
          0x5c,      /* FC_PAD */
/* 548 */
          0x48,      /* FC_VARIABLE_REPEAT */

```

```

          0x49,      /* FC_FIXED_OFFSET */
/* 550 */ NdrFcShort( 0x4 ), /* 4 */
/* 552 */ NdrFcShort( 0x0 ), /* 0 */
/* 554 */ NdrFcShort( 0x1 ), /* 1 */
/* 556 */ NdrFcShort( 0x0 ), /* 0 */
/* 558 */ NdrFcShort( 0x0 ), /* 0 */
/* 560 */ 0x12, 0x0, /* FC_UP */
/* 562 */ NdrFcShort( 0x182 ), /* Offset= 386 (948) */
/* 564 */
          0x5b,      /* FC_END */
          0x8,        /* FC_LONG */
/* 566 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 568 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x3,        /* 3 */
/* 570 */ NdrFcShort( 0x8 ), /* 8 */
/* 572 */ NdrFcShort( 0x0 ), /* 0 */
/* 574 */ NdrFcShort( 0x6 ), /* Offset= 6 (580) */
/* 576 */ 0x8,        /* FC_LONG */
          0x36,      /* FC_POINTER */
/* 578 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 580 */
          0x11, 0x0, /* FC_RP */
/* 582 */ NdrFcShort( 0xfffffd4 ), /* Offset= -44 (538) */
/* 584 */
          0x2f,      /* FC_IP */
          0x5a,      /* FC_CONSTANT_IID */
/* 586 */ NdrFcLong( 0x2f ), /* 47 */
/* 590 */ NdrFcShort( 0x0 ), /* 0 */
/* 592 */ NdrFcShort( 0x0 ), /* 0 */
/* 594 */ 0xc0,      /* 192 */
          0x0,        /* 0 */
/* 596 */ 0x0,      /* 0 */
          0x0,        /* 0 */
/* 598 */ 0x0,      /* 0 */
          0x0,        /* 0 */
/* 600 */ 0x0,      /* 0 */
          0x46,      /* 70 */
/* 602 */
          0x1b,      /* FC_CARRAY */
          0x0,        /* 0 */
/* 604 */ NdrFcShort( 0x1 ), /* 1 */
/* 606 */ 0x19,      /* Corr desc: field pointer, FC_ULONG */
          0x0,        /* */
/* 608 */ NdrFcShort( 0x4 ), /* 4 */
/* 610 */ 0x1,      /* FC_BYTE */
          0x5b,      /* FC_END */
/* 612 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x3,        /* 3 */

```

```

/* 614 */ NdrFcShort( 0x10 ), /* 16 */
/* 616 */ NdrFcShort( 0x0 ), /* 0 */
/* 618 */ NdrFcShort( 0xa ), /* Offset= 10 (628) */
/* 620 */ 0x8, /* FC_LONG */
        0x8, /* FC_LONG */
/* 622 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
        0x0, /* 0 */
/* 624 */ NdrFcShort( 0xffffffff8 ), /* Offset= -40 (584) */
/* 626 */ 0x36, /* FC_POINTER */
        0x5b, /* FC_END */
/* 628 */
        0x12, 0x0, /* FC_UP */
/* 630 */ NdrFcShort( 0xffffffffe4 ), /* Offset= -28 (602) */
/* 632 */
        0x1b, /* FC_CARRAY */
        0x3, /* 3 */
/* 634 */ NdrFcShort( 0x4 ), /* 4 */
/* 636 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
        0x0, /* */
/* 638 */ NdrFcShort( 0x0 ), /* 0 */
/* 640 */
        0x4b, /* FC_PP */
        0x5c, /* FC_PAD */
/* 642 */
        0x48, /* FC_VARIABLE_REPEAT */
        0x49, /* FC_FIXED_OFFSET */
/* 644 */ NdrFcShort( 0x4 ), /* 4 */
/* 646 */ NdrFcShort( 0x0 ), /* 0 */
/* 648 */ NdrFcShort( 0x1 ), /* 1 */
/* 650 */ NdrFcShort( 0x0 ), /* 0 */
/* 652 */ NdrFcShort( 0x0 ), /* 0 */
/* 654 */ 0x12, 0x0, /* FC_UP */
/* 656 */ NdrFcShort( 0xffffffffd4 ), /* Offset= -44 (612) */
/* 658 */
        0x5b, /* FC_END */
/* 660 */
        0x8, /* FC_LONG */
/* 660 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 662 */
        0x1a, /* FC_BOGUS_STRUCT */
        0x3, /* 3 */
/* 664 */ NdrFcShort( 0x8 ), /* 8 */
/* 666 */ NdrFcShort( 0x0 ), /* 0 */
/* 668 */ NdrFcShort( 0x6 ), /* Offset= 6 (674) */
/* 670 */ 0x8, /* FC_LONG */
        0x36, /* FC_POINTER */
/* 672 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 674 */
        0x11, 0x0, /* FC_RP */
/* 676 */ NdrFcShort( 0xffffffffd4 ), /* Offset= -44 (632) */
/* 678 */

```

```

        0x1d, /* FC_SMFARRAY */
        0x0, /* 0 */
/* 680 */ NdrFcShort( 0x8 ), /* 8 */
/* 682 */ 0x2, /* FC_CHAR */
        0x5b, /* FC_END */
/* 684 */
        0x15, /* FC_STRUCT */
        0x3, /* 3 */
/* 686 */ NdrFcShort( 0x10 ), /* 16 */
/* 688 */ 0x8, /* FC_LONG */
        0x6, /* FC_SHORT */
/* 690 */ 0x6, /* FC_SHORT */
        0x4c, /* FC_EMBEDDED_COMPLEX */
/* 692 */ 0x0, /* 0 */
        NdrFcShort( 0xffffffff1 ), /* Offset= -15 (678) */
        0x5b, /* FC_END */
/* 696 */
        0x1a, /* FC_BOGUS_STRUCT */
        0x3, /* 3 */
/* 698 */ NdrFcShort( 0x18 ), /* 24 */
/* 700 */ NdrFcShort( 0x0 ), /* 0 */
/* 702 */ NdrFcShort( 0xa ), /* Offset= 10 (712) */
/* 704 */ 0x8, /* FC_LONG */
        0x36, /* FC_POINTER */
/* 706 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
        0x0, /* 0 */
/* 708 */ NdrFcShort( 0xffffffffe8 ), /* Offset= -24 (684) */
/* 710 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 712 */
        0x11, 0x0, /* FC_RP */
/* 714 */ NdrFcShort( 0xffffffff0c ), /* Offset= -244 (470) */
/* 716 */
        0x1b, /* FC_CARRAY */
        0x0, /* 0 */
/* 718 */ NdrFcShort( 0x1 ), /* 1 */
/* 720 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
        0x0, /* */
/* 722 */ NdrFcShort( 0x0 ), /* 0 */
/* 724 */ 0x1, /* FC_BYTE */
        0x5b, /* FC_END */
/* 726 */
        0x16, /* FC_PSTRUCT */
        0x3, /* 3 */
/* 728 */ NdrFcShort( 0x8 ), /* 8 */
/* 730 */
        0x4b, /* FC_PP */
        0x5c, /* FC_PAD */
/* 732 */
        0x46, /* FC_NO_REPEAT */
        0x5c, /* FC_PAD */
/* 734 */ NdrFcShort( 0x4 ), /* 4 */
/* 736 */ NdrFcShort( 0x4 ), /* 4 */

```

```

/* 738 */ 0x12, 0x0, /* FC_UP */
/* 740 */ NdrFcShort( 0xffffffffe8 ), /* Offset= -24 (716) */
/* 742 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 744 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 746 */
    0x1b, /* FC_CARRAY */
    0x1, /* 1 */
/* 748 */ NdrFcShort( 0x2 ), /* 2 */
/* 750 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
    0x0, /* */
/* 752 */ NdrFcShort( 0x0 ), /* 0 */
/* 754 */ 0x6, /* FC_SHORT */
    0x5b, /* FC_END */
/* 756 */
    0x16, /* FC_PSTRUCT */
    0x3, /* 3 */
/* 758 */ NdrFcShort( 0x8 ), /* 8 */
/* 760 */
    0x4b, /* FC_PP */
    0x5c, /* FC_PAD */
/* 762 */
    0x46, /* FC_NO_REPEAT */
    0x5c, /* FC_PAD */
/* 764 */ NdrFcShort( 0x4 ), /* 4 */
/* 766 */ NdrFcShort( 0x4 ), /* 4 */
/* 768 */ 0x12, 0x0, /* FC_UP */
/* 770 */ NdrFcShort( 0xffffffffe8 ), /* Offset= -24 (746) */
/* 772 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 774 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 776 */
    0x1b, /* FC_CARRAY */
    0x3, /* 3 */
/* 778 */ NdrFcShort( 0x4 ), /* 4 */
/* 780 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
    0x0, /* */
/* 782 */ NdrFcShort( 0x0 ), /* 0 */
/* 784 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 786 */
    0x16, /* FC_PSTRUCT */
    0x3, /* 3 */
/* 788 */ NdrFcShort( 0x8 ), /* 8 */
/* 790 */
    0x4b, /* FC_PP */
    0x5c, /* FC_PAD */

```

```

/* 792 */
    0x46, /* FC_NO_REPEAT */
    0x5c, /* FC_PAD */
/* 794 */ NdrFcShort( 0x4 ), /* 4 */
/* 796 */ NdrFcShort( 0x4 ), /* 4 */
/* 798 */ 0x12, 0x0, /* FC_UP */
/* 800 */ NdrFcShort( 0xffffffffe8 ), /* Offset= -24 (776) */
/* 802 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 804 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 806 */
    0x1b, /* FC_CARRAY */
    0x7, /* 7 */
/* 808 */ NdrFcShort( 0x8 ), /* 8 */
/* 810 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
    0x0, /* */
/* 812 */ NdrFcShort( 0x0 ), /* 0 */
/* 814 */ 0xb, /* FC_HYPER */
    0x5b, /* FC_END */
/* 816 */
    0x16, /* FC_PSTRUCT */
    0x3, /* 3 */
/* 818 */ NdrFcShort( 0x8 ), /* 8 */
/* 820 */
    0x4b, /* FC_PP */
    0x5c, /* FC_PAD */
/* 822 */
    0x46, /* FC_NO_REPEAT */
    0x5c, /* FC_PAD */
/* 824 */ NdrFcShort( 0x4 ), /* 4 */
/* 826 */ NdrFcShort( 0x4 ), /* 4 */
/* 828 */ 0x12, 0x0, /* FC_UP */
/* 830 */ NdrFcShort( 0xffffffffe8 ), /* Offset= -24 (806) */
/* 832 */
    0x5b, /* FC_END */

    0x8, /* FC_LONG */
/* 834 */ 0x8, /* FC_LONG */
    0x5b, /* FC_END */
/* 836 */
    0x15, /* FC_STRUCT */
    0x3, /* 3 */
/* 838 */ NdrFcShort( 0x8 ), /* 8 */
/* 840 */ 0x8, /* FC_LONG */
    0x8, /* FC_LONG */
/* 842 */ 0x5c, /* FC_PAD */
    0x5b, /* FC_END */
/* 844 */
    0x1b, /* FC_CARRAY */
    0x3, /* 3 */

```

```

/* 846 */ NdrFcShort( 0x8 ), /* 8 */
/* 848 */ 0x7, /* Corr desc: FC_USHORT */
          0x0, /* */
/* 850 */ NdrFcShort( 0xffd8 ), /* -40 */
/* 852 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
          0x0, /* 0 */
/* 854 */ NdrFcShort( 0xfffffee ), /* Offset= -18 (836) */
/* 856 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 858 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x3, /* 3 */
/* 860 */ NdrFcShort( 0x28 ), /* 40 */
/* 862 */ NdrFcShort( 0xfffffee ), /* Offset= -18 (844) */
/* 864 */ NdrFcShort( 0x0 ), /* Offset= 0 (864) */
/* 866 */ 0x6, /* FC_SHORT */
          0x6, /* FC_SHORT */
/* 868 */ 0x38, /* FC_ALIGNM4 */
          0x8, /* FC_LONG */
/* 870 */ 0x8, /* FC_LONG */
          0x4c, /* FC_EMBEDDED_COMPLEX */
/* 872 */ 0x0, /* 0 */
          NdrFcShort( 0xfffffd7 ), /* Offset= -521 (352) */
          0x5b, /* FC_END */
/* 876 */
          0x12, 0x0, /* FC_UP */
/* 878 */ NdrFcShort( 0xfffffef6 ), /* Offset= -266 (612) */
/* 880 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 882 */ 0x1, /* FC_BYTE */
          0x5c, /* FC_PAD */
/* 884 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 886 */ 0x6, /* FC_SHORT */
          0x5c, /* FC_PAD */
/* 888 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 890 */ 0x8, /* FC_LONG */
          0x5c, /* FC_PAD */
/* 892 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 894 */ 0xa, /* FC_FLOAT */
          0x5c, /* FC_PAD */
/* 896 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 898 */ 0xc, /* FC_DOUBLE */
          0x5c, /* FC_PAD */
/* 900 */
          0x12, 0x0, /* FC_UP */
/* 902 */ NdrFcShort( 0xfffffd90 ), /* Offset= -624 (278) */
/* 904 */
          0x12, 0x10, /* FC_UP [pointer_deref] */
/* 906 */ NdrFcShort( 0xfffffd92 ), /* Offset= -622 (284) */

```

```

/* 908 */
          0x12, 0x10, /* FC_UP [pointer_deref] */
/* 910 */ NdrFcShort( 0xfffffda6 ), /* Offset= -602 (308) */
/* 912 */
          0x12, 0x10, /* FC_UP [pointer_deref] */
/* 914 */ NdrFcShort( 0xfffffdb4 ), /* Offset= -588 (326) */
/* 916 */
          0x12, 0x10, /* FC_UP [pointer_deref] */
/* 918 */ NdrFcShort( 0xfffffdc2 ), /* Offset= -574 (344) */
/* 920 */
          0x12, 0x10, /* FC_UP [pointer_deref] */
/* 922 */ NdrFcShort( 0x2 ), /* Offset= 2 (924) */
/* 924 */
          0x12, 0x0, /* FC_UP */
/* 926 */ NdrFcShort( 0x16 ), /* Offset= 22 (948) */
/* 928 */
          0x15, /* FC_STRUCT */
          0x7, /* 7 */
/* 930 */ NdrFcShort( 0x10 ), /* 16 */
/* 932 */ 0x6, /* FC_SHORT */
          0x1, /* FC_BYTE */
/* 934 */ 0x1, /* FC_BYTE */
          0x38, /* FC_ALIGNM4 */
/* 936 */ 0x8, /* FC_LONG */
          0x39, /* FC_ALIGNM8 */
/* 938 */ 0xb, /* FC_HYPER */
          0x5b, /* FC_END */
/* 940 */
          0x12, 0x0, /* FC_UP */
/* 942 */ NdrFcShort( 0xfffffff2 ), /* Offset= -14 (928) */
/* 944 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 946 */ 0x2, /* FC_CHAR */
          0x5c, /* FC_PAD */
/* 948 */
          0x1a, /* FC_BOGUS_STRUCT */
          0x7, /* 7 */
/* 950 */ NdrFcShort( 0x20 ), /* 32 */
/* 952 */ NdrFcShort( 0x0 ), /* 0 */
/* 954 */ NdrFcShort( 0x0 ), /* Offset= 0 (954) */
/* 956 */ 0x8, /* FC_LONG */
          0x8, /* FC_LONG */
/* 958 */ 0x6, /* FC_SHORT */
          0x6, /* FC_SHORT */
/* 960 */ 0x6, /* FC_SHORT */
          0x6, /* FC_SHORT */
/* 962 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
          0x0, /* 0 */
/* 964 */ NdrFcShort( 0xfffffc42 ), /* Offset= -958 (6) */
/* 966 */ 0x5c, /* FC_PAD */
          0x5b, /* FC_END */
/* 968 */ 0xb4, /* FC_USER_MARSHAL */
          0x83, /* 131 */

```

```

/* 970 */ NdrFcShort( 0x0 ), /* 0 */
/* 972 */ NdrFcShort( 0x10 ), /* 16 */
/* 974 */ NdrFcShort( 0x0 ), /* 0 */
/* 976 */ NdrFcShort( 0xfffffc32 ), /* Offset= -974 (2) */
/* 978 */
    0x11, 0x4, /* FC_RP [allocated_on_stack] */
/* 980 */ NdrFcShort( 0x6 ), /* Offset= 6 (986) */
/* 982 */
    0x13, 0x0, /* FC_OP */
/* 984 */ NdrFcShort( 0xfffffcdc ), /* Offset= -36 (948) */
/* 986 */ 0xb4, /* FC_USER_MARSHAL */
    0x83, /* 131 */
/* 988 */ NdrFcShort( 0x0 ), /* 0 */
/* 990 */ NdrFcShort( 0x10 ), /* 16 */
/* 992 */ NdrFcShort( 0x0 ), /* 0 */
/* 994 */ NdrFcShort( 0xfffffff4 ), /* Offset= -12 (982) */

    0x0
}
};

const CInterfaceProxyVtbl * _tpcc_com_ps_ProxyVtblList[] =
{
    ( CInterfaceProxyVtbl *) &_ITPCCProxyVtbl,
    0
};

const CInterfaceStubVtbl * _tpcc_com_ps_StubVtblList[] =
{
    ( CInterfaceStubVtbl *) &_ITPCCStubVtbl,
    0
};

PCInterfaceName const _tpcc_com_ps_InterfaceNamesList[] =
{
    "ITPCC",
    0
};

#define _tpcc_com_ps_CHECK_IID(n) IID_GENERIC_CHECK_IID( _tpcc_com_ps,
pIID, n)

int __stdcall _tpcc_com_ps_IID_Lookup( const IID * pIID, int * pIndex )
{
    if(!_tpcc_com_ps_CHECK_IID(0))
    {
        *pIndex = 0;
        return 1;
    }

    return 0;
}

```

```

}

const ExtendedProxyFileInfo tpcc_com_ps_ProxyFileInfo =
{
    (PCInterfaceProxyVtblList *) &_tpcc_com_ps_ProxyVtblList,
    (PCInterfaceStubVtblList *) &_tpcc_com_ps_StubVtblList,
    (const PCInterfaceName *) &_tpcc_com_ps_InterfaceNamesList,
    0, // no delegation
    &_tpcc_com_ps_IID_Lookup,
    1,
    2,
    0, /* table of [async_uuid] interfaces */
    0, /* Filler1 */
    0, /* Filler2 */
    0 /* Filler3 */
};

#endif /* !defined(_M_IA64) && !defined(_M_AXP64)*/

#pragma warning( disable: 4049 ) /* more than 64k source lines */

/* this ALWAYS GENERATED file contains the proxy stub code */

/* File created by MIDL compiler version 5.03.0280 */
/* at Sat Apr 08 16:40:10 2000 */
/*
/* Compiler settings for .\src\tpcc_com_ps.idl:
    Oicf (OptLev=i2), Wl, Zp8, env=Win64 (32b run,appending), ms_ext, c_ext,
robust
    error checks: allocation ref bounds_check enum stub_data
    VC __declspec() decoration level:
        __declspec(uuid()), __declspec(selectany), __declspec(novtable)
        DECLSPEC_UUID(), MIDL_INTERFACE()
*/
//@@MIDL_FILE_HEADING( )

#ifdef _M_IA64 || defined(_M_AXP64)
#define USE_STUBLESS_PROXY

/* verify that the <rpcproxy.h> version is high enough to compile this
file*/
#ifndef __REDQ_RPCPROXY_H_VERSION__
#define __REQUIRED_RPCPROXY_H_VERSION__ 475
#endif

#include "rpcproxy.h"
#ifndef __RPCPROXY_H_VERSION__
#error this stub requires an updated version of <rpcproxy.h>

```

```

#endif // __RPCPROXY_H_VERSION__

#include "tpcc_com_ps.h"

#define TYPE_FORMAT_STRING_SIZE 979
#define PROC_FORMAT_STRING_SIZE 253
#define TRANSMIT_AS_TABLE_SIZE 0
#define WIRE_MARSHAL_TABLE_SIZE 1

typedef struct _MIDL_TYPE_FORMAT_STRING
{
    short          Pad;
    unsigned char  Format[ TYPE_FORMAT_STRING_SIZE ];
} MIDL_TYPE_FORMAT_STRING;

typedef struct _MIDL_PROC_FORMAT_STRING
{
    short          Pad;
    unsigned char  Format[ PROC_FORMAT_STRING_SIZE ];
} MIDL_PROC_FORMAT_STRING;

extern const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString;
extern const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString;

/* Standard interface: __MIDL_itf_tpcc_com_ps_0000, ver. 0.0,
   GUID={0x00000000,0x0000,0x0000,{0x00,0x00,0x00,0x00,0x00,0x00,0x00,0x00}}
*/

/* Object interface: IUnknown, ver. 0.0,
   GUID={0x00000000,0x0000,0x0000,{0xC0,0x00,0x00,0x00,0x00,0x00,0x00,0x46}}
*/

/* Object interface: ITPCC, ver. 0.0,
   GUID={0xFEEE6AA2,0x84B1,0x11d2,{0xBA,0x47,0x00,0xC0,0x4F,0xBF,0xE0,0x8B}}
*/

extern const MIDL_STUB_DESC Object_StubDesc;

extern const MIDL_SERVER_INFO ITPCC_ServerInfo;

#pragma code_seg(".orpc")
static const unsigned short ITPCC_FormatStringOffsetTable[] =
{
    0,
    44,
    88,
    132,
    176,
    220
};

static const MIDL_SERVER_INFO ITPCC_ServerInfo =
{
    &Object_StubDesc,
    0,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0,
    0,
    0
};

static const MIDL_STUBLESS_PROXY_INFO ITPCC_ProxyInfo =
{
    &Object_StubDesc,
    __MIDL_ProcFormatString.Format,
    &ITPCC_FormatStringOffsetTable[-3],
    0,
    0,
    0
};

CINTERFACE_PROXY_VTABLE(9) _ITPCCProxyVtbl =
{
    &ITPCC_ProxyInfo,
    &IID_ITPCC,
    IUnknown_QueryInterface_Proxy,
    IUnknown_AddRef_Proxy,
    IUnknown_Release_Proxy ,
    (void *)-1 /* ITPCC::NewOrder */ ,
    (void *)-1 /* ITPCC::Payment */ ,
    (void *)-1 /* ITPCC::Delivery */ ,
    (void *)-1 /* ITPCC::StockLevel */ ,
    (void *)-1 /* ITPCC::OrderStatus */ ,
    (void *)-1 /* ITPCC::CallSetComplete */
};

const CInterfaceStubVtbl _ITPCCStubVtbl =
{
    &IID_ITPCC,
    &ITPCC_ServerInfo,
    9,
    0, /* pure interpreted */
    CStdStubBuffer_METHODS
};

extern const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE ];

```

```

static const MIDL_STUB_DESC Object_StubDesc =
{
    0,
    NdrOleAllocate,
    NdrOleFree,
    0,
    0,
    0,
    0,
    0,
    0,
    __MIDL_TypeFormatString.Format,
    1, /* -error bounds_check flag */
    0x50002, /* Ndr library version */
    0,
    0x5030118, /* MIDL Version 5.3.280 */
    0,
    UserMarshalRoutines,
    0, /* notify & notify_flag routine table */
    0x1, /* MIDL flag */
    0, /* Reserved3 */
    0, /* Reserved4 */
    0 /* Reserved5 */
};

#pragma data_seg(".rdata")

static const USER_MARSHAL_ROUTINE_QUADRUPLE UserMarshalRoutines[
WIRE_MARSHAL_TABLE_SIZE ] =
{
    {
        VARIANT_UserSize
        ,VARIANT_UserMarshal
        ,VARIANT_UserUnmarshal
        ,VARIANT_UserFree
    }
};

#if !defined(__RPC_WIN64__)
#error Invalid build platform for this stub.
#endif

static const MIDL_PROC_FORMAT_STRING __MIDL_ProcFormatString =
{
    0,
    {
        /* Procedure NewOrder */

        0x33, /* FC_AUTO_HANDLE */

```

```

        0x6c, /* Old Flags: object, Oi2 */
/* 2 */ NdrFcLong( 0x0 ), /* 0 */
/* 6 */ NdrFcShort( 0x3 ), /* 3 */
#ifdef _ALPHA_
/* 8 */ NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
        NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 10 */ NdrFcShort( 0x0 ), /* 0 */
/* 12 */ NdrFcShort( 0x8 ), /* 8 */
/* 14 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has
return, has ext, */
        0x3, /* 3 */
/* 16 */ 0xa, /* 10 */
        0x7, /* Ext Flags: new corr desc, clt corr check, srv
corr check, */
/* 18 */ NdrFcShort( 0x20 ), /* 32 */
/* 20 */ NdrFcShort( 0x20 ), /* 32 */
/* 22 */ NdrFcShort( 0x0 ), /* 0 */
/* 24 */ NdrFcShort( 0x0 ), /* 0 */

        /* Parameter txn_in */

/* 26 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
/* 28 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
        NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 30 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

        /* Parameter txn_out */

/* 32 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 34 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
        NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 36 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

        /* Return value */

/* 38 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 40 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
        NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 42 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

```

```

/* Procedure Payment */

/* 44 */ 0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */
/* 46 */ NdrFcLong( 0x0 ), /* 0 */
/* 50 */ NdrFcShort( 0x4 ), /* 4 */
#ifdef _ALPHA_
/* 52 */ NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
        NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 54 */ NdrFcShort( 0x0 ), /* 0 */
/* 56 */ NdrFcShort( 0x8 ), /* 8 */
/* 58 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has
return, has ext, */
        0x3, /* 3 */
/* 60 */ 0xa, /* 10 */
        0x7, /* Ext Flags: new corr desc, clt corr check, srv
corr check, */
/* 62 */ NdrFcShort( 0x20 ), /* 32 */
/* 64 */ NdrFcShort( 0x20 ), /* 32 */
/* 66 */ NdrFcShort( 0x0 ), /* 0 */
/* 68 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 70 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
/* 72 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
        NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 74 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 76 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 78 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
        NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 80 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

/* 82 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 84 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else

```

```

        NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 86 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

/* Procedure Delivery */

/* 88 */ 0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */
/* 90 */ NdrFcLong( 0x0 ), /* 0 */
/* 94 */ NdrFcShort( 0x5 ), /* 5 */
#ifdef _ALPHA_
/* 96 */ NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
        NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 98 */ NdrFcShort( 0x0 ), /* 0 */
/* 100 */ NdrFcShort( 0x8 ), /* 8 */
/* 102 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has
return, has ext, */
        0x3, /* 3 */
/* 104 */ 0xa, /* 10 */
        0x7, /* Ext Flags: new corr desc, clt corr check, srv
corr check, */
/* 106 */ NdrFcShort( 0x20 ), /* 32 */
/* 108 */ NdrFcShort( 0x20 ), /* 32 */
/* 110 */ NdrFcShort( 0x0 ), /* 0 */
/* 112 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 114 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
/* 116 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
        NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 118 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 120 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 122 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
        NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 124 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

```

```

/* 126 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 128 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
    NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 130 */ 0x8, /* FC_LONG */
    0x0, /* 0 */

/* Procedure StockLevel */

/* 132 */ 0x33, /* FC_AUTO_HANDLE */
    0x6c, /* Old Flags: object, Oi2 */
/* 134 */ NdrFcLong( 0x0 ), /* 0 */
/* 138 */ NdrFcShort( 0x6 ), /* 6 */
#ifdef _ALPHA_
/* 140 */ NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
    NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 142 */ NdrFcShort( 0x0 ), /* 0 */
/* 144 */ NdrFcShort( 0x8 ), /* 8 */
/* 146 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has
return, has ext, */
    0x3, /* 3 */
/* 148 */ 0xa, /* 10 */
    0x7, /* Ext Flags: new corr desc, clt corr check, srv
corr check, */
/* 150 */ NdrFcShort( 0x20 ), /* 32 */
/* 152 */ NdrFcShort( 0x20 ), /* 32 */
/* 154 */ NdrFcShort( 0x0 ), /* 0 */
/* 156 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 158 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
/* 160 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
    NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 162 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 164 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=24 */
#ifdef _ALPHA_
/* 166 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
    NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif

```

```

/* 168 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

/* Return value */

/* 170 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 172 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
    NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 174 */ 0x8, /* FC_LONG */
    0x0, /* 0 */

/* Procedure OrderStatus */

/* 176 */ 0x33, /* FC_AUTO_HANDLE */
    0x6c, /* Old Flags: object, Oi2 */
/* 178 */ NdrFcLong( 0x0 ), /* 0 */
/* 182 */ NdrFcShort( 0x7 ), /* 7 */
#ifdef _ALPHA_
/* 184 */ NdrFcShort( 0x38 ), /* ia64 Stack size/offset = 56 */
#else
    NdrFcShort( 0x30 ), /* axp64 Stack size/offset = 48 */
#endif
/* 186 */ NdrFcShort( 0x0 ), /* 0 */
/* 188 */ NdrFcShort( 0x8 ), /* 8 */
/* 190 */ 0x47, /* Oi2 Flags: srv must size, clt must size, has
return, has ext, */
    0x3, /* 3 */
/* 192 */ 0xa, /* 10 */
    0x7, /* Ext Flags: new corr desc, clt corr check, srv
corr check, */
/* 194 */ NdrFcShort( 0x20 ), /* 32 */
/* 196 */ NdrFcShort( 0x20 ), /* 32 */
/* 198 */ NdrFcShort( 0x0 ), /* 0 */
/* 200 */ NdrFcShort( 0x0 ), /* 0 */

/* Parameter txn_in */

/* 202 */ NdrFcShort( 0x8b ), /* Flags: must size, must free, in, by val,
*/
#ifdef _ALPHA_
/* 204 */ NdrFcShort( 0x10 ), /* ia64 Stack size/offset = 16 */
#else
    NdrFcShort( 0x8 ), /* axp64 Stack size/offset = 8 */
#endif
/* 206 */ NdrFcShort( 0x3b6 ), /* Type Offset=950 */

/* Parameter txn_out */

/* 208 */ NdrFcShort( 0x6113 ), /* Flags: must size, must free, out,
simple ref, srv alloc size=24 */
#ifdef _ALPHA_

```

```

/* 210 */ NdrFcShort( 0x28 ), /* ia64 Stack size/offset = 40 */
#else
        NdrFcShort( 0x20 ), /* axp64 Stack size/offset = 32 */
#endif
/* 212 */ NdrFcShort( 0x3c8 ), /* Type Offset=968 */

        /* Return value */

/* 214 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
#ifdef _ALPHA_
/* 216 */ NdrFcShort( 0x30 ), /* ia64 Stack size/offset = 48 */
#else
        NdrFcShort( 0x28 ), /* axp64 Stack size/offset = 40 */
#endif
/* 218 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

        /* Procedure CallSetComplete */

/* 220 */ 0x33, /* FC_AUTO_HANDLE */
        0x6c, /* Old Flags: object, Oi2 */
/* 222 */ NdrFcLong( 0x0 ), /* 0 */
/* 226 */ NdrFcShort( 0x8 ), /* 8 */
/* 228 */ NdrFcShort( 0x10 ), /* ia64, axp64 Stack size/offset = 16 */
/* 230 */ NdrFcShort( 0x0 ), /* 0 */
/* 232 */ NdrFcShort( 0x8 ), /* 8 */
/* 234 */ 0x44, /* Oi2 Flags: has return, has ext, */
        0x1, /* 1 */
/* 236 */ 0xa, /* 10 */
        0x1, /* Ext Flags: new corr desc, */
/* 238 */ NdrFcShort( 0x0 ), /* 0 */
/* 240 */ NdrFcShort( 0x0 ), /* 0 */
/* 242 */ NdrFcShort( 0x0 ), /* 0 */
/* 244 */ NdrFcShort( 0x0 ), /* 0 */

        /* Return value */

/* 246 */ NdrFcShort( 0x70 ), /* Flags: out, return, base type, */
/* 248 */ NdrFcShort( 0x8 ), /* ia64, axp64 Stack size/offset = 8 */
/* 250 */ 0x8, /* FC_LONG */
        0x0, /* 0 */

        0x0
    };

static const MIDL_TYPE_FORMAT_STRING __MIDL_TypeFormatString =
{
    0,
    {
        NdrFcShort( 0x0 ), /* 0 */
/* 2 */
        0x12, 0x0, /* FC_UP */

```

```

/* 4 */ NdrFcShort( 0x39e ), /* Offset= 926 (930) */
/* 6 */
        0x2b, /* FC_NON_ENCAPSULATED_UNION */
        0x9, /* FC_ULONG */
/* 8 */ 0x7, /* Corr desc: FC_USHORT */
        0x0, /* */
/* 10 */ NdrFcShort( 0xffff8 ), /* -8 */
/* 12 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 14 */ NdrFcShort( 0x2 ), /* Offset= 2 (16) */
/* 16 */ NdrFcShort( 0x10 ), /* 16 */
/* 18 */ NdrFcShort( 0x2b ), /* 43 */
/* 20 */ NdrFcLong( 0x3 ), /* 3 */
/* 24 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 26 */ NdrFcLong( 0x11 ), /* 17 */
/* 30 */ NdrFcShort( 0x8001 ), /* Simple arm type: FC_BYTE */
/* 32 */ NdrFcLong( 0x2 ), /* 2 */
/* 36 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 38 */ NdrFcLong( 0x4 ), /* 4 */
/* 42 */ NdrFcShort( 0x800a ), /* Simple arm type: FC_FLOAT */
/* 44 */ NdrFcLong( 0x5 ), /* 5 */
/* 48 */ NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 50 */ NdrFcLong( 0xb ), /* 11 */
/* 54 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 56 */ NdrFcLong( 0xa ), /* 10 */
/* 60 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 62 */ NdrFcLong( 0x6 ), /* 6 */
/* 66 */ NdrFcShort( 0xd6 ), /* Offset= 214 (280) */
/* 68 */ NdrFcLong( 0x7 ), /* 7 */
/* 72 */ NdrFcShort( 0x800c ), /* Simple arm type: FC_DOUBLE */
/* 74 */ NdrFcLong( 0x8 ), /* 8 */
/* 78 */ NdrFcShort( 0xd0 ), /* Offset= 208 (286) */
/* 80 */ NdrFcLong( 0xd ), /* 13 */
/* 84 */ NdrFcShort( 0xe4 ), /* Offset= 228 (312) */
/* 86 */ NdrFcLong( 0x9 ), /* 9 */
/* 90 */ NdrFcShort( 0xf0 ), /* Offset= 240 (330) */
/* 92 */ NdrFcLong( 0x2000 ), /* 8192 */
/* 96 */ NdrFcShort( 0xfc ), /* Offset= 252 (348) */
/* 98 */ NdrFcLong( 0x24 ), /* 36 */
/* 102 */ NdrFcShort( 0x2f4 ), /* Offset= 756 (858) */
/* 104 */ NdrFcLong( 0x4024 ), /* 16420 */
/* 108 */ NdrFcShort( 0x2ee ), /* Offset= 750 (858) */
/* 110 */ NdrFcLong( 0x4011 ), /* 16401 */
/* 114 */ NdrFcShort( 0x2ec ), /* Offset= 748 (862) */
/* 116 */ NdrFcLong( 0x4002 ), /* 16386 */
/* 120 */ NdrFcShort( 0x2ea ), /* Offset= 746 (866) */
/* 122 */ NdrFcLong( 0x4003 ), /* 16387 */
/* 126 */ NdrFcShort( 0x2e8 ), /* Offset= 744 (870) */
/* 128 */ NdrFcLong( 0x4004 ), /* 16388 */
/* 132 */ NdrFcShort( 0x2e6 ), /* Offset= 742 (874) */
/* 134 */ NdrFcLong( 0x4005 ), /* 16389 */
/* 138 */ NdrFcShort( 0x2e4 ), /* Offset= 740 (878) */
/* 140 */ NdrFcLong( 0x400b ), /* 16395 */
/* 144 */ NdrFcShort( 0x2d2 ), /* Offset= 722 (866) */

```

```

/* 146 */ NdrFcLong( 0x400a ), /* 16394 */
/* 150 */ NdrFcShort( 0x2d0 ), /* Offset= 720 (870) */
/* 152 */ NdrFcLong( 0x4006 ), /* 16390 */
/* 156 */ NdrFcShort( 0x2d6 ), /* Offset= 726 (882) */
/* 158 */ NdrFcLong( 0x4007 ), /* 16391 */
/* 162 */ NdrFcShort( 0x2cc ), /* Offset= 716 (878) */
/* 164 */ NdrFcLong( 0x4008 ), /* 16392 */
/* 168 */ NdrFcShort( 0x2ce ), /* Offset= 718 (886) */
/* 170 */ NdrFcLong( 0x400d ), /* 16397 */
/* 174 */ NdrFcShort( 0x2cc ), /* Offset= 716 (890) */
/* 176 */ NdrFcLong( 0x4009 ), /* 16393 */
/* 180 */ NdrFcShort( 0x2ca ), /* Offset= 714 (894) */
/* 182 */ NdrFcLong( 0x6000 ), /* 24576 */
/* 186 */ NdrFcShort( 0x2c8 ), /* Offset= 712 (898) */
/* 188 */ NdrFcLong( 0x400c ), /* 16396 */
/* 192 */ NdrFcShort( 0x2c6 ), /* Offset= 710 (902) */
/* 194 */ NdrFcLong( 0x10 ), /* 16 */
/* 198 */ NdrFcShort( 0x8002 ), /* Simple arm type: FC_CHAR */
/* 200 */ NdrFcLong( 0x12 ), /* 18 */
/* 204 */ NdrFcShort( 0x8006 ), /* Simple arm type: FC_SHORT */
/* 206 */ NdrFcLong( 0x13 ), /* 19 */
/* 210 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 212 */ NdrFcLong( 0x16 ), /* 22 */
/* 216 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 218 */ NdrFcLong( 0x17 ), /* 23 */
/* 222 */ NdrFcShort( 0x8008 ), /* Simple arm type: FC_LONG */
/* 224 */ NdrFcLong( 0xe ), /* 14 */
/* 228 */ NdrFcShort( 0x2aa ), /* Offset= 682 (910) */
/* 230 */ NdrFcLong( 0x400e ), /* 16398 */
/* 234 */ NdrFcShort( 0x2b0 ), /* Offset= 688 (922) */
/* 236 */ NdrFcLong( 0x4010 ), /* 16400 */
/* 240 */ NdrFcShort( 0x2ae ), /* Offset= 686 (926) */
/* 242 */ NdrFcLong( 0x4012 ), /* 16402 */
/* 246 */ NdrFcShort( 0x26c ), /* Offset= 620 (866) */
/* 248 */ NdrFcLong( 0x4013 ), /* 16403 */
/* 252 */ NdrFcShort( 0x26a ), /* Offset= 618 (870) */
/* 254 */ NdrFcLong( 0x4016 ), /* 16406 */
/* 258 */ NdrFcShort( 0x264 ), /* Offset= 612 (870) */
/* 260 */ NdrFcLong( 0x4017 ), /* 16407 */
/* 264 */ NdrFcShort( 0x25e ), /* Offset= 606 (870) */
/* 266 */ NdrFcLong( 0x0 ), /* 0 */
/* 270 */ NdrFcShort( 0x0 ), /* Offset= 0 (270) */
/* 272 */ NdrFcLong( 0x1 ), /* 1 */
/* 276 */ NdrFcShort( 0x0 ), /* Offset= 0 (276) */
/* 278 */ NdrFcShort( 0xffffffff ), /* Offset= -1 (277) */
/* 280 */
    0x15, /* FC_STRUCT */
    0x7, /* 7 */
/* 282 */ NdrFcShort( 0x8 ), /* 8 */
/* 284 */ 0xb, /* FC_HYPER */
    0x5b, /* FC_END */
/* 286 */
    0x12, 0x0, /* FC_UP */

```

```

/* 288 */ NdrFcShort( 0xe ), /* Offset= 14 (302) */
/* 290 */
    0x1b, /* FC_CARRAY */
    0x1, /* 1 */
/* 292 */ NdrFcShort( 0x2 ), /* 2 */
/* 294 */ 0x9, /* Corr desc: FC_ULONG */
    0x0, /* */
/* 296 */ NdrFcShort( 0xfffc ), /* -4 */
/* 298 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 300 */ 0x6, /* FC_SHORT */
    0x5b, /* FC_END */
/* 302 */
    0x17, /* FC_CSTRUCT */
    0x3, /* 3 */
/* 304 */ NdrFcShort( 0x8 ), /* 8 */
/* 306 */ NdrFcShort( 0xffffffff0 ), /* Offset= -16 (290) */
/* 308 */ 0x8, /* FC_LONG */
    0x8, /* FC_LONG */
/* 310 */ 0x5c, /* FC_PAD */
    0x5b, /* FC_END */
/* 312 */
    0x2f, /* FC_IP */
    0x5a, /* FC_CONSTANT_IID */
/* 314 */ NdrFcLong( 0x0 ), /* 0 */
/* 318 */ NdrFcShort( 0x0 ), /* 0 */
/* 320 */ NdrFcShort( 0x0 ), /* 0 */
/* 322 */ 0xc0, /* 192 */
    0x0, /* 0 */
/* 324 */ 0x0, /* 0 */
    0x0, /* 0 */
/* 326 */ 0x0, /* 0 */
    0x0, /* 0 */
/* 328 */ 0x0, /* 0 */
    0x46, /* 70 */
/* 330 */
    0x2f, /* FC_IP */
    0x5a, /* FC_CONSTANT_IID */
/* 332 */ NdrFcLong( 0x20400 ), /* 132096 */
/* 336 */ NdrFcShort( 0x0 ), /* 0 */
/* 338 */ NdrFcShort( 0x0 ), /* 0 */
/* 340 */ 0xc0, /* 192 */
    0x0, /* 0 */
/* 342 */ 0x0, /* 0 */
    0x0, /* 0 */
/* 344 */ 0x0, /* 0 */
    0x0, /* 0 */
/* 346 */ 0x0, /* 0 */
    0x46, /* 70 */
/* 348 */
    0x12, 0x10, /* FC_UP [pointer_deref] */
/* 350 */ NdrFcShort( 0x2 ), /* Offset= 2 (352) */
/* 352 */
    0x12, 0x0, /* FC_UP */

```

```

/* 354 */ NdrFcShort( 0x1e6 ), /* Offset= 486 (840) */
/* 356 */
        0x2a, /* FC_ENCAPSULATED_UNION */
        0x89, /* 137 */
/* 358 */ NdrFcShort( 0x20 ), /* 32 */
/* 360 */ NdrFcShort( 0xa ), /* 10 */
/* 362 */ NdrFcLong( 0x8 ), /* 8 */
/* 366 */ NdrFcShort( 0x50 ), /* Offset= 80 (446) */
/* 368 */ NdrFcLong( 0xd ), /* 13 */
/* 372 */ NdrFcShort( 0x70 ), /* Offset= 112 (484) */
/* 374 */ NdrFcLong( 0x9 ), /* 9 */
/* 378 */ NdrFcShort( 0x90 ), /* Offset= 144 (522) */
/* 380 */ NdrFcLong( 0xc ), /* 12 */
/* 384 */ NdrFcShort( 0xb0 ), /* Offset= 176 (560) */
/* 386 */ NdrFcLong( 0x24 ), /* 36 */
/* 390 */ NdrFcShort( 0x104 ), /* Offset= 260 (650) */
/* 392 */ NdrFcLong( 0x800d ), /* 32781 */
/* 396 */ NdrFcShort( 0x120 ), /* Offset= 288 (684) */
/* 398 */ NdrFcLong( 0x10 ), /* 16 */
/* 402 */ NdrFcShort( 0x13a ), /* Offset= 314 (716) */
/* 404 */ NdrFcLong( 0x2 ), /* 2 */
/* 408 */ NdrFcShort( 0x150 ), /* Offset= 336 (744) */
/* 410 */ NdrFcLong( 0x3 ), /* 3 */
/* 414 */ NdrFcShort( 0x166 ), /* Offset= 358 (772) */
/* 416 */ NdrFcLong( 0x14 ), /* 20 */
/* 420 */ NdrFcShort( 0x17c ), /* Offset= 380 (800) */
/* 422 */ NdrFcShort( 0xffffffff ), /* Offset= -1 (421) */
/* 424 */
        0x21, /* FC_BOGUS_ARRAY */
        0x3, /* 3 */
/* 426 */ NdrFcShort( 0x0 ), /* 0 */
/* 428 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
        0x0, /* */
/* 430 */ NdrFcShort( 0x0 ), /* 0 */
/* 432 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 434 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 438 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 440 */
        0x12, 0x0, /* FC_UP */
/* 442 */ NdrFcShort( 0xfffff74 ), /* Offset= -140 (302) */
/* 444 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 446 */
        0x1a, /* FC_BOGUS_STRUCT */
        0x3, /* 3 */
/* 448 */ NdrFcShort( 0x10 ), /* 16 */
/* 450 */ NdrFcShort( 0x0 ), /* 0 */
/* 452 */ NdrFcShort( 0x6 ), /* Offset= 6 (458) */
/* 454 */ 0x8, /* FC_LONG */
        0x39, /* FC_ALIGNM8 */
/* 456 */ 0x36, /* FC_POINTER */
        0x5b, /* FC_END */
/* 458 */

```

```

        0x11, 0x0, /* FC_RP */
/* 460 */ NdrFcShort( 0xfffff5dc ), /* Offset= -36 (424) */
/* 462 */
        0x21, /* FC_BOGUS_ARRAY */
        0x3, /* 3 */
/* 464 */ NdrFcShort( 0x0 ), /* 0 */
/* 466 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
        0x0, /* */
/* 468 */ NdrFcShort( 0x0 ), /* 0 */
/* 470 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 472 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 476 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 478 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
        0x0, /* 0 */
/* 480 */ NdrFcShort( 0xfffff58 ), /* Offset= -168 (312) */
/* 482 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 484 */
        0x1a, /* FC_BOGUS_STRUCT */
        0x3, /* 3 */
/* 486 */ NdrFcShort( 0x10 ), /* 16 */
/* 488 */ NdrFcShort( 0x0 ), /* 0 */
/* 490 */ NdrFcShort( 0x6 ), /* Offset= 6 (496) */
/* 492 */ 0x8, /* FC_LONG */
        0x39, /* FC_ALIGNM8 */
/* 494 */ 0x36, /* FC_POINTER */
        0x5b, /* FC_END */
/* 496 */
        0x11, 0x0, /* FC_RP */
/* 498 */ NdrFcShort( 0xfffff5dc ), /* Offset= -36 (462) */
/* 500 */
        0x21, /* FC_BOGUS_ARRAY */
        0x3, /* 3 */
/* 502 */ NdrFcShort( 0x0 ), /* 0 */
/* 504 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
        0x0, /* */
/* 506 */ NdrFcShort( 0x0 ), /* 0 */
/* 508 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 510 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 514 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 516 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
        0x0, /* 0 */
/* 518 */ NdrFcShort( 0xfffff44 ), /* Offset= -188 (330) */
/* 520 */ 0x5c, /* FC_PAD */
        0x5b, /* FC_END */
/* 522 */
        0x1a, /* FC_BOGUS_STRUCT */
        0x3, /* 3 */
/* 524 */ NdrFcShort( 0x10 ), /* 16 */
/* 526 */ NdrFcShort( 0x0 ), /* 0 */
/* 528 */ NdrFcShort( 0x6 ), /* Offset= 6 (534) */
/* 530 */ 0x8, /* FC_LONG */
        0x39, /* FC_ALIGNM8 */

```

```

/* 532 */ 0x36,      /* FC_POINTER */
          0x5b,      /* FC_END */
/* 534 */
          0x11, 0x0, /* FC_RP */
/* 536 */ NdrFcShort( 0xffffffffc ), /* Offset= -36 (500) */
/* 538 */
          0x21,      /* FC_BOGUS_ARRAY */
          0x3,       /* 3 */
/* 540 */ NdrFcShort( 0x0 ), /* 0 */
/* 542 */ 0x19,      /* Corr desc: field pointer, FC_ULONG */
          0x0,       /* */
/* 544 */ NdrFcShort( 0x0 ), /* 0 */
/* 546 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 548 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 552 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 554 */
          0x12, 0x0, /* FC_UP */
/* 556 */ NdrFcShort( 0x176 ), /* Offset= 374 (930) */
/* 558 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 560 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x3,       /* 3 */
/* 562 */ NdrFcShort( 0x10 ), /* 16 */
/* 564 */ NdrFcShort( 0x0 ), /* 0 */
/* 566 */ NdrFcShort( 0x6 ), /* Offset= 6 (572) */
/* 568 */ 0x8,       /* FC_LONG */
          0x39,      /* FC_ALIGNM8 */
/* 570 */ 0x36,      /* FC_POINTER */
          0x5b,      /* FC_END */
/* 572 */
          0x11, 0x0, /* FC_RP */
/* 574 */ NdrFcShort( 0xffffffffc ), /* Offset= -36 (538) */
/* 576 */
          0x2f,      /* FC_IP */
          0x5a,      /* FC_CONSTANT_IID */
/* 578 */ NdrFcLong( 0x2f ), /* 47 */
/* 582 */ NdrFcShort( 0x0 ), /* 0 */
/* 584 */ NdrFcShort( 0x0 ), /* 0 */
/* 586 */ 0xc0,      /* 192 */
          0x0,       /* 0 */
/* 588 */ 0x0,       /* 0 */
          0x0,       /* 0 */
/* 590 */ 0x0,       /* 0 */
          0x0,       /* 0 */
/* 592 */ 0x0,       /* 0 */
          0x46,      /* 70 */
/* 594 */
          0x1b,      /* FC_CARRAY */
          0x0,       /* 0 */
/* 596 */ NdrFcShort( 0x1 ), /* 1 */
/* 598 */ 0x19,      /* Corr desc: field pointer, FC_ULONG */
          0x0,       /* */

```

```

/* 600 */ NdrFcShort( 0x4 ), /* 4 */
/* 602 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 604 */ 0x1,       /* FC_BYTE */
          0x5b,      /* FC_END */
/* 606 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x3,       /* 3 */
/* 608 */ NdrFcShort( 0x18 ), /* 24 */
/* 610 */ NdrFcShort( 0x0 ), /* 0 */
/* 612 */ NdrFcShort( 0xc ), /* Offset= 12 (624) */
/* 614 */ 0x8,       /* FC_LONG */
          0x8,       /* FC_LONG */
/* 616 */ 0x4c,      /* FC_EMBEDDED_COMPLEX */
          0x0,       /* 0 */
/* 618 */ NdrFcShort( 0xffffffffd6 ), /* Offset= -42 (576) */
/* 620 */ 0x39,      /* FC_ALIGNM8 */
          0x36,      /* FC_POINTER */
/* 622 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 624 */
          0x12, 0x0, /* FC_UP */
/* 626 */ NdrFcShort( 0xffffffffe0 ), /* Offset= -32 (594) */
/* 628 */
          0x21,      /* FC_BOGUS_ARRAY */
          0x3,       /* 3 */
/* 630 */ NdrFcShort( 0x0 ), /* 0 */
/* 632 */ 0x19,      /* Corr desc: field pointer, FC_ULONG */
          0x0,       /* */
/* 634 */ NdrFcShort( 0x0 ), /* 0 */
/* 636 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 638 */ NdrFcLong( 0xffffffff ), /* -1 */
/* 642 */ NdrFcShort( 0x0 ), /* Corr flags: */
/* 644 */
          0x12, 0x0, /* FC_UP */
/* 646 */ NdrFcShort( 0xffffffffd8 ), /* Offset= -40 (606) */
/* 648 */ 0x5c,      /* FC_PAD */
          0x5b,      /* FC_END */
/* 650 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x3,       /* 3 */
/* 652 */ NdrFcShort( 0x10 ), /* 16 */
/* 654 */ NdrFcShort( 0x0 ), /* 0 */
/* 656 */ NdrFcShort( 0x6 ), /* Offset= 6 (662) */
/* 658 */ 0x8,       /* FC_LONG */
          0x39,      /* FC_ALIGNM8 */
/* 660 */ 0x36,      /* FC_POINTER */
          0x5b,      /* FC_END */
/* 662 */
          0x11, 0x0, /* FC_RP */
/* 664 */ NdrFcShort( 0xffffffffc ), /* Offset= -36 (628) */
/* 666 */
          0x1d,      /* FC_SMFARRAY */
          0x0,       /* 0 */

```

```

/* 668 */ NdrFcShort( 0x8 ), /* 8 */
/* 670 */ 0x2, /* FC_CHAR */
/* 672 */ 0x5b, /* FC_END */
/* 674 */ 0x15, /* FC_STRUCT */
/* 676 */ 0x3, /* 3 */
/* 678 */ NdrFcShort( 0x10 ), /* 16 */
/* 680 */ 0x8, /* FC_LONG */
/* 682 */ 0x6, /* FC_SHORT */
/* 684 */ 0x6, /* FC_SHORT */
/* 686 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
/* 688 */ 0x0, /* 0 */
/* 690 */ NdrFcShort( 0xffffffffl ), /* Offset= -15 (666) */
/* 692 */ 0x5b, /* FC_END */
/* 694 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 696 */ 0x3, /* 3 */
/* 698 */ NdrFcShort( 0x20 ), /* 32 */
/* 700 */ NdrFcShort( 0x0 ), /* 0 */
/* 702 */ NdrFcShort( 0xa ), /* Offset= 10 (700) */
/* 704 */ 0x8, /* FC_LONG */
/* 706 */ 0x39, /* FC_ALIGNM8 */
/* 708 */ 0x36, /* FC_POINTER */
/* 710 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
/* 712 */ 0x0, /* 0 */
/* 714 */ NdrFcShort( 0xffffffff7 ), /* Offset= -25 (672) */
/* 716 */ 0x5b, /* FC_END */
/* 718 */ 0x11, 0x0, /* FC_RP */
/* 720 */ NdrFcShort( 0xffffffff10 ), /* Offset= -240 (462) */
/* 722 */ 0x1b, /* FC_CARRAY */
/* 724 */ 0x0, /* 0 */
/* 726 */ NdrFcShort( 0x1 ), /* 1 */
/* 728 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 730 */ 0x0, /* */
/* 732 */ NdrFcShort( 0x0 ), /* 0 */
/* 734 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 736 */ 0x1, /* FC_BYTE */
/* 738 */ 0x5b, /* FC_END */
/* 740 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 742 */ 0x3, /* 3 */
/* 744 */ NdrFcShort( 0x10 ), /* 16 */
/* 746 */ NdrFcShort( 0x0 ), /* 0 */
/* 748 */ NdrFcShort( 0x6 ), /* Offset= 6 (728) */
/* 750 */ 0x8, /* FC_LONG */
/* 752 */ 0x39, /* FC_ALIGNM8 */
/* 754 */ 0x36, /* FC_POINTER */
/* 756 */ 0x5b, /* FC_END */
/* 758 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 760 */ 0x3, /* 3 */
/* 762 */ NdrFcShort( 0x10 ), /* 16 */
/* 764 */ NdrFcShort( 0x0 ), /* 0 */
/* 766 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 768 */ 0x8, /* FC_LONG */
/* 770 */ 0x5b, /* FC_END */
/* 772 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 774 */ 0x3, /* 3 */
/* 776 */ NdrFcShort( 0x10 ), /* 16 */
/* 778 */ NdrFcShort( 0x0 ), /* 0 */
/* 780 */ NdrFcShort( 0x6 ), /* Offset= 6 (784) */
/* 782 */ 0x8, /* FC_LONG */
/* 784 */ 0x39, /* FC_ALIGNM8 */
/* 786 */ 0x36, /* FC_POINTER */
/* 788 */ 0x5b, /* FC_END */
/* 790 */ 0x12, 0x0, /* FC_UP */
/* 792 */ NdrFcShort( 0xffffffff6 ), /* Offset= -26 (704) */

```

```

/* 732 */ 0x1b, /* FC_CARRAY */
/* 734 */ 0x1, /* 1 */
/* 736 */ NdrFcShort( 0x2 ), /* 2 */
/* 738 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 740 */ 0x0, /* */
/* 742 */ NdrFcShort( 0x0 ), /* 0 */
/* 744 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 746 */ 0x6, /* FC_SHORT */
/* 748 */ 0x5b, /* FC_END */
/* 750 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 752 */ 0x3, /* 3 */
/* 754 */ NdrFcShort( 0x10 ), /* 16 */
/* 756 */ NdrFcShort( 0x0 ), /* 0 */
/* 758 */ NdrFcShort( 0x6 ), /* Offset= 6 (756) */
/* 760 */ 0x8, /* FC_LONG */
/* 762 */ 0x39, /* FC_ALIGNM8 */
/* 764 */ 0x36, /* FC_POINTER */
/* 766 */ 0x5b, /* FC_END */
/* 768 */ 0x12, 0x0, /* FC_UP */
/* 770 */ NdrFcShort( 0xffffffff6 ), /* Offset= -26 (732) */
/* 772 */ 0x1b, /* FC_CARRAY */
/* 774 */ 0x3, /* 3 */
/* 776 */ NdrFcShort( 0x4 ), /* 4 */
/* 778 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 780 */ 0x0, /* */
/* 782 */ NdrFcShort( 0x0 ), /* 0 */
/* 784 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 786 */ 0x8, /* FC_LONG */
/* 788 */ 0x5b, /* FC_END */
/* 790 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 792 */ 0x3, /* 3 */
/* 794 */ NdrFcShort( 0x10 ), /* 16 */
/* 796 */ NdrFcShort( 0x0 ), /* 0 */
/* 798 */ NdrFcShort( 0x6 ), /* Offset= 6 (784) */
/* 800 */ 0x8, /* FC_LONG */
/* 802 */ 0x39, /* FC_ALIGNM8 */
/* 804 */ 0x36, /* FC_POINTER */
/* 806 */ 0x5b, /* FC_END */
/* 808 */ 0x12, 0x0, /* FC_UP */
/* 810 */ NdrFcShort( 0xffffffff6 ), /* Offset= -26 (760) */
/* 812 */ 0x1b, /* FC_CARRAY */
/* 814 */ 0x7, /* 7 */
/* 816 */ NdrFcShort( 0x8 ), /* 8 */
/* 818 */ 0x19, /* Corr desc: field pointer, FC_ULONG */
/* 820 */ 0x0, /* */
/* 822 */ NdrFcShort( 0x0 ), /* 0 */

```

```

/* 796 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 798 */ 0xb, /* FC_HYPER */
/* 800 */ 0x5b, /* FC_END */
/* 802 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 804 */ 0x3, /* 3 */
/* 806 */ NdrFcShort( 0x10 ), /* 16 */
/* 808 */ NdrFcShort( 0x0 ), /* 0 */
/* 810 */ NdrFcShort( 0x6 ), /* Offset= 6 (812) */
/* 812 */ 0x8, /* FC_LONG */
/* 814 */ 0x39, /* FC_ALIGNM8 */
/* 816 */ 0x36, /* FC_POINTER */
/* 818 */ 0x5b, /* FC_END */
/* 820 */ 0x12, 0x0, /* FC_UP */
/* 822 */ NdrFcShort( 0xfffffe6 ), /* Offset= -26 (788) */
/* 824 */ 0x15, /* FC_STRUCT */
/* 826 */ 0x3, /* 3 */
/* 828 */ NdrFcShort( 0x8 ), /* 8 */
/* 830 */ 0x8, /* FC_LONG */
/* 832 */ 0x5c, /* FC_PAD */
/* 834 */ 0x5b, /* FC_END */
/* 836 */ 0x1b, /* FC_CARRAY */
/* 838 */ 0x3, /* 3 */
/* 840 */ NdrFcShort( 0x8 ), /* 8 */
/* 842 */ 0x7, /* Corr desc: FC_USHORT */
/* 844 */ 0x0, /* */
/* 846 */ NdrFcShort( 0xffc8 ), /* -56 */
/* 848 */ NdrFcShort( 0x1 ), /* Corr flags: early, */
/* 850 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
/* 852 */ 0x0, /* 0 */
/* 854 */ NdrFcShort( 0xfffffec ), /* Offset= -20 (816) */
/* 856 */ 0x5c, /* FC_PAD */
/* 858 */ 0x5b, /* FC_END */
/* 860 */ 0x1a, /* FC_BOGUS_STRUCT */
/* 862 */ 0x3, /* 3 */
/* 864 */ NdrFcShort( 0x38 ), /* 56 */
/* 866 */ NdrFcShort( 0xfffffec ), /* Offset= -20 (824) */
/* 868 */ NdrFcShort( 0x0 ), /* Offset= 0 (846) */
/* 870 */ 0x6, /* FC_SHORT */
/* 872 */ 0x6, /* FC_SHORT */
/* 874 */ 0x38, /* FC_ALIGNM4 */
/* 876 */ 0x8, /* FC_LONG */
/* 878 */ 0x8, /* FC_LONG */
/* 880 */ 0x4c, /* FC_EMBEDDED_COMPLEX */
/* 882 */ 0x4, /* 4 */
/* 884 */ NdrFcShort( 0xffffe0d ), /* Offset= -499 (356) */
/* 886 */ 0x5b, /* FC_END */
/* 888 */

```

```

0x12, 0x0, /* FC_UP */
/* 860 */ NdrFcShort( 0xfffff02 ), /* Offset= -254 (606) */
/* 862 */
/* 864 */ 0x12, 0x8, /* FC_UP [simple_pointer] */
/* 866 */ 0x1, /* FC_BYTE */
/* 868 */ 0x5c, /* FC_PAD */
/* 870 */
/* 872 */ 0x12, 0x8, /* FC_UP [simple_pointer] */
/* 874 */ 0x6, /* FC_SHORT */
/* 876 */ 0x5c, /* FC_PAD */
/* 878 */
/* 880 */ 0x12, 0x8, /* FC_UP [simple_pointer] */
/* 882 */ 0x8, /* FC_LONG */
/* 884 */ 0x5c, /* FC_PAD */
/* 886 */
/* 888 */ 0x12, 0x8, /* FC_UP [simple_pointer] */
/* 890 */ 0xa, /* FC_FLOAT */
/* 892 */ 0x5c, /* FC_PAD */
/* 894 */
/* 896 */ 0x12, 0x8, /* FC_UP [simple_pointer] */
/* 898 */ 0xc, /* FC_DOUBLE */
/* 900 */ 0x5c, /* FC_PAD */
/* 902 */
/* 904 */ NdrFcShort( 0xfffffda4 ), /* Offset= -604 (280) */
/* 906 */
/* 908 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 910 */ NdrFcShort( 0xfffffda6 ), /* Offset= -602 (286) */
/* 912 */
/* 914 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 916 */ NdrFcShort( 0xfffffdb6 ), /* Offset= -580 (312) */
/* 918 */
/* 920 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 922 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 924 */
/* 926 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 928 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 930 */
/* 932 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 934 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 936 */
/* 938 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 940 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 942 */
/* 944 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 946 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 948 */
/* 950 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 952 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 954 */
/* 956 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 958 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 960 */
/* 962 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 964 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 966 */
/* 968 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 970 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 972 */
/* 974 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 976 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 978 */
/* 980 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 982 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 984 */
/* 986 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 988 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 990 */
/* 992 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 994 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */
/* 996 */
/* 998 */ 0x12, 0x10, /* FC_UP [pointer_deref] */
/* 1000 */ NdrFcShort( 0xfffffdb8 ), /* Offset= -580 (312) */

```

```

/* 920 */ 0xb,      /* FC_HYPER */
          0x5b,      /* FC_END */

/* 922 */
          0x12, 0x0, /* FC_UP */
/* 924 */ NdrFcShort( 0xffffffff2 ), /* Offset= -14 (910) */
/* 926 */
          0x12, 0x8, /* FC_UP [simple_pointer] */
/* 928 */ 0x2,      /* FC_CHAR */
          0x5c,      /* FC_PAD */

/* 930 */
          0x1a,      /* FC_BOGUS_STRUCT */
          0x7,       /* 7 */

/* 932 */ NdrFcShort( 0x20 ), /* 32 */
/* 934 */ NdrFcShort( 0x0 ), /* 0 */
/* 936 */ NdrFcShort( 0x0 ), /* Offset= 0 (936) */
/* 938 */ 0x8,      /* FC_LONG */
          0x8,       /* FC_LONG */

/* 940 */ 0x6,      /* FC_SHORT */
          0x6,       /* FC_SHORT */

/* 942 */ 0x6,      /* FC_SHORT */
          0x6,       /* FC_SHORT */

/* 944 */ 0x4c,     /* FC_EMBEDDED_COMPLEX */
          0x0,       /* 0 */

/* 946 */ NdrFcShort( 0xfffffc54 ), /* Offset= -940 (6) */
/* 948 */ 0x5c,     /* FC_PAD */
          0x5b,     /* FC_END */
/* 950 */ 0xb4,     /* FC_USER_MARSHAL */
          0x83,     /* 131 */

/* 952 */ NdrFcShort( 0x0 ), /* 0 */
/* 954 */ NdrFcShort( 0x18 ), /* 24 */
/* 956 */ NdrFcShort( 0x0 ), /* 0 */
/* 958 */ NdrFcShort( 0xfffffc44 ), /* Offset= -956 (2) */
/* 960 */
          0x11, 0x4, /* FC_RP [allocated_on_stack] */
/* 962 */ NdrFcShort( 0x6 ), /* Offset= 6 (968) */
/* 964 */
          0x13, 0x0, /* FC_OP */
/* 966 */ NdrFcShort( 0xfffffcdc ), /* Offset= -36 (930) */
/* 968 */ 0xb4,     /* FC_USER_MARSHAL */
          0x83,     /* 131 */

/* 970 */ NdrFcShort( 0x0 ), /* 0 */
/* 972 */ NdrFcShort( 0x18 ), /* 24 */
/* 974 */ NdrFcShort( 0x0 ), /* 0 */
/* 976 */ NdrFcShort( 0xfffffff4 ), /* Offset= -12 (964) */

          0x0
    }
};

const CInterfaceProxyVtbl * _tpcc_com_ps_ProxyVtblList[] =
{
    ( CInterfaceProxyVtbl *) &_ITPCCProxyVtbl,
    0
}

```

```

};

const CInterfaceStubVtbl * _tpcc_com_ps_StubVtblList[] =
{
    ( CInterfaceStubVtbl *) &_ITPCCStubVtbl,
    0
};

PCInterfaceName const _tpcc_com_ps_InterfaceNamesList[] =
{
    "ITPCC",
    0
};

#define _tpcc_com_ps_CHECK_IID(n) IID_GENERIC_CHECK_IID( _tpcc_com_ps,
pIID, n)

int __stdcall _tpcc_com_ps_IID_Lookup( const IID * pIID, int * pIndex )
{
    if(!_tpcc_com_ps_CHECK_IID(0))
    {
        *pIndex = 0;
        return 1;
    }

    return 0;
}

const ExtendedProxyFileInfo tpcc_com_ps_ProxyFileInfo =
{
    (PCInterfaceProxyVtblList *) &_tpcc_com_ps_ProxyVtblList,
    (PCInterfaceStubVtblList *) &_tpcc_com_ps_StubVtblList,
    (const PCInterfaceName * ) &_tpcc_com_ps_InterfaceNamesList,
    0, // no delegation
    &_tpcc_com_ps_IID_Lookup,
    1,
    2,
    0, /* table of [async_uuid] interfaces */
    0, /* Filler1 */
    0, /* Filler2 */
    0 /* Filler3 */
};

#endif /* defined(_M_IA64) || defined(_M_AXP64)*/

```

Appendix B - Database Details

BACKUP.SQL

```
-- File:      BACKUP.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates backup of tpcc database

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

dump database tpcc to tpccback1, tpccback2, tpccback3, tpccback4, tpccback5
with init, stats = 1

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go
```

BACKUPDEV.SQL

```
-- File:      BACKUPDEVB.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates tpcc database Backup Devices

use master
go

-- create backup devices

exec sp_addumpdevice 'disk','tpccback1','X:\tpccback1.dmp'
exec sp_addumpdevice 'disk','tpccback2','Y:\tpccback2.dmp'
exec sp_addumpdevice 'disk','tpccback3','Z:\tpccback3.dmp'
exec sp_addumpdevice 'disk','tpccback4','W:\tpccback4.dmp'
exec sp_addumpdevice 'disk','tpccback5','V:\tpccback5.dmp'
go
```

CREATEDB.SQL

```
-- File:      CREATEDB.SQL
```

```
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates tpcc database and backup files

use master
go

-- Create temporary table for timing

if exists ( select name from sysobjects where name = 'tpcc_timer' )
drop table tpcc_timer
go

create table tpcc_timer
(
    start_date          char(30),
    end_date            char(30)
)

insert into tpcc_timer values (0,0)
go

-- Store starting time

update tpcc_timer
set start_date = (select convert(char(30), getdate(),9))
go

-- create main database files

CREATE DATABASE tpcc
ON PRIMARY
(
    NAME          = MSSQL70_tpcc_root,
    FILENAME      = "C:\tpcc_root.mdf",
    SIZE          = 50MB,
    FILEGROWTH    =0),
FILEGROUP MSSQL70_cs_fg
(
    NAME          = MSSQL70_cs1,
    FILENAME      = "E:",
    SIZE          = 44500MB,
    FILEGROWTH    = 0),
(
    NAME          = MSSQL70_cs2,
    FILENAME      = "F:",
    SIZE          = 44500MB,
    FILEGROWTH    = 0),
```

```

( NAME = MSSQL70_cs3,
  FILENAME = "G:",
  SIZE = 44500MB,
  FILEGROWTH = 0),
( NAME = MSSQL70_cs4,
  FILENAME = "H:",
  SIZE = 44500MB,
  FILEGROWTH = 0),
( NAME = MSSQL70_cs5,
  FILENAME = "I:",
  SIZE = 44500MB,
  FILEGROWTH = 0),
FILEGROUP MSSQL70_misc_fg
( NAME = MSSQL70_misc1,
  FILENAME = "N:",
  SIZE = 24000MB,
  FILEGROWTH = 0),
( NAME = MSSQL70_misc2,
  FILENAME = "O:",
  SIZE = 24000MB,
  FILEGROWTH = 0),
( NAME = MSSQL70_misc3,
  FILENAME = "P:",
  SIZE = 24000MB,
  FILEGROWTH = 0),
( NAME = MSSQL70_misc4,
  FILENAME = "Q:",
  SIZE = 24000MB,
  FILEGROWTH = 0),
( NAME = MSSQL70_misc5,
  FILENAME = "R:",
  SIZE = 24000MB,
  FILEGROWTH = 0)
LOG ON
( NAME =MSSQL70_tpcc_log,
  FILENAME ="L:",
  SIZE =90000MB,
  FILEGROWTH=0)

go

-- Store ending time
update tpcc_timer
set end_date = (select convert(char(30), getdate(),9))
go

select "Elapsed time (in seconds): ", datediff(second,(select start_date
from tpcc_timer),(select end_date from tpcc_timer))

-- remove temporary table

if exists ( select name from sysobjects where name = 'tpcc_timer' )
drop table tpcc_timer
go

```

DBOPT1.SQL

```

-- File:      DBOPT1.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Sets database options for data load

```

```

use master
go

```

```

exec sp_dboption tpcc,'select into/bulkcopy',true
exec sp_dboption tpcc,'trunc. log on chkpt.',true
go

```

```

use tpcc
go

```

```

checkpoint
go

```

DBOPT2.SQL

```

-- File:      DBOPT2.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Resets database options after data load

```

```

sp_dboption tpcc,'select into/bulkcopy',FALSE
GO

```

```

sp_dboption tpcc,'trunc. log on chkpt.',FALSE
GO

```

```

USE tpcc
GO

```

```

CHECKPOINT
GO

```

```

sp_configure 'allow updates',1
GO

```

```

RECONFIGURE WITH OVERRIDE
GO

```

```

DECLARE @msg varchar(50)

IF (SELECT (SUBSTRING((SELECT @@version),1,26))) = 'Microsoft SQL Server
2000'
BEGIN
--
-- OPTIONS FOR SQL SERVER 8.0
-- Set option values for user-defined indexes
--

SET @msg = ' '
PRINT @msg
SET @msg = 'Setting SQL Server 8.0 indexoptions'
PRINT @msg
SET @msg = ' '
PRINT @msg

EXEC sp_indexoption 'customer', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'district', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'warehouse', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'stock', 'DisallowPageLocks', TRUE
EXEC sp_indexoption 'order_line', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'orders', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'new_order', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'item', 'DisallowRowLocks', TRUE
EXEC sp_indexoption 'item', 'DisallowPageLocks', TRUE

END
ELSE
BEGIN
--
-- OPTIONS FOR SQL SERVER 7.0
-- Set option values for user-defined indexes
--

SET @msg = ' '
PRINT @msg
SET @msg = 'Setting SQL Server 7.0 indexoptions'
PRINT @msg
SET @msg = ' '
PRINT @msg

EXEC sp_indexoption 'customer', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'district', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'warehouse', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'stock', 'AllowPageLocks', FALSE
EXEC sp_indexoption 'order_line', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'orders', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'new_order', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'item', 'AllowRowLocks', FALSE
EXEC sp_indexoption 'item', 'AllowPageLocks', FALSE

END
GO

```

```

Print ' '
Print '*****'
Print 'Pre-specified Locking Hierarchy:'
Print ' Lockflag = 0 ==> No pre-specified hierarchy'
Print ' Lockflag = 1 ==> Lock at Page-level then Table-level'
Print ' Lockflag = 2 ==> Lock at Row-level then Table-level'
Print ' Lockflag = 3 ==> Lock at Table-level'
Print ' '

```

```

SELECT name,lockflags
FROM sysindexes
WHERE object_id('warehouse') = id OR
object_id('district') = id OR
object_id('customer') = id OR
object_id('stock') = id OR
object_id('orders') = id OR
object_id('order_line') = id OR
object_id('history') = id OR
object_id('new_order') = id OR
object_id('item') = id
ORDERBY lockflags asc
GO

sp_configure 'allow updates',0
GO

RECONFIGURE WITH OVERRIDE
GO

EXEC sp_dboption tpcc, 'auto update statistics', FALSE
EXEC sp_dboption tpcc, 'auto create statistics', FALSE
EXEC sp_dboption tpcc, 'torn page detection', FALSE
GO

EXEC sp_tableoption 'district', 'pintable',true
EXEC sp_tableoption 'warehouse', 'pintable',true
EXEC sp_tableoption 'new_order', 'pintable',true
EXEC sp_tableoption 'item', 'pintable',true
GO

```

REMOVEDB.SQL

```

-- File: REMOVEDB.SQL
-- Microsoft TPC-C Benchmark Kit Ver. 4.20
-- Copyright Microsoft, 1999
-- Purpose: Removes tpcc database and backup files

use master
go

-- remove any existing database and backup files

```

```
exec sp_dbremove tpcc, dropdev
go
```

```
exec sp_dropdevice 'tpccback1'
exec sp_dropdevice 'tpccback2'
exec sp_dropdevice 'tpccback3'
exec sp_dropdevice 'tpccback4'
exec sp_dropdevice 'tpccback5'
go
```

RESTORE.SQL

```
-- File:      RESTORE.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Loads database backup from backup files
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```
load database tpcc from tpccback1, tpccback2, tpccback3, tpccback4,
tpccback5 with stats = 1
```

```
select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
```

```
go
```

VERIFYTPCCLOAD.SQL

```
-- File:      VERIFYTPCCLOAD.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Performs series of TPCC database checks to verify
--           that database load completed correctly
```

```
print " "
select  convert(char(30), getdate(),9)
print " "
```

```
use tpcc
go
```

```
-- *****
--
-- Check rows per table from SYSINDEXES
--
```

```
-- *****
```

```
print 'WAREHOUSE TABLE'
```

```
select  rows
from sysindexes
whereid = object_id("warehouse")
go
```

```
print 'DISTRICT TABLE = (10 * No of warehouses)'
```

```
select  rows
from sysindexes
whereid =object_id("district")
go
```

```
print 'ITEM TABLE = 100,000'
```

```
select  rows
from sysindexes
whereid =object_id("item")
go
```

```
print 'CUSTOMER TABLE = (30,000 * No of warehouses)'
```

```
select  rows
from sysindexes
whereid =object_id("customer")
go
```

```
print 'ORDERS TABLE = (30,000 * No of warehouses)'
```

```
select  rows
from sysindexes
whereid =object_id("orders")
go
```

```
print 'HISTORY TABLE = (30,000 * No of warehouses)'
```

```
select  rows
from sysindexes
whereid =object_id("history")
go
```

```
print 'STOCK TABLE = (100,000 * No of warehouses)'
```

```
select  rows
from sysindexes
whereid =object_id("stock")
go
```

```
print 'ORDER_LINE TABLE = (300,000 * No of warehouses + some change)'
```

```

select      rows
from sysindexes
where id    =object_id("order_line")
go

print 'NEW_ORDER TABLE = (9000 * No of warehouses)'
```

```

select      rows
from sysindexes
where id    =object_id("new_order")
go

--      *****
--
--      Check indices
--
--      *****

print '*****Index Check*****'
```

```

use tpcc
go

sp_helpindex      customer
go

sp_helpindex      stock
go

sp_helpindex      district
go

sp_helpindex      item
go

sp_helpindex      new_order
go

sp_helpindex      orders
go

sp_helpindex      order_line
go

sp_helpindex      warehouse
go
```

IDXCUSCL.SQL

```

-- File:      IDXCUSCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on customer table
```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'customer_c1' )
    drop index customer.customer_c1

create unique clustered index customer_c1 on customer(c_w_id, c_d_id, c_id)
on MSSQL70_cs_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go
```

IDXCUSNC.SQL

```

-- File:      IDXCUSNC.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates non-clustered index on customer table
```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'customer_nc1' )
    drop index customer.customer_nc1

create unique nonclustered index customer_nc1 on customer(c_w_id, c_d_id,
c_last, c_first, c_id)
on MSSQL70_cs_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go
```

IDXDISCL.SQL

```
-- File:      IDXDISCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on district table
```

```
use tpcc
go
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```
if exists ( select name from sysindexes where name = 'district_cl' )
    drop index district.district_cl
```

```
create unique clustered index district_cl on district(d_w_id, d_id)
    with fillfactor=100 on MSSQL70_misc_fg
```

```
select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
```

```
go
```

IDXITMCL.SQL

```
-- File:      IDXITMCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on item table
```

```
use tpcc
go
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```
if exists ( select name from sysindexes where name = 'item_cl' )
    drop index item.item_cl
```

```
create unique clustered index item_cl on item(i_id)
    on MSSQL70_misc_fg
```

```
select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
```

```
go
```

IDXNODCL.SQL

```
-- File:      IDXNODCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on new_order table
```

```
use tpcc
go
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```
if exists ( select name from sysindexes where name = 'new_order_cl' )
    drop index new_order.new_order_cl
```

```
create unique clustered index new_order_cl on new_order(no_w_id, no_d_id,
no_o_id)
    on MSSQL70_misc_fg
```

```
select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)
```

```
go
```

IDXODLCL.SQL

```
-- File:      IDXODLCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on order_line table
```

```
use tpcc
go
```

```
declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)
```

```

if exists ( select name from sysindexes where name = 'order_line_c1' )
    drop index order_line.order_line_c1

create unique clustered index order_line_c1 on order_line(ol_w_id, ol_d_id,
ol_o_id, ol_number)
    on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

IDXORDCL.SQL

```

-- File:      IDXORDCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on orders table

```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'orders_c1' )
    drop index orders.orders_c1

create unique clustered index orders_c1 on orders(o_w_id, o_d_id, o_id)
    on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

IDXORDNC.SQL

```

-- File:      IDXORDNC.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates non-clustered index on orders table

```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'orders_nc1' )
    drop index orders.orders_nc1

create index orders_nc1 on orders(o_w_id, o_d_id, o_c_id, o_id)
    on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

IDXSTKCL.SQL

```

-- File:      IDXSTKCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on stock table

```

```

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'stock_c1' )
    drop index stock.stock_c1

create unique clustered index stock_c1 on stock(s_i_id, s_w_id)
    on MSSQL70_cs_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go

```

IDXWARCL.SQL

```
-- File:      IDXWARCL.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates clustered index on warehouse table

use tpcc
go

declare @startdate datetime
declare @enddate datetime
select @startdate = getdate()
select "Start date:", convert(varchar(30),@startdate,9)

if exists ( select name from sysindexes where name = 'warehouse_c1' )
    drop index warehouse.warehouse_c1

create unique clustered index warehouse_c1 on warehouse(w_id)
    with fillfactor=100 on MSSQL70_misc_fg

select @enddate = getdate()
select "End date: ", convert(varchar(30),@enddate,9)
select "Elapsed time (in seconds): ", datediff(second, @startdate, @enddate)

go
```

TABLES.SQL

```
-- File:      TABLES.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.20
--           Copyright Microsoft, 1999
-- Purpose:   Creates TPC-C tables

use tpcc
go

--
-- Remove all existing TPC-C tables
--

if exists ( select name from sysobjects where name = 'warehouse' )
    drop table warehouse
go
if exists ( select name from sysobjects where name = 'district' )
    drop table district
go
if exists ( select name from sysobjects where name = 'customer' )
```

```
    drop table customer
go
if exists ( select name from sysobjects where name = 'history' )
    drop table history
go
if exists ( select name from sysobjects where name = 'new_order' )
    drop table new_order
go
if exists ( select name from sysobjects where name = 'orders' )
    drop table orders
go
if exists ( select name from sysobjects where name = 'order_line' )
    drop table order_line
go
if exists ( select name from sysobjects where name = 'item' )
    drop table item
go
if exists ( select name from sysobjects where name = 'stock' )
    drop table stock
go

--
-- Create new tables
--

create table warehouse
(
    w_id                smallint,
    w_name              char(10),
    w_street_1         char(20),
    w_street_2         char(20),
    w_city             char(20),
    w_state            char(2),
    w_zip             char(9),
    w_tax             numeric(4,4),
    w_ytd             numeric(12,2)
) on MSSQL70_misc_fg
go

create table district
(
    d_id              tinyint,
    d_w_id           smallint,
    d_name           char(10),
    d_street_1      char(20),
    d_street_2      char(20),
    d_city          char(20),
    d_state         char(2),
    d_zip          char(9),
    d_tax          numeric(4,4),
    d_ytd          numeric(12,2),
    d_next_o_id    int
) on MSSQL70_misc_fg
```

```

go
create table customer
(
    c_id            int,
    c_d_id         tinyint,
    c_w_id         smallint,
    c_first        char(16),
    c_middle       char(2),
    c_last         char(16),
    c_street_1     char(20),
    c_street_2     char(20),
    c_city         char(20),
    c_state        char(2),
    c_zip          char(9),
    c_phone        char(16),
    c_since        datetime,
    c_credit       char(2),
    c_credit_lim   numeric(12,2),
    c_discount     numeric(4,4),
    c_balance      numeric(12,2),
    c_ytd_payment  numeric(12,2),
    c_payment_cnt  smallint,
    c_delivery_cnt smallint,
    c_data         char(500)
) on MSSQL70_cs_fg
go
create table history
(
    h_c_id            int,
    h_c_d_id         tinyint,
    h_c_w_id         smallint,
    h_d_id           tinyint,
    h_w_id           smallint,
    h_date           datetime,
    h_amount         numeric(6,2),
    h_data           char(24)
) on MSSQL70_misc_fg
go
create table new_order
(
    no_o_id          int,
    no_d_id          tinyint,
    no_w_id          smallint
) on MSSQL70_misc_fg
go
create table orders
(
    o_id            int,
    o_d_id          tinyint,

```

```

    o_w_id          smallint,
    o_c_id          int,
    o_entry_d       datetime,
    o_carrier_id    tinyint,
    o_ol_cnt        tinyint,
    o_all_local     tinyint
) on MSSQL70_misc_fg
go
create table order_line
(
    ol_o_id          int,
    ol_d_id          tinyint,
    ol_w_id          smallint,
    ol_number        tinyint,
    ol_i_id          int,
    ol_supply_w_id   smallint,
    ol_delivery_d    datetime,
    ol_quantity      smallint,
    ol_amount        numeric(6,2),
    ol_dist_info     char(24)
) on MSSQL70_misc_fg
go
create table item
(
    i_id            int,
    i_im_id         int,
    i_name          char(24),
    i_price         numeric(5,2),
    i_data          char(50)
) on MSSQL70_misc_fg
go
create table stock
(
    s_i_id          int,
    s_w_id          smallint,
    s_quantity      smallint,
    s_dist_01       char(24),
    s_dist_02       char(24),
    s_dist_03       char(24),
    s_dist_04       char(24),
    s_dist_05       char(24),
    s_dist_06       char(24),
    s_dist_07       char(24),
    s_dist_08       char(24),
    s_dist_09       char(24),
    s_dist_10       char(24),
    s_ytd           int,
    s_order_cnt     smallint,
    s_remote_cnt    smallint,
    s_data          char(50)

```

```
) on MSSQL70_cs_fg
go
```

DELIVERY.SQL

```
-- File:      DELIVERY.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Creates delivery transaction stored procedure
--
-- Interface Level: 4.10.000

use tpcc
go

if exists (select name from sysobjects where name = "tpcc_delivery" )
    drop procedure tpcc_delivery
go

create proc tpcc_delivery @w_id          smallint,
                        @o_carrier_id  smallint
as

declare @d_id  tinyint,
        @o_id  int,
        @c_id  int,
        @total numeric(12,2),
        @oid1  int,
        @oid2  int,
        @oid3  int,
        @oid4  int,
        @oid5  int,
        @oid6  int,
        @oid7  int,
        @oid8  int,
        @oid9  int,
        @oid10 int

select @d_id = 0

begin tran d

    while (@d_id < 10)
    begin

        select @d_id = @d_id + 1,
               @total = 0,
               @o_id = 0

        select top 1
               @o_id = no_o_id
        from new_order (serializable uplock)
```

```
        wherenow_id = @w_id and
               no_d_id = @d_id
        order by no_o_id asc
```

```
        if (@@rowcount <> 0)
        begin
```

```
-- claim the order for this district
```

```
        delete new_order
        wherenow_id = @w_id and
        no_d_id = @d_id and
        no_o_id = @o_id
```

```
-- set carrier_id on this order (and get customer id)
```

```
        update orders
        set o_carrier_id = @o_carrier_id,
            @c_id = o_c_id
        wherenow_id = @w_id and
        o_d_id = @d_id and
        o_id = @o_id
```

```
-- set date in all lineitems for this order (and sum amounts)
```

```
        update order_line
        set ol_delivery_d = getdate(),
            @total = @total + ol_amount
        whereol_w_id = @w_id and
        ol_d_id = @d_id and
        ol_o_id = @o_id
```

```
-- accumulate lineitem amounts for this order into customer
```

```
        update customer
        set c_balance = c_balance + @total,
            c_delivery_cnt = c_delivery_cnt + 1
        wherec_w_id = @w_id and
        c_d_id = @d_id and
        c_id = @c_id
```

```
    end
```

```
select @oid1 = case @d_id when 1 then @o_id else @oid1 end,
       @oid2 = case @d_id when 2 then @o_id else @oid2 end,
       @oid3 = case @d_id when 3 then @o_id else @oid3 end,
       @oid4 = case @d_id when 4 then @o_id else @oid4 end,
       @oid5 = case @d_id when 5 then @o_id else @oid5 end,
       @oid6 = case @d_id when 6 then @o_id else @oid6 end,
       @oid7 = case @d_id when 7 then @o_id else @oid7 end,
       @oid8 = case @d_id when 8 then @o_id else @oid8 end,
       @oid9 = case @d_id when 9 then @o_id else @oid9 end,
       @oid10 = case @d_id when 10 then @o_id else @oid10 end
```

```

end
commit tran d
-- return delivery data to client
select @oid1,
       @oid2,
       @oid3,
       @oid4,
       @oid5,
       @oid6,
       @oid7,
       @oid8,
       @oid9,
       @oid10
go

```

NEWORD.SQL

```

-- File:      NEWORD.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Creates new order transaction stored procedure
--
-- Interface Level: 4.10.000

use tpcc
go

if exists ( select name from sysobjects where name = "tpcc_neworder" )
  drop procedure tpcc_neworder
go

create proc tpcc_neworder
        @w_id      smallint,
        @d_id      tinyint,
        @c_id      int,
        @o_ol_cnt  tinyint,
        @o_all_local tinyint,
        @i_id1 int = 0, @s_w_id1 smallint = 0, @ol_qty1
smallint = 0,
        @i_id2 int = 0, @s_w_id2 smallint = 0, @ol_qty2
smallint = 0,
        @i_id3 int = 0, @s_w_id3 smallint = 0, @ol_qty3
smallint = 0,
        @i_id4 int = 0, @s_w_id4 smallint = 0, @ol_qty4
smallint = 0,
        @i_id5 int = 0, @s_w_id5 smallint = 0, @ol_qty5
smallint = 0,

```

```

        @i_id6 int = 0, @s_w_id6 smallint = 0, @ol_qty6
smallint = 0,
        @i_id7 int = 0, @s_w_id7 smallint = 0, @ol_qty7
smallint = 0,
        @i_id8 int = 0, @s_w_id8 smallint = 0, @ol_qty8
smallint = 0,
        @i_id9 int = 0, @s_w_id9 smallint = 0, @ol_qty9
smallint = 0,
        @i_id10 int = 0, @s_w_id10 smallint = 0, @ol_qty10
smallint = 0,
        @i_id11 int = 0, @s_w_id11 smallint = 0, @ol_qty11
smallint = 0,
        @i_id12 int = 0, @s_w_id12 smallint = 0, @ol_qty12
smallint = 0,
        @i_id13 int = 0, @s_w_id13 smallint = 0, @ol_qty13
smallint = 0,
        @i_id14 int = 0, @s_w_id14 smallint = 0, @ol_qty14
smallint = 0,
        @i_id15 int = 0, @s_w_id15 smallint = 0, @ol_qty15
smallint = 0

as
declare  @w_tax      numeric(4,4),
        @d_tax      numeric(4,4),
        @c_last     char(16),
        @c_credit   char(2),
        @c_discount numeric(4,4),
        @i_price    numeric(5,2),
        @i_name     char(24),
        @i_data     char(50),
        @o_entry_d  datetime,
        @remote_flag int,
        @s_quantity smallint,
        @s_data     char(50),
        @s_dist     char(24),
        @li_no      int,
        @o_id       int,
        @commit_flag tinyint,
        @li_id      int,
        @li_s_w_id  smallint,
        @li_qty     smallint,
        @ol_number int,
        @c_id_local int

begin
begin transaction n
-- get district tax and next available order id and update
-- plus initialize local variables

update district
set @d_tax = d_tax,

```

```

        @o_id      = d_next_o_id,
        d_next_o_id = d_next_o_id + 1,
        @o_entry_d  = getdate(),
        @li_no      = 0,
        @commit_flag = 1
whered_w_id      = @w_id and
        d_id       = @d_id

-- process orderlines

        while (@li_no < @o_ol_cnt)
        begin

                select @li_no = @li_no + 1

-- set i_id, s_w_id, and qty for this lineitem

                select      @li_id = case @li_no
                        when 1 then @i_id1
                        when 2 then @i_id2
                        when 3 then @i_id3
                        when 4 then @i_id4
                        when 5 then @i_id5
                        when 6 then @i_id6
                        when 7 then @i_id7
                        when 8 then @i_id8
                        when 9 then @i_id9
                        when 10 then @i_id10
                        when 11 then @i_id11
                        when 12 then @i_id12
                        when 13 then @i_id13
                        when 14 then @i_id14
                        when 15 then @i_id15
                        end,

                        @li_s_w_id = case @li_no
                        when 1 then @s_w_id1
                        when 2 then @s_w_id2
                        when 3 then @s_w_id3
                        when 4 then @s_w_id4
                        when 5 then @s_w_id5
                        when 6 then @s_w_id6
                        when 7 then @s_w_id7
                        when 8 then @s_w_id8
                        when 9 then @s_w_id9
                        when 10 then @s_w_id10
                        when 11 then @s_w_id11
                        when 12 then @s_w_id12
                        when 13 then @s_w_id13
                        when 14 then @s_w_id14
                        when 15 then @s_w_id15
                        end,

```

```

        @li_qty = case @li_no
                when 1 then @ol_qty1
                when 2 then @ol_qty2
                when 3 then @ol_qty3
                when 4 then @ol_qty4
                when 5 then @ol_qty5
                when 6 then @ol_qty6
                when 7 then @ol_qty7
                when 8 then @ol_qty8
                when 9 then @ol_qty9
                when 10 then @ol_qty10
                when 11 then @ol_qty11
                when 12 then @ol_qty12
                when 13 then @ol_qty13
                when 14 then @ol_qty14
                when 15 then @ol_qty15
                end

-- get item data (no one updates item)

                select      @i_price = i_price,
                        @i_name  = i_name,
                        @i_data  = i_data
                from item (tablock repeatableread)
                where i_id = @li_id

-- update stock values

                update      stock
                set      s_ytd      = s_ytd + @li_qty,
                        @s_quantity = s_quantity - @li_qty +
                                case when (s_quantity - @li_qty < 10)
                                then 91 else 0 end,
                        s_order_cnt = s_order_cnt + 1,
                        s_remote_cnt = s_remote_cnt + case when (@li_s_w_id =
@s_w_id) then 0 else 1 end,
                        @s_data      = s_data,
                        @s_dist      = case @d_id
                                when 1 then s_dist_01
                                when 2 then s_dist_02
                                when 3 then s_dist_03
                                when 4 then s_dist_04
                                when 5 then s_dist_05
                                when 6 then s_dist_06
                                when 7 then s_dist_07
                                when 8 then s_dist_08
                                when 9 then s_dist_09
                                when 10 then s_dist_10
                                end

                wheres_i_id = @li_id and
                        s_w_id = @li_s_w_id

-- if there actually is a stock (and item) with these ids, go to work

```

```

        if (@@rowcount > 0)
        begin
-- insert order_line data (using data from item and stock)

            insert into order_line values(@o_id,
                @d_id,
                @w_id,
                @li_no,
                @li_id,
                @li_s_w_id,
                "dec 31, 1899",
                @li_qty,
                @i_price * @li_qty,
                @s_dist)

-- send line-item data to client

            select      @i_name,
                @s_quantity,
                b_g = case when ( (patindex("%ORIGINAL%",@i_data) > 0)
and
                (patindex("%ORIGINAL%",@s_data) > 0) )
                then "B" else "G" end,
                @i_price,
                @i_price * @li_qty

            end
            else
            begin

-- no item (or stock) found - triggers rollback condition

                select "",0,"",0,0
                select @commit_flag = 0

            end

            end

-- get customer last name, discount, and credit rating

            select      @c_last      = c_last,
                @c_discount = c_discount,
                @c_credit   = c_credit,
                @c_id_local = c_id
            from customer (repeatableread)
            where c_id      = @c_id and
                c_w_id      = @w_id and
                c_d_id      = @d_id

-- insert fresh row into orders table

```

```

            insert into orders values (      @o_id,
                @d_id,
                @w_id,
                @c_id_local,
                @o_entry_d,
                0,
                @o_ol_cnt,
                @o_all_local)

-- insert corresponding row into new-order table

            insert into new_order values ( @o_id,
                @d_id,
                @w_id)

-- select warehouse tax

            select      @w_tax      = w_tax
            from warehouse (repeatableread)
            where w_id = @w_id

            if (@commit_flag = 1)
                commit transaction n
            else

-- all that work for nuthin!!!

                rollback transaction n

-- return order data to client

            select      @w_tax,
                @d_tax,
                @o_id,
                @c_last,
                @c_discount,
                @c_credit,
                @o_entry_d,
                @commit_flag

            end

            go

ORDSTAT.SQL

-- File:      ORDSTAT.SQL
--            Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--            Copyright Microsoft, 1999, 2000
-- Purpose:   Creates order status transaction stored procedure
--
--            Interface Level: 4.10.000

```

```

use tpcc
go

if exists ( select name from sysobjects where name = "tpcc_orderstatus" )
    drop procedure    tpcc_orderstatus
go

create proc tpcc_orderstatus    @w_idsmallint,
                                @d_idtinyint,
                                @c_idint,
                                @c_last    char(16) = ""
as

declare @c_balance    numeric(12,2),
        @c_first      char(16),
        @c_middle     char(2),
        @o_id         int,
        @o_entry_d    datetime,
        @o_carrier_id smallint,
        @cnt          smallint

begin tran o

if (@c_id = 0)
    begin

-- get customer id and info using last name

        select    @cnt = (count(*)+1)/2
        from customer (repeatableread)
        where c_last = @c_last and
              c_w_id = @w_id and
              c_d_id = @d_id

        set rowcount @cnt

        select    @c_id = c_id,
        @c_balance = c_balance,
        @c_first = c_first,
        @c_last = c_last,
        @c_middle = c_middle
        from customer (repeatableread)
        where c_last = @c_last and
              c_w_id = @w_id and
              c_d_id = @d_id
        order by c_w_id, c_d_id, c_last, c_first

        set rowcount 0
    end
else

```

```

begin

-- get customer info if by id

        select    @c_balance = c_balance,
        @c_first = c_first,
        @c_middle = c_middle,
        @c_last = c_last
        from customer (repeatableread)
        where c_id = @c_id and
              c_d_id = @d_id and
              c_w_id = @w_id

        select    @cnt = @@rowcount

    end

-- if no such customer

    if (@cnt = 0)
        begin
            raiserror("Customer not found",18,1)
            goto custnotfound
        end

-- get order info

        select    @o_id = o_id,
        @o_entry_d = o_entry_d,
        @o_carrier_id = o_carrier_id
        from orders (serializable)
        where o_c_id = @c_id and
              o_d_id = @d_id and
              o_w_id = @w_id
        order by o_id asc

-- select order lines for the current order

        select    ol_supply_w_id,
        ol_i_id,
        ol_quantity,
        ol_amount,
        ol_delivery_d
        from order_line (repeatableread)
        where ol_o_id = @o_id and
              ol_d_id = @d_id and
              ol_w_id = @w_id

custnotfound:

commit tran o

-- return data to client

```

```

select  @c_id,
        @c_last,
        @c_first,
        @c_middle,
        @o_entry_d,
        @o_carrier_id,
        @c_balance,
        @o_id

```

```
go
```

PAYMENT.SQL

```

-- File:      PAYMENT.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--           Copyright Microsoft, 1999, 2000
-- Purpose:   Creates payment transaction stored procedure
--
-- Interface Level: 4.10.000

```

```

use tpcc
go

```

```

if exists (select name from sysobjects where name = "tpcc_payment" )
    drop procedure tpcc_payment
go

```

```

create proc tpcc_payment  @w_id          smallint,
                        @c_w_id        smallint,
                        @h_amount      numeric(6,2),
                        @d_id          tinyint,
                        @c_d_id        tinyint,
                        @c_id          int,
                        @c_last       char(16) = ""

```

```

as
declare  @w_street_1  char(20),
         @w_street_2  char(20),
         @w_city      char(20),
         @w_state     char(2),
         @w_zip       char(9),
         @w_name      char(10),
         @d_street_1  char(20),
         @d_street_2  char(20),
         @d_city      char(20),
         @d_state     char(2),
         @d_zip       char(9),
         @d_name      char(10),
         @c_first     char(16),
         @c_middle    char(2),
         @c_street_1  char(20),

```

```

@c_street_2  char(20),
@c_city      char(20),
@c_state     char(2),
@c_zip       char(9),
@c_phone     char(16),
@c_since     datetime,
@c_credit    char(2),
@c_credit_lim numeric(12,2),
@c_balance   numeric(12,2),
@c_discount  numeric(4,4),
@data       char(500),
@c_data     char(500),
@datetime   datetime,
@w_ytd      numeric(12,2),
@d_ytd      numeric(12,2),
@cnt        smallint,
@val        smallint,
@screen_data char(200),
@d_id_local tinyint,
@w_id_local smallint,
@c_id_local int

```

```
select @screen_data = ""
```

```
begin tran p
```

```
-- get payment date
```

```

select  @datetime = getdate()

if (@c_id = 0)
begin

```

```
-- get customer id and info using last name
```

```

select  @cnt = count(*)
from customer (repeatableread)
where c_last = @c_last and
       c_w_id = @c_w_id and
       c_d_id = @c_d_id

```

```

select  @val = (@cnt + 1) / 2
set rowcount @val

```

```

select  @c_id= c_id
from customer (repeatableread)
where c_last = @c_last and
       c_w_id = @c_w_id and
       c_d_id = @c_d_id

orderby c_last, c_first

```

```
set rowcount 0
```

```
end
```

```

-- get customer info and update balances

update customer
set @c_balance = c_balance = c_balance - @h_amount,
    c_payment_cnt = c_payment_cnt + 1,
    c_ytd_payment = c_ytd_payment + @h_amount,
    @c_first = c_first,
    @c_middle = c_middle,
    @c_last = c_last,
    @c_street_1 = c_street_1,
    @c_street_2 = c_street_2,
    @c_city = c_city,
    @c_state = c_state,
    @c_zip = c_zip,
    @c_phone = c_phone,
    @c_credit = c_credit,
    @c_credit_lim = c_credit_lim,
    @c_discount = c_discount,
    @c_since = c_since,
    @data = c_data,
    @c_id_local = c_id
where c_id = @c_id and
      c_w_id = @c_w_id and
      c_d_id = @c_d_id

-- if customer has bad credit get some more info

if (@c_credit = "BC")
begin

-- compute new info

select @c_data = convert(char(5),@c_id) +
        convert(char(4),@c_d_id) +
        convert(char(5),@c_w_id) +
        convert(char(4),@d_id) +
        convert(char(5),@w_id) +
        convert(char(19),@h_amount) +
        substring(@data, 1, 458)

-- update customer info

update customer
set c_data = @c_data
where c_id = @c_id and
      c_w_id = @c_w_id and
      c_d_id = @c_d_id

select @screen_data = substring (@c_data,1,200)
end

-- get district data and update year-to-date

```

```

update district
set d_ytd = d_ytd + @h_amount,
    @d_street_1 = d_street_1,
    @d_street_2 = d_street_2,
    @d_city = d_city,
    @d_state = d_state,
    @d_zip = d_zip,
    @d_name = d_name,
    @d_id_local = d_id
where d_w_id = @w_id and
      d_id = @d_id

-- get warehouse data and update year-to-date

update warehouse
set w_ytd = w_ytd + @h_amount,
    @w_street_1 = w_street_1,
    @w_street_2 = w_street_2,
    @w_city = w_city,
    @w_state = w_state,
    @w_zip = w_zip,
    @w_name = w_name,
    @w_id_local = w_id
where w_id = @w_id

-- create history record

insert into history values ( @c_id_local,
                            @c_d_id,
                            @c_w_id,
                            @d_id_local,
                            @w_id_local,
                            @datetime,
                            @h_amount,
                            @w_name + " " + @d_name)

commit tran p

-- return data to client

select @c_id,
       @c_last,
       @datetime,
       @w_street_1,
       @w_street_2,
       @w_city,
       @w_state,
       @w_zip,
       @d_street_1,
       @d_street_2,
       @d_city,
       @d_state,
       @d_zip,

```

```

@c_first,
@c_middle,
@c_street_1,
@c_street_2,
@c_city,
@c_state,
@c_zip,
@c_phone,
@c_since,
@c_credit,
@c_credit_lim,
@c_discount,
@c_balance,
@screen_data

```

go

STOCKLEV.SQL

```

-- File:      STOCKLEV.SQL
--            Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--            Copyright Microsoft, 1999, 2000
-- Purpose:   Creates stock level transaction stored procedure
--
-- Interface Level: 4.10.000

```

```

use tpcc
go

```

```

if exists (select name from sysobjects where name = "tpcc_stocklevel" )
    drop procedure tpcc_stocklevel
go

```

```

create proc tpcc_stocklevel    @w_id          smallint,
                               @d_id          tinyint,
                               @threshold    smallint
as

```

```

declare  @o_id_low int,
         @o_id_high int

```

```

select  @o_id_low = (d_next_o_id - 20),
        @o_id_high = (d_next_o_id - 1)
from district
where d_w_id = @w_id and
       d_id = @d_id

```

```

select  count(distinct(s_i_id))
from stock, order_line
where ol_w_id = @w_id and
       ol_d_id = @d_id and
       ol_o_id between @o_id_low and
                    @o_id_high and

```

```

s_w_id      = ol_w_id and
s_i_id      = ol_i_id and
s_quantity < @threshold

```

go

VERSION.SQL

```

-- File:      VERSION.SQL
--            Microsoft TPC-C Benchmark Kit Ver. 4.21.000
--            Copyright Microsoft, 1999, 2000
-- Purpose:   Returns version level of TPC-C stored procs
-- Note:     Always update the return value of this proc for
--           any interface changes or "must have" bug fixes.
--

```

```

-- The value returned by this SP defines the "interface level",
-- which must match between the stored procs and the client code.
-- The interface level may be down rev from the current kit. This
-- indicates that the interface hasn't changed since that version.

```

```

use tpcc
go

```

```

if exists ( select name from sysobjects where name = "tpcc_version" )
    drop procedure tpcc_version
go

```

```

create proc tpcc_version
as
declare  @version char(8)

begin
    select @version = "4.10.000"
    select @version as "Version"
end

```

go

GETARGS.C

```

// File:      GETARGS.C
//            Microsoft TPC-C Kit Ver. 4.20
//            Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for command line processing

```

```

// Includes
#include "tpcc.h"

```

```

//=====
//

```

```

// Function name: GetArgsLoader
//
//=====
void GetArgsLoader(int argc, char **argv, TPCCLDR_ARGS *pargs)
{
    int      i;
    char    *ptr;

#ifdef DEBUG
    printf("[%ld]DBG: Entering GetArgsLoader()\n", (int)
GetCurrentThreadId());
#endif

    /* init args struct with some useful values */
    pargs->server      = SERVER;
    pargs->user         = USER;
    pargs->password     = PASSWORD;
    pargs->database     = DATABASE;
    pargs->batch        = BATCH;
    pargs->num_warehouses = UNDEF;
    pargs->tables_all   = TRUE;
    pargs->table_item   = FALSE;
    pargs->table_warehouse = FALSE;
    pargs->table_customer = FALSE;
    pargs->table_orders  = FALSE;
    pargs->loader_res_file = LOADER_RES_FILE;
    pargs->pack_size     = DEFLDPACKSIZE;
    pargs->starting_warehouse = DEF_STARTING_WAREHOUSE;
    pargs->build_index   = BUILD_INDEX;
    pargs->index_order   = INDEX_ORDER;
    pargs->index_script_path = INDEX_SCRIPT_PATH;
    pargs->scale_down    = SCALE_DOWN;

    /* check for zero command line args */
    if ( argc == 1 )
        GetArgsLoaderUsage();

    for ( i = 1; i < argc; ++i )
    {
        if (argv[i][0] != '-' && argv[i][0] != '/')
        {
            printf("\nUnrecognized command");
            GetArgsLoaderUsage();
            exit(1);
        }

        ptr = argv[i];

        switch (ptr[1])
        {
            case 'h':      /* Fall throught */
            case 'H':

```

```

        GetArgsLoaderUsage();
        break;

        case 'D':
            pargs->database = ptr+2;
            break;

        case 'P':
            pargs->password = ptr+2;
            break;

        case 'S':
            pargs->server = ptr+2;
            break;

        case 'U':
            pargs->user = ptr+2;
            break;

        case 'b':
            pargs->batch = atol(ptr+2);
            break;

        case 'W':
            pargs->num_warehouses = atol(ptr+2);
            break;

        case 's':
            pargs->starting_warehouse = atol(ptr+2);
            break;

        case 't':
            {
                pargs->tables_all = FALSE;
                if (strcmp(ptr+2,"item") == 0)
                    pargs->table_item = TRUE;
                else if (strcmp(ptr+2,"warehouse") == 0)
                    pargs->table_warehouse = TRUE;
                else if (strcmp(ptr+2,"customer") == 0)
                    pargs->table_customer = TRUE;
                else if (strcmp(ptr+2,"orders") == 0)
                    pargs->table_orders = TRUE;
                else
                {
                    printf("\nUnrecognized command");
                    GetArgsLoaderUsage();
                    exit(1);
                }

                break;
            }

        case 'f':

```

```

        pargs->loader_res_file = ptr+2;
        break;

    case 'p':
        pargs->pack_size = atol(ptr+2);
        break;

    case 'i':
        pargs->build_index = atol(ptr+2);
        break;

    case 'o':
        pargs->index_order = atol(ptr+2);
        break;

    case 'c':
        pargs->scale_down = atol(ptr+2);
        break;

    case 'd':
        pargs->index_script_path = ptr+2;
        break;

    default:
        GetArgsLoaderUsage();
        exit(-1);
        break;
}

/* check for required args */
if (pargs->num_warehouses == UNDEF)
{
    printf("Number of Warehouses is required\n");
    exit(-2);
}

return;
}

//=====
//
// Function name: GetArgsLoaderUsage
//
//=====

void GetArgsLoaderUsage()
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering GetArgsLoaderUsage()\n", (int)
GetCurrentThreadId());

```

```

#endif

    printf("TPCCLDR:\n\n");
    printf("Parameter
Default\n");
    printf("-----
\n");
    printf("-W Number of Warehouses to Load           Required
\n");
    printf("-S Server                               %s\n",
SERVER);
    printf("-U Username                               %s\n",
USER);
    printf("-P Password                               %s\n",
PASSWORD);
    printf("-D Database                               %s\n",
DATABASE);
    printf("-b Batch Size                               %ld\n",
(long) BATCH);
    printf("-p TDS packet size                               %ld\n",
(long) DEFLDPAKSIZE);
    printf("-f Loader Results Output Filename           %s\n",
LOADER_RES_FILE);
    printf("-s Starting Warehouse                               %ld\n",
(long) DEF_STARTING_WAREHOUSE);
    printf("-i Build Option (data = 0, data and index = 1)   %ld\n",
(long) BUILD_INDEX);
    printf("-o Cluster Index Build Order (before = 1, after = 0) %ld\n",
(long) INDEX_ORDER);
    printf("-c Build Scaled Database (normal = 0, tiny = 1)   %ld\n",
(long) SCALE_DOWN);
    printf("-d Index Script Path                               %s\n",
INDEX_SCRIPT_PATH);
    printf("-t Table to Load                               all
tables \n");
    printf("    [item|warehouse|customer|orders]\n");
    printf("    Notes: \n");
    printf("    - the '-t' parameter may be included multiple times to
\n");
    printf("    specify multiple tables to be loaded \n");
    printf("    - 'item' loads ITEM table \n");
    printf("    - 'warehouse' loads WAREHOUSE, DISTRICT, and STOCK tables
\n");
    printf("    - 'customer' loads CUSTOMER and HISTORY tables \n");
    printf("    - 'orders' load NEW-ORDER, ORDERS, ORDER-LINE tables \n");

    printf("\nNote: Command line switches are case sensitive.\n");

    exit(0);
}

```

RANDOM.C

```
// File:      RANDOM.C
//           Microsoft TPC-C Kit Ver. 4.20
//           Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Random number generation routines for database loader
```

```
// Includes
#include "tpcc.h"
#include "math.h"
```

```
// Defines
#define A      16807
#define M      2147483647
#define Q      127773      /* M div A */
#define R      2836        /* M mod A */
#define Thread __declspec(thread)
```

```
// Globals
long Thread Seed = 0;      /* thread local seed */
```

```
/******
```

```
***
*
* random -
*
* Implements a GOOD pseudo random number generator. This generator
* will/should? run the complete period before repeating.
```

```
*
* Copied from:
*
* Random Numbers Generators: Good Ones Are Hard to Find.
* Communications of the ACM - October 1988 Volume 31 Number 10
```

```
*
* Machine Dependencies:
*
* long must be 2 ^ 31 - 1 or greater.
```

```
*****
**/
```

```
/******
***
```

```
* seed - load the Seed value used in irand and drand. Should be used before
*
* first call to irand or drand.
```

```
*****
**/
```

```
void seed(long val)
{
```

```
#ifdef DEBUG
    printf("[%ld]DBG: Entering seed()...\n", (int) GetCurrentThreadId());
    printf("Old Seed %ld New Seed %ld\n", Seed, val);
#endif
```

```
if ( val < 0 )
    val = abs(val);
```

```
Seed = val;
```

```
}
```

```
/******
```

```
**
*
* irand - returns a 32 bit integer pseudo random number with a period of
* 1 to 2 ^ 32 - 1.
```

```
*
* parameters:
```

```
* none.
```

```
* returns:
```

```
* 32 bit integer - defined as long ( see above ).
```

```
* side effects:
```

```
* seed get recomputed.
```

```
*****
**/
```

```
long irand()
```

```

{
    register long    s;        /* copy of seed */
    register long    test;     /* test flag */
    register long    hi;       /* tmp value for speed */
    register long    lo;       /* tmp value for speed */

#ifdef DEBUG
    printf("[%ld]DBG: Entering irand()...\n", (int) GetCurrentThreadId());
#endif

    s = Seed;
    hi = s / Q;
    lo = s % Q;

    test = A * lo - R * hi;
    if ( test > 0 )
        Seed = test;
    else
        Seed = test + M;

    return( Seed );
}

/*****
**
*
*
* drand - returns a double pseudo random number between 0.0 and 1.0.
*
*     See irand.
*
*****/
double drand()
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering drand()...\n", (int) GetCurrentThreadId());
#endif

    return( (double)irand() / 2147483647.0);
}

//=====
// Function    : RandomNumber
//
// Description:
//=====
long RandomNumber(long lower, long upper)
{
    long rand_num;

```

```

#ifdef DEBUG
    printf("[%ld]DBG: Entering RandomNumber()...\n", (int)
GetCurrentThreadId());
#endif

    if ( upper == lower )        /* pgd 08-13-96 perf enhancement */
        return lower;

    upper++;

    if ( upper <= lower )
        rand_num = upper;
    else
        rand_num = lower + irand() % (upper - lower); /* pgd 08-13-96 perf
enhancement */

#ifdef DEBUG
    printf("[%ld]DBG: RandomNumber between %ld & %ld ==> %ld\n",
(int) GetCurrentThreadId(), lower, upper, rand_num);
#endif

    return rand_num;
}

#if 0
//Original code pgd 08/13/96
long RandomNumber(long lower,
                  long upper)
{
    long rand_num;

#ifdef DEBUG
    printf("[%ld]DBG: Entering RandomNumber()...\n", (int)
GetCurrentThreadId());
#endif

    upper++;

    if ((upper <= lower))
        rand_num = upper;
    else
        rand_num = lower + irand() % ((upper > lower) ? upper - lower :
upper);

#ifdef DEBUG
    printf("[%ld]DBG: RandomNumber between %ld & %ld ==> %ld\n",

```

```

        (int) GetCurrentThreadId(), lower, upper, rand_num);
#endif

    return rand_num;
}
#endif

//=====
// Function   : NURand
//
// Description:
//=====
long NURand(int iConst,
            long x,
            long y,
            long C)
{
    long rand_num;

#ifdef DEBUG
    printf("[%ld]DBG: Entering NURand()...\n", (int) GetCurrentThreadId());
#endif

    rand_num = (((RandomNumber(0,iConst) | RandomNumber(x,y)) + C) % (y-
x+1))+x;

#ifdef DEBUG
    printf("[%ld]DBG: NURand: num = %d\n", (int) GetCurrentThreadId(),
rand_num);
#endif

    return rand_num;
}

```

STRINGS.C

```

// File:      STRINGS.C
//            Microsoft TPC-C Kit Ver. 4.20
//            Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for database loader string functions

// Includes
#include "tpcc.h"
#include <string.h>
#include <ctype.h>

//=====
//
// Function name: MakeAddress

```

```

//
//=====

void MakeAddress(char *street_1,
                char *street_2,
                char *city,
                char *state,
                char *zip)
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeAddress()\n", (int)
GetCurrentThreadId());
#endif

    MakeAlphaString (10, 20, ADDRESS_LEN, street_1);
    MakeAlphaString (10, 20, ADDRESS_LEN, street_2);
    MakeAlphaString (10, 20, ADDRESS_LEN, city);
    MakeAlphaString ( 2,  2, STATE_LEN, state);
    MakeZipNumberString( 9,  9, ZIP_LEN, zip);

#ifdef DEBUG
    printf("[%ld]DBG: MakeAddress: street_1: %s, street_2: %s, city: %s,
state: %s, zip: %s\n",
           (int) GetCurrentThreadId(), street_1, street_2, city, state,
zip);
#endif

    return;
}

//=====
//
// Function name: LastName
//
//=====

void LastName(int num,
             char *name)
{
    static char *n[] =
    {
        "BAR" , "OUGHT", "ABLE" , "PRI" , "PRES",
        "ESE" , "ANTI" , "CALLY", "ATION", "EING"
    };

#ifdef DEBUG
    printf("[%ld]DBG: Entering LastName()\n", (int) GetCurrentThreadId());
#endif

    if ((num >= 0) && (num < 1000))

```

```

{
    strcpy(name, n[(num/100)%10]);
    strcat(name, n[(num/10)%10]);
    strcat(name, n[(num/1)%10]);

    if (strlen(name) < LAST_NAME_LEN)
    {
        PaddString(LAST_NAME_LEN, name);
    }

}
else
{
    printf("\nError in LastName()... num <%d> out of range
(0,999)\n", num);
    exit(-1);
}

#ifdef DEBUG
    printf("[%ld]DBG: LastName: num = [%d] ==> [%d][%d][%d]\n",
        (int) GetCurrentThreadId(), num, num/100, (num/10)%10,
num%10);
    printf("[%ld]DBG: LastName: String = %s\n", (int) GetCurrentThreadId(),
name);
#endif

    return;
}

//=====
//
// Function name: MakeAlphaString
//
//=====

//philipdu 08/13/96 Changed MakeAlphaString to use A-Z, a-z, and 0-9 in
//accordance with spec see below:
//The spec says:
//4.3.2.2 The notation random a-string [x .. y]
//(respectively, n-string [x .. y]) represents a string of random
alphanumeric
//(respectively, numeric) characters of a random length of minimum x,
maximum y,
//and mean (y+x)/2. Alphanumerics are A..Z, a..z, and 0..9. The only other
//requirement is that the character set used "must be able to represent a
minimum
//of 128 different characters". We are using 8-bit chars, so this is a non
issue.
//It is completely unreasonable to stuff non-printing chars into the text
fields.

```

```

//--CLevine 08/13/96

int MakeAlphaString( int x, int y, int z, char *str)
{
    int len;
    int i;
    char cc = 'a';
    static char chArray[] =
"0123456789ABCDEFGHIJKLMNopqrstuvwxyz";
    static int chArrayMax = 61;

#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeAlphaString()\n", (int)
GetCurrentThreadId());
#endif

    len= RandomNumber(x, y);

    for (i=0; i<len; i++)
    {
        cc = chArray[RandomNumber(0, chArrayMax)];
        str[i] = cc;
    }
    if ( len < z )
        memset(str+len, ' ', z - len);
    str[len] = 0;

    return len;
}

//=====
//
// Function name: MakeOriginalAlphaString
//
//=====

int MakeOriginalAlphaString(int x,
                            int y,
                            int z,
                            char *str,
                            int percent)
{
    int len;
    int val;
    int start;

#ifdef DEBUG
    printf("[%ld]DBG: Entering MakeOriginalAlphaString()\n", (int)
GetCurrentThreadId());
#endif

    // verify percentage is valid

```

```

    if ((percent < 0) || (percent > 100))
    {
        printf("MakeOriginalAlphaString: Invalid percentage: %d\n",
percent);
        exit(-1);
    }

    // verify string is at least 8 chars in length
    if ((x + y) <= 8)
    {
        printf("MakeOriginalAlphaString: string length must be >= 8\n");
        exit(-1);
    }

    // Make Alpha String
    len = MakeAlphaString(x,y, z, str);

    val = RandomNumber(1,100);
    if (val <= percent)
    {
        start = RandomNumber(0, len - 8);
        strncpy(str + start, "ORIGINAL", 8);
    }

#ifdef DEBUG
    printf("[%ld]DBG: MakeOriginalAlphaString: : %s\n",
        (int) GetCurrentThreadId(), str);
#endif

    return strlen(str);
}

//=====
//
// Function name: MakeNumberString
//
//=====
int MakeNumberString(int x, int y, int z, char *str)
{
    char tmp[16];

    //MakeNumberString is always called MakeZipNumberString(16, 16, 16,
string)

    memset(str, '0', 16);
    itoa(RandomNumber(0, 99999999), tmp, 10);
    memcpy(str, tmp, strlen(tmp));

    itoa(RandomNumber(0, 99999999), tmp, 10);
    memcpy(str+8, tmp, strlen(tmp));

```

```

    str[16] = 0;

    return 16;
}

//=====
//
// Function name: MakeZipNumberString
//
//=====
int MakeZipNumberString(int x, int y, int z, char *str)
{
    char tmp[16];

    //MakeZipNumberString is always called MakeZipNumberString(9, 9, 9,
string)

    strcpy(str, "000011111");

    itoa(RandomNumber(0, 9999), tmp, 10);
    memcpy(str, tmp, strlen(tmp));

    return 9;
}

//=====
//
// Function name: InitString
//
//=====
void InitString(char *str, int len)
{
#ifdef DEBUG
    printf("[%ld]DBG: Entering InitString()\n", (int) GetCurrentThreadId());
#endif

    memset(str, ' ', len);
    str[len] = 0;
}

//=====
//
// Function name: InitAddress
//
// Description:
//
//=====
void InitAddress(char *street_1, char *street_2, char *city, char *state,
char *zip)
{

```

```

memset(street_1, ' ', ADDRESS_LEN+1);
memset(street_2, ' ', ADDRESS_LEN+1);
memset(city, ' ', ADDRESS_LEN+1);

street_1[ADDRESS_LEN+1] = 0;
street_2[ADDRESS_LEN+1] = 0;
city[ADDRESS_LEN+1] = 0;

memset(state, ' ', STATE_LEN+1);
state[STATE_LEN+1] = 0;

memset(zip, ' ', ZIP_LEN+1);
zip[ZIP_LEN+1] = 0;
}

```

```

//=====
//
// Function name: PaddString
//
//=====

```

```

void PaddString(int max, char *name)
{
    int    len;

    len = strlen(name);
    if ( len < max )
        memset(name+len, ' ', max - len);
    name[max] = 0;

    return;
}

```

TIME.C

```

// File:      TIME.C
//           Microsoft TPC-C Kit Ver. 4.20
//           Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for time functions

```

```

// Includes
#include "tpcc.h"

```

```

// Globals
static long start_sec;

```

```

//=====
//
// Function name: TimeNow
//

```

```

//=====
long TimeNow()
{
    long    time_now;
    struct _timeb el_time;

#ifdef DEBUG
    printf("[%ld]DBG: Entering TimeNow()\n", (int) GetCurrentThreadId());
#endif

    _ftime(&el_time);

    time_now = ((el_time.time - start_sec) * 1000) + el_time.millitm;

    return time_now;
}

```

TPCC.H

```

// File:      TPCC.H
//           Microsoft TPC-C Kit Ver. 4.20
//           Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Header file for TPC-C database loader

```

```

// Build number of TPC Benchmark Kit
#define TPCKIT_VER    "4.20"

```

```

// General headers
#include <windows.h>
#include <winbase.h>
#include <stdlib.h>
#include <stdio.h>
#include <process.h>
#include <stddef.h>
#include <stdarg.h>
#include <string.h>
#include <time.h>
#include <sys\timeb.h>
#include <sys\types.h>

```

```

// ODBC headers
#include <sql.h>
#include <sqlext.h>
#include <odbcss.h>

```

```

// General constants
#define MILLI            1000
#define FALSE            0
#define TRUE             1

```

```

#define UNDEF                -1
#define MINPRINTASCII       32
#define MAXPRINTASCII       126

// Default environment constants
#define SERVER                ""
#define DATABASE              "tpcc"
#define USER                  "sa"
#define PASSWORD              ""

// Default loader arguments
#define BATCH                  10000
#define DEFLOADPACKSIZE      32768
#define LOADER_RES_FILE      "logs\\load.out"
#define LOADER_NURAND_C      123
#define DEF_STARTING_WAREHOUSE 1
#define BUILD_INDEX          1 // build both data and
indexes
#define INDEX_ORDER          1 // build indexes before load
#define SCALE_DOWN          0 // build a normal scale
database
#define INDEX_SCRIPT_PATH   "scripts"

typedef struct
{
    char            *server;
    char            *database;
    char            *user;
    char            *password;
    BOOL            tables_all; // set if loading all
tables
    BOOL            table_item; // set if loading ITEM
table specifically
    BOOL            table_warehouse; // set if loading WAREHOUSE,
DISTRICT, and STOCK
    BOOL            table_customer; // set if loading CUSTOMER
and HISTORY
    BOOL            table_orders; // set if loading NEW-ORDER,
ORDERS, ORDER-LINE
    long            num_warehouses;
    long            batch;
    long            verbose;
    long            pack_size;
    char            *loader_res_file;
    char            *synch_servername;
    long            case_sensitivity;
    long            starting_warehouse;
    long            build_index;
    long            index_order;
    long            scale_down;
    char            *index_script_path;
} TPCCLDR_ARGS;

```

```

// String length constants
#define SERVER_NAME_LEN      20
#define DATABASE_NAME_LEN   20
#define USER_NAME_LEN       20
#define PASSWORD_LEN        20
#define TABLE_NAME_LEN    20
#define I_DATA_LEN          50
#define I_NAME_LEN          24
#define BRAND_LEN           1
#define LAST_NAME_LEN       16
#define W_NAME_LEN          10
#define ADDRESS_LEN         20
#define STATE_LEN           2
#define ZIP_LEN              9
#define S_DIST_LEN          24
#define S_DATA_LEN          50
#define D_NAME_LEN          10
#define FIRST_NAME_LEN      16
#define MIDDLE_NAME_LEN     2
#define PHONE_LEN           16
#define CREDIT_LEN          2
#define C_DATA_LEN          500
#define H_DATA_LEN          24
#define DIST_INFO_LEN       24
#define MAX_OL_NEW_ORDER_ITEMS 15
#define MAX_OL_ORDER_STATUS_ITEMS 15
#define STATUS_LEN          25
#define OL_DIST_INFO_LEN    24
#define C_SINCE_LEN         23
#define H_DATE_LEN          23
#define OL_DELIVERY_D_LEN   23
#define O_ENTRY_D_LEN       23

// Functions in random.c
void seed();
long irand();
double drand();
void WUCreate();
short WURand();
long RandomNumber(long lower, long upper);

// Functions in getargs.c;
void GetArgsLoader();
void GetArgsLoaderUsage();

// Functions in time.c
long TimeNow();

// Functions in strings.c
void MakeAddress();
void LastName();
int MakeAlphaString();

```

```

int MakeOriginalAlphaString();
int MakeNumberString();
int MakeZipNumberString();
void InitString();
void InitAddress();
void PaddString();

```

TPCCLDR.C

```

// File:      TPCCLDR.C
//           Microsoft TPC-C Kit Ver. 4.20
//           Copyright Microsoft, 1996, 1997, 1998, 1999
// Purpose:   Source file for TPC-C database loader

```

```

// Includes
#include "tpcc.h"
#include "search.h"

```

```

// Defines
#define MAXITEMS          100000
#define MAXITEMS_SCALE_DOWN 100
#define CUSTOMERS_PER_DISTRICT 3000
#define CUSTOMERS_SCALE_DOWN 30
#define DISTRICT_PER_WAREHOUSE 10
#define ORDERS_PER_DISTRICT 3000
#define ORDERS_SCALE_DOWN 30
#define MAX_CUSTOMER_THREADS 2
#define MAX_ORDER_THREADS 3
#define MAX_MAIN_THREADS 4

```

```

// Functions declarations

```

```

void HandleErrorDBC (SQLHDBC hdbc1);

```

```

void CheckSQL();
void CheckDataBase();

```

```

long NURand();
void LoadItem();
void LoadWarehouse();

```

```

void Stock();
void District();

```

```

void LoadCustomer();
void CustomerBufInit();
void CustomerBufLoad();
void LoadCustomerTable();
void LoadHistoryTable();

```

```

void LoadOrders();
void OrdersBufInit();

```

```

void OrdersBufLoad();
void LoadOrdersTable();
void LoadNewOrderTable();
void LoadOrderLineTable();
void GetPermutation();
void CheckForCommit();
void OpenConnections();
void BuildIndex();
void FormatDate ();

```

```

// Shared memory structures

```

```

typedef struct
{
    long          ol_i_id;
    long          ol_supply_w_id;
    short         ol_quantity;
    double        ol_amount;
    char          ol_dist_info[DIST_INFO_LEN+1];
    char          ol_delivery_d[OL_DELIVERY_D_LEN+1];
} ORDER_LINE_STRUCT;

```

```

typedef struct
{
    long          o_id;
    short        o_d_id;
    short        o_w_id;
    long         o_c_id;
    short        o_carrier_id;
    short        o_ol_cnt;
    short        o_all_local;
    ORDER_LINE_STRUCT o_ol[15];
} ORDERS_STRUCT;

```

```

typedef struct
{
    long          c_id;
    short        c_d_id;
    short        c_w_id;
    char         c_first[FIRST_NAME_LEN+1];
    char         c_middle[MIDDLE_NAME_LEN+1];
    char         c_last[LAST_NAME_LEN+1];
    char         c_street_1[ADDRESS_LEN+1];
    char         c_street_2[ADDRESS_LEN+1];
    char         c_city[ADDRESS_LEN+1];
    char         c_state[STATE_LEN+1];
    char         c_zip[ZIP_LEN+1];
    char         c_phone[PHONE_LEN+1];
    char         c_credit[CREDIT_LEN+1];
    double       c_credit_lim;
    double       c_discount;
}

```

```

// fix to avoid ODBC float to numeric conversion problem.

```

```

// double      c_balance;
// char        c_balance[6];

double        c_ytd_payment;
short         c_payment_cnt;
short         c_delivery_cnt;
char          c_data[C_DATA_LEN+1];
double        h_amount;
char          h_data[H_DATA_LEN+1];
} CUSTOMER_STRUCT;

typedef struct
{
    char        c_last[LAST_NAME_LEN+1];
    char        c_first[FIRST_NAME_LEN+1];
    long        c_id;
} CUSTOMER_SORT_STRUCT;

typedef struct
{
    long        time_start;
} LOADER_TIME_STRUCT;

// Global variables

char szLastError[300];

HENV henv;

HDBC v_hdbc; // for SQL Server version
verification
HDBC i_hdbc1; // for ITEM table
HDBC w_hdbc1; // for WAREHOUSE, DISTRICT, STOCK
HDBC c_hdbc1; // for CUSTOMER
HDBC c_hdbc2; // for HISTORY
HDBC o_hdbc1; // for ORDERS
HDBC o_hdbc2; // for NEW-ORDER
HDBC o_hdbc3; // for ORDER-LINE

HSTMTv_hstmt; // for SQL Server version verification
HSTMTi_hstmt1;
HSTMTw_hstmt1;
HSTMTc_hstmt1, c_hstmt2;
HSTMTo_hstmt1, o_hstmt2, o_hstmt3;

ORDERS_STRUCT orders_buf[ORDERS_PER_DISTRICT];
CUSTOMER_STRUCT customer_buf[CUSTOMERS_PER_DISTRICT];
long orders_rows_loaded;
long new_order_rows_loaded;
long order_line_rows_loaded;
long history_rows_loaded;
long customer_rows_loaded;

```

```

long stock_rows_loaded;
long district_rows_loaded;
long item_rows_loaded;
long warehouse_rows_loaded;
long main_time_start;
long main_time_end;
long max_items;
long customers_per_district;
long orders_per_district;
long first_new_order;
long last_new_order;

TPCCCLR_ARGS *aptr, args;

//=====
//
// Function name: main
//
//=====

int main(int argc, char **argv)
{
    DWORD dwThreadId[MAX_MAIN_THREADS];
    HANDLE hThread[MAX_MAIN_THREADS];
    FILE *fLoader;
    char buffer[255];
    int i;

    for (i=0; i<MAX_MAIN_THREADS; i++)
        hThread[i] = NULL;

    printf("\n*****");
    printf("\n* ");
    printf("\n* Microsoft SQL Server ");
    printf("\n* ");
    printf("\n* TPC-C BENCHMARK KIT: Database loader ");
    printf("\n* Version %s ");
    TPCKIT_VER);
    printf("\n* ");
    printf("\n*****\n\n");

    // process command line arguments

    aptr = &args;
    GetArgsLoader(argc, argv, aptr);

    // verify correct SQL Server version in use
    // you must be using SQL Server 7.00.623 or better to load

    CheckSQL();
}

```

```

// verify database and tables exist before attempting to load
CheckDataBase();

printf("Build interface is ODBC.\n");

if (aptr->build_index == 0)
    printf("Data load only - no index creation.\n");
else
    printf("Data load and index creation.\n");

if (aptr->index_order == 0)
    printf("Clustered indexes will be created after bulk load.\n");
else
    printf("Clustered indexes will be created before bulk load.\n");

// set database scale values
if (aptr->scale_down == 1)
{
    printf("*** Scaled Down Database ***\n");
    max_items = MAXITEMS_SCALE_DOWN;
    customers_per_district = CUSTOMERS_SCALE_DOWN;
    orders_per_district = ORDERS_SCALE_DOWN;
    first_new_order = 0;
    last_new_order = 30;
}
else
{
    max_items = MAXITEMS;
    customers_per_district = CUSTOMERS_PER_DISTRICT;
    orders_per_district = ORDERS_PER_DISTRICT;
    first_new_order = 2100;
    last_new_order = 3000;
}

// open connections to SQL Server
OpenConnections();

// open file for loader results
fLoader = fopen(aptr->loader_res_file, "w");

if (fLoader == NULL)
{
    printf("Error, loader result file open failed.");
    exit(-1);
}

// start loading data

```

```

sprintf(buffer,"TPC-C load started for %ld warehouses.\n",aptr-
>num_warehouses);

printf("%s",buffer);
fprintf(fLoader,"%s",buffer);

main_time_start = (TimeNow() / MILLI);

// start parallel load threads

if (aptr->tables_all || aptr->table_item)
{
    fprintf(fLoader, "\nStarting loader threads for: item\n");

    hThread[0] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadItem,
                                NULL,
                                0,
                                &dwThreadID[0]);

    if (hThread[0] == NULL)
    {
        printf("Error, failed in creating creating thread = 0.\n");
        exit(-1);
    }
}

if (aptr->tables_all || aptr->table_warehouse)
{
    fprintf(fLoader, "Starting loader threads for: warehouse\n");

    hThread[1] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadWarehouse,
                                NULL,
                                0,
                                &dwThreadID[1]);

    if (hThread[1] == NULL)
    {
        printf("Error, failed in creating creating thread = 1.\n");
        exit(-1);
    }
}

if (aptr->tables_all || aptr->table_customer)
{
    fprintf(fLoader, "Starting loader threads for: customer\n");
}

```

```

        hThread[2] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadCustomer,
                                NULL,
                                0,
                                &dwThreadID[2]);

        if (hThread[2] == NULL)
        {
            printf("Error, failed in creating creating main thread =
2.\n");
            exit(-1);
        }

        if (aptr->tables_all || aptr->table_orders)
        {
            fprintf(fLoader, "Starting loader threads for: orders\n");

            hThread[3] = CreateThread(NULL,
                                    0,
                                    (LPTHREAD_START_ROUTINE)
LoadOrders,
                                    NULL,
                                    0,
                                    &dwThreadID[3]);

            if (hThread[3] == NULL)
            {
                printf("Error, failed in creating creating main thread =
3.\n");
                exit(-1);
            }

            // Wait for threads to finish...
            for (i=0; i<MAX_MAIN_THREADS; i++)
            {
                if (hThread[i] != NULL)
                {
                    WaitForSingleObject( hThread[i], INFINITE );
                    CloseHandle(hThread[i]);
                    hThread[i] = NULL;
                }
            }

            main_time_end = (TimeNow() / MILLI);

            sprintf(buffer, "\nTPC-C load completed successfully in %ld minutes.\n",
                    (main_time_end - main_time_start)/60);

            printf("%s", buffer);

```

```

        fprintf(fLoader, "%s", buffer);

        fclose(fLoader);

        SQLFreeEnv(henv);

        exit(0);

        return 0;
    }

//=====
//
// Function name: LoadItem
//
//=====

void LoadItem()
{
    long         i_id;
    long         i_im_id;
    char         i_name[I_NAME_LEN+1];
    double       i_price;
    char         i_data[I_DATA_LEN+1];
    char         name[20];
    long         time_start;
    RETCODE      rc;
    DBINT        rcint;
    char         bcphint[128];

    // Seed with unique number
    seed(1);

    printf("Loading item table...\n");

    // if build index before load
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxitmcl");

    InitString(i_name, I_NAME_LEN+1);
    InitString(i_data, I_DATA_LEN+1);

    sprintf(name, "%s..%s", aptr->database, "item");

    rc = bcp_init(i_hdbc1, name, NULL, "logs\\item.err", DB_IN);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (i_id), ROWS_PER_BATCH =
100000");

```

```

        rc = bcp_control(i_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEEDED)
            HandleErrorDBC(i_hdbc1);
    }

    rc = bcp_bind(i_hdbc1, (BYTE *) &i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    rc = bcp_bind(i_hdbc1, (BYTE *) &i_im_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 2);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    rc = bcp_bind(i_hdbc1, (BYTE *) i_name, 0, I_NAME_LEN, NULL, 0, 0, 3);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    rc = bcp_bind(i_hdbc1, (BYTE *) &i_price, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 4);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    rc = bcp_bind(i_hdbc1, (BYTE *) i_data, 0, I_DATA_LEN, NULL, 0, 0, 5);
    if (rc != SUCCEEDED)
        HandleErrorDBC(i_hdbc1);

    time_start = (TimeNow() / MILLI);

    item_rows_loaded = 0;

    for (i_id = 1; i_id <= max_items; i_id++)
    {
        i_im_id = RandomNumber(1L, 10000L);

        MakeAlphaString(14, 24, I_NAME_LEN, i_name);

        i_price = ((float) RandomNumber(100L, 10000L))/100.0;

        MakeOriginalAlphaString(26, 50, I_DATA_LEN, i_data, 10);

        rc = bcp_sendrow(i_hdbc1);
        if (rc != SUCCEEDED)
            HandleErrorDBC(i_hdbc1);

        item_rows_loaded++;
        CheckForCommit(i_hdbc1, i_hstmt1, item_rows_loaded, "item",
&time_start);
    }

    rcint = bcp_done(i_hdbc1);
    if (rcint < 0)

```

```

        HandleErrorDBC(i_hdbc1);

    printf("Finished loading item table.\n");

    SQLFreeStmt(i_hstmt1, SQL_DROP);
    SQLDisconnect(i_hdbc1);
    SQLFreeConnect(i_hdbc1);

    // if build index after load
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
        BuildIndex("idxitmcl");
}

//=====
//
// Function : LoadWarehouse
//
// Loads WAREHOUSE table and loads Stock and District as Warehouses are
created
//
//=====
void LoadWarehouse()
{
    short w_id;
    char w_name[W_NAME_LEN+1];
    char w_street_1[ADDRESS_LEN+1];
    char w_street_2[ADDRESS_LEN+1];
    char w_city[ADDRESS_LEN+1];
    char w_state[STATE_LEN+1];
    char w_zip[ZIP_LEN+1];
    double w_tax;
    double w_ytd;
    char name[20];
    long time_start;
    RETCODE rc;
    DBINT rcint;
    char bcphint[128];

    // Seed with unique number
    seed(2);

    printf("Loading warehouse table...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxwarcl");

```

```

InitString(w_name, W_NAME_LEN+1);
InitAddress(w_street_1, w_street_2, w_city, w_state, w_zip);

sprintf(name, "%s..%s", aptr->database, "warehouse");

rc = bcp_init(w_hdbc1, name, NULL, "logs\\whouse.err", DB_IN);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

if ((aptr->build_index == 1) && (aptr->index_order == 1))
{
    sprintf(bcphint, "tablock, order (w_id), ROWS_PER_BATCH = %d",
aptr->num_warehouses);
    rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
}

rc = bcp_bind(w_hdbc1, (BYTE *) &w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 1);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) w_name, 0, W_NAME_LEN, NULL, 0, 0, 2);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) w_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
3);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) w_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
4);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) w_city, 0, ADDRESS_LEN, NULL, 0, 0, 5);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) w_state, 0, STATE_LEN, NULL, 0, 0, 6);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) w_zip, 0, ZIP_LEN, NULL, 0, 0, 7);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &w_tax, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 8);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

```

```

rc = bcp_bind(w_hdbc1, (BYTE *) &w_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 9);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

time_start = (TimeNow() / MILLI);

warehouse_rows_loaded = 0;

for (w_id = (short)aptr->starting_warehouse; w_id <= aptr-
>num_warehouses; w_id++)
{
    MakeAlphaString(6,10, W_NAME_LEN, w_name);

    MakeAddress(w_street_1, w_street_2, w_city, w_state, w_zip);

    w_tax = ((float) RandomNumber(0L,2000L))/10000.00;

    w_ytd = 300000.00;

    rc = bcp_sendrow(w_hdbc1);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    warehouse_rows_loaded++;
    CheckForCommit(w_hdbc1, i_hstmt1, warehouse_rows_loaded,
"warehouse", &time_start);
}

rcint = bcp_done(w_hdbc1);
if (rcint < 0)
    HandleErrorDBC(w_hdbc1);

printf("Finished loading warehouse table.\n");

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxwarcl");

stock_rows_loaded = 0;
district_rows_loaded = 0;

District();
Stock();
}

//=====
//
// Function : District
//

```

```

//=====
void District()
{
    short d_id;
    short d_w_id;
    char d_name[D_NAME_LEN+1];
    char d_street_1[ADDRESS_LEN+1];
    char d_street_2[ADDRESS_LEN+1];
    char d_city[ADDRESS_LEN+1];
    char d_state[STATE_LEN+1];
    char d_zip[ZIP_LEN+1];
    double d_tax;
    double d_ytd;
    char name[20];
    long d_next_o_id;
    long time_start;
    int w_id;
    RETCODE rc;
    DBINTRcint;
    char bcphint[128];

    // Seed with unique number
    seed(4);

    printf("Loading district table...\n");

    // build index before load
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxdiscl");

    InitString(d_name, D_NAME_LEN+1);
    InitAddress(d_street_1, d_street_2, d_city, d_state, d_zip);
    sprintf(name, "%s..%s", aptr->database, "district");

    rc = bcp_init(w_hdbc1, name, NULL, "logs\\district.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (d_w_id, d_id), ROWS_PER_BATCH =
%u", (aptr->num_warehouses * 10));
        rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(w_hdbc1);
    }

    rc = bcp_bind(w_hdbc1, (BYTE *) &d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);
}

```

```

    rc = bcp_bind(w_hdbc1, (BYTE *) &d_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) d_name, 0, D_NAME_LEN, NULL, 0, 0, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) d_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
4);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) d_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
5);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) d_city, 0, ADDRESS_LEN, NULL, 0, 0, 6);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) d_state, 0, STATE_LEN, NULL, 0, 0, 7);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) d_zip, 0, ZIP_LEN, NULL, 0, 0, 8);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) &d_tax, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 9);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) &d_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 10);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) &d_next_o_id, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT4, 11);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    d_ytd = 30000.0;

    d_next_o_id = orders_per_district+1;

    time_start = (TimeNow() / MILLI);
}

```

```

    for (w_id = aptr->starting_warehouse; w_id <= aptr->num_warehouses;
        w_id++)
    {
        d_w_id = w_id;

        for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
        {
            MakeAlphaString(6,10,D_NAME_LEN, d_name);

            MakeAddress(d_street_1, d_street_2, d_city, d_state, d_zip);

            d_tax = ((float) RandomNumber(0L,2000L))/10000.00;

            rc = bcp_sendrow(w_hdbc1);
            if (rc != SUCCEED)
                HandleErrorDBC(w_hdbc1);

            district_rows_loaded++;
            CheckForCommit(w_hdbc1, w_hstmt1, district_rows_loaded,
                "district", &time_start);
        }

        rcint = bcp_done(w_hdbc1);
        if (rcint < 0)
            HandleErrorDBC(w_hdbc1);

        printf("Finished loading district table.\n");

        // if build index after load...
        if ((aptr->build_index == 1) && (aptr->index_order == 0))
            BuildIndex("idxdiscl");

    return;
}

//=====
//
// Function   : Stock
//
//=====

void Stock()
{
    long   s_i_id;
    short  s_w_id;
    short  s_quantity;
    char   s_dist_01[S_DIST_LEN+1];
    char   s_dist_02[S_DIST_LEN+1];
    char   s_dist_03[S_DIST_LEN+1];
    char   s_dist_04[S_DIST_LEN+1];
    char   s_dist_05[S_DIST_LEN+1];

```

```

    char   s_dist_06[S_DIST_LEN+1];
    char   s_dist_07[S_DIST_LEN+1];
    char   s_dist_08[S_DIST_LEN+1];
    char   s_dist_09[S_DIST_LEN+1];
    char   s_dist_10[S_DIST_LEN+1];
    long   s_ytd;
    short  s_order_cnt;
    short  s_remote_cnt;
    char   s_data[S_DATA_LEN+1];
    short  len;
    char   name[20];
    long   time_start;
    RETCODE rc;
    DBINT rcint;
    char   bcphint[128];

    // Seed with unique number
    seed(3);

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxstkcl");

    sprintf(name, "%s..%s", aptr->database, "stock");

    rc = bcp_init(w_hdbc1, name, NULL, "logs\\stock.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (s_i_id, s_w_id), ROWS_PER_BATCH
= %u", (aptr->num_warehouses * 100000));
        rc = bcp_control(w_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(w_hdbc1);
    }

    rc = bcp_bind(w_hdbc1, (BYTE *) &s_i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    bcp_bind(w_hdbc1, (BYTE *) &s_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = bcp_bind(w_hdbc1, (BYTE *) &s_quantity, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

```

```

4);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_01, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

5);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_02, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

6);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_03, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

7);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_04, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

8);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_05, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

9);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_06, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

10);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_07, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

11);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_08, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

12);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_09, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

13);
rc = bcp_bind(w_hdbc1, (BYTE *) s_dist_10, 0, S_DIST_LEN, NULL, 0, 0,
);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &s_ytd, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 14);
if (rc != SUCCEED)

```

```

    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &s_order_cnt, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 15);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) &s_remote_cnt, 0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 16);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

rc = bcp_bind(w_hdbc1, (BYTE *) s_data, 0, S_DATA_LEN, NULL, 0, 0, 17);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

s_ytd = s_order_cnt = s_remote_cnt = 0;

time_start = (TimeNow() / MILLI);

printf("...Loading stock table\n");

for (s_i_id=1; s_i_id <= max_items; s_i_id++)
{

    for (s_w_id = (short)aptr->starting_warehouse; s_w_id <= aptr-
>num_warehouses; s_w_id++)
    {

        s_quantity = (short)RandomNumber(10L,100L);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_01);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_02);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_03);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_04);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_05);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_06);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_07);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_08);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_09);
        len = MakeAlphaString(24,24,S_DIST_LEN, s_dist_10);

        len = MakeOriginalAlphaString(26,50, S_DATA_LEN, s_data,10);

rc = bcp_sendrow(w_hdbc1);
if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

stock_rows_loaded++;
CheckForCommit(w_hdbc1, w_hstmt1, stock_rows_loaded, "stock",
&time_start);
    }
}

```

```

rcint = bcp_done(w_hdbc1);
if (rcint < 0)
    HandleErrorDBC(w_hdbc1);

printf("Finished loading stock table.\n");

SQLFreeStmt(w_hstmt1, SQL_DROP);
SQLDisconnect(w_hdbc1);
SQLFreeConnect(w_hdbc1);

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxstkcl");

return;
}

//=====
//
// Function   : LoadCustomer
//
//=====

void LoadCustomer()
{
    LOADER_TIME_STRUCT    customer_time_start;
    LOADER_TIME_STRUCT    history_time_start;
    short                w_id;
    short                d_id;
    DWORD                dwThreadID[MAX_CUSTOMER_THREADS];
    HANDLE                hThread[MAX_CUSTOMER_THREADS];
    char                 name[20];
    RETCODE               rc;
    DBINT                rcint;
    char                 bcphint[128];
    char                 cmd[256];
    // SQLRETURN           rc_1;
    // SQLSMALLINT         recnum, MsgLen;
    // SQLCHAR             SqlState[6],
Msg[SQL_MAX_MESSAGE_LENGTH];
    // SQLINTEGER          NativeError;

    // Seed with unique number
    seed(5);

    printf("Loading customer and history tables...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
        BuildIndex("idxcuscl");

```

```

// Initialize bulk copy
sprintf(name, "%s..%s", aptr->database, "customer");

rc = bcp_init(c_hdbc1, name, NULL, "logs\\customer.err", DB_IN);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

if ((aptr->build_index == 1) && (aptr->index_order == 1))
{
    sprintf(bcphint, "tablock, order (c_w_id, c_d_id, c_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 30000));
    rc = bcp_control(c_hdbc1, BCPHINTS, (void*) bcphint);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc1);
}

sprintf(name, "%s..%s", aptr->database, "history");

rc = bcp_init(c_hdbc2, name, NULL, "logs\\history.err", DB_IN);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc2);

sprintf(bcphint, "tablock");
rc = bcp_control(c_hdbc2, BCPHINTS, (void*) bcphint);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc2);

customer_rows_loaded    = 0;
history_rows_loaded     = 0;

CustomerBufInit();

customer_time_start.time_start = (TimeNow() / MILLI);
history_time_start.time_start = (TimeNow() / MILLI);

for (w_id = (short)aptr->starting_warehouse; w_id <= aptr-
>num_warehouses; w_id++)
{
    for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
    {
        CustomerBufLoad(d_id, w_id);

        // Start parallel loading threads here...

        // Start customer table thread

        printf("...Loading customer table for: d_id = %d, w_id =
%d\n", d_id, w_id);

        hThread[0] = CreateThread(NULL,
                                0,

```

```

                                (LPTHREAD_START_ROUTINE)
LoadCustomerTable,
                                &customer_time_start,
                                0,
                                &dwThreadID[0]);

    if (hThread[0] == NULL)
    {
        printf("Error, failed in creating creating thread =
0.\n");
        exit(-1);
    }

    // Start History table thread

    printf("...Loading history table for: d_id = %d, w_id =
%d\n", d_id, w_id);

    hThread[1] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadHistoryTable,
                                &history_time_start,
                                0,
                                &dwThreadID[1]);

    if (hThread[1] == NULL)
    {
        printf("Error, failed in creating creating thread =
1.\n");
        exit(-1);
    }

    WaitForSingleObject( hThread[0], INFINITE );
    WaitForSingleObject( hThread[1], INFINITE );

    if (CloseHandle(hThread[0]) == FALSE)
    {
        printf("Error, failed in closing customer thread handle
with errno: %d\n", GetLastError());
    }

    if (CloseHandle(hThread[1]) == FALSE)
    {
        printf("Error, failed in closing history thread handle
with errno: %d\n", GetLastError());
    }

}
}

```

```

// flush the bulk connection
rcint = bcp_done(c_hdbc1);
if (rcint < 0)
    HandleErrorDBC(c_hdbc1);

rcint = bcp_done(c_hdbc2);
if (rcint < 0)
    HandleErrorDBC(c_hdbc2);

printf("Finished loading customer table.\n");

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxcuscl");

// build non-clustered index
if (aptr->build_index == 1)
    BuildIndex("idxcusnc");

// Output the NURAND used for the loader into C_FIRST for C_ID = 1,
// C_W_ID = 1, and C_D_ID = 1
sprintf(cmd, "isql -S%s -U%s -P%s -d%s -e -Q\"update customer set
c_first = 'C_LOAD = %d' where c_id = 1 and c_w_id = 1 and c_d_id = 1\" >
logs\\nurand_load.log",
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database,
        LOADER_NURAND_C);

system(cmd);

SQLFreeStmt(c_hstmt1, SQL_DROP);
SQLDisconnect(c_hdbc1);
SQLFreeConnect(c_hdbc1);

SQLFreeStmt(c_hstmt2, SQL_DROP);
SQLDisconnect(c_hdbc2);
SQLFreeConnect(c_hdbc2);

return;
}

//=====
//
// Function : CustomerBufInit
//
//=====

void CustomerBufInit()

```

```

{
    int    i;

    for (i=0;i<customers_per_district;i++)
    {
        customer_buf[i].c_id = 0;
        customer_buf[i].c_d_id = 0;
        customer_buf[i].c_w_id = 0;

        strcpy(customer_buf[i].c_first,"");
        strcpy(customer_buf[i].c_middle,"");
        strcpy(customer_buf[i].c_last,"");
        strcpy(customer_buf[i].c_street_1,"");
        strcpy(customer_buf[i].c_street_2,"");
        strcpy(customer_buf[i].c_city,"");
        strcpy(customer_buf[i].c_state,"");
        strcpy(customer_buf[i].c_zip,"");
        strcpy(customer_buf[i].c_phone,"");
        strcpy(customer_buf[i].c_credit,"");

        customer_buf[i].c_credit_lim = 0;
        customer_buf[i].c_discount = (float) 0;

        //  fix to avoid ODBC float to numeric conversion problem.
        //  customer_buf[i].c_balance = 0;
        strcpy(customer_buf[i].c_balance,"");

        customer_buf[i].c_ytd_payment = 0;
        customer_buf[i].c_payment_cnt = 0;
        customer_buf[i].c_delivery_cnt = 0;

        strcpy(customer_buf[i].c_data,"");

        customer_buf[i].h_amount = 0;

        strcpy(customer_buf[i].h_data,"");
    }
}

//=====================================================
//
// Function    : CustomerBufLoad
//
// Fills shared buffer for HISTORY and CUSTOMER
//=====================================================

void CustomerBufLoad(int d_id, int w_id)
{
    long          i;
    CUSTOMER_SORT_STRUCT  c[CUSTOMERS_PER_DISTRICT];

```

```

    for (i=0;i<customers_per_district;i++)
    {
        if (i < 1000)
            LastName(i, c[i].c_last);
        else
            LastName(NURand(255,0,999,LOADER_NURAND_C), c[i].c_last);

        MakeAlphaString(8,16,FIRST_NAME_LEN, c[i].c_first);

        c[i].c_id = i+1;
    }

    printf("...Loading customer buffer for: d_id = %d, w_id = %d\n",
           d_id, w_id);

    for (i=0;i<customers_per_district;i++)
    {

        customer_buf[i].c_d_id = d_id;
        customer_buf[i].c_w_id = w_id;
        customer_buf[i].h_amount = 10.0;

        customer_buf[i].c_ytd_payment = 10.0;

        customer_buf[i].c_payment_cnt = 1;
        customer_buf[i].c_delivery_cnt = 0;

        // Generate CUSTOMER and HISTORY data

        customer_buf[i].c_id = c[i].c_id;

        strcpy(customer_buf[i].c_first, c[i].c_first);
        strcpy(customer_buf[i].c_last, c[i].c_last);

        customer_buf[i].c_middle[0] = 'O';
        customer_buf[i].c_middle[1] = 'E';

        MakeAddress(customer_buf[i].c_street_1,
                   customer_buf[i].c_street_2,
                   customer_buf[i].c_city,
                   customer_buf[i].c_state,
                   customer_buf[i].c_zip);

        MakeNumberString(16, 16, PHONE_LEN, customer_buf[i].c_phone);

        if (RandomNumber(1L, 100L) > 10)
            customer_buf[i].c_credit[0] = 'G';
        else
            customer_buf[i].c_credit[0] = 'B';
        customer_buf[i].c_credit[1] = 'C';

```

```

customer_buf[i].c_credit_lim = 50000.0;
customer_buf[i].c_discount = ((float) RandomNumber(0L, 5000L)) /
10000.0;

// fix to avoid ODBC float to numeric conversion problem.

// customer_buf[i].c_balance = -10.0;
strcpy(customer_buf[i].c_balance, "-10.0");

MakeAlphaString(300, 500, C_DATA_LEN, customer_buf[i].c_data);

// Generate HISTORY data
MakeAlphaString(12, 24, H_DATA_LEN, customer_buf[i].h_data);
}
}

//=====
//
// Function : LoadCustomerTable
//
//=====

void LoadCustomerTable(LOADER_TIME_STRUCT *customer_time_start)
{
    int            i;
    long           c_id;
    short          c_d_id;
    short          c_w_id;
    char           c_first[FIRST_NAME_LEN+1];
    char           c_middle[MIDDLE_NAME_LEN+1];
    char           c_last[LAST_NAME_LEN+1];
    char           c_street_1[ADDRESS_LEN+1];
    char           c_street_2[ADDRESS_LEN+1];
    char           c_city[ADDRESS_LEN+1];
    char           c_state[STATE_LEN+1];
    char           c_zip[ZIP_LEN+1];
    char           c_phone[PHONE_LEN+1];
    char           c_credit[CREDIT_LEN+1];
    double         c_credit_lim;
    double         c_discount;

    // fix to avoid ODBC float to numeric conversion problem.
    // double       c_balance;
    char           c_balance[6];

    double         c_ytd_payment;
    short          c_payment_cnt;
    short          c_delivery_cnt;
    char           c_data[C_DATA_LEN+1];
    char           c_since[C_SINCE_LEN+1];

```

```

RETCODE          rc;

rc = bcp_bind(c_hdbc1, (BYTE *) &c_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_first, 0, FIRST_NAME_LEN, NULL, 0, 0,
4);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_middle, 0, MIDDLE_NAME_LEN, NULL, 0, 0,
5);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_last, 0, LAST_NAME_LEN, NULL, 0, 0,
6);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_street_1, 0, ADDRESS_LEN, NULL, 0, 0,
7);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_street_2, 0, ADDRESS_LEN, NULL, 0, 0,
8);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_city, 0, ADDRESS_LEN, NULL, 0, 0, 9);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_state, 0, STATE_LEN, NULL, 0, 0, 10);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_zip, 0, ZIP_LEN, NULL, 0, 0, 11);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

```

```

rc = bcp_bind(c_hdbc1, (BYTE *) c_phone, 0, PHONE_LEN, NULL, 0, 0, 12);

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_since, 0, C_SINCE_LEN, NULL, 0,
SQLCHARACTER, 13);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) c_credit, 0, CREDIT_LEN, NULL, 0, 0,
14);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_credit_lim, 0, SQL_VARLEN_DATA, NULL,
0, SQLFLT8, 15);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_discount, 0, SQL_VARLEN_DATA, NULL,
0, SQLFLT8, 16);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

// fix to avoid ODBC float to numeric conversion problem.

// rc = bcp_bind(c_hdbc1, (BYTE *) &c_balance, 0, SQL_VARLEN_DATA,
NULL, 0, SQLFLT8, 17);
// if (rc != SUCCEED)
//     HandleErrorDBC(c_hdbc1);
rc = bcp_bind(c_hdbc1, (BYTE *) c_balance, 0, 5, NULL, 0, SQLCHARACTER,
17);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_ytd_payment, 0, SQL_VARLEN_DATA,
NULL, 0, SQLFLT8, 18);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_payment_cnt, 0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 19);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = bcp_bind(c_hdbc1, (BYTE *) &c_delivery_cnt, 0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 20);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

```

```

rc = bcp_bind(c_hdbc1, (BYTE *) c_data, 0, 500, NULL, 0, 0, 21);
if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

for (i = 0; i < customers_per_district; i++)
{
    c_id = customer_buf[i].c_id;
    c_d_id = customer_buf[i].c_d_id;
    c_w_id = customer_buf[i].c_w_id;

    strcpy(c_first, customer_buf[i].c_first);
    strcpy(c_middle, customer_buf[i].c_middle);
    strcpy(c_last, customer_buf[i].c_last);
    strcpy(c_street_1, customer_buf[i].c_street_1);
    strcpy(c_street_2, customer_buf[i].c_street_2);
    strcpy(c_city, customer_buf[i].c_city);
    strcpy(c_state, customer_buf[i].c_state);
    strcpy(c_zip, customer_buf[i].c_zip);
    strcpy(c_phone, customer_buf[i].c_phone);
    strcpy(c_credit, customer_buf[i].c_credit);

    FormatDate(&c_since);

    c_credit_lim = customer_buf[i].c_credit_lim;
    c_discount = customer_buf[i].c_discount;

    // fix to avoid ODBC float to numeric conversion problem.

    // c_balance = customer_buf[i].c_balance;
    strcpy(c_balance, customer_buf[i].c_balance);

    c_ytd_payment = customer_buf[i].c_ytd_payment;
    c_payment_cnt = customer_buf[i].c_payment_cnt;
    c_delivery_cnt = customer_buf[i].c_delivery_cnt;

    strcpy(c_data, customer_buf[i].c_data);

    // Send data to server
    rc = bcp_sendrow(c_hdbc1);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc1);

    customer_rows_loaded++;
    CheckForCommit(c_hdbc1, c_hstmt1, customer_rows_loaded,
"customer", &customer_time_start->time_start);
}

}

//=====
//

```

```

// Function   : LoadHistoryTable
//
//=====

void LoadHistoryTable(LOADER_TIME_STRUCT *history_time_start)
{
    int         i;
    long        c_id;
    short       c_d_id;
    short       c_w_id;
    double      h_amount;
    char        h_data[H_DATA_LEN+1];
    char        h_date[H_DATE_LEN+1];
    RETCODE     rc;

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 4);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &c_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 5);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &h_date, 0, H_DATE_LEN, NULL, 0,
SQLCHARACTER, 6);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) &h_amount, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 7);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    rc = bcp_bind(c_hdbc2, (BYTE *) h_data, 0, H_DATA_LEN, NULL, 0, 0, 8);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);
}

```

```

for (i = 0; i < customers_per_district; i++)
{
    c_id = customer_buf[i].c_id;
    c_d_id = customer_buf[i].c_d_id;
    c_w_id = customer_buf[i].c_w_id;
    h_amount = customer_buf[i].h_amount;
    strcpy(h_data, customer_buf[i].h_data);

    FormatDate(&h_date);

    // send to server
    rc = bcp_sendrow(c_hdbc2);
    if (rc != SUCCEED)
        HandleErrorDBC(c_hdbc2);

    history_rows_loaded++;
    CheckForCommit(c_hdbc2, c_hstmt2, history_rows_loaded, "history",
&history_time_start->time_start);
}
}

//=====
//
// Function   : LoadOrders
//
//=====
==

void LoadOrders()
{
    LOADER_TIME_STRUCT    orders_time_start;
    LOADER_TIME_STRUCT    new_order_time_start;
    LOADER_TIME_STRUCT    order_line_time_start;
    short                 w_id;
    short                 d_id;
    DWORD                 dwThreadId[MAX_ORDER_THREADS];
    HANDLE                 hThread[MAX_ORDER_THREADS];
    char                  name[20];
    RETCODE               rc;
    char                  bcphint[128];

    // seed with unique number
    seed(6);

    printf("Loading orders...\n");

    // if build index before load...
    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {

```

```

        BuildIndex("idxordc1");
        BuildIndex("idxnodc1");
        BuildIndex("idxodlc1");
    }

    // initialize bulk copy
    sprintf(name, "%s..%s", aptr->database, "orders");

    rc = bcp_init(o_hdbc1, name, NULL, "logs\\orders.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (o_w_id, o_d_id, o_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 30000));
        rc = bcp_control(o_hdbc1, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc1);
    }

    sprintf(name, "%s..%s", aptr->database, "new_order");

    rc = bcp_init(o_hdbc2, name, NULL, "logs\\neword.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (no_w_id, no_d_id, no_o_id),
ROWS_PER_BATCH = %u", (aptr->num_warehouses * 9000));
        rc = bcp_control(o_hdbc2, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc2);
    }

    sprintf(name, "%s..%s", aptr->database, "order_line");

    rc = bcp_init(o_hdbc3, name, NULL, "logs\\ordline.err", DB_IN);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc3);

    if ((aptr->build_index == 1) && (aptr->index_order == 1))
    {
        sprintf(bcphint, "tablock, order (ol_w_id, ol_d_id, ol_o_id,
ol_number), ROWS_PER_BATCH = %u", (aptr->num_warehouses * 300000));
        rc = bcp_control(o_hdbc3, BCPHINTS, (void*) bcphint);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc3);
    }

    orders_rows_loaded = 0;

```

```

new_order_rows_loaded = 0;
order_line_rows_loaded = 0;

OrdersBufInit();

orders_time_start.time_start = (TimeNow() / MILLI);
new_order_time_start.time_start = (TimeNow() / MILLI);
order_line_time_start.time_start = (TimeNow() / MILLI);

for (w_id = (short)aptr->starting_warehouse; w_id <= aptr-
>num_warehouses; w_id++)
{
    for (d_id = 1; d_id <= DISTRICT_PER_WAREHOUSE; d_id++)
    {
        OrdersBufLoad(d_id, w_id);

        // start parallel loading threads here...

        // start Orders table thread
        printf("...Loading Order Table for: d_id = %d, w_id = %d\n",
d_id, w_id);

        hThread[0] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadOrdersTable,
                                &orders_time_start,
                                0,
                                &dwThreadID[0]);

        if (hThread[0] == NULL)
        {
            printf("Error, failed in creating creating thread =
0.\n");
            exit(-1);
        }

        // start NewOrder table thread
        printf("...Loading New-Order Table for: d_id = %d, w_id =
%d\n", d_id, w_id);

        hThread[1] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadNewOrderTable,
                                &new_order_time_start,
                                0,
                                &dwThreadID[1]);

        if (hThread[1] == NULL)

```

```

        {
            printf("Error, failed in creating creating thread =
1.\n");
            exit(-1);
        }

        // start Order-Line table thread

        printf("...Loading Order-Line Table for: d_id = %d, w_id =
%d\n", d_id, w_id);

        hThread[2] = CreateThread(NULL,
                                0,
                                (LPTHREAD_START_ROUTINE)
LoadOrderLineTable,
                                &order_line_time_start,
                                0,
                                &dwThreadID[2]);

        if (hThread[2] == NULL)
        {
            printf("Error, failed in creating creating thread =
2.\n");
            exit(-1);
        }

        WaitForSingleObject( hThread[0], INFINITE );
        WaitForSingleObject( hThread[1], INFINITE );
        WaitForSingleObject( hThread[2], INFINITE );

        if (CloseHandle(hThread[0]) == FALSE)
        {
            printf("Error, failed in closing Orders thread handle
with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[1]) == FALSE)
        {
            printf("Error, failed in closing NewOrder thread handle
with errno: %d\n", GetLastError());
        }

        if (CloseHandle(hThread[2]) == FALSE)
        {
            printf("Error, failed in closing OrderLine thread
handle with errno: %d\n", GetLastError());
        }
    }

    printf("Finished loading orders.\n");

```

```

    return;
}

//=====
//
// Function    : OrdersBufInit
//
// Clears shared buffer for ORDERS, NEWORDER, and ORDERLINE
//
//=====
void OrdersBufInit()
{
    int    i;
    int    j;

    for (i=0;i<orders_per_district;i++)
    {
        orders_buf[i].o_id = 0;
        orders_buf[i].o_d_id = 0;
        orders_buf[i].o_w_id = 0;
        orders_buf[i].o_c_id = 0;
        orders_buf[i].o_carrier_id = 0;
        orders_buf[i].o_ol_cnt = 0;
        orders_buf[i].o_all_local = 0;

        for (j=0;j<=14;j++)
        {
            orders_buf[i].o_ol[j].ol = 0;
            orders_buf[i].o_ol[j].ol_i_id = 0;
            orders_buf[i].o_ol[j].ol_supply_w_id = 0;
            orders_buf[i].o_ol[j].ol_quantity = 0;
            orders_buf[i].o_ol[j].ol_amount = 0;
            strcpy(orders_buf[i].o_ol[j].ol_dist_info, "");
        }
    }
}

//=====
//
// Function    : OrdersBufLoad
//
// Fills shared buffer for ORDERS, NEWORDER, and ORDERLINE
//
//=====
void OrdersBufLoad(int d_id, int w_id)
{

```

```

int     cust[ORDERS_PER_DISTRICT+1];
long    o_id;
short   ol;

printf("...Loading Order Buffer for: d_id = %d, w_id = %d\n",
      d_id, w_id);

GetPermutation(cust, orders_per_district);

for (o_id=0;o_id<orders_per_district;o_id++)
{
    // Generate ORDER and NEW-ORDER data

    orders_buf[o_id].o_d_id = d_id;
    orders_buf[o_id].o_w_id = w_id;
    orders_buf[o_id].o_id = o_id+1;
    orders_buf[o_id].o_c_id = cust[o_id+1];
    orders_buf[o_id].o_ol_cnt = (short)RandomNumber(5L, 15L);

    if (o_id < first_new_order)
    {
        orders_buf[o_id].o_carrier_id = (short)RandomNumber(1L, 10L);
        orders_buf[o_id].o_all_local = 1;
    }
    else
    {
        orders_buf[o_id].o_carrier_id = 0;
        orders_buf[o_id].o_all_local = 1;
    }

    for (ol=0; ol<orders_buf[o_id].o_ol_cnt; ol++)
    {
        orders_buf[o_id].o_ol[ol].ol = ol+1;
        orders_buf[o_id].o_ol[ol].ol_i_id = RandomNumber(1L,
max_items);
        orders_buf[o_id].o_ol[ol].ol_supply_w_id = w_id;
        orders_buf[o_id].o_ol[ol].ol_quantity = 5;
        MakeAlphaString(24, 24, OL_DIST_INFO_LEN,
&orders_buf[o_id].o_ol[ol].ol_dist_info);

        // Generate ORDER-LINE data
        if (o_id < first_new_order)
        {
            orders_buf[o_id].o_ol[ol].ol_amount = 0;
            // Added to insure ol_delivery_d set properly during
load
            FormatDate(&orders_buf[o_id].o_ol[ol].ol_delivery_d);

        }
        else

```

```

        {
            orders_buf[o_id].o_ol[ol].ol_amount =
RandomNumber(1,999999)/100.0;
            // Added to insure ol_delivery_d set properly during
load
            // odbc datetime format
            strcpy(orders_buf[o_id].o_ol[ol].ol_delivery_d,"1899-
12-31 00:00:00.000");
        }
    }
}

//=====
//
// Function   : LoadOrdersTable
//
//=====

void LoadOrdersTable(LOADER_TIME_STRUCT *orders_time_start)
{
    int         i;
    long        o_id;
    short       o_d_id;
    short       o_w_id;
    long        o_c_id;
    short       o_carrier_id;
    short       o_ol_cnt;
    short       o_all_local;
    char        o_entry_d[O_ENTRY_D_LEN+1];
    RETCODE     rc;
    DBINT       rcint;

    // bind ORDER data
    rc = bcp_bind(o_hdbc1, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

```

```

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_c_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 4);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_entry_d, 0, O_ENTRY_D_LEN, NULL, 0,
SQLCHARACTER, 5);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_carrier_id, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 6);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_ol_cnt, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 7);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    rc = bcp_bind(o_hdbc1, (BYTE *) &o_all_local, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 8);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

for (i = 0; i < orders_per_district; i++)
{
    o_id      = orders_buf[i].o_id;
    o_d_id    = orders_buf[i].o_d_id;
    o_w_id    = orders_buf[i].o_w_id;
    o_c_id    = orders_buf[i].o_c_id;
    o_carrier_id = orders_buf[i].o_carrier_id;
    o_ol_cnt  = orders_buf[i].o_ol_cnt;
    o_all_local = orders_buf[i].o_all_local;

    FormatDate(&o_entry_d);

    // send data to server
    rc = bcp_sendrow(o_hdbc1);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc1);

    orders_rows_loaded++;
    CheckForCommit(o_hdbc1, o_hstmt1, orders_rows_loaded, "orders",
&orders_time_start->time_start);
}

// rcint = bcp_batch(o_hdbc1);
// if (rcint < 0)
//     HandleErrorDBC(o_hdbc1);

if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
{

```

```

rcint = bcp_done(o_hdbc1);
if (rcint < 0)
    HandleErrorDBC(o_hdbc1);

SQLFreeStmt(o_hstmt1, SQL_DROP);
SQLDisconnect(o_hdbc1);
SQLFreeConnect(o_hdbc1);

// if build index after load...
if ((aptr->build_index == 1) && (aptr->index_order == 0))
    BuildIndex("idxordc1");

// build non-clustered index
if (aptr->build_index == 1)
    BuildIndex("idxordnc");
}
}

//=====
//
// Function   : LoadNewOrderTable
//
//=====

void LoadNewOrderTable(LOADER_TIME_STRUCT *new_order_time_start)
{
    int      i;
    long     o_id;
    short    o_d_id;
    short    o_w_id;
    RETCODE  rc;
    DBINT    rcint;

    // Bind NEW-ORDER data

    rc = bcp_bind(o_hdbc2, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    rc = bcp_bind(o_hdbc2, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    rc = bcp_bind(o_hdbc2, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    for (i = first_new_order; i < last_new_order; i++)

```

```

{
    o_id    = orders_buf[i].o_id;
    o_d_id  = orders_buf[i].o_d_id;
    o_w_id  = orders_buf[i].o_w_id;

    rc = bcp_sendrow(o_hdbc2);
    if (rc != SUCCEED)
        HandleErrorDBC(o_hdbc2);

    new_order_rows_loaded++;
    CheckForCommit(o_hdbc2, o_hstmt2, new_order_rows_loaded,
"new_order", &new_order_time_start->time_start);
}

// rcint = bcp_batch(o_hdbc2);
// if (rcint < 0)
//     HandleErrorDBC(o_hdbc2);

if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
{
    rcint = bcp_done(o_hdbc2);
    if (rcint < 0)
        HandleErrorDBC(o_hdbc2);

    SQLFreeStmt(o_hstmt2, SQL_DROP);
    SQLDisconnect(o_hdbc2);
    SQLFreeConnect(o_hdbc2);

    // if build index after load...
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
        BuildIndex("idxnodc1");
}
}

//=====
//
// Function   : LoadOrderLineTable
//
//=====

void LoadOrderLineTable(LOADER_TIME_STRUCT *order_line_time_start)
{
    int        i,j;
    long       o_id;
    short      o_d_id;
    short      o_w_id;
    long       ol;
    long       ol_i_id;
    short      ol_supply_w_id;
    short      ol_quantity;

```

```

double       ol_amount;
char         ol_dist_info[DIST_INFO_LEN+1];
char         ol_delivery_d[OL_DELIVERY_D_LEN+1];
RETCODE      rc;
DBINT        rcint;

// bind ORDER-LINE data
rc = bcp_bind(o_hdbc3, (BYTE *) &o_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 1);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &o_d_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 2);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &o_w_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT2, 3);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &ol, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 4);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &ol_i_id, 0, SQL_VARLEN_DATA, NULL, 0,
SQLINT4, 5);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &ol_supply_w_id, 0, SQL_VARLEN_DATA,
NULL, 0, SQLINT2, 6);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &ol_delivery_d, 0, OL_DELIVERY_D_LEN,
NULL, 0, SQLCHARACTER, 7);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &ol_quantity, 0, SQL_VARLEN_DATA, NULL,
0, SQLINT2, 8);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = bcp_bind(o_hdbc3, (BYTE *) &ol_amount, 0, SQL_VARLEN_DATA, NULL, 0,
SQLFLT8, 9);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

```

```

rc = bcp_bind(o_hdbc3, (BYTE *) ol_dist_info, 0, DIST_INFO_LEN, NULL, 0,
0, 10);
if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

for (i = 0; i < orders_per_district; i++)
{
    o_id    = orders_buf[i].o_id;
    o_d_id  = orders_buf[i].o_d_id;
    o_w_id  = orders_buf[i].o_w_id;

    for (j=0; j < orders_buf[i].o_ol_cnt; j++)
    {
        ol            = orders_buf[i].o_ol[j].ol;
        ol_i_id       = orders_buf[i].o_ol[j].ol_i_id;
        ol_supply_w_id = orders_buf[i].o_ol[j].ol_supply_w_id;
        ol_quantity   = orders_buf[i].o_ol[j].ol_quantity;
        ol_amount     = orders_buf[i].o_ol[j].ol_amount;

        strcpy(ol_delivery_d,orders_buf[i].o_ol[j].ol_delivery_d);

        strcpy(ol_dist_info,orders_buf[i].o_ol[j].ol_dist_info);

        rc = bcp_sendrow(o_hdbc3);
        if (rc != SUCCEED)
            HandleErrorDBC(o_hdbc3);

        order_line_rows_loaded++;
        CheckForCommit(o_hdbc3, o_hstmt3, order_line_rows_loaded,
"order_line", &order_line_time_start->time_start);
    }

}

// rcint = bcp_batch(o_hdbc3);
// if (rcint < 0)
//     HandleErrorDBC(o_hdbc3);

if ((o_w_id == aptr->num_warehouses) && (o_d_id == 10))
{
    rcint = bcp_done(o_hdbc3);
    if (rcint < 0)
        HandleErrorDBC(o_hdbc3);

    SQLFreeStmt(o_hstmt3, SQL_DROP);
    SQLDisconnect(o_hdbc3);
    SQLFreeConnect(o_hdbc3);

    // if build index after load...
    if ((aptr->build_index == 1) && (aptr->index_order == 0))
        BuildIndex("idxodlcl");
}

```

```

}

//=====
//
// Function   : GetPermutation
//
//=====

void GetPermutation(int perm[], int n)
{
    int i, r, t;

    for (i=1;i<=n;i++)
        perm[i] = i;

    for (i=1;i<=n;i++)
    {
        r = RandomNumber(i,n);
        t = perm[i];
        perm[i] = perm[r];
        perm[r] = t;
    }
}

//=====
//
// Function   : CheckForCommit
//
//=====

void CheckForCommit(HDBC hdbc,
                    HSTMT hstmt,
                    int rows_loaded,
                    char *table_name,
                    long *time_start)
{
    long time_end, time_diff;
    // DBINT rcint;

    if ( !(rows_loaded % aptr->batch) )
    {
        // rcint = bcp_batch(hdbc);
        // if (rcint < 0)
        //     HandleErrorDBC(hdbc);

        time_end = (TimeNow() / MILLI);
        time_diff = time_end - *time_start;
    }
}

```

```

        printf("-> Loaded %ld rows into %s in %ld sec - Total = %d (%.2f
rps)\n",
            aptr->batch,
            table_name,
            time_diff,
            rows_loaded,
            (float) aptr->batch / (time_diff ? time_diff : 1L));

        *time_start = time_end;
    }

    return;
}

//=====
//
// Function   : OpenConnections
//
//=====

void OpenConnections()
{
    RETCODE      rc;

    char         szDriverString[300];
    char         szDriverStringOut[1024];
    SQLSMALLINT  cbDriverStringOut;

    SQLAllocHandle(SQL_HANDLE_ENV, SQL_NULL_HANDLE, &henv );

    SQLSetEnvAttr(henv, SQL_ATTR_ODBC_VERSION, (void*)SQL_OV_ODBC3, 0 );

    SQLAllocHandle(SQL_HANDLE_DBC, henv , &i_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv , &w_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv , &c_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv , &c_hdbc2);
    SQLAllocHandle(SQL_HANDLE_DBC, henv , &o_hdbc1);
    SQLAllocHandle(SQL_HANDLE_DBC, henv , &o_hdbc2);
    SQLAllocHandle(SQL_HANDLE_DBC, henv , &o_hdbc3);

    SQLSetConnectAttr(i_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(w_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(c_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(c_hdbc2, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

```

```

    SQLSetConnectAttr(o_hdbc1, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(o_hdbc2, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );
    SQLSetConnectAttr(o_hdbc3, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

    // Open connections to SQL Server

    // Connection 1

    sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
            aptr->server,
            aptr->user,
            aptr->password,
            aptr->database );

    rc = SQLSetConnectOption (i_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

    if (rc != SUCCEED)
        HandleErrorDBC(i_hdbc1);

    rc = SQLDriverConnect ( i_hdbc1,
                            NULL,
                            (SQLCHAR*)&szDriverString[0] ,
                            SQL_NTS,
                            (SQLCHAR*)&szDriverStringOut[0],
                            sizeof(szDriverStringOut),
                            &cbDriverStringOut,
                            SQL_DRIVER_NOPROMPT );

    if (rc != SUCCEED)
        HandleErrorDBC(i_hdbc1);

    // Connection 2

    sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
            aptr->server,
            aptr->user,
            aptr->password,
            aptr->database );

    rc = SQLSetConnectOption (w_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

    if (rc != SUCCEED)
        HandleErrorDBC(w_hdbc1);

    rc = SQLDriverConnect ( w_hdbc1,
                            NULL,
                            (SQLCHAR*)&szDriverString[0] ,
                            SQL_NTS,
                            (SQLCHAR*)&szDriverStringOut[0],

```

```

        sizeof(szDriverStringOut),
        &cbDriverStringOut,
        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(w_hdbc1);

// Connection 3

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (c_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

rc = SQLDriverConnect ( c_hdbc1,
        NULL,
        (SQLCHAR*)&szDriverString[0] ,
        SQL_NTS,
        (SQLCHAR*)&szDriverStringOut[0],
        sizeof(szDriverStringOut),
        &cbDriverStringOut,
        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc1);

// Connection 4

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (c_hdbc2, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc2);

rc = SQLDriverConnect ( c_hdbc2,
        NULL,
        (SQLCHAR*)&szDriverString[0] ,
        SQL_NTS,
        (SQLCHAR*)&szDriverStringOut[0],
        sizeof(szDriverStringOut),
        &cbDriverStringOut,
        SQL_DRIVER_NOPROMPT );

```

```

if (rc != SUCCEED)
    HandleErrorDBC(c_hdbc2);

// Connection 5

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (o_hdbc1, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc1);

rc = SQLDriverConnect ( o_hdbc1,
        NULL,
        (SQLCHAR*)&szDriverString[0] ,
        SQL_NTS,
        (SQLCHAR*)&szDriverStringOut[0],
        sizeof(szDriverStringOut),
        &cbDriverStringOut,
        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc1);

// Connection 6

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (o_hdbc2, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc2);

rc = SQLDriverConnect ( o_hdbc2,
        NULL,
        (SQLCHAR*)&szDriverString[0] ,
        SQL_NTS,
        (SQLCHAR*)&szDriverStringOut[0],
        sizeof(szDriverStringOut),
        &cbDriverStringOut,
        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc2);

```

```

// Connection 7

sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
        aptr->server,
        aptr->user,
        aptr->password,
        aptr->database );

rc = SQLSetConnectOption (o_hdbc3, SQL_PACKET_SIZE, aptr->pack_size);

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);

rc = SQLDriverConnect ( o_hdbc3,
                        NULL,
                        (SQLCHAR*)&szDriverString[0] ,
                        SQL_NTS,
                        (SQLCHAR*)&szDriverStringOut[0],
                        sizeof(szDriverStringOut),
                        &cbDriverStringOut,
                        SQL_DRIVER_NOPROMPT );

if (rc != SUCCEED)
    HandleErrorDBC(o_hdbc3);
}

//=====
//
// Function name: BuildIndex
//
//=====

void BuildIndex(char *index_script)
{
    char cmd[256];

    printf("Starting index creation:  %s\n",index_script);

    sprintf(cmd, "isql -S%s -U%s -P%s -e -i%s\\%s.sql > logs\\%s.log",
            aptr->server,
            aptr->user,
            aptr->password,
            aptr->index_script_path,
            index_script,
            index_script);

    system(cmd);

    printf("Finished index creation:  %s\n",index_script);
}

```

```

void HandleErrorDBC (SQLHDBC hdbc1)
{
    SQLCHAR          SqlState[6], Msg[SQL_MAX_MESSAGE_LENGTH];
    SQLINTEGER       NativeError;
    SQLSMALLINT      i, MsgLen;
    SQLRETURN        rc2;
    char             timebuf[128];
    char             datebuf[128];
    FILE             *fp1;

    i = 1;
    while (( rc2 = SQLGetDiagRec(SQL_HANDLE_DBC , hdbc1, i, SqlState ,
&NativeError,
                                Msg, sizeof(Msg) , &MsgLen ) != SQL_NO_DATA )
        {
            sprintf( szLastError , "%s" , Msg );

            _strtime(timebuf);
            _strdate(datebuf);

            printf( "[%s : %s] %s\n" , datebuf, timebuf, szLastError);

            fp1 = fopen("logs\\tpccldr.err","w");
            if (fp1 == NULL)
                printf("ERROR:  Unable to open errorlog file.\n");
            else
            {
                fprintf(fp1, "[%s : %s] %s\n" , datebuf, timebuf,
szLastError);
                fclose(fp1);
            }

            i++;
        }
}

void HandleErrorSTMT (HSTMT hstmt1)
{
    SQLCHAR          SqlState[6], Msg[SQL_MAX_MESSAGE_LENGTH];
    SQLINTEGER       NativeError;
    SQLSMALLINT      i, MsgLen;
    SQLRETURN        rc2;
    char             timebuf[128];
    char             datebuf[128];
    FILE             *fp1;

    i = 1;
    while (( rc2 = SQLGetDiagRec(SQL_HANDLE_STMT , hstmt1, i, SqlState ,
&NativeError,

```

```

        Msg, sizeof(Msg) , &MsgLen )) != SQL_NO_DATA )
    {
        sprintf( szLastError , "%s" , Msg );
        _strtime(timebuf);
        _strdate(datebuf);
        printf( "[%s : %s] %s\n" , datebuf, timebuf, szLastError);
        fp1 = fopen("logs\\tpccldr.err","w");
        if (fp1 == NULL)
            printf("ERROR: Unable to open errorlog file.\n");
        else
        {
            fprintf(fp1, "[%s : %s] %s\n" , datebuf, timebuf,
szLastError);
            fclose(fp1);
        }
        i++;
    }
}

```

```

void FormatDate ( char* szTimeCOutput )
{

```

```

    struct tm when;
    time_t now;

    time( &now );
    when = *localtime( &now );

    mktime( &when );

    // odbc datetime format
    strftime( szTimeCOutput , 30 , "%Y-%m-%d %H:%M:%S.000" , &when );

    return;
}

```

```

//=====
//
// Function   : CheckSQL
//
//=====

```

```

void CheckSQL()
{

```

```

    RETCODE        rc;

    char            szDriverString[300];
    char            szDriverStringOut[1024];
    int             SQLBuildFlag;

    SQLSMALLINT    cbDriverStringOut;
    SQLCHAR        SQLVersion[19];
    SQLINTEGER     SQLVersionInd;

    SQLAllocHandle(SQL_HANDLE_ENV, SQL_NULL_HANDLE, &henv );

    SQLSetEnvAttr(henv, SQL_ATTR_ODBC_VERSION, (void*)SQL_OV_ODBC3, 0 );

    SQLAllocHandle(SQL_HANDLE_DBC, henv , &v_hdbc);

    SQLSetConnectAttr(v_hdbc, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

    // Open connection to SQL Server

    sprintf( szDriverString , "DRIVER={SQL Server};SERVER=%s;UID=%s;PWD=%s"
,
                aptr->server,
                aptr->user,
                aptr->password );

    if ( SQLSetConnectAttr( v_hdbc, SQL_ATTR_PACKET_SIZE, (SQLPOINTER)aptr-
>pack_size, SQL_IS_UIINTEGER ) != SQL_SUCCESS )
        HandleErrorDBC(v_hdbc);

    rc = SQLDriverConnect ( v_hdbc,
                            NULL,
                            (SQLCHAR*)&szDriverString[0] ,
                            SQL_NTS,
                            (SQLCHAR*)&szDriverStringOut[0],
                            sizeof(szDriverStringOut),
                            &cbDriverStringOut,
                            SQL_DRIVER_NOPROMPT );

    if ((rc != SQL_SUCCESS) && (rc != SQL_SUCCESS_WITH_INFO))
        HandleErrorDBC(v_hdbc);

    if ( SQLAllocHandle(SQL_HANDLE_STMT, v_hdbc , &v_hstmt) != SQL_SUCCESS
)
        HandleErrorSTMT(v_hstmt);

    rc = SQLBindCol(v_hstmt, 4, SQL_C_CHAR, &SQLVersion,
sizeof(SQLVersion), &SQLVersionInd);

```

```

// issue SQL Server extended stored procedure (xp_msver) to determine
installed version
rc = SQLExecDirect(v_hstmt, "EXECUTE xp_msver ProductVersion",
SQL_NTS);

if ((rc != SQL_SUCCESS) && (rc != SQL_SUCCESS_WITH_INFO))
    HandleErrorSTMT(v_hstmt);

rc = SQLFetch(v_hstmt);

if (rc != SQL_SUCCESS)
    HandleErrorDBC(v_hdbc);

// Check build number to ensure 7.00.623 or higher

SQLBuildFlag = 1;

if ( SQLVersion[0] == 55 )
{
    if ( SQLVersion[2] == 48 )
    {
        if ( SQLVersion[5] == 56 )
        {
            if ( (SQLVersion[6] >= 48) & (SQLVersion[7] >= 53) )
            {
                SQLBuildFlag = 0;
                printf("You are using SQL Server version =
%s\n\n", SQLVersion);
            }
            else
            {
                SQLBuildFlag = 1;
            }
        }
        else
        {
            if ( SQLVersion[5] >= 54 )
            {
                if ( (SQLVersion[6] >= 50) & (SQLVersion[7] >= 51) )
                {
                    SQLBuildFlag = 0;
                    printf("You are using SQL Server version =
%s\n\n", SQLVersion);
                }
                else
                {
                    SQLBuildFlag = 1;
                }
            }
            else
            {

```

```

if ( SQLVersion[5] >= 55 )
{
    if ( (SQLVersion[6] >= 48) & (SQLVersion[7]
    >= 48) )
    {
        SQLBuildFlag = 0;
        printf("You are using SQL Server version
= %9s\n\n", SQLVersion);
    }
    else
    {
        SQLBuildFlag = 1;
    }
}
}
else
{
    if ( SQLVersion[5] >= 49 )
    {
        if ( (SQLVersion[6] >= 52) & (SQLVersion[7] >= 48) )
        {
            SQLBuildFlag = 0;
            printf("You are using SQL Server version =
%s\n\n", SQLVersion);
        }
        else
        {
            SQLBuildFlag = 1;
        }
    }
    else
    {
        SQLBuildFlag = 1;
    }
}
}
else
{
    SQLBuildFlag = 1;
}
}

if ( SQLBuildFlag == 1 )
{
    printf("ERROR. The SQL Server version you are using is not
supported\n");
    printf("for TPC-C benchmarking. You currently have SQL Server
version %9s\n",SQLVersion);
    printf("installed. Please upgrade to Microsoft SQL Server
7.00.623 or better.\n");
}

```

```

        printf("and re-run the SETUP program.\n\n");
        exit(1);
    }

    SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
    SQLDisconnect(v_hdbc);
    SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

    return;
}

//=====
//
// Function   : CheckDataBase
//
//=====

void CheckDataBase()
{
    RETCODE      rc;

    char         szDriverString[300];
    char         szDriverStringOut[1024];
    char         TablesBitMap[9] = {"000000000"};
    int          i, ExitFlag;

    SQLSMALLINT  cbDriverStringOut;
    SQLCHAR      TabName[10];
    SQLINTEGER   TabNameInd, TabCount, TabCountInd;

    ExitFlag = 0;

    SQLAllocHandle(SQL_HANDLE_ENV, SQL_NULL_HANDLE, &henv );

    SQLSetEnvAttr(henv, SQL_ATTR_ODBC_VERSION, (void*)SQL_OV_ODBC3, 0 );

    SQLAllocHandle(SQL_HANDLE_DBC, henv , &v_hdbc);

    SQLSetConnectAttr(v_hdbc, SQL_COPT_SS_BCP, (void *)SQL_BCP_ON,
SQL_IS_INTEGER );

    // Open connection to SQL Server

    sprintf( szDriverString , "DRIVER={SQL
Server};SERVER=%s;UID=%s;PWD=%s;DATABASE=%s" ,
            aptr->server,
            aptr->user,
            aptr->password,
            aptr->database );

```

```

        rc = SQLSetConnectAttr( v_hdbc, SQL_ATTR_PACKET_SIZE, (SQLPOINTER)aptr-
>pack_size, SQL_IS_INTEGER );
        if (rc != SQL_SUCCESS)
            HandleErrorDBC(v_hdbc);

        rc = SQLDriverConnect ( v_hdbc,
                                NULL,
                                (SQLCHAR*)&szDriverString[0] ,
                                SQL_NTS,
                                (SQLCHAR*)&szDriverStringOut[0],
                                sizeof(szDriverStringOut),
                                &cbDriverStringOut,
                                SQL_DRIVER_NOPROMPT );

        // if the rc is SQL_ERROR, the the TPCC database probably does not
        exist
        if (rc == SQL_ERROR)
        {
            printf("The database TPCC does not appear to exist!\n");
            printf("\nCheck LOGS\\ directory for database creation
errors.\n");

            // cleanup database connections and handles
            SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
            SQLDisconnect(v_hdbc);
            SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

            // since there is not a database, exit back to SETUP.CMD
            exit(1);
        }

        if ( SQLAllocHandle(SQL_HANDLE_STMT, v_hdbc , &v_hstmt) != SQL_SUCCESS
)
            HandleErrorDBC(v_hdbc);

        if ( SQLBindCol(v_hstmt, 1, SQL_C_ULONG, &TabCount, 0, &TabCountInd) !=
SQL_SUCCESS )
            HandleErrorSTMT(v_hstmt);

        // count the number of user tables from sysobjects
        rc = SQLExecDirect(v_hstmt, "select count(*) from sysobjects where
xtype = 'U'", SQL_NTS);
        if ((rc != SQL_SUCCESS) && (rc != SQL_SUCCESS_WITH_INFO))
            HandleErrorSTMT(v_hstmt);

        if ( SQLFetch(v_hstmt) != SQL_SUCCESS )
            HandleErrorSTMT(v_hstmt);

        // if the number of tables is less than 9, select all the user tables
        in TPCC
        if (TabCount != 9)
        {
            SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);

```

```

SQLAllocHandle(SQL_HANDLE_STMT, v_hdbc , &v_hstmt);

if ( SQLBindCol(v_hstmt, 1, SQL_C_CHAR, &TabName, sizeof(TabName),
&TabNameInd) != SQL_SUCCESS )
    HandleErrorSTMT(v_hstmt);

// select the list of user tables into a result set
rc = SQLExecDirect(v_hstmt, "select * from sysobjects where xtype
= \U\'", SQL_NTS);
if ((rc != SQL_SUCCESS) && (rc != SQL_SUCCESS_WITH_INFO))
    HandleErrorSTMT(v_hstmt);

// go through the result set and set the bitmap for each found
table
// set the bitmap to '1' if the table name is found

while ((rc = SQLFetch(v_hstmt)) != SQL_NO_DATA)
{
    switch( TabName[0] )
    {
    case 'w':
        TablesBitMap[0] = '1';
        break;
    case 'd':
        TablesBitMap[1] = '1';
        break;
    case 'c':
        TablesBitMap[2] = '1';
        break;
    case 'h':
        TablesBitMap[3] = '1';
        break;
    case 'n':
        TablesBitMap[4] = '1';
        break;
    case 'o':
        if (TabName[5] = 's')
            TablesBitMap[5] = '1';
        if (TabName[5] = '_')
            TablesBitMap[6] = '1';
        break;
    case 'i':
        TablesBitMap[7] = '1';
        break;
    case 's':
        TablesBitMap[8] = '1';
        break;
    }
}

```

// a '0' ExitFlag means do NOT exit the loader early, a '1' means exit the loader early

```

ExitFlag = 0;

// iterate through the bitmap to display which table(s) is
actually missing
for (i = 0; i <= 8; i++)
{
    switch(i)
    {
    case 0:
        if (TablesBitMap[i] == '0')
        {
            printf("The Warehouse table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 1:
        if (TablesBitMap[i] == '0')
        {
            printf("The District table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 2:
        if (TablesBitMap[i] == '0')
        {
            printf("The Customer table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 3:
        if (TablesBitMap[i] == '0')
        {
            printf("The History table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 4:
        if (TablesBitMap[i] == '0')
        {
            printf("The New_Order table is missing or
damaged.\n");
            ExitFlag = 1;
        }
        break;
    case 5:
        if (TablesBitMap[i] == '0')
        {
            printf("The Orders table is missing or
damaged.\n");

```

```

        ExitFlag = 1;
    }
    break;
case 6:
    if (TablesBitMap[i] == '0')
    {
        printf("The Order_Line table is missing or
damaged.\n");
        ExitFlag = 1;
    }
    break;
case 7:
    if (TablesBitMap[i] == '0')
    {
        printf("The Item table is missing or damaged.\n");
        ExitFlag = 1;
    }
    break;
case 8:
    if (TablesBitMap[i] == '0')
    {
        printf("The Stock table is missing or
damaged.\n");
        ExitFlag = 1;
    }
    break;
}
}

// if one or more tables are missing, display message and exit the
loader
if (ExitFlag = 1)
{
    printf("\nExiting TPC-C Loader!\n");
    printf("\nCheck LOGS\ directory for database\n");
    printf("or table creation errors.\n");

    // cleanup database connections and handles
    SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
    SQLDisconnect(v_hdbc);
    SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

    exit(1);
}

// cleanup database connections and handles
SQLFreeHandle(SQL_HANDLE_STMT, v_hstmt);
SQLDisconnect(v_hdbc);
SQLFreeHandle(SQL_HANDLE_DBC, v_hdbc);

return;
}

```


Appendix C - Tunable Parameters and Options

This section discloses hardware information and the Windows 2000 Advanced Server SP2 registry parameters used on the PRIMERGY R450 server system.

System Information report written at: 03/05/2002 08:34:16 AM
[System Summary]

```

Item Value
OS Name      Microsoft Windows 2000 Advanced Server
Version      5.0.2195 Service Pack 2 Build 2195
OS Manufacturer Microsoft Corporation
System Name   R450
System Manufacturer FUJITSU SIEMENS
System Model  R450R
System Type   X86-based PC
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
Processor    x86 Family 15 Model 1 Stepping 1 GenuineIntel ~1591 Mhz
BIOS Version "PhoenixBIOS Version 4.06 Rev. 0.98H.1290
Windows Directory C:\WINNT
System Directory C:\WINNT\System32
Boot Device      \Device\Harddisk0\Partition1
Locale           United States
User Name        R450\Administrator
Time Zone        W. Europe Standard Time
Total Physical Memory 8,174,884 KB
Available Physical Memory 7,925,168 KB
Total Virtual Memory 18,241,604 KB
Available Virtual Memory 17,935,560 KB
Page File Space 10,066,720 KB
Page File        C:\pagefile.sys
    
```

System Information report written at: 03/05/2002 08:34:45 AM
[Hardware Resources]

[Following are sub-categories of this main category]

[Conflicts/Sharing]

```

Resource Device
IRQ 9Microsoft ACPI-Compliant System
IRQ 9Standard OpenHCD USB Host Controller
    
```

[DMA]

Channel	Device	Status
4	Direct memory access controller	OK
3	ECP Printer Port (LPT1)	OK
2	Standard floppy disk controller	OK

[Forced Hardware]

```

Device      PNP Device ID
No Forced Hardware
    
```

[I/O]

Address Range	Device	Status
0x0000-0x03AF	PCI bus	OK
0x0000-0x03AF	Direct memory access controller	OK
0x03B0-0x03DF	PCI bus	OK
0x03B0-0x03DF	ATI Technologies Inc. RAGE XL PCI	OK
0x03E0-0x0CF7	PCI bus	OK
0x0D00-0x0FFF	PCI bus	OK
0x1000-0x144F	PCI bus	OK
0x1000-0x144F	ATI Technologies Inc. RAGE XL PCI	OK
0x1400-0x143F	FSC Remote Service Controller, shared memory device	OK
0x03C0-0x03DF	ATI Technologies Inc. RAGE XL PCI	OK
0x0060-0x0060	Standard 101/102-Key or Microsoft Natural PS/2 Keyboard	OK
0x0064-0x0064	Standard 101/102-Key or Microsoft Natural PS/2 Keyboard	OK
0x0081-0x008F	Direct memory access controller	OK
0x00C0-0x00DF	Direct memory access controller	OK
0x0070-0x0071	System CMOS/real time clock	OK
0x0020-0x0021	Programmable interrupt controller	OK
0x00A0-0x00A1	Programmable interrupt controller	OK
0x00F0-0x00FF	Numeric data processor	OK
0x0040-0x0043	System timer	OK
0x0061-0x0061	System speaker	OK
0x0080-0x0080	Motherboard resources	OK
0x040B-0x040B	Motherboard resources	OK
0x04D0-0x04D1	Motherboard resources	OK
0x04D6-0x04D6	Motherboard resources	OK
0x0500-0x051F	Motherboard resources	OK

```

0x0C00-0x0C01 Motherboard resources OK
0x0C06-0x0C08 Motherboard resources OK
0x0C14-0x0C14 Motherboard resources OK
0x0C20-0x0C3F Motherboard resources OK
0x0C50-0x0C52 Motherboard resources OK
0x0C6F-0x0C6F Motherboard resources OK
0x0CD6-0x0CD7 Motherboard resources OK
0x0CE0-0x0CEF Motherboard resources OK
0x0F50-0x0F58 Motherboard resources OK
0x02F8-0x02FF Communications Port (COM1) OK
0x03F8-0x03FF Communications Port (COM2) OK
0x0378-0x037F ECP Printer Port (LPT1) OK
0x0778-0x077F ECP Printer Port (LPT1) OK
0x03F0-0x03F5 Standard floppy disk controller OK
0x03F7-0x03F7 Standard floppy disk controller OK
0x1440-0x144F Standard Dual Channel PCI IDE Controller OK
0x01F0-0x01F7 Primary IDE Channel OK
0x03F6-0x03F6 Primary IDE Channel OK
0x0170-0x0177 Secondary IDE Channel OK
0x0376-0x0376 Secondary IDE Channel OK
0x0A79-0x0A79 ISAPNP Read Data Port OK
0x0279-0x0279 ISAPNP Read Data Port OK
0x02F4-0x02F7 ISAPNP Read Data Port OK
0x2000-0x3FFF PCI bus OK
0x2000-0x3FFF DEC 21154 PCI to PCI bridge OK
0x2000-0x3FFF Mylex EXR2000 Disk Array Controller OK
0x3000-0x3FFF DEC 21154 PCI to PCI bridge OK
0x3000-0x3FFF Mylex EXR2000 Disk Array Controller OK
0x4000-0x5FFF PCI bus OK
0x4000-0x5FFF Adaptec AIC-7899 Ultra160/m PCI SCSI Card OK
0x5000-0x5FFF DEC 21154 PCI to PCI bridge OK
0x5000-0x5FFF Mylex EXR2000 Disk Array Controller OK
0x4400-0x44FF Adaptec AIC-7899 Ultra160/m PCI SCSI Card OK
0x6000-0x6FFF PCI bus OK
0x6000-0x6FFF DEC 21154 PCI to PCI bridge OK
0x6000-0x6FFF Mylex EXR2000 Disk Array Controller OK
0x7000-0x7FFF PCI bus OK
0x7000-0x7FFF DEC 21154 PCI to PCI bridge OK
0x7000-0x7FFF Mylex EXR2000 Disk Array Controller OK
0x8000-0x8FFF PCI bus OK
0x8000-0x8FFF DEC 21154 PCI to PCI bridge OK
0x8000-0x8FFF Mylex EXR2000 Disk Array Controller OK
0x9000-0x903F PCI bus OK

```

[IRQs]

```

IRQ Number Device
9 Microsoft ACPI-Compliant System
9 Standard OpenHCD USB Host Controller
32 FSC Remote Service Controller, shared memory device
36 ATI Technologies Inc. RAGE XL PCI
1 Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
8 System CMOS/real time clock

```

```

13 Numeric data processor
12 PS/2 Compatible Mouse
3 Communications Port (COM1)
4 Communications Port (COM2)
6 Standard floppy disk controller
15 Secondary IDE Channel
28 Mylex EXR2000 Disk Array Controller
30 Mylex EXR2000 Disk Array Controller
26 Mylex EXR2000 Disk Array Controller
38 Adaptec AIC-7899 Ultra160/m PCI SCSI Card
39 Adaptec AIC-7899 Ultra160/m PCI SCSI Card
24 Mylex EXR2000 Disk Array Controller
22 Mylex EXR2000 Disk Array Controller
20 Mylex EXR2000 Disk Array Controller
18 Alteon WebSystems PCI Gigabit Ethernet Adapter

```

[Memory]

Range	Device	Status
0xA0000-0xBFFFF	PCI bus	OK
0xA0000-0xBFFFF	ATI Technologies Inc. RAGE XL PCI	OK
0xD0000-0xE7FFF	PCI bus	OK
0xF3000000-0xF42FFFFF	PCI bus	OK
0xF3000000-0xF42FFFFF	ATI Technologies Inc. RAGE XL PCI	OK
0xF4300000-0xF43FFFFF	PCI bus	OK
0xF4300000-0xF43FFFFF	FSC Remote Service Controller, shared memory device	OK
0xF4000000-0xF400FFFF	FSC Remote Service Controller, shared memory device	OK
0xF4001000-0xF4001FFF	ATI Technologies Inc. RAGE XL PCI	OK
0xF4002000-0xF4002FFF	Standard OpenHCD USB Host Controller	OK
0xF4500000-0xF57FFFFF	PCI bus	OK
0xF5800000-0xF67FFFFF	PCI bus	OK
0xF5800000-0xF67FFFFF	DEC 21154 PCI to PCI bridge	OK
0xF5800000-0xF67FFFFF	Mylex EXR2000 Disk Array Controller	OK
0xF4800000-0xF4FFFFF	DEC 21154 PCI to PCI bridge	OK
0xF4800000-0xF4FFFFF	Mylex EXR2000 Disk Array Controller	OK
0xF5000000-0xF57FFFFF	DEC 21154 PCI to PCI bridge	OK
0xF5000000-0xF57FFFFF	Mylex EXR2000 Disk Array Controller	OK
0xF6000000-0xF67FFFFF	DEC 21154 PCI to PCI bridge	OK
0xF6000000-0xF67FFFFF	Mylex EXR2000 Disk Array Controller	OK
0xF6800000-0xF77FFFFF	PCI bus	OK
0xF6800000-0xF77FFFFF	Adaptec AIC-7899 Ultra160/m PCI SCSI Card	OK
0xF7800000-0xF7FFFFF	PCI bus	OK
0xF7800000-0xF7FFFFF	DEC 21154 PCI to PCI bridge	OK
0xF7800000-0xF7FFFFF	Mylex EXR2000 Disk Array Controller	OK
0xF7000000-0xF77FFFFF	DEC 21154 PCI to PCI bridge	OK
0xF7000000-0xF77FFFFF	Mylex EXR2000 Disk Array Controller	OK
0xF6801000-0xF6801FFF	Adaptec AIC-7899 Ultra160/m PCI SCSI Card	OK
0xF8000000-0xF89FFFFF	PCI bus	OK
0xF8000000-0xF89FFFFF	DEC 21154 PCI to PCI bridge	OK
0xF8000000-0xF89FFFFF	Mylex EXR2000 Disk Array Controller	OK
0xF9000000-0xF97FFFFF	PCI bus	OK

```

0xF9000000-0xF97FFFFFFF DEC 21154 PCI to PCI bridge OK
0xF9000000-0xF97FFFFFFF Mylex EXR2000 Disk Array Controller OK
0xF9800000-0xFA1FFFFFFF PCI bus OK
0xF9800000-0xFA1FFFFFFF DEC 21154 PCI to PCI bridge OK
0xF9800000-0xFA1FFFFFFF Mylex EXR2000 Disk Array Controller OK
0xFA800000-0xFAFFFFFFF PCI bus OK
0xFA800000-0xFAFFFFFFF DEC 21154 PCI to PCI bridge OK
0xFA800000-0xFAFFFFFFF Mylex EXR2000 Disk Array Controller OK
0xFB000000-0xFB9FFFFFFF PCI bus OK
0xFB000000-0xFB9FFFFFFF DEC 21154 PCI to PCI bridge OK
0xFB000000-0xFB9FFFFFFF Mylex EXR2000 Disk Array Controller OK
0xFC000000-0xFC7FFFFFFF PCI bus OK
0xFC000000-0xFC7FFFFFFF DEC 21154 PCI to PCI bridge OK
0xFC000000-0xFC7FFFFFFF Mylex EXR2000 Disk Array Controller OK
0xFC800000-0xFC8FFFFFFF PCI bus OK
0xFC800000-0xFC8FFFFFFF Alteon WebSystems PCI Gigabit Ethernet Adapter
OK

```

System Information report written at: 03/05/2002 08:35:44 AM

[Components]

[Following are sub-categories of this main category]

[Multimedia]

[Following are sub-categories of this main category]

[Audio Codecs]

CodecManufacturer	Description	Status	File Version	Size
	Creation Date			
c:\winnt\system32\iac25_32.ax	Intel Corporation	Indeo® audio software	2.05.53	195.00 KB (199,680 bytes)
c:\winnt\system32\msg723.acm	Microsoft Corporation	OK	4.4.3385	106.77 KB (109,328 bytes)
c:\winnt\system32\lhacm.acm	Microsoft Corporation	OK	4.4.3385	33.27 KB (34,064 bytes)
c:\winnt\system32\tssoft32.acm	DSP GROUP, INC.	OK	1.01	9.27 KB (9,488 bytes)
c:\winnt\system32\msg711.acm	Microsoft Corporation	OK	5.00.2134.1	10.27 KB (10,512 bytes)
c:\winnt\system32\imaadp32.acm	Microsoft Corporation	OK	5.00.2134.1	16.27 KB (16,656 bytes)
c:\winnt\system32\msadp32.acm	Microsoft Corporation	OK	5.00.2134.1	14.77 KB (15,120 bytes)

```

c:\winnt\system32\msgsm32.acm Microsoft Corporation OK
C:\WINNT\System32\MSGSM32.ACM 5.00.2134.1 22.27 KB (22,800
bytes) 12/7/1999 1:00:00 PM

```

[Video Codecs]

CodecManufacturer	Description	Status	File Version	Size
	Creation Date			
c:\winnt\system32\ir50_32.dll	Intel Corporation	Indeo® video 5.10	R.5.10.15.2.55	737.50 KB (755,200 bytes)
c:\winnt\system32\msh261.drv	Microsoft Corporation	OK	4.4.3385	163.77 KB (167,696 bytes)
c:\winnt\system32\msh263.drv	Microsoft Corporation	OK	4.4.3385	252.27 KB (258,320 bytes)
c:\winnt\system32\msvidc32.dll	Microsoft Corporation	OK	5.00.2134.1	27.27 KB (27,920 bytes)
c:\winnt\system32\ir32_32.dll	Intel(R) Corporation	OK	Not Available	194.50 KB (199,168 bytes)
c:\winnt\system32\iccvid.dll	Radius Inc.	OK	1.10.0.6	108.00 KB (110,592 bytes)
c:\winnt\system32\msrle32.dll	Microsoft Corporation	OK	5.00.2134.1	10.77 KB (11,024 bytes)

[CD-ROM]

```

Item Value
DriveD:
Description CD-ROM Drive
Media Loaded False
Media Type CD-ROM
Name MITSUMI CD-ROM SR243T
Manufacturer (Standard CD-ROM drives)
Status OK
Transfer Rate Not Available
SCSI Target ID 0
PNP Device ID IDE\CDROMMITSUMI_CD-
ROM_SR243T_L02F_\5&1159A16&0&0.0.0

```

[Sound Device]

```

Item Value
No sound devices

```

[Display]

Item Value
Name ATI Technologies Inc. RAGE XL PCI
PNP Device ID
PCI\VEN_1002&DEV_4752&SUBSYS_0083110A&REV_27\3&291BF6FF&0&28
Adapter Type ATI RAGE XL PCI, ATI Technologies Inc. compatible
Adapter Description ATI Technologies Inc. RAGE XL PCI
Adapter RAM 8.00 MB (8,388,608 bytes)
Installed Drivers atidrab.dll
Driver Version 5.00.2179.1
INF File display.inf (atirage3 section)
Color Planes 1
Color Table Entries 65536
Resolution 800 x 600 x 72 hertz
Bits/Pixel 16

[Infrared]

Item Value
No infrared devices

[Input]

[Following are sub-categories of this main category]

[Keyboard]

Item Value
Description Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
Name Enhanced (101- or 102-key)
Layout 00000409
PNP Device ID ACPI\PNP0303\4&2647A8AF&0
NumberOfFunctionKeys 12

[Pointing Device]

Item Value
Hardware Type PS/2 Compatible Mouse
Number of Buttons 3
Status OK
PNP Device ID ACPI\PNP0F13\4&2647A8AF&0
Power Management Supported False
Double Click Threshold 6
Handedness Right Handed Operation

[Modem]

Item Value
No modems

[Network]

[Following are sub-categories of this main category]

[Adapter]

Item Value
Name [00000000] RAS Async Adapter
Adapter Type Not Available
Product Name RAS Async Adapter
Installed True
PNP Device ID Not Available
Last Reset 3/4/2002 11:20:22 AM
Index0
Service Name AsyncMac
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Not Available

Name [00000001] WAN Miniport (L2TP)
Adapter Type Not Available
Product Name WAN Miniport (L2TP)
Installed True
PNP Device ID ROOT\MS_L2TPMINIPORT\0000
Last Reset 3/4/2002 11:20:22 AM
Index1
Service Name Rasl2tp
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Rasl2tp
Driver c:\winnt\system32\drivers\rasl2tp.sys (50800, 5.00.2179.1)

Name [00000002] WAN Miniport (PPTP)
Adapter Type Wide Area Network (WAN)
Product Name WAN Miniport (PPTP)
Installed True
PNP Device ID ROOT\MS_PPTPMINIPORT\0000
Last Reset 3/4/2002 11:20:22 AM
Index2
Service Name PptpMiniport
IP Address Not Available
IP Subnet Not Available

Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address 50:50:54:50:30:30
Service Name PptpMiniport
Driver c:\winnt\system32\drivers\rasppptp.sys (47856, 5.00.2160.1)

Name [00000003] Direct Parallel
Adapter Type Not Available
Product Name Direct Parallel
Installed True
PNP Device ID ROOT\MS_PTMINIPOINT\0000
Last Reset 3/4/2002 11:20:22 AM

Index3
Service Name Raspti
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Raspti
Driver c:\winnt\system32\drivers\raspti.sys (16880, 5.00.2146.1)

Name [00000004] WAN Miniport (IP)
Adapter Type Not Available
Product Name WAN Miniport (IP)
Installed True
PNP Device ID ROOT\MS_NDISWANIP\0000
Last Reset 3/4/2002 11:20:22 AM

Index4
Service Name NdisWan
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name NdisWan
Driver c:\winnt\system32\drivers\ndiswan.sys (90096, 5.00.2195.2779)

Name [00000005] Intel 8255x-based PCI Ethernet Adapter (10/100)
Adapter Type Not Available
Product Name Intel 8255x-based PCI Ethernet Adapter (10/100)
Installed True
PNP Device ID Not Available
Last Reset 3/4/2002 11:20:22 AM

Index5
Service Name E100B
IP Address 129.103.181.251
IP Subnet 255.255.255.0
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address 00:60:CF:20:03:6E
Service Name Not Available

Name [00000006] Intel 8255x-based PCI Ethernet Adapter (10/100)
Adapter Type Not Available
Product Name Intel 8255x-based PCI Ethernet Adapter (10/100)
Installed True
PNP Device ID
PCI\VEN_8086&DEV_1229&SUBSYS_0083110A&REV_09\3&2AEF1B1C&0&48
Last Reset 3/4/2002 11:20:22 AM

Index6
Service Name E100B
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled True
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name E100B
Driver c:\winnt\system32\drivers\e100bnt5.sys (119056, 5.40.11.0000)

Name [00000007] Alteon WebSystems PCI Gigabit Ethernet Adapter
Adapter Type Ethernet 802.3
Product Name Alteon WebSystems PCI Gigabit Ethernet Adapter
Installed True
PNP Device ID
PCI\VEN_12AE&DEV_0001&SUBSYS_00000000&REV_01\3&2AEF1B1C&0&28
Last Reset 3/4/2002 11:20:22 AM

Index7
Service Name altnd5
IP Address 129.103.181.251
IP Subnet 255.255.255.0
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address 00:60:CF:20:03:6E
Service Name altnd5
IRQ Number 18
Driver c:\winnt\system32\drivers\altnd5.sys (597776, 1.17.13)

[Protocol]

Item Value
Name MSAFD Tcpip [TCP/IP]
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 16 bytes
MaximumMessageSize 0 bytes
MessageOriented False
MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData True
SupportsGracefulClosing True
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD Tcpip [UDP/IP]
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 16 bytes
MaximumMessageSize 65467 bytes
MessageOriented True
MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting True

Name RSVP UDP Service Provider
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 16 bytes
MaximumMessageSize 65467 bytes
MessageOriented True
MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption True

SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting True

Name RSVP TCP Service Provider
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 16 bytes
MaximumMessageSize 0 bytes
MessageOriented False
MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption True
SupportsExpeditedData True
SupportsGracefulClosing True
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\\Device\\NetBT_Tcpip_{94EA42D7-2D61-4FF8-BE75-502153BA7F26}] SEQPACKET 4
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\\Device\\NetBT_Tcpip_{94EA42D7-2D61-4FF8-BE75-502153BA7F26}] DATAGRAM 4
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True

SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{F6AFCEF4-10BC-4DF5-B6B3-03E207EAA97C}] SEQPACKET 3
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{F6AFCEF4-10BC-4DF5-B6B3-03E207EAA97C}] DATAGRAM 3
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{4BCAF550-58F2-4980-8BB6-BA327F2239C6}] SEQPACKET 0
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes

MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{4BCAF550-58F2-4980-8BB6-BA327F2239C6}] DATAGRAM 0
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{615586FA-2158-413F-B657-99FE2790A24F}] SEQPACKET 1
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{615586FA-2158-413F-B657-99FE2790A24F}] DATAGRAM 1
ConnectionlessService True

GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{2E8A660D-603D-4D5A-9F8B-CEADE80A363E}] SEQPACKET 2
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{2E8A660D-603D-4D5A-9F8B-CEADE80A363E}] DATAGRAM 2
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

[WinSock]

Item Value
File c:\winnt\system32\winsock.dll
Version 3.10
Size 2.80 KB (2,864 bytes)

File c:\winnt\system32\wsock32.dll
Version 5.00.2195.2871
Size 21.27 KB (21,776 bytes)

[Ports]

[Following are sub-categories of this main category]

[Serial]

Item Value
Name COM1
Status OK
PNP Device ID ACPI\PNP0501\1
Maximum Input Buffer Size 0
Maximum Output Buffer Size False
Settable Baud Rate True
Settable Data Bits True
Settable Flow Control True
Settable Parity True
Settable Parity Check True
Settable Stop Bits True
Settable RLSD True
Supports RLSD True
Supports 16 Bit Mode False
Supports Special Characters False
Baud Rate 9600
Bits/Byte 8
Stop Bits 1
Parity None
Busy 0
Abort Read/Write on Error 0
Binary Mode Enabled -1
Continue Xmit on XOff 0
CTS Outflow Control 0
Discard NULL Bytes 0
DSR Outflow Control 0
DSR Sensitivity 0
DTR Flow Control Type Enable
EOF Character 0
Error Replace Character 0
Error Replacement Enabled 0
Event Character 0

Parity Check Enabled 0
RTS Flow Control Type Enable
XOff Character 19
XOffXmit Threshold 512
XOn Character 17
XOnXmit Threshold 2048
XOnXOff InFlow Control 0
XOnXOff OutFlow Control 0
IRQ Number 3
I/O Port 0x02F8-0x02FF
Driver c:\winnt\system32\drivers\serial.sys (62416, 5.00.2195.2780)

Name COM2
Status OK
PNP Device ID ACPI\PNP0501\2
Maximum Input Buffer Size 0
Maximum Output Buffer Size False
Settable Baud Rate True
Settable Data Bits True
Settable Flow Control True
Settable Parity True
Settable Parity Check True
Settable Stop Bits True
Settable RLSD True
Supports RLSD True
Supports 16 Bit Mode False
Supports Special Characters False
Baud Rate 9600
Bits/Byte 8
Stop Bits 1
Parity None
Busy 0
Abort Read/Write on Error 0
Binary Mode Enabled -1
Continue Xmit on Xoff 0
CTS Outflow Control 0
Discard NULL Bytes 0
DSR Outflow Control 0
DSR Sensitivity 0
DTR Flow Control Type Enable
EOF Character 0
Error Replace Character 0
Error Replacement Enabled 0
Event Character 0
Parity Check Enabled 0
RTS Flow Control Type Enable
XOff Character 19
XOffXmit Threshold 512
XOn Character 17
XOnXmit Threshold 2048
XOnXOff InFlow Control 0
XOnXOff OutFlow Control 0
IRQ Number 4

I/O Port 0x03F8-0x03FF
Driver c:\winnt\system32\drivers\serial.sys (62416, 5.00.2195.2780)

[Parallel]

Item Value
Name LPT1
PNP Device ID ACPI\PNP0401\4&2647A8AF&0

[Storage]

[Following are sub-categories of this main category]

[Drives]

Item Value
DriveA:
Description 3 1/2 Inch Floppy Drive

DriveC:
Description Local Fixed Disk
Compressed False
File System NTFS
Size 17.01 GB (18,268,311,552 bytes)
Free Space 12.52 GB (13,438,304,256 bytes)
Volume Name
Volume Serial Number DC603830
Partition Disk #0, Partition #0
Partition Size 17.01 GB (18,268,314,624 bytes)
Starting Offset 32256 bytes
Drive Description Disk drive
Drive Manufacturer (Standard disk drives)
Drive Model FUJITSU MAG3182LC SCSI Disk Device
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 1
Drive SCSI Bus 0
Drive SCSI Logical Unit 0
Drive SCSI Port 2
Drive SCSI Target Id 3
Drive SectorsPerTrack 63
Drive Size 18268346880 bytes
Drive TotalCylinders 2221
Drive TotalSectors 35680365
Drive TotalTracks 566355
Drive TracksPerCylinder 255

DriveE:
Description Local Fixed Disk
Compressed Not Available

File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #2, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE2
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 5
Drive SCSTargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveF:
Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #3, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE3
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 6
Drive SCSTargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495

Drive TracksPerCylinder 255

DriveG:
Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #4, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE4
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 7
Drive SCSTargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveH:
Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #5, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE5
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 8
Drive SCSTargetId 0

Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveI:

Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #6, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE6
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSI Bus 4
Drive SCSI LogicalUnit 0
Drive SCSI Port 9
Drive SCSI TargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveL:

Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #1, Partition #0
Partition Size 119.48 GB (128,289,692,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE1
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media

Drive Partitions 1
Drive SCSI Bus 4
Drive SCSI LogicalUnit 0
Drive SCSI Port 4
Drive SCSI TargetId 0
Drive SectorsPerTrack 63
Drive Size 128297917440 bytes
Drive TotalCylinders 15598
Drive TotalSectors 250581870
Drive TotalTracks 3977490
Drive TracksPerCylinder 255

DriveN:

Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #2, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE2
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSI Bus 4
Drive SCSI LogicalUnit 0
Drive SCSI Port 5
Drive SCSI TargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveO:

Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #3, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE3

Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSI Bus 4
Drive SCSI LogicalUnit 0
Drive SCSI Port 6
Drive SCSI TargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveP:

Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #4, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE4
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSI Bus 4
Drive SCSI LogicalUnit 0
Drive SCSI Port 7
Drive SCSI TargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveQ:

Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available

Volume Serial Number Not Available
Partition Disk #5, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE5
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSI Bus 4
Drive SCSI LogicalUnit 0
Drive SCSI Port 8
Drive SCSI TargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveR:

Description Local Fixed Disk
Compressed Not Available
File System Not Available
Size Not Available
Free Space Not Available
Volume Name Not Available
Volume Serial Number Not Available
Partition Disk #6, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE6
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSI Bus 4
Drive SCSI LogicalUnit 0
Drive SCSI Port 9
Drive SCSI TargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveV:

Description Local Fixed Disk

Compressed False
File System NTFS
Size 195.31 GB (209,711,706,112 bytes)
Free Space 80.37 GB (86,297,014,272 bytes)
Volume Name backup5
Volume Serial Number 900EC9EB
Partition Disk #6, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE6
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 9
Drive SCSTargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveW:
Description Local Fixed Disk
Compressed False
File System NTFS
Size 195.31 GB (209,711,706,112 bytes)
Free Space 80.37 GB (86,296,948,736 bytes)
Volume Name backup4
Volume Serial Number 04FD68FA
Partition Disk #5, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE5
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 8
Drive SCSTargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185

Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveX:
Description Local Fixed Disk
Compressed False
File System NTFS
Size 195.31 GB (209,711,706,112 bytes)
Free Space 79.25 GB (85,098,795,008 bytes)
Volume Name backup1
Volume Serial Number 64C06FCC
Partition Disk #2, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE2
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 5
Drive SCSTargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveY:
Description Local Fixed Disk
Compressed False
File System NTFS
Size 195.31 GB (209,711,706,112 bytes)
Free Space 80.36 GB (86,283,358,208 bytes)
Volume Name bachup2
Volume Serial Number 38F2D544
Partition Disk #3, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE3
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCSIbus 4
Drive SCSILogicalUnit 0
Drive SCSIPort 6

Drive SCSITargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

DriveZ:
Description Local Fixed Disk
Compressed False
File System NTFS
Size 195.31 GB (209,711,706,112 bytes)
Free Space 80.37 GB (86,296,948,736 bytes)
Volume Name backup3
Volume Serial Number 24E4D799
Partition Disk #4, Partition #0
Partition Size 751.08 GB (806,464,028,160 bytes)
Starting Offset 8225280 bytes
Drive Description \\.\PHYSICALDRIVE4
Drive Manufacturer Not Available
Drive Model Not Available
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 3
Drive SCISIBus 4
Drive SCSILogicalUnit 0
Drive SCSIIPort 7
Drive SCSITargetId 0
Drive SectorsPerTrack 63
Drive Size 806480478720 bytes
Drive TotalCylinders 98049
Drive TotalSectors 1575157185
Drive TotalTracks 25002495
Drive TracksPerCylinder 255

[SCSI]

Item Value
Name Mylex EXR2000 Disk Array Controller
Caption Mylex EXR2000 Disk Array Controller
Driver dac2w2k
Status OK
PNP Device ID
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2254B0D&0&4030
Device ID PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2254B0D&0&4030
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 28
I/O Port 0x2000-0x3FFF

Driver c:\winnt\system32\drivers\dac2w2k.sys (185488, 6.00-03)
Name FSC Storage Subsystem
Caption FSC Storage Subsystem
Driver Not Available
Status OK
PNP Device ID
SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.06\5&2EB0A3BB&0&080
Device ID SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.06\5&2EB0A3BB&0&080
Device Map Not Available
Index Not Available
Max Number Controlled Not Available

Name FSC Storage Subsystem
Caption FSC Storage Subsystem
Driver Not Available
Status OK
PNP Device ID
SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.06\5&2EB0A3BB&0&180
Device ID SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.06\5&2EB0A3BB&0&180
Device Map Not Available
Index Not Available
Max Number Controlled Not Available

Name Mylex EXR2000 Disk Array Controller
Caption Mylex EXR2000 Disk Array Controller
Driver dac2w2k
Status OK
PNP Device ID
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1C72A60D&0&4038
Device ID PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1C72A60D&0&4038
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 30
I/O Port 0x3000-0x3FFF
Driver c:\winnt\system32\drivers\dac2w2k.sys (185488, 6.00-03)

Name Mylex EXR2000 Disk Array Controller
Caption Mylex EXR2000 Disk Array Controller
Driver dac2w2k
Status OK
PNP Device ID
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1ECE4987&0&4028
Device ID PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1ECE4987&0&4028
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 26
I/O Port 0x5000-0x5FFF
Driver c:\winnt\system32\drivers\dac2w2k.sys (185488, 6.00-03)

Name Adaptec AIC-7899 Ultra160/m PCI SCSI Card

Caption Adaptec AIC-7899 Ultra160/m PCI SCSI Card
Driver adpul60m
Status OK
PNP Device ID
PCI\VEN_9005&DEV_00CF&SUBSYS_0083110A&REV_01\3&12F48E42&0&40
Device ID PCI\VEN_9005&DEV_00CF&SUBSYS_0083110A&REV_01\3&12F48E42&0&40
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 38
I/O Port 0x4000-0x5FFF
Driver c:\winnt\system32\drivers\adpul60m.sys (64432, v3.10a)

Name Adaptec AIC-7899 Ultra160/m PCI SCSI Card
Caption Adaptec AIC-7899 Ultra160/m PCI SCSI Card
Driver adpul60m
Status OK
PNP Device ID
PCI\VEN_9005&DEV_00CF&SUBSYS_0083110A&REV_01\3&12F48E42&0&41
Device ID PCI\VEN_9005&DEV_00CF&SUBSYS_0083110A&REV_01\3&12F48E42&0&41
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 39
I/O Port 0x4400-0x44FF
Driver c:\winnt\system32\drivers\adpul60m.sys (64432, v3.10a)

Name Mylex EXR2000 Disk Array Controller
Caption Mylex EXR2000 Disk Array Controller
Driver dac2w2k
Status OK
PNP Device ID
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2F92D4B0&0&4020
Device ID PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2F92D4B0&0&4020
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 24
I/O Port 0x6000-0x6FFF
Driver c:\winnt\system32\drivers\dac2w2k.sys (185488, 6.00-03)

Name Mylex EXR2000 Disk Array Controller
Caption Mylex EXR2000 Disk Array Controller
Driver dac2w2k
Status OK
PNP Device ID
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2DF34B01&0&4018
Device ID PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2DF34B01&0&4018
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 22
I/O Port 0x7000-0x7FFF

Driver c:\winnt\system32\drivers\dac2w2k.sys (185488, 6.00-03)
Name Mylex EXR2000 Disk Array Controller
Caption Mylex EXR2000 Disk Array Controller
Driver dac2w2k
Status OK
PNP Device ID
PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2BEE4042&0&4010
Device ID PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2BEE4042&0&4010
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 20
I/O Port 0x8000-0x8FFF
Driver c:\winnt\system32\drivers\dac2w2k.sys (185488, 6.00-03)

Name FSC Storage Subsystem
Caption FSC Storage Subsystem
Driver Not Available
Status OK
PNP Device ID
SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&080
Device ID SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&080
Device Map Not Available
Index Not Available
Max Number Controlled Not Available

Name FSC Storage Subsystem
Caption FSC Storage Subsystem
Driver Not Available
Status OK
PNP Device ID
SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&180
Device ID SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&180
Device Map Not Available
Index Not Available
Max Number Controlled Not Available

Name FSC Storage Subsystem
Caption FSC Storage Subsystem
Driver Not Available
Status OK
PNP Device ID
SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&280
Device ID SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&280
Device Map Not Available
Index Not Available
Max Number Controlled Not Available

Name FSC Storage Subsystem
Caption FSC Storage Subsystem
Driver Not Available
Status OK

```
PNP Device ID
  SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&380
Device ID SCSI\PROCESSOR&VEN_QLOGIC&PROD_GEM359&REV_1.07\5&944483E&0&380
Device Map Not Available
Index Not Available
Max Number Controlled      Not Available
```

[Printing]

```
Name Port Name Server Name
No printing information
```

[Problem Devices]

```
Device      PNP Device ID  Error Code
Intel 8255x-based PCI Ethernet Adapter (10/100) #2
  PCI\VEN_8086&DEV_1229&SUBSYS_0083110A&REV_09\3&2AEF1B1C&0&48    22
```

[USB]

```
Device      PNP Device ID
Standard OpenHCD USB Host Controller
  PCI\VEN_1166&DEV_0220&SUBSYS_02201166&REV_05\3&291BF6FF&0&7A
USB Root Hub  USB\ROOT_HUB\4&19BF1ADC&0
```

===== disk configuration controller 0 =====

```
Begin
BeginGroup
  PhysicalDevice0 = Channel=0, Target=0, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice1 = Channel=1, Target=0, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice2 = Channel=0, Target=1, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice3 = Channel=1, Target=1, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice4 = Channel=0, Target=2, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice5 = Channel=1, Target=2, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice6 = Channel=0, Target=3, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice7 = Channel=1, Target=3, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice8 = Channel=0, Target=4, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice9 = Channel=1, Target=4, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice10 = Channel=0, Target=10, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
  PhysicalDevice11 = Channel=1, Target=10, Size=17480mb, State=Online,
    TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
```

```
PhysicalDevice12 = Channel=0, Target=11, Size=17480mb, State=Online,
  TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice13 = Channel=1, Target=11, Size=17480mb, State=Online,
  TransferSpeed=80MHz, TransferWidth=16Bit, MaxTag=16;
IntermediateDevice0 = StripeSize=128kb, Raid=1, WriteThrough=1,
Size=17480mb,
  (PhysicalDevice0, StartAddress=0mb, Size=17480mb),
  (PhysicalDevice1, StartAddress=0mb, Size=17480mb);
IntermediateDevice1 = StripeSize=128kb, Raid=1, WriteThrough=1,
Size=17480mb,
  (PhysicalDevice2, StartAddress=0mb, Size=17480mb),
  (PhysicalDevice3, StartAddress=0mb, Size=17480mb);
IntermediateDevice2 = StripeSize=128kb, Raid=1, WriteThrough=1,
Size=17480mb,
  (PhysicalDevice4, StartAddress=0mb, Size=17480mb),
  (PhysicalDevice5, StartAddress=0mb, Size=17480mb);
IntermediateDevice3 = StripeSize=128kb, Raid=1, WriteThrough=1,
Size=17480mb,
  (PhysicalDevice6, StartAddress=0mb, Size=17480mb),
  (PhysicalDevice7, StartAddress=0mb, Size=17480mb);
IntermediateDevice4 = StripeSize=128kb, Raid=1, WriteThrough=1,
Size=17480mb,
  (PhysicalDevice8, StartAddress=0mb, Size=17480mb),
  (PhysicalDevice9, StartAddress=0mb, Size=17480mb);
IntermediateDevice5 = StripeSize=128kb, Raid=1, WriteThrough=1,
Size=17480mb,
  (PhysicalDevice10, StartAddress=0mb, Size=17480mb),
  (PhysicalDevice11, StartAddress=0mb, Size=17480mb);
IntermediateDevice6 = StripeSize=128kb, Raid=1, WriteThrough=1,
Size=17480mb,
  (PhysicalDevice12, StartAddress=0mb, Size=17480mb),
  (PhysicalDevice13, StartAddress=0mb, Size=17480mb);
LogicalDevice0 = StripeSize=128kb, Raid=12, WriteThrough=1,
Size=122360mb, BIOSGeometry=8GB,
  (IntermediateDevice0, StartAddress=0mb, Size=34960mb),
  (IntermediateDevice1, StartAddress=0mb, Size=34960mb),
  (IntermediateDevice2, StartAddress=0mb, Size=34960mb),
  (IntermediateDevice3, StartAddress=0mb, Size=34960mb),
  (IntermediateDevice4, StartAddress=0mb, Size=34960mb),
  (IntermediateDevice5, StartAddress=0mb, Size=34960mb),
  (IntermediateDevice6, StartAddress=0mb, Size=34960mb);
EndGroup
BeginControllerParameter
  ControllerName = eXtremeRAID 2000;
  ControllerType = 28;
  FirmwareVersion = 5.60;
  CacheLineSize = 8KB;
  BackgroundTaskRate = 50;
  InitiatorID = 7;
  DiskStartupMode = AutoSpin;
  DevicesPerSpin = 2;
  InitialDelay = 6S;
  SequentialDelay = 0S;
```

```

EnableDriveSizing = 0;
EnableClustering = 0;
EnableBGInit = 1;
EnableReadAhead = 0;
EnableBiosLoadDelay = 0;
EnableForcedUnitAccess = 0;
DisableBios = 1;
EnableCDROMBoot = 0;
EnableStorageWorks = 0;
EnableSAFTE = 0;
EnableSES = 0;
EnableARM = 0;
EnableOFM = 0;
OEMCode = 0;
StartupOption = 0;
EndControllerParameter
End
===== disk configuration controller 1 .. 5 =====

Begin
BeginGroup
PhysicalDevice0 = Channel=0, Target=12, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice1 = Channel=0, Target=11, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice2 = Channel=0, Target=10, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice3 = Channel=0, Target=9, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice4 = Channel=0, Target=6, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice5 = Channel=0, Target=5, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice6 = Channel=0, Target=4, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice7 = Channel=0, Target=3, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice8 = Channel=0, Target=2, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice9 = Channel=0, Target=1, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice10 = Channel=0, Target=0, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice11 = Channel=1, Target=12, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice12 = Channel=1, Target=11, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice13 = Channel=1, Target=10, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice14 = Channel=1, Target=9, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice15 = Channel=1, Target=6, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;

```

```

PhysicalDevice16 = Channel=1, Target=5, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice17 = Channel=1, Target=4, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice18 = Channel=1, Target=3, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice19 = Channel=1, Target=2, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice20 = Channel=1, Target=1, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice21 = Channel=1, Target=0, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice22 = Channel=2, Target=12, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice23 = Channel=2, Target=11, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice24 = Channel=2, Target=10, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice25 = Channel=2, Target=9, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice26 = Channel=2, Target=6, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice27 = Channel=2, Target=5, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice28 = Channel=2, Target=4, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice29 = Channel=2, Target=3, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice30 = Channel=2, Target=2, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice31 = Channel=2, Target=1, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice32 = Channel=2, Target=0, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice33 = Channel=3, Target=12, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice34 = Channel=3, Target=11, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice35 = Channel=3, Target=10, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice36 = Channel=3, Target=9, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice37 = Channel=3, Target=6, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice38 = Channel=3, Target=5, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice39 = Channel=3, Target=4, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice40 = Channel=3, Target=3, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice41 = Channel=3, Target=2, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice42 = Channel=3, Target=1, Size=17480mb, State=Online,

```

```

TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
PhysicalDevice43 = Channel=3, Target=0, Size=17480mb, State=Online,
TransferSpeed=40MHz, TransferWidth=16Bit, MaxTag=16;
IntermediateDevice0 = StripeSize=128kb, Raid=0, WriteThrough=1,
Size=192280mb,
(PhysicalDevice0, StartAddress=0mb, Size=17480mb),
(PhysicalDevice1, StartAddress=0mb, Size=17480mb),
(PhysicalDevice2, StartAddress=0mb, Size=17480mb),
(PhysicalDevice3, StartAddress=0mb, Size=17480mb),
(PhysicalDevice4, StartAddress=0mb, Size=17480mb),
(PhysicalDevice5, StartAddress=0mb, Size=17480mb),
(PhysicalDevice6, StartAddress=0mb, Size=17480mb),
(PhysicalDevice7, StartAddress=0mb, Size=17480mb),
(PhysicalDevice8, StartAddress=0mb, Size=17480mb),
(PhysicalDevice9, StartAddress=0mb, Size=17480mb),
(PhysicalDevice10, StartAddress=0mb, Size=17480mb);
IntermediateDevice1 = StripeSize=128kb, Raid=0, WriteThrough=1,
Size=192280mb,
(PhysicalDevice11, StartAddress=0mb, Size=17480mb),
(PhysicalDevice12, StartAddress=0mb, Size=17480mb),
(PhysicalDevice13, StartAddress=0mb, Size=17480mb),
(PhysicalDevice14, StartAddress=0mb, Size=17480mb),
(PhysicalDevice15, StartAddress=0mb, Size=17480mb),
(PhysicalDevice16, StartAddress=0mb, Size=17480mb),
(PhysicalDevice17, StartAddress=0mb, Size=17480mb),
(PhysicalDevice18, StartAddress=0mb, Size=17480mb),
(PhysicalDevice19, StartAddress=0mb, Size=17480mb),
(PhysicalDevice20, StartAddress=0mb, Size=17480mb),
(PhysicalDevice21, StartAddress=0mb, Size=17480mb);
IntermediateDevice2 = StripeSize=128kb, Raid=0, WriteThrough=1,
Size=192280mb,
(PhysicalDevice22, StartAddress=0mb, Size=17480mb),
(PhysicalDevice23, StartAddress=0mb, Size=17480mb),
(PhysicalDevice24, StartAddress=0mb, Size=17480mb),
(PhysicalDevice25, StartAddress=0mb, Size=17480mb),
(PhysicalDevice26, StartAddress=0mb, Size=17480mb),
(PhysicalDevice27, StartAddress=0mb, Size=17480mb),
(PhysicalDevice28, StartAddress=0mb, Size=17480mb),
(PhysicalDevice29, StartAddress=0mb, Size=17480mb),
(PhysicalDevice30, StartAddress=0mb, Size=17480mb),
(PhysicalDevice31, StartAddress=0mb, Size=17480mb),
(PhysicalDevice32, StartAddress=0mb, Size=17480mb);
IntermediateDevice3 = StripeSize=128kb, Raid=0, WriteThrough=1,
Size=192280mb,
(PhysicalDevice33, StartAddress=0mb, Size=17480mb),
(PhysicalDevice34, StartAddress=0mb, Size=17480mb),
(PhysicalDevice35, StartAddress=0mb, Size=17480mb),
(PhysicalDevice36, StartAddress=0mb, Size=17480mb),
(PhysicalDevice37, StartAddress=0mb, Size=17480mb),
(PhysicalDevice38, StartAddress=0mb, Size=17480mb),
(PhysicalDevice39, StartAddress=0mb, Size=17480mb),
(PhysicalDevice40, StartAddress=0mb, Size=17480mb),
(PhysicalDevice41, StartAddress=0mb, Size=17480mb),

```

```

(PhysicalDevice42, StartAddress=0mb, Size=17480mb),
(PhysicalDevice43, StartAddress=0mb, Size=17480mb);
LogicalDevice0 = StripeSize=128kb, Raid=12, WriteThrough=1,
Size=769120mb, BIOSGeometry=8GB,
(IntermediateDevice0, StartAddress=0mb, Size=192280mb),
(IntermediateDevice1, StartAddress=0mb, Size=192280mb),
(IntermediateDevice2, StartAddress=0mb, Size=192280mb),
(IntermediateDevice3, StartAddress=0mb, Size=192280mb);

```

```

EndGroup
BeginControllerParameter
ControllerName = eXtremeRAID 2000;
ControllerType = 28;
FirmwareVersion = 5.60;
CacheLineSize = 8KB;
BackgroundTaskRate = 50;
InitiatorID = 7;
DiskStartupMode = AutoSpin;
DevicesPerSpin = 2;
InitialDelay = 6S;
SequentialDelay = 0S;
EnableDriveSizing = 0;
EnableClustering = 0;
EnableBGInit = 0;
EnableReadAhead = 0;
EnableBiosLoadDelay = 0;
EnableForcedUnitAccess = 1;
DisableBios = 1;
EnableCDROMBoot = 0;
EnableStorageWorks = 0;
EnableSAFTE = 0;
EnableSES = 0;
EnableARM = 0;
EnableOFM = 0;
OEMCode = 0;
StartupOption = 0;
EndControllerParameter
End

```

System Information report written at: 03/05/2002 08:35:10 AM
[Software Environment]

[Following are sub-categories of this main category]

[Drivers]

Name	Description	File Type	Started	Start Mode	State	Status	Error
Control	Accept Pause	Accept Stop					
abiosdsk	Abiosdsk	Not Available	Kernel Driver	False	Disabled		
	Stopped	OK	Ignore	False	False		
abp480n5	abp480n5	Not Available	Kernel Driver	False	Disabled		
	Stopped	OK	Normal	False	False		

```

acpi Microsoft ACPI Driver      c:\winnt\system32\drivers\acpi.sys
Kernel Driver True Boot Running OK Normal FalseTrue
acpiec ACPIEC c:\winnt\system32\drivers\acpiec.sys Kernel Driver
FalseDisabled Stopped OK Normal FalseFalse
adpul60m adpul60m c:\winnt\system32\drivers\adpul60m.sys Kernel
Driver True Boot Running OK Normal FalseTrue
afd AFD Networking Support Environment
c:\winnt\system32\drivers\afd.sys Kernel Driver True Auto
Running OK Normal FalseTrue
aha154x Aha154x Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
aic116x aic116x Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
aic78u2 aic78u2 Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
aic78xx aic78xx Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
altnd5 Alteon WebSystems PCI Gigabit Ethernet Adapter
c:\winnt\system32\drivers\altnd5.sys Kernel Driver True Manual
Running OK Normal FalseTrue
ami0nt ami0nt Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
amsint amsint Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
asc asc Not Available Kernel Driver FalseDisabled Stopped OK
Normal FalseFalse
asc3350p asc3350p Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
asc3550 asc3550 Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
asynctac RAS Asynchronous Media Driver
c:\winnt\system32\drivers\asynctac.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
atapi Standard IDE/ESDI Hard Disk Controller
c:\winnt\system32\drivers\atapi.sys Kernel Driver True Boot
Running OK Normal FalseTrue
atdisk Atdisk Not Available Kernel Driver FalseDisabled
Stopped OK Ignore FalseFalse
atirage3 atirage3 c:\winnt\system32\drivers\atimpab.sys Kernel
Driver True Manual Running OK Ignore FalseTrue
atmarpc ATM ARP Client Protocol
c:\winnt\system32\drivers\atmarpc.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
audstub Audio Stub Driver c:\winnt\system32\drivers\audstub.sys
Kernel Driver True Manual Running OK Normal FalseTrue
beep Beep c:\winnt\system32\drivers\beep.sys Kernel Driver True
System Running OK Normal FalseTrue
buslogic BusLogic Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
cd20xrnt cd20xrnt Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
cdaudio Cdaudio c:\winnt\system32\drivers\cdaudio.sys Kernel
Driver FalseSystem Stopped OK Ignore FalseFalse

```

```

cdfs Cdfs c:\winnt\system32\drivers\cdfs.sys File System Driver True
Disabled Running OK Normal FalseTrue
cdrom CD-ROM Driver c:\winnt\system32\drivers\cdrom.sys Kernel Driver
True System Running OK Normal FalseTrue
changer Changer Not Available Kernel Driver FalseSystem
Stopped OK Ignore FalseFalse
cpqarray Cpqarray Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
cpqarray2 cpqarray2 Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
cpqfcalm cpqfcalm Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
cpqfws2e cpqfws2e Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
dac2w2k dac2w2k c:\winnt\system32\drivers\dac2w2k.sys Kernel
Driver True Boot Running OK Normal FalseTrue
dac960nt dac960nt Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
deckzpsx deckzpsx Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
dfsdriver DfsDriver c:\winnt\system32\drivers\dfs.sys File System
Driver True Boot Running OK Normal FalseTrue
disk Disk Driver c:\winnt\system32\drivers\disk.sys Kernel Driver
True Boot Running OK Normal FalseTrue
diskperf Diskperf c:\winnt\system32\drivers\diskperf.sys Kernel
Driver FalseDisabled Stopped OK Normal FalseFalse
dmboot dmboot c:\winnt\system32\drivers\dmboot.sys Kernel Driver
FalseDisabled Stopped OK Normal FalseFalse
dmio Logical Disk Manager Driver c:\winnt\system32\drivers\dmio.sys
Kernel Driver True Boot Running OK Normal FalseTrue
dmload dmload c:\winnt\system32\drivers\dmload.sys Kernel Driver
True Boot Running OK Normal FalseTrue
dspicifg DsPciCfg \??\c:\winnt\system32\drivers\dspicifg.sys
Kernel Driver True Auto Running OK Normal FalseTrue
e1000 Intel(R) PRO/1000 Adapter Driver
c:\winnt\system32\drivers\e1000nt5.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
e100b Intel(R) PRO Adapter Driver
c:\winnt\system32\drivers\e100bnt5.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
efs EFS c:\winnt\system32\drivers\efs.sys File System Driver True
Disabled Running OK Normal FalseTrue
fastfat Fastfat c:\winnt\system32\drivers\fastfat.sys File
System Driver True Disabled Running OK Normal FalseTrue
fd16_700 Fd16_700 Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
fdc Floppy Disk Controller Driver c:\winnt\system32\drivers\fdc.sys
Kernel Driver True Manual Running OK Normal FalseTrue
fips Fips c:\winnt\system32\drivers\fips.sys Kernel Driver True Auto
Running OK Normal FalseTrue
fireport fireport Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse

```

```

flashpnt flashpnt Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
flpydisk Floppy Disk Driver c:\winnt\system32\drivers\flpydisk.sys
Kernel Driver True Manual Running OK Normal FalseTrue
ftdisk Volume Manager Driver c:\winnt\system32\drivers\ftdisk.sys
Kernel Driver True Boot Running OK Normal FalseTrue
gamdrv gamdrv c:\winnt\system32\drivers\gamdrv.sys Kernel Driver
True Boot Running OK Normal FalseTrue
gpc Generic Packet Classifier c:\winnt\system32\drivers\msgpc.sys
Kernel Driver True Manual Running OK Normal FalseTrue
i8042prt i8042 Keyboard and PS/2 Mouse Port Driver
c:\winnt\system32\drivers\i8042prt.sys Kernel Driver True
System Running OK Normal FalseTrue
ini910u ini910u Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
intelide IntelIde Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
interruptaffinityfilter Interrupt Affinity Filter
c:\winnt\system32\drivers\intfiltr.sys Kernel Driver True Boot
Running OK Normal FalseTrue
ipfilterdriver IP Traffic Filter Driver
c:\winnt\system32\drivers\ipfltdrv.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
ipinip IP in IP Tunnel Driver c:\winnt\system32\drivers\ipinip.sys
Kernel Driver FalseManual Stopped OK Normal FalseFalse
ipnat IP Network Address Translator c:\winnt\system32\drivers\ipnat.sys
Kernel Driver FalseManual Stopped OK Normal FalseFalse
ipsec IPSEC driver c:\winnt\system32\drivers\ipsec.sys Kernel Driver
FalseManual Stopped OK Normal FalseFalse
ipsraidn ipsraidn Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
isapnp PnP ISA/EISA Bus Driver c:\winnt\system32\drivers\isapnp.sys
Kernel Driver True Boot Running OK Critical FalseTrue
kbdclass Keyboard Class Driver
c:\winnt\system32\drivers\kbdclass.sys Kernel Driver True
System Running OK Normal FalseTrue
ksecdd KSecDD c:\winnt\system32\drivers\ksecdd.sys Kernel Driver
True Boot Running OK Normal FalseTrue
lbrtfdc lbrtfdc Not Available Kernel Driver FalseSystem
Stopped OK Ignore FalseFalse
lp6nds35 lp6nds35 Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
macdisk macdisk c:\winnt\system32\drivers\mac2w2k.sys Kernel
Driver True Boot Running OK Normal FalseTrue
mmddmmdd c:\winnt\system32\drivers\mmdd.sys Kernel Driver True
System Running OK Ignore FalseTrue
modemModem c:\winnt\system32\drivers\modem.sys Kernel Driver False
Manual Stopped OK Ignore FalseFalse
mouclass Mouse Class Driver c:\winnt\system32\drivers\mouclass.sys
Kernel Driver True System Running OK Normal FalseTrue
mountmgr MountMgr c:\winnt\system32\drivers\mountmgr.sys Kernel
Driver True Boot Running OK Normal FalseTrue

```

```

mraid35x mraid35x Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
mrxsmb MRXSMB c:\winnt\system32\drivers\mrxsmb.sys File System
Driver True System Running OK Normal FalseTrue
msfs Msfs c:\winnt\system32\drivers\msfs.sys File System Driver True
System Running OK Normal FalseTrue
mksrv Microsoft Streaming Service Proxy
c:\winnt\system32\drivers\mksrv.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
mspclock Microsoft Streaming Clock Proxy
c:\winnt\system32\drivers\mspclock.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
mspqm Microsoft Streaming Quality Manager Proxy
c:\winnt\system32\drivers\mspqm.sys Kernel Driver FalseManual
Stopped OK Normal FalseFalse
mup Mup c:\winnt\system32\drivers\mup.sys File System Driver True
Boot Running OK Normal FalseTrue
ncrc710 Ncrc710 Not Available Kernel Driver FalseDisabled
Stopped OK Normal FalseFalse
ndis NDIS System Driver c:\winnt\system32\drivers\ndis.sys Kernel
Driver True Boot Running OK Normal FalseTrue
ndistapi Remote Access NDIS TAPI Driver
c:\winnt\system32\drivers\ndistapi.sys Kernel Driver True
Manual Running OK Normal FalseTrue
ndiswan Remote Access NDIS WAN Driver
c:\winnt\system32\drivers\ndiswan.sys Kernel Driver True
Manual Running OK Normal FalseTrue
ndproxy NDIS Proxy c:\winnt\system32\drivers\ndproxy.sys Kernel
Driver True Manual Running OK Normal FalseTrue
netbios NetBIOS Interface c:\winnt\system32\drivers\netbios.sys
File System Driver True System Running OK Normal False
True
netbtNetBios over Tcpip c:\winnt\system32\drivers\netbt.sys Kernel
Driver True System Running OK Normal FalseTrue
netdetect NetDetect c:\winnt\system32\drivers\netdetect.sys Kernel
Driver FalseManual Stopped OK Normal FalseFalse
npfs Npfs c:\winnt\system32\drivers\npfs.sys File System Driver True
System Running OK Normal FalseTrue
ntfs Ntfs c:\winnt\system32\drivers\ntfs.sys File System Driver True
Disabled Running OK Normal FalseTrue
null Null c:\winnt\system32\drivers\null.sys Kernel Driver True
System Running OK Normal FalseTrue
nwlnkflt IPX Traffic Filter Driver
c:\winnt\system32\drivers\nwlnkflt.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
nwlnkfld IPX Traffic Forwarder Driver
c:\winnt\system32\drivers\nwlnkfld.sys Kernel Driver False
Manual Stopped OK Normal FalseFalse
openhci Microsoft USB Open Host Controller Driver
c:\winnt\system32\drivers\openhci.sys Kernel Driver True
Manual Running OK Normal FalseTrue

```

```

parallel Parallel class driver
  c:\winnt\system32\drivers\parallel.sys Kernel Driver True
  Manual Running OK Normal FalseTrue
parport Parallel port driver c:\winnt\system32\drivers\parport.sys
  Kernel Driver True System Running OK Ignore FalseTrue
partmgr PartMgr c:\winnt\system32\drivers\partmgr.sys Kernel
Driver True Boot Running OK Normal FalseTrue
parvdm ParVdm c:\winnt\system32\drivers\parvdm.sys Kernel Driver
  True Auto Running OK Ignore FalseTrue
pci PCI Bus Driver c:\winnt\system32\drivers\pci.sys Kernel Driver
  True Boot Running OK Critical FalseTrue
pcidump PCIDump Not Available Kernel Driver FalseSystem
  Stopped OK Ignore FalseFalse
pciide PCIIde c:\winnt\system32\drivers\pciide.sys Kernel Driver
  True Boot Running OK Normal FalseTrue
pcmcia Pcmcia c:\winnt\system32\drivers\pcmcia.sys Kernel Driver
  FalseDisabled Stopped OK Normal FalseFalse
pdcomp PDCOMP Not Available Kernel Driver FalseManual
  Stopped OK Ignore FalseFalse
pdframe PDFRAME Not Available Kernel Driver FalseManual
  Stopped OK Ignore FalseFalse
pdreli PDRELI Not Available Kernel Driver FalseManual
  Stopped OK Ignore FalseFalse
pdrframe PDRFRAME Not Available Kernel Driver FalseManual
  Stopped OK Ignore FalseFalse
pptpminiport WAN Miniport (PPTP)
  c:\winnt\system32\drivers\raspptp.sys Kernel Driver True
  Manual Running OK Normal FalseTrue
ptilink Direct Parallel Link Driver
  c:\winnt\system32\drivers\ptilink.sys Kernel Driver True
  Manual Running OK Normal FalseTrue
ql1080 ql1080 Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
ql10wnt Ql10wnt Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
ql1240 ql1240 Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
ql2100 ql2100 Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
rasacd Remote Access Auto Connection Driver
  c:\winnt\system32\drivers\rasacd.sys Kernel Driver True System
  Running OK Normal FalseTrue
rasl2tp WAN Miniport (L2TP) c:\winnt\system32\drivers\rasl2tp.sys
  Kernel Driver True Manual Running OK Normal FalseTrue
raspti Direct Parallel c:\winnt\system32\drivers\raspti.sys Kernel
Driver True Manual Running OK Normal FalseTrue
rca Microsoft Streaming Network Raw Channel Access
  c:\winnt\system32\drivers\rca.sys Kernel Driver FalseManual
  Stopped OK Normal FalseFalse
rdbssRdbssc:\winnt\system32\drivers\rdbss.sys File System Driver True
  System Running OK Normal FalseTrue
rdpwdRDPWDC:\winnt\system32\drivers\rdpwd.sys Kernel Driver False
  Manual Stopped OK Ignore FalseFalse

```

```

redbook Digital CD Audio Playback Filter Driver
  c:\winnt\system32\drivers\redbook.sys Kernel Driver False
  System Stopped OK Normal FalseFalse
sccoper Copernicus Management Controllers
  c:\winnt\system32\drivers\sccoper.sys Kernel Driver True
  Manual Running OK Normal FalseTrue
serenum Serenum Filter Driver
  c:\winnt\system32\drivers\serenum.sys Kernel Driver True
  Manual Running OK Normal FalseTrue
serial Serial port driver c:\winnt\system32\drivers\serial.sys
  Kernel Driver True System Running OK Ignore FalseTrue
sfloppy Sfloppy c:\winnt\system32\drivers\sfloppy.sys Kernel
Driver FalseSystem Stopped OK Ignore FalseFalse
sglfbsglfbNot Available Kernel Driver FalseSystem Stopped OK
  Normal FalseFalse
simbad Simbad Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
sparrow Sparrow Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
srv Srv c:\winnt\system32\drivers\srv.sys File System Driver False
  Manual Stopped OK Normal FalseFalse
swenum Software Bus Driver c:\winnt\system32\drivers\swenum.sys
  Kernel Driver True Manual Running OK Normal FalseTrue
symc810 symc810 Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
symc8xx symc8xx Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
sym_hi sym_hi Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse
sym_u3 Sym_u3 c:\winnt\system32\drivers\sym_u3.sys Kernel Driver
  True Boot Running OK Normal FalseTrue
tcpipTCP/IP Protocol Driver c:\winnt\system32\drivers\tcpip.sys
  Kernel Driver True System Running OK Normal FalseTrue
tdasync TDASYNC c:\winnt\system32\drivers\tdasync.sys Kernel
Driver FalseManual Stopped OK Ignore FalseFalse
tdipxTDIPXC:\winnt\system32\drivers\tdipx.sys Kernel Driver False
  Manual Stopped OK Ignore FalseFalse
tdnetb TDNETB c:\winnt\system32\drivers\tdnetb.sys Kernel Driver
  FalseManual Stopped OK Ignore FalseFalse
tdpipe TDPIPE c:\winnt\system32\drivers\tdpipe.sys Kernel Driver
  FalseManual Stopped OK Ignore FalseFalse
tdspxTDSPIXc:\winnt\system32\drivers\tdspx.sys Kernel Driver False
  Manual Stopped OK Ignore FalseFalse
tdtcpTDTCPc:\winnt\system32\drivers\tdtcp.sys Kernel Driver False
  Manual Stopped OK Ignore FalseFalse
termdd Terminal Device Driver c:\winnt\system32\drivers\termdd.sys
  Kernel Driver FalseDisabled Stopped OK Normal FalseFalse
tga tga Not Available Kernel Driver FalseSystem Stopped OK
  Ignore FalseFalse
udfs Udfs c:\winnt\system32\drivers\udfs.sys File System Driver False
  Disabled Stopped OK Normal FalseFalse
ultra66 ultra66 Not Available Kernel Driver FalseDisabled
  Stopped OK Normal FalseFalse

```

```

update      Microcode Update Driver  c:\winnt\system32\drivers\update.sys
            Kernel Driver  True Manual  Running  OK   Normal  FalseTrue
usbhub      Microsoft USB Standard Hub Driver
            c:\winnt\system32\drivers\usbhub.sys Kernel Driver  True Manual
            Running  OK   Normal  FalseTrue
vgasave     VgaSave  c:\winnt\system32\drivers\vga.sys  Kernel Driver
            True System  Running  OK   Ignore  FalseTrue
wanarp      Remote Access IP ARP Driver
            c:\winnt\system32\drivers\wanarp.sys Kernel Driver  True Manual
            Running  OK   Normal  FalseTrue
wdica       WDICANot Available  Kernel Driver  FalseManual  Stopped  OK
            Ignore  FalseFalse

```

[Environment Variables]

```

Variable  Value  User Name
ComSpec   %SystemRoot%\system32\cmd.exe  <SYSTEM>
NUMBER_OF_PROCESSORS 8      <SYSTEM>
OS        Windows_NT <SYSTEM>
Os2LibPath %SystemRoot%\system32\os2\dll; <SYSTEM>
Path      %SystemRoot%\system32;%SystemRoot%;%SystemRoot%\System32\Wbem;C:\Program
Files\Microsoft SQL Server\MSSQL\Tools\BINN;C:\Program
Files\Microsoft SQL Server\MSSQL\BINN;C:\Program Files\Microsoft SQL
Server\80\Tools\BINN <SYSTEM>
PATHEXT   .COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS;.JSE;.WSF;.WSH <SYSTEM>
PROCESSOR_ARCHITECTURE x86 <SYSTEM>
PROCESSOR_IDENTIFIER x86 Family 15 Model 1 Stepping 1, GenuineIntel
<SYSTEM>
PROCESSOR_LEVEL 15 <SYSTEM>
PROCESSOR_REVISION 0101 <SYSTEM>
TEMP      %SystemRoot%\TEMP <SYSTEM>
TMP       %SystemRoot%\TEMP <SYSTEM>
windir    %SystemRoot% <SYSTEM>
TEMP      %USERPROFILE%\Local Settings\Temp R450\Administrator
TMP       %USERPROFILE%\Local Settings\Temp R450\Administrator

```

[Jobs]

[Following are sub-categories of this main category]

[Print]

Document	Size	Owner	Notify	Status	Time Submitted	Start Time	Until				
Time Elapsed	Time	Pages Printed	Job ID	Priority	Parameters	Driver Name	Print Processor	Host	Print Queue	Data Type	Name
Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown
Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown
Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown	Unknown

[Network Connections]

Local Name	Remote Name	Type	Status	User Name
------------	-------------	------	--------	-----------

No network connections information

[Running Tasks]

Name	Path	Process ID	Priority	Min Working Set	Max Working Set	Start Time
Version	Size	File Date				
system	idle process	Not Available	0	0	Not Available	Not Available
system	Not Available	Unknown	Unknown	Unknown	Unknown	Unknown
system	Not Available	8	8	0	1413120	Not Available
	Unknown	Unknown	Unknown			
smss.exe	c:\winnt\system32\smss.exe	152	11	204800	1413120	3/4/2002 10:21:07 AM
		5.00.2195.2901	44.27	KB (45,328 bytes)		12/7/1999 1:00:00 PM
csrss.exe	Not Available	212	13	Not Available	Not Available	3/4/2002 10:21:11 AM
		Unknown	Unknown	Unknown	Unknown	Unknown
winlogon.exe	c:\winnt\system32\winlogon.exe	232	13	204800		3/4/2002 10:21:12 AM
		5.00.2195.2953	173.77	KB (177,936 bytes)		12/7/1999 1:00:00 PM
services.exe	c:\winnt\system32\services.exe	260	9	204800		3/4/2002 10:21:14 AM
		5.00.2195.2780	86.77	KB (88,848 bytes)		12/7/1999 1:00:00 PM
lsass.exe	c:\winnt\system32\lsass.exe	272	9	204800	1413120	3/4/2002 10:21:14 AM
		5.00.2195.2964	32.77	KB (33,552 bytes)		12/7/1999 1:00:00 PM
svchost.exe	c:\winnt\system32\svchost.exe	432	8	204800		3/4/2002 10:21:16 AM
		5.00.2134.1	7.77	KB (7,952 bytes)		12/7/1999 1:00:00 PM
svchost.exe	c:\winnt\system32\svchost.exe	460	8	204800		3/4/2002 10:21:17 AM
		5.00.2134.1	7.77	KB (7,952 bytes)		12/7/1999 1:00:00 PM
winmgmt.exe	c:\winnt\system32\wbem\winmgmt.exe	484	8	204800		3/4/2002 10:21:18 AM
		1.50.1085.0029	192.08	KB (196,685 bytes)		12/17/2001 2:36:42 PM
svchost.exe	c:\winnt\system32\svchost.exe	796	8	204800		3/4/2002 10:21:32 AM
		5.00.2134.1	7.77	KB (7,952 bytes)		12/7/1999 1:00:00 PM
explorer.exe	c:\winnt\explorer.exe	692	8	204800	1413120	3/4/2002 10:22:40 AM
		5.00.3315.2846	237.27	KB (242,960 bytes)		12/17/2001 2:36:36 PM
promon.exe	c:\winnt\system32\promon.exe	636	8	204800	1413120	3/4/2002 10:22:40 AM
		5.1.71.0	68.00	KB (69,632 bytes)		1/17/2002 8:16:38 AM
mmc.exe	c:\winnt\system32\mmc.exe	332	8	204800	1413120	3/5/2002 8:33:14 AM
		5.00.2195.2301	589.27	KB (603,408 bytes)		12/17/2001 2:36:14 PM

[Loaded Modules]

Name	Version	Size	File Date	Manufacturer	Path
wbemprox.dll	1.50.1085.0045	40.08	KB (41,040 bytes)	Microsoft Corporation	c:\winnt\system32\wbem\wbemprox.dll
mlang.dll	5.00.3103.1000	510.77	KB (523,024 bytes)	Microsoft Corporation	c:\winnt\system32\mlang.dll

```

rassapi.dll      5.00.2188.1    14.27 KB (14,608 bytes)  12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\rassapi.dll
adsnt.dll       5.00.2195.2778 195.27 KB (199,952 bytes) 12/17/2001 2:36:02 PM
Microsoft Corporation    c:\winnt\system32\adsnt.dll
dbghelp.dll     5.00.2195.2104 159.27 KB (163,088 bytes) 5/4/2001
1:05:02 PM Microsoft Corporation    c:\winnt\system32\dbghelp.dll
localesec.dll  5.00.2195.2130 230.27 KB (235,792 bytes) 12/17/2001
2:36:14 PM Microsoft Corporation    c:\winnt\system32\localesec.dll
devmgr.dll     5.00.2166.1    215.77 KB (220,944 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation    c:\winnt\system32\devmgr.dll
filemgmt.dll   5.00.2195.2165 287.27 KB (294,160 bytes) 12/17/2001
2:36:09 PM Microsoft Corporation    c:\winnt\system32\filemgmt.dll
pdh.dll        5.00.2195.2739 147.77 KB (151,312 bytes) 12/17/2001 2:36:26 PM
Microsoft Corporation    c:\winnt\system32\pdh.dll
smlogcfg.dll   5.00.2195.2485 273.27 KB (279,824 bytes) 12/17/2001
2:36:31 PM Microsoft Corporation    c:\winnt\system32\smlogcfg.dll
cabinet.dll    5.00.2147.1    54.77 KB (56,080 bytes)  12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\cabinet.dll
msinfo32.dll   5.00.2177.1    312.27 KB (319,760 bytes) 12/17/2001
1:56:09 PM Microsoft Corporation    c:\program files\common
files\microsoft shared\msinfo\msinfo32.dll
riched20.dll   5.30.23.1205   421.27 KB (431,376 bytes) 12/17/2001
2:36:28 PM Microsoft Corporation    c:\winnt\system32\riched20.dll
riched32.dll   5.00.2134.1    3.77 KB (3,856 bytes)    12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\riched32.dll
els.dll        5.00.2175.1    151.27 KB (154,896 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation    c:\winnt\system32\els.dll
ntmsmgr.dll    1,0,0,1        427.77 KB (438,032 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation and HighGround Systems, Inc.
c:\winnt\system32\ntmsmgr.dll
mmfutil.dll    1.50.1085.0000 32.06 KB (32,829 bytes)  12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\mmfutil.dll
logdrive.dll   1.50.1085.0000 200.06 KB (204,863 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\logdrive.dll
dfrgres.dll    5.00.2150.1    27.50 KB (28,160 bytes)  12/7/1999
1:00:00 PM Executive Software International, Inc.
c:\winnt\system32\dfrgres.dll
dfrgsnap.dll   5.00.2195.2104 41.77 KB (42,768 bytes)  12/17/2001
2:36:05 PM Executive Software International, Inc.
c:\winnt\system32\dfrgsnap.dll
dmdskres.dll   2195.2104.297.3 119.50 KB (122,368 bytes) 12/17/2001
2:36:06 PM Microsoft Corp., VERITAS Software
c:\winnt\system32\dmdskres.dll
dmutil.dll     2195.2104.297.3 42.27 KB (43,280 bytes)  12/17/2001 2:36:06 PM
VERITAS Software Corp.    c:\winnt\system32\dmutil.dll
ntmsapi.dll    5.00.1948.1    51.77 KB (53,008 bytes)  12/17/2001
2:36:24 PM Microsoft Corporation    c:\winnt\system32\ntmsapi.dll
dmdskmgr.dll   2215.2215.297.3 160.27 KB (164,112 bytes) 12/17/2001
2:36:06 PM Microsoft Corp., VERITAS Software
c:\winnt\system32\dmdskmgr.dll
mycomput.dll   5.00.2134.1    107.77 KB (110,352 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\mycomput.dll

```

```

comdlg32.dll   5.00.3103.1000 236.77 KB (242,448 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\comdlg32.dll
mmcndmgr.dll  5.00.2178.1    815.27 KB (834,832 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\mmcndmgr.dll
msvcp50.dll   5.00.7051.552.50 KB (565,760 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation    c:\winnt\system32\msvcp50.dll
mfc42u.dll    6.00.8665.0    972.05 KB (995,384 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation    c:\winnt\system32\mfc42u.dll
mmc.exe       5.00.2195.2301 589.27 KB (603,408 bytes) 12/17/2001 2:36:14 PM
Microsoft Corporation    c:\winnt\system32\mmc.exe
nmsapi.dll    2.0.42.0       144.00 KB (147,456 bytes) 1/17/2002 8:16:37 AM Intel
Corporation    c:\winnt\system32\nmsapi.dll
promon.exe    5.1.71.0       68.00 KB (69,632 bytes)   1/17/2002 8:16:38 AM Intel
Corporation    c:\winnt\system32\promon.exe
shdoclc.dll   5.00.3315.2879 324.50 KB (332,288 bytes) 12/17/2001
2:36:30 PM Microsoft Corporation    c:\winnt\system32\shdoclc.dll
urlmon.dll    5.00.3315.1000 441.27 KB (451,856 bytes) 12/17/2001 2:36:34 PM
Microsoft Corporation    c:\winnt\system32?urlmon.dll
faxshell.dll  5.00.2134.1    8.27 KB (8,464 bytes)    12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\faxshell.dll
msacm32.dll   5.00.2134.1    65.27 KB (66,832 bytes)  12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\msacm32.dll
avifil32.dll  5.00.2134.1    76.27 KB (78,096 bytes)  12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\avifil32.dll
msvfw32.dll   5.00.2134.1    113.77 KB (116,496 bytes) 12/17/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\msvfw32.dll
docprop2.dll  5.00.2178.1    297.77 KB (304,912 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\docprop2.dll
browselc.dll  5.00.3315.2846 34.50 KB (35,328 bytes)   12/17/2001
2:36:02 PM Microsoft Corporation    c:\winnt\system32\browselc.dll
wininet.dll   5.00.3315.1000 456.77 KB (467,728 bytes) 12/17/2001
2:36:35 PM Microsoft Corporation    c:\winnt\system32\wininet.dll
msonsext.dll  9.0.3503       548.06 KB (561,210 bytes) 11/3/1999 4:38:34 PM
Microsoft Corporation
c:\progra~1\common~1\micro~1\webfol~1\msonsext.dll
wzshlstb.dll  3.0 (32-bit)   24.07 KB (24,644 bytes)  11/22/2000
8:00:00 AM WinZip Computing, Inc.    c:\tools\winzip80\wzshlstb.dll
ntshrui.dll   5.00.2134.1    46.77 KB (47,888 bytes)  12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\ntshrui.dll
linkinfo.dll  5.00.2134.1    15.77 KB (16,144 bytes)  12/7/1999
1:00:00 PM Microsoft Corporation    c:\winnt\system32\linkinfo.dll
msi.dll       1.11.2405.0    1.69 MB (1,767,184 bytes) 12/17/2001 2:36:16 PM
Microsoft Corporation    c:\winnt\system32\msi.dll
powrprof.dll  5.00.3103.1000 13.27 KB (13,584 bytes)  12/17/2001
2:36:26 PM Microsoft Corporation    c:\winnt\system32\powrprof.dll
batmeter.dll  5.00.3103.1000 20.27 KB (20,752 bytes)  12/17/2001
2:36:02 PM Microsoft Corporation    c:\winnt\system32\batmeter.dll
stobject.dll  5.00.2195.2780 79.27 KB (81,168 bytes)  12/17/2001
2:36:32 PM Microsoft Corporation    c:\winnt\system32\stobject.dll
webcheck.dll  5.00.3315.1000 251.77 KB (257,808 bytes) 12/17/2001
2:36:35 PM Microsoft Corporation    c:\winnt\system32\webcheck.dll
browseui.dll  5.00.3315.2846 788.77 KB (807,696 bytes) 12/17/2001
2:36:03 PM Microsoft Corporation    c:\winnt\system32\browseui.dll

```

```

shdocvw.dll      5.00.3315.2879  1.05 MB (1,104,144 bytes) 12/17/2001
2:36:30 PM Microsoft Corporation c:\winnt\system32\shdocvw.dll
explorer.exe    5.00.3315.2846  237.27 KB (242,960 bytes) 12/17/2001
2:36:36 PM Microsoft Corporation c:\winnt\explorer.exe
ntmarta.dll     5.00.2195.2862  98.77 KB (101,136 bytes) 12/17/2001
2:36:24 PM Microsoft Corporation c:\winnt\system32\ntmarta.dll
tapisrv.dll    5.00.2195.2955  169.27 KB (173,328 bytes) 12/17/2001
2:36:32 PM Microsoft Corporation c:\winnt\system32\tapisrv.dll
netui1.dll     5.00.2134.1    210.27 KB (215,312 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\netui1.dll
netui0.dll     5.00.2134.1    70.27 KB (71,952 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\netui0.dll
ntlanman.dll   5.00.2157.1    35.27 KB (36,112 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\ntlanman.dll
perfos.dll     5.00.2155.1    21.27 KB (21,776 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\perfos.dll
provthrd.dll   1.50.1085.0000  68.07 KB (69,708 bytes) 12/17/2001
1:56:02 PM Microsoft Corporation c:\winnt\system32\wbem\provthrd.dll
ntevt.dll     1.50.1085.0000  192.06 KB (196,669 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\wbem\ntevt.dll
psapi.dll     5.00.2134.1    28.27 KB (28,944 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\psapi.dll
framedyn.dll  1.50.1085.0000  164.05 KB (167,992 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\wbem\framedyn.dll
cimwin32.dll  1.50.1085.0038  1.02 MB (1,073,232 bytes) 12/17/2001
2:36:40 PM Microsoft Corporation c:\winnt\system32\wbem\cimwin32.dll
wbemsvc.dll   1.50.1085.0007  40.07 KB (41,036 bytes) 12/17/2001
2:36:42 PM Microsoft Corporation c:\winnt\system32\wbem\wbemsvc.dll
wbemess.dll   1.50.1085.0039  364.07 KB (372,804 bytes) 12/17/2001
2:36:42 PM Microsoft Corporation c:\winnt\system32\wbem\wbemess.dll
fastprox.dll  1.50.1085.0037  144.08 KB (147,536 bytes) 12/17/2001
2:36:40 PM Microsoft Corporation c:\winnt\system32\wbem\fastprox.dll
wbemcore.dll  1.50.1085.0036  628.07 KB (643,140 bytes) 12/17/2001
2:36:41 PM Microsoft Corporation c:\winnt\system32\wbem\wbemcore.dll
wbemcomn.dll  1.50.1085.0021  692.07 KB (708,675 bytes) 12/17/2001
2:36:41 PM Microsoft Corporation c:\winnt\system32\wbem\wbemcomn.dll
winmgmt.exe   1.50.1085.0029  192.08 KB (196,685 bytes) 12/17/2001
2:36:42 PM Microsoft Corporation c:\winnt\system32\wbem\winmgmt.exe
rasdlg.dll    5.00.2195.2671  514.27 KB (526,608 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\rasdlg.dll
netcfgx.dll   5.00.2195.2228  534.77 KB (547,600 bytes) 12/17/2001
2:36:22 PM Microsoft Corporation c:\winnt\system32\netcfgx.dll
rasmans.dll   5.00.2195.2728  147.27 KB (150,800 bytes) 12/17/2001
2:36:27 PM Microsoft Corporation c:\winnt\system32\rasmans.dll
wmi.dll       5.00.2191.1    6.27 KB (6,416 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\wmi.dll
netshell.dll  5.00.2195.2779  457.27 KB (468,240 bytes) 12/17/2001
2:36:23 PM Microsoft Corporation c:\winnt\system32\netshell.dll
netman.dll    5.00.2195.2779  89.27 KB (91,408 bytes) 12/17/2001 2:36:23 PM
Microsoft Corporation c:\winnt\system32\netman.dll
sens.dll      5.00.2163.1    36.77 KB (37,648 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\sens.dll

```

```

txfaux.dll     2000.2.3471.1  374.27 KB (383,248 bytes) 12/17/2001 2:36:33 PM
Microsoft Corporation c:\winnt\system32\txfaux.dll
es.dll         2000.2.3471.1  222.27 KB (227,600 bytes) 12/17/2001 2:36:08 PM
Microsoft Corporation c:\winnt\system32\es.dll
rpcss.dll     5.00.2195.2815  231.27 KB (236,816 bytes) 12/17/2001 2:36:29 PM
Microsoft Corporation c:\winnt\system32\rpcss.dll
svchost.exe   5.00.2134.1    7.77 KB (7,952 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\svchost.exe
scecli.dll    5.00.2195.2780  105.27 KB (107,792 bytes) 12/17/2001 2:36:29 PM
Microsoft Corporation c:\winnt\system32\scecli.dll
atl.dll       3.00.8449 57.56 KB (58,938 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\atl.dll
certcli.dll   5.00.2195.2778  130.77 KB (133,904 bytes) 12/17/2001
2:36:04 PM Microsoft Corporation c:\winnt\system32\certcli.dll
ntdsatq.dll   5.00.2195.2878  31.27 KB (32,016 bytes) 12/17/2001
2:36:23 PM Microsoft Corporation c:\winnt\system32\ntdsatq.dll
ntdsa.dll     5.00.2195.2899  990.77 KB (1,014,544 bytes) 12/17/2001
2:36:23 PM Microsoft Corporation c:\winnt\system32\ntdsa.dll
kdcsvc.dll    5.00.2195.2878  137.77 KB (141,072 bytes) 12/17/2001 2:36:13 PM
Microsoft Corporation c:\winnt\system32\kdcsvc.dll
sfmapi.dll    5.00.2134.1    38.77 KB (39,696 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\sfmapi.dll
rassfm.dll    5.00.2195.2671  21.27 KB (21,776 bytes) 12/17/2001 2:36:28 PM
Microsoft Corporation c:\winnt\system32\rassfm.dll
mpr.dll       5.00.2195.2779  53.27 KB (54,544 bytes) 12/17/2001 2:36:14 PM
Microsoft Corporation c:\winnt\system32\mpr.dll
rsabase.dll   5.00.2195.2228  128.27 KB (131,344 bytes) 5/4/2001
1:05:02 PM Microsoft Corporation c:\winnt\system32\rsabase.dll
schannel.dll  5.00.2195.2922  138.27 KB (141,584 bytes) 5/4/2001
1:05:02 PM Microsoft Corporation c:\winnt\system32\schannel.dll
netlogon.dll  5.00.2195.2865  357.77 KB (366,352 bytes) 12/17/2001
2:36:22 PM Microsoft Corporation c:\winnt\system32\netlogon.dll
msvl_0.dll    5.00.2195.2900  111.77 KB (114,448 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\msvl_0.dll
kerberos.dll  5.00.2195.2913  198.77 KB (203,536 bytes) 12/17/2001
2:36:13 PM Microsoft Corporation c:\winnt\system32\kerberos.dll
msprivs.dll   5.00.2154.1    41.50 KB (42,496 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\msprivs.dll
samsrv.dll    5.00.2195.2918  369.77 KB (378,640 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\samsrv.dll
lsasrv.dll    5.00.2195.2964  492.77 KB (504,592 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\lsasrv.dll
lsass.exe     5.00.2195.2964  32.77 KB (33,552 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\lsass.exe
esent.dll     6.0.3940.13    1.08 MB (1,135,376 bytes) 12/17/2001 2:36:09 PM
Microsoft Corporation c:\winnt\system32\esent.dll
cfgmgr32.dll  5.00.2134.1    16.77 KB (17,168 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\cfgmgr32.dll
dmserver.dll  2195.2778.297.3 11.77 KB (12,048 bytes) 12/17/2001
2:36:06 PM VERITAS Software Corp. c:\winnt\system32\dmserver.dll
wmicore.dll   5.00.2195.2842  72.27 KB (74,000 bytes) 12/17/2001
2:36:35 PM Microsoft Corporation c:\winnt\system32\wmicore.dll

```

```

rasadhlp.dll 5.00.2168.1 7.27 KB (7,440 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\rasadhlp.dll
winnr.dll 5.00.2160.1 18.77 KB (19,216 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\winnr.dll
dhcpcsvc.dll 5.00.2195.2778 88.77 KB (90,896 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\dhcpcsvc.dll
tapi32.dll 5.00.2182.1 123.27 KB (126,224 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\tapi32.dll
rasman.dll 5.00.2195.2780 54.77 KB (56,080 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\rasman.dll
rasapi32.dll 5.00.2195.2671 189.77 KB (194,320 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\rasapi32.dll
rtutils.dll 5.00.2168.1 43.77 KB (44,816 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\rtutils.dll
adslfdc.dll 5.00.2195.2842 127.27 KB (130,320 bytes) 12/17/2001
2:36:01 PM Microsoft Corporation c:\winnt\system32\adslfdc.dll
activeds.dll 5.00.2195.2778 174.77 KB (178,960 bytes) 12/17/2001
2:35:54 PM Microsoft Corporation c:\winnt\system32\activeds.dll
mprapi.dll 5.00.2181.1 79.27 KB (81,168 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\mprapi.dll
iphlpapi.dll 5.00.2173.2 67.77 KB (69,392 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\iphlpapi.dll
rnr20.dll 5.00.2195.2871 35.77 KB (36,624 bytes) 12/17/2001 2:36:28 PM
Microsoft Corporation c:\winnt\system32\rnr20.dll
wshtcpip.dll 5.00.2195.2104 17.27 KB (17,680 bytes) 12/17/2001
2:36:36 PM Microsoft Corporation c:\winnt\system32\wshtcpip.dll
msafd.dll 5.00.2195.2779 106.77 KB (109,328 bytes) 12/17/2001 2:36:15 PM
Microsoft Corporation c:\winnt\system32\msafd.dll
mswsock.dll 5.00.2195.2871 62.77 KB (64,272 bytes) 12/17/2001
2:36:21 PM Microsoft Corporation c:\winnt\system32\mswsock.dll
msgsvc.dll 5.00.2195.2939 34.27 KB (35,088 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\msgsvc.dll
alrsvc.dll 5.00.2134.1 17.77 KB (18,192 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\alrsvc.dll
psbase.dll 5.00.2195.2779 111.77 KB (114,448 bytes) 12/17/2001 2:36:27 PM
Microsoft Corporation c:\winnt\system32\psbase.dll
cryptsvc.dll 5.00.2181.1 61.77 KB (63,248 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\cryptsvc.dll
cryptdll.dll 5.00.2135.1 41.27 KB (42,256 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\cryptdll.dll
wkssvc.dll 5.00.2195.2780 95.27 KB (97,552 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\wkssvc.dll
icmp.dll 5.00.2134.1 7.27 KB (7,440 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\icmp.dll
lmhsvc.dll 5.00.2195.2778 9.77 KB (10,000 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\lmhsvc.dll
eventlog.dll 5.00.2178.1 43.77 KB (44,816 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\eventlog.dll
ntdsapi.dll 5.00.2195.2661 55.77 KB (57,104 bytes) 12/17/2001
2:36:23 PM Microsoft Corporation c:\winnt\system32\ntdsapi.dll
scserv.dll 5.00.2195.2780 226.27 KB (231,696 bytes) 12/17/2001 2:36:29 PM
Microsoft Corporation c:\winnt\system32\scserv.dll

```

```

umpnpgmgr.dll 5.00.2182.1 86.27 KB (88,336 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\umpnpgmgr.dll
services.exe 5.00.2195.2780 86.77 KB (88,848 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\services.exe
cscui.dll 5.00.2195.2959 228.27 KB (233,744 bytes) 12/17/2001 2:36:05 PM
Microsoft Corporation c:\winnt\system32\cscui.dll
winsta.dll 5.00.2195.2386 36.77 KB (37,648 bytes) 12/17/2001 2:36:35 PM
Microsoft Corporation c:\winnt\system32\winsta.dll
sclgntfy.dll 5.00.2191.1 20.27 KB (20,752 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\sclgntfy.dll
cryptnet.dll 5.131.2157.1 41.77 KB (42,768 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\cryptnet.dll
clbcatq.dll 2000.2.3471.1 496.77 KB (508,688 bytes) 12/17/2001
2:36:04 PM Microsoft Corporation c:\winnt\system32\clbcatq.dll
oleaut32.dll 2.40.4517 612.27 KB (626,960 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\oleaut32.dll
winspool.drv 5.00.2195.2780 109.77 KB (112,400 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\winspool.drv
wincard.dll 5.00.2134.1 77.27 KB (79,120 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\wincard.dll
wlnotify.dll 5.00.2195.2780 53.77 KB (55,056 bytes) 12/17/2001
2:36:35 PM Microsoft Corporation c:\winnt\system32\wlnotify.dll
csddl.dll 5.00.2195.2401 98.27 KB (100,624 bytes) 12/17/2001 2:36:05 PM
Microsoft Corporation c:\winnt\system32\csddl.dll
lz32.dll 5.00.2134.1 9.77 KB (10,000 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\lz32.dll
version.dll 5.00.2134.1 15.77 KB (16,144 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\version.dll
rsaenh.dll 5.00.2195.2228 130.77 KB (133,904 bytes) 12/17/2001 2:37:35 PM
Microsoft Corporation c:\winnt\system32\rsaenh.dll
mscat32.dll 5.131.2134.1 7.77 KB (7,952 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\mscat32.dll
ole32.dll 5.00.2195.2887 969.77 KB (993,040 bytes) 12/17/2001 2:36:25 PM
Microsoft Corporation c:\winnt\system32\ole32.dll
imagehlp.dll 5.00.2195.2778 125.77 KB (128,784 bytes) 5/4/2001
1:05:02 PM Microsoft Corporation c:\winnt\system32\imagehlp.dll
msasn1.dll 5.00.2134.1 51.27 KB (52,496 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\msasn1.dll
crypt32.dll 5.131.2195.2833 451.27 KB (462,096 bytes) 12/17/2001
2:36:05 PM Microsoft Corporation c:\winnt\system32\crypt32.dll
wintrust.dll 5.131.2195.2779 162.27 KB (166,160 bytes) 12/17/2001
2:36:35 PM Microsoft Corporation c:\winnt\system32\wintrust.dll
setupapi.dll 5.00.2195.2663 555.77 KB (569,104 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\setupapi.dll
winmm.dll 5.00.2161.1 184.77 KB (189,200 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\winmm.dll
comctl32.dll 5.81 537.77 KB (550,672 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\comctl32.dll
shlwapi.dll 5.00.3315.1000 282.77 KB (289,552 bytes) 12/17/2001
2:36:31 PM Microsoft Corporation c:\winnt\system32\shlwapi.dll
shell32.dll 5.00.3315.2902 2.25 MB (2,359,056 bytes) 12/17/2001
2:36:31 PM Microsoft Corporation c:\winnt\system32\shell32.dll

```

```

msgina.dll 5.00.2195.2779 324.27 KB (332,048 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\msgina.dll
wsock32.dll 5.00.2195.2871 21.27 KB (21,776 bytes) 12/17/2001
2:36:36 PM Microsoft Corporation c:\winnt\system32\wsock32.dll
dnsapi.dll 5.00.2195.2785 130.77 KB (133,904 bytes) 12/17/2001 2:36:06 PM
Microsoft Corporation c:\winnt\system32\dnsapi.dll
wldap32.dll 5.00.2195.2797 125.27 KB (128,272 bytes) 12/17/2001
2:36:35 PM Microsoft Corporation c:\winnt\system32\wldap32.dll
ws2help.dll 5.00.2134.1 17.77 KB (18,192 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\ws2help.dll
ws2_32.dll 5.00.2195.2780 67.77 KB (69,392 bytes) 12/17/2001 2:36:36 PM
Microsoft Corporation c:\winnt\system32\ws2_32.dll
samlib.dll 5.00.2195.2780 49.77 KB (50,960 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\samlib.dll
netrap.dll 5.00.2134.1 11.27 KB (11,536 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\netrap.dll
netapi32.dll 5.00.2195.2808 303.77 KB (311,056 bytes) 12/17/2001
2:36:22 PM Microsoft Corporation c:\winnt\system32\netapi32.dll
profmap.dll 5.00.2181.1 29.27 KB (29,968 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\profmap.dll
secur32.dll 5.00.2195.2862 46.77 KB (47,888 bytes) 12/17/2001
2:36:30 PM Microsoft Corporation c:\winnt\system32\secur32.dll
sfc.dll 5.00.2195.2896 92.11 KB (94,320 bytes) 12/17/2001 2:36:30 PM
Microsoft Corporation c:\winnt\system32\sfc.dll
nddeapi.dll 5.00.2137.1 15.27 KB (15,632 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\nddeapi.dll
userenv.dll 5.00.2195.2780 361.77 KB (370,448 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\userenv.dll
user32.dll 5.00.2195.2821 392.77 KB (402,192 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\user32.dll
gdi32.dll 5.00.2195.2778 228.77 KB (234,256 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\gdi32.dll
rpcrt4.dll 5.00.2195.2832 437.27 KB (447,760 bytes) 12/17/2001 2:36:28 PM
Microsoft Corporation c:\winnt\system32\rpcrt4.dll
advapi32.dll 5.00.2195.2867 351.77 KB (360,208 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\advapi32.dll
kernel32.dll 5.00.2195.2778 714.77 KB (731,920 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\kernel32.dll
msvcrt.dll 6.10.8924.0 284.05 KB (290,869 bytes) 5/4/2001 1:05:02 PM
Microsoft Corporation c:\winnt\system32\msvcrt.dll
winlogon.exe 5.00.2195.2953 173.77 KB (177,936 bytes) 12/7/1999
1:00:00 PM Microsoft Corporation c:\winnt\system32\winlogon.exe
sfcfiles.dll 5.00.2195.2967 948.27 KB (971,024 bytes) 12/17/2001
2:36:30 PM Microsoft Corporation c:\winnt\system32\sfcfiles.dll
ntdll.dll 5.00.2195.2779 478.77 KB (490,256 bytes) 5/4/2001 1:05:02 PM
Microsoft Corporation c:\winnt\system32\ntdll.dll
smss.exe 5.00.2195.2901 44.27 KB (45,328 bytes) 12/7/1999 1:00:00 PM
Microsoft Corporation c:\winnt\system32\smss.exe

```

[Services]

```

Display Name Name State Start Mode Service Type Path Error Control
Start Name Tag ID

```

```

Alerter Alerter Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Application Management AppMgmt Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Computer Browser Browser Stopped Disabled Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Indexing Service cisvc Stopped Manual Share Process
c:\winnt\system32\cisvc.exe Normal LocalSystem 0
ClipBook ClipSrv Stopped Manual Own Process
c:\winnt\system32\clipsrv.exe Normal LocalSystem 0
Distributed File System Dfs Stopped Manual Own Process
c:\winnt\system32\dfssvc.exe Normal LocalSystem 0
DHCP Client Dhcp Stopped Disabled Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Logical Disk Manager Administrative Service dmadmin Stopped
Manual Share Process c:\winnt\system32\dmadmin.exe /com
Normal LocalSystem 0
Logical Disk Manager dmserver Running Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
DNS Client Dnscache Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Event Log Eventlog Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
COM+ Event System EventSystem Running Manual Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Fax Service Fax Stopped Manual Own Process
c:\winnt\system32\faxsvc.exe Normal LocalSystem 0
Intersite Messaging IsmServ Stopped Disabled Own Process
c:\winnt\system32\ismserv.exe Normal LocalSystem 0
Kerberos Key Distribution Center kdc Stopped Disabled Share
Process c:\winnt\system32\lsass.exe Normal LocalSystem 0
Server lanmanserver Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Workstation lanmanworkstation Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
License Logging Service LicenseService Stopped Manual Own
Process c:\winnt\system32\llssrv.exe Normal LocalSystem 0
TCP/IP NetBIOS Helper Service LmHosts Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Messenger Messenger Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
NetMeeting Remote Desktop Sharing mnmsrvc Stopped Manual Own
Process c:\winnt\system32\mnmsrvc.exe Normal LocalSystem 0
Distributed Transaction Coordinator MSDTC Stopped Manual Own
Process c:\winnt\system32\msdtc.exe Normal LocalSystem 0
Windows Installer MSIServer Stopped Manual Share Process
c:\winnt\system32\msiexec.exe /v Normal LocalSystem 0
MSSQLSERVER MSSQLSERVER Stopped Manual Own Process
c:\progra~1\microso~2\mssql\bin\sqlservr.exe Normal
LocalSystem 0

```

```

MSSQLServerADHelper MSSQLServerADHelper Stopped Manual Own
Process c:\program files\microsoft sql
server\80\tools\bin\sqladhlp.exe Normal LocalSystem 0
Network DDE NetDDE Stopped Manual Share Process
c:\winnt\system32\netdde.exe Normal LocalSystem 0
Network DDE DSDM NetDDEdsdm Stopped Manual Share Process
c:\winnt\system32\netdde.exe Normal LocalSystem 0
Net Logon Netlogon Stopped Manual Share Process
c:\winnt\system32\lsass.exe Normal LocalSystem 0
Network Connections Netman Running Manual Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
NMS Service NMSSvc Stopped Disabled Own Process
c:\winnt\system32\nmssvc.exe Normal LocalSystem 0
File Replication NtFrs Stopped Manual Own Process
c:\winnt\system32\ntfrs.exe Ignore LocalSystem 0
NT LM Security Support Provider NtLmSsp Stopped Manual Share
Process c:\winnt\system32\lsass.exe Normal LocalSystem 0
Removable Storage NtmsSvc Stopped Manual Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Plug and Play PlugPlay Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
IPSEC Policy Agent PolicyAgent Stopped Manual Share Process
c:\winnt\system32\lsass.exe Normal LocalSystem 0
Protected Storage ProtectedStorage Running Auto Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Remote Access Auto Connection Manager RasAuto Stopped Manual
Share Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Remote Access Connection Manager RasMan Stopped Manual Share
Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Routing and Remote Access RemoteAccess Stopped Disabled Share
Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Remote Registry Service RemoteRegistry Stopped Disabled Own
Process c:\winnt\system32\regsvc.exe Normal LocalSystem 0
Remote Procedure Call (RPC) Locator RpcLocator Stopped Manual Own
Process c:\winnt\system32\locator.exe Normal LocalSystem 0
Remote Procedure Call (RPC) RpcSsRunning Auto Share Process
c:\winnt\system32\svchost.exe -k rpcss Normal LocalSystem 0
QoS RSVP RSVP Stopped Manual Own Process
c:\winnt\system32\rsvp.exe -s Normal LocalSystem 0
Security Accounts Manager SamSs Stopped Manual Share Process
c:\winnt\system32\lsass.exe Normal LocalSystem 0
Smart Card Helper SCardDrv Stopped Manual Share Process
c:\winnt\system32\scardsvr.exe Ignore LocalSystem 0
Smart Card SCardSvr Stopped Manual Share Process
c:\winnt\system32\scardsvr.exe Ignore LocalSystem 0
Task Scheduler Schedule Stopped Manual Share Process
c:\winnt\system32\mstask.exe Normal LocalSystem 0

```

```

RunAs Service seclogon Stopped Manual Share Process
c:\winnt\system32\services.exe Ignore LocalSystem 0
System Event Notification SENS Running Auto Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Internet Connection Sharing SharedAccess Stopped Manual Share
Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Print Spooler Spooler Stopped Disabled Own Process
c:\winnt\system32\spoolsv.exe Normal LocalSystem 0
SQLSERVERAGENT SQLSERVERAGENT Stopped Manual Own Process
c:\progra~1\microso~2\mssql\bin\sqlagent.exe Normal
LocalSystem 0
Performance Logs and Alerts SysmonLog Stopped Manual Own
Process c:\winnt\system32\smlogsvc.exe Normal LocalSystem 0
Telephony TapiSrv Running Manual Share Process
c:\winnt\system32\svchost.exe -k tapisrv Normal LocalSystem
0
Terminal Services TermService Stopped Disabled Own Process
c:\winnt\system32\termsrv.exe Normal LocalSystem 0
Telnet TlntSvr Stopped Manual Own Process
c:\winnt\system32\tlntsvr.exe Normal LocalSystem 0
Distributed Link Tracking Server TrkSvr Stopped Manual Share
Process c:\winnt\system32\services.exe Normal LocalSystem 0
Distributed Link Tracking Client TrkWks Stopped Manual Share
Process c:\winnt\system32\services.exe Normal LocalSystem 0
Uninterruptible Power Supply UPS Stopped Manual Own Process
c:\winnt\system32\ups.exe Normal LocalSystem 0
Utility Manager UtilMan Stopped Manual Own Process
c:\winnt\system32\utilman.exe Normal LocalSystem 0
Windows Time W32Time Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
Windows Management Instrumentation WinMgmt Running Auto Own
Process c:\winnt\system32\wbem\winmgmt.exe Ignore LocalSystem
0
Windows Management Instrumentation Driver Extensions Wmi Running
Manual Share Process c:\winnt\system32\services.exe Normal
LocalSystem 0
[Program Groups]
Group Name Name User Name
Accessories Default User:Accessories Default User
Accessories\Accessibility Default User:Accessories\Accessibility
Default User
Accessories\Entertainment Default User:Accessories\Entertainment
Default User
Accessories\System Tools Default User:Accessories\System Tools
Default User
Startup Default User:Startup Default User
Accessories All Users:Accessories All Users
Accessories\Communications All Users:Accessories\Communications All Users
Accessories\Entertainment All Users:Accessories\Entertainment All Users

```

```

Accessories\System Tools All Users:Accessories\System Tools All Users
Administrative Tools All Users:Administrative Tools All Users
Intel Processor Frequency ID Utility All Users:Intel Processor Frequency
ID Utility All Users
Microsoft SQL Server All Users:Microsoft SQL Server All Users
Startup All Users:Startup All Users
WinZip All Users:WinZip All Users
Accessories R450\Administrator:Accessories R450\Administrator
Accessories\Accessibility R450\Administrator:Accessories\Accessibility
R450\Administrator
Accessories\Entertainment R450\Administrator:Accessories\Entertainment
R450\Administrator
Accessories\System Tools R450\Administrator:Accessories\System Tools
R450\Administrator
Administrative Tools R450\Administrator:Administrative Tools
R450\Administrator
Startup R450\Administrator:StartupR450\Administrator

```

[Startup Programs]

Program	Command	User Name	Location
Promon.exe	promon.exe	All Users	HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run

[OLE Registration]

Object	Local Server
Sound (OLE2)	sndrec32.exe
Media Clip	mplay32.exe
Video Clip	mplay32.exe /avi
MIDI Sequence	mplay32.exe /mid
Sound	Not Available
Media Clip	Not Available
Image Document	"C:\Program Files\Windows NT\Accessories\ImageVue\KodakImg.exe"
Windows Media Services DRM Storage object	Not Available
Bitmap Image	mspaint.exe

```

Key Name: SYSTEM\CurrentControlSet\Services\NDIS
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:31 PM
Value 0
Name: DisplayName
Type: REG_SZ
Data: NDIS System Driver

```

```

Value 1
Name: ErrorControl
Type: REG_DWORD
Data: 0x1

```

Value 2

```

Name: Group
Type: REG_SZ
Data: NDIS Wrapper

```

```

Value 3
Name: Start
Type: REG_DWORD
Data: 0

```

```

Value 4
Name: Type
Type: REG_DWORD
Data: 0x1

```

```

Key Name: SYSTEM\CurrentControlSet\Services\NDIS\Enum
Class Name: <NO CLASS>
Last Write Time: 3/4/2002 - 10:20 AM
Value 0

```

```

Name: 0
Type: REG_SZ
Data: Root\LEGACY_NDIS\0000

```

```

Value 1
Name: Count
Type: REG_DWORD
Data: 0x1

```

```

Value 2
Name: NextInstance
Type: REG_DWORD
Data: 0x1

```

```

Key Name: SYSTEM\CurrentControlSet\Services\NDIS\MediaTypes
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:31 PM

```

```

Key Name: SYSTEM\CurrentControlSet\Services\NDIS\NetDetect
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

```

```

Key Name: SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

```

```

Value 0
Name: BusType
Type: REG_DWORD
Data: 0x2

```

```

Key Name: SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\3C592

```

Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x20596d50

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xf0ffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA&*TCM5920

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\3C597
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x70596d50

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xf0ffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA&*TCM5970

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\579TP
Class Name: <NO CLASS>
Last Write Time: 1/22/2002 - 8:18 AM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x93506d50

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2

Name: Token
Type: REG_SZ
Data: *TCM5093

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\BONSAI
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x62110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA_CPQ6200_TOPNET

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\BONSAIPORT2
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x62110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA_CPQ6200_BOTTOMNET

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\DEC300
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x230a310

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA&DEFEA

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\DEC422
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x2042a310

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xf0ffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA&DEC422

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\DURANGO
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0
Name: Id
Type: REG_DWORD
Data: 0x260110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *CPQ6002

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\EE100E
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0

Name: Id
Type: REG_DWORD
Data: 0x6010d425

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xf0ffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA&INT1060

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\HP2577A
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0

Name: Id
Type: REG_DWORD
Data: 0x4019f022

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xf0ffffff

Value 2
Name: Token
Type: REG_SZ
Data: *HWP1940

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\INTEL32E
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM
Value 0

Name: Id
Type: REG_DWORD
Data: 0x112d425

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *INT1201

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\MAPLE
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x160110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *CPQ6001

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\MDGEB
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x3008734

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *MDG0003

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\MDGER1
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id

Type: REG_DWORD
Data: 0x1008734

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *MDG0001

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\MDGER2
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x2008734

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *MDG0002

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\MDGER3
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x4008734

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *MDG0004

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\NE3200
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x7cc3a

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *NVL0701

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\NETFLEX3
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x20f1110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xf0ffffff

Value 2
Name: Token
Type: REG_SZ
Data: *CPQF120

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\NETFLEX3.1
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x40f1110e

Value 1
Name: Mask
Type: REG_DWORD

Data: 0xf0ffffff

Value 2
Name: Token
Type: REG_SZ
Data: *CPQF140

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\NETFLX
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x61110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *CPQ6100

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\NPEISA
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x93a

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffff

Value 2
Name: Token
Type: REG_SZ
Data: *NPIEISA

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\OC3133
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0

Name: Id
Type: REG_DWORD
Data: 0x209833d

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA&*OLC0902

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\OCTK32
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x112833d

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: *OLC1201

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\P1990
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x604f42

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA&*PRO6000

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\RODAN
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x63110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA_CPQ6300_TOPNET

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\EISA\RODANPORT2
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: Id
Type: REG_DWORD
Data: 0x63110e

Value 1
Name: Mask
Type: REG_DWORD
Data: 0xffffffff

Value 2
Name: Token
Type: REG_SZ
Data: EISA_CPQ6300_BOTTOMNET

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\NetDetect\ISA
Class Name: <NO CLASS>
Last Write Time: 12/17/2001 - 2:34 PM

Value 0
Name: BusType
Type: REG_DWORD
Data: 0x1

Key Name:
SYSTEM\CurrentControlSet\Services\NDIS\Parameters
Class Name: <NO CLASS>

Last Write Time: 1/8/2002 - 2:12 PM

Value 0
Name: ProcessorAffinityMask
Type: REG_DWORD
Data: 0

Key Name: SYSTEM\CurrentControlSet\Control\Session
Manager\Memory Management

Class Name: <NO CLASS>
Last Write Time: 1/29/2002 - 7:35 AM

Value 0
Name: ClearPageFileAtShutdown
Type: REG_DWORD
Data: 0

Value 1
Name: DisablePagingExecutive
Type: REG_DWORD
Data: 0

Value 2
Name: DontVerifyRandomDrivers
Type: REG_DWORD
Data: 0x1

Value 3
Name: IoPageLockLimit
Type: REG_DWORD
Data: 0

Value 4
Name: LargeSystemCache
Type: REG_DWORD
Data: 0

Value 5
Name: NonPagedPoolQuota
Type: REG_DWORD
Data: 0

Value 6
Name: NonPagedPoolSize
Type: REG_DWORD
Data: 0

Value 7
Name: PagedPoolQuota
Type: REG_DWORD
Data: 0

Value 8
Name: PagedPoolSize

Type: REG_DWORD
Data: 0

Value 9
Name: PagingFiles
Type: REG_MULTI_SZ
Data: C:\pagefile.sys 2046 4092

Value 10
Name: PhysicalAddressExtension
Type: REG_DWORD
Data: 0x1

Value 11
Name: SecondLevelDataCache
Type: REG_DWORD
Data: 0

Value 12
Name: SystemPages
Type: REG_DWORD
Data: 0

Key Name: SYSTEM\CurrentControlSet\Control\Session Manager\I/O
System

Class Name: <NO CLASS>
Last Write Time: 2/26/2002 - 11:22 AM

Value 0
Name: CountOperations
Type: REG_DWORD
Data: 0

Value 1
Name: LargeIrpStackLocations
Type: REG_DWORD
Data: 0x7

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server
Class Name: <NO CLASS>

Last Write Time: 3/5/2002 - 8:32 AM

Value 0
Name: InstalledInstances
Type: REG_MULTI_SZ
Data: MSSQLSERVER

Value 1
Name: SqlMdacRegRefCount
Type: REG_DWORD
Data: 0x1

```

Value 2
  Name:      SsrpActiveServer
  Type:      REG_SZ
  Data:

Key Name:    SOFTWARE\Microsoft\Microsoft SQL Server\8.00.000
Class Name:  <NO CLASS>
Last Write Time: 1/8/2002 - 1:07 PM

Key Name:    SOFTWARE\Microsoft\Microsoft SQL Server\80
Class Name:  <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM

Key Name:    SOFTWARE\Microsoft\Microsoft SQL
Server\80\MSSQLLicenseInfo
Class Name:  <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM

Key Name:    SOFTWARE\Microsoft\Microsoft SQL
Server\80\MSSQLLicenseInfo\MSSQL8.00
Class Name:  <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM
Value 0
  Name:      ConcurrentLimit
  Type:      REG_DWORD
  Data:      0x4

Value 1
  Name:      DisplayName
  Type:      REG_SZ
  Data:      SQL Server 2000

Value 2
  Name:      FamilyDisplayName
  Type:      REG_SZ
  Data:      Microsoft SQL Server

Value 3
  Name:      FlipAllow
  Type:      REG_DWORD
  Data:      0

Value 4
  Name:      Mode
  Type:      REG_DWORD
  Data:      0x2

Key Name:    SOFTWARE\Microsoft\Microsoft SQL
Server\80\Registration
Class Name:  <NO CLASS>

```

```

Last Write Time: 1/8/2002 - 1:34 PM
Value 0
  Name:      CD_KEY
  Type:      REG_SZ
  Data:      BC6JV-WVYQ9-PC8H6-W938R-8BWJD

Value 1
  Name:      DigitalProductID
  Type:      REG_BINARY
  Data:
00000000 a4 00 00 00 03 00 00 00 - 35 33 39 33 34 2d 30 30
00000010 00 00 00 00 00 00 00 00 - 53 34 34 30 30 30 30 39 - 35 2d 30 35 35 36 37 00 0-00000095-
05567.
00000020 0a 00 00 00 38 31 30 2d - 30 30 35 36 30 00 00 00 ...810-
00560...
00000030 00 00 00 00 12 00 00 00 - 00 a6 0a 0f 5e 9d 9e ef
.....|..^..i
00000040 0d 05 00 00 00 00 00 00 - 9a ee 3a 3c d7 a5 06 00
.....î:<x¥..
00000050 00 00 00 00 00 00 00 00 - 00 00 00 00 00 00 00 00
.....
00000060 00 00 00 00 00 00 00 00 - 31 33 35 32 33 00 00 00
.....13523...
00000070 00 00 00 00 00 5a 19 00 00 - 30 38 60 dc 00 08 00 00
....Z...08`Û....
00000080 86 01 00 00 00 00 00 00 - 00 00 00 00 00 00 00 00
.....
00000090 00 00 00 00 00 00 00 00 - 00 00 00 00 00 00 00 00
.....
000000a0 3d ec ef 48                                     =iîH

Value 2
  Name:      ProductID
  Type:      REG_SZ
  Data:      53934-000-0000095-05567

Key Name:    SOFTWARE\Microsoft\Microsoft SQL Server\80\Replication
Class Name:  <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM

Key Name:    SOFTWARE\Microsoft\Microsoft SQL
Server\80\Replication\MergeReplicationProvider
Class Name:  <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM

Key Name:    SOFTWARE\Microsoft\Microsoft SQL
Server\80\Replication\MergeReplicationProvider\MsJet
Class Name:  <NO CLASS>
Last Write Time: 1/25/2002 - 2:04 PM
Value 0
  Name:      <NO NAME>

```

Type: REG_SZ
Data: {f159cf30-0db4-11d1-b272-00aa00b8de95}

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server\80\Tools
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:39 PM

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server\80\Tools\ClientSetup
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM
Value 0
Name: SQLPath
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\80\Tools

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server\80\Tools\ClientSetup\CurrentVersion
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM
Value 0
Name: CurrentVersion
Type: REG_SZ
Data: 8.00.194

Value 1
Name: Language
Type: REG_DWORD
Data: 0x409

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server\80\Tools\Help
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM
Value 0
Name: HelpFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\80\Tools\Books\SQL80.col

Value 1
Name: HelpLCID
Type: REG_SZ
Data: 1033

Value 2
Name: HelpPath
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL Server\80\Tools\Books

Value 3

Name: RefCount
Type: REG_DWORD
Data: 0x1

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server\80\Tools\Service Manager
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM
Value 0
Name: Action Verify
Type: REG_DWORD
Data: 0

Value 1
Name: Default
Type: REG_SZ
Data: MSSQLSERVER

Value 2
Name: Remote
Type: REG_DWORD
Data: 0x1

Value 3
Name: Services
Type: REG_MULTI_SZ
Data: MSDTC

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server\80\Tools\SQLLEW
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM
Value 0
Name: CustomizableAlertBaseURL
Type: REG_SZ
Data:

Value 1
Name: CustomizableAlertDefaultBtnShortText
Type: REG_SZ
Data: Feedbac&k

Value 2
Name: CustomizableAlertDefaultButtonText
Type: REG_SZ
Data: &Send Feedback

Key Name: SOFTWARE\Microsoft\Microsoft SQL Server\80\Tools\SQLLEW\Replication
Class Name: <NO CLASS>

Last Write Time: 1/8/2002 - 1:34 PM

Value 0
Name: PerfmonFile
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\80\Tools\BINN\REPLMON.PMC

Key Name: SOFTWARE\Microsoft\Microsoft SQL
Server\80\Tools\SQLWizards
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM

Value 0
Name: Web Assistant
Type: REG_SZ
Data: C:\Program Files\Microsoft SQL
Server\80\Tools\BINN\semwebwz.DLL^WebWizardEntry

Key Name: SOFTWARE\Microsoft\Microsoft SQL
Server\80\Tools\Tracking
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM

Value 0
Name: {E07FDDA8-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Value 1
Name: {E07FDDA9-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Value 2
Name: {E07FDDAA-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Value 3
Name: {E07FDDAC-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Value 4
Name: {E07FDDAD-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Value 5
Name: {E07FDDAF-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Value 6
Name: {E07FDDBE-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Value 7
Name: {E07FDDBF-5A21-11d2-9DAD-00C04F79D434}
Type: REG_DWORD
Data: 0x1

Key Name: SOFTWARE\Microsoft\Microsoft SQL
Server\80\Tools\Tracking\Shortcuts
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 1:34 PM

Value 0
Name: Books Online
Type: REG_DWORD
Data: 0x1

Value 1
Name: Client Network Utility
Type: REG_DWORD
Data: 0x1

Value 2
Name: Configure SQL XML Support in IIS
Type: REG_DWORD
Data: 0x1

Value 3
Name: Enterprise Manager
Type: REG_DWORD
Data: 0x1

Value 4
Name: Import and Export Data
Type: REG_DWORD
Data: 0x1

Value 5
Name: Profiler
Type: REG_DWORD
Data: 0x1

Value 6
Name: Query Analyzer
Type: REG_DWORD
Data: 0x1

Value 7
Name: Server Network Utility
Type: REG_DWORD

```

Data:          0x1

Value 8
Name:          Service Manager
Type:          REG_DWORD
Data:          0x1

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0007
Class Name:    <NO CLASS>
Last Write Time: 2/14/2002 - 7:54 AM
Value 0
Name:          BusType
Type:          REG_SZ
Data:          5

Value 1
Name:          Characteristics
Type:          REG_DWORD
Data:          0x84

Value 2
Name:          CksumOffload
Type:          REG_SZ
Data:          1

Value 3
Name:          ComponentId
Type:          REG_SZ
Data:          pci\ven_12ae&dev_0001&subsys_00000000

Value 4
Name:          DebugPci
Type:          REG_SZ
Data:          0

Value 5
Name:          DriverDate
Type:          REG_SZ
Data:          10-19-1999

Value 6
Name:          DriverDateData
Type:          REG_BINARY
Data:          00000000 00 c0 db e2 c4 19 bf 01 - .ÃÛãÃ.¿.

Value 7
Name:          DriverDesc
Type:          REG_SZ
Data:          Alteon WebSystems PCI Gigabit Ethernet Adapter

```

```

Value 8
Name:          DriverVersion
Type:          REG_SZ
Data:          1.16.2.0

Value 9
Name:          FdrFilter
Type:          REG_SZ
Data:          0

Value 10
Name:          Fix450GX
Type:          REG_SZ
Data:          0

Value 11
Name:          HostTracing
Type:          REG_SZ
Data:          1

Value 12
Name:          InfPath
Type:          REG_SZ
Data:          netalt.inf

Value 13
Name:          InfSection
Type:          REG_SZ
Data:          acenic.ndi

Value 14
Name:          InfSectionExt
Type:          REG_SZ
Data:          .NT

Value 15
Name:          IntCount
Type:          REG_SZ
Data:          2000

Value 16
Name:          JumboFrames
Type:          REG_SZ
Data:          0

Value 17
Name:          JumboMtu
Type:          REG_SZ
Data:          1500

Value 18
Name:          LinkNegotiation
Type:          REG_SZ

```

Data: 1

Value 19
 Name: MatchingDeviceId
 Type: REG_SZ
 Data: pci\ven_12ae&dev_0001&subsys_00000000

Value 20
 Name: NetCfgInstanceId
 Type: REG_SZ
 Data: {94EA42D7-2D61-4FF8-BE75-502153BA7F26}

Value 21
 Name: NicTracing
 Type: REG_SZ
 Data: 0

Value 22
 Name: PciLatencyTimer
 Type: REG_SZ
 Data: 40

Value 23
 Name: PciMemInvalidate
 Type: REG_SZ
 Data: 1

Value 24
 Name: PciReadMax
 Type: REG_SZ
 Data: ffffffff

Value 25
 Name: PciWriteMax
 Type: REG_SZ
 Data: ffffffff

Value 26
 Name: ProviderName
 Type: REG_SZ
 Data: Microsoft

Value 27
 Name: RecvCoalMax
 Type: REG_SZ
 Data: 80

Value 28
 Name: RecvCoalTicks
 Type: REG_SZ
 Data: 10000

Value 29

Name: RxFlowControl
 Type: REG_SZ
 Data: 0

Value 30
 Name: SendCoalMax
 Type: REG_SZ
 Data: 80

Value 31
 Name: SendCoalTicks
 Type: REG_SZ
 Data: 10000

Value 32
 Name: StatTicks
 Type: REG_SZ
 Data: 100000

Value 33
 Name: TxFlowControl
 Type: REG_SZ
 Data: 0

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Linkage
 Class Name: <NO CLASS>
 Last Write Time: 2/12/2002 - 3:56 PM

Value 0
 Name: Export
 Type: REG_MULTI_SZ
 Data: \Device\{94EA42D7-2D61-4FF8-BE75-502153BA7F26}

Value 1
 Name: RootDevice
 Type: REG_MULTI_SZ
 Data: {94EA42D7-2D61-4FF8-BE75-502153BA7F26}

Value 2
 Name: UpperBind
 Type: REG_MULTI_SZ
 Data: Tcpip

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi
 Class Name: <NO CLASS>
 Last Write Time: 2/12/2002 - 3:56 PM

Value 0

Name: Service
Type: REG_SZ
Data: altn5

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\Interfaces

Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: LowerRange
Type: REG_SZ
Data: ethernet

Value 1
Name: UpperRange
Type: REG_SZ
Data: ndis5

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params

Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\JumboFrames

Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: default
Type: REG_SZ
Data: 0

Value 1
Name: ParamDesc
Type: REG_SZ
Data: JumboFrames

Value 2
Name: type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\JumboFrames\enum

Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: 0
Type: REG_SZ
Data: Off

Value 1
Name: 1
Type: REG_SZ
Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\JumboMtu

Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: base
Type: REG_SZ
Data: 10

Value 1
Name: default
Type: REG_SZ
Data: 1500

Value 2
Name: max
Type: REG_SZ
Data: 9000

Value 3
Name: min
Type: REG_SZ
Data: 1500

Value 4
Name: ParamDesc
Type: REG_SZ
Data: JumboMtu

Value 5
Name: step
Type: REG_SZ
Data: 100

Value 6
Name: type
Type: REG_SZ
Data: dword

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\LinkNegotiation

Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: default

Type: REG_SZ
Data: 1

Value 1
Name: ParamDesc
Type: REG_SZ
Data: LinkNegotiation

Value 2
Name: type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\LinkNegotiation\enum
Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: 0
Type: REG_SZ
Data: Off

Value 1
Name: 1
Type: REG_SZ
Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\NetworkAddress
Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: default
Type: REG_SZ
Data: 0060CF000000

Value 1
Name: optional
Type: REG_SZ
Data: 1

Value 2
Name: ParamDesc
Type: REG_SZ
Data: NetworkAddress

Value 3
Name: type
Type: REG_SZ
Data: edit

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\RxFowControl
Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: default
Type: REG_SZ
Data: 1

Value 1
Name: ParamDesc
Type: REG_SZ
Data: RxFowControl

Value 2
Name: type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\RxFowControl\enum
Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: 0
Type: REG_SZ
Data: Off

Value 1
Name: 1
Type: REG_SZ
Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0007\Ndi\params\TxFlowControl
Class Name: <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM

Value 0
Name: default
Type: REG_SZ
Data: 0

Value 1
Name: ParamDesc
Type: REG_SZ
Data: TxFlowControl

Value 2
Name: type
Type: REG_SZ

```

Data:          enum

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0007\Ngi\params\TxFlowControl\enum
Class Name:    <NO CLASS>
Last Write Time: 2/12/2002 - 3:56 PM
Value 0
  Name:        0
  Type:        REG_SZ
  Data:        Off

Value 1
  Name:        1
  Type:        REG_SZ
  Data:        On

Key Name:      SYSTEM\CurrentControlSet\Services\dac2w2k
Class Name:    <NO CLASS>
Last Write Time: 1/8/2002 - 2:04 PM
Value 0
  Name:        ErrorControl
  Type:        REG_DWORD
  Data:        0x1

Value 1
  Name:        Group
  Type:        REG_SZ
  Data:        SCSI Miniport

Value 2
  Name:        ImagePath
  Type:        REG_EXPAND_SZ
  Data:        System32\DRIVERS\dac2w2k.sys

Value 3
  Name:        Start
  Type:        REG_DWORD
  Data:        0

Value 4
  Name:        Tag
  Type:        REG_DWORD
  Data:        0x21

Value 5
  Name:        Type
  Type:        REG_DWORD
  Data:        0x1

Key Name:      SYSTEM\CurrentControlSet\Services\dac2w2k\Enum

```

```

Class Name:    <NO CLASS>
Last Write Time: 3/4/2002 - 10:20 AM
Value 0
  Name:        0
  Type:        REG_SZ
  Data:        PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2254b0d&0&4030

Value 1
  Name:        1
  Type:        REG_SZ
  Data:        PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1c72a60d&0&4038

Value 2
  Name:        2
  Type:        REG_SZ
  Data:        PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&1ece4987&0&4028

Value 3
  Name:        3
  Type:        REG_SZ
  Data:        PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2f92d4b0&0&4020

Value 4
  Name:        4
  Type:        REG_SZ
  Data:        PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2df34b01&0&4018

Value 5
  Name:        5
  Type:        REG_SZ
  Data:        PCI\VEN_1069&DEV_BA56&SUBSYS_00401069&REV_00\4&2bee4042&0&4010

Value 6
  Name:        Count
  Type:        REG_DWORD
  Data:        0x6

Value 7
  Name:        NextInstance
  Type:        REG_DWORD
  Data:        0x6

Key Name:      SYSTEM\CurrentControlSet\Services\dac2w2k\Parameters
Class Name:    <NO CLASS>
Last Write Time: 1/8/2002 - 2:04 PM

```

```

Key Name:
SYSTEM\CurrentControlSet\Services\dac2w2k\Parameters\Device
Class Name: <NO CLASS>
Last Write Time: 2/19/2002 - 9:51 AM
Value 0
  Name: DriverParameter
  Type: REG_SZ
  Data: EnableSIR

Key Name:
SYSTEM\CurrentControlSet\Services\dac2w2k\Parameters\PnpInterface
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 2:04 PM
Value 0
  Name: 5
  Type: REG_DWORD
  Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\dac2w2k\Security
Class Name: <NO CLASS>
Last Write Time: 1/8/2002 - 2:04 PM
Value 0
  Name: Security
  Type: REG_BINARY
  Data:
00000000 01 00 14 80 a0 00 00 00 - ac 00 00 00 14 00 00 00
.....
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00
0.....
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00
ÿ.....
00000030 02 00 70 00 04 00 00 00 - 00 00 18 00 fd 01 02 00
..p.....ÿ...
00000040 01 01 00 00 00 00 00 05 - 12 00 00 00 74 00 69 00
.....t.i.
00000050 00 00 1c 00 ff 01 0f 00 - 01 02 00 00 00 00 00 05
...ÿ.....
00000060 20 00 00 00 20 02 00 00 - 76 00 65 00 00 00 18 00 ...
...v.e....
00000070 8d 01 02 00 01 01 00 00 - 00 00 00 05 0b 00 00 00
.....
00000080 20 02 00 00 00 00 1c 00 - fd 01 02 00 01 02 00 00
.....ÿ.....
00000090 00 00 00 05 20 00 00 00 - 23 02 00 00 76 00 65 00 ....
...#...v.e.
000000a0 01 01 00 00 00 00 00 05 - 12 00 00 00 01 01 00 00
.....
000000b0 00 00 00 05 12 00 00 00 -
.....

```

This section discloses hardware information and the Windows 2000 registry parameters used on the PRIMERGY L200 client systems.

System Information report written at: 03/05/2002 08:56:52 AM
[System Summary]

```

Item Value
OS Name      Microsoft Windows 2000 Server
Version      5.0.2195 Service Pack 2 Build 2195
OS Manufacturer Microsoft Corporation
System Name   L200CL1
System Manufacturer FUJITSU SIEMENS
System Model  D1307
System Type   X86-based PC
Processor    x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1261 Mhz
Processor    x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1261 Mhz
BIOS Version  4.06 Rev. 1.02.1307
Windows Directory C:\WINNT
System Directory C:\WINNT\System32
Boot Device   \Device\Harddisk0\Partition1
Locale        United States
User Name     L200CL1\Administrator
Time Zone     W. Europe Standard Time
Total Physical Memory 523,816 KB
Available Physical Memory 445,704 KB
Total Virtual Memory 1,540,284 KB
Available Virtual Memory 1,406,964 KB
Page File Space 1,016,468 KB
Page File     C:\pagefile.sys

```

System Information report written at: 03/05/2002 08:57:29 AM
[Hardware Resources]

[Following are sub-categories of this main category]

[Conflicts/Sharing]

Resource Device
No conflicted/shared resources

[DMA]

```

Channel Device Status
4 Direct memory access controller OK
2 Standard floppy disk controller OK

```

[Forced Hardware]

Device PNP Device ID
No Forced Hardware

[I/O]

Address Range	Device	Status
0x0000-0x0CF7	PCI bus	OK
0x0000-0x0CF7	Direct memory access controller	OK
0x0D00-0x0FFF	PCI bus	OK
0x1000-0x1C0F	PCI bus	OK
0x1000-0x1C0F	ATI Technologies Inc. RAGE XL PCI	OK
0x03B0-0x03BB	ATI Technologies Inc. RAGE XL PCI	OK
0x03C0-0x03DF	ATI Technologies Inc. RAGE XL PCI	OK
0x1400-0x143F	Intel 8255x-based PCI Ethernet Adapter (10/100)	OK
0x1800-0x183F	Intel 8255x-based PCI Ethernet Adapter (10/100) #2	OK
0x0A79-0x0A79	ISAPNP Read Data Port	OK
0x0279-0x0279	ISAPNP Read Data Port	OK
0x02F4-0x02F7	ISAPNP Read Data Port	OK
0x0010-0x001F	Motherboard resources	OK
0x0022-0x002D	Motherboard resources	OK
0x0030-0x003F	Motherboard resources	OK
0x0050-0x0053	Motherboard resources	OK
0x0062-0x0063	Motherboard resources	OK
0x0065-0x006F	Motherboard resources	OK
0x0074-0x007F	Motherboard resources	OK
0x0090-0x009F	Motherboard resources	OK
0x00A2-0x00B1	Motherboard resources	OK
0x00B4-0x00BF	Motherboard resources	OK
0x00E0-0x00EF	Motherboard resources	OK
0x0072-0x0073	Motherboard resources	OK
0x04D0-0x04D1	Motherboard resources	OK
0xF100-0xF10F	Motherboard resources	OK
0x0080-0x008F	Direct memory access controller	OK
0x00C0-0x00DF	Direct memory access controller	OK
0x0020-0x0021	Programmable interrupt controller	OK
0x00A0-0x00A1	Programmable interrupt controller	OK
0x0070-0x0071	System CMOS/real time clock	OK
0x0040-0x0043	System timer	OK
0x00F0-0x00FE	Numeric data processor	OK
0x0061-0x0061	System speaker	OK
0x0060-0x0060	Standard 101/102-Key or Microsoft Natural PS/2 Keyboard	OK
0x0064-0x0064	Standard 101/102-Key or Microsoft Natural PS/2 Keyboard	OK
0x03F0-0x03F5	Standard floppy disk controller	OK
0x03F7-0x03F7	Standard floppy disk controller	OK
0x1C00-0x1C0F	Standard Dual Channel PCI IDE Controller	OK
0x01F0-0x01F7	Primary IDE Channel	OK
0x03F6-0x03F6	Primary IDE Channel	OK
0x0170-0x0177	Secondary IDE Channel	OK
0x0376-0x0376	Secondary IDE Channel	OK
0x2000-0x20FF	PCI bus	OK
0x2000-0x20FF	Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device	OK

[IRQs]

IRQ Number Device

9	Microsoft ACPI-Compliant System
30	Intel 8255x-based PCI Ethernet Adapter (10/100)
31	Intel 8255x-based PCI Ethernet Adapter (10/100) #2
8	System CMOS/real time clock
13	Numeric data processor
1	Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
12	PS/2 Compatible Mouse
6	Standard floppy disk controller
15	Secondary IDE Channel
29	Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device

[Memory]

Range	Device	Status
0xA0000-0xBFFFF	PCI bus	OK
0xA0000-0xBFFFF	ATI Technologies Inc. RAGE XL PCI	OK
0xC8000-0xDFFFF	PCI bus	OK
0xFC000000-0xFDFFFFFF	PCI bus	OK
0xFC000000-0xFDFFFFFF	Intel 8255x-based PCI Ethernet Adapter (10/100)	OK
0xFED00000-0xFEDFFFFFF	PCI bus	OK
0xFEE01000-0xFFBFFFFFF	PCI bus	OK
0xFD000000-0xFDFFFFFF	ATI Technologies Inc. RAGE XL PCI	OK
0xFC040000-0xFC040FFF	ATI Technologies Inc. RAGE XL PCI	OK
0xFC041000-0xFC041FFF	Intel 8255x-based PCI Ethernet Adapter (10/100)	OK
0xFC042000-0xFC042FFF	Intel 8255x-based PCI Ethernet Adapter (10/100)	OK
#2	OK	
0xFC020000-0xFC03FFFF	Intel 8255x-based PCI Ethernet Adapter (10/100)	OK
#2	OK	
0xFE000000-0xFE3FFFFF	PCI bus	OK
0xFE000000-0xFE3FFFFF	Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device	OK
0xFE002000-0xFE0023FF	Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device	OK

System Information report written at: 03/05/2002 08:57:18 AM

[Components]

[Following are sub-categories of this main category]

[Multimedia]

[Following are sub-categories of this main category]

[Audio Codecs]

Codec	Manufacturer	Description	Status	File Version	Size
		Creation Date			

```

c:\winnt\system32\iac25_32.ax Intel Corporation Indeo® audio software
OK C:\WINNT\System32\IAC25_32.AX 2.05.53 195.00 KB (199,680
bytes) 12/7/1999 1:00:00 PM
c:\winnt\system32\lhacm.acm Microsoft Corporation OK
C:\WINNT\System32\LHACM.ACM 4.4.3385 33.27 KB (34,064 bytes)
2/12/2001 3:47:53 PM
c:\winnt\system32\msg723.acm Microsoft Corporation OK
C:\WINNT\System32\MSG723.ACM 4.4.3385 106.77 KB (109,328 bytes)
2/12/2001 3:47:52 PM
c:\winnt\system32\tssoft32.acm DSP GROUP, INC. OK
C:\WINNT\System32\TSSOFT32.ACM 1.01 9.27 KB (9,488 bytes)
12/7/1999 1:00:00 PM
c:\winnt\system32\msg711.acm Microsoft Corporation OK
C:\WINNT\System32\MSG711.ACM 5.00.2134.1 10.27 KB (10,512
bytes) 12/7/1999 1:00:00 PM
c:\winnt\system32\msgsm32.acm Microsoft Corporation OK
C:\WINNT\System32\MSGSM32.ACM 5.00.2134.1 22.27 KB (22,800
bytes) 12/7/1999 1:00:00 PM
c:\winnt\system32\msadp32.acm Microsoft Corporation OK
C:\WINNT\System32\MSADP32.ACM 5.00.2134.1 14.77 KB (15,120
bytes) 12/7/1999 1:00:00 PM
c:\winnt\system32\imaadp32.acm Microsoft Corporation OK
C:\WINNT\System32\IMAADP32.ACM 5.00.2134.1 16.27 KB (16,656
bytes) 12/7/1999 1:00:00 PM

```

[Video Codecs]

CodecManufacturer	Description	Status	File Version	Size
Creation Date				
c:\winnt\system32\ir50_32.dll	Intel Corporation Indeo® video 5.10	OK	R.5.10.15.2.55	737.50 KB (755,200 bytes)
c:\winnt\system32\msh261.drv	Microsoft Corporation	OK	4.4.3385	163.77 KB (167,696 bytes)
c:\winnt\system32\iccvid.dll	Radius Inc.	OK	1.10.0.6	108.00 KB (110,592 bytes)
c:\winnt\system32\msvidc32.dll	Microsoft Corporation	OK	5.00.2134.1	27.27 KB (27,920 bytes)
c:\winnt\system32\ir32_32.dll	Intel(R) Corporation	OK	Not Available	194.50 KB (199,168 bytes)
c:\winnt\system32\msrle32.dll	Microsoft Corporation	OK	5.00.2134.1	10.77 KB (11,024 bytes)
c:\winnt\system32\msh263.drv	Microsoft Corporation	OK	4.4.3385	252.27 KB (258,320 bytes)

[CD-ROM]

```

Item Value
DriveD:
Description CD-ROM Drive
Media Loaded False
Media Type CD-ROM
Name MITSUMI CD-ROM SR243T
Manufacturer (Standard CD-ROM drives)
Status OK
Transfer Rate Not Available
SCSI Target ID 0
PNP Device ID IDE\CDROMMITSUMI_CD-
ROM_SR243T_____L02G____\5&3858FEE&0&0.0.0

```

[Sound Device]

```

Item Value
No sound devices

```

[Display]

```

Item Value
Name ATI Technologies Inc. RAGE XL PCI
PNP Device ID
PCI\VEN_1002&DEV_4752&SUBSYS_007A110A&REV_27\3&13C0B0C5&0&20
Adapter Type ATI RAGE XL PCI, ATI Technologies Inc. compatible
Adapter Description ATI Technologies Inc. RAGE XL PCI
Adapter RAM 8.00 MB (8,388,608 bytes)
Installed Drivers atidrab.dll
Driver Version 5.00.2179.1
INF File display.inf (atirage3 section)
Color Planes 1
Color Table Entries 16777216
Resolution 800 x 600 x 85 hertz
Bits/Pixel 24

```

[Infrared]

```

Item Value
No infrared devices

```

[Input]

[Following are sub-categories of this main category]

[Keyboard]

```

Item Value
Description Standard 101/102-Key or Microsoft Natural PS/2 Keyboard
Name Enhanced (101- or 102-key)
Layout 00000409
PNP Device ID ACPI\PNP0303\5&1413D98F&0

```

NumberOfFunctionKeys 12

[Pointing Device]

Item Value
Hardware Type PS/2 Compatible Mouse
Number of Buttons 2
Status OK
PNP Device ID ACPI\PNP0F13\5&1413D98F&0
Power Management SupportedFalse
Double Click Threshold 6
Handedness Right Handed Operation

[Modem]

Item Value
No modems

[Network]

[Following are sub-categories of this main category]

[Adapter]

Item Value
Name [00000000] Intel 8255x-based PCI Ethernet Adapter (10/100)
Adapter Type Ethernet 802.3
Product Name Intel 8255x-based PCI Ethernet Adapter (10/100)
Installed True
PNP Device ID
PCI\VEN_8086&DEV_1229&SUBSYS_004B110A&REV_09\3&13C0B0C5&0&50
Last Reset 3/4/2002 11:17:08 AM
Index0
Service Name E100B
IP Address 129.103.181.211
IP Subnet 255.255.255.0
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address 00:30:05:15:8A:F8
Service Name E100B
IRQ Number 30
I/O Port 0x1400-0x143F
Driver c:\winnt\system32\drivers\e100bnt5.sys (119056, 5.40.11.0000)

Name [00000001] RAS Async Adapter
Adapter Type Not Available
Product Name RAS Async Adapter
Installed True

PNP Device ID Not Available
Last Reset 3/4/2002 11:17:08 AM
Index1
Service Name AsyncMac
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Not Available

Name [00000002] WAN Miniport (L2TP)
Adapter Type Not Available
Product Name WAN Miniport (L2TP)
Installed True
PNP Device ID ROOT\MS_L2TPMINIPORT\0000
Last Reset 3/4/2002 11:17:08 AM
Index2
Service Name Rasl2tp
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Rasl2tp
Driver c:\winnt\system32\drivers\rasl2tp.sys (50800, 5.00.2179.1)

Name [00000003] WAN Miniport (PPTP)
Adapter Type Wide Area Network (WAN)
Product Name WAN Miniport (PPTP)
Installed True
PNP Device ID ROOT\MS_PPTPMINIPORT\0000
Last Reset 3/4/2002 11:17:08 AM
Index3
Service Name PptpMiniport
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address 50:50:54:50:30:30
Service Name PptpMiniport
Driver c:\winnt\system32\drivers\raspptp.sys (47856, 5.00.2160.1)

Name [00000004] Direct Parallel

Adapter Type Not Available
Product Name Direct Parallel
Installed True
PNP Device ID ROOT\MS_PTMINIPOINT\0000
Last Reset 3/4/2002 11:17:08 AM
Index4
Service Name Raspti
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name Raspti
Driver c:\winnt\system32\drivers\raspti.sys (16880, 5.00.2146.1)

Name [00000005] WAN Miniport (IP)
Adapter Type Not Available
Product Name WAN Miniport (IP)
Installed True
PNP Device ID ROOT\MS_NDISWANIP\0000
Last Reset 3/4/2002 11:17:08 AM
Index5
Service Name NdisWan
IP Address Not Available
IP Subnet Not Available
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available
MAC Address Not Available
Service Name NdisWan
Driver c:\winnt\system32\drivers\ndiswan.sys (90096, 5.00.2195.2779)

Name [00000006] Intel 8255x-based PCI Ethernet Adapter (10/100)
Adapter Type Ethernet 802.3
Product Name Intel 8255x-based PCI Ethernet Adapter (10/100)
Installed True
PNP Device ID
PCI\VEN_8086&DEV_1229&SUBSYS_004B110A&REV_09\3&13C0B0C5&0&58
Last Reset 3/4/2002 11:17:08 AM
Index6
Service Name E100B
IP Address 129.103.211.1
IP Subnet 255.255.255.0
Default IP Gateway Not Available
DHCP Enabled False
DHCP Server Not Available
DHCP Lease Expires Not Available
DHCP Lease Obtained Not Available

MAC Address 00:30:05:26:D8:07
Service Name E100B
IRQ Number 31
I/O Port 0x1800-0x183F
Driver c:\winnt\system32\drivers\e100bnt5.sys (119056, 5.40.11.0000)

[Protocol]

Item Value
Name MSAFD Tcpip [TCP/IP]
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 16 bytes
MaximumMessageSize 0 bytes
MessageOriented False
MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData True
SupportsGracefulClosing True
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD Tcpip [UDP/IP]
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 16 bytes
MaximumMessageSize 65467 bytes
MessageOriented True
MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting True

Name RSVP UDP Service Provider
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 16 bytes
MaximumMessageSize 65467 bytes
MessageOriented True

MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption True
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting True

Name RSVP TCP Service Provider
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 16 bytes
MaximumMessageSize 0 bytes
MessageOriented False
MinimumAddressSize 16 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption True
SupportsExpeditedData True
SupportsGracefulClosing True
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{5A32B06F-0639-4600-9EA0-12CBF488ACDD}] SEQPACKET 3
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{5A32B06F-0639-4600-9EA0-12CBF488ACDD}] DATAGRAM 3
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False

MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{940C64C1-6989-48A3-8BC2-A1D440A00EF8}] SEQPACKET 0
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{940C64C1-6989-48A3-8BC2-A1D440A00EF8}] DATAGRAM 0
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}] SEQPACKET 1
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}] DATAGRAM 1
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}] SEQPACKET 2
ConnectionlessService False
GuaranteesDelivery True
GuaranteesSequencing True
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting False
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False

SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

Name MSAFD NetBIOS [\Device\NetBT_Tcpip_{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}] DATAGRAM 2
ConnectionlessService True
GuaranteesDelivery False
GuaranteesSequencing False
MaximumAddressSize 20 bytes
MaximumMessageSize 64000 bytes
MessageOriented True
MinimumAddressSize 20 bytes
PseudoStreamOriented False
SupportsBroadcasting True
SupportsConnectData False
SupportsDisconnectData False
SupportsEncryption False
SupportsExpeditedData False
SupportsGracefulClosing False
SupportsGuaranteedBandwidth False
SupportsMulticasting False

[WinSock]

Item Value
File c:\winnt\system32\winsock.dll
Version 3.10
Size 2.80 KB (2,864 bytes)

File c:\winnt\system32\wsock32.dll
Version 5.00.2195.2871
Size 21.27 KB (21,776 bytes)

[Ports]

[Following are sub-categories of this main category]

[Serial]

Item Value
No serial port information

[Parallel]

Item Value
No parallel port information

[Storage]

[Following are sub-categories of this main category]

[Drives]

Item Value
DriveA:
Description 3 1/2 Inch Floppy Drive

DriveC:
Description Local Fixed Disk
Compressed False
File System NTFS
Size 17.01 GB (18,268,311,552 bytes)
Free Space 14.96 GB (16,058,630,144 bytes)
Volume Name
Volume Serial Number 080A3D50
Partition Disk #0, Partition #0
Partition Size 17.01 GB (18,268,314,624 bytes)
Starting Offset 32256 bytes
Drive Description Disk drive
Drive Manufacturer (Standard disk drives)
Drive Model FUJITSU MAG3182LC SCSI Disk Device
Drive BytesPerSector 512
Drive MediaLoaded True
Drive MediaType Fixed hard disk media
Drive Partitions 1
Drive SCsIBus 0
Drive SCsILogicalUnit 0
Drive SCsIPort 2
Drive SCsITargetId 0
Drive SectorsPerTrack 63
Drive Size 18268346880 bytes
Drive TotalCylinders 2221
Drive TotalSectors 35680365
Drive TotalTracks 566355
Drive TracksPerCylinder 255

[SCSI]

Item Value
Name Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device
Caption Symbios Ultra3 PCI SCSI Adapter; 53C1010-66 Device
Driver Sym_u3
Status OK
PNP Device ID
PCI\VEN_1000&DEV_0021&SUBSYS_6030110A&REV_01\3&1070020&0&50
Device ID PCI\VEN_1000&DEV_0021&SUBSYS_6030110A&REV_01\3&1070020&0&50
Device Map Not Available
Index Not Available
Max Number Controlled Not Available
IRQ Number 29
I/O Port 0x2000-0x20FF
Driver c:\winnt\system32\drivers\sym_u3.sys (37920, SYM_U3NT-5.08.00)

[Printing]

Name Port Name Server Name
No printing information

[Problem Devices]

Device PNP Device ID Error Code
No Problem Devices

[USB]

Device PNP Device ID
No USB Devices

System Information report written at: 03/05/2002 08:56:52 AM
[System Summary]

Item Value

OS Name Microsoft Windows 2000 Server
Version 5.0.2195 Service Pack 2 Build 2195
OS Manufacturer Microsoft Corporation
System Name L200CL1
System Manufacturer FUJITSU SIEMENS
System Model D1307
System Type X86-based PC
Processor x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1261 Mhz
Processor x86 Family 6 Model 11 Stepping 1 GenuineIntel ~1261 Mhz
BIOS Version 4.06 Rev. 1.02.1307
Windows Directory C:\WINNT
System Directory C:\WINNT\System32
Boot Device \Device\Harddisk0\Partition1
Locale United States
User Name L200CL1\Administrator
Time Zone W. Europe Standard Time
Total Physical Memory 523,816 KB
Available Physical Memory 445,704 KB
Total Virtual Memory 1,540,284 KB
Available Virtual Memory 1,406,964 KB
Page File Space 1,016,468 KB
Page File C:\pagefile.sys

System Information report written at: 03/05/2002 08:58:08 AM
[Environment Variables]

Variable Value User Name
ComSpec %SystemRoot%\system32\cmd.exe <SYSTEM>
Os2LibPath %SystemRoot%\system32\os2\dll; <SYSTEM>

```

Path
  %SystemRoot%\system32;%SystemRoot%;%SystemRoot%\System32\Wbem;C:\Program Files\Microsoft SQL Server\80\Tools\BINN <SYSTEM>
windir %SystemRoot% <SYSTEM>
OS Windows_NT <SYSTEM>
PROCESSOR_ARCHITECTURE x86 <SYSTEM>
PROCESSOR_LEVEL 6 <SYSTEM>
PROCESSOR_IDENTIFIER x86 Family 6 Model 11 Stepping 1, GenuineIntel <SYSTEM>
PROCESSOR_REVISION 0b01 <SYSTEM>
NUMBER_OF_PROCESSORS 2 <SYSTEM>
PATHEXT .COM;.EXE;.BAT;.CMD;.VBS;.VBE;.JS;.JSE;.WSF;.WSH <SYSTEM>
TEMP %SystemRoot%\TEMP <SYSTEM>
TMP %SystemRoot%\TEMP <SYSTEM>
TEMP %USERPROFILE%\Local Settings\Temp L200CL1\Administrator
TMP %USERPROFILE%\Local Settings\Temp L200CL1\Administrator

```

System Information report written at: 03/05/2002 08:58:34 AM
[Services]

Display Name	Name	State	Start	Mode	Service Type	Path	Error	Control
Start Name	Tag	ID						
Alerter	Alerter	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Application Management	AppMgmt	Stopped	Manual	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Computer Browser	Browser	Stopped	Disabled	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Indexing Service	cisvc	Stopped	Manual	Share	Process	c:\winnt\system32\cisvc.exe	Normal	LocalSystem 0
ClipBook	ClipSrv	Stopped	Manual	Own	Process	c:\winnt\system32\clipsrv.exe	Normal	LocalSystem 0
Distributed File System	Dfs	Stopped	Manual	Own	Process	c:\winnt\system32\dfssvc.exe	Normal	LocalSystem 0
DHCP Client	Dhcp	Stopped	Disabled	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Logical Disk Manager	Administrative Service	Stopped	Manual	Share	Process	c:\winnt\system32\dmadmin.exe	Normal	LocalSystem 0
Logical Disk Manager	dmserver	Stopped	Manual	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
DNS Client	Dnscache	Stopped	Manual	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Event Log	Eventlog	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
COM+ Event System	EventSystem	Running	Auto	Share	Process	c:\winnt\system32\svchost.exe	-k netsvcs	Normal LocalSystem 0
Fax Service	Fax	Stopped	Disabled	Own	Process	c:\winnt\system32\faxsvc.exe	Normal	LocalSystem 0
IIS Admin Service	IISADMIN	Running	Manual	Share	Process	c:\winnt\system32\inet_srv\inetinfo.exe	Normal	LocalSystem 0

Intersite Messaging	IsmServ	Stopped	Disabled	Own	Process	c:\winnt\system32\ismserv.exe	Normal	LocalSystem 0
Kerberos Key Distribution Center	kdc	Stopped	Disabled	Share	Process	c:\winnt\system32\lsass.exe	Normal	LocalSystem 0
Server	lanmanserver	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Workstation	lanmanworkstation	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
License Logging Service	LicenseService	Stopped	Manual	Own	Process	c:\winnt\system32\llssrv.exe	Normal	LocalSystem 0
TCP/IP NetBIOS Helper Service	LmHosts	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Messenger	Messenger	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
NetMeeting Remote Desktop Sharing	nmmsrvc	Stopped	Disabled	Own	Process	c:\winnt\system32\nmmsrvc.exe	Normal	LocalSystem 0
Distributed Transaction Coordinator	MSDTC	Stopped	Manual	Own	Process	c:\winnt\system32\msdtc.exe	Normal	LocalSystem 0
Windows Installer	MSIServer	Stopped	Manual	Share	Process	c:\winnt\system32\msiexec.exe	/v	Normal LocalSystem 0
Network DDE	NetDDE	Stopped	Manual	Share	Process	c:\winnt\system32\netdde.exe	Normal	LocalSystem 0
Network DDE DSDM	NetDDEdsdm	Stopped	Manual	Share	Process	c:\winnt\system32\netdde.exe	Normal	LocalSystem 0
Net Logon	Netlogon	Stopped	Manual	Share	Process	c:\winnt\system32\lsass.exe	Normal	LocalSystem 0
Network Connections	Netman	Running	Manual	Share	Process	c:\winnt\system32\svchost.exe	-k netsvcs	Normal LocalSystem 0
NMS Service	NMSSvc	Stopped	Manual	Own	Process	c:\winnt\system32\nmssvc.exe	Normal	LocalSystem 0
File Replication	NtFrfs	Stopped	Manual	Own	Process	c:\winnt\system32\ntfrfs.exe	Ignore	LocalSystem 0
NT LM Security Support Provider	NtLmSsp	Stopped	Manual	Share	Process	c:\winnt\system32\lsass.exe	Normal	LocalSystem 0
Removable Storage	NtmsSvc	Stopped	Disabled	Share	Process	c:\winnt\system32\svchost.exe	-k netsvcs	Normal LocalSystem 0
Plug and Play	PlugPlay	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
IPSEC Policy Agent	PolicyAgent	Stopped	Manual	Share	Process	c:\winnt\system32\lsass.exe	Normal	LocalSystem 0
Protected Storage	ProtectedStorage	Running	Auto	Share	Process	c:\winnt\system32\services.exe	Normal	LocalSystem 0
Remote Access Auto Connection Manager	RasAuto	Stopped	Manual	Share	Process	c:\winnt\system32\svchost.exe	-k netsvcs	Normal LocalSystem 0
Remote Access Connection Manager	RasMan	Stopped	Manual	Share	Process	c:\winnt\system32\svchost.exe	-k netsvcs	Normal LocalSystem 0
Routing and Remote Access	RemoteAccess	Stopped	Disabled	Share	Process	c:\winnt\system32\svchost.exe	-k netsvcs	Normal LocalSystem 0

```

Remote Registry Service RemoteRegistry Stopped Manual Own
Process c:\winnt\system32\regsvc.exe Normal LocalSystem 0
Remote Command Service RMSYS Stopped Disabled Own Process
c:\benchcrf_422\rsv.exe Normal LocalSystem 0
Remote Procedure Call (RPC) Locator RpcLocator Stopped Manual Own
Process c:\winnt\system32\locator.exe Normal LocalSystem 0
Remote Procedure Call (RPC) RpcSs Running Auto Share Process
c:\winnt\system32\svchost -k rpcss Normal LocalSystem 0
QoS RSVP RSVP Running Manual Own Process
c:\winnt\system32\rsvp.exe -s Normal LocalSystem 0
Security Accounts Manager SamSs Stopped Manual Share Process
c:\winnt\system32\lsass.exe Normal LocalSystem 0
Smart Card Helper SCardDrv Stopped Manual Share Process
c:\winnt\system32\scardsvr.exe Ignore LocalSystem 0
Smart Card SCardSvr Stopped Manual Share Process
c:\winnt\system32\scardsvr.exe Ignore LocalSystem 0
Task Scheduler Scheduler Stopped Manual Share Process
c:\winnt\system32\mstask.exe Normal LocalSystem 0
RunAs Service seclogon Stopped Manual Share Process
c:\winnt\system32\services.exe Ignore LocalSystem 0
System Event Notification SENS Running Auto Share Process
c:\winnt\system32\svchost.exe -k netsvcs Normal LocalSystem
0
Internet Connection Sharing SharedAccess Stopped Manual Share
Process c:\winnt\system32\svchost.exe -k netsvcs Normal
LocalSystem 0
Simple Mail Transport Protocol (SMTP) SMTPSVC Stopped Manual
Share Process c:\winnt\system32\inetrv\inetinfo.exe Normal
LocalSystem 0
Print Spooler Spooler Stopped Manual Own Process
c:\winnt\system32\spoolsv.exe Normal LocalSystem 0
Performance Logs and Alerts SysmonLog Stopped Manual Own
Process c:\winnt\system32\smlogsvc.exe Normal LocalSystem 0
Telephony TapiSrv Stopped Disabled Share Process
c:\winnt\system32\svchost.exe -k tapisrv Normal LocalSystem
0
Terminal Services TermService Stopped Disabled Own Process
c:\winnt\system32\termsrv.exe Normal LocalSystem 0
Telnet TlntSvr Stopped Disabled Own Process
c:\winnt\system32\tlntsvr.exe Normal LocalSystem 0
Distributed Link Tracking Server TrkSvr Stopped Manual Share
Process c:\winnt\system32\services.exe Normal LocalSystem 0
Distributed Link Tracking Client TrkWks Stopped Manual Share
Process c:\winnt\system32\services.exe Normal LocalSystem 0
Uninterruptible Power Supply UPS Stopped Manual Own Process
c:\winnt\system32\ups.exe Normal LocalSystem 0
Utility Manager UtilMan Stopped Manual Own Process
c:\winnt\system32\utilman.exe Normal LocalSystem 0
Windows Time W32Time Stopped Manual Share Process
c:\winnt\system32\services.exe Normal LocalSystem 0
World Wide Web Publishing Service W3SVC Running Auto Share Process
c:\winnt\system32\inetrv\inetinfo.exe Normal LocalSystem
0

```

```

Windows Management Instrumentation WinMgmt Running Auto Own
Process c:\winnt\system32\wbem\winmgmt.exe Ignore LocalSystem
0
Windows Management Instrumentation Driver Extensions Wmi Running
Manual Share Process c:\winnt\system32\services.exe Normal
LocalSystem 0

```

```

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0000
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 1:25 PM
Value 0
Name: Adaptive_IFS
Type: REG_SZ
Data: 0
Value 1
Name: AdaptiveCarrierLoss
Type: REG_SZ
Data: 1
Value 2
Name: AdaptiveStalledInterrupts
Type: REG_SZ
Data: 1
Value 3
Name: AdaptiveTransmitMethod
Type: REG_SZ
Data: 1
Value 4
Name: BusType
Type: REG_SZ
Data: 5
Value 5
Name: Characteristics
Type: REG_DWORD
Data: 0x84
Value 6
Name: Coalesce
Type: REG_SZ
Data: 0
Value 7
Name: CoInstallFlag
Type: REG_DWORD
Data: 0x80000004
Value 8

```

Name:	ComponentId	Data:	003005158AF8
Type:	REG_SZ		
Data:	pci\ven_8086&dev_1229&rev_09		
Value 9		Value 19	
Name:	CPUSaver	Name:	InfPath
Type:	REG_SZ	Type:	REG_SZ
Data:	1536	Data:	oem4.inf
Value 10		Value 20	
Name:	DeviceVxDsPrefix	Name:	InfSection
Type:	REG_SZ	Type:	REG_SZ
Data:	e100b	Data:	D101SG.ndi
Value 11		Value 21	
Name:	DriverDate	Name:	InfSectionExt
Type:	REG_SZ	Type:	REG_SZ
Data:	1-10-2001	Data:	.NT
Value 12		Value 22	
Name:	DriverDateData	Name:	IPSecTunnelMode
Type:	REG_BINARY	Type:	REG_SZ
Data:	00000000 00 80 55 46 98 7a c0 01 - ..UF.zÀ.	Data:	1
Value 13		Value 23	
Name:	DriverDesc	Name:	LinkBasedLogin
Type:	REG_SZ	Type:	REG_SZ
Data:	Intel 8255x-based PCI Ethernet Adapter (10/100)	Data:	0
Value 14		Value 24	
Name:	DriverVersion	Name:	LogErrorMessages
Type:	REG_SZ	Type:	REG_SZ
Data:	5.40.11.0	Data:	1
Value 15		Value 25	
Name:	EnablePME	Name:	MatchingDeviceId
Type:	REG_SZ	Type:	REG_SZ
Data:	2	Data:	pci\ven_8086&dev_1229&rev_09
Value 16		Value 26	
Name:	EnablePowerDownOnLinkLoss	Name:	MaxNumSecAssoc
Type:	REG_SZ	Type:	REG_SZ
Data:	0	Data:	64
Value 17		Value 27	
Name:	FlowControlReceive	Name:	MWIEnable
Type:	REG_SZ	Type:	REG_SZ
Data:	0	Data:	0
Value 18		Value 28	
Name:	HardwareAddress	Name:	NetCfgInstanceId
Type:	REG_SZ	Type:	REG_SZ
		Data:	{940C64C1-6989-48A3-8BC2-A1D440A00EF8}
		Value 29	

Name: NumCoalesce
 Type: REG_SZ
 Data: 8

Value 30
 Name: NumRfd
 Type: REG_SZ
 Data: 32

Value 31
 Name: NumTcb
 Type: REG_SZ
 Data: 16

Value 32
 Name: Pcnic
 Type: REG_SZ
 Data: 1

Value 33
 Name: ProviderName
 Type: REG_SZ
 Data: Intel

Value 34
 Name: SpeedDuplex
 Type: REG_SZ
 Data: 0

Value 35
 Name: TaggingMode
 Type: REG_SZ
 Data: 0

Value 36
 Name: TaskOffload
 Type: REG_SZ
 Data: 1

Value 37
 Name: Threshold
 Type: REG_SZ
 Data: 12

Value 38
 Name: UcodeSW
 Type: REG_SZ
 Data: 0

Value 39
 Name: WakeOn
 Type: REG_SZ
 Data: 2147483890

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Linkage
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Export
 Type: REG_MULTI_SZ
 Data: \Device\{940C64C1-6989-48A3-8BC2-A1D440A00EF8}

Value 1
 Name: RootDevice
 Type: REG_MULTI_SZ
 Data: {940C64C1-6989-48A3-8BC2-A1D440A00EF8}

Value 2
 Name: UpperBind
 Type: REG_MULTI_SZ
 Data: Tcpip

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Service
 Type: REG_SZ
 Data: E100B

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\Interfaces
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: LowerRange
 Type: REG_SZ
 Data: ethernet

Value 1
 Name: UpperRange
 Type: REG_SZ
 Data: ndis5

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params
 Class Name: <NO CLASS>

Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\Adaptive_IFS
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Base
 Type: REG_SZ
 Data: 10

Value 1
 Name: Default
 Type: REG_SZ
 Data: 0

Value 2
 Name: Max
 Type: REG_SZ
 Data: 255

Value 3
 Name: Min
 Type: REG_SZ
 Data: 0

Value 4
 Name: ParamDesc
 Type: REG_SZ
 Data: Adaptive Inter-Frame Spacing

Value 5
 Name: Step
 Type: REG_SZ
 Data: 1

Value 6
 Name: Type
 Type: REG_SZ
 Data: int

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\Coalesce
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 0

Value 1
 Name: ParamDesc

Type: REG_SZ
 Data: PCI Bus Efficiency

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\Coalesce\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Disabled

Value 1
 Name: 1
 Type: REG_SZ
 Data: Enabled

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\EnablePME
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 2

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: Enable PME

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\EnablePME\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Disabled

Value 1
 Name: 1
 Type: REG_SZ
 Data: Enabled

Value 2
 Name: 2
 Type: REG_SZ
 Data: No Action

Value 3
 Name: 255
 Type: REG_SZ
 Data: Hardware Default

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\EnablePowerDownOnLinkLoss
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 0

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: Smart Power Down

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\EnablePowerDownOnLinkLoss\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Disabled

Value 1
 Name: 1
 Type: REG_SZ
 Data: Enabled

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\FlowControlReceive

Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 0

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: Respond to Flow Control

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\FlowControlReceive\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Off

Value 1
 Name: 1
 Type: REG_SZ
 Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\LinkBasedLogin
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 0

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: Adaptive Link Response

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\LinkBasedLogin\Enum
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: 0
Type: REG_SZ
Data: Off

Value 1
Name: 1
Type: REG_SZ
Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\MaxNumSecAssoc
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: Base
Type: REG_SZ
Data: 10

Value 1
Name: Default
Type: REG_SZ
Data: 64

Value 2
Name: Max
Type: REG_SZ
Data: 5000

Value 3
Name: Min
Type: REG_SZ
Data: 1

Value 4
Name: ParamDesc
Type: REG_SZ
Data: Security Associations

Value 5
Name: Step
Type: REG_SZ
Data: 1

Value 6
Name: Type
Type: REG_SZ
Data: int

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\NumCoalesce
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: Base
Type: REG_SZ
Data: 10

Value 1
Name: Default
Type: REG_SZ
Data: 8

Value 2
Name: Max
Type: REG_SZ
Data: 32

Value 3
Name: Min
Type: REG_SZ
Data: 1

Value 4
Name: ParamDesc
Type: REG_SZ
Data: Coalesce Buffers

Value 5
Name: Step
Type: REG_SZ
Data: 1

Value 6
Name: Type
Type: REG_SZ
Data: int

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\NumRfd
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: Base
Type: REG_SZ
Data: 10

Value 1
Name: Default

```

Type:          REG_SZ
Data:          32

Value 2
Name:          Max
Type:          REG_SZ
Data:          1024

Value 3
Name:          Min
Type:          REG_SZ
Data:          8

Value 4
Name:          ParamDesc
Type:          REG_SZ
Data:          Receive Buffers

Value 5
Name:          Step
Type:          REG_SZ
Data:          1

Value 6
Name:          Type
Type:          REG_SZ
Data:          int

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0000\Ndi\params\NumTcb
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          Base
Type:          REG_SZ
Data:          10

Value 1
Name:          Default
Type:          REG_SZ
Data:          16

Value 2
Name:          Max
Type:          REG_SZ
Data:          64

Value 3
Name:          Min
Type:          REG_SZ
Data:          8

```

```

Value 4
Name:          ParamDesc
Type:          REG_SZ
Data:          Transmit Control Blocks

Value 5
Name:          Step
Type:          REG_SZ
Data:          1

Value 6
Name:          Type
Type:          REG_SZ
Data:          int

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0000\Ndi\params\SpeedDuplex
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          default
Type:          REG_SZ
Data:          0

Value 1
Name:          ParamDesc
Type:          REG_SZ
Data:          Link Speed & Duplex

Value 2
Name:          type
Type:          REG_SZ
Data:          enum

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0000\Ndi\params\SpeedDuplex\enum
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          0
Type:          REG_SZ
Data:          Auto Detect

Value 1
Name:          1
Type:          REG_SZ
Data:          10Mbps/Half Duplex

Value 2
Name:          2
Type:          REG_SZ

```

Data: 10Mbps/Full Duplex

Value 3
 Name: 3
 Type: REG_SZ
 Data: 100Mbps/Half Duplex

Value 4
 Name: 4
 Type: REG_SZ
 Data: 100Mbps/Full Duplex

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\TaggingMode
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 0

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: QoS Packet Tagging

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\TaggingMode\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Disabled

Value 1
 Name: 1
 Type: REG_SZ
 Data: Enabled

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\TaskOffload
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0

Name: Default
 Type: REG_SZ
 Data: 1

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: Offloading

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\TaskOffload\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: None

Value 1
 Name: 1
 Type: REG_SZ
 Data: IP Security

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\Threshold
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Base
 Type: REG_SZ
 Data: 10

Value 1
 Name: Default
 Type: REG_SZ
 Data: 12

Value 2
 Name: Max
 Type: REG_SZ
 Data: 200

Value 3
 Name: Min
 Type: REG_SZ
 Data: 0

Value 4
Name: ParamDesc
Type: REG_SZ
Data: Adaptive Transmit Threshold

Value 5
Name: Step
Type: REG_SZ
Data: 1

Value 6
Name: Type
Type: REG_SZ
Data: int

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\UcodeSW
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: Default
Type: REG_SZ
Data: 0

Value 1
Name: ParamDesc
Type: REG_SZ
Data: Adaptive Technology

Value 2
Name: Type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\Ndi\params\UcodeSW\Enum
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: 0
Type: REG_SZ
Data: Off

Value 1
Name: 1
Type: REG_SZ
Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\Adaptive_IFS
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: MiniHelp
Type: REG_SZ
Data: Compensates for excessive Ethernet packet collisions.
Default = 1.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\Coalesce
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: MiniHelp
Type: REG_SZ
Data: Coalesces transmit packets into single buffer before sending them to network.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\EnablePME
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: MiniHelp
Type: REG_SZ
Data: Allows wake-up from APM power management when enabled. Disable shuts down LAN controller under ACPI

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\EnablePowerDownOnLinkLoss
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Removes adapter power when LAN cable disconnected.
 Recommended = Enabled.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\FlowControlReceive
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Pauses packet transmission on receipt of full flow control frame.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\LinkBasedLogin
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Enables Adaptive Link Response to check PHYLink status. Default = Disabled.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\MaxNumSecAssoc
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Simultaneous Security Associations that can be offloaded to the adapters co-processor.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\NumCoalesce
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Number of buffers available for transmits acceleration.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\NumRfd

Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Number of buffers used by the driver when copying data to the protocol memory. Recommended = 48

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\NumTcb
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Sets the number of control blocks available for adapter use. Recommended = 32.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\SpeedDuplex
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Sets link speed to 10/100 Mbps and duplex to half or full. Must coincide with switch port or no link will occur. Default = Auto Detect

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\TaggingMode
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Send and receive IEEE Tagged frames (802.3ac/802.1p/802.1Q).

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\TaskOffload
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Saves CPU cycles if set to correspond to the adapter type. Range: None, IP Security, Checksum.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\Threshold
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Sets number of bytes before adapter empties its FIFO buffer. Actual value is 8 times setting.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\NdiExt\params\UcodeSW
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: MiniHelp
 Type: REG_SZ
 Data: Enables/Disables the Adaptive Technology performance feature. Recommended value = ON.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\Params
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\Params\CPUSaver
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 1:25 PM
 Value 0
 Name: Default
 Type: REG_SZ
 Data: 1536

Value 1
 Name: ExposeLevel
 Type: REG_SZ
 Data: 2

Value 2
 Name: LeftLabel
 Type: REG_SZ
 Data: Adapter Bandwidth

Value 3
 Name: MiniHelp
 Type: REG_SZ
 Data: Sets optimal point of CPU/Adapter performance for this system. See help.

Value 4
 Name: ParamDesc
 Type: REG_SZ
 Data: Adaptive Performance Tuning

Value 5
 Name: RightLabel
 Type: REG_SZ
 Data: CPU Utilization

Value 6
 Name: Type
 Type: REG_SZ
 Data: slider

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\Params\CPUSaver\Values
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: 0
 Type: REG_SZ
 Data: 0

Value 1
 Name: 1
 Type: REG_SZ
 Data: 1

Value 2
 Name: 10
 Type: REG_SZ
 Data: 2560

Value 3
 Name: 11
 Type: REG_SZ
 Data: 2816

Value 4
 Name: 12
 Type: REG_SZ
 Data: 3072

Value 5
 Name: 13
 Type: REG_SZ
 Data: 3328

Value 6
 Name: 14
 Type: REG_SZ

Data: 3584

Value 7
 Name: 15
 Type: REG_SZ
 Data: 3840

Value 8
 Name: 16
 Type: REG_SZ
 Data: 4096

Value 9
 Name: 2
 Type: REG_SZ
 Data: 512

Value 10
 Name: 3
 Type: REG_SZ
 Data: 768

Value 11
 Name: 4
 Type: REG_SZ
 Data: 1024

Value 12
 Name: 5
 Type: REG_SZ
 Data: 1280

Value 13
 Name: 6
 Type: REG_SZ
 Data: 1536

Value 14
 Name: 7
 Type: REG_SZ
 Data: 1792

Value 15
 Name: 8
 Type: REG_SZ
 Data: 2048

Value 16
 Name: 9
 Type: REG_SZ
 Data: 2304

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\Params\NetworkAddress
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 1:25 PM

Value 0
 Name: Base
 Type: REG_SZ
 Data: 16

Value 1
 Name: Default
 Type: REG_SZ
 Data:

Value 2
 Name: ExposeLevel
 Type: REG_SZ
 Data: 2

Value 3
 Name: MiniHelp
 Type: REG_SZ
 Data: Allows you to change the network address.

Value 4
 Name: ParamDesc
 Type: REG_SZ
 Data: Locally Administered Address

Value 5
 Name: Type
 Type: REG_SZ
 Data: edit

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\Params\WakeOn
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: default
 Type: REG_SZ
 Data: 2147483890

Value 1
 Name: ExposeLevel
 Type: REG_SZ
 Data: 2

Value 2
 Name: MiniHelp
 Type: REG_SZ

Data: Determines how to Wake up the system (Link Change, Magic Packet, Pattern Matching, etc.).

Value 3
Name: ParamDesc
Type: REG_SZ
Data: Wake on Settings

Value 4
Name: type
Type: REG_SZ
Data: bitfield

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0000\PROSetNdi\Params\WakeOn\Enum
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: 1
Type: REG_SZ
Data: Wake on Link Change

Value 1
Name: 144
Type: REG_SZ
Data: Wake on NBT Query

Value 2
Name: 2
Type: REG_SZ
Data: Wake on Magic Packet

Value 3
Name: 2147483664
Type: REG_SZ
Data: Wake On Other Pattern

Value 4
Name: 4
Type: REG_SZ
Data: Wake on LAA

Value 5
Name: 48
Type: REG_SZ
Data: Wake on ARP

Value 6
Name: 80
Type: REG_SZ
Data: Wake on directed packet

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 1:25 PM

Value 0
Name: Adaptive_IFS
Type: REG_SZ
Data: 0

Value 1
Name: AdaptiveCarrierLoss
Type: REG_SZ
Data: 1

Value 2
Name: AdaptiveStalledInterrupts
Type: REG_SZ
Data: 1

Value 3
Name: AdaptiveTransmitMethod
Type: REG_SZ
Data: 1

Value 4
Name: BusType
Type: REG_SZ
Data: 5

Value 5
Name: Characteristics
Type: REG_DWORD
Data: 0x84

Value 6
Name: Coalesce
Type: REG_SZ
Data: 0

Value 7
Name: CoInstallFlag
Type: REG_DWORD
Data: 0x80000004

Value 8
Name: ComponentId
Type: REG_SZ
Data: pci\ven_8086&dev_1229&rev_09

Value 9
Name: CPUSaver
Type: REG_SZ

Data: 1536

Value 10
 Name: DeviceVxDsPrefix
 Type: REG_SZ
 Data: e100b

Value 11
 Name: DriverDate
 Type: REG_SZ
 Data: 1-10-2001

Value 12
 Name: DriverDateData
 Type: REG_BINARY
 Data: 00000000 00 80 55 46 98 7a c0 01 - ..UF.zÀ.

Value 13
 Name: DriverDesc
 Type: REG_SZ
 Data: Intel 8255x-based PCI Ethernet Adapter (10/100)

Value 14
 Name: DriverVersion
 Type: REG_SZ
 Data: 5.40.11.0

Value 15
 Name: EnablePME
 Type: REG_SZ
 Data: 2

Value 16
 Name: EnablePowerDownOnLinkLoss
 Type: REG_SZ
 Data: 0

Value 17
 Name: FlowControlReceive
 Type: REG_SZ
 Data: 0

Value 18
 Name: HardwareAddress
 Type: REG_SZ
 Data: 00300526D807

Value 19
 Name: InfPath
 Type: REG_SZ
 Data: oem4.inf

Value 20
 Name: InfSection
 Type: REG_SZ
 Data: D101SG.ndi

Value 21
 Name: InfSectionExt
 Type: REG_SZ
 Data: .NT

Value 22
 Name: IPsecTunnelMode
 Type: REG_SZ
 Data: 1

Value 23
 Name: LinkBasedLogin
 Type: REG_SZ
 Data: 0

Value 24
 Name: LogErrorMessage
 Type: REG_SZ
 Data: 1

Value 25
 Name: MatchingDeviceId
 Type: REG_SZ
 Data: pci\ven_8086&dev_1229&rev_09

Value 26
 Name: MaxNumSecAssoc
 Type: REG_SZ
 Data: 64

Value 27
 Name: MWIEnable
 Type: REG_SZ
 Data: 0

Value 28
 Name: NetCfgInstanceId
 Type: REG_SZ
 Data: {5A32B06F-0639-4600-9EA0-12CBF488ACDD}

Value 29
 Name: NumCoalesce
 Type: REG_SZ
 Data: 8

Value 30
 Name: NumRfd
 Type: REG_SZ

Data: 32

Value 31
 Name: NumTcb
 Type: REG_SZ
 Data: 16

Value 32
 Name: Pcnic
 Type: REG_SZ
 Data: 1

Value 33
 Name: ProviderName
 Type: REG_SZ
 Data: Intel

Value 34
 Name: SpeedDuplex
 Type: REG_SZ
 Data: 0

Value 35
 Name: TaggingMode
 Type: REG_SZ
 Data: 0

Value 36
 Name: TaskOffload
 Type: REG_SZ
 Data: 1

Value 37
 Name: Threshold
 Type: REG_SZ
 Data: 12

Value 38
 Name: UcodeSW
 Type: REG_SZ
 Data: 0

Value 39
 Name: WakeOn
 Type: REG_SZ
 Data: 2147483890

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Linkage
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0

Name: Export
 Type: REG_MULTI_SZ
 Data: \Device\{5A32B06F-0639-4600-9EA0-12CBF488ACDD}

Value 1
 Name: RootDevice
 Type: REG_MULTI_SZ
 Data: {5A32B06F-0639-4600-9EA0-12CBF488ACDD}

Value 2
 Name: UpperBind
 Type: REG_MULTI_SZ
 Data: Tcpiip

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: Service
 Type: REG_SZ
 Data: E100B

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\Interfaces
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0
 Name: LowerRange
 Type: REG_SZ
 Data: ethernet

Value 1
 Name: UpperRange
 Type: REG_SZ
 Data: ndis5

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\Adaptive_IFS
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM
 Value 0

```

Name:          Base
Type:          REG_SZ
Data:          10

Value 1
Name:          Default
Type:          REG_SZ
Data:          0

Value 2
Name:          Max
Type:          REG_SZ
Data:          255

Value 3
Name:          Min
Type:          REG_SZ
Data:          0

Value 4
Name:          ParamDesc
Type:          REG_SZ
Data:          Adaptive Inter-Frame Spacing

Value 5
Name:          Step
Type:          REG_SZ
Data:          1

Value 6
Name:          Type
Type:          REG_SZ
Data:          int

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006\Ndi\params\Coalesce
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          Default
Type:          REG_SZ
Data:          0

Value 1
Name:          ParamDesc
Type:          REG_SZ
Data:          PCI Bus Efficiency

Value 2
Name:          Type
Type:          REG_SZ
Data:          enum

```

```

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006\Ndi\params\Coalesce\Enum
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          0
Type:          REG_SZ
Data:          Disabled

Value 1
Name:          1
Type:          REG_SZ
Data:          Enabled

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006\Ndi\params\EnablePME
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          Default
Type:          REG_SZ
Data:          2

Value 1
Name:          ParamDesc
Type:          REG_SZ
Data:          Enable PME

Value 2
Name:          Type
Type:          REG_SZ
Data:          enum

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006\Ndi\params\EnablePME\Enum
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          0
Type:          REG_SZ
Data:          Disabled

Value 1
Name:          1
Type:          REG_SZ
Data:          Enabled

Value 2
Name:          2

```

Type: REG_SZ
Data: No Action

Value 3
Name: 255
Type: REG_SZ
Data: Hardware Default

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\EnablePowerDownOnLinkLoss
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: Default
Type: REG_SZ
Data: 0

Value 1
Name: ParamDesc
Type: REG_SZ
Data: Smart Power Down

Value 2
Name: Type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\EnablePowerDownOnLinkLoss\Enum
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: 0
Type: REG_SZ
Data: Disabled

Value 1
Name: 1
Type: REG_SZ
Data: Enabled

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\FlowControlReceive
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: Default
Type: REG_SZ
Data: 0

Value 1
Name: ParamDesc
Type: REG_SZ
Data: Respond to Flow Control

Value 2
Name: Type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\FlowControlReceive\Enum
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: 0
Type: REG_SZ
Data: Off

Value 1
Name: 1
Type: REG_SZ
Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\LinkBasedLogin
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: Default
Type: REG_SZ
Data: 0

Value 1
Name: ParamDesc
Type: REG_SZ
Data: Adaptive Link Response

Value 2
Name: Type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\LinkBasedLogin\Enum
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: 0
Type: REG_SZ

```

Data:          Off

Value 1
Name:          1
Type:          REG_SZ
Data:          On

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006\Ndi\params\MaxNumSecAssoc
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          Base
Type:          REG_SZ
Data:          10

Value 1
Name:          Default
Type:          REG_SZ
Data:          64

Value 2
Name:          Max
Type:          REG_SZ
Data:          5000

Value 3
Name:          Min
Type:          REG_SZ
Data:          1

Value 4
Name:          ParamDesc
Type:          REG_SZ
Data:          Security Associations

Value 5
Name:          Step
Type:          REG_SZ
Data:          1

Value 6
Name:          Type
Type:          REG_SZ
Data:          int

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006\Ndi\params\NumCoalesce
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0

```

```

Name:          Base
Type:          REG_SZ
Data:          10

Value 1
Name:          Default
Type:          REG_SZ
Data:          8

Value 2
Name:          Max
Type:          REG_SZ
Data:          32

Value 3
Name:          Min
Type:          REG_SZ
Data:          1

Value 4
Name:          ParamDesc
Type:          REG_SZ
Data:          Coalesce Buffers

Value 5
Name:          Step
Type:          REG_SZ
Data:          1

Value 6
Name:          Type
Type:          REG_SZ
Data:          int

Key Name:      SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-
11CE-BFC1-08002BE10318}\0006\Ndi\params\NumRfd
Class Name:    <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name:          Base
Type:          REG_SZ
Data:          10

Value 1
Name:          Default
Type:          REG_SZ
Data:          32

Value 2
Name:          Max
Type:          REG_SZ
Data:          1024

```

Value 3
 Name: Min
 Type: REG_SZ
 Data: 8

Value 4
 Name: ParamDesc
 Type: REG_SZ
 Data: Receive Buffers

Value 5
 Name: Step
 Type: REG_SZ
 Data: 1

Value 6
 Name: Type
 Type: REG_SZ
 Data: int

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\NumTcb
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Base
 Type: REG_SZ
 Data: 10

Value 1
 Name: Default
 Type: REG_SZ
 Data: 16

Value 2
 Name: Max
 Type: REG_SZ
 Data: 64

Value 3
 Name: Min
 Type: REG_SZ
 Data: 8

Value 4
 Name: ParamDesc
 Type: REG_SZ
 Data: Transmit Control Blocks

Value 5
 Name: Step

Type: REG_SZ
 Data: 1

Value 6
 Name: Type
 Type: REG_SZ
 Data: int

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\SpeedDuplex
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: default
 Type: REG_SZ
 Data: 0

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: Link Speed & Duplex

Value 2
 Name: type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\SpeedDuplex\enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Auto Detect

Value 1
 Name: 1
 Type: REG_SZ
 Data: 10Mbps/Half Duplex

Value 2
 Name: 2
 Type: REG_SZ
 Data: 10Mbps/Full Duplex

Value 3
 Name: 3
 Type: REG_SZ
 Data: 100Mbps/Half Duplex

Value 4
 Name: 4
 Type: REG_SZ
 Data: 100Mbps/Full Duplex

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\TaggingMode
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 0

Value 1
 Name: ParamDesc
 Type: REG_SZ
 Data: QoS Packet Tagging

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\TaggingMode\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Disabled

Value 1
 Name: 1
 Type: REG_SZ
 Data: Enabled

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\TaskOffload
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Default
 Type: REG_SZ
 Data: 1

Value 1
 Name: ParamDesc
 Type: REG_SZ

Data: Offloading

Value 2
 Name: Type
 Type: REG_SZ
 Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\TaskOffload\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 0
 Type: REG_SZ
 Data: None

Value 1
 Name: 1
 Type: REG_SZ
 Data: IP Security

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\Ndi\params\Threshold
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: Base
 Type: REG_SZ
 Data: 10

Value 1
 Name: Default
 Type: REG_SZ
 Data: 12

Value 2
 Name: Max
 Type: REG_SZ
 Data: 200

Value 3
 Name: Min
 Type: REG_SZ
 Data: 0

Value 4
 Name: ParamDesc
 Type: REG_SZ
 Data: Adaptive Transmit Threshold

Value 5

Name: Step
Type: REG_SZ
Data: 1

Value 6
Name: Type
Type: REG_SZ
Data: int

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\params\UcodeSW
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: Default
Type: REG_SZ
Data: 0

Value 1
Name: ParamDesc
Type: REG_SZ
Data: Adaptive Technology

Value 2
Name: Type
Type: REG_SZ
Data: enum

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\params\UcodeSW\Enum
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: 0
Type: REG_SZ
Data: Off

Value 1
Name: 1
Type: REG_SZ
Data: On

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt
Class Name: <NO CLASS>

Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\Adaptive_IFS
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Compensates for excessive Ethernet packet collisions.
Default = 1.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\Coalesce
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Coalesces transmit packets into single buffer before sending them to network.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\EnablePME
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Allows wake-up from APM power management when enabled. Disable shuts down LAN controller under ACPI

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\EnablePowerDownOnLinkLoss
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Removes adapter power when LAN cable disconnected.
Recommended = Enabled.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\FlowControlReceive
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Pauses packet transmission on receipt of full flow control frame.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\LinkBasedLogin
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Enables Adaptive Link Response to check PHYLink status. Default = Disabled.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\MaxNumSecAssoc
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Simultaneous Security Associations that can be offloaded to the adapters co-processor.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\NumCoalesce
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Number of buffers available for transmits acceleration.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\NumRfd
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Number of buffers used by the driver when copying data to the protocol memory. Recommended = 48

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\NumTcb
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Sets the number of control blocks available for adapter use. Recommended = 32.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\SpeedDuplex
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Sets link speed to 10/100 Mbps and duplex to half or full. Must coincide with switch port or no link will occur. Default = Auto Detect

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\TaggingMode
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Send and receive IEEE Tagged frames (802.3ac/802.1p/802.1Q).

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\TaskOffload
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp
Type: REG_SZ
Data: Saves CPU cycles if set to correspond to the adapter type. Range: None, IP Security, Checksum.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\Threshold
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
Name: MiniHelp

Type: REG_SZ
Data: Sets number of bytes before adapter empties its FIFO buffer. Actual value is 8 times setting.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\NdiExt\params\UcodeSW

Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: MiniHelp
Type: REG_SZ
Data: Enables/Disables the Adaptive Technology performance feature. Recommended value = ON.

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\Params

Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\Params\CPUSaver

Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 1:25 PM

Value 0
Name: Default
Type: REG_SZ
Data: 1536

Value 1
Name: ExposeLevel
Type: REG_SZ
Data: 2

Value 2
Name: LeftLabel
Type: REG_SZ
Data: Adapter Bandwidth

Value 3
Name: MiniHelp
Type: REG_SZ
Data: Sets optimal point of CPU/Adapter performance for this system. See help.

Value 4
Name: ParamDesc
Type: REG_SZ
Data: Adaptive Performance Tuning

Value 5
Name: RightLabel

Type: REG_SZ
Data: CPU Utilization

Value 6
Name: Type
Type: REG_SZ
Data: slider

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\Params\CPUSaver\Values

Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: 0
Type: REG_SZ
Data: 0

Value 1
Name: 1
Type: REG_SZ
Data: 1

Value 2
Name: 10
Type: REG_SZ
Data: 2560

Value 3
Name: 11
Type: REG_SZ
Data: 2816

Value 4
Name: 12
Type: REG_SZ
Data: 3072

Value 5
Name: 13
Type: REG_SZ
Data: 3328

Value 6
Name: 14
Type: REG_SZ
Data: 3584

Value 7
Name: 15
Type: REG_SZ
Data: 3840

Value 8
 Name: 16
 Type: REG_SZ
 Data: 4096

Value 9
 Name: 2
 Type: REG_SZ
 Data: 512

Value 10
 Name: 3
 Type: REG_SZ
 Data: 768

Value 11
 Name: 4
 Type: REG_SZ
 Data: 1024

Value 12
 Name: 5
 Type: REG_SZ
 Data: 1280

Value 13
 Name: 6
 Type: REG_SZ
 Data: 1536

Value 14
 Name: 7
 Type: REG_SZ
 Data: 1792

Value 15
 Name: 8
 Type: REG_SZ
 Data: 2048

Value 16
 Name: 9
 Type: REG_SZ
 Data: 2304

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\Params\NetworkAddress
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 1:25 PM

Value 0
 Name: Base
 Type: REG_SZ

Data: 16

Value 1
 Name: Default
 Type: REG_SZ
 Data:

Value 2
 Name: ExposeLevel
 Type: REG_SZ
 Data: 2

Value 3
 Name: MiniHelp
 Type: REG_SZ
 Data: Allows you to change the network address.

Value 4
 Name: ParamDesc
 Type: REG_SZ
 Data: Locally Administered Address

Value 5
 Name: Type
 Type: REG_SZ
 Data: edit

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\Params\WakeOn
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: default
 Type: REG_SZ
 Data: 2147483890

Value 1
 Name: ExposeLevel
 Type: REG_SZ
 Data: 2

Value 2
 Name: MiniHelp
 Type: REG_SZ
 Data: Determines how to Wake up the system (Link Change, Magic Packet, Pattern Matching, etc.).

Value 3
 Name: ParamDesc
 Type: REG_SZ
 Data: Wake on Settings

Value 4
 Name: type
 Type: REG_SZ
 Data: bitfield

Key Name: SYSTEM\CurrentControlSet\Control\Class\{4D36E972-E325-11CE-BFC1-08002BE10318}\0006\PROSetNdi\Params\WakeOn\Enum
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 12:50 PM

Value 0
 Name: 1
 Type: REG_SZ
 Data: Wake on Link Change

Value 1
 Name: 144
 Type: REG_SZ
 Data: Wake on NBT Query

Value 2
 Name: 2
 Type: REG_SZ
 Data: Wake on Magic Packet

Value 3
 Name: 2147483664
 Type: REG_SZ
 Data: Wake On Other Pattern

Value 4
 Name: 4
 Type: REG_SZ
 Data: Wake on LAA

Value 5
 Name: 48
 Type: REG_SZ
 Data: Wake on ARP

Value 6
 Name: 80
 Type: REG_SZ
 Data: Wake on directed packet

Key Name: SYSTEM\CurrentControlSet\Services\E100B
 Class Name: <NO CLASS>
 Last Write Time: 2/13/2001 - 8:26 AM

Value 0
 Name: DisplayName
 Type: REG_SZ
 Data: Intel(R) PRO Adapter Driver

Value 1
 Name: ErrorControl
 Type: REG_DWORD
 Data: 0x1

Value 2
 Name: Group
 Type: REG_SZ
 Data: NDIS

Value 3
 Name: ImagePath
 Type: REG_EXPAND_SZ
 Data: System32\DRIVERS\e100bnt5.sys

Value 4
 Name: Start
 Type: REG_DWORD
 Data: 0x3

Value 5
 Name: Tag
 Type: REG_DWORD
 Data: 0xa

Value 6
 Name: TextModeFlags
 Type: REG_DWORD
 Data: 0x1

Value 7
 Name: Type
 Type: REG_DWORD
 Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\E100B\Enum
 Class Name: <NO CLASS>
 Last Write Time: 3/4/2002 - 10:17 AM

Value 0
 Name: 0
 Type: REG_SZ
 Data: PCI\VEN_8086&DEV_1229&SUBSYS_004B110A&REV_09\3&13c0b0c5&0&50

Value 1
 Name: 1
 Type: REG_SZ
 Data: PCI\VEN_8086&DEV_1229&SUBSYS_004B110A&REV_09\3&13c0b0c5&0&58

Value 2

```

Name:          Count
Type:          REG_DWORD
Data:          0x2

Value 3
Name:          NextInstance
Type:          REG_DWORD
Data:          0x2

Key Name:      SYSTEM\CurrentControlSet\Services\E100B\Security
Class Name:    <NO CLASS>
Last Write Time: 2/12/2001 - 4:30 PM
Value 0
Name:          Security
Type:          REG_BINARY
Data:          00000000 01 00 14 80 a0 00 00 00 - ac 00 00 00 14 00 00 00
.....
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00
0.....
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00
ÿ.....
00000030 02 00 70 00 04 00 00 00 - 00 00 18 00 fd 01 02 00
..p.....ÿ...
00000040 01 01 00 00 00 00 00 05 - 12 00 00 00 20 02 00 00
.....
00000050 00 00 1c 00 ff 01 0f 00 - 01 02 00 00 00 00 00 05
...ÿ.....
00000060 20 00 00 00 20 02 00 00 - 74 00 00 00 00 00 18 00  ...
...t.....
00000070 8d 01 02 00 01 01 00 00 - 00 00 00 05 0b 00 00 00
.....
00000080 20 02 00 00 00 00 1c 00 - fd 01 02 00 01 02 00 00
.....ÿ.....
00000090 00 00 00 05 20 00 00 00 - 23 02 00 00 74 00 00 00  ....
...#...t...
000000a0 01 01 00 00 00 00 00 05 - 12 00 00 00 01 01 00 00
.....
000000b0 00 00 00 05 12 00 00 00 - .....

Key Name:      SOFTWARE\Microsoft\MSSQLServer
Class Name:    <NO CLASS>
Last Write Time: 2/13/2001 - 9:00 AM

Key Name:      SOFTWARE\Microsoft\MSSQLServer\Client
Class Name:    <NO CLASS>
Last Write Time: 3/12/2001 - 2:20 PM
Value 0
Name:          SharedMemoryOn
Type:          REG_DWORD
Data:          0

```

```

Key Name:      SOFTWARE\Microsoft\MSSQLServer\Client\ConnectTo
Class Name:    <NO CLASS>
Last Write Time: 3/7/2001 - 9:39 AM

Key Name:      SOFTWARE\Microsoft\MSSQLServer\Client\DB-Lib
Class Name:    <NO CLASS>
Last Write Time: 5/17/2001 - 8:31 AM
Value 0
Name:          AutoAnsiToOem
Type:          REG_SZ
Data:          OFF

Value 1
Name:          UseIntlSettings
Type:          REG_SZ
Data:          ON

Key Name:      SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib
Class Name:    <NO CLASS>
Last Write Time: 3/12/2001 - 2:20 PM
Value 0
Name:          Encrypt
Type:          REG_DWORD
Data:          0

Value 1
Name:          ProtocolOrder
Type:          REG_MULTI_SZ
Data:          tcp
np

Key Name:      SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib\LastConnect
Class Name:    <NO CLASS>
Last Write Time: 3/1/2002 - 10:45 AM
Value 0
Name:          H250
Type:          REG_SZ
Data:          369229832:tcp:H250,1433

Value 1
Name:          H400
Type:          REG_SZ
Data:          2113994760:tcp:H400,1433

Value 2
Name:          r450

```

Type: REG_SZ
Data: 369229832:tcp:r450,1433

Key Name:
SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib\Np
Class Name: <NO CLASS>
Last Write Time: 2/13/2001 - 9:02 AM
Value 0
Name: DefaultPipe
Type: REG_SZ
Data: sql\query

Key Name:
SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib\Tcp
Class Name: <NO CLASS>
Last Write Time: 2/13/2001 - 9:02 AM
Value 0
Name: DefaultPort
Type: REG_DWORD
Data: 0x599

Key Name:
SOFTWARE\Microsoft\MSSQLServer\Client\SuperSocketNetLib\VIA
Class Name: <NO CLASS>
Last Write Time: 2/13/2001 - 9:00 AM
Value 0
Name: DefaultClientNIC
Type: REG_SZ
Data: 0

Value 1
Name: DefaultServerPort
Type: REG_SZ
Data: 0:1433

Value 2
Name: RecognizedVendors
Type: REG_SZ
Data: Giganet, ServerNet II

Value 3
Name: Vendor
Type: REG_SZ
Data:

Key Name: SOFTWARE\Microsoft\MSSQLServer\Client\TDS
Class Name: <NO CLASS>
Last Write Time: 2/20/2002 - 1:35 PM
Value 0

Name: h250
Type: REG_SZ
Data: 7.0

Value 1
Name: h400
Type: REG_SZ
Data: 7.0

Value 2
Name: r450
Type: REG_SZ
Data: 7.0

Key Name: SYSTEM\CurrentControlSet\Services\InetInfo
Class Name: <NO CLASS>
Last Write Time: 2/12/2001 - 3:45 PM

Key Name: SYSTEM\CurrentControlSet\Services\InetInfo\Parameters
Class Name: <NO CLASS>
Last Write Time: 2/26/2002 - 9:20 AM
Value 0
Name: DispatchEntries
Type: REG_MULTI_SZ
Data: LDAPSVC
SMTPSVC

Value 1
Name: ListenBackLog
Type: REG_DWORD
Data: 0x2710

Value 2
Name: PoolThreadLimit
Type: REG_DWORD
Data: 0x200

Value 3
Name: ThreadTimeout
Type: REG_DWORD
Data: 0x15180

Key Name: SYSTEM\CurrentControlSet\Services\InetInfo\Performance
Class Name: <NO CLASS>
Last Write Time: 3/4/2002 - 10:17 AM
Value 0
Name: Close
Type: REG_SZ
Data: CloseINFOPerformanceData

```

Value 1
  Name:      Collect
  Type:      REG_SZ
  Data:      CollectINFOPerformanceData

Value 2
  Name:      First Counter
  Type:      REG_DWORD
  Data:      0x802

Value 3
  Name:      First Help
  Type:      REG_DWORD
  Data:      0x803

Value 4
  Name:      Last Counter
  Type:      REG_DWORD
  Data:      0x842

Value 5
  Name:      Last Help
  Type:      REG_DWORD
  Data:      0x843

Value 6
  Name:      Library
  Type:      REG_SZ
  Data:      infoctrs.dll

Value 7
  Name:      Library Validation Code
  Type:      REG_BINARY
  Data:      00000000 7e 16 f0 b4 0a 95 c0 01 - 10 25 00 00 00 00 00 00
  ~.ð´..Ä..%.....

Value 8
  Name:      Open
  Type:      REG_SZ
  Data:      OpenINFOPerformanceData

Value 9
  Name:      WbemAdapFileSize
  Type:      REG_DWORD
  Data:      0x2510

Value 10
  Name:      WbemAdapFileTime
  Type:      REG_BINARY
  Data:      00000000 00 9b 1a af 81 d4 c0 01 - ...-.ÔÀ.

```

```

Value 11
  Name:      WbemAdapStatus
  Type:      REG_DWORD
  Data:      0

Key Name:    SYSTEM\CurrentControlSet\Services\Tcpip
Class Name:  Class
Last Write Time: 2/12/2001 - 4:40 PM
Value 0
  Name:      Description
  Type:      REG_SZ
  Data:      TCP/IP Protocol Driver

Value 1
  Name:      DisplayName
  Type:      REG_SZ
  Data:      TCP/IP Protocol Driver

Value 2
  Name:      ErrorControl
  Type:      REG_DWORD
  Data:      0x1

Value 3
  Name:      Group
  Type:      REG_SZ
  Data:      PNP_TDI

Value 4
  Name:      ImagePath
  Type:      REG_EXPAND_SZ
  Data:      System32\DRIVERS\tcpip.sys

Value 5
  Name:      Start
  Type:      REG_DWORD
  Data:      0x1

Value 6
  Name:      Tag
  Type:      REG_DWORD
  Data:      0x4

Value 7
  Name:      Type
  Type:      REG_DWORD
  Data:      0x1

Key Name:    SYSTEM\CurrentControlSet\Services\Tcpip\Enum
Class Name:  <NO CLASS>
Last Write Time: 3/4/2002 - 10:17 AM

```

Value 0
Name: 0
Type: REG_SZ
Data: Root\LEGACY_TCPIP\0000

Value 1
Name: Count
Type: REG_DWORD
Data: 0x1

Value 2
Name: NextInstance
Type: REG_DWORD
Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\Tcpip\Linkage
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM

Value 0
Name: Bind
Type: REG_MULTI_SZ
Data: \Device\{5A32B06F-0639-4600-9EA0-12CBF488ACDD}
\Device\{940C64C1-6989-48A3-8BC2-A1D440A00EF8}
\Device\NdisWanIp

Value 1
Name: Export
Type: REG_MULTI_SZ
Data: \Device\Tcpip_{5A32B06F-0639-4600-9EA0-12CBF488ACDD}
\Device\Tcpip_{940C64C1-6989-48A3-8BC2-A1D440A00EF8}
\Device\Tcpip_{CA92CE14-2FC2-4FF3-B680-1F7DF9594EAF}
\Device\Tcpip_{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}

Value 2
Name: Route
Type: REG_MULTI_SZ
Data: "{5A32B06F-0639-4600-9EA0-12CBF488ACDD}"
"{940C64C1-6989-48A3-8BC2-A1D440A00EF8}"
"NdisWanIp"

Key Name: SYSTEM\CurrentControlSet\Services\Tcpip\Parameters
Class Name: Class
Last Write Time: 2/25/2002 - 12:56 PM

Value 0
Name: AllowUnqualifiedQuery
Type: REG_DWORD
Data: 0

Value 1
Name: DataBasePath
Type: REG_EXPAND_SZ
Data: %SystemRoot%\System32\drivers\etc

Value 2
Name: DeadGWDetectDefault
Type: REG_DWORD
Data: 0x1

Value 3
Name: Domain
Type: REG_SZ
Data:

Value 4
Name: DontAddDefaultGatewayDefault
Type: REG_DWORD
Data: 0

Value 5
Name: EnableICMPRedirect
Type: REG_DWORD
Data: 0x1

Value 6
Name: EnableSecurityFilters
Type: REG_DWORD
Data: 0

Value 7
Name: ForwardBroadcasts
Type: REG_DWORD
Data: 0

Value 8
Name: Hostname
Type: REG_SZ
Data: L200CL1

Value 9
Name: IPEnableRouter
Type: REG_DWORD
Data: 0

Value 10
Name: MaxUserPort
Type: REG_DWORD
Data: 0xffff

Value 11
Name: NameServer
Type: REG_SZ

```

Data:
Value 12
  Name:      NV Hostname
  Type:      REG_SZ
  Data:      L200CL1
Value 13
  Name:      PrioritizeRecordData
  Type:      REG_DWORD
  Data:      0x1
Value 14
  Name:      SearchList
  Type:      REG_SZ
  Data:
Value 15
  Name:      UseDomainNameDevolution
  Type:      REG_DWORD
  Data:      0

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters
Class Name:      <NO CLASS>
Last Write Time: 2/12/2001 - 4:40 PM

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters\NdisWanIp
Class Name:      <NO CLASS>
Last Write Time: 2/12/2001 - 4:41 PM
Value 0
  Name:      IpConfig
  Type:      REG_MULTI_SZ
  Data:      Tcpip\Parameters\Interfaces\{CA92CE14-2FC2-4FF3-B680-
1F7DF9594EAF}
          Tcpip\Parameters\Interfaces\{FD73BFE5-0643-4705-9572-
5E3D92E4F8AD}
Value 1
  Name:      IpInterfaces
  Type:      REG_BINARY
  Data:      00000000 14 ce 92 ca c2 2f f3 4f - b6 80 1f 7d f9 59 4e af
          .f.ÊÂ/60¶..}ùYN
          00000010 e5 bf 73 fd 43 06 05 47 - 95 72 5e 3d 92 e4 f8 ad
          à¿sýC..G.r^=.äø-
Value 2
  Name:      LLInterface
  Type:      REG_SZ

```

```

Data:      WANARP
Value 3
  Name:      NumInterfaces
  Type:      REG_DWORD
  Data:      0x2

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters\{5A32B06F-
0639-4600-9EA0-12CBF488ACDD}
Class Name:      <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
  Name:      IpConfig
  Type:      REG_MULTI_SZ
  Data:      Tcpip\Parameters\Interfaces\{5A32B06F-0639-4600-9EA0-
12CBF488ACDD}

Value 1
  Name:      LLInterface
  Type:      REG_SZ
  Data:

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Adapters\{940C64C1-
6989-48A3-8BC2-A1D440A00EF8}
Class Name:      <NO CLASS>
Last Write Time: 2/25/2002 - 12:50 PM
Value 0
  Name:      IpConfig
  Type:      REG_MULTI_SZ
  Data:      Tcpip\Parameters\Interfaces\{940C64C1-6989-48A3-8BC2-
A1D440A00EF8}

Value 1
  Name:      LLInterface
  Type:      REG_SZ
  Data:

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\DNSRegisteredAdapters
Class Name:      DynDnsRootClass
Last Write Time: 2/12/2001 - 4:40 PM

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces
Class Name:      <NO CLASS>
Last Write Time: 2/12/2001 - 4:40 PM

```

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{5A32B06F-0639-4600-9EA0-12CBF488ACDD}
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 1:21 PM

Value 0
Name: DefaultGateway
Type: REG_MULTI_SZ
Data:

Value 1
Name: DefaultGatewayMetric
Type: REG_MULTI_SZ
Data:

Value 2
Name: DisableDynamicUpdate
Type: REG_DWORD
Data: 0x1

Value 3
Name: Domain
Type: REG_SZ
Data:

Value 4
Name: EnableAdapterDomainNameRegistration
Type: REG_DWORD
Data: 0

Value 5
Name: EnableDeadGWDetect
Type: REG_DWORD
Data: 0x1

Value 6
Name: EnableDHCP
Type: REG_DWORD
Data: 0

Value 7
Name: InterfaceMetric
Type: REG_DWORD
Data: 0x1

Value 8
Name: IPAddress
Type: REG_MULTI_SZ
Data: 129.103.211.1

Value 9

Name: NameServer
Type: REG_SZ
Data:

Value 10
Name: NTEContextList
Type: REG_MULTI_SZ
Data: 0x00000002

Value 11
Name: RawIPAllowedProtocols
Type: REG_MULTI_SZ
Data: 0

Value 12
Name: SubnetMask
Type: REG_MULTI_SZ
Data: 255.255.255.0

Value 13
Name: TCPAllowedPorts
Type: REG_MULTI_SZ
Data: 0

Value 14
Name: UDPAllowedPorts
Type: REG_MULTI_SZ
Data: 0

Value 15
Name: UseZeroBroadcast
Type: REG_DWORD
Data: 0

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{940C64C1-6989-48A3-8BC2-A1D440A00EF8}
Class Name: <NO CLASS>
Last Write Time: 2/25/2002 - 1:20 PM

Value 0
Name: DefaultGateway
Type: REG_MULTI_SZ
Data:

Value 1
Name: DefaultGatewayMetric
Type: REG_MULTI_SZ

Data:			
Value 2	Name:	DisableDynamicUpdate	Value 12
	Type:	REG_DWORD	Name:
	Data:	0x1	Type:
			Data:
Value 3	Name:	Domain	SubnetMask
	Type:	REG_SZ	REG_MULTI_SZ
	Data:		255.255.255.0
Value 4	Name:	EnableAdapterDomainNameRegistration	Value 13
	Type:	REG_DWORD	Name:
	Data:	0	Type:
Value 5	Name:	EnableDeadGWDetect	Data:
	Type:	REG_DWORD	0
	Data:	0x1	Value 14
Value 6	Name:	EnabledHCP	Name:
	Type:	REG_DWORD	Type:
	Data:	0	Data:
Value 7	Name:	InterfaceMetric	UDPAllowedPorts
	Type:	REG_DWORD	REG_MULTI_SZ
	Data:	0x1	0
Value 8	Name:	IPAddress	Value 15
	Type:	REG_MULTI_SZ	Name:
	Data:	129.103.181.211	Type:
Value 9	Name:	NameServer	Data:
	Type:	REG_SZ	0
	Data:		Key Name:
Value 10	Name:	NTEContextList	SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{CA92CE14-
	Type:	REG_MULTI_SZ	2FC2-4FF3-B680-1F7DF9594EAF}
	Data:	0x00000003	Class Name: <NO CLASS>
Value 11	Name:	RawIPAllowedProtocols	Last Write Time: 2/12/2001 - 4:41 PM
	Type:	REG_MULTI_SZ	Value 0
	Data:	0	Name:
			Type:
			Data:
			DefaultGateway
			REG_MULTI_SZ
			Value 1
			Name:
			Type:
			Data:
			0
			Value 2
			Name:
			Type:
			Data:
			0x1
			Value 3
			Name:
			Type:
			Data:
			0
			Value 4
			Name:
			IPAddress

Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 5
Name: SubnetMask
Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 6
Name: UseZeroBroadcast
Type: REG_DWORD
Data: 0

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Interfaces\{FD73BFE5-0643-4705-9572-5E3D92E4F8AD}
Class Name: <NO CLASS>
Last Write Time: 2/12/2001 - 4:41 PM

Value 0
Name: DefaultGateway
Type: REG_MULTI_SZ
Data:

Value 1
Name: DontAddDefaultGateway
Type: REG_DWORD
Data: 0

Value 2
Name: EnableDeadGWDetect
Type: REG_DWORD
Data: 0x1

Value 3
Name: EnableDHCP
Type: REG_DWORD
Data: 0

Value 4
Name: IPAddress
Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 5
Name: SubnetMask
Type: REG_MULTI_SZ
Data: 0.0.0.0

Value 6
Name: UseZeroBroadcast
Type: REG_DWORD
Data: 0

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\PersistentRoutes
Class Name: <NO CLASS>
Last Write Time: 2/12/2001 - 4:40 PM

Key Name:
SYSTEM\CurrentControlSet\Services\Tcpip\Parameters\Winsock
Class Name: <NO CLASS>
Last Write Time: 2/12/2001 - 4:40 PM

Value 0
Name: HelperDllName
Type: REG_EXPAND_SZ
Data: %SystemRoot%\System32\wshtcpip.dll

Value 1
Name: Mapping
Type: REG_BINARY
Data:
00000000 0b 00 00 00 03 00 00 00 - 02 00 00 00 01 00 00 00
.....
00000010 06 00 00 00 02 00 00 00 - 01 00 00 00 00 00 00 00
.....
00000020 02 00 00 00 00 00 00 00 - 06 00 00 00 00 00 00 00
.....
00000030 00 00 00 00 06 00 00 00 - 00 00 00 00 01 00 00 00
.....
00000040 06 00 00 00 02 00 00 00 - 02 00 00 00 11 00 00 00
.....
00000050 02 00 00 00 02 00 00 00 - 00 00 00 00 02 00 00 00
.....
00000060 00 00 00 00 11 00 00 00 - 00 00 00 00 00 00 00 00
.....
00000070 11 00 00 00 00 00 00 00 - 02 00 00 00 11 00 00 00
.....
00000080 02 00 00 00 03 00 00 00 - 00 00 00 00
.....

Value 2
Name: MaxSockAddrLength
Type: REG_DWORD
Data: 0x10

Value 3
Name: MinSockAddrLength
Type: REG_DWORD
Data: 0x10

Value 5
 Name: NetbtPriority
 Type: REG_DWORD
 Data: 0x7d1

Value 6
 Name: ProviderPath
 Type: REG_EXPAND_SZ
 Data: %SystemRoot%\System32\wsock32.dll

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC
 Class Name: <NO CLASS>
 Last Write Time: 2/25/2002 - 8:42 AM

Value 0
 Name: DependOnGroup
 Type: REG_MULTI_SZ
 Data:

Value 1
 Name: DependOnService
 Type: REG_MULTI_SZ
 Data: IISADMIN

Value 2
 Name: Description
 Type: REG_SZ
 Data: Provides Web connectivity and administration through the Internet Information Services snap-in.

Value 3
 Name: DisplayName
 Type: REG_SZ
 Data: World Wide Web Publishing Service

Value 4
 Name: ErrorControl
 Type: REG_DWORD
 Data: 0x1

Value 5
 Name: ImagePath
 Type: REG_EXPAND_SZ
 Data: C:\WINNT\System32\inet_srv\inetinfo.exe

Value 6
 Name: ObjectName
 Type: REG_SZ
 Data: LocalSystem

Value 7

Name: Start
 Type: REG_DWORD
 Data: 0x2

Value 8
 Name: Type
 Type: REG_DWORD
 Data: 0x20

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\ASP
 Class Name: <NO CLASS>
 Last Write Time: 2/12/2001 - 3:46 PM

Value 0
 Name: NOTE
 Type: REG_SZ
 Data: This is for backward compatibility only.

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\ASP\Parameters
 Class Name: <NO CLASS>
 Last Write Time: 2/12/2001 - 3:46 PM

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\Enum
 Class Name: <NO CLASS>
 Last Write Time: 3/4/2002 - 10:17 AM

Value 0
 Name: 0
 Type: REG_SZ
 Data: Root\LEGACY_W3SVC\0000

Value 1
 Name: Count
 Type: REG_DWORD
 Data: 0x1

Value 2
 Name: NextInstance
 Type: REG_DWORD
 Data: 0x1

Key Name: SYSTEM\CurrentControlSet\Services\W3SVC\Parameters
 Class Name: <NO CLASS>
 Last Write Time: 3/2/2001 - 1:38 PM

Value 0
 Name: AcceptExOutstanding
 Type: REG_DWORD
 Data: 0x28

Value 1
 Name: AccessDeniedMessage
 Type: REG_SZ

Data: Error: Access is Denied.

Value 2
 Name: CertMapList
 Type: REG_SZ
 Data: C:\WINNT\System32\inet_srv\iisrmap.dll

Value 3
 Name: Filter DLLs
 Type: REG_SZ
 Data:

Value 4
 Name: InstallPath
 Type: REG_SZ
 Data: C:\WINNT\System32\inet_srv

Value 5
 Name: LogFileDirectory
 Type: REG_SZ
 Data: C:\WINNT\System32\LogFiles

Value 6
 Name: MajorVersion
 Type: REG_DWORD
 Data: 0x5

Value 7
 Name: MinorVersion
 Type: REG_DWORD
 Data: 0

Key Name:
 SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\ADCLaunch
 Class Name: <NO CLASS>
 Last Write Time: 2/12/2001 - 3:47 PM

Key Name:
 SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\ADCLaunch\AdvancedData
 Factory
 Class Name: <NO CLASS>
 Last Write Time: 2/12/2001 - 3:47 PM

Key Name:
 SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\ADCLaunch\RDSSTa
 Factory
 Class Name: <NO CLASS>
 Last Write Time: 2/12/2001 - 3:47 PM

Key Name:
 SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\Script Map
 Class Name: <NO CLASS>

Last Write Time: 2/12/2001 - 3:57 PM

Key Name:
 SYSTEM\CurrentControlSet\Services\W3SVC\Parameters\Virtual Roots
 Class Name: <NO CLASS>
 Last Write Time: 2/13/2001 - 8:46 AM

Value 0
 Name: /
 Type: REG_SZ
 Data: c:\inetpub\wwwroot,,205

Value 1
 Name: /IISAdmin
 Type: REG_SZ
 Data: C:\WINNT\System32\inet_srv\iisadmin,,201

Value 2
 Name: /IISHelp
 Type: REG_SZ
 Data: c:\winnt\help\iishelp,,201

Value 3
 Name: /IISSamples
 Type: REG_SZ
 Data: c:\inetpub\iissamples,,201

Value 4
 Name: /MSADC
 Type: REG_SZ
 Data: c:\program files\common files\system\msadc,,205

Value 5
 Name: /Printers
 Type: REG_SZ
 Data: C:\WINNT\web\printers,,201

Value 6
 Name: /Scripts
 Type: REG_SZ
 Data: c:\inetpub\scripts,,204

Key Name:
 SYSTEM\CurrentControlSet\Services\W3SVC\Performance
 Class Name: <NO CLASS>
 Last Write Time: 3/4/2002 - 10:17 AM

Value 0
 Name: Close
 Type: REG_SZ
 Data: CloseW3PerformanceData

Value 1
 Name: Collect
 Type: REG_SZ

```

Data:          CollectW3PerformanceData

Value 2
Name:          First Counter
Type:          REG_DWORD
Data:          0x844

Value 3
Name:          First Help
Type:          REG_DWORD
Data:          0x845

Value 4
Name:          Last Counter
Type:          REG_DWORD
Data:          0x8e6

Value 5
Name:          Last Help
Type:          REG_DWORD
Data:          0x8e7

Value 6
Name:          Library
Type:          REG_SZ
Data:          w3ctrs.dll

Value 7
Name:          Library Validation Code
Type:          REG_BINARY
Data:          00000000 e0 81 84 b7 0a 95 c0 01 - 10 3d 00 00 00 00 00 00
à.....Ä.=.....

Value 8
Name:          Open
Type:          REG_SZ
Data:          OpenW3PerformanceData

Value 9
Name:          WbemAdapFileSize
Type:          REG_DWORD
Data:          0x1d10

Value 10
Name:          WbemAdapFileTime
Type:          REG_BINARY
Data:          00000000 00 9b 1a af 81 d4 c0 01 - ...-.ôÄ.

Value 11
Name:          WbemAdapStatus
Type:          REG_DWORD

```

```

Data:          0

Key Name:      SYSTEM\CurrentControlSet\Services\W3SVC\Security
Class Name:    <NO CLASS>
Last Write Time: 2/12/2001 - 3:46 PM
Value 0
Name:          Security
Type:          REG_BINARY
Data:          00000000 01 00 14 80 a0 00 00 00 - ac 00 00 00 14 00 00 00
.....7.....
00000010 30 00 00 00 02 00 1c 00 - 01 00 00 00 02 80 14 00
0.....
00000020 ff 01 0f 00 01 01 00 00 - 00 00 00 01 00 00 00 00
ÿ.....
00000030 02 00 70 00 04 00 00 00 - 00 00 18 00 fd 01 02 00
..P.....ÿ...
00000040 01 01 00 00 00 00 00 05 - 12 00 00 00 74 00 6f 00
.....t.o.
00000050 00 00 1c 00 ff 01 0f 00 - 01 02 00 00 00 00 00 05
...ÿ.....
00000060 20 00 00 00 20 02 00 00 - 72 00 73 00 00 00 18 00 ...
...r.s.....
00000070 8d 01 02 00 01 01 00 00 - 00 00 00 05 0b 00 00 00
.....
00000080 20 02 00 00 00 00 1c 00 - fd 01 02 00 01 02 00 00
.....ÿ.....
00000090 00 00 00 05 20 00 00 00 - 23 02 00 00 72 00 73 00 ....
...#...r.s.
000000a0 01 01 00 00 00 00 00 05 - 12 00 00 00 01 01 00 00
.....
000000b0 00 00 00 05 12 00 00 00 - .....

Key Name:      SOFTWARE\Microsoft\TPCC
Class Name:    <NO CLASS>
Last Write Time: 2/26/2002 - 9:22 AM
Value 0
Name:          COM_SinglePool
Type:          REG_SZ
Data:          YES

Value 1
Name:          DB_Protocol
Type:          REG_SZ
Data:          ODBC

Value 2
Name:          DbName
Type:          REG_SZ
Data:          tpcc

```

Value 3
 Name: DbPassword
 Type: REG_SZ
 Data:

Value 4
 Name: DbServer
 Type: REG_SZ
 Data: r450

Value 5
 Name: DbUser
 Type: REG_SZ
 Data: sa

Value 6
 Name: MaxConnections
 Type: REG_DWORD
 Data: 0x36b0

Value 7
 Name: MaxPendingDeliveries
 Type: REG_DWORD
 Data: 0x5dc

Value 8
 Name: NumberOfDeliveryThreads
 Type: REG_DWORD
 Data: 0x8

Value 9
 Name: Path
 Type: REG_SZ
 Data: c:\inetpub\wwwroot\

Value 10
 Name: TxnMonitor
 Type: REG_SZ
 Data: COM

Component Services Configuration:
 COM+ Component TPCC.AllTXns Settings:

Enable object pooling
 Minimum pool size 82
 Maximum pool size 82
 Creation timeout 60,000
 Enable object construction
 Enable just in time activation

Concurrency required

This section discloses the RTE parameters used on the PRIMERGY 870 system.

Profile: HTML_39000_5xRTE_3xL200
 File Path: K:\TPCC_R450\HTML_39000_5xRTE_3xL200.pro
 Version: 1.0.1

Number of Engines: 15

Name: DRIVER01
 Description: tuerkis1
 Directory: c:\log_b210_t1.log
 Machine: tuerkis
 Parameter Set: All_Times3
 Index: 0
 Seed: 11063
 Configured Users: 3000
 Pipe Name: DRIVER15224187
 Connect Rate: 300
 Start Rate: 280
 CLIENT_NURAND: 233
 CPU: 0

Name: DRIVER02
 Description: tuerkis2
 Directory: c:\log_b210_t2.log
 Machine: tuerkis
 Parameter Set: All_Times3
 Index: 100000000
 Seed: 11063
 Configured Users: 3000
 Pipe Name: DRIVER25270250
 Connect Rate: 300
 Start Rate: 280
 CLIENT_NURAND: 233
 CPU: 3

Name: DRIVER03
 Description: tuerkis3
 Directory: c:\log_b210_t3.log
 Machine: tuerkis
 Parameter Set: All_Times3
 Index: 200000000
 Seed: 11063
 Configured Users: 3000
 Pipe Name: DRIVER35312546
 Connect Rate: 300
 Start Rate: 280

CLIENT_NURAND: 233
CPU: 2

Name: DRIVER04
Description: ros1
Directory: c:\log_b210_r1.log
Machine: rosa
Parameter Set: All_Times3
Index: 300000000
Seed: 11063
Configured Users: 3000
Pipe Name: DRIVER41041459859
Connect Rate: 300
Start Rate: 270
CLIENT_NURAND: 233
CPU: 0

Name: DRIVER05
Description: rosa2
Directory: c:\log_b210_r2.log
Machine: rosa
Parameter Set: All_Times3
Index: 400000000
Seed: 11063
Configured Users: 3000
Pipe Name: DRIVER51041520281
Connect Rate: 300
Start Rate: 270
CLIENT_NURAND: 233
CPU: 3

Name: DRIVER06
Description: rosa3
Directory: c:\log_b210_r3.log
Machine: rosa
Parameter Set: All_Times3
Index: 500000000
Seed: 11063
Configured Users: 3000
Pipe Name: DRIVER61041625140
Connect Rate: 300
Start Rate: 270
CLIENT_NURAND: 233
CPU: 2

Name: DRIVER07
Description: schwarz1
Directory: c:\log_b210_s1.log
Machine: schwarz
Parameter Set: All_Times3
Index: 600000000
Seed: 11063
Configured Users: 3000

Pipe Name: DRIVER71041660703
Connect Rate: 300
Start Rate: 260
CLIENT_NURAND: 233
CPU: 0

Name: DRIVER08
Description: schwarz2
Directory: c:\log_b210_s2.log
Machine: schwarz
Parameter Set: All_Times3
Index: 700000000
Seed: 11063
Configured Users: 3000
Pipe Name: DRIVER81041694031
Connect Rate: 300
Start Rate: 260
CLIENT_NURAND: 233
CPU: 3

Name: DRIVER09
Description: schwarz3
Directory: c:\log_b210_s3.log
Machine: schwarz
Parameter Set: All_Times3
Index: 800000000
Seed: 11063
Configured Users: 3000
Pipe Name: DRIVER91041723703
Connect Rate: 300
Start Rate: 260
CLIENT_NURAND: 233
CPU: 2

Name: DRIVER10
Description: oliv1
Directory: d:\log_b210_o1.log
Machine: oliv
Parameter Set: All_Times3
Index: 900000000
Seed: 11063
Configured Users: 2000
Pipe Name: DRIVER101041749140
Connect Rate: 200
Start Rate: 180
CLIENT_NURAND: 233
CPU: 0

Name: DRIVER11
Description: oliv2
Directory: d:\log_b210_o2.log
Machine: oliv
Parameter Set: All_Times3

Index: 1000000000
Seed: 11063
Configured Users: 2000
Pipe Name: DRIVER111041774140
Connect Rate: 200
Start Rate: 180
CLIENT_NURAND: 233
CPU: 3

Name: DRIVER12
Description: oliv3
Directory: d:\log_b210_o3.log
Machine: oliv
Parameter Set: All_Times3
Index: 1100000000
Seed: 11063
Configured Users: 2000
Pipe Name: DRIVER121041803109
Connect Rate: 200
Start Rate: 180
CLIENT_NURAND: 233
CPU: 2

Name: DRIVER13
Description: blaul
Directory: d:\log_b210_b1.log
Machine: blau
Parameter Set: All_Times3
Index: 1200000000
Seed: 11063
Configured Users: 2000
Pipe Name: DRIVER131041826250
Connect Rate: 200
Start Rate: 170
CLIENT_NURAND: 233
CPU: 0

Name: DRIVER14
Description: blau2
Directory: d:\log_b210_b2.log
Machine: blau
Parameter Set: All_Times3
Index: 1300000000
Seed: 11063
Configured Users: 2000
Pipe Name: DRIVER141041861093
Connect Rate: 200
Start Rate: 170
CLIENT_NURAND: 233
CPU: 3

Name: DRIVER15
Description: blau3

Directory: d:\log_b210_b3.log
Machine: blau
Parameter Set: All_Times3
Index: 1400000000
Seed: 11063
Configured Users: 2000
Pipe Name: DRIVER151041887750
Connect Rate: 200
Start Rate: 170
CLIENT_NURAND: 233
CPU: 2

Number of User groups: 15

Driver Engine: DRIVER01
IIS Server: 1200c11
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 1 - 300
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER02
IIS Server: 1200c12
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 301 - 600
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER03
IIS Server: 1200c13
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 601 - 900
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER04
IIS Server: 1200c11
SQL Server: r450

User: sa
Protocol: Html
w_id Range: 901 - 1200
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER05
IIS Server: 1200cl2
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 1201 - 1500
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER06
IIS Server: 1200cl3
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 1501 - 1800
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER07
IIS Server: 1200cl1
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 1801 - 2100
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER08
IIS Server: 1200cl2
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 2101 - 2400
w_id Max Warehouse: 3900
Scale: Normal

User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER09
IIS Server: 1200cl3
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 2401 - 2700
w_id Max Warehouse: 3900
Scale: Normal
User Count: 3000
District id: 1
Scale Down: No

Driver Engine: DRIVER10
IIS Server: 1200cl1
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 2701 - 2900
w_id Max Warehouse: 3900
Scale: Normal
User Count: 2000
District id: 1
Scale Down: No

Driver Engine: DRIVER11
IIS Server: 1200cl2
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 2901 - 3100
w_id Max Warehouse: 3900
Scale: Normal
User Count: 2000
District id: 1
Scale Down: No

Driver Engine: DRIVER12
IIS Server: 1200cl3
SQL Server: r450
User: sa
Protocol: Html
w_id Range: 3101 - 3300
w_id Max Warehouse: 3900
Scale: Normal
User Count: 2000
District id: 1
Scale Down: No

Driver Engine: DRIVER13

IIS Server: 1200cl1
 SQL Server: r450
 User: sa
 Protocol: Html
 w_id Range: 3301 - 3500
 w_id Max Warehouse: 3900
 Scale: Normal
 User Count: 2000
 District id: 1
 Scale Down: No

Driver Engine: DRIVER14
 IIS Server: 1200cl2
 SQL Server: r450
 User: sa
 Protocol: Html
 w_id Range: 3501 - 3700
 w_id Max Warehouse: 3900
 Scale: Normal
 User Count: 2000
 District id: 1
 Scale Down: No

Driver Engine: DRIVER15
 IIS Server: 1200cl3
 SQL Server: r450
 User: sa
 Protocol: Html
 w_id Range: 3701 - 3900
 w_id Max Warehouse: 3900
 Scale: Normal
 User Count: 2000
 District id: 1
 Scale Down: No

Number of Parameter Sets: 4

~Default		Default Parameter Set					
		Txn Weight	Think Time	Key Time	RT Delay	RT Fence	Menu Delay
5.00	0.10	10.00	12.05	18.01	0.10		
5.00	0.10	10.00	12.05	3.01	0.10		
5.00	0.10	1.00	5.05	2.01	0.10		
20.00	0.10	1.00	5.05	2.01	0.10		
5.00	0.10	1.00	10.05	2.01	0.10		

All_Times3		Run 2H					
		Txn Weight	Think Time	Key Time	RT Delay	RT Fence	Menu Delay
5.00	0.10	44.88	12.05	18.01	0.10		
5.00	0.10	43.03	12.05	3.01	0.10		
5.00	0.10	4.03	5.05	2.01	0.10		
20.00	0.10	4.03	5.05	2.01	0.10		
5.00	0.10	4.03	10.05	2.01	0.10		
All_Times2		Times2					
		Txn Weight	Think Time	Key Time	RT Delay	RT Fence	Menu Delay
5.00	0.10	44.78	12.05	18.01	0.10		
5.00	0.10	43.07	12.05	3.01	0.10		
5.00	0.10	4.05	5.05	2.01	0.10		
20.00	0.10	4.05	5.05	2.01	0.10		
5.00	0.10	4.05	10.08	2.01	0.10		
All_Times		HTML Param. Set					
		Txn Weight	Think Time	Key Time	RT Delay	RT Fence	Menu Delay
5.00	0.10	44.86	12.05	18.01	0.10		
5.00	0.10	43.05	12.05	3.01	0.10		
5.00	0.10	4.03	5.05	2.01	0.10		
20.00	0.10	4.03	5.05	2.01	0.10		
5.00	0.10	4.03	10.05	2.01	0.10		

This section discloses the Microsoft SQL Server 2000 Enterprise Edition SP2 parameters used on the PRIMERGY R450 server system.

Microsoft SQL Server Startup Parameters:

```
sqlservr -c -x -T3502 -g160
```

where:

- c Start SQL Server independently of the Windows NT Service Control Manager
- x Disables the keeping of CPU time and cache-hit ratio statistics
- T3502 Prints a message to the SQL Server log at start and end of each checkpoint
- g80 memory in MB reserved for memory requests outside the buffer pool

Microsoft SQL Server Stack Size:

The default stack size for Microsoft SQL Server 2000 was changed using the EDITBIN utility:
editbin /STACK:131072

```
1> 2> 3> 4> 5> 6> 7> 8> 9> 10> 11>
-- File:      VERSION.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.22
--           Copyright Microsoft, 2001
-- Purpose:   Returns SQL Server version string
```

```
print " "
select convert(char(30), getdate(),9)
print " "
```

```
-----
Feb 28 2002 12:06:44:967PM
```

(1 row affected)

```
1> 2> 3>
select @@version
```

```
-----
-----
-----
Microsoft SQL Server 2000 - 8.00.534 (Intel X86)
Nov 19 2001 13:23:50
Cop
yright (c) 1988-2000 Microsoft Corporation
Enterprise Edition on Windo
ws NT 5.0 (Build 2195: Service Pack 2)
```

(1 row affected)

```
1> 2>
1> 2> 3> 4> 5> 6> 7> 8> 9> 10>
-- File:      CONFIG.SQL
--           Microsoft TPC-C Benchmark Kit Ver. 4.22
--           Copyright Microsoft, 2001
-- Purpose:   Collects SQL Server configuration parameters
```

```
print " "
select convert(char(30), getdate(),9)
print " "
```

```
-----
Feb 28 2002 12:06:45:793PM
```

(1 row affected)

1> 2> 3> DBCC execution completed. If DBCC printed error messages, contact your system administrator. Configuration option 'show advanced options' changed from 1 to 1. Run the RECONFIGURE statement to install.

```
sp_configure "show advanced",1
1> 2> reconfigure with override
1> 2> sp_configure
```


name	minimum	maximum	config_value	run_value
affinity mask	-2147483648	2147483647	255	255
allow updates	0	1	0	0
awe enabled	0	1	1	1
c2 audit mode	0	1	0	0
cost threshold for parallelism	0	32767	5	5
cursor threshold	-1	2147483647	-1	-1
default full-text language	0	2147483647	1033	1033
default language	0	9999	0	0
fill factor (%)	0	100	0	0
index create memory (KB)	704	2147483647	0	0
lightweight pooling	0	1	1	1
locks	5000	2147483647	8000	8000
max degree of parallelism	0	32	1	1
max server memory (MB)	4	2147483647	2147483647	2147483647
max text repl size (B)	0	2147483647	65536	65536
max worker threads	32	32767	300	300
media retention	0	365	0	0
min memory per query (KB)	512	2147483647	512	512
min server memory (MB)	0	2147483647	0	0
nested triggers	0	1	1	1
network packet size (B)	512	65536	4096	4096
open objects	0	2147483647	0	0
priority boost	0	1	1	1
query governor cost limit	0	2147483647	0	0
query wait (s)	-1	2147483647	-1	-1
recovery interval (min)	0	32767	56	56
remote access	0	1	0	0
remote login timeout (s)	0	2147483647	20	20
remote proc trans	0	1	0	0
remote query timeout (s)	0	2147483647	0	0
scan for startup procs	0	1	0	0
set working set size	0	1	0	0
show advanced options	0	1	1	1
two digit year cutoff	1753	9999	2049	2049
user connections	0	32767	0	0
user options	0	32767	0	0

1>

Appendix D – Space Calculation

				Microsoft SQL Server		
Note : Numbers are in KBytes unless otherwise specified				Updated for Version 7 (FR)		
Warehouses	3900	tpmC	48906	tpmC/W	12.54	
Table	Rows	Data	Index	5% Space	8H Space	Total Space
Warehouse	3,900	424	48	24		496
District	39,000	4,336	48	219		4,603
Item	100,000	9,528	64	480		10,072
New-order	35,100,000	554,944	1,312		312,000	868,256
History	171,000,001	6,500,008	120		1,304,186	7,804,314
Orders	117,000,000	3,586,208	1,639,816		1,048,549	6,274,573
Customer	171,000,000	85,090,912	5,073,968	4,508,244		94,673,124
Order-line	1,169,996,242	73,124,768	154,808		14,702,814	87,982,390
Stock	390,000,000	124,800,008	233,296	6,251,665		131,284,969
Totals		293,671,136	7,103,480	10,760,632	17,367,549	328,902,797
Segment	LogDev Cnt.	Seg. Size	Needed	Overhead		Not Needed
misc	5	122,880,000	103,974,151	1,039,742		17,866,108
customer/stock	5	227,840,000	228,217,674	2,282,177		(2,659,851)
Totals		350,720,000	332,191,825	3,321,918		15,206,257
Dynamic space	83,210,984	Sum of Data for Order, Order-Line and History				
Static space	231,646,182	Data + Index + 5% Space + Overhead - Dynamic space				
Free space	20,656,577	Total Seg. Size - Dynamic Space - Static Space - Not Needed				
Daily growth	16,695,452	(Dynamic space/W * 62.5) * tpmC				
Daily spread	(4,386,601)	Free space - 1.5 * Daily growth (zero if negative)				
60 day (KB)	1,233,373,292	Static space + 60 (daily growth + daily spread)				
60 day (GB)	1,176.24	60-day space in GB (excludes OS, Paging and RDBMS Logs)				
Log size (MB)	90,000	Total size of log file				
% Log used	47.4702	% of log file used during entire run				
Total N-O Txn	9325485	Total count of N-O transactions during entire run				
Log per N-O txn	4.6913	KB of log per New-Order transaction				
8 Hour Log (GB)	105.03	8 hours of log in GB (excluding space for redundancy)				
Disk Capacity	MB	GB	disks needed	disks priced	GB priced	
18 GB 15000 rpm	17480	17.07		220	3,755.47	
60 day (GB)		1,176.24	68.91	220	3,755.47	
Disk Capacity	MB	GB	disks needed	disks priced		
18 GB 15000 rpm	17480	17.07				
8 Hour Log (RAID 1)		105.03	6.15	7+7		

Appendix E - Price Quotations



Note: this is the portal to get access to Buerotechnik Sachsen GmbH.

Bürotechnik Sachsen GmbH - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Home Search Favorites History Print Copy Paste Links

Address <http://212.5.34.167/cgi-bin/ePages.storefront/3c6ba0ff0105193e2740d40522a40608/Product/view/41> Go Links



Bürotechnik Sachsen GmbH

PRODUKTE

SUCHE

WARENKORB

HOME

KONTAKT

AGB

D-Link 10/100/1000 Switches



Produktdetails

DES-3225G, 10/100 Mbit 24-Port Switch (24x 10/100 Mbit RJ-45 Nway), RMON, VLAN, Trunking, IGMP, 10.6 GB/s, Garantie der Lüfter und der Netzteile 1 Jahr

Hersteller-Nr:	DES-3225G
Hersteller:	D-Link
Sprache:	ML
System:	D/W/LIN
Garantie:	60
Datenblatt:	 Download Reader 
Nettopreis:	737.62 EUR 1442.66 DM
Preis inkl. MwSt.:	855.64 EUR 1673.49 DM
	 kaufen

[zurück](#)

Done Internet

Bürotechnik Sachsen GmbH - Microsoft Internet Explorer

File Edit View Favorites Tools Help

Back Forward Stop Home Search Favorites History Print Copy Paste Links

Address <http://212.5.34.167/cgi-bin/ePages.storefront/3c6b9e5a0058b40a273fd40522a40640/Product/View/41> Go Links



Bürotechnik Sachsen GmbH

PRODUKTE

SUCHE

WARENKORB

HOME

KONTAKT

AGB

D-Link Switch Modul

DERZEIT
LEIDER KEIN
PRODUKT
BILD
VERFÜGBAR



[zurück](#)

Produktdetails

DES-3251G, 1port Gigabit Modul (SC),
Garantie der Lüfter und der Netzteile 1 Jahr

Hersteller-Nr:	DES-3251G
Hersteller:	D-Link
Sprache:	ML
System:	D/31/M9x/NT/2000/L
Garantie:	60
Datenblatt:	 Download Reader 
Nettopreis:	458.62 EUR 896.98 DM
Preis inkl. MwSt.:	532.00 EUR 1040.50 DM
	 kaufen

Done Internet

TPC-C Full Disclosure Report Appendix C - Tunable Parameters and Options -296-
© 2000 Fujitsu Siemens Computers GmbH. All rights reserved.

March 12, 2002

Appendix F - Attestation Letter

Benchmark Sponsor: Franz-Josef Bathe
Fujitsu Siemens Computers
Heinz-Nixdorf-Ring 1
D-33106 Paderborn, Germany

March 7, 2002

I remotely verified the TPC Benchmark™ C performance of the following Client/Server configuration:

Platform: **Siemens PRIMERGY R450**
Operating system: **Microsoft Windows 2000 Advanced Server SP2**
Database Manager: **Microsoft SQL Server 2000 Enterprise Edition SP2**
Transaction Manager: **Microsoft COM+ (Included in Windows 2000)**

The results were:

CPU's Speed	Memory	Disks	NewOrder 90% Response Time	tpmC
Server: Siemens PRIMERGY R450				
4 x Intel Xeon MP (1.60 GHz)	8 GB Main (1M L3 Cache per processor)	235 x 18 GB	0.56 Seconds	48906.18
Three (3) Clients: PRIMERGY L200 (Specification for each)				
2 x Pentium III (1.26 GHz)	512 MB Main Cache: 512 KB	1 x 18 GB	n/a	n/a

In my opinion, these performance results were produced in compliance with the TPC's requirements for the benchmark. The following verification items were given special attention:

- The database records were the proper size
- The database was properly scaled and populated
- The required ACID properties were met

- The transactions were correctly implemented
- Input data was generated according to the specified percentages
- The transaction cycle times included the required keying and think times
- The reported response times were correctly measured.
- All 90% response times were under the specified maximums
- At least 90% of all delivery transactions met the 80 Second completion time limit
- The reported measurement interval was 120 minutes (7200 seconds)
- The reported measurement interval was representative of steady state conditions
- One checkpoint was taken during the reported measurement interval
- The repeatability of the measured performance was verified
- The 60 day storage requirement was correctly computed
- The system pricing was verified for major components and maintenance

Respectfully Yours,



François Raab, President



Bradley J. Askins, Auditor